

# TEST REPORT

## For Bluetooth-EDR

Report No.....	CHTW24090004	Report Verification:	
Project No.....	SHT2407056602W		
FCC ID.....	2BBCY3588S		
Applicant's name.....	Lisheng Communications Co., Ltd.		
Address .....	5#, ChongXiang St., Econ & Tech. Area, Quanzhou, Fujian, China.		
Product Name .....	POC Two Way Radio / IP Two Way radio		
Trade Mark .....	LISHENG		
Model No. ....	Q-3588S		
Listed Model(s) .....	3288T		
Standard.....	FCC CFR Title 47 Part 15 Subpart C § 15.247		
Date of receipt of test sample.....	Aug. 14, 2024		
Date of testing.....	Aug. 15, 2024- Sep. 02, 2024		
Date of issue.....	Sep. 03, 2024		
Result.....	PASS		


Compiled by  
( Position+Printed name+Signature): File administrators Caspar Chen



Supervised by  
(Position+Printed name+Signature): Project Engineer Caspar Chen



Approved by  
(Position+Printed name+Signature): RF Manager Xu yang



Testing Laboratory Name .....

Shenzhen Huatongwei International Inspection Co., Ltd.

Address .....

Building 7, Baiwang Idea Factory, No.1051, Songbai Road,  
Yangguang Community, Xili Subdistrict, Nanshan District,  
Shenzhen, Guangdong, China

**Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

The test report merely correspond to the test sample.

## Contents

<u>1. TEST STANDARDS AND REPORT VERSION</u>	<u>3</u>
1.1. Test Standards	3
1.2. Report version	3
<u>2. TEST DESCRIPTION</u>	<u>4</u>
<u>3. SUMMARY</u>	<u>5</u>
3.1. Client Information	5
3.2. Product Description	5
3.3. Radio Specification Description	5
3.4. Testing Laboratory Information	6
<u>4. TEST CONFIGURATION</u>	<u>7</u>
4.1. Test frequency list	7
4.2. Descriptions of Test mode	7
4.3. Test mode	7
4.4. Test sample information	8
4.5. Support unit used in test configuration and system	8
4.6. Testing environmental condition	8
4.7. Statement of the measurement uncertainty	9
4.8. Equipment Used during the Test	10
<u>5. TEST CONDITIONS AND RESULTS</u>	<u>11</u>
5.1. Antenna Requirement	11
5.2. AC Conducted Emission	12
5.3. Peak Output Power	13
5.4. 20 dB Bandwidth	14
5.5. 99% Occupied Bandwidth	15
5.6. Carrier Frequencies Separation	16
5.7. Hopping Channel Number	17
5.8. Dwell Time	18
5.9. Duty Cycle Correction Factor (DCCF)	19
5.10. Pseudorandom Frequency Hopping Sequence	20
5.11. Conducted Band edge and Spurious Emission	21
5.12. Radiated Band edge Emission	22
5.13. Radiated Spurious Emission	24
<u>6. TEST SETUP PHOTOS</u>	<u>29</u>
<u>7. EXTERNAL AND INTERNAL PHOTOS</u>	<u>30</u>
<u>8. APPENDIX REPORT</u>	<u>30</u>

## 1. **TEST STANDARDS AND REPORT VERSION**

### 1.1. Test Standards

The tests were performed according to following standards:

- [FCC CFR Title 47 Part 15 Subpart C § 15.247](#): Operation within the bands 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz
- [ANSI C63.10:2020](#): American National Standard for Testing Unlicensed Wireless Devices
- [KDB 558074 D01 15.247 Meas Guidance v05r02](#): Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating under Section 15.247 of The FCC Rules

### 1.2. Report version

Revision No.	Date of issue	Description
N/A	2024-09-03	Original

## 2. TEST DESCRIPTION

Report clause	Test Items	Standard Requirement	Result	Test Engineer
5.1	Antenna Requirement	15.203/15.247 (c)	PASS	Xiangyu Wei
5.2	AC Conducted Emission	15.207	N/A	-
5.3	Peak Output Power	15.247 (b)(1)	PASS	Xiangyu Wei
5.4	20 dB Bandwidth	15.247 (a)(1)	PASS	Xiangyu Wei
5.5	99% Occupied Bandwidth	-	PASS <sup>*1</sup>	Xiangyu Wei
5.6	Carrier Frequency Separation	15.247 (a)(1)	PASS	Xiangyu Wei
5.7	Hopping Channel Number	15.247 (a)(1)	PASS	Xiangyu Wei
5.8	Dwell Time	15.247 (a)(1)	PASS	Xiangyu Wei
5.9	Duty Cycle Correction Factor	-	PASS <sup>*1</sup>	Xiangyu Wei
5.10	Pseudorandom Frequency Hopping Sequence	15.247(b)(4)	PASS	Xiangyu Wei
5.11	Conducted Band Edge and Spurious Emission	15.247(d)/15.205	PASS	Xiangyu Wei
5.12	Radiated Band Edge Emission	15.205/15.209	PASS	Yifan Wang
5.13	Radiated Spurious Emission	15.247(d)/15.205/15.209	PASS	Yifan Wang

Note:

- The measurement uncertainty is not included in the test result.
- \*1: No requirement on standard, only report these test data.

### 3. SUMMARY

#### 3.1. Client Information

Applicant:	Lisheng Communications Co., Ltd.
Address:	5#, ChongXiang St., Econ & Tech. Area, Quanzhou, Fujian, China.
Manufacturer:	Lisheng Communications Co., Ltd.
Address:	5#, ChongXiang St., Econ & Tech. Area, Quanzhou, Fujian, China.

#### 3.2. Product Description

Main unit information:	
Product Name:	POC Two Way Radio / IP Two Way radio
Trade Mark:	LISHENG
Model No.:	Q-3588S
Listed Model(s):	3288T
Power supply:	DC 3.7V from Battery
Hardware version:	P301_V2.0
Software version:	V1.0
Accessory unit information:	
Battery information:	LI-ION BATTERY PACK Model: 3588-BAT DC 3.7V 3800mAh 14.06Wh
Charger information:	Model: BC-3588 Input: 5V 1A Output: 4.2V 1A
Adapter information:	MODEL: TEKA-UCA20US INPUT: 100-240V~50/60Hz 0.35A MAX OUTPUT: 5.0V, 2.0A

#### 3.3. Radio Specification Description

Bluetooth version:	V4.0
Support function:	EDR
Modulation:	GFSK, π/4DQPSK, 8DPSK
Operation frequency:	2402MHz~2480MHz
Channel number:	79
Channel separation:	1MHz
Antenna type:	FPC
Antenna gain:	2.5dBi

### 3.4. Testing Laboratory Information

Laboratory Name	Shenzhen Huatongwei International Inspection Co., Ltd.	
Laboratory Location	Building 7, Baiwang Idea Factory, No.1051, Songbai Road, Yangguang Community, Xili Subdistrict, Nanshan District, Shenzhen, Guangdong, China	
Contact information:	Phone: 86-755-26715499 E-mail: <a href="mailto:cs@szhtw.com.cn">cs@szhtw.com.cn</a> <a href="http://www.szhtw.com.cn">http://www.szhtw.com.cn</a>	
Qualifications	Type	Accreditation Number
	FCC Registration Number	762235
	FCC Designation Number	CN1181

## 4. TEST CONFIGURATION

### 4.1. Test frequency list

According to section 15.31(m), regards to the operating frequency range over 10 MHz, must select three channels which were tested. The Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, please see the below blue front.

Channel	Frequency (MHz)
00	2402
01	2403
:	:
39	2441
:	:
77	2479
78	2480

### 4.2. Descriptions of Test mode

Preliminary tests were performed in different data rates and recorded the RF output power in the clause 5.3

Note:

- 1) The manufacturer declare that the maximum power value of the product is set as a default value in the enter test mode software.
- 2) All the test data for each data rate were verified, found GFSK Modulation which is worse case mode

### 4.3. Test mode

For RF test items:			
Test Item	Modulation / Data Rate		
	GFSK 1Mbps	$\pi/4$ DQPSK 2Mbps	8DPSK 3Mbps
Conducted test item	✓	✓	✓
Radiated test item	✓	-	-

Remark:

- For radiated test item, the worst mode data rate 1Mbps was reported only, because this data rate has the highest RF output power at preliminary tests.
- The EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

#### 4.4. Test sample information

Test item	HTW sample no.
RF Conducted test items	Refer to the description in the appendix report
RF Radiated test items	YPHT24070566002
EMI test items	-

Note:

RF Conducted test items: Peak Output Power, 20 dB Bandwidth, 99% Occupied Bandwidth, Carrier Frequency Separation, Hopping Channel Number, Dwell Time, Duty Cycle Correction Factor, Pseudorandom Frequency Hopping Sequence, Conducted Band Edge and Spurious Emission

RF Radiated test items: Radiated Band Edge Emission, Radiated Spurious Emission

EMI test items: AC Conducted Emission

#### 4.5. Support unit used in test configuration and system

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

The following peripheral devices and interface cables were connected during the measurement:

Whether support unit is used?			
<input checked="" type="checkbox"/> No			
Item	Equipment	Trade Name	Model No.
1			
2			

#### 4.6. Testing environmental condition

Type	Requirement	Actual
Temperature:	15~35°C	25°C
Relative Humidity:	25~75%	50%
Air Pressure:	860~1060mbar	1000mbar

#### 4.7. Statement of the measurement uncertainty

No.	Test Items	Measurement Uncertainty
1	AC Conducted Emission	3.21dB
2	Peak Output Power	1.07
3	Power Spectral Density	1.07
4	6dB Bandwidth	0.002%
5	99% Occupied Bandwidth	0.002%
6	Duty cycle	-
7	Conducted Band Edge and Spurious Emission	1.68dB
8	Radiated Band Edge Emission	4.54dB for 30MHz-1GHz 5.10dB for above 1GHz
9	Radiated Spurious Emission	4.54dB for 30MHz-1GHz 5.10dB for above 1GHz

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=1.96$ .

#### 4.8. Equipment Used during the Test

● RF Conducted test item							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Signal & Spectrum Analyzer	R&S	HTWE0262	FSW26	103440	2023/08/22	2024/08/21
						2024/08/21	2025/08/20
●	Vector signal generator	R&S	HTWE0244	SMBV100A	260790	2024/5/25	2025/5/24
●	Test software	Tonscend	N/A	JS1120	N/A	N/A	N/A

● Radiated emission- 9kHz~30MHz							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0127	SAC-3m-02	C11121	2023/04/06	2026/04/05
●	EMI Test Receiver	R&S	HTWE0099	ESCI 7	100900	2024/08/12	2025/08/11
●	Loop Antenna	R&S	HTWE0170	HFH2-Z2	100020	2024/04/08	2027/04/07
●	Test Software	R&S	N/A	EMC32	N/A	N/A	N/A

● Radiated emission- 30MHz~1GHz							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0127	SAC-3m-02	C11121	2023/04/06	2026/04/05
●	EMI Test Receiver	R&S	HTWE0099	ESCI 7	100900	2024/08/12	2025/08/11
●	Ultra-Broadband Antenna	SCHWARZBECK	HTWE0119	VULB9163	546	2023/02/22	2026/02/21
●	Pre-Amplifier	SCHWARZBECK	HTWE0295	BBV 9742	/	2024/5/24	2025/5/23
●	Test Software	R&S	N/A	EMC32	N/A	N/A	N/A

● Radiated emission- Above 1GHz							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0122	SAC-3m-01	C11121	2023/04/17	2026/04/16
●	Spectrum Analyzer	R&S	HTWE0098	FSP40	100597	2024/08/12	2025/08/11
●	Spectrum Analyzer	R&S	HTWE0385	N9020A	MY54486658	2024/08/12	2025/08/11
●	Horn Antenna	SCHWARZBECK	HTWE0126	BBHA 9120D	1011	2023/02/14	2026/02/13
●	Pre-Amplifier	CD	HTWE0071	PAP-0102	12004	2024/06/06	2025/06/05
●	Broadband Pre-amplifier	SCHWARZBECK	HTWE0551	SCU18F	100855	2024/06/06	2025/06/05
●	Test Software	Audix	N/A	E3	N/A	N/A	N/A

## 5. TEST CONDITIONS AND RESULTS

### 5.1. Antenna Requirement

#### REQUIREMENT


#### **FCC CFR Title 47 Part 15 Subpart C Section 15.203:**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

#### TEST RESULT

Passed       Not Applicable

The antenna type is a FPC antenna, Refer to the below antenna photo.



## 5.2. AC Conducted Emission


### LIMIT

#### FCC CFR Title 47 Part 15 Subpart C Section 15.207

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\* Decreases with the logarithm of the frequency.

### TEST CONFIGURATION



### TEST PROCEDURE

1. The EUT was setup according to ANSI C63.10 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedances stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment.
4. The peripheral devices are also connected to the main power through a LISN. (Refer to the block diagram of the test setup and photographs)
5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
7. Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
8. During the above scans, the emissions were maximized by cable manipulation.

### TEST MODE

Refer to the clause 4.3

### TEST RESULT

Passed

Not Applicable


### 5.3. Peak Output Power

#### LIMIT

##### **FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(1):**

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt.  
For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

#### TEST CONFIGURATION



#### TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the pathloss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:  
Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel  
 $RBW \geq$  the 20 dB bandwidth of the emission being measured,  $VBW \geq RBW$   
Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.

#### TEST MODE

Refer to the clause 4.3

#### TEST RESULT

Passed       Not Applicable

#### TEST DATA


Refer to the appendix report

## 5.4. 20 dB Bandwidth

### LIMIT

N/A

### TEST CONFIGURATION



### TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:  
Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel  
RBW  $\geq$  1% of the 20 dB bandwidth, VBW  $\geq$  RBW  
Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.

### TEST MODE

Refer to the clause 4.3

### TEST RESULT

Passed       Not Applicable

### TEST DATA


Refer to the appendix report

## 5.5. 99% Occupied Bandwidth

### LIMIT

N/A

### TEST CONFIGURATION



### TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Configure the spectrum analyzer as shown below (enter all losses between the transmitter output and the spectrum analyzer).  
Center Frequency = channel center frequency  
Span  $\geq 1.5 \times$  OBW  
RBW = 1%~5%OBW  
VBW  $\geq 3 \times$  RBW  
Sweep time= auto couple  
Detector = Peak  
Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.

### TEST MODE

Refer to the clause 4.3

### TEST RESULT

Passed       Not Applicable

### TEST DATA

Refer to the appendix report


## 5.6. Carrier Frequencies Separation

### LIMIT

#### **FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):**

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

### TEST CONFIGURATION



### TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:  
Span = wide enough to capture the peaks of two adjacent channels  
 $RBW \geq 1\%$  of the span,  $VBW \geq RBW$   
Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.

### TEST MODE

Refer to the clause 4.3

### TEST RESULTS

Passed       Not Applicable

### TEST DATA

Refer to the appendix report


## 5.7. Hopping Channel Number

### LIMIT

#### FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least **15** channels.

### TEST CONFIGURATION



### TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:  
Span = the frequency band of operation  
 $RBW \geq 1\%$  of the span,  $VBW \geq RBW$   
Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.

### TEST MODE

Refer to the clause 4.3

### TEST RESULTS

Passed       Not Applicable

### TEST DATA


Refer to the appendix report

## 5.8. Dwell Time

### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

### TEST CONFIGURATION



### TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:  
Span = zero span, centered on a hopping channel, RBW= 1 MHz, VBW  $\geq$  RBW  
Sweep = as necessary to capture the entire dwell time per hopping channel,  
Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.

### TEST MODE

Refer to the clause 4.3

### TEST RESULTS

Passed       Not Applicable

### TEST DATA


Refer to the appendix report

## 5.9. Duty Cycle Correction Factor (DCCF)

### LIMIT

N/A

### TEST CONFIGURATION



### TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:  
Span = zero span, centered on a hopping channel, RBW= 1 MHz, VBW  $\geq$  RBW  
Sweep = as necessary to capture the entire dwell time per hopping channel,  
Detector function = peak, Trigger mode
4. Measure and record the duty cycle data

### TEST MODE

Refer to the clause 4.3

### TEST DATA

Refer to the appendix report

## 5.10. Pseudorandom Frequency Hopping Sequence


### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1): Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

### TEST RESULTS


The pseudorandom frequency hopping sequence may be generated in a nine-stage shift register whose 5<sup>th</sup> and 9<sup>th</sup> stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first one of 9 consecutive ones, for example: the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence:  $2^9 - 1 = 511$  bits
- Longest sequence of zeros: 8 (non-inverted signal)



*Linear Feedback Shift Register for Generation of the PRBS sequence*

An example of pseudorandom frequency hopping sequence as follows:



Each frequency is used equally on the average by each transmitter.


The system receiver has input bandwidths that match the hopping channel bandwidths of their corresponding transmitter and shift frequencies in synchronization with the transmitted signals.

## 5.11. Conducted Band edge and Spurious Emission

### LIMIT

**FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):** In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

### TEST CONFIGURATION



### TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Emission level measurement  
Set the center frequency and span to encompass frequency range to be measured  
RBW = 100 kHz, VBW  $\geq$  3 x RBW  
Detector = peak, Sweep time = auto couple, Trace mode = max hold  
Allow trace to fully stabilize  
Use the peak marker function to determine the maximum amplitude level.
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
4. Ensure that the amplitude of all unwanted emission outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified (at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz). Report the three highest emission relative to the limit.

### TEST MODE

Refer to the clause 4.3

### TEST RESULT

Passed       Not Applicable

### TEST DATA

Refer to the appendix report


## 5.12. Radiated Band edge Emission

### LIMIT

#### FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, Radiated Emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the Radiated Emissions limits specified in §15.209(a) (see §15.205(c)).

### TEST CONFIGURATION



### TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10 .
2. The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT waspositioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find themaximum emission, all of the interface cables were manipulated according to ANSI C63.10 on radiated measurement.
5. Use the following spectrum analyzer settings:
  - a) Span shall wide enough to fully capture the emission being measured
  - b) Set RBW=100kHz for <1GHz, VBW=3\*RBW, Sweep time=auto, Detector=peak, Trace=max hold
  - c) Set RBW=1MHz, VBW=3MHz for >1GHz, Sweep time=auto, Detector=peak, Trace=max hold for Peak measurement
 For average measurement: use duty cycle correction factor method (DCCF)  
 Averager level = Peak level + DCCF

### TEST MODE

Refer to the clause 4.3

### TEST RESULT

Passed       Not Applicable

Note:

- 1) Level= Reading + Factor; Factor =Antenna Factor+ Cable Loss- Preamp Factor
- 2) Over Limit = Level- Limit
- 3) Average measurement was not performed if peak level is lower than average limit(54 dBuV/m).

Test channel:		CH00		Polarity				Horizontal	
Mark	Frequency MHz	Reading dB <sub>u</sub> V/m	Antenna dB	Cable dB	Preamp dB	Level dB <sub>u</sub> V/m	Limit dB <sub>u</sub> V/m	Over limit	Remark
1	2310.00	47.50	27.86	3.95	41.18	38.13	74.00	-35.87	Peak
2	2390.03	50.64	27.54	4.08	41.11	41.15	74.00	-32.85	Peak

Test channel:		CH00		Polarity				Vertical	
Mark	Frequency MHz	Reading dB <sub>u</sub> V/m	Antenna dB	Cable dB	Preamp dB	Level dB <sub>u</sub> V/m	Limit dB <sub>u</sub> V/m	Over limit	Remark
1	2310.00	47.93	27.86	3.95	41.18	38.56	74.00	-35.44	Peak
2	2390.03	48.68	27.54	4.08	41.11	39.19	74.00	-34.81	Peak

Test channel:		CH78		Polarity				Horizontal	
Mark	Frequency MHz	Reading dB <sub>u</sub> V/m	Antenna dB	Cable dB	Preamp dB	Level dB <sub>u</sub> V/m	Limit dB <sub>u</sub> V/m	Over limit	Remark
1	2483.50	71.73	27.33	4.18	41.04	62.20	74.00	-11.80	Peak
2	2500.00	47.51	27.30	4.20	41.02	37.99	74.00	-36.01	Peak
Fundamental of Average									
No.	Freq. [MHz]	PK level [dB <sub>u</sub> V/m]	DCCF [dB]	Level [dB <sub>u</sub> V/m]	Limit [dB <sub>u</sub> V/m]	Over Limit [dB]	Polarity		
1	2483.50	62.20	-30.87	31.33	54.00	-22.67	Horizontal		

Test channel:		CH78		Polarity				Vertical	
Mark	Frequency MHz	Reading dB <sub>u</sub> V/m	Antenna dB	Cable dB	Preamp dB	Level dB <sub>u</sub> V/m	Limit dB <sub>u</sub> V/m	Over limit	Remark
1	2483.50	69.47	27.33	4.18	41.04	59.94	74.00	-14.06	Peak
2	2500.00	48.00	27.30	4.20	41.02	38.48	74.00	-35.52	Peak
Fundamental of Average									
No.	Freq. [MHz]	PK level [dB <sub>u</sub> V/m]	DCCF [dB]	Level [dB <sub>u</sub> V/m]	Limit [dB <sub>u</sub> V/m]	Over Limit [dB]	Polarity		
1	2483.50	59.94	-30.87	29.07	54.00	-24.93	Vertical		

## 5.13. Radiated Spurious Emission

### LIMIT

#### FCC CFR Title 47 Part 15 Subpart C Section 15.209

Frequency	Limit (dBuV/m)	Value
0.009 MHz ~ 0.49 MHz	2400/F(kHz) @300m	Quasi-peak
0.49 MHz ~ 1.705 MHz	24000/F(kHz) @30m	Quasi-peak
1.705 MHz ~30 MHz	30 @30m	Quasi-peak


Note: Limit dBuV/m @3m = Limit dBuV/m @300m + 40\*log(300/3)= Limit dBuV/m @300m +80,

Limit dBuV/m @3m = Limit dBuV/m @30m +40\*log(30/3)= Limit dBuV/m @30m + 40.


Frequency	Limit (dBuV/m @3m)	Value
30MHz~88MHz	40.00	Quasi-peak
88MHz~216MHz	43.50	Quasi-peak
216MHz~960MHz	46.00	Quasi-peak
960MHz~1GHz	54.00	Quasi-peak
Above 1GHz	54.00	Average
	74.00	Peak

### TEST CONFIGURATION


- 9 kHz ~ 30 MHz



- 30 MHz ~ 1 GHz



- Above 1 GHz



## TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10.
2. The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings
  - a) Span shall wide enough to fully capture the emission being measured;
  - b) Below 1 GHz:  
RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold;  
If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
  - c) Set RBW=1MHz, VBW=3MHz for >1GHz, Sweep time=auto, Detector=peak, Trace=max hold for Peak measurement  
For average measurement: use duty cycle correction factor method (DCCF)  
Averager level = Peak level + DCCF

## TEST MODE

Refer to the clause 4.3

## TEST RESULT

Passed       Not Applicable

Note:


- 1) Level= Reading + Factor/Transd; Factor/Transd =Antenna Factor+ Cable Loss- Preamp Factor
- 2) Over Limit = Level- Limit
- 3) Average measurement was not performed if peak level is lower than average limit(54 dBuV/m) for above 1GHz.

**For 9 kHz ~ 30 MHz**

The EUT was pre-scanned this frequency band, found the radiated level 20dB lower than the limit, so don't show data on this report.

**For 30 MHz ~ 1000 MHz**

Have pre-scan all test channel, found CH39 which it was worst case, so only show the worst case's data on this report.



**For 1 GHz ~ 25 GHz**

Test channel		CH00		Polarity				Horizontal		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	4478.63	40.45	30.56	5.88	40.45	36.44	74.00	-37.56	Peak	
2	6235.36	41.79	32.77	6.79	39.20	42.15	74.00	-31.85	Peak	
3	7941.19	39.17	36.85	8.03	39.95	44.10	74.00	-29.90	Peak	
4	10888.51	39.06	40.48	8.84	40.59	47.79	74.00	-26.21	Peak	

Test channel		CH00		Polarity				Vertical		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	3913.39	41.89	29.70	5.33	40.41	36.51	74.00	-37.49	Peak	
2	6235.36	41.79	32.77	6.79	39.20	42.15	74.00	-31.85	Peak	
3	7921.00	40.94	36.73	8.02	39.96	45.73	74.00	-28.27	Peak	
4	11515.68	39.18	40.47	9.22	40.22	48.65	74.00	-25.35	Peak	

Test channel		CH39		Polarity				Horizontal		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	4524.47	42.24	30.65	5.87	40.41	38.35	74.00	-35.65	Peak	
2	6299.18	39.27	32.90	6.83	39.20	39.80	74.00	-34.20	Peak	
3	8104.56	40.65	36.98	8.05	39.91	45.77	74.00	-28.23	Peak	
4	11486.41	39.81	40.49	9.19	40.21	49.28	74.00	-24.72	Peak	

Test channel		CH39		Polarity				Vertical		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	3993.90	41.59	29.79	5.43	40.32	36.49	74.00	-37.51	Peak	
2	5060.69	40.73	31.76	6.05	40.13	38.41	74.00	-35.59	Peak	
3	7063.69	40.20	35.41	7.38	39.53	43.46	74.00	-30.54	Peak	
4	10165.29	40.17	39.27	8.73	40.00	48.17	74.00	-25.83	Peak	



Test channel		CH78		Polarity				Horizontal		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	3893.52	43.02	29.69	5.32	40.44	37.59	74.00	-36.41	Peak	
2	6187.93	40.92	32.68	6.76	39.20	41.16	74.00	-32.84	Peak	
3	7921.00	41.63	36.73	8.02	39.96	46.42	74.00	-27.58	Peak	
4	10916.26	41.27	40.50	8.83	40.62	49.98	74.00	-24.02	Peak	


  

Test channel		CH78		Polarity				Vertical		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	4299.89	41.98	30.20	5.86	40.56	37.48	74.00	-36.52	Peak	
2	5462.30	42.52	31.80	6.37	39.74	40.95	74.00	-33.05	Peak	
3	8593.22	40.32	37.47	8.27	40.16	45.90	74.00	-28.10	Peak	
4	10805.68	41.32	40.31	8.88	40.51	50.00	74.00	-24.00	Peak	

## 6. TEST SETUP PHOTOS

Radiated Emission





## **7. EXTERNAL AND INTERNAL PHOTOS**

Refer to the test report No.: CHTW24090001

## **8. APPENDIX REPORT**