

SPECIFICATION FOR APPROVAL

DATE: 2022.12.09

REV.: V1.0

CUSTOMER: Huida

PART NAME: HD540 pro External rubber rod
antenna

SUPPLIER P/N: N12-7253-R0A

Date: **Q'TY:** **Pcs**

CUSTOMER APPROVED BY		
ENGINEER R&D DEPT	BUSSINESS DEPT	APPROVED BY

Index


1. RF Fixture Experiment	3
1.1 Test Setup	3
1.2 UE configuration	4
2. Test Result	5
2.2 Passive Test Result(S parameters)	6
3. Mechanical instruction	7
4. Packing	8

1. RF Fixture Experiment

1.1 Test Setup


1.1.1 VNA Test Setup

VSWR and Return Loss measurements (S11) were performed using an Keysight E5071C Network Analyzer. The isolation between antennas is also tested. The testing was performed with apparatus in free space.



1.1.4 Anechoic Chamber Test Setup


When we test Gain and Efficiency of the antenna, we will use the ETS 3D chamber. The chamber provides test frequency from 400MHz to 6GHz. The real test environment is showing as following picture






1.2 UE configuration

1.2.1 Antenna location pictures



1.2.2 RF matching for different antennas




E1(0201)	NA
E2(0201)	0 ohm
E3(0201)	NA

2. Test Result





2.2 Passive Test Result(S parameters)

S11







3D

2.4G




5G





Efficiency

Freq (MHz)	Effi (%)	Gain (dBi)
2400	47.80	2.90
2410	45.55	2.93
2420	48.77	3.05
2430	48.57	3.15
2440	48.82	3.34
2450	49.84	3.19
2460	51.55	3.18
2470	48.53	3.16
2480	46.68	3.02
2490	49.93	3.03
2500	49.22	2.99

Freq (MHz)	Effi (%)	Gain (dBi)
5100	42.20	2.84
5200	43.06	3.27
5300	40.13	2.87
5400	44.23	3.08
5500	40.43	3.04
5600	43.85	3.31
5700	45.06	2.84
5800	44.28	2.90



105 1 2 3 4 5 6 7 8



- remark: remarks: comment
1. Marked with "*" as the key size, the unmarked tolerance size is tested according to ± 0.15
 2. Please refer to the drawing if the dimensions are not marked.
 3. RoHS compliant
 4. Shipping method: Single shipment

Shenzhen free technology Co., LTD

No.	Name	Material	Color	Treatment	Amount	Remark
6	heat shrink tubing	EVA	yellow		1	
5	SMA	RP-SMA	yellow		1	
4	RF cable	RG174	black		1	
3	PCB	FR4	black		1	
2	stem casing	ABS	black		1	
1	top base	Silica gel, hardness 50°	black		1	

Rev	Description	Date	Remark
1	New drawing		

Third Angle	Project	S540 PR0	Date	2022.12.9
Part No.	External antenna 1	M12-7253-ROA	Designed by	MD tianjin
Material		N/A	Checked by	RF machuitao
Angle	40~	± 2.0	Approved by	
Location	N/A		Unit	mm
			Scale	1:1
			Rev	A

1 2 3 4 5 6 7 8


Product packaging specification

date: 2021.10.16




page: 1 of 1

	versions A
Product name: External antenna	



一: Finished antenna



Two: Put it in a PE bag



4. The actual packing shall prevail



Four: The box is sealed, and the outer box is affixed with our production label and ROHS label.