

FCC ID: 2BC96NI-8311

RF Exposure Evaluation

Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

Pd = power density in mW/cm², **Pout** = output power to antenna in mW;

G = gain of antenna in linear scale, **Pi** = 3.1416;

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

Test Result of RF Exposure Evaluation

Modulation	Frequency (MHz)	Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
802.11b	2412	17.78	59.979108	0.039240	1.0	PASS
	2437	17.95	62.373484	0.040807	1.0	PASS
	2462	18.48	70.469307	0.046103	1.0	PASS
802.11g	2412	18.63	72.945751	0.047723	1.0	PASS
	2437	18.79	75.683290	0.049514	1.0	PASS
	2462	18.34	68.233869	0.044641	1.0	PASS
802.11n20	2412	19.78	95.060479	0.062191	1.0	PASS
	2437	19.85	96.605088	0.063202	1.0	PASS
	2462	19.22	83.560302	0.054668	1.0	PASS
GFSK	2402	3.80	2.398833	0.000848	1.0	PASS
	2440	2.33	1.710015	0.000605	1.0	PASS
	2480	3.02	2.004472	0.000709	1.0	PASS

In the case of simultaneous launches for Wifi and BLE:

Calc. Thresholds : 0.063202 + 0.000848 = 0.06405 < 1

Remark: wifi Antenna gain is 5.17 dBi, BLE Antenna gain is 2.499 dBi

So a SAR test is not required