

RF TEST REPORT

FCC ID: 2BCFY-ERO1BE

Test Report No.....: RF250516014-02-003

Product(s) Name.....: Wireless Home Mesh

Model(s).....: ERO1BE

Trade Mark.....: HEIGHTS

Applicant.....: HEIGHTS TELECOM T LTD

Address.....: Ha-Sakhlav 6,7680900 Iruv, Israel

Receipt Date.....: 2025.06.20

Test Date.....: 2025.09.15~2025.09.16

Issued Date.....: 2025.09.16

Standards.....: 47 CFR FCC Part 15, Subpart E(Section 15.407);
ANSI C63.10:2013

Testing Laboratory.....: Shenzhen Haiyun Standard Technical Co., Ltd.

Prepared By:	Checked By:	Approved By:	
Jason Huang	Black Ding	Tim Zhang	
<i>Jason Huang</i>	<i>Black Ding</i>	<i>Tim Zhang</i>	

Table of Contents

History of this test report.....	3
1. General Information	4
1.1 Applicant.....	4
1.2 Manufacturer	4
1.3 Basic Description of Equipment Under Test.....	4
1.4 Transmit Operating Mode.....	5
2. Summary of Test Results	7
2.1 Summary of Test Items	7
2.2 Application of Standard	7
2.3 Test Instruments.....	8
2.4 Operation Mode.....	9
2.5 Test Condition	9
2.6 Duty Cycle of Test Signal	10
2.7 Measurement Uncertainty	13
2.8 Test Location	13
2.9 SUPPORT UNITS	13
3. Test Procedure And Results	14
3.1 AC Power Line Conducted Emission.....	14
3.1.1 Limit	14
3.1.2 Test Procedure	14
3.1.3 Test Setup.....	14
3.1.4 Test Result.....	15
3.2 Radiated Emission.....	17
3.2.1 Limit	17
3.2.2 Test Procedure	18
3.2.3 Test Setup.....	19
3.2.4 Test Result.....	20

History of this test report

Original Report Issue Date: 2025.09.16

- No additional attachment
- Additional attachments were issued following record

Attachment No.	Issue Date	Description

1. General Information

1.1 Applicant

HEIGHTS TELECOM T LTD

Ha-Sakhlav 6,7680900 Iruv, Israel

1.2 Manufacturer

HEIGHTS TELECOM SWITZERLAND SA

Boulevard Georges-Favon, 43

1204 – Geneva

Switzerland

1.3 Basic Description of Equipment Under Test

Test sample no.	POC250516014-S004	
Product(s) Name	Wireless Home Mesh	
Test Model	ERO1BE	
Model differences	Model ERO1BE makes change based on Model ERO1BEM PRO, The structure remains unchanged, with the hardware removing the 6G WiFi component. Change 2 PHY from 10G to 2.5G, bit number GU1, GU2:2010060005381021 (10G PHY) to 2010060005331021 (2.5G PHY), bit number T2, T3:210010015252044 (10G network transformer) to 2100100012532044 (2.5G network transformer). Comes with a 2A adapter.	
Trade Mark	HEIGHTS	
Power Supply	DC 12V from adapter	
Adapter information	SOY-1200200US-539 Input: 100-240V~ 50/60Hz 0.6A Max Output: DC 12.0V/2A	
Operate temperature	0℃-40℃	
EUT Stage	○ Product Unit	● Final-Sample
Operating Band & Max Conducted Output Power	5150MHz ~5250MHz	802.11BE40: 29.07dBm(0.807W)
	5250MHz ~5350MHz	802.11BE80: 23.80dBm(0.240W)
	5470MHz ~5725MHz	802.11BE40: 23.90dBm(0.245W)
	5725MHz ~5850MHz	802.11BE80: 29.75dBm(0.944W)
Product Type	IEEE 802.11a/n/ac/ax/be: WLAN (MIMO)	
Nominal Bandwidth	20MHz / 40MHz / 80MHz / 160MHz	
Modulation	IEEE 802.11a/n/ac: OFDM IEEE 802.11ax/be: OFDMA	
Antenna gain	Ant1: 4.72dBi, Ant2: 4.68dBi, Ant3: 4.73dBi, Ant4: 4.19dBi	
Directional gain	1.14dBi(from the antenna report)	
Beamforming	6.91dB	
Antenna type	PCB antenna	

Data Rate (Mbps)	IEEE 802.11a mode : 6/9/12/18/24/36/48/54 IEEE 802.11n mode : up to 600 IEEE 802.11ac mode : up to 3466.7 IEEE 802.11ax mode : up to 4803.9 IEEE 802.11be mode : up to 5764.4
------------------	---

Note: Model ERO1BE makes change based on Model ERO1BEM PRO, The structure remains unchanged, with the hardware removing the 6G WiFi component. Change 2 PHY from 10G to 2.5G, bit number GU1, GU2:2010060005381021 (10G PHY) to 2010060005331021 (2.5G PHY), bit number T2, T3:210010015252044 (10G network transformer) to 2100100012532044 (2.5G network transformer). Comes with a 2A adapter.

Channel Information			
Frequency Range (MHz)	IEEE Std. 802.11	Ch. Frequency (MHz)	Channel Number
5150-5250	802.11a /n /ac /ax /be (20MHz)	5180-5240	36-48
5250-5350		5260-5320	52-64
5470-5725		5500-5700	100-140
5725-5850		5745-5825	149-165
5150-5250	802.11n /ac /ax /be (40MHz)	5190-5230	38-46
5250-5350		5270-5310	54-62
5470-5725		5510-5670	102-134
5725-5850		5755-5795	151-159
5150-5250	802.11ac /ax /be (80MHz)	5210	42
5250-5350		5290	58
5470-5725		5530-5610	106-122
5725-5850		5775	155
5150-5350	802.11 ac /ax /be (160MHz)	5250	50
5470-5725		5570	114

Note: For 802.11ax, 802.11be mode only support full RU mode.

1.4 Transmit Operating Mode

Transmit Operating Mode					Transmit Multiple Antennas					
☐	Operating mode 1 (single antenna)				☐	1TX				
☐	Operating mode 2 (multiple antenna, no beam forming)				☐	2TX	☐	3TX	☐	4TX
☒	Operating mode 3 (multiple antenna, with beam forming)				☐	2TX	☐	3TX	☒	4TX
☒	802.11a	Operating mode	☐	1TX	☐	2TX	☐	3TX	☒	4TX
☒	802.11n(20MHz)	Operating mode	☐	1TX	☐	2TX	☐	3TX	☒	4TX
☒	802.11n(40MHz)	Operating mode	☐	1TX	☐	2TX	☐	3TX	☒	4TX
☒	802.11ac(20MHz)	Operating mode	☐	1TX	☐	2TX	☐	3TX	☒	4TX
☒	802.11ac(40MHz)	Operating mode	☐	1TX	☐	2TX	☐	3TX	☒	4TX
☒	802.11ac(80MHz)	Operating mode	☐	1TX	☐	2TX	☐	3TX	☒	4TX
☒	802.11ac(160MHz)	Operating mode	☐	1TX	☐	2TX	☐	3TX	☒	4TX
☒	802.11ax(20MHz)	Operating mode	☐	1TX	☐	2TX	☐	3TX	☒	4TX

●	802.11ax(40MHz)	Operating mode	☐	1TX	☐	2TX	☐	3TX	●	4TX
●	802.11ax(80MHz)	Operating mode	☐	1TX	☐	2TX	☐	3TX	●	4TX
●	802.11ax(160MHz)	Operating mode	☐	1TX	☐	2TX	☐	3TX	●	4TX
●	802.11be(20MHz)	Operating mode	☐	1TX	☐	2TX	☐	3TX	●	4TX
●	802.11be (40MHz)	Operating mode	☐	1TX	☐	2TX	☐	3TX	●	4TX
●	802.11be (80MHz)	Operating mode	☐	1TX	☐	2TX	☐	3TX	●	4TX
●	802.11be (160MHz)	Operating mode	☐	1TX	☐	2TX	☐	3TX	●	4TX

2. Summary of Test Results

2.1 Summary of Test Items

47 CFR FCC Part 15, Subpart E (Section 15.407)			
Test item	Standard	Results	Remarks
AC Power Conducted Emission	15.207 15.407(b)	Pass	Meet the requirement of the limit
Radiated Emission	15.205(a) 15.209(a) 15.407(b)	Pass	Meet the requirement of the limit
Antenna Requirements	15.203	Compliance	Note1
Spectrum Bandwidth	15.407(a) 15.407(e)	Pass Note 2	Meet the requirement of the limit
Conducted Output Power	15.407(a)	Pass Note 2	Meet the requirement of the limit
Power Spectral Density	15.407(a)	Pass Note 2	Meet the requirement of the limit
Dynamic Frequency Selection (DFS)	15.407(h)	Pass Note 3	Meet the requirement of the limit

Note:

1. The EUT has four non removable internal antenna units.
2. After evaluation, only the AC Power Line Conducted Emissions and Radiated Emissions were tested. The remaining data refer to the report RF250516014-01-003 of model ERO1BEM PRO
3. For test data, please refer to the report RF250516014-01-004 of model ERO1BEM PRO.

2.2 Application of Standard

47 CFR FCC Part 15, Subpart E

KDB 789033 D02 General UNII Test Procedures New Rules v02r01

KDB 662911 D01 Multiple Transmitter Output v02r01

KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02

ANSI C63.10:2013

2.3 Test Instruments

No.	Name of Equipment	Manufacturer	Model Number	Serial Number	Inventory No.	Last Calibration	Due Calibration
Radiated Emission							
1	Test receiver	Rohde&Schwarz	ESU	100184	JLE011	2025/3/1	2026/2/28
2	Log periodic antenna	Schwarzbeck	VULB 9168	1151	JLE012	2025/4/12	2026/4/11
3	Low frequency amplifier	/	LNA 0920N	2014	JLE023	2025/3/1	2026/2/28
4	High frequency amplifier	Schwarzbeck	BBV 9718	9718-284	JLE024	2025/3/1	2026/2/28
5	Horn Antenna	SCHWARZBECK	BBHA 9120 D	02670	JLE028	2025/4/12	2026/4/11
6	Temp&Humidity Recorder	Meideshi	JR900	/	JLE021	2025/4/15	2026/4/14
7	Horn Antenna	SCHWARZBECK	BBHA 9170	9170#685	JLE029	2024/7/15	2025/7/14
8	Loop Antenna	SCHWARZBECK	FMZB1519B	00029	JLE030	2024/7/15	2025/7/14
9	Broadband preamplifier	Schwarzbeck	BBV9721	9721-019	JLE025	2025/3/1	2026/2/28
10	Test software	Farad Technology Co., Ltd	EZ-EMC Ver.TW-03A2				
Conducted Emission							
1	LISN	Rohde&Schwarz	ENV216	100075	JLE002	2025/3/1	2026/2/28
2	ISN	Schwarzbeck	CATE 5 8158	#171	JLE003	2025/2/21	2026/2/20
3	ISN	Schwarzbeck	CAT 3 8158	00187	JLE032	2025/2/21	2026/2/20
4	Test receiver	Rohde&Schwarz	ESCI	100718	JLE010	2025/3/1	2026/2/28
5	Pulse limiter	Rohde&Schwarz	ESH3-Z2	102299	JLE047	2025/3/1	2026/2/28
6	Temp&Humidity Recorder	Meideshi	JR900	/	JLE020	2025/4/15	2026/4/14
7	Test software	Farad Technology Co., Ltd	EZ-EMC Ver.TW-03A2				
RF Conducted Emissions							
1	MXA Signal Analyzer	Keysight	N9021B	MY60080169	JLE050	2025/3/1	2026/2/28
2	RF Control Unit	dsusoft	JS0806-2	21G8060449	JLE053	2025/3/1	2026/2/28
3	power supply unit	dsusoft	JS0806-4ADC	N/A	JLE055	2025/3/1	2026/2/28
4	VXG Signal Generator	Keysight	M9384B	MY61270787	JLE051	2024/6/11 2025/6/10	2025/6/10 2026/6/09
5	EXG Analog Signal Generator	Keysight	N5173B	MY59101282	JLE052	2025/3/1	2026/2/28
6	Wideband Radio Communication Tester	Rohde&Schwarz	CMW500	1201.0002K5 0-116064-Dt	JLE054	2025/3/1	2026/2/28
7	Test software	dsusoft	JS1120-3 Ver.3.2.22.0				

2.4 Operation Mode

The EUT was supplied by and it was run in TX mode that was controlled by Master provided RF testing program. The worst case test result was showed in the report.

Test channel mode
802.11a_Nss 1,(6Mbps)
802.11be EHT20-BF_Nss1,(MCS0)
802.11be EHT40-BF_Nss1,(MCS0)
802.11be EHT80-BF_Nss1,(MCS0)
802.11be EHT160-BF_Nss1,(MCS0)

Evaluated EHT20/EHT40/EHT80/EHT160 covers HT20/HT40/VHT20/VHT40/VHT80/VHT160/HEW20/HEW40/HEW80/HEW160 due to similar modulation. The power setting for HT20/HT40/VHT20/VHT40/VHT80/VHT160/HEW20/HEW40/HEW80/HEW160 is the same or lower than EHT20/EHT40/EHT80/EHT160.

The EUT supports non-beamforming and beamforming modes, after evaluating, the beamforming mode has been selected to test.

2.5 Test Condition

Test Item	Environmental conditions	Input Power	Tested by
AC Power Conducted Emission	25°C, 53% RH	AC 120V/60Hz	Keith Huang
Radiated Emission	24°C, 51% RH	AC 120V/60Hz	Lemon He

Note: Adapter supply voltage AC 120V/60Hz.

The applicant declare the operating environment of EUT as below:

Normal conditions: DC 12V, 0~40°C


2.6 Duty Cycle of Test Signal

If duty cycle is $\geq 98\%$, duty factor is not required.


If duty cycle is $< 98\%$, duty factor shall be considered.

All the duty factor of other test mode have been considered.


TestMode	Antenna	Frequency[MHz]	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle [%]
11A-CDD	Ant1	5180	2.07	2.18	94.95
11BE20MIMO	Ant1	5180	1.50	1.53	98.04
11BE40MIMO	Ant1	5190	0.78	0.81	96.30
11BE80MIMO	Ant1	5210	0.41	0.44	93.18
11BE160MIMO	Ant1	5250	0.24	0.27	88.89




11BE20MIMO_Ant1_5180




11BE40MIMO_Ant1_5190



11BE80MIMO_Ant1_5210



11BE160MIMO_Ant1_5250



2.7 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Uncertainty	
Parameter	Uncertainty
Occupied Channel Bandwidth	$\pm 102\text{kHz}$
Power Spectral Density	$\pm 0.243\text{dB}$
Conducted Spurious Emission	$\pm 0.743\text{dB}$
RF power conducted	$\pm 1.328\text{dB}$
Conducted emission(9kHz~30MHz) AC main	$\pm 2.68\text{dB}$
Radiated emission(9kHz~30MHz)	$\pm 3.50\text{dB}$
Radiated emission (30MHz~1GHz)	$\pm 4.20\text{dB}$
Radiated emission (1GHz~18GHz)	$\pm 5.10\text{dB}$
Radiated emission (18GHz~40GHz)	$\pm 5.26\text{dB}$

2.8 Test Location

Company:	Shenzhen Haiyun Standard Technical Co., Ltd.
Address:	No. 110-113, 115, 116, Block B, Jinyuan Business Building, Bao'an District, Shenzhen, China
CNAS Registration Number:	CNAS L18252
CAB identifier:	CN0145
A2LA Certificate Number:	6823.01
Telephone:	0755-26024411

2.9 SUPPORT UNITS

No.	Equipment	Model	Manufacturer	Series No
1	PC	M4500T	Thinkpad	M032004854IT
2	Notebook	L450	Think	/
3	Notebook	L450	Think	/

3. Test Procedure And Results

3.1 AC Power Line Conducted Emission

3.1.1 Limit

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μ V)	Average Level dB(μ V)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. * Decreasing linearly with logarithm of frequency.


2. The lower limit shall apply at the transition frequencies.

3.1.2 Test Procedure

Test Method	
●Conducted Measurement	○Radiated Measurement
Test Channels	
○ Lowest, Middle and Highest Channel	○ Lowest and Highest Channel
Environmental conditions	
●Normal	○Normal and Extreme
Note: ●:Test ○:No Test	

- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

3.1.3 Test Setup



3.1.4 Test Result


Note:

1. Correct Factor = LISN Factor + Cable Loss + Pulse Limiter Factor, the value was added to Original Receiver Reading by the software automatically.
2. Measurement = Reading + Correct Factor.
3. Over = Measurement – Limit
4. The TX N40 Mode Channel 159 is found to be the worst case and recorded.


150kHz~30MHz

TX 11AX40MIMO Channel 64

Line



Conducted Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV	dBuV	dB	cm	degree	Comment
1	*	0.1503	31.94	19.70	51.64	65.98	-14.34	QP		
2		0.1503	13.19	19.70	32.89	55.98	-23.09	AVG		
3		0.1833	26.50	19.70	46.20	64.33	-18.13	QP		
4		0.1833	6.66	19.70	26.36	54.33	-27.97	AVG		
5		0.3747	18.70	19.70	38.40	58.40	-20.00	QP		
6		0.3747	10.78	19.70	30.48	48.40	-17.92	AVG		
7		3.4671	9.13	20.25	29.38	56.00	-26.62	QP		
8		3.4671	1.91	20.25	22.16	46.00	-23.84	AVG		
9		16.7155	17.29	20.55	37.84	60.00	-22.16	QP		
10		16.7155	8.48	20.55	29.03	50.00	-20.97	AVG		
11		20.1685	16.18	20.34	36.52	60.00	-23.48	QP		
12		20.1685	10.00	20.34	30.34	50.00	-19.66	AVG		

3.2 Radiated Emission

3.2.1 Limit

1) Limit of radiated emission measurement:

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequency (MHz)	Distance Meters(m)	Field Strength Limit	
		$\mu\text{V}/\text{m}$	$\text{dB}(\mu\text{V})/\text{m}$
0.009 – 0.49	300	$2400/F(\text{kHz})$	-
0.490 – 1.705	30	$24000/F(\text{kHz})$	-
1.705 – 30	30	30	-
30~88	3	100	40.0
88~216	3	150	43.5
216~960	3	200	46.0
960~1000	3	500	54.0
Above 1000	3	74.0 $\text{dB}(\mu\text{V})/\text{m}$ (Peak) 54.0 $\text{dB}(\mu\text{V})/\text{m}$ (Average)	

Note: (1) Emission level $\text{dB}\mu\text{V} = 20 \log$ Emission level $\mu\text{V}/\text{m}$

(2) The smaller limit shall apply at the cross point between two frequency bands.

(3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

2) Limit of unwanted emission out of the restricted bands:

Frequency(MHz)	EIRP Limit(dBm/MHz)	Equivalent Field Strength at 3m($\text{dB}\mu\text{V}/\text{m}$)
5150-5250	-27	68.2
5250-5350	-27	68.2
5470-5725	-27	68.2
5725-5850	-27 NOTE (2)	68.2
	10 NOTE (2)	105.2
	15.6 NOTE (2)	110.8
	27 NOTE (2)	122.2

Note: (1) The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength: $E[\text{dB}\mu\text{V}/\text{m}] = \text{EIRP}[\text{dBm}] + 95.2$, for $d=3\text{m}$

(2) According to 15.407(b)(4)(i), all emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.


3.2.2 Test Procedure

Test Method	
○Conducted Measurement	●Radiated Measurement
Test Channels	
●Lowest, Middle and Highest Channel	○ Lowest and Highest Channel
Environmental conditions	
●Normal	○Normal and Extreme
Note:●:Test ○:No Test	


- a) The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1 GHz)
- b) The measuring distance of 3 m or 1.5m shall be used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1GHz)
- c) The height of the equipment or of the substitution antenna shall be 0.8m or 1.5m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights find the maximum reading (used Bore sight function).
- e) The receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.
- f) The initial step in collecting radiated emission data is a receiver peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- g) All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform. (below 1 GHz)
- h) All readings are Peak Mode value unless otherwise stated AVG in column of Note. If the Peak Mode Measured value compliance with the Peak Limits and lower than AVG Limits, the EUT shall be deemed to meet both Peak & AVG Limits and then only Peak Mode was measured, but AVG Mode didn't perform. (above 1 GHz)
- i) For the actual test configuration, please refer to the related Item -EUT Test Photos.

3.2.3 Test Setup


(A) Radiated Emission Test Set-Up Frequency Below 30 MHz



(B) Radiated Emission Test Set-Up Frequency 30 MHz-1000 MHz



(C) Radiated Emission Test Set-Up Frequency Above 1 GHz



3.2.4 Test Result

1) Radiated emission: 9kHz-30MHz

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not recorded in this report.

2) Radiated emission: 30MHz-1G


Note:

1. Measurement = Reading + Correct Factor.
2. Over = Measurement – Limit
3. The TX N40 Mode Channel 159 is found to be the worst case and recorded.


Below 1G (30MHz~1GHz)

TX 11AX40MIMO Channel 64

VERTICAL



HORIZONTAL




3) Radiated emission: Above 1G


Note:

1. Measurement = Reading + Correct Factor.
2. Over = Measurement – Limit
3. Pre-scan TPC_H and TPC_L, worst case for TPC_H was recorded.


Above 1G (1GHz~18GHz)	Test mode:11A CDD	Test Channel:36
VERTICAL		




HORIZONTAL




VERTICAL




HORIZONTAL



VERTICAL



HORIZONTAL




Above 1G (1GHz~18GHz)


Test mode: 11A CDD

Test Channel:149

VERTICAL



HORIZONTAL




Above 1G (1GHz~18GHz)


Test mode: 11A CDD

Test Channel:165


VERTICAL




HORIZONTAL




VERTICAL




HORIZONTAL




VERTICAL




HORIZONTAL




VERTICAL




HORIZONTAL




VERTICAL




HORIZONTAL




VERTICAL




HORIZONTAL



VERTICAL




HORIZONTAL



VERTICAL


Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	11596.445	48.75	-0.66	48.09	54.00	-5.91	AVG		
2		11601.767	59.75	-0.68	59.07	74.00	-14.93	peak		
3		17385.167	48.69	4.66	53.35	68.20	-14.85	peak		


HORIZONTAL

Radiated Emission




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	11588.822	48.44	-0.64	47.80	54.00	-6.20	AVG		
2		11599.500	57.22	-0.67	56.55	74.00	-17.45	peak		
3		17385.433	49.40	4.66	54.06	68.20	-14.14	peak		


VERTICAL




HORIZONTAL




VERTICAL




HORIZONTAL




VERTICAL




HORIZONTAL




VERTICAL




HORIZONTAL




VERTICAL




HORIZONTAL



VERTICAL



HORIZONTAL



Note: The high frequency, which started from 18GHz to 40GHz, was pre-scanned and the result which was 20dB lower than the limit line was not recorded in this report.

Statement

1. The report is invalid without the official seal or special seal of Shenzhen Haiyun Standard Technical Co., Ltd. (hereinafter referred to as the unit).
2. The report is invalid without the signature of the approver.
3. The report is invalid if altered arbitrarily.
4. The report shall not be partially copied without the written approval of the unit.
5. The reported test results are only valid for the tested samples.
6. If there is any objection to the test report, it shall be submitted to the test unit within 15 days from the date of receiving the report, and the overdue shall not be accepted.

Shenzhen Haiyun Standard Technical Co., Ltd.

Address: Room 110, 111, 112, 113, 115, 116, Block B, Jinyuan Business Building, No. 302, Xixiang Avenue, Labor Community, Xixiang Street, Baoan District, Shenzhen, China

Tel: 0755-26024411

Email: service@hy-lab.cn

(END OF REPORT)