


# TEST REPORT

For FCC Part15B

**Report No.** .....: **CHTEW23100012** Report verification: 

**Project No.** .....: **SHT2307072001EW**

**FCC ID**.....: **2BCVK-NARIPO-01**

**Applicant's name**.....: **Shenzhen Narig Bio-Medical Technology Co.,Ltd.**

**Address**.....: 1106 Room,East Tower,Digital Culture Industry Base No.10128  
Shennan Road,Nanshan District Shenzhen,Guangdong 518052  
China

**Product Name** .....: **Pulse Oximeter**

**Trade Mark** .....: -

**Model No.** .....: CF-100B

**Listed Model(s)** .....: CF-100,FRO-200,FRO-202

**Standard** .....: **FCC CFR Title 47 Part 15 Subpart B**

**Date of receipt of test sample**.....: Sep.06, 2023

**Date of testing**.....: Sep.06, 2023- Oct.09, 2023

**Date of issue**.....: Oct.10, 2023

**Result**.....: **Pass**

Compiled by  
(position+printed name+signature)....: File administrators Echo Wei

Supervised by  
(position+printed name+signature)....: Project Engineer Caspar Chen

Approved by  
(position+printed name+signature)....: RF Manager Xu Yang

*Echo Wei*

*Caspar Chen*

*Xu Yang*

**Testing Laboratory Name** .....: **Shenzhen Huatongwei International Inspection Co., Ltd.**

**Address**.....: 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao,  
Gongming, Shenzhen, China

**Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

*The test report merely corresponds to the test sample.*

## Contents

<b><u>1.</u></b>	<b><u>TEST STANDARDS AND REPORT VERSION .....</u></b>	<b><u>3</u></b>
1.1.	Test Standards	3
1.2.	Report version information	3
<b><u>2.</u></b>	<b><u>TEST DESCRIPTION .....</u></b>	<b><u>4</u></b>
<b><u>3.</u></b>	<b><u>SUMMARY.....</u></b>	<b><u>5</u></b>
3.1.	Client Information	5
3.2.	Product Description	5
3.3.	Testing Laboratory Information	5
<b><u>4.</u></b>	<b><u>TEST CONFIGURATION.....</u></b>	<b><u>6</u></b>
4.1.	Descriptions of test mode	6
4.2.	Support unit used in test configuration	6
4.3.	Environmental conditions	6
4.4.	Statement of the measurement uncertainty	6
4.5.	Equipments Used during the Test	7
<b><u>5.</u></b>	<b><u>TEST CONDITIONS AND RESULTS .....</u></b>	<b><u>8</u></b>
5.1.	Conducted Emissions	8
5.2.	Radiated Emissions	9
<b><u>6.</u></b>	<b><u>TEST SETUP PHOTOS OF THE EUT .....</u></b>	<b><u>15</u></b>
<b><u>7.</u></b>	<b><u>EXTERNAL AND INTERNAL PHOTOS OF THE EUT .....</u></b>	<b><u>15</u></b>

## 1. TEST STANDARDS AND REPORT VERSION

### 1.1. Test Standards

The tests were performed according to following standards:

[FCC CFR Title 47 Part 15 Subpart B](#) - Unintentional Radiators

[ANSI C63.4: 2014](#) – American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40GHz

### 1.2. Report version information

Revision No.	Date of issue	Description
N/A	2023-10-10	Original

## 2. TEST DESCRIPTION

Section	Test Item	Section in CFR 47	Result <sup>#1</sup>	Test Engineer
5.1	Conducted Emissions	15.107(a)	N/A	N/A
5.2	Radiated Emissions	15.109(a)	PASS	Chuanfeng Li

Note:

#1: The test result does not include measurement uncertainty value

### 3. SUMMARY

#### 3.1. Client Information

Applicant:	Shenzhen Narig Bio-Medical Technology Co.,Ltd.
Address:	1106 Room,East Tower,Digital Culture Industry Base No.10128 Shennan Road,Nanshan District Shenzhen,Guangdong 518052 China
Manufacturer:	Shenzhen Narig Bio-Medical Technology Co.,Ltd.
Address:	1106 Room,East Tower,Digital Culture Industry Base No.10128 Shennan Road,Nanshan District Shenzhen,Guangdong 518052 China

#### 3.2. Product Description

Main unit information:	
Product Name:	Pulse Oximeter
Trade Mark:	-
Model No.:	CF-100B
Listed Model(s):	CF-100,FRO-200,FRO-202
Power supply:	DC 3V from AAA*2
Hardware version:	V01.00.00
Software version:	V01.00.02

#### 3.3. Testing Laboratory Information

Laboratory Name	Shenzhen Huatongwei International Inspection Co., Ltd.	
Laboratory Location	1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China	
Contact information:	Tel: 86-755-26715499 E-mail: <a href="mailto:cs@szhtw.com.cn">cs@szhtw.com.cn</a> <a href="http://www.szhtw.com.cn">http://www.szhtw.com.cn</a>	
Qualifications	Type	Accreditation Number
	FCC	762235

## 4. TEST CONFIGURATION

### 4.1. Descriptions of test mode

Test mode	Description
Working mode	Keep EUT in power on working state

### 4.2. Support unit used in test configuration

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

The following peripheral devices and interface cables were connected during the measurement:

Whether support unit is used?			
✓ No			
Item	Equipment	Trade Name	Model No.
1			
2			

### 4.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15~35°C
Relative Humidity:	30~60 %
Air Pressure:	950~1050mba

### 4.4. Statement of the measurement uncertainty

No.	Test Items	Measurement Uncertainty
1	AC Conducted Emission	3.21dB
2	Radiated Emission	4.54dB for 30MHz-1GHz 5.10dB for above 1GHz

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

#### 4.5. Equipments Used during the Test

● Radiated Emission - 30MHz~1GHz							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0127	SAC-3m-02	C11121	2023/4/6	2026/4/5
●	EMI Test Receiver	R&S	HTWE0099	ESCI 7	100900	2023/8/22	2024/8/21
●	Ultra-Broadband Antenna	SCHWARZBECK	HTWE0119	VULB9163	546	2023/2/22	2026/2/21
●	Pre-Amplifier	SCHWARZBECK	HTWE0295	BBV 9742	/	2023/5/25	2024/5/24
●	Test Software	R&S	N/A	EMC32	N/A	N/A	N/A

● Radiated emission-Above 1GHz							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0122	SAC-3m-01	C11121	2023/4/17	2026/4/16
●	Spectrum Analyzer	R&S	HTWE0098	FSP40	100597	2023/8/22	2024/8/21
●	Horn Antenna	SCHWARZBECK	HTWE0126	BBHA 9120D	1011	2023/2/14	2026/2/13
●	Horn Antenna	SCHWARZBECK	HTWE0103	BBHA9170	BBHA9170472	2023/2/20	2026/2/19
●	Broadband Pre-amplifier	SCHWARZBECK	HTWE0201	BBV 9718	9718-248	2023/5/25	2024/5/24
●	Test Software	R&S	N/A	EMC32	N/A	N/A	N/A

## 5. TEST CONDITIONS AND RESULTS

### 5.1. Conducted Emissions


#### LIMIT

FCC CFR Title 47 Part 15 Subpart B Section 15.107:

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\* Decreases with the logarithm of the frequency.

#### TEST CONFIGURATION



#### TEST PROCEDURE

1. The EUT was setup according to ANSI C63.4:2014
2. The EUT was placed on a plat form of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedance stabilization network (LISN). The LISN provides a 50ohm / 50uH coupling impedance for the measuring equipment.
4. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
7. Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
8. During the above scans, the emissions were maximized by cable manipulation.

#### TEST MODE:

Please refer to the clause 3.3

#### TEST RESULTS

☐ Passed ☒ Not Applicable



## 5.2. Radiated Emissions


### LIMIT

#### FCC CFR Title 47 Part 15 Subpart B Section 15.109


Frequency	Limit (dBuV/m @3m)	Value
30MHz-88MHz	40.00	Quasi-peak
88MHz-216MHz	43.50	Quasi-peak
216MHz-960MHz	46.00	Quasi-peak
960MHz-1GHz	54.00	Quasi-peak
Above 1GHz	54.00	Average
	74.00	Peak

### TEST CONFIGURATION

#### ➤ 30MHz ~ 1GHz



#### ➤ Above 1GHz



### TEST PROCEDURE

1. The EUT was tested according to ANSI C63.4:2014.
2. The EUT is placed on a turn table which is 0.8 meter above ground.
3. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
4. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
5. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna.
6. Use the following spectrum analyzer settings
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Below 1GHz,  
RBW=120KHz, VBW=300KHz, Sweep=auto, Detector function=peak, Trace=max hold;  
If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
  - (3) From 1GHz to 5th harmonic, RBW=1MHz, VBW=3MHz

**TEST MODE:**

Please refer to the clause 3.3

**TEST RESULTS**


☒ **Passed**      ☐ **Not Applicable**

Note: Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor  
The emission levels of frequency above 6GHz are very lower than limit and not show in test report.


**CF-100B**

Polarization:

Horizontal

**Final Result**


Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
296.8713	25.18	46.00	20.82	100.0	H	0.0	-7.5
376.8963	25.23	46.00	20.77	100.0	H	5.0	-5.1
431.7013	25.36	46.00	20.64	100.0	H	349.0	-3.4
535.6125	26.54	46.00	19.46	300.0	H	198.0	-1.4
944.8313	34.01	46.00	11.99	300.0	H	147.0	7.1
980.7213	35.36	54.00	18.64	300.0	H	191.0	7.7

**Final Result**


Frequency (MHz)	MaxPeak (dBuV/m)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2211.2500	35.62	---	74.00	38.38	150.0	H	232.0	-5.7
2819.3750	35.92	---	74.00	38.08	150.0	H	105.0	-5.0
2890.0000	---	33.46	54.00	20.54	150.0	H	110.0	-4.4
3159.3750	36.97	---	74.00	37.03	150.0	H	56.0	-3.7
3425.0000	---	34.08	54.00	19.92	150.0	H	124.0	-4.1
3973.1250	37.80	---	74.00	36.20	150.0	H	79.0	-1.5
3997.5000	---	35.61	54.00	18.39	150.0	H	263.0	-1.6
4836.8750	39.78	---	74.00	34.22	150.0	H	96.0	1.4
4836.8750	---	37.37	54.00	16.63	150.0	H	96.0	1.4
5425.0000	---	39.53	54.00	14.47	150.0	H	306.0	2.9
5930.0000	41.51	---	74.00	32.49	150.0	H	303.0	3.9
5985.6250	---	39.77	54.00	14.23	150.0	H	277.0	4.1

Polarization:

Vertical

**Final Result**

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
46.6113	18.90	40.00	21.10	100.0	V	11.0	-8.8
60.5550	19.80	40.00	20.20	100.0	V	0.0	-10.1
494.0238	25.53	46.00	20.47	100.0	V	287.0	-2.0
537.5525	26.35	46.00	19.65	100.0	V	48.0	-1.4
687.5388	29.84	46.00	16.16	100.0	V	273.0	2.1
919.0050	32.98	46.00	13.02	100.0	V	48.0	7.1


**Final Result**

Frequency (MHz)	MaxPeak (dBuV/m)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2062.5000	35.71	---	74.00	38.29	150.0	V	0.0	-7.5
2718.1250	35.44	---	74.00	38.56	150.0	V	292.0	-5.6
3003.7500	---	35.09	54.00	18.91	150.0	V	337.0	-4.1
3003.7500	36.75	---	74.00	37.25	150.0	V	337.0	-4.1
3149.3750	---	34.81	54.00	19.19	150.0	V	208.0	-3.7
3725.6250	---	36.04	54.00	17.96	150.0	V	29.0	-2.5
4091.8750	38.00	---	74.00	36.00	150.0	V	135.0	-1.4
5011.8750	---	37.71	54.00	16.29	150.0	V	144.0	1.9
5011.8750	39.87	---	74.00	34.13	150.0	V	144.0	1.9
5127.5000	42.42	---	74.00	31.58	150.0	V	98.0	2.8
5465.6250	---	39.73	54.00	14.27	150.0	V	163.0	3.1
5880.0000	---	39.97	54.00	14.04	150.0	V	329.0	4.0


**FRO-200**

Polarization:

Horizontal

**Final Result**


Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
50.9763	18.90	40.00	21.10	100.0	H	131.0	-8.8
384.8988	24.67	46.00	21.33	100.0	H	0.0	-5.0
422.8500	24.76	46.00	21.24	100.0	H	11.0	-3.8
553.9213	25.43	46.00	20.57	100.0	H	22.0	-0.8
945.1950	38.78	46.00	7.22	300.0	H	42.0	7.1
948.4688	40.96	46.00	5.04	300.0	H	154.0	7.1

**Final Result**


Frequency (MHz)	MaxPeak (dBuV/m)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2168.7500	34.85	---	74.00	39.15	150.0	H	320.0	-6.0
2688.7500	---	34.02	54.00	19.98	150.0	H	29.0	-5.8
2880.0000	35.78	---	74.00	38.22	150.0	H	240.0	-4.4
3124.3750	---	34.88	54.00	19.12	150.0	H	0.0	-3.8
3285.6250	36.38	---	74.00	37.62	150.0	H	215.0	-4.3
4107.5000	---	35.45	54.00	18.55	150.0	H	104.0	-1.4
4164.3750	38.65	---	74.00	35.35	150.0	H	212.0	-1.2
4580.0000	---	38.34	54.00	15.66	150.0	H	232.0	0.9
4670.6250	---	38.30	54.00	15.70	150.0	H	308.0	0.8
4825.6250	39.70	---	74.00	34.30	150.0	H	141.0	1.4
5401.8750	---	39.38	54.00	14.62	150.0	H	67.0	2.7
5873.1250	42.14	---	74.00	31.86	150.0	H	0.0	3.9

Polarization:

Vertical

**Final Result**


Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
553.0725	26.49	46.00	19.51	100.0	V	97.0	-0.8
575.2613	27.26	46.00	18.74	100.0	V	0.0	-0.3
597.2075	28.68	46.00	17.32	100.0	V	328.0	1.0
687.5388	31.94	46.00	14.06	100.0	V	169.0	2.1
945.3163	38.46	46.00	7.54	100.0	V	161.0	7.1
948.4688	41.00	46.00	5.00	100.0	V	129.0	7.1

**Final Result**


Frequency (MHz)	MaxPeak (dBuV/m)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2062.5000	36.25	---	74.00	37.75	150.0	V	61.0	-7.5
2673.1250	36.25	---	74.00	37.75	150.0	V	55.0	-5.8
2875.6250	---	33.79	54.00	20.21	150.0	V	305.0	-4.4
3170.6250	36.41	---	74.00	37.59	150.0	V	259.0	-3.6
3170.6250	---	34.03	54.00	19.97	150.0	V	259.0	-3.6
3458.7500	---	34.17	54.00	19.83	150.0	V	135.0	-3.8
3945.6250	---	36.13	54.00	17.87	150.0	V	0.0	-1.7
3945.6250	38.74	---	74.00	35.26	150.0	V	0.0	-1.7
4901.2500	---	38.89	54.00	15.11	150.0	V	265.0	1.4
4901.2500	40.34	---	74.00	33.66	150.0	V	265.0	1.4
5464.3750	---	39.11	54.00	14.89	150.0	V	175.0	3.1
5493.7500	41.74	---	74.00	32.26	150.0	V	245.0	3.1

## 6. TEST SETUP PHOTOS OF THE EUT

Radiated Emissions (30MHz-1GHz)



Radiated Emissions (Above 1GHz)



## 7. EXTERNAL AND INTERNAL PHOTOS OF THE EUT

Refer to the test report No.: CHTEW23100011

-----End of Report-----