

FCC Test Report (2.4GHz WLAN)

Report No.: RFBARR-WTW-P21030485

FCC ID: RAS-MT7922A22M

Test Model: MT7922A22M

Received Date: Mar. 12, 2021

Test Date: Mar. 12 to May 17, 2021

Issued Date: May 26, 2021

Applicant: MediaTek Inc.

Address: No. 1, Dusing 1st Rd., Hsinchu Science Park Hsinchu City 30078, Taiwan

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan

Test Location: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan

**FCC Registration /
Designation Number:** 723255 / TW2022



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Table of Contents

Release Control Record	4
1 Certificate of Conformity.....	5
2 Summary of Test Results	6
2.1 Measurement Uncertainty	6
2.2 Modification Record	6
3 General Information.....	7
3.1 General Description of EUT (2.4GHz WLAN)	7
3.2 Description of Test Modes	9
3.2.1 Test Mode Applicability and Tested Channel Detail	10
3.3 Duty Cycle of Test Signal	12
3.4 Description of Support Units	14
3.4.1 Configuration of System under Test	15
3.5 General Description of Applied Standards and References	16
4 Test Types and Results	17
4.1 Radiated Emission and Bandedge Measurement.....	17
4.1.1 Limits of Radiated Emission and Bandedge Measurement	17
4.1.2 Test Instruments	18
4.1.3 Test Procedures.....	22
4.1.4 Deviation from Test Standard	23
4.1.5 Test Setup.....	23
4.1.6 EUT Operating Conditions.....	24
4.1.7 Test Results	25
4.2 Conducted Emission Measurement	56
4.2.1 Limits of Conducted Emission Measurement	56
4.2.2 Test Instruments	56
4.2.3 Test Procedures.....	57
4.2.4 Deviation from Test Standard	57
4.2.5 Test Setup.....	57
4.2.6 EUT Operating Conditions.....	57
4.2.7 Test Results	58
4.3 6dB Bandwidth Measurement.....	60
4.3.1 Limits of 6dB Bandwidth Measurement.....	60
4.3.2 Test Setup.....	60
4.3.3 Test Instruments	60
4.3.4 Test Procedure	60
4.3.5 Deviation from Test Standard	60
4.3.6 EUT Operating Conditions.....	60
4.3.7 Test Result.....	61
4.4 Conducted Output Power Measurement.....	64
4.4.1 Limits of Conducted Output Power Measurement	64
4.4.2 Test Setup.....	64
4.4.3 Test Instruments	64
4.4.4 Test Procedures.....	64
4.4.5 Deviation from Test Standard	64
4.4.6 EUT Operating Conditions.....	64
4.4.7 Test Results	65
4.5 Power Spectral Density Measurement.....	69
4.5.1 Limits of Power Spectral Density Measurement	69
4.5.2 Test Setup.....	69
4.5.3 Test Instruments	69
4.5.4 Test Procedure	69
4.5.5 Deviation from Test Standard	69
4.5.6 EUT Operating Condition	69

4.5.7 Test Results	70
4.6 Conducted Out of Band Emission Measurement.....	73
4.6.1 Limits of Conducted Out of Band Emission Measurement	73
4.6.2 Test Setup.....	73
4.6.3 Test Instruments	73
4.6.4 Test Procedure	73
4.6.5 Deviation from Test Standard	73
4.6.6 EUT Operating Condition	73
4.6.7 Test Results	73
5 Pictures of Test Arrangements.....	99
Annex A - Band-Edge Measurement.....	100
Appendix – Information of the Testing Laboratories	112

Release Control Record

Issue No.	Description	Date Issued
RFBARR-WTW-P21030485	Original release.	May 26, 2021

1 Certificate of Conformity

Product: 2TX 11ax (WiFi6E) BW160 + BT/BLE Combo Card

Brand: MediaTek

Test Model: MT7922A22M

Sample Status: Engineering sample

Applicant: MediaTek Inc.

Test Date: Mar. 12 to May 17, 2021

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)
ANSI C63.10: 2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : Phoenix Huang, **Date:** May 26, 2021
Phoenix Huang / Specialist

Approved by : Clark Lin, **Date:** May 26, 2021
Clark Lin / Technical Manager

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)			
FCC Clause	Test Item	Result	Remarks
15.207	AC Power Conducted Emission	Pass	Meet the requirement of limit. Minimum passing margin is -13.65 dB at 0.15105 MHz.
15.205 / 15.209 / 15.247(d)	Radiated Emissions and Band Edge Measurement	Pass	Meet the requirement of limit. Minimum passing margin is -0.1dB at 2390.00 MHz, 2483.50 MHz, 2484.28 MHz and 4874.00 MHz.
15.247(d)	Antenna Port Emission	Pass	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	Pass	Meet the requirement of limit.
15.247(b)	Conducted power	Pass	Meet the requirement of limit.
15.247(e)	Power Spectral Density	Pass	Meet the requirement of limit.
15.203	Antenna Requirement	Pass	Antenna connector is i-pex(MHF) not a standard connector.

Note:

- For 2.4 GHz band compliance with rule 15.247(d) of the band-edge items, the test plots were recorded in Annex A.
- Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150kHz ~ 30MHz	1.9 dB
Conducted emissions	-	2.5 dB
Radiated Emissions up to 1 GHz	9kHz ~ 30MHz	3.1 dB
	30MHz ~ 1GHz	5.5 dB
Radiated Emissions above 1 GHz	1GHz ~ 18GHz	5.1 dB
	18GHz ~ 40GHz	5.3 dB

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT (2.4GHz WLAN)

Product	2TX 11ax (WiFi6E) BW160 + BT/BLE Combo Card
Brand	MediaTek
Test Model	MT7922A22M
Status of EUT	Engineering sample
Power Supply Rating	3.3 Vdc from host equipment
Modulation Type	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM 256QAM for OFDM in 11ac mode and VHT20/40 in 2.4GHz mode 1024QAM for OFDMA in 11ax mode only
Modulation Technology	DSSS, OFDM, OFDMA
Transfer Rate	802.11b: up to 11 Mbps 802.11g: up to 54 Mbps 802.11n: up to 300 Mbps VHT20/40: up to 400 Mbps 802.11ax: up to 573.5 Mbps
Operating Frequency	2.412 ~ 2.472 GHz
Number of Channel	802.11b, 802.11g, 802.11n (HT20), VHT20, 802.11ax (HE20): 13 802.11n (HT40), VHT40, 802.11ax (HE40): 9
Output Power	769.216 mW
Antenna Type	Refer to Note
Antenna Connector	Refer to Note
Accessory Device	NA
Data Cable Supplied	NA

Note:

1. There are Bluetooth and WLAN (2.4GHz & 5GHz) technology used for the EUT.
2. Simultaneously transmission condition.

Condition	Technology	
1	WLAN (5GHz)	Bluetooth

Note: The emission of the simultaneous operation has been evaluated and no non-compliance was found.

3. The antennas provided to the EUT, please refer to the following table:

Antenna No.	RF Chain No.	Brand	Model	Antenna Net Gain (dBi)	Frequency Range (GHz)	Antenna Type	Connector Type	Cable Length (mm)
1	Chain0	PSA	RFMTA340718EMLB302	3.18 4.92	2.4~2.4835 5.15~5.85	PIFA	i-pex(MHF)	200
2	Chain1	PSA	RFMTA340718EMLB302	3.18 4.92	2.4~2.4835 5.15~5.85	PIFA	i-pex(MHF)	200
3	Chain0	PSA	RFMTA311020EMMB301	1.71 4.82 4.76 4.29 4.61 4.09	2.4~2.4835 5.15~5.85 5.925~6.425 6.425~6.525 6.525~6.875 6.875~7.125	PIFA	i-pex(MHF)	200
4	Chain1	PSA	RFMTA311020EMMB301	1.71 4.82 4.76 4.29 4.61 4.09	2.4~2.4835 5.15~5.85 5.925~6.425 6.425~6.525 6.525~6.875 6.875~7.125	PIFA	i-pex(MHF)	200

Note: Max. gain was selected for the final test.

4. The EUT incorporates a MIMO function:

2.4GHz Band		
MODULATION MODE	TX & RX CONFIGURATION	
802.11b	2TX	2RX
802.11g	2TX	2RX
802.11n (HT20)	2TX	2RX
802.11n (HT40)	2TX	2RX
VHT20	2TX	2RX
VHT40	2TX	2RX
802.11ax (HE20)	2TX	2RX
802.11ax (HE40)	2TX	2RX
802.11ax (RU26/52/106/242/484)	2TX	2RX

Note:

1. The modulation and bandwidth are similar for 802.11n mode for 20MHz (40MHz) and VHT mode for 20MHz (40MHz), therefore the manufacturer will control the power for 802.11n/VHT mode is the same as the 802.11ax or more lower than it and investigated worst case to representative mode in test report.
2. For Partial RU, after pre-tested, only the worse cases were chosen for final test and presented in the test report. (Final test mode refer section 3.2.1)

5. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

6. The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

3.2 Description of Test Modes

13 channels are provided for 802.11b, 802.11g, 802.11n (HT20), VHT20, 802.11ax (HE20):

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432	12	2467
6	2437	13	2472
7	2442		

9 channels are provided for 802.11n (HT40), VHT40, 802.11ax (HE40):

Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	8	2447
4	2427	9	2452
5	2432	10	2457
6	2437	11	2462
7	2442		

3.2.1 Test Mode Applicability and Tested Channel Detail

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE≥1G	RE<1G	PLC	APCM	
-	√	√	√	√	-

Where **RE≥1G**: Radiated Emission above 1GHz & Bandedge Measurement

RE<1G: Radiated Emission below 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

Note: The EUT's PIFA antenna had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **Z-place**.

Radiated Emission Test (Above 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, RU configurations and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate Parameter	RU Configuration
802.11b	1 to 13	1, 6, 11, 12, 13	DSSS	DBPSK	1Mb/s	-
802.11g	1 to 13	1, 6, 11, 12, 13	OFDM	BPSK	6Mb/s	-
802.11ax (HE20)	1 to 13	1, 6, 11, 12, 13	OFDMA	BPSK	MCS0	-
802.11ax (HE40)	3 to 11	3, 6, 9, 10, 11	OFDMA	BPSK	MCS0	-
802.11ax (RU26)	1 to 13	1, 11, 12, 13	OFDMA	BPSK	MCS0	26/0, 26/8, 26/8, 26/8
802.11ax (RU52)	1 to 13	6	OFDMA	BPSK	MCS0	52/37
802.11ax (RU106)	1 to 13	1, 11, 12, 13	OFDMA	BPSK	MCS0	106/53, 106/54, 106/54, 106/54

Radiated Emission Test (Below 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, RU configurations and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate Parameter
802.11b	1 to 13	1	DSSS	DBPSK	1Mb/s

Power Line Conducted Emission Test:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, RU configurations and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate Parameter
802.11b	1 to 13	1	DSSS	DBPSK	1Mb/s

Antenna Port Conducted Measurement:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, RU configurations and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE PARAMETER	RU Configuration
802.11b	1 to 13	1, 6, 11, 12, 13	DSSS	DBPSK	1Mb/s	-
802.11g	1 to 13	1, 6, 11, 12, 13	OFDM	BPSK	6Mb/s	-
VHT20 (output power only)	1 to 13	1, 6, 11, 12, 13	OFDM	BPSK	MCS0	-
VHT40 (output power only)	3 to 11	3, 6, 9, 10, 11	OFDM	BPSK	MCS0	-
802.11ax (HE20)	1 to 13	1, 6, 11, 12, 13	OFDMA	BPSK	MCS0	-
802.11ax (HE40)	3 to 11	3, 6, 9, 10, 11	OFDMA	BPSK	MCS0	-
802.11ax (RU26)	1 to 13	1, 11, 12, 13	OFDMA	BPSK	MCS0	26/0, 26/8, 26/8, 26/8
802.11ax (RU52)	1 to 13	6	OFDMA	BPSK	MCS0	52/37
802.11ax (RU106)	1 to 13	1, 11, 12, 13	OFDMA	BPSK	MCS0	106/53, 106/54, 106/54, 106/54

Test Condition:

Applicable to	Environmental Conditions	Input Power (System)	Tested By
RE≥1G	25deg. C, 66%RH, 25deg. C, 75%RH, 25deg. C, 65%RH	120Vac, 60Hz	Sampson Chen, Sampson Chen, Carter Lin
RE<1G	22deg. C, 62%RH	120Vac, 60Hz	Sampson Chen
PLC	25deg. C, 75%RH	120Vac, 60Hz	Sampson Chen
APCM	21deg. C, 60%RH	120Vac, 60Hz	Kevin.Ko

3.3 Duty Cycle of Test Signal

If duty cycle of test signal is $\geq 98\%$, duty factor is not required.
If duty cycle of test signal is $< 98\%$, duty factor shall be considered.


For Legacy mode:

802.11b: Duty cycle = 12.188 ms/12.442 ms = 0.98

802.11g: Duty cycle = 5.475 ms/5.825 ms = 0.94, Duty factor = $10 * \log(1/\text{Duty cycle}) = 0.27 \text{ dB}$

802.11ax (HE20): Duty cycle = 3.783 ms/4.263 ms = 0.887, Duty factor = $10 * \log(1/\text{Duty cycle}) = 0.52 \text{ dB}$

802.11ax (HE40): Duty cycle = 3.785 ms/4.26 ms = 0.888, Duty factor = $10 * \log(1/\text{Duty cycle}) = 0.51 \text{ dB}$



For RU mode:


Duty cycle of test signal is < 98%, duty factor shall be considered.

802.11ax (RU26): Duty cycle = 0.584 ms/0.791 ms = 0.738, Duty factor = $10 \cdot \log(1/\text{Duty cycle}) = 1.32 \text{ dB}$


802.11ax (RU52): Duty cycle = 0.5 ms/0.706 ms = 0.708, Duty factor = $10 \cdot \log(1/\text{Duty cycle}) = 1.5 \text{ dB}$

802.11ax (RU106): Duty cycle = 0.436 ms/0.642 ms = 0.679, Duty factor = $10 \cdot \log(1/\text{Duty cycle}) = 1.68 \text{ dB}$


802.11ax (RU26)



802.11ax (RU52)



802.11ax (RU106)



3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	Laptop	DELL	E5430	HYV4VY1	DoC	Provided by Lab
B.	Test Tool	MediaTek	MTK1849	NA	NA	Supplied by client
C.	Adapter	Dell	LA65NS2-01	NA	NA	Provided by Lab

Note:


1. All power cords of the above support units are non-shielded (1.8m).

ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	DC Cable	1	1.8	No	1	Provided by Lab
2.	AC Cable	1	1.8	No	0	Provided by Lab


Note: The core(s) is(are) originally attached to the cable(s).

3.4.1 Configuration of System under Test

For AC Power Conducted Emission test:



For Radiated Emission test:



3.5 General Description of Applied Standards and References

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards and references:

Test Standard:

FCC Part 15, Subpart C (15.247)

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

References Test Guidance:

KDB 558074 D01 15.247 Meas Guidance v05r02

KDB 662911 D01 Multiple Transmitter Output v02r01

All test items have been performed as a reference to the above KDB test guidance.

4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Note:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.1.2 Test Instruments

For Radiated Emission (Below 1GHz) test:

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver Agilent	N9038A	MY51210202	Dec. 01, 2020	Nov. 30, 2021
Pre-Amplifier EMCI	EMC001340	980142	May 25, 2020	May 24, 2021
Loop Antenna Electro-Metrics	EM-6879	264	Mar. 05, 2021	Mar. 04, 2022
RF Cable	5D-FB	LOOPCAB-001	Jan. 07, 2021	Jan. 06, 2022
RF Cable	5D-FB	LOOPCAB-002	Jan. 07, 2021	Jan. 06, 2022
Pre-Amplifier EMCI	EMC330N	980701	Mar. 10, 2021	Mar. 09, 2022
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-406	Nov. 06, 2020	Nov. 05, 2021
RF Cable	8D	966-4-1	Mar. 17, 2021	Mar. 16, 2022
RF Cable	8D	966-4-2	Mar. 17, 2021	Mar. 16, 2022
RF Cable	8D	966-4-3	Mar. 17, 2021	Mar. 16, 2022
Fixed attenuator Mini-Circuits	UNAT-5+	PAD-ATT5-03	Jan. 11, 2021	Jan. 10, 2022
Software	ADT_Radiated_V8.7.08	NA	NA	NA
Boresight Antenna Tower & Turn Table Max-Full	MF-7802BS	MF780208530	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in 966 Chamber No. 4.
3. Tested Date: Mar. 19, 2021

For Bandedge of legacy mode test: (Low & High channel)

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver Agilent	N9038A	MY51210202	Dec. 01, 2020	Nov. 30, 2021
Horn_Antenna SCHWARZBECK	BBHA 9120D	9120D-783	Nov. 22, 2020	Nov. 21, 2021
Pre-Amplifier EMCI	EMC 12630 SE	980638	Apr. 08, 2020	Apr. 07, 2021
RF Cable	EMC104-SM-SM-1200	160922	Dec. 25, 2020	Dec. 24, 2021
RF Cable	EMC104-SM-SM-2000	180502	Apr. 29, 2020	Apr. 28, 2021
RF Cable	EMC104-SM-SM-6000	180418	Apr. 29, 2020	Apr. 28, 2021
Pre-Amplifier EMCI	EMC184045SE	980387	Jan. 11, 2021	Jan. 10, 2022
Horn_Antenna SCHWARZBECK	BBHA 9170	BBHA9170519	Nov. 22, 2020	Nov. 21, 2021
RF Cable	EMC102-KM-KM-1200	160924	Jan. 11, 2021	Jan. 10, 2022
RF Cable	EMC-KM-KM-4000	200214	Mar. 10, 2021	Mar. 09, 2022
Software	ADT_Radiated_V8.7.08	NA	NA	NA
Boresight Antenna Tower & Turn Table Max-Full	MF-7802BS	MF780208530	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in 966 Chamber No. 4.
3. Tested Date: Mar. 12, 2021

For Radiated Emission (Above 1GHz) test:

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver Agilent	N9038A	MY51210202	Dec. 01, 2020	Nov. 30, 2021
Horn_Antenna SCHWARZBECK	BBHA 9120D	9120D-783	Nov. 22, 2020	Nov. 21, 2021
Pre-Amplifier EMCI	EMC 12630 SE	980638	Apr. 07, 2021	Apr. 06, 2022
RF Cable	EMC104-SM-SM-1200	160922	Dec. 25, 2020	Dec. 24, 2021
RF Cable	EMC104-SM-SM-2000	180502	Apr. 26, 2021	Apr. 25, 2022
RF Cable	EMC104-SM-SM-6000	180418	Apr. 26, 2021	Apr. 25, 2022
Pre-Amplifier EMCI	EMC184045SE	980387	Jan. 11, 2021	Jan. 10, 2022
Horn_Antenna SCHWARZBECK	BBHA 9170	BBHA9170519	Nov. 22, 2020	Nov. 21, 2021
RF Cable	EMC102-KM-KM-1200	160924	Jan. 11, 2021	Jan. 10, 2022
RF Cable	EMC-KM-KM-4000	200214	Mar. 10, 2021	Mar. 09, 2022
Software	ADT_Radiated_V8.7.08	NA	NA	NA
Boresight Antenna Tower & Turn Table Max-Full	MF-7802BS	MF780208530	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in 966 Chamber No. 4.
3. Tested Date: May 13 to 17, 2021

For other Bandedge test:

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver Agilent	N9038A	MY51210202	Dec. 01, 2020	Nov. 30, 2021
Horn_Antenna SCHWARZBECK	BBHA 9120D	9120D-783	Nov. 22, 2020	Nov. 21, 2021
Pre-Amplifier EMCI	EMC 12630 SE	980638	Apr. 07, 2021	Apr. 06, 2022
RF Cable	EMC104-SM-SM-1200	160922	Dec. 25, 2020	Dec. 24, 2021
RF Cable	EMC104-SM-SM-2000	180502	Apr. 29, 2020	Apr. 28, 2021
RF Cable	EMC104-SM-SM-6000	180418	Apr. 29, 2020	Apr. 28, 2021
Pre-Amplifier EMCI	EMC184045SE	980387	Jan. 11, 2021	Jan. 10, 2022
Horn_Antenna SCHWARZBECK	BBHA 9170	BBHA9170519	Nov. 22, 2020	Nov. 21, 2021
RF Cable	EMC102-KM-KM-1200	160924	Jan. 11, 2021	Jan. 10, 2022
RF Cable	EMC-KM-KM-4000	200214	Mar. 10, 2021	Mar. 09, 2022
Software	ADT_Radiated_V8.7.08	NA	NA	NA
Boresight Antenna Tower & Turn Table Max-Full	MF-7802BS	MF780208530	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in 966 Chamber No. 4.
3. Tested Date: Apr. 20, 2021

For other test items:

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Spectrum Analyzer R&S	FSV40	100964	May 29, 2020	May 28, 2021
Power meter Anritsu	ML2495A	1529002	July 22, 2020	July 21, 2021
Power sensor Anritsu	MA2411B	1339443	July 22, 2020	July 21, 2021
10dB Attenuator Woken	MDCS18N-10	MDCS18N-10-01	Apr. 13, 2021	Apr. 12, 2022
Software	ADT_RF Test Software V6.6.5.4	NA	NA	NA

NOTE:

1. The test was performed in Oven room 2.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
3. Tested Date: Apr. 22, 2021

4.1.3 Test Procedures

For Radiated emission below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 Deviation from Test Standard


No deviation.

4.1.5 Test Setup


For Radiated emission below 30MHz



For Radiated emission 30MHz to 1GHz



For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Conditions

- Placed the EUT on the testing table.
- Controlling software (MT7922 QAtool_7922_HQA_20210310) has been activated to set the EUT under transmission condition continuously at specific channel frequency.

4.1.7 Test Results

Above 1GHz Data:

RF Mode	TX 802.11b	Channel	CH 1 : 2412 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	59.4 PK	74.0	-14.6	2.66 H	60	63.7	-4.3
2	2390.00	53.3 AV	54.0	-0.7	2.66 H	60	57.6	-4.3
3	*2412.00	117.4 PK			2.66 H	60	121.7	-4.3
4	*2412.00	115.2 AV			2.66 H	60	119.5	-4.3
5	4824.00	48.6 PK	74.0	-25.4	2.67 H	271	48.1	0.5
6	4824.00	48.2 AV	54.0	-5.8	2.67 H	271	47.7	0.5
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	58.6 PK	74.0	-15.4	1.16 V	274	62.9	-4.3
2	2390.00	50.9 AV	54.0	-3.1	1.16 V	274	55.2	-4.3
3	*2412.00	114.9 PK			1.16 V	274	119.2	-4.3
4	*2412.00	112.9 AV			1.16 V	274	117.2	-4.3
5	4824.00	55.0 PK	74.0	-19.0	1.31 V	210	54.5	0.5
6	4824.00	53.3 AV	54.0	-0.7	1.31 V	210	52.8	0.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11b	Channel	CH 6 : 2437 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	60.7 PK	74.0	-13.3	2.69 H	64	65.0	-4.3
2	2390.00	49.5 AV	54.0	-4.5	2.69 H	64	53.8	-4.3
3	*2437.00	117.1 PK			2.69 H	64	121.4	-4.3
4	*2437.00	115.1 AV			2.69 H	64	119.4	-4.3
5	2483.50	61.0 PK	74.0	-13.0	2.69 H	64	65.4	-4.4
6	2483.50	50.0 AV	54.0	-4.0	2.69 H	64	54.4	-4.4
7	4874.00	49.2 PK	74.0	-24.8	2.62 H	277	48.7	0.5
8	4874.00	48.7 AV	54.0	-5.3	2.62 H	277	48.2	0.5
9	7311.00	45.8 PK	74.0	-28.2	1.82 H	52	39.0	6.8
10	7311.00	41.2 AV	54.0	-12.8	1.82 H	52	34.4	6.8

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	60.6 PK	74.0	-13.4	1.18 V	282	64.9	-4.3
2	2390.00	49.5 AV	54.0	-4.5	1.18 V	282	53.8	-4.3
3	*2437.00	115.2 PK			1.18 V	282	119.5	-4.3
4	*2437.00	113.4 AV			1.18 V	282	117.7	-4.3
5	2483.50	60.7 PK	74.0	-13.3	1.18 V	282	65.1	-4.4
6	2483.50	49.9 AV	54.0	-4.1	1.18 V	282	54.3	-4.4
7	4874.00	54.4 PK	74.0	-19.6	1.37 V	217	53.9	0.5
8	4874.00	53.9 AV	54.0	-0.1	1.37 V	217	53.4	0.5
9	7311.00	46.6 PK	74.0	-27.4	1.14 V	37	39.8	6.8
10	7311.00	41.5 AV	54.0	-12.5	1.14 V	37	34.7	6.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11b	Channel	CH 11 : 2462 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	115.8 PK			2.83 H	243	120.1	-4.3
2	*2462.00	113.9 AV			2.83 H	243	118.2	-4.3
3	2483.50	59.6 PK	74.0	-14.4	2.83 H	243	64.0	-4.4
4	2483.50	53.7 AV	54.0	-0.3	2.83 H	243	58.1	-4.4
5	4924.00	47.3 PK	74.0	-26.7	2.63 H	280	46.6	0.7
6	4924.00	46.0 AV	54.0	-8.0	2.63 H	280	45.3	0.7
7	7386.00	44.8 PK	74.0	-29.2	1.81 H	68	37.6	7.2
8	7386.00	40.2 AV	54.0	-13.8	1.81 H	68	33.0	7.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	112.9 PK			1.21 V	271	117.2	-4.3
2	*2462.00	110.9 AV			1.21 V	271	115.2	-4.3
3	2483.50	55.7 PK	74.0	-18.3	1.21 V	271	60.1	-4.4
4	2483.50	45.9 AV	54.0	-8.1	1.21 V	271	50.3	-4.4
5	4924.00	52.6 PK	74.0	-21.4	1.40 V	219	51.9	0.7
6	4924.00	52.3 AV	54.0	-1.7	1.40 V	219	51.6	0.7
7	7386.00	44.5 PK	74.0	-29.5	1.11 V	47	37.3	7.2
8	7386.00	40.1 AV	54.0	-13.9	1.11 V	47	32.9	7.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11b	Channel	CH 12 : 2467 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2467.00	112.9 PK			2.82 H	242	117.2	-4.3
2	*2467.00	111.0 AV			2.82 H	242	115.3	-4.3
3	2483.50	60.7 PK	74.0	-13.3	2.82 H	242	65.1	-4.4
4	2483.50	53.9 AV	54.0	-0.1	2.82 H	242	58.3	-4.4
5	4934.00	47.8 PK	74.0	-26.2	2.60 H	296	47.0	0.8
6	4934.00	46.4 AV	54.0	-7.6	2.60 H	296	45.6	0.8
7	7401.00	45.1 PK	74.0	-28.9	1.81 H	54	37.8	7.3
8	7401.00	40.5 AV	54.0	-13.5	1.81 H	54	33.2	7.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2467.00	109.7 PK			1.17 V	287	114.0	-4.3
2	*2467.00	108.5 AV			1.17 V	287	112.8	-4.3
3	2484.77	56.7 PK	74.0	-17.3	1.17 V	287	61.1	-4.4
4	2484.77	49.5 AV	54.0	-4.5	1.17 V	287	53.9	-4.4
5	4934.00	50.0 PK	74.0	-24.0	1.40 V	229	49.2	0.8
6	4934.00	49.8 AV	54.0	-4.2	1.40 V	229	49.0	0.8
7	7401.00	44.7 PK	74.0	-29.3	1.10 V	62	37.4	7.3
8	7401.00	40.4 AV	54.0	-13.6	1.10 V	62	33.1	7.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11b	Channel	CH 13 : 2472 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2472.00	111.5 PK			2.25 H	41	115.8	-4.3
2	*2472.00	109.2 AV			2.25 H	41	113.5	-4.3
3	2487.68	59.1 PK	74.0	-14.9	2.25 H	41	63.5	-4.4
4	2487.68	53.2 AV	54.0	-0.8	2.25 H	41	57.6	-4.4
5	4944.00	47.5 PK	74.0	-26.5	2.67 H	265	46.7	0.8
6	4944.00	46.3 AV	54.0	-7.7	2.67 H	265	45.5	0.8
7	7416.00	45.1 PK	74.0	-28.9	1.79 H	83	37.8	7.3
8	7416.00	40.3 AV	54.0	-13.7	1.79 H	83	33.0	7.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2472.00	108.7 PK			1.11 V	284	113.0	-4.3
2	*2472.00	106.5 AV			1.11 V	284	110.8	-4.3
3	2486.73	59.4 PK	74.0	-14.6	1.11 V	284	63.8	-4.4
4	2486.73	52.5 AV	54.0	-1.5	1.11 V	284	56.9	-4.4
5	4944.00	50.9 PK	74.0	-23.1	1.35 V	233	50.1	0.8
6	4944.00	50.1 AV	54.0	-3.9	1.35 V	233	49.3	0.8
7	7416.00	44.5 PK	74.0	-29.5	1.09 V	62	37.2	7.3
8	7416.00	40.5 AV	54.0	-13.5	1.09 V	62	33.2	7.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11g	Channel	CH 1 : 2412 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2388.96	66.3 PK	74.0	-7.7	2.38 H	69	70.5	-4.2
2	2388.96	53.1 AV	54.0	-0.9	2.38 H	69	57.3	-4.2
3	*2412.00	115.3 PK			2.38 H	69	119.6	-4.3
4	*2412.00	107.2 AV			2.38 H	69	111.5	-4.3
5	4824.00	47.3 PK	74.0	-26.7	2.62 H	261	46.8	0.5
6	4824.00	46.5 AV	54.0	-7.5	2.62 H	261	46.0	0.5
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2387.86	61.2 PK	74.0	-12.8	1.12 V	266	65.4	-4.2
2	2387.86	49.1 AV	54.0	-4.9	1.12 V	266	53.3	-4.2
3	*2412.00	112.8 PK			1.12 V	266	117.1	-4.3
4	*2412.00	104.7 AV			1.12 V	266	109.0	-4.3
5	4824.00	47.2 PK	74.0	-26.8	1.35 V	242	46.7	0.5
6	4824.00	46.2 AV	54.0	-7.8	1.35 V	242	45.7	0.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11g	Channel	CH 6 : 2437 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	64.4 PK	74.0	-9.6	2.48 H	229	68.7	-4.3
2	2390.00	53.1 AV	54.0	-0.9	2.48 H	229	57.4	-4.3
3	*2437.00	119.4 PK			2.48 H	229	123.7	-4.3
4	*2437.00	111.2 AV			2.48 H	229	115.5	-4.3
5	2483.50	68.2 PK	74.0	-5.8	2.48 H	229	72.6	-4.4
6	2483.50	50.4 AV	54.0	-3.6	2.48 H	229	54.8	-4.4
7	4874.00	47.3 PK	74.0	-26.7	2.66 H	256	46.8	0.5
8	4874.00	46.3 AV	54.0	-7.7	2.66 H	256	45.8	0.5
9	7311.00	45.3 PK	74.0	-28.7	1.76 H	82	38.5	6.8
10	7311.00	40.3 AV	54.0	-13.7	1.76 H	82	33.5	6.8

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	60.9 PK	74.0	-13.1	1.15 V	278	65.2	-4.3
2	2390.00	50.0 AV	54.0	-4.0	1.15 V	278	54.3	-4.3
3	*2437.00	116.8 PK			1.15 V	278	121.1	-4.3
4	*2437.00	108.3 AV			1.15 V	278	112.6	-4.3
5	2483.50	60.7 PK	74.0	-13.3	1.15 V	278	65.1	-4.4
6	2483.50	49.6 AV	54.0	-4.4	1.15 V	278	54.0	-4.4
7	4874.00	47.5 PK	74.0	-26.5	1.34 V	239	47.0	0.5
8	4874.00	46.4 AV	54.0	-7.6	1.34 V	239	45.9	0.5
9	7311.00	44.9 PK	74.0	-29.1	1.04 V	65	38.1	6.8
10	7311.00	40.1 AV	54.0	-13.9	1.04 V	65	33.3	6.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11g	Channel	CH 11 : 2462 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	116.2 PK			2.83 H	243	120.5	-4.3
2	*2462.00	107.2 AV			2.83 H	243	111.5	-4.3
3	2483.50	66.5 PK	74.0	-7.5	2.83 H	243	70.9	-4.4
4	2483.50	53.4 AV	54.0	-0.6	2.83 H	243	57.8	-4.4
5	4924.00	48.0 PK	74.0	-26.0	2.66 H	267	47.3	0.7
6	4924.00	46.6 AV	54.0	-7.4	2.66 H	267	45.9	0.7
7	7386.00	44.8 PK	74.0	-29.2	1.74 H	92	37.6	7.2
8	7386.00	40.2 AV	54.0	-13.8	1.74 H	92	33.0	7.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	113.2 PK			1.15 V	288	117.5	-4.3
2	*2462.00	104.8 AV			1.15 V	288	109.1	-4.3
3	2484.00	58.7 PK	74.0	-15.3	1.15 V	288	63.1	-4.4
4	2484.00	47.9 AV	54.0	-6.1	1.15 V	288	52.3	-4.4
5	4924.00	47.3 PK	74.0	-26.7	1.34 V	246	46.6	0.7
6	4924.00	46.2 AV	54.0	-7.8	1.34 V	246	45.5	0.7
7	7386.00	44.6 PK	74.0	-29.4	1.10 V	69	37.4	7.2
8	7386.00	39.8 AV	54.0	-14.2	1.10 V	69	32.6	7.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11g	Channel	CH 12 : 2467 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2467.00	114.4 PK			2.78 H	243	118.7	-4.3
2	*2467.00	105.1 AV			2.78 H	243	109.4	-4.3
3	2483.50	65.0 PK	74.0	-9.0	2.78 H	243	69.4	-4.4
4	2483.50	53.8 AV	54.0	-0.2	2.78 H	243	58.2	-4.4
5	4934.00	47.3 PK	74.0	-26.7	2.62 H	269	46.5	0.8
6	4934.00	46.2 AV	54.0	-7.8	2.62 H	269	45.4	0.8
7	7401.00	45.4 PK	74.0	-28.6	1.74 H	77	38.1	7.3
8	7401.00	40.7 AV	54.0	-13.3	1.74 H	77	33.4	7.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2467.00	110.2 PK			1.11 V	279	114.5	-4.3
2	*2467.00	102.9 AV			1.11 V	279	107.2	-4.3
3	2483.50	60.3 PK	74.0	-13.7	1.11 V	279	64.7	-4.4
4	2483.50	49.6 AV	54.0	-4.4	1.11 V	279	54.0	-4.4
5	4934.00	47.7 PK	74.0	-26.3	1.40 V	231	46.9	0.8
6	4934.00	46.7 AV	54.0	-7.3	1.40 V	231	45.9	0.8
7	7401.00	44.8 PK	74.0	-29.2	1.05 V	53	37.5	7.3
8	7401.00	39.7 AV	54.0	-14.3	1.05 V	53	32.4	7.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11g	Channel	CH 13 : 2472 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2472.00	109.6 PK			2.59 H	67	113.9	-4.3
2	*2472.00	101.5 AV			2.59 H	67	105.8	-4.3
3	2485.18	63.9 PK	74.0	-10.1	2.59 H	67	68.3	-4.4
4	2485.18	53.6 AV	54.0	-0.4	2.59 H	67	58.0	-4.4
5	4944.00	47.2 PK	74.0	-26.8	2.71 H	279	46.4	0.8
6	4944.00	46.2 AV	54.0	-7.8	2.71 H	279	45.4	0.8
7	7416.00	44.8 PK	74.0	-29.2	1.83 H	89	37.5	7.3
8	7416.00	40.2 AV	54.0	-13.8	1.83 H	89	32.9	7.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2472.00	106.6 PK			1.10 V	270	110.9	-4.3
2	*2472.00	98.9 AV			1.10 V	270	103.2	-4.3
3	2484.23	61.9 PK	74.0	-12.1	1.10 V	270	66.3	-4.4
4	2484.23	52.1 AV	54.0	-1.9	1.10 V	270	56.5	-4.4
5	4944.00	47.4 PK	74.0	-26.6	1.34 V	253	46.6	0.8
6	4944.00	46.6 AV	54.0	-7.4	1.34 V	253	45.8	0.8
7	7416.00	44.1 PK	74.0	-29.9	1.07 V	58	36.8	7.3
8	7416.00	39.6 AV	54.0	-14.4	1.07 V	58	32.3	7.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11ax (HE20)	Channel	CH 1 : 2412 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	66.7 PK	74.0	-7.3	2.87 H	250	71.0	-4.3
2	2390.00	53.7 AV	54.0	-0.3	2.87 H	250	58.0	-4.3
3	*2412.00	118.0 PK			2.87 H	250	122.3	-4.3
4	*2412.00	107.4 AV			2.87 H	250	111.7	-4.3
5	4824.00	47.4 PK	74.0	-26.6	2.70 H	266	46.9	0.5
6	4824.00	46.3 AV	54.0	-7.7	2.70 H	266	45.8	0.5
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	63.3 PK	74.0	-10.7	1.17 V	285	67.6	-4.3
2	2390.00	50.6 AV	54.0	-3.4	1.17 V	285	54.9	-4.3
3	*2412.00	116.1 PK			1.17 V	285	120.4	-4.3
4	*2412.00	104.6 AV			1.17 V	285	108.9	-4.3
5	4824.00	47.8 PK	74.0	-26.2	1.39 V	246	47.3	0.5
6	4824.00	46.9 AV	54.0	-7.1	1.39 V	246	46.4	0.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11ax (HE20)	Channel	CH 6 : 2437 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	66.0 PK	74.0	-8.0	2.77 H	250	70.3	-4.3
2	2390.00	53.3 AV	54.0	-0.7	2.77 H	250	57.6	-4.3
3	*2437.00	119.7 PK			2.77 H	250	124.0	-4.3
4	*2437.00	109.9 AV			2.77 H	250	114.2	-4.3
5	2483.50	67.6 PK	74.0	-6.4	2.77 H	250	72.0	-4.4
6	2483.50	51.5 AV	54.0	-2.5	2.77 H	250	55.9	-4.4
7	4874.00	47.6 PK	74.0	-26.4	2.70 H	261	47.1	0.5
8	4874.00	46.6 AV	54.0	-7.4	2.70 H	261	46.1	0.5
9	7311.00	45.3 PK	74.0	-28.7	1.75 H	92	38.5	6.8
10	7311.00	40.5 AV	54.0	-13.5	1.75 H	92	33.7	6.8

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	61.2 PK	74.0	-12.8	1.14 V	291	65.5	-4.3
2	2390.00	50.1 AV	54.0	-3.9	1.14 V	291	54.4	-4.3
3	*2437.00	116.3 PK			1.14 V	291	120.6	-4.3
4	*2437.00	106.4 AV			1.14 V	291	110.7	-4.3
5	2483.50	61.1 PK	74.0	-12.9	1.14 V	291	65.5	-4.4
6	2483.50	49.9 AV	54.0	-4.1	1.14 V	291	54.3	-4.4
7	4874.00	47.9 PK	74.0	-26.1	1.40 V	240	47.4	0.5
8	4874.00	46.8 AV	54.0	-7.2	1.40 V	240	46.3	0.5
9	7311.00	45.1 PK	74.0	-28.9	1.05 V	62	38.3	6.8
10	7311.00	40.5 AV	54.0	-13.5	1.05 V	62	33.7	6.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11ax (HE20)	Channel	CH 11 : 2462 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	116.1 PK			2.84 H	244	120.4	-4.3
2	*2462.00	106.4 AV			2.84 H	244	110.7	-4.3
3	2483.50	65.3 PK	74.0	-8.7	2.84 H	244	69.7	-4.4
4	2483.50	53.7 AV	54.0	-0.3	2.84 H	244	58.1	-4.4
5	4924.00	47.2 PK	74.0	-26.8	2.66 H	268	46.5	0.7
6	4924.00	46.1 AV	54.0	-7.9	2.66 H	268	45.4	0.7
7	7386.00	45.3 PK	74.0	-28.7	1.73 H	76	38.1	7.2
8	7386.00	40.7 AV	54.0	-13.3	1.73 H	76	33.5	7.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	114.1 PK			1.13 V	301	118.4	-4.3
2	*2462.00	103.3 AV			1.13 V	301	107.6	-4.3
3	2483.50	64.5 PK	74.0	-9.5	1.13 V	301	68.9	-4.4
4	2483.50	50.7 AV	54.0	-3.3	1.13 V	301	55.1	-4.4
5	4924.00	48.1 PK	74.0	-25.9	1.33 V	225	47.4	0.7
6	4924.00	46.8 AV	54.0	-7.2	1.33 V	225	46.1	0.7
7	7386.00	44.1 PK	74.0	-29.9	1.00 V	50	36.9	7.2
8	7386.00	39.6 AV	54.0	-14.4	1.00 V	50	32.4	7.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11ax (HE20)	Channel	CH 12 : 2467 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2467.00	114.3 PK			2.82 H	236	118.6	-4.3
2	*2467.00	104.5 AV			2.82 H	236	108.8	-4.3
3	2485.86	63.6 PK	74.0	-10.4	2.82 H	236	68.0	-4.4
4	2485.86	53.7 AV	54.0	-0.3	2.82 H	236	58.1	-4.4
5	4934.00	46.7 PK	74.0	-27.3	2.61 H	257	45.9	0.8
6	4934.00	45.8 AV	54.0	-8.2	2.61 H	257	45.0	0.8
7	7401.00	45.6 PK	74.0	-28.4	1.81 H	71	38.3	7.3
8	7401.00	40.6 AV	54.0	-13.4	1.81 H	71	33.3	7.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2467.00	111.9 PK			1.20 V	299	116.2	-4.3
2	*2467.00	100.7 AV			1.20 V	299	105.0	-4.3
3	2487.21	61.5 PK	74.0	-12.5	1.20 V	299	65.9	-4.4
4	2487.21	49.3 AV	54.0	-4.7	1.20 V	299	53.7	-4.4
5	4934.00	47.4 PK	74.0	-26.6	1.35 V	228	46.6	0.8
6	4934.00	46.6 AV	54.0	-7.4	1.35 V	228	45.8	0.8
7	7401.00	44.6 PK	74.0	-29.4	1.09 V	59	37.3	7.3
8	7401.00	39.6 AV	54.0	-14.4	1.09 V	59	32.3	7.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11ax (HE20)	Channel	CH 13 : 2472 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2472.00	106.2 PK			2.78 H	245	110.5	-4.3
2	*2472.00	96.4 AV			2.78 H	245	100.7	-4.3
3	2484.28	63.3 PK	74.0	-10.7	2.78 H	245	67.7	-4.4
4	2484.28	53.9 AV	54.0	-0.1	2.78 H	245	58.3	-4.4
5	4944.00	48.0 PK	74.0	-26.0	2.61 H	257	47.2	0.8
6	4944.00	46.7 AV	54.0	-7.3	2.61 H	257	45.9	0.8
7	7416.00	45.7 PK	74.0	-28.3	1.74 H	83	38.4	7.3
8	7416.00	40.6 AV	54.0	-13.4	1.74 H	83	33.3	7.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2472.00	104.1 PK			1.20 V	288	108.4	-4.3
2	*2472.00	94.3 AV			1.20 V	288	98.6	-4.3
3	2484.96	60.8 PK	74.0	-13.2	1.20 V	288	65.2	-4.4
4	2484.96	49.8 AV	54.0	-4.2	1.20 V	288	54.2	-4.4
5	4944.00	48.1 PK	74.0	-25.9	1.29 V	254	47.3	0.8
6	4944.00	46.9 AV	54.0	-7.1	1.29 V	254	46.1	0.8
7	7416.00	45.2 PK	74.0	-28.8	1.06 V	69	37.9	7.3
8	7416.00	40.2 AV	54.0	-13.8	1.06 V	69	32.9	7.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11ax (HE40)	Channel	CH 3 : 2422 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2389.44	62.9 PK	74.0	-11.1	2.42 H	63	67.1	-4.2
2	2389.44	53.4 AV	54.0	-0.6	2.42 H	63	57.6	-4.2
3	*2422.00	111.9 PK			2.42 H	63	116.2	-4.3
4	*2422.00	101.2 AV			2.42 H	63	105.5	-4.3
5	4844.00	48.0 PK	74.0	-26.0	2.60 H	266	47.5	0.5
6	4844.00	46.6 AV	54.0	-7.4	2.60 H	266	46.1	0.5
7	7266.00	45.7 PK	74.0	-28.3	1.80 H	79	39.0	6.7
8	7266.00	40.8 AV	54.0	-13.2	1.80 H	79	34.1	6.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2388.75	60.8 PK	74.0	-13.2	1.12 V	300	65.0	-4.2
2	2388.75	49.5 AV	54.0	-4.5	1.12 V	300	53.7	-4.2
3	*2422.00	109.8 PK			1.12 V	300	114.1	-4.3
4	*2422.00	98.3 AV			1.12 V	300	102.6	-4.3
5	4844.00	47.0 PK	74.0	-27.0	1.39 V	242	46.5	0.5
6	4844.00	46.0 AV	54.0	-8.0	1.39 V	242	45.5	0.5
7	7266.00	44.9 PK	74.0	-29.1	1.04 V	67	38.2	6.7
8	7266.00	40.1 AV	54.0	-13.9	1.04 V	67	33.4	6.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11ax (HE40)	Channel	CH 6 : 2437 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	65.1 PK	74.0	-8.9	2.89 H	245	69.4	-4.3
2	2390.00	52.1 AV	54.0	-1.9	2.89 H	245	56.4	-4.3
3	*2437.00	116.7 PK			2.89 H	245	121.0	-4.3
4	*2437.00	105.5 AV			2.89 H	245	109.8	-4.3
5	2483.50	66.9 PK	74.0	-7.1	2.89 H	245	71.3	-4.4
6	2483.50	53.2 AV	54.0	-0.8	2.89 H	245	57.6	-4.4
7	4874.00	48.5 PK	74.0	-25.5	2.58 H	252	48.0	0.5
8	4874.00	47.0 AV	54.0	-7.0	2.58 H	252	46.5	0.5
9	7311.00	44.9 PK	74.0	-29.1	1.74 H	75	38.1	6.8
10	7311.00	40.1 AV	54.0	-13.9	1.74 H	75	33.3	6.8

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	61.4 PK	74.0	-12.6	1.15 V	279	65.7	-4.3
2	2390.00	49.9 AV	54.0	-4.1	1.15 V	279	54.2	-4.3
3	*2437.00	113.8 PK			1.15 V	279	118.1	-4.3
4	*2437.00	102.5 AV			1.15 V	279	106.8	-4.3
5	2483.50	61.0 PK	74.0	-13.0	1.15 V	279	65.4	-4.4
6	2483.50	49.9 AV	54.0	-4.1	1.15 V	279	54.3	-4.4
7	4874.00	47.7 PK	74.0	-26.3	1.32 V	227	47.2	0.5
8	4874.00	46.4 AV	54.0	-7.6	1.32 V	227	45.9	0.5
9	7311.00	44.6 PK	74.0	-29.4	1.05 V	53	37.8	6.8
10	7311.00	40.0 AV	54.0	-14.0	1.05 V	53	33.2	6.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11ax (HE40)	Channel	CH 9 : 2452 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2452.00	113.5 PK			2.83 H	244	117.8	-4.3
2	*2452.00	103.0 AV			2.83 H	244	107.3	-4.3
3	2484.27	63.9 PK	74.0	-10.1	2.83 H	244	68.3	-4.4
4	2484.27	53.6 AV	54.0	-0.4	2.83 H	244	58.0	-4.4
5	4904.00	48.2 PK	74.0	-25.8	2.64 H	251	47.6	0.6
6	4904.00	46.9 AV	54.0	-7.1	2.64 H	251	46.3	0.6
7	7356.00	45.8 PK	74.0	-28.2	1.78 H	92	38.8	7.0
8	7356.00	41.0 AV	54.0	-13.0	1.78 H	92	34.0	7.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2452.00	110.7 PK			1.15 V	274	115.0	-4.3
2	*2452.00	97.9 AV			1.15 V	274	102.2	-4.3
3	2489.60	59.8 PK	74.0	-14.2	1.15 V	274	64.2	-4.4
4	2489.60	48.6 AV	54.0	-5.4	1.15 V	274	53.0	-4.4
5	4904.00	47.7 PK	74.0	-26.3	1.37 V	245	47.1	0.6
6	4904.00	46.6 AV	54.0	-7.4	1.37 V	245	46.0	0.6
7	7356.00	45.2 PK	74.0	-28.8	1.08 V	71	38.2	7.0
8	7356.00	40.3 AV	54.0	-13.7	1.08 V	71	33.3	7.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11ax (HE40)	Channel	CH 10 : 2457 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2457.00	111.0 PK			2.87 H	245	115.3	-4.3
2	*2457.00	100.9 AV			2.87 H	245	105.2	-4.3
3	2483.50	62.7 PK	74.0	-11.3	2.87 H	245	67.1	-4.4
4	2483.50	53.4 AV	54.0	-0.6	2.87 H	245	57.8	-4.4
5	4914.00	48.1 PK	74.0	-25.9	2.65 H	265	47.4	0.7
6	4914.00	47.0 AV	54.0	-7.0	2.65 H	265	46.3	0.7
7	7371.00	45.8 PK	74.0	-28.2	1.73 H	99	38.7	7.1
8	7371.00	40.7 AV	54.0	-13.3	1.73 H	99	33.6	7.1
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2457.00	108.2 PK			1.20 V	275	112.5	-4.3
2	*2457.00	95.6 AV			1.20 V	275	99.9	-4.3
3	2487.18	57.5 PK	74.0	-16.5	1.20 V	275	61.9	-4.4
4	2487.18	47.8 AV	54.0	-6.2	1.20 V	275	52.2	-4.4
5	4914.00	47.4 PK	74.0	-26.6	1.30 V	223	46.7	0.7
6	4914.00	46.0 AV	54.0	-8.0	1.30 V	223	45.3	0.7
7	7371.00	45.3 PK	74.0	-28.7	1.00 V	66	38.2	7.1
8	7371.00	40.4 AV	54.0	-13.6	1.00 V	66	33.3	7.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11ax (HE40)	Channel	CH 11 : 2462 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	107.0 PK			2.83 H	64	111.3	-4.3
2	*2462.00	97.3 AV			2.83 H	64	101.6	-4.3
3	2483.50	62.5 PK	74.0	-11.5	2.83 H	64	66.9	-4.4
4	2483.50	53.3 AV	54.0	-0.7	2.83 H	64	57.7	-4.4
5	4924.00	48.2 PK	74.0	-25.8	2.56 H	248	47.5	0.7
6	4924.00	46.9 AV	54.0	-7.1	2.56 H	248	46.2	0.7
7	7386.00	45.9 PK	74.0	-28.1	1.74 H	89	38.7	7.2
8	7386.00	40.9 AV	54.0	-13.1	1.74 H	89	33.7	7.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	106.4 PK			1.13 V	295	110.7	-4.3
2	*2462.00	93.8 AV			1.13 V	295	98.1	-4.3
3	2484.69	60.3 PK	74.0	-13.7	1.13 V	295	64.7	-4.4
4	2484.69	50.0 AV	54.0	-4.0	1.13 V	295	54.4	-4.4
5	4924.00	47.7 PK	74.0	-26.3	1.29 V	224	47.0	0.7
6	4924.00	46.4 AV	54.0	-7.6	1.29 V	224	45.7	0.7
7	7386.00	45.4 PK	74.0	-28.6	1.09 V	79	38.2	7.2
8	7386.00	40.4 AV	54.0	-13.6	1.09 V	79	33.2	7.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

802.11ax (RU26)

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 1 : 2412 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2368.45	70.5 PK	74.0	-3.5	2.70 H	245	74.7	-4.2
2	2368.45	53.6 AV	54.0	-0.4	2.70 H	245	57.8	-4.2
3	*2412.00	124.7 PK			2.70 H	245	129.0	-4.3
4	*2412.00	116.1 AV			2.70 H	245	120.4	-4.3
5	4824.00	49.3 PK	74.0	-24.7	1.17 H	77	48.8	0.5
6	4824.00	43.7 AV	54.0	-10.3	1.17 H	77	43.2	0.5
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2370.60	67.8 PK	74.0	-6.2	1.19 V	275	72.0	-4.2
2	2370.60	51.5 AV	54.0	-2.5	1.19 V	275	55.7	-4.2
3	*2412.00	121.5 PK			1.19 V	275	125.8	-4.3
4	*2412.00	113.6 AV			1.19 V	275	117.9	-4.3
5	4824.00	50.6 PK	74.0	-23.4	2.12 V	136	50.1	0.5
6	4824.00	44.6 AV	54.0	-9.4	2.12 V	136	44.1	0.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 11 : 2462 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	124.4 PK			2.65 H	239	128.7	-4.3
2	*2462.00	115.5 AV			2.65 H	239	119.8	-4.3
3	2486.10	69.7 PK	74.0	-4.3	2.65 H	239	74.1	-4.4
4	2486.10	53.0 AV	54.0	-1.0	2.65 H	239	57.4	-4.4
5	2486.90	66.0 PK	74.0	-8.0	2.65 H	239	70.4	-4.4
6	2486.90	53.6 AV	54.0	-0.4	2.65 H	239	58.0	-4.4
7	4924.00	51.1 PK	74.0	-22.9	1.22 H	85	50.4	0.7
8	4924.00	44.3 AV	54.0	-9.7	1.22 H	85	43.6	0.7
9	7386.00	50.7 PK	74.0	-23.3	3.00 H	275	43.5	7.2
10	7386.00	40.5 AV	54.0	-13.5	3.00 H	275	33.3	7.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	121.1 PK			1.00 V	285	125.4	-4.3
2	*2462.00	113.4 AV			1.00 V	285	117.7	-4.3
3	2486.10	62.5 PK	74.0	-11.5	1.00 V	285	66.9	-4.4
4	2486.10	48.6 AV	54.0	-5.4	1.00 V	285	53.0	-4.4
5	2487.30	60.2 PK	74.0	-13.8	1.00 V	285	64.6	-4.4
6	2487.30	50.6 AV	54.0	-3.4	1.00 V	285	55.0	-4.4
7	4924.00	51.1 PK	74.0	-22.9	2.11 V	152	50.4	0.7
8	4924.00	45.0 AV	54.0	-9.0	2.11 V	152	44.3	0.7
9	7386.00	49.7 PK	74.0	-24.3	2.03 V	149	42.5	7.2
10	7386.00	39.5 AV	54.0	-14.5	2.03 V	149	32.3	7.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 12 : 2467 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2467.00	121.6 PK			2.73 H	251	125.9	-4.3
2	*2467.00	113.4 AV			2.73 H	251	117.7	-4.3
3	2483.50	67.6 PK	74.0	-6.4	2.73 H	251	72.0	-4.4
4	2483.50	53.0 AV	54.0	-1.0	2.73 H	251	57.4	-4.4
5	2484.55	66.5 PK	74.0	-7.5	2.73 H	251	70.9	-4.4
6	2484.55	53.5 AV	54.0	-0.5	2.73 H	251	57.9	-4.4
7	4934.00	48.4 PK	74.0	-25.6	1.20 H	89	47.6	0.8
8	4934.00	42.8 AV	54.0	-11.2	1.20 H	89	42.0	0.8
9	7401.00	49.9 PK	74.0	-24.1	2.95 H	276	42.6	7.3
10	7401.00	39.7 AV	54.0	-14.3	2.95 H	276	32.4	7.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2467.00	118.2 PK			1.10 V	278	122.5	-4.3
2	*2467.00	110.2 AV			1.10 V	278	114.5	-4.3
3	2484.20	60.7 PK	74.0	-13.3	1.10 V	278	65.1	-4.4
4	2484.20	48.6 AV	54.0	-5.4	1.10 V	278	53.0	-4.4
5	2486.07	62.5 PK	74.0	-11.5	1.10 V	278	66.9	-4.4
6	2486.07	47.3 AV	54.0	-6.7	1.10 V	278	51.7	-4.4
7	4934.00	48.7 PK	74.0	-25.3	2.19 V	143	47.9	0.8
8	4934.00	43.8 AV	54.0	-10.2	2.19 V	143	43.0	0.8
9	7401.00	48.8 PK	74.0	-25.2	2.02 V	134	41.5	7.3
10	7401.00	38.7 AV	54.0	-15.3	2.02 V	134	31.4	7.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 13 : 2472 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2472.00	116.5 PK			2.61 H	255	120.8	-4.3
2	*2472.00	106.5 AV			2.61 H	255	110.8	-4.3
3	2483.50	73.9 PK	74.0	-0.1	2.61 H	255	78.3	-4.4
4	2483.50	53.7 AV	54.0	-0.3	2.61 H	255	58.1	-4.4
5	4944.00	40.8 PK	74.0	-33.2	1.24 H	95	40.0	0.8
6	4944.00	35.3 AV	54.0	-18.7	1.24 H	95	34.5	0.8
7	7416.00	42.3 PK	74.0	-31.7	2.96 H	271	35.0	7.3
8	7416.00	35.7 AV	54.0	-18.3	2.96 H	271	28.4	7.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2472.00	113.7 PK			1.17 V	272	118.0	-4.3
2	*2472.00	103.7 AV			1.17 V	272	108.0	-4.3
3	2483.50	73.8 PK	74.0	-0.2	1.17 V	272	78.2	-4.4
4	2483.50	53.3 AV	54.0	-0.7	1.17 V	272	57.7	-4.4
5	4944.00	41.8 PK	74.0	-32.2	2.20 V	132	41.0	0.8
6	4944.00	36.3 AV	54.0	-17.7	2.20 V	132	35.5	0.8
7	7416.00	41.1 PK	74.0	-32.9	2.03 V	154	33.8	7.3
8	7416.00	34.7 AV	54.0	-19.3	2.03 V	154	27.4	7.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

802.11ax (RU52)

ABOVE 1GHz DATA

RF Mode	TX 20MHz Preamble 802.11ax (RU52)	Channel	CH 6 : 2437 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	73.2 PK	74.0	-0.8	2.65 H	248	77.5	-4.3
2	2390.00	53.9 AV	54.0	-0.1	2.65 H	248	58.2	-4.3
3	*2437.00	124.5 PK			2.65 H	248	128.8	-4.3
4	*2437.00	116.8 AV			2.65 H	248	121.1	-4.3
5	2483.50	62.2 PK	74.0	-11.8	2.65 H	248	66.6	-4.4
6	2483.50	47.0 AV	54.0	-7.0	2.65 H	248	51.4	-4.4
7	4874.00	51.8 PK	74.0	-22.2	1.23 H	81	51.3	0.5
8	4874.00	45.1 AV	54.0	-8.9	1.23 H	81	44.6	0.5
9	7311.00	51.5 PK	74.0	-22.5	2.91 H	279	44.7	6.8
10	7311.00	41.0 AV	54.0	-13.0	2.91 H	279	34.2	6.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	65.7 PK	74.0	-8.3	1.21 V	272	70.0	-4.3
2	2390.00	50.0 AV	54.0	-4.0	1.21 V	272	54.3	-4.3
3	*2437.00	121.8 PK			1.21 V	272	126.1	-4.3
4	*2437.00	113.0 AV			1.21 V	272	117.3	-4.3
5	2483.50	62.7 PK	74.0	-11.3	1.21 V	272	67.1	-4.4
6	2483.50	47.4 AV	54.0	-6.6	1.21 V	272	51.8	-4.4
7	4874.00	51.4 PK	74.0	-22.6	2.13 V	126	50.9	0.5
8	4874.00	45.2 AV	54.0	-8.8	2.13 V	126	44.7	0.5
9	7311.00	49.7 PK	74.0	-24.3	2.04 V	145	42.9	6.8
10	7311.00	39.8 AV	54.0	-14.2	2.04 V	145	33.0	6.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.

802.11ax (RU106)

RF Mode	TX 20MHz Preamble 802.11ax (RU106)	Channel	CH 1 : 2412 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2389.47	73.7 PK	74.0	-0.3	2.68 H	240	77.9	-4.2
2	2389.47	53.1 AV	54.0	-0.9	2.68 H	240	57.3	-4.2
3	*2412.00	119.3 PK			2.68 H	240	123.6	-4.3
4	*2412.00	110.5 AV			2.68 H	240	114.8	-4.3
5	4824.00	51.4 PK	74.0	-22.6	1.25 H	70	50.9	0.5
6	4824.00	44.8 AV	54.0	-9.2	1.25 H	70	44.3	0.5
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	70.5 PK	74.0	-3.5	1.01 V	280	74.8	-4.3
2	2390.00	52.8 AV	54.0	-1.2	1.01 V	280	57.1	-4.3
3	*2412.00	115.9 PK			1.01 V	280	120.2	-4.3
4	*2412.00	107.4 AV			1.01 V	280	111.7	-4.3
5	4824.00	51.3 PK	74.0	-22.7	2.12 V	155	50.8	0.5
6	4824.00	45.0 AV	54.0	-9.0	2.12 V	155	44.5	0.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 20MHz Preamble 802.11ax (RU106)	Channel	CH 11 : 2462 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	119.5 PK			2.53 H	235	123.8	-4.3
2	*2462.00	109.9 AV			2.53 H	235	114.2	-4.3
3	2484.36	71.4 PK	74.0	-2.6	2.53 H	235	75.8	-4.4
4	2484.36	53.7 AV	54.0	-0.3	2.53 H	235	58.1	-4.4
5	4924.00	51.7 PK	74.0	-22.3	1.18 H	79	51.0	0.7
6	4924.00	44.8 AV	54.0	-9.2	1.18 H	79	44.1	0.7
7	7386.00	51.1 PK	74.0	-22.9	2.98 H	269	43.9	7.2
8	7386.00	40.9 AV	54.0	-13.1	2.98 H	269	33.7	7.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	115.3 PK			1.21 V	270	119.6	-4.3
2	*2462.00	106.9 AV			1.21 V	270	111.2	-4.3
3	2485.23	65.7 PK	74.0	-8.3	1.21 V	270	70.1	-4.4
4	2485.23	48.6 AV	54.0	-5.4	1.21 V	270	53.0	-4.4
5	4924.00	51.4 PK	74.0	-22.6	2.08 V	149	50.7	0.7
6	4924.00	45.0 AV	54.0	-9.0	2.08 V	149	44.3	0.7
7	7386.00	49.7 PK	74.0	-24.3	2.04 V	165	42.5	7.2
8	7386.00	39.6 AV	54.0	-14.4	2.04 V	165	32.4	7.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 20MHz Preamble 802.11ax (RU106)	Channel	CH 12 : 2467 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2467.00	116.3 PK			2.70 H	250	120.6	-4.3
2	*2467.00	107.1 AV			2.70 H	250	111.4	-4.3
3	2483.50	69.3 PK	74.0	-4.7	2.70 H	250	73.7	-4.4
4	2483.50	53.7 AV	54.0	-0.3	2.70 H	250	58.1	-4.4
5	4934.00	49.0 PK	74.0	-25.0	1.14 H	105	48.2	0.8
6	4934.00	43.1 AV	54.0	-10.9	1.14 H	105	42.3	0.8
7	7401.00	50.1 PK	74.0	-23.9	2.95 H	277	42.8	7.3
8	7401.00	39.6 AV	54.0	-14.4	2.95 H	277	32.3	7.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2467.00	113.2 PK			1.16 V	269	117.5	-4.3
2	*2467.00	104.9 AV			1.16 V	269	109.2	-4.3
3	2483.50	61.5 PK	74.0	-12.5	1.16 V	269	65.9	-4.4
4	2483.50	52.4 AV	54.0	-1.6	1.16 V	269	56.8	-4.4
5	2486.03	67.3 PK	74.0	-6.7	1.16 V	269	71.7	-4.4
6	2486.03	49.7 AV	54.0	-4.3	1.16 V	269	54.1	-4.4
7	4934.00	48.7 PK	74.0	-25.3	2.15 V	140	47.9	0.8
8	4934.00	43.5 AV	54.0	-10.5	2.15 V	140	42.7	0.8
9	7401.00	48.6 PK	74.0	-25.4	2.01 V	135	41.3	7.3
10	7401.00	38.7 AV	54.0	-15.3	2.01 V	135	31.4	7.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 20MHz Preamble 802.11ax (RU106)	Channel	CH 13 : 2472 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2472.00	111.8 PK			2.63 H	256	116.1	-4.3
2	*2472.00	102.5 AV			2.63 H	256	106.8	-4.3
3	2483.50	73.1 PK	74.0	-0.9	2.63 H	256	77.5	-4.4
4	2483.50	53.8 AV	54.0	-0.2	2.63 H	256	58.2	-4.4
5	4944.00	40.8 PK	74.0	-33.2	1.26 H	84	40.0	0.8
6	4944.00	35.1 AV	54.0	-18.9	1.26 H	84	34.3	0.8
7	7416.00	42.4 PK	74.0	-31.6	2.93 H	284	35.1	7.3
8	7416.00	35.8 AV	54.0	-18.2	2.93 H	284	28.5	7.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2472.00	108.6 PK			1.21 V	273	112.9	-4.3
2	*2472.00	101.8 AV			1.21 V	273	106.1	-4.3
3	2483.50	68.8 PK	74.0	-5.2	1.21 V	273	73.2	-4.4
4	2483.50	50.5 AV	54.0	-3.5	1.21 V	273	54.9	-4.4
5	4944.00	41.5 PK	74.0	-32.5	2.24 V	118	40.7	0.8
6	4944.00	35.9 AV	54.0	-18.1	2.24 V	118	35.1	0.8
7	7416.00	40.6 PK	74.0	-33.4	2.06 V	167	33.3	7.3
8	7416.00	34.2 AV	54.0	-19.8	2.06 V	167	26.9	7.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.


Below 1GHz Data:

RF Mode	TX 802.11b	Channel	CH 1 : 2412 MHz
Frequency Range	9kHz ~ 1GHz	Detector Function	Quasi-Peak (QP)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	165.33	38.4 QP	43.5	-5.1	2.00 H	257	50.7	-12.3
2	197.37	40.5 QP	43.5	-3.0	1.50 H	60	55.6	-15.1
3	240.05	42.8 QP	46.0	-3.2	1.50 H	294	55.9	-13.1
4	298.97	43.0 QP	46.0	-3.0	2.00 H	317	53.7	-10.7
5	697.69	42.8 QP	46.0	-3.2	1.00 H	274	43.3	-0.5
6	720.96	42.5 QP	46.0	-3.5	1.50 H	211	42.7	-0.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.




RF Mode	TX 802.11b	Channel	CH 1 : 2412 MHz
Frequency Range	9kHz ~ 1GHz	Detector Function	Quasi-Peak (QP)

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	31.97	33.4 QP	40.0	-6.6	1.00 V	325	46.9	-13.5
2	167.43	38.9 QP	43.5	-4.6	1.50 V	350	51.1	-12.2
3	299.31	41.5 QP	46.0	-4.5	2.00 V	321	52.2	-10.7
4	697.97	40.6 QP	46.0	-5.4	1.50 V	255	41.1	-0.5
5	720.31	40.5 QP	46.0	-5.5	1.00 V	307	40.7	-0.2
6	897.37	41.2 QP	46.0	-4.8	1.50 V	287	37.7	3.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.



4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2.2 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver R&S	ESCS 30	847124/029	Oct. 20, 2020	Oct. 19, 2021
Line-Impedance Stabilization Network (for EUT) R&S	ESH3-Z5	848773/004	Oct. 27, 2020	Oct. 26, 2021
50 ohms Terminator	50	3	Oct. 26, 2020	Oct. 25, 2021
RF Cable	5D-FB	COCCAB-001	Sep. 26, 2020	Sep. 25, 2021
Fixed attenuator EMCI	STI02-2200-10	005	Aug. 29, 2020	Aug. 28, 2021
Software BVADT	BVADT_Cond_V7.3.7.4	NA	NA	NA

Note:

1. The calibration interval of the above test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Conduction 1.
- 3 Tested Date: Mar. 20, 2021

4.2.3 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

4.2.4 Deviation from Test Standard

No deviation.

4.2.5 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT Operating Conditions

Same as 4.1.6.


4.2.7 Test Results

RF Mode	TX 802.11b	Channel	CH 1 : 2412 MHz
Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15911	9.95	34.49	16.73	44.44	26.68	65.51	55.51	-21.07	-28.83
2	0.18275	9.96	38.74	27.56	48.70	37.52	64.36	54.36	-15.66	-16.84
3	0.22487	9.97	30.85	19.09	40.82	29.06	62.64	52.64	-21.82	-23.58
4	0.44498	9.99	25.37	16.47	35.36	26.46	56.97	46.97	-21.61	-20.51
5	1.45453	10.05	16.40	11.18	26.45	21.23	56.00	46.00	-29.55	-24.77
6	13.95813	10.77	15.74	8.67	26.51	19.44	60.00	50.00	-33.49	-30.56

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




RF Mode	TX 802.11b	Channel	CH 1 : 2412 MHz
Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15105	9.92	42.37	23.66	52.29	33.58	65.94	55.94	-13.65	-22.36
2	0.16803	9.93	35.86	13.50	45.79	23.43	65.06	55.06	-19.27	-31.63
3	0.22572	9.95	30.67	16.79	40.62	26.74	62.61	52.61	-21.99	-25.87
4	0.27567	9.95	26.57	19.70	36.52	29.65	60.95	50.95	-24.43	-21.30
5	0.45258	9.96	25.62	18.74	35.58	28.70	56.83	46.83	-21.25	-18.13
6	1.44501	10.02	11.49	4.37	21.51	14.39	56.00	46.00	-34.49	-31.61

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




4.3 6dB Bandwidth Measurement

4.3.1 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 Test Setup



4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.3.4 Test Procedure

- a. Set resolution bandwidth (RBW) = 100kHz
- b. Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
- c. Trace mode = max hold.
- d. Sweep = auto couple.
- e. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

4.3.5 Deviation from Test Standard

No deviation.

4.3.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually.

4.3.7 Test Result

802.11b

Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1		
1	2412	8.13	8.12	0.5	Pass
6	2437	8.07	8.6	0.5	Pass
11	2462	8.11	8.13	0.5	Pass
12	2467	8.11	8.1	0.5	Pass
13	2472	8.1	8.09	0.5	Pass

802.11g

Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1		
1	2412	16.36	16.4	0.5	Pass
6	2437	16.06	16.3	0.5	Pass
11	2462	16.05	16.31	0.5	Pass
12	2467	15.84	16.36	0.5	Pass
13	2472	16.36	16.38	0.5	Pass

802.11ax (HE20)

Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1		
1	2412	18.96	18.93	0.5	Pass
6	2437	18.83	18.48	0.5	Pass
11	2462	18.58	18.31	0.5	Pass
12	2467	18.72	18.71	0.5	Pass
13	2472	18.89	18.82	0.5	Pass

802.11ax (HE40)

Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1		
3	2422	36.72	35.31	0.5	Pass
6	2437	36.86	35.24	0.5	Pass
9	2452	36.32	35.21	0.5	Pass
10	2457	37.51	36.86	0.5	Pass
11	2462	37.06	35.83	0.5	Pass

802.11ax (RU26)

Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1		
1	2412	2.15	2.14	0.5	Pass
11	2462	2.16	2.17	0.5	Pass
12	2467	2.14	2.12	0.5	Pass
13	2472	2.1	2.15	0.5	Pass

802.11ax (RU52)


Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1		
6	2437	17.16	14.61	0.5	Pass

802.11ax (RU106)


Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1		
1	2412	17.21	17.18	0.5	Pass
11	2462	17.22	17.2	0.5	Pass
12	2467	17.22	17.19	0.5	Pass
13	2472	17.21	17.17	0.5	Pass

Spectrum Plot of Worst Value


802.11b_Chain 0 / CH6




802.11g_Chain 0 / CH12



802.11ax (HE20)_Chain 1 / CH11




802.11ax (HE40)_Chain 1 / CH9




Spectrum Plot of Worst Value


802.11ax (RU26)_Chain 0 / CH13



802.11ax (RU52)_Chain 1 / CH6



802.11ax (RU106)_Chain 1 / CH13



4.4 Conducted Output Power Measurement

4.4.1 Limits of Conducted Output Power Measurement

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

Per KDB 662911 D01 Multiple Transmitter Output Method of conducted output power measurement on IEEE 802.11 devices,


Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$;

Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any N_{ANT} ;

Array Gain = $5 \log(N_{ANT}/N_{SS})$ dB or 3 dB, whichever is less for 20-MHz channel widths with $N_{ANT} \geq 5$.

For power measurements on all other devices: Array Gain = $10 \log(N_{ANT}/N_{SS})$ dB.

4.4.2 Test Setup



4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.4.4 Test Procedures

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

Average power sensor was used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

4.4.5 Deviation from Test Standard

No deviation.

4.4.6 EUT Operating Conditions

Same as Item 4.3.6.

4.4.7 Test Results

FOR PEAK POWER

802.11b

Chan.	Chan. Freq. (MHz)	Peak Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
1	2412	23.85	24.26	509.347	27.07	30	Pass
6	2437	23.69	24.24	499.344	26.98	30	Pass
11	2462	22.32	23.23	380.986	25.81	30	Pass
12	2467	21.07	21.91	283.177	24.52	30	Pass
13	2472	19.05	20.07	181.977	22.60	30	Pass

802.11g

Chan.	Chan. Freq. (MHz)	Peak Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
1	2412	23.76	24.20	500.711	27.00	30	Pass
6	2437	25.59	25.44	712.188	28.53	30	Pass
11	2462	22.99	23.65	430.807	26.34	30	Pass
12	2467	19.57	20.21	195.528	22.91	30	Pass
13	2472	17.19	18.20	118.429	20.73	30	Pass

VHT20

Chan.	Chan. Freq. (MHz)	Peak Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
1	2412	23.52	23.69	458.789	26.62	30	Pass
6	2437	25.42	25.36	691.895	28.40	30	Pass
11	2462	22.50	23.42	397.614	25.99	30	Pass
12	2467	19.04	19.86	176.996	22.48	30	Pass
13	2472	15.39	15.92	73.678	18.67	30	Pass

VHT40

Chan.	Chan. Freq. (MHz)	Peak Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
3	2422	20.46	20.88	233.635	23.69	30	Pass
6	2437	22.90	23.37	412.255	26.15	30	Pass
9	2452	20.04	20.82	221.707	23.46	30	Pass
10	2457	17.74	18.52	130.551	21.16	30	Pass
11	2462	15.80	16.68	84.578	19.27	30	Pass

802.11ax (HE20)

Chan.	Chan. Freq. (MHz)	Peak Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
1	2412	23.81	23.93	487.609	26.88	30	Pass
6	2437	25.89	25.81	769.216	28.86	30	Pass
11	2462	22.80	23.69	424.43	26.28	30	Pass
12	2467	19.31	20.10	187.639	22.73	30	Pass
13	2472	16.12	16.70	87.7	19.43	30	Pass

802.11ax (HE40)

Chan.	Chan. Freq. (MHz)	Peak Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
3	2422	20.73	21.12	247.724	23.94	30	Pass
6	2437	23.15	23.66	438.812	26.42	30	Pass
9	2452	20.27	21.06	234.058	23.69	30	Pass
10	2457	17.99	18.81	138.983	21.43	30	Pass
11	2462	16.08	16.89	89.416	19.51	30	Pass

802.11ax (RU26)

Chan.	Chan. Freq. (MHz)	Peak Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
1	2412	25.82	25.81	763.01	28.83	30	Pass
11	2462	25.76	25.51	732.335	28.65	30	Pass
12	2467	21.83	22.43	327.39	25.15	30	Pass
13	2472	19.92	20.27	204.589	23.11	30	Pass

802.11ax (RU52)

Chan.	Chan. Freq. (MHz)	Peak Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
6	2437	25.85	25.76	761.296	28.82	30	Pass

802.11ax (RU106)

Chan.	Chan. Freq. (MHz)	Peak Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
1	2412	25.71	25.63	737.986	28.68	30	Pass
11	2462	25.49	25.56	713.747	28.54	30	Pass
12	2467	22.95	24.04	450.755	26.54	30	Pass
13	2472	20.61	20.70	232.57	23.67	30	Pass

FOR AVERAGE POWER

802.11b

Chan.	Chan. Freq. (MHz)	Average Power (dBm)		Total Average Power (mW)	Total Average Power (dBm)
		Chain 0	Chain 1		
1	2412	21.62	22.04	305.167	24.85
6	2437	21.49	22.00	299.418	24.76
11	2462	19.94	20.82	219.409	23.41
12	2467	18.62	19.51	162.109	22.10
13	2472	16.78	17.73	106.936	20.29

802.11g

Chan.	Chan. Freq. (MHz)	Average Power (dBm)		Total Average Power (mW)	Total Average Power (dBm)
		Chain 0	Chain 1		
1	2412	18.01	18.24	129.922	21.14
6	2437	20.57	20.97	239.051	23.78
11	2462	17.93	18.81	138.12	21.40
12	2467	14.44	15.20	60.91	17.85
13	2472	11.61	12.30	31.47	14.98

VHT20

Chan.	Chan. Freq. (MHz)	Average Power (dBm)		Total Average Power (mW)	Total Average Power (dBm)
		Chain 0	Chain 1		
1	2412	17.50	17.63	114.177	20.58
6	2437	20.06	20.43	211.799	23.26
11	2462	17.24	18.12	117.83	20.71
12	2467	13.91	14.62	53.577	17.29
13	2472	9.50	9.71	18.267	12.62

VHT40

Chan.	Chan. Freq. (MHz)	Average Power (dBm)		Total Average Power (mW)	Total Average Power (dBm)
		Chain 0	Chain 1		
3	2422	14.82	15.21	63.528	18.03
6	2437	17.82	18.27	127.677	21.06
9	2452	14.75	15.49	65.254	18.15
10	2457	12.33	13.12	37.612	15.75
11	2462	9.88	10.75	21.612	13.35

802.11ax (HE20)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)		Total Average Power (mW)	Total Average Power (dBm)
		Chain 0	Chain 1		
1	2412	17.72	17.83	119.83	20.79
6	2437	20.33	20.72	225.927	23.54
11	2462	17.49	18.34	124.339	20.95
12	2467	14.18	14.85	56.731	17.54
13	2472	9.95	10.46	21.003	13.22

802.11ax (HE40)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)		Total Average Power (mW)	Total Average Power (dBm)
		Chain 0	Chain 1		
3	2422	15.11	15.48	67.752	18.31
6	2437	18.08	18.50	135.063	21.31
9	2452	15.05	15.73	69.4	18.41
10	2457	12.54	13.40	39.825	16.00
11	2462	10.11	11.01	22.875	13.59

802.11ax (RU26)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)		Total Average Power (mW)	Total Average Power (dBm)
		Chain 0	Chain 1		
1	2412	17.16	17.46	107.718	20.32
11	2462	17.25	17.88	114.465	20.59
12	2467	14.47	15.13	60.573	17.82
13	2472	11.54	12.21	30.89	14.90

802.11ax (RU52)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)		Total Average Power (mW)	Total Average Power (dBm)
		Chain 0	Chain 1		
6	2437	20.45	20.80	231.144	23.64

802.11ax (RU106)


Chan.	Chan. Freq. (MHz)	Average Power (dBm)		Total Average Power (mW)	Total Average Power (dBm)
		Chain 0	Chain 1		
1	2412	17.69	18.03	122.282	20.87
11	2462	17.67	18.47	128.786	21.10
12	2467	14.87	15.39	65.284	18.15
13	2472	11.85	12.68	33.846	15.30

4.5 Power Spectral Density Measurement

4.5.1 Limits of Power Spectral Density Measurement

The Maximum of Power Spectral Density Measurement is 8dBm in any 3 kHz.

4.5.2 Test Setup



4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.5.4 Test Procedure

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set the VBW $\geq 3 \times \text{RBW}$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.

4.5.5 Deviation from Test Standard

No deviation.

4.5.6 EUT Operating Condition

Same as Item 4.3.6

4.5.7 Test Results

802.11b

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)		Total PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Pass / Fail
		Chain 0	Chain 1			
1	2412	-0.72	-0.16	2.58	7.81	Pass
6	2437	0.21	-0.89	2.70	7.81	Pass
11	2462	-2.20	-1.08	1.41	7.81	Pass
12	2467	-3.06	-2.55	0.21	7.81	Pass
13	2472	-3.41	-3.60	-0.49	7.81	Pass

Note: The directional gain = 3.18 dBi + 10log(2) = 6.19 dBi > 6dBi , so the power density limit shall be reduced to 8-(6.19-6) = 7.81 dBm.

802.11g

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)		Total PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Pass / Fail
		Chain 0	Chain 1			
1	2412	-5.99	-7.26	-3.57	7.81	Pass
6	2437	-3.67	-4.03	-0.84	7.81	Pass
11	2462	-6.78	-6.37	-3.56	7.81	Pass
12	2467	-9.35	-10.29	-6.78	7.81	Pass
13	2472	-13.18	-13.09	-10.12	7.81	Pass

Note: The directional gain = 3.18 dBi + 10log(2) = 6.19 dBi > 6dBi , so the power density limit shall be reduced to 8-(6.19-6) = 7.81 dBm.

802.11ax (HE20)

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)		Total PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Pass / Fail
		Chain 0	Chain 1			
1	2412	-8.33	-8.32	-5.32	7.81	Pass
6	2437	-4.97	-6.34	-2.59	7.81	Pass
11	2462	-8.62	-8.06	-5.32	7.81	Pass
12	2467	-12.34	-11.84	-9.07	7.81	Pass
13	2472	-15.33	-15.20	-12.25	7.81	Pass

Note: The directional gain = 3.18 dBi + 10log(2) = 6.19 dBi > 6dBi , so the power density limit shall be reduced to 8-(6.19-6) = 7.81 dBm.

802.11ax (HE40)

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)		Total PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Pass / Fail
		Chain 0	Chain 1			
3	2422	-13.02	-13.68	-10.33	7.81	Pass
6	2437	-9.75	-9.88	-6.80	7.81	Pass
9	2452	-12.72	-12.45	-9.57	7.81	Pass
10	2457	-15.79	-14.47	-12.07	7.81	Pass
11	2462	-17.60	-18.18	-14.87	7.81	Pass

Note: The directional gain = 3.18 dBi + 10log(2) = 6.19 dBi > 6dBi , so the power density limit shall be reduced to 8-(6.19-6) = 7.81 dBm.

802.11ax (RU26)

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)		Total PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Pass / Fail
		Chain 0	Chain 1			
1	2412	1.69	1.19	4.46	7.81	Pass
11	2462	1.12	1.77	4.47	7.81	Pass
12	2467	-2.06	-1.36	1.31	7.81	Pass
13	2472	-4.51	-5.39	-1.92	7.81	Pass

Note: The directional gain = $3.18 \text{ dBi} + 10\log(2) = 6.19 \text{ dBi} > 6\text{dBi}$, so the power density limit shall be reduced to $8-(6.19-6) = 7.81 \text{ dBm}$.

802.11ax (RU52)

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)		Total PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Pass / Fail
		Chain 0	Chain 1			
6	2437	0.84	0.28	3.58	7.81	Pass

Note: The directional gain = $3.18 \text{ dBi} + 10\log(2) = 6.19 \text{ dBi} > 6\text{dBi}$, so the power density limit shall be reduced to $8-(6.19-6) = 7.81 \text{ dBm}$.


802.11ax (RU106)

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)		Total PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Pass / Fail
		Chain 0	Chain 1			
1	2412	-4.05	-4.86	-1.43	7.81	Pass
11	2462	-5.34	-5.64	-2.48	7.81	Pass
12	2467	-7.98	-8.23	-5.09	7.81	Pass
13	2472	-10.66	-11.12	-7.87	7.81	Pass


Note: The directional gain = $3.18 \text{ dBi} + 10\log(2) = 6.19 \text{ dBi} > 6\text{dBi}$, so the power density limit shall be reduced to $8-(6.19-6) = 7.81 \text{ dBm}$.

Spectrum Plot of Worst Value


802.11b_Chain 0 / CH6




802.11g_Chain 0 / CH6




802.11ax (HE20)_Chain 0 / CH6




802.11ax (HE40)_Chain 0 / CH6




802.11ax (RU26)_Chain 1 / CH11



802.11ax (RU52)_Chain 0 / CH6



802.11ax (RU106)_Chain 0 / CH1




4.6 Conducted Out of Band Emission Measurement

4.6.1 Limits of Conducted Out of Band Emission Measurement

Below 20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 Test Setup



4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.6.4 Test Procedure

MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW $\geq$ 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW $\geq$ 300 kHz.
3. Detector = peak.
4. Sweep = auto couple.
5. Trace Mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum amplitude level.

4.6.5 Deviation from Test Standard

No deviation.

4.6.6 EUT Operating Condition


Same as Item 4.3.6

4.6.7 Test Results


The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.

802.11b
Chain 0


CH 1




CH 6





CH 11





CH 12





CH 13



CH 1 Band edge





CH 12 Band edge





Chain 1



CH 1





CH 6





CH 11





CH 12





CH 13



CH 1 Band edge




CH 12 Band edge




802.11g
Chain 0


CH 1




CH 6





CH 11





CH 12





CH 13





CH 1 Band edge



CH 12 Band edge




CH 13 Band edge




Chain 1


CH 1




CH 6





CH 11





CH 12





CH 13



CH 1 Band edge




CH 12 Band edge




802.11ax (HE20)

Chain 0


CH 1




CH 6





CH 11





CH 12





CH 13



CH 1 Band edge




CH 12 Band edge




Chain 1


CH 1




CH 6




CH 11




CH 12




CH 13




CH 1 Band edge



CH 12 Band edge




CH 13 Band edge




802.11ax (HE40)

Chain 0


CH 3




CH 6





CH 9





CH 10





CH 11



CH 3 Band edge




CH 10 Band edge




Chain 1


CH 3




CH 6





CH 9





CH 10





CH 11



CH 3 Band edge




CH 10 Band edge




802.11ax (RU26)

Chain 0


CH 1




CH 11




CH 12




CH 13




CH 1 Band edge




CH 11 Band edge



CH 12 Band edge




CH 13 Band edge




Chain 1


CH 1




CH 11




CH 12




CH 13




CH 1 Band edge




CH 11 Band edge



CH 12 Band edge




CH 13 Band edge



802.11ax (RU52)


Chain 0

CH 6



Chain 1


CH 6




802.11ax (RU106)

Chain 0


CH 1




CH 11




CH 12




CH 13




CH 1 Band edge




CH 11 Band edge



CH 12 Band edge




CH 13 Band edge




Chain 1


CH 1




CH 11




CH 12




CH 13




CH 1 Band edge




CH 11 Band edge



CH 12 Band edge




CH 13 Band edge





5 Pictures of Test Arrangements


Please refer to the attached file (Test Setup Photo).


Annex A - Band-Edge Measurement













802.11ax (HE20) Channel 12


Horizontal (Peak)




Horizontal (Average)



Vertical (Peak)




Vertical (Average)




802.11ax (HE20) Channel 13


Horizontal (Peak)




Horizontal (Average)



Vertical (Peak)




Vertical (Average)




802.11ax (HE40) Channel 3


Horizontal (Peak)




Horizontal (Average)



Vertical (Peak)




Vertical (Average)




802.11ax (HE40) Channel 9


Horizontal (Peak)




Horizontal (Average)




Vertical (Peak)




Vertical (Average)






802.11ax (RU26)




20MHz Preamble 802.11ax (RU26) Channel 12


Horizontal (Peak)




Horizontal (Average)



Vertical (Peak)




Vertical (Average)




20MHz Preamble 802.11ax (RU26) Channel 13


Horizontal (Peak)




Horizontal (Average)




Vertical (Peak)



Vertical (Average)




802.11ax (RU106)




20MHz Preamble 802.11ax (RU106) Channel 12


Horizontal (Peak)




Horizontal (Average)



Vertical (Peak)




Vertical (Average)




20MHz Preamble 802.11ax (RU106) Channel 13


Horizontal (Peak)




Horizontal (Average)



Vertical (Peak)



Vertical (Average)



Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---