


双频胶棒天线测试报告


胶棒天线图片：



小胶棒天线 S11 数据：

频率（MHz）	2400	2450	2500	5150	5350	5700	5900
ReturnLoss	-27.36	-17.27	-13.04	-5.19	-8.83	-12.56	-26.25
VSWR	1.16	1.42	1.68	3.50	2.17	1.53	1.14









小胶棒天线增益效率和方向图：

Fq (MHz)	2400	2410	2420	2430	2440	2450	2460	2470	2480	2490	2500
Gain (dBi)	1.40	1.78	2.02	2.15	2.40	2.53	2.48	2.29	1.95	1.72	1.75
Efficie (%)	57.2	59.1	59.7	60.6	62.1	64.4	66.2	67.1	65.6	64.2	63.2
Fq (MHz)	5150	5200	5250	5300	5350		5700	5750	5800	5850	
Gain (dBi)	1.07	1.83	1.87	1.28	2.11		2.93	3.16	2.67	2.27	
Efficie (%)	50.2	50.6	51.5	50.8	51.4		57.3	58.2	54.1	52.7	

2450MHz 方向图:




5250MHz 方向图:




5800MHz 方向图:

5800.0MHz H+V, Eff: 54.1%


Back View



5800.0MHz Total(E1-XZ), Max= 2.36dBi



5800.0MHz Total(E2-YZ), Max= 1.76dBi



Total(H-XY), Max= 2.66dBi, CirD=2.28

