

FCC ID: 2BFDF-G50U

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot \sqrt{f(\text{GHz})} \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

BT

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	-2.13	0.61	-2±1	-1	0.79	<5	0.24622	3.00	YES
	2.441	-2.3	0.59	-2±1	-1	0.79	<5	0.24821	3.00	YES
	2.480	-3.09	0.49	-3±1	-2	0.63	<5	0.19873	3.00	YES
π/4-DQPSK	2.402	0.52	1.13	0±1	1	1.26	<5	0.39023	3.00	YES
	2.441	0.15	1.04	0±1	1	1.26	<5	0.39338	3.00	YES
	2.480	-0.86	0.82	0±1	1	1.26	<5	0.39651	3.00	YES
8-DPSK	2.402	1.11	1.29	1±1	2	1.58	<5	0.49127	3.00	YES
	2.441	0.67	1.17	1±1	2	1.58	<5	0.49524	3.00	YES
	2.480	-0.29	0.94	0±1	1	1.26	<5	0.39651	3.00	YES

Conclusion:

For the max result : $0.49524 \leq 3.0$ for 1g SAR, SAR is not required.

Signature:



Date: 3/13/2025

NAME AND TITLE (Please print or type): Alex li /Manager

COMPANY (Please print or type): No. 24 Xinfu East Road, Xiangshan Community, Xinqiao Street, Baoan District, Shenzhen, Guangdong, People's Republic of China.