



FCC TEST REPORT
FCC ID:2BFKA-L11

Report Number.....: ZHT-240313020E

Date of Test.....: Mar. 13, 2024 to Mar. 26, 2024

Date of issue.....: Mar. 26, 2024

Test Result.....: PASS

Testing Laboratory.....: Guangdong Zhonghan Testing Technology Co., Ltd.

Address: Room 104, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

Applicant's name: Shenzhen Fulaifu Electronic Technology Co., Ltd.

Address: Room A714-15, Floor 7, Block A, Block A, Block B, Jiangsu Building.No.6013, Yitian Road, Fuxin Community, Lianhua Street, FutianDistrict, Shenzhen

Manufacturer's name: Shenzhen Fulaifu Electronic Technology Co., Ltd.

Address: Room A714-15, Floor 7, Block A, Block A, Block B, Jiangsu Building.No.6013, Yitian Road, Fuxin Community, Lianhua Street, FutianDistrict, Shenzhen

Test specification:

Standard.....: FCC CFR Title 47 Part 15 Subpart C Section 15.247

Test procedure.....: KDB558074 D01 15.247 Meas Guidance v05r02
ANSI C63.10:2013

Non-standard test method: N/A

This device described above has been tested by ZHT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of ZHT, this document may be altered or revised by ZHT, personal only, and shall be noted in the revision of the document.

Product name.....: Low power battery camera

Trademark: /

Model/Type reference.....: L11

Model Difference: /

Ratings.....: Input: DC 5V by USB or DC 3.7V by battery



Testing procedure and testing location:

Testing Laboratory.....: **Guangdong Zhonghan Testing Technology Co., Ltd.**

Address.....: Room 104, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

Tested by (name + signature).....: Leon Li

Leon Li

Reviewer (name + signature).....: Baret Wu

Baret Wu

Approved (name + signature).....: Levi Lee

Levi Lee



Table of Contents

	Page
1. VERSION	5
2. SUMMARY OF TEST RESULTS	6
2.1 TEST FACILITY	7
2.2 MEASUREMENT UNCERTAINTY	7
3. GENERAL INFORMATION	8
3.1 GENERAL DESCRIPTION OF EUT	8
3.2 DESCRIPTION OF TEST MODES	9
3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	9
3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	10
3.5EQUIPMENTS LIST FOR ALL TEST ITEMS	11
4. EMC EMISSION TEST	13
4.1 CONDUCTED EMISSION MEASUREMENT	13
4.1.1 POWER LINE CONDUCTED EMISSION Limits	13
4.1.2 TEST PROCEDURE	13
4.1.3 DEVIATION FROM TEST STANDARD	13
4.1.4 TEST SETUP	14
4.1.5 EUT OPERATING CONDITIONS	14
4.2 RADIATED EMISSION MEASUREMENT	17
4.2.1 RADIATED EMISSION LIMITS	17
4.2.2 TEST PROCEDURE	17
4.2.3 DEVIATION FROM TEST STANDARD	18
4.2.4 TEST SETUP	18
4.2.5 EUT OPERATING CONDITIONS	19
4.2.6 TEST RESULTS	19
5. RADIATED BAND EMISSIONMEASUREMENT	24
5.1 TEST REQUIREMENT:	24
5.2 TEST PROCEDURE	24
5.3 DEVIATION FROM TEST STANDARD	24
5.4 TEST SETUP	25
5.5 EUT OPERATING CONDITIONS	25
5.6 TEST RESULT	26
6. POWER SPECTRAL DENSITY TEST	28
6.1 APPLIED PROCEDURES / LIMIT	28
6.2 TEST PROCEDURE	28
6.3 DEVIATION FROM STANDARD	28
6.4 TEST SETUP	28
6.5 EUT OPERATION CONDITIONS	28



- 6.6 TEST RESULT29
- 7. CHANNEL BANDWIDTH 30
 - 7.1 APPLIED PROCEDURES / LIMIT 30
 - 7.2 TEST PROCEDURE 30
 - 7.3 DEVIATION FROM STANDARD 30
 - 7.4 TEST SETUP30
 - 7.5 EUT OPERATION CONDITIONS 30
 - 7.6 TEST RESULT31
- 8. OUTPUT POWER TEST 32
 - 8.1 APPLIED PROCEDURES/LIMIT 32
 - 8.2 TEST PROCEDURE 32
 - 8.3 DEVIATION FROM STANDARD 32
 - 8.4 TEST SETUP32
 - 8.5 EUT OPERATION CONDITIONS 32
 - 8.6 TEST RESULT32
- 9. CONDUCTED BAND EDGE AND SPURIOUS EMISSION 33
 - 9.1 APPLICABLE STANDARD 33
 - 9.2 TEST PROCEDURE 33
 - 9.3 DEVIATION FROM STANDARD 33
 - 9.4 TEST SETUP 33
 - 9.5 EUT OPERATION CONDITIONS 33
 - 9.6 TEST RESULTS 33
- 10. ANTENNA REQUIREMENT 34
- 11. APPENDIX WIFI 35
 - 11.1 DUTY CYCLE 35
 - 11.2 MAXIMUM PEAK CONDUCTED OUTPUT POWER 42
 - 11.3 -6DB BANDWIDTH 49
 - 11.4 OCCUPIED CHANNEL BANDWIDTH 56
 - 11.5 MAXIMUM AVERAGE SPECTRAL DENSITY LEVEL 63
 - 11.6 BAND EDGE 70
 - 11.7 CONDUCTED RF SPURIOUS EMISSION 79
- 12. TEST SETUP PHOTO 92
- 13. EUT CONSTRUCTIONAL DETAILS92



1. VERSION

Report No.	Version	Description	Approved
ZHT-240313020E	Rev.01	Initial issue of report	Mar. 26, 2024



2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Result	Remark
FCC part 15.203/15.247 (b)(4)	Antenna requirement	PASS	
FCC part 15.207	AC Power Line Conducted Emission	PASS	
FCC part 15.247 (b)(3)	Conducted Peak Output Power	PASS	
FCC part 15.247 (a)(2)	Channel Bandwidth	PASS	
FCC part 15.247 (e)	Power Spectral Density	PASS	
FCC part 15.247(d)	Band Edge	PASS	
FCC part 15.205/15.209	Spurious Emission	PASS	

NOTE:

(1) " N/A" denotes test is not applicable in this Test Report



2.1 TEST FACILITY

Guangdong Zhonghan Testing Technology Co., Ltd.

Add. : Room 104, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District Shenzhen, Guangdong, China

FCC Registration Number:255941

Designation Number: CN0325

IC Registered No.: 29832

CAB identifier: CN0143

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF conducted power	$\pm 0.16\text{dB}$
3	Conducted spurious emissions	$\pm 0.21\text{dB}$
4	All radiated emissions (9k-30MHz)	$\pm 4.68\text{dB}$
5	All radiated emissions (<1G)	$\pm 4.68\text{dB}$
6	All radiated emissions (>1G)	$\pm 4.89\text{dB}$
7	Temperature	$\pm 0.5^\circ\text{C}$
8	Humidity	$\pm 2\%$
9	Occupied Bandwidth	$\pm 4.96\%$



3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Product Name:	Low power battery camera
Test Model No.:	L11
Hardware Version:	V1.0
Software Version:	V1.0
Sample(s) Status:	Engineer sample
Channel numbers:	802.11b/802.11g /802.11n(HT20):11/ 802.11n(HT40):7
Operation Frequency:	802.11b/802.11g /802.11n(HT20): 2412-2462MHz 802.11n(HT40): 2422-2452MHz
Channel separation:	5MHz
Modulation technology:	IEEE 802.11b: DQPSK/DBPSK/DSSS/CCK IEEE 802.11g: QPSK/BPSK/16QAM/64QAM/OFDM IEEE 802.11n: QPSK/BPSK/16QAM/64QAM/OFDM
Antenna Type:	PCB Antenna
Antenna gain:	0dBi
Power supply:	Input: DC 5V by USB or DC 3.7V by battery

.....



Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz	X	

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	Frequency (MHz)	
	802.11b/802.11g/802.11n(HT20)	802.11n(HT40)
Lowest channel	2412MHz	2422MHz
Middle channel	2437MHz	2437MHz
Highest channel	2462MHz	2452MHz

3.2 DESCRIPTION OF TEST MODES

Transmitting mode	Keep the EUT in continuously transmitting mode
Remark: EUT use new battery during the test,the dutycycle >98%, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.	

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:				
Pre-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.				
Mode	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)
Data rate	1Mbps	6Mbps	6.5Mbps	13.5Mbps

3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Emission



Conducted Spurious





3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Adapter	N/A	HW-059200CHQ	N/A	AE

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.



Radiation Test equipment

Item	Equipment	Manufacturer	Model	Last Cal.	Next Cal.
1	Receiver	R&S	ESCI	May 12, 2023	May 11, 2024
2	Loop antenna	EMCI	LAP600	May 12, 2023	May 11, 2024
3	Amplifier	Schwarzbeck	BBV 9743 B	May 12, 2023	May 11, 2024
4	Amplifier	Schwarzbeck	BBV 9718 B	May 12, 2023	May 11, 2024
5	Bilog Antenna	Schwarzbeck	VULB9162	May 17, 2023	May 16, 2024
6	Horn Antenna	Schwarzbeck	BBHA9120D	May 17, 2023	May 16, 2024
7	Horn Antenna	A.H.SYSTEMS	SAS574	May 12, 2023	May 11, 2024
8	Amplifier	AEROFLEX	100KHz-40GHz	May 12, 2023	May 11, 2024
9	Spectrum Analyzer	R&S	FSV40	May 12, 2023	May 11, 2024
10	966 Anechoic Chamber	EMToni	9m6m6m	Nov. 25, 2021	Nov. 24, 2024
11	Spectrum Analyzer	KEYSIGHT	N9020A	May 12, 2023	May 11, 2024
12	WIDBAND RADIO COMMUNICATION TESTER	R&S	CMW500	May 12, 2023	May 11, 2024
13	Single Generator	Agilent	N5182A	May 12, 2023	May 11, 2024
14	Power Sensor	MWRftest	MW100-RFCB	May 12, 2023	May 11, 2024
15	Audio analyzer	R&S	UPL	May 12, 2023	May 11, 2024
16	Single Generator	R&S	SMB100A	May 12, 2023	May 11, 2024
17	Power Amplifier Shielding Room	EMToni	2m3m3m	Nov. 25, 2021	Nov. 24, 2024

Conduction Test equipment

Equipment	Manufacturer	Model	Last Cal.	Next Cal.
Receiver	R&S	ESCI	May 12, 2023	May 11, 2024
LISN	R&S	ENV216	May 12, 2023	May 11, 2024
ISN CAT 6	Schwarzbeck	NTFM 8158	May 12, 2023	May 11, 2024
ISN CAT 5	Schwarzbeck	CAT5 8158	May 12, 2023	May 11, 2024
Capacitive Voltage Probe	Schwarzbeck	CVP 9222 C	May 12, 2023	May 11, 2024
Current Transformer Clamp	Schwarzbeck	SW 9605	May 12, 2023	May 11, 2024
CE Shielding Room	EMToni	9m4m3m	Nov. 25, 2021	Nov. 24, 2024



4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10:2013
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

4.1.1 POWER LINE CONDUCTED EMISSION Limits

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) *Decreases with the logarithm of the frequency.

4.1.2 TEST PROCEDURE


- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation



4.1.4 TEST SETUP




4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



4.1.6 test result

Temperature:	24.3℃	Relative Humidity :	50%
Pressure:	101kPa	Phase :	L
Test Voltage:	AC 120V/60Hz		




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.5460	13.12	9.89	23.01	56.00	-32.99	QP	P	
2	0.5460	-1.13	9.89	8.76	46.00	-37.24	AVG	P	
3	0.5685	12.51	9.89	22.40	56.00	-33.60	QP	P	
4	0.5685	-1.01	9.89	8.88	46.00	-37.12	AVG	P	
5	0.6134	14.16	9.90	24.06	56.00	-31.94	QP	P	
6	0.6134	-0.86	9.90	9.04	46.00	-36.96	AVG	P	
7	0.6403	13.48	9.90	23.38	56.00	-32.62	QP	P	
8	0.6403	-0.80	9.90	9.10	46.00	-36.90	AVG	P	
9	0.6764	12.80	9.90	22.70	56.00	-33.30	QP	P	
10	0.6764	-1.63	9.90	8.27	46.00	-37.73	AVG	P	
11 *	0.7842	15.00	9.90	24.90	56.00	-31.10	QP	P	
12	0.7842	-0.63	9.90	9.27	46.00	-36.73	AVG	P	

Notes:

- 1.An initial pre-scan was performed on the line and neutral lines with peak detector.
- 2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
- 3.Measurement Level = Reading level + Correct Factor
- 4.The test data shows only the worst case 802.11b mode (Low Channel:2412MHz).



Temperature:	24.3°C	Relative Humidity :	50%
Pressure:	101kPa	Phase :	N
Test Voltage:	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.4964	13.79	9.89	23.68	56.06	-32.38	QP	P	
2	0.4964	-0.61	9.89	9.28	46.06	-36.78	AVG	P	
3	0.5100	13.21	9.89	23.10	56.00	-32.90	QP	P	
4	0.5100	-0.83	9.89	9.06	46.00	-36.94	AVG	P	
5	0.5503	12.61	9.89	22.50	56.00	-33.50	QP	P	
6	0.5503	-0.72	9.89	9.17	46.00	-36.83	AVG	P	
7	0.6045	13.23	9.90	23.13	56.00	-32.87	QP	P	
8	0.6045	-1.21	9.90	8.69	46.00	-37.31	AVG	P	
9	0.6945	13.40	9.90	23.30	56.00	-32.70	QP	P	
10	0.6945	-1.47	9.90	8.43	46.00	-37.57	AVG	P	
11 *	0.7395	14.07	9.90	23.97	56.00	-32.03	QP	P	
12	0.7395	-1.64	9.90	8.26	46.00	-37.74	AVG	P	

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor
4. The test data shows only the worst case 802.11b mode (Low Channel:2412MHz).



Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
Peak		1MHz	10Hz	Average	

4.2.1 RADIATED EMISSION LIMITS

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

4.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoiccamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of variable-height antenna tower.

- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- g. Different from above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change from table 0.8 meter to 1.5 meter (Above 18GHz the distance is 1 meter and table is 1.5 meter).
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

4.2.3 DEVIATION FROM TEST STANDARD


No deviation

4.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

4.2.6 TEST RESULTS


Between 9KHz – 30MHz

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.



Between 30MHz – 1GHz


Temperature :	25.1°C	Relative Humidity :	50%
Pressure :	101kPa	Polarization :	Horizontal
Test Voltage :	DC 3.7V		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	216.0240	49.86	-10.31	39.55	46.00	-6.45	QP
2 *	360.4476	51.23	-6.66	44.57	46.00	-1.43	QP
3	432.5455	44.84	-5.22	39.62	46.00	-6.38	QP
4 !	504.7062	48.03	-3.99	44.04	46.00	-1.96	QP
5 !	576.6443	47.07	-2.68	44.39	46.00	-1.61	QP
6 !	649.6594	45.80	-1.46	44.34	46.00	-1.66	QP



Temperature :	25.1°C	Relative Humidity :	50%
Pressure :	101kPa	Polarization :	Vertical
Test Voltage :	DC 3.7V		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 !	360.4476	49.83	-6.66	43.17	46.00	-2.83	QP
2 !	432.5455	48.72	-5.22	43.50	46.00	-2.50	QP
3 !	504.7062	47.46	-3.99	43.47	46.00	-2.53	QP
4 *	552.8832	47.05	-3.12	43.93	46.00	-2.07	QP
5 !	576.6443	46.03	-2.68	43.35	46.00	-2.65	QP
6 !	906.4823	40.58	2.26	42.84	46.00	-3.16	QP

Remarks:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. The test data shows only the worst case 802.11b mode (Low Channel:2412MHz).



1GHz~25GHz

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detect or Type
802.11b									
Low Channel:2412MHz									
V	4824.00	58.37	30.55	5.77	24.66	58.25	74	-15.75	Pk
V	4824.00	41.03	30.55	5.77	24.66	40.91	54	-13.09	AV
H	4824.00	56.05	30.33	6.32	24.55	56.59	74	-17.41	Pk
H	4824.00	41.53	30.33	6.32	24.55	42.07	54	-11.93	AV
Middle Channel:2437MHz									
V	4874.00	56.9	30.55	5.77	24.66	56.78	74	-17.22	Pk
V	4874.00	43.55	30.55	5.77	24.66	43.43	54	-10.57	AV
H	4874.00	55.82	30.33	6.32	24.55	56.36	74	-17.64	Pk
H	4874.00	41.59	30.33	6.32	24.55	42.13	54	-11.87	AV
High Channel:2462MHz									
V	4924.00	58.69	30.55	5.77	24.66	58.57	74	-15.43	Pk
V	4924.00	41.09	30.55	5.77	24.66	40.97	54	-13.03	AV
H	4924.00	57.13	30.33	6.32	24.55	57.67	74	-16.33	Pk
H	4924.00	43.81	30.33	6.32	24.55	44.35	54	-9.65	AV
802.11g									
Low Channel:2412MHz									
V	4824.00	59.91	30.55	5.77	24.66	59.79	74	-14.21	Pk
V	4824.00	41.05	30.55	5.77	24.66	40.93	54	-13.07	AV
H	4824.00	59.03	30.33	6.32	24.55	59.57	74	-14.43	Pk
H	4824.00	41.77	30.33	6.32	24.55	42.31	54	-11.69	AV
Middle Channel:2437MHz									
V	4874.00	57.66	30.55	5.77	24.66	57.54	74	-16.46	Pk
V	4874.00	41.99	30.55	5.77	24.66	41.87	54	-12.13	AV
H	4874.00	56.95	30.33	6.32	24.55	57.49	74	-16.51	Pk
H	4874.00	41.71	30.33	6.32	24.55	42.25	54	-11.75	AV
High Channel:2462MHz									
V	4924.00	59.8	30.55	5.77	24.66	59.68	74	-14.32	Pk
V	4924.00	41.92	30.55	5.77	24.66	41.8	54	-12.2	AV
H	4924.00	58.37	30.33	6.32	24.55	58.91	74	-15.09	Pk
H	4924.00	42.68	30.33	6.32	24.55	43.22	54	-10.78	AV
802.11n 20									
Low Channel:2412MHz									
V	4824.00	56.08	30.55	5.77	24.66	55.96	74	-18.04	Pk
V	4824.00	43.79	30.55	5.77	24.66	43.67	54	-10.33	AV
H	4824.00	56.25	30.33	6.32	24.55	56.79	74	-17.21	Pk
H	4824.00	42.96	30.33	6.32	24.55	43.5	54	-10.5	AV
Middle Channel:2437MHz									
V	4874.00	58.39	30.55	5.77	24.66	58.27	74	-15.73	Pk
V	4874.00	44.57	30.55	5.77	24.66	44.45	54	-9.55	AV
H	4874.00	55.8	30.33	6.32	24.55	56.34	74	-17.66	Pk
H	4874.00	43.54	30.33	6.32	24.55	44.08	54	-9.92	AV
High Channel:2462MHz									
V	4924.00	56.69	30.55	5.77	24.66	56.57	74	-17.43	Pk
V	4924.00	41.53	30.55	5.77	24.66	41.41	54	-12.59	AV
H	4924.00	55	30.33	6.32	24.55	55.54	74	-18.46	Pk
H	4924.00	42.54	30.33	6.32	24.55	43.08	54	-10.92	AV



802.11n 40									
Low Channel:2422MHz									
V	4844.00	59.99	30.55	5.77	24.66	59.87	74	-14.13	Pk
V	4844.00	41.7	30.55	5.77	24.66	41.58	54	-12.42	AV
H	4844.00	56.4	30.33	6.32	24.55	56.94	74	-17.06	Pk
H	4844.00	41.68	30.33	6.32	24.55	42.22	54	-11.78	AV
Middle Channel:2437MHz									
V	4874.00	57.41	30.55	5.77	24.66	57.29	74	-16.71	Pk
V	4874.00	41.09	30.55	5.77	24.66	40.97	54	-13.03	AV
H	4874.00	58.25	30.33	6.32	24.55	58.79	74	-15.21	Pk
H	4874.00	44.06	30.33	6.32	24.55	44.6	54	-9.4	AV
High Channel:2452MHz									
V	4904.00	58.35	30.55	5.77	24.66	58.23	74	-15.77	Pk
V	4904.00	43.96	30.55	5.77	24.66	43.84	54	-10.16	AV
H	4904.00	59.6	30.33	6.32	24.55	60.14	74	-13.86	Pk
H	4904.00	43.84	30.33	6.32	24.55	44.38	54	-9.62	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
4. For above 1GHz, the test result of peak was 20dB below to the limit of peak, which can be compliant to the average limit, so just peak value was recorded.

5. RADIATED BAND EMISSION MEASUREMENT

5.1 TEST REQUIREMENT:

Test Requirement:	FCC Part15 C Section 15.209 and 15.205				
Test Method:	ANSI C63.10: 2013				
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Average	1MHz	3MHz	Average

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

5.2 TEST PROCEDURE

Above 1GHz test procedure as below:

- a. 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could bestopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dBmargin would be re-tested one by one using peak, quasi-peak or average method as specified and then reportedin a data sheet.
- g. Test the EUT in the lowest channel,the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

5.3 DEVIATION FROM TEST STANDARD

No deviation



Radiated Emission Test-Up Frequency Above 1GHz



5.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



5.6 TEST RESULT

	Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
802.11b	LowChannel 2412MHz										
	H	2390.00	61.52	30.22	4.85	23.98	60.13	74.00	-13.87	PK	PASS
	H	2390.00	47.48	30.22	4.85	23.98	46.09	54.00	-7.91	AV	PASS
	H	2400.00	59.60	30.22	4.85	23.98	58.21	74.00	-15.79	PK	PASS
	H	2400.00	47.11	30.22	4.85	23.98	45.72	54.00	-8.28	AV	PASS
	V	2390.00	60.71	30.22	4.85	23.98	59.32	74.00	-14.68	PK	PASS
	V	2390.00	46.37	30.22	4.85	23.98	44.98	54.00	-9.02	AV	PASS
	V	2400.00	62.11	30.22	4.85	23.98	60.72	74.00	-13.28	PK	PASS
	V	2400.00	48.43	30.22	4.85	23.98	47.04	54.00	-6.96	AV	PASS
	High Channel 2462MHz										
	H	2483.50	62.23	30.22	4.85	23.98	60.84	74.00	-13.16	AV	PASS
	H	2483.50	48.12	30.22	4.85	23.98	46.73	54.00	-7.27	PK	PASS
	H	2500.00	62.85	30.22	4.85	23.98	61.46	74.00	-12.54	AV	PASS
	H	2500.00	46.10	30.22	4.85	23.98	44.71	54.00	-9.29	PK	PASS
	V	2483.50	60.12	30.22	4.85	23.98	58.73	74.00	-15.27	AV	PASS
	V	2483.50	48.89	30.22	4.85	23.98	47.50	54.00	-6.50	PK	PASS
V	2500.00	60.23	30.22	4.85	23.98	58.84	74.00	-15.16	AV	PASS	
V	2500.00	47.52	30.22	4.85	23.98	46.13	54.00	-7.87	AV	PASS	
802.11g	Low Channel 2412MHz										
	H	2390.00	62.47	30.22	4.85	23.98	61.08	74.00	-12.92	PK	PASS
	H	2390.00	46.76	30.22	4.85	23.98	45.37	54.00	-8.63	AV	PASS
	H	2400.00	61.23	30.22	4.85	23.98	59.84	74.00	-14.16	PK	PASS
	H	2400.00	46.26	30.22	4.85	23.98	44.87	54.00	-9.13	AV	PASS
	V	2390.00	60.28	30.22	4.85	23.98	58.89	74.00	-15.11	PK	PASS
	V	2390.00	48.82	30.22	4.85	23.98	47.43	54.00	-6.57	AV	PASS
	V	2400.00	61.00	30.22	4.85	23.98	59.61	74.00	-14.39	PK	PASS
	V	2400.00	47.26	30.22	4.85	23.98	45.87	54.00	-8.13	AV	PASS
	High Channel 2462MHz										
	H	2483.50	59.30	30.22	4.85	23.98	57.91	74.00	-16.09	PK	PASS
	H	2483.50	48.83	30.22	4.85	23.98	47.44	54.00	-6.56	AV	PASS
	H	2500.00	61.57	30.22	4.85	23.98	60.18	74.00	-13.82	PK	PASS
	H	2500.00	47.88	30.22	4.85	23.98	46.49	54.00	-7.51	AV	PASS
	V	2483.50	60.43	30.22	4.85	23.98	59.04	74.00	-14.96	PK	PASS
	V	2483.50	47.66	30.22	4.85	23.98	46.27	54.00	-7.73	AV	PASS
V	2500.00	61.88	30.22	4.85	23.98	60.49	74.00	-13.51	PK	PASS	
V	2500.00	48.03	30.22	4.85	23.98	46.64	54.00	-7.36	AV	PASS	
802.11n20	Low Channel 2412MHz										
	H	2390.00	60.09	30.22	4.85	23.98	58.70	74.00	-15.30	PK	PASS
	H	2390.00	47.37	30.22	4.85	23.98	45.98	54.00	-8.02	AV	PASS
	H	2400.00	61.18	30.22	4.85	23.98	59.79	74.00	-14.21	PK	PASS
	H	2400.00	47.88	30.22	4.85	23.98	46.49	54.00	-7.51	AV	PASS
	V	2390.00	61.91	30.22	4.85	23.98	60.52	74.00	-13.48	PK	PASS
	V	2390.00	46.67	30.22	4.85	23.98	45.28	54.00	-8.72	AV	PASS
	V	2400.00	62.21	30.22	4.85	23.98	60.82	74.00	-13.18	PK	PASS
	V	2400.00	47.84	30.22	4.85	23.98	46.45	54.00	-7.55	AV	PASS
	High Channel 2462MHz										
	H	2483.50	59.38	30.22	4.85	23.98	57.99	74.00	-16.01	PK	PASS
	H	2483.50	47.82	30.22	4.85	23.98	46.43	54.00	-7.57	AV	PASS
	H	2500.00	61.63	30.22	4.85	23.98	60.24	74.00	-13.76	PK	PASS
	H	2500.00	48.94	30.22	4.85	23.98	47.55	54.00	-6.45	AV	PASS
	V	2483.50	61.23	30.22	4.85	23.98	59.84	74.00	-14.16	PK	PASS



802.11n 40	V	2483.50	47.38	30.22	4.85	23.98	45.99	54.00	-8.01	AV	PASS
	V	2500.00	61.69	30.22	4.85	23.98	60.30	74.00	-13.70	PK	PASS
	V	2500.00	47.46	30.22	4.85	23.98	46.07	54.00	-7.93	AV	PASS
	Low Channel 2422MHz										
	H	2390.00	59.54	30.22	4.85	23.98	58.15	74.00	-15.85	PK	PASS
	H	2390.00	47.39	30.22	4.85	23.98	46.00	54.00	-8.00	AV	PASS
	H	2400.00	62.01	30.22	4.85	23.98	60.62	74.00	-13.38	PK	PASS
	H	2400.00	46.43	30.22	4.85	23.98	45.04	54.00	-8.96	AV	PASS
	V	2390.00	61.60	30.22	4.85	23.98	60.21	74.00	-13.79	PK	PASS
	V	2390.00	46.42	30.22	4.85	23.98	45.03	54.00	-8.97	AV	PASS
	V	2400.00	60.70	30.22	4.85	23.98	59.31	74.00	-14.69	PK	PASS
	V	2400.00	46.59	30.22	4.85	23.98	45.20	54.00	-8.80	AV	PASS
	High Channel 2452MHz										
	H	2483.50	62.62	30.22	4.85	23.98	61.23	74.00	-12.77	PK	PASS
	H	2483.50	48.83	30.22	4.85	23.98	47.44	54.00	-6.56	AV	PASS
	H	2500.00	61.31	30.22	4.85	23.98	59.92	74.00	-14.08	PK	PASS
	H	2500.00	46.44	30.22	4.85	23.98	45.05	54.00	-8.95	AV	PASS
	V	2483.50	60.44	30.22	4.85	23.98	59.05	74.00	-14.95	PK	PASS
	V	2483.50	47.51	30.22	4.85	23.98	46.12	54.00	-7.88	AV	PASS
V	2500.00	61.80	30.22	4.85	23.98	60.41	74.00	-13.59	PK	PASS	
V	2500.00	46.42	30.22	4.85	23.98	45.03	54.00	-8.97	AV	PASS	

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit

6. POWER SPECTRAL DENSITY TEST

Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	KDB558074 D0115.247 Meas Guidancev05r02

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8dBm/3kHz	2400-2483.5	PASS

6.2 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
4. Set the VBW $\geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.



6.6 TEST RESULT

Temperature :	25.9℃	Relative Humidity :	52%
Pressure :	101kPa	Test Voltage :	DC 3.7V

Please refer to APPENDIX WIFI



7. CHANNEL BANDWIDTH

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	KDB558074 D0115.247 Meas Guidancev05r02

7.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5	PASS

7.2 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP



7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



7.6 TEST RESULT

Temperature :	25.8℃	Relative Humidity :	52%
Pressure :	101kPa	Test Voltage :	DC 3.7V
Test Mode :	TX Mode		

Please refer to APPENDIX WIFI

8. OUTPUT POWER TEST

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	KDB558074 D0115.247 Meas Guidancev05r02

8.1 APPLIED PROCEDURES/LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Output Power	1 watt or 30dBm	2400-2483.5	PASS


8.2 TEST PROCEDURE

- a. The EUT was directly connected to the Spectrum analyzer

8.3 DEVIATION FROM STANDARD

No deviation.

8.4 TEST SETUP



8.5 EUT OPERATION CONDITIONS

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 1MHz. VBW =3MHz. Sweep = auto; Detector Function = Peak.
3. Keep the EUT in transmitting at lowest, medium and highest channel individually. Record the max value.

8.6 TEST RESULT

Temperature :	25.3°C	Relative Humidity :	55%
Pressure :	101kPa	Test Voltage :	DC 3.7V

Please refer to APPENDIX WIFI



9. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	KDB558074 D0115.247 Meas Guidanceev05r02

9.1 APPLICABLE STANDARD

in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in§15.205(a), must also comply with the radiated emission limits specified in15.209(a).

9.2 TEST PROCEDURE

Using the following spectrum analyzer setting:

- A) Set the RBW = 100KHz.
- B) Set the VBW = 300KHz.
- C) Sweep time = auto couple.
- D) Detector function = peak.
- E) Trace mode = max hold.
- F) Allow trace to fully stabilize.

9.3 DEVIATION FROM STANDARD

No deviation.

9.4 TEST SETUP



9.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

9.6 TEST RESULTS

Please refer to APPENDIX WIFI



10. ANTENNA REQUIREMENT

Standard requirement:	FCC Part15 C Section 15.203 /247(b)(4)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
15.247(b) (4) requirement: (4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.	
EUT Antenna: The antenna is PCB Antenna, the best case gain of the antenna is 0dBi, reference to the appendix II for details	




11. APPENDIX WIFI

11.1 DUTY CYCLE


Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
b	2412	Ant1	99.52	0	0.08
b	2437	Ant1	99.68	0	0.08
b	2462	Ant1	98.96	0	0.08
g	2412	Ant1	93.64	0.29	0.49
g	2437	Ant1	92.79	0.32	0.49
g	2462	Ant1	94.5	0.25	0.49
n20	2412	Ant1	95.52	0.2	0.52
n20	2437	Ant1	96.48	0.16	0.52
n20	2462	Ant1	94.58	0.24	0.52
n40	2422	Ant1	91.92	0.37	1.1
n40	2437	Ant1	84.4	0.74	1.09
n40	2452	Ant1	85.05	0.7	1.1







Test Graphs Duty Cycle NVNT b 2412MHz Ant1



Duty Cycle NVNT b 2437MHz Ant1











Duty Cycle NVNT n20 2412MHz Ant1




Duty Cycle NVNT n20 2437MHz Ant1







Duty Cycle NVNT n20 2462MHz Ant1



Duty Cycle NVNT n40 2422MHz Ant1








11.2 MAXIMUM AVERAGE CONDUCTED OUTPUT POWER


Mode	Frequency (MHz)	Conducted Power (dBm)	Duty Factor (dB)	Total Power (dBm)	Limit (dBm)	Verdict
b	2412	0.97	0	0.97	30	Pass
b	2437	-3.73	0	-3.73	30	Pass
b	2462	-5.35	0	-5.35	30	Pass
g	2412	0.86	0.29	1.15	30	Pass
g	2437	-1.12	0.32	-0.8	30	Pass
g	2462	-5.85	0.25	-5.6	30	Pass
n20	2412	2.33	0.2	2.53	30	Pass
n20	2437	-1.18	0.16	-1.02	30	Pass
n20	2462	-2.6	0.24	-2.36	30	Pass
n40	2422	-4.77	0.37	-4.4	30	Pass
n40	2437	-4.8	0.74	-4.06	30	Pass
n40	2452	-6.43	0.7	-5.73	30	Pass



Test Graphs Average Power NVNT b 2412MHz Ant1




Average Power NVNT b 2437MHz Ant1






Average Power NVNT b 2462MHz Ant1




Average Power NVNT g 2412MHz Ant1










Average Power NVNT g 2437MHz Ant1





Average Power NVNT g 2462MHz Ant1












Mode	Frequency (MHz)	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
b	2412	10.085	0.5	Pass
b	2437	10.075	0.5	Pass
b	2462	10.033	0.5	Pass
g	2412	16.361	0.5	Pass
g	2437	16.356	0.5	Pass
g	2462	16.335	0.5	Pass
n20	2412	17.296	0.5	Pass
n20	2437	17.064	0.5	Pass
n20	2462	16.876	0.5	Pass
n40	2422	35.755	0.5	Pass
n40	2437	35.679	0.5	Pass
n40	2452	35.549	0.5	Pass




Test Graphs

-6dB Bandwidth NVNT b 2412MHz Ant1




-6dB Bandwidth NVNT b 2437MHz Ant1






-6dB Bandwidth NVNT b 2462MHz Ant1




-6dB Bandwidth NVNT g 2412MHz Ant1






-6dB Bandwidth NVNT g 2437MHz Ant1




-6dB Bandwidth NVNT g 2462MHz Ant1






-6dB Bandwidth NVNT n20 2412MHz Ant1




-6dB Bandwidth NVNT n20 2437MHz Ant1






-6dB Bandwidth NVNT n20 2462MHz Ant1




-6dB Bandwidth NVNT n40 2422MHz Ant1






-6dB Bandwidth NVNT n40 2437MHz Ant1



-6dB Bandwidth NVNT n40 2452MHz Ant1






11.4 OCCUPIED CHANNEL BANDWIDTH


Mode	Frequency (MHz)	99% OBW (MHz)
b	2412	15.016
b	2437	14.956
b	2462	14.969
g	2412	16.558
g	2437	16.483
g	2462	16.536
n20	2412	17.674
n20	2437	17.611
n20	2462	17.61
n40	2422	36.188
n40	2437	36.064
n40	2452	36.165



Test Graphs OBW NVNT b 2412MHz Ant1




OBW NVNT b 2437MHz Ant1






OBW NVNT b 2462MHz Ant1




OBW NVNT g 2412MHz Ant1






OBW NVNT g 2437MHz Ant1




OBW NVNT g 2462MHz Ant1






OBW NVNT n20 2412MHz Ant1




OBW NVNT n20 2437MHz Ant1






OBW NVNT n20 2462MHz Ant1




OBW NVNT n40 2422MHz Ant1






OBW NVNT n40 2437MHz Ant1



OBW NVNT n40 2452MHz Ant1






11.5 MAXIMUM POWER SPECTRAL DENSITY LEVEL

Mode	Frequency (MHz)	Conducted PSD (dBm/3kHz)	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
b	2412	-21.5	-21.5	8	Pass
b	2437	-25.93	-25.93	8	Pass
b	2462	-26.41	-26.41	8	Pass
g	2412	-23.7	-23.7	8	Pass
g	2437	-25.46	-25.46	8	Pass
g	2462	-30.01	-30.01	8	Pass
n20	2412	-22.13	-22.13	8	Pass
n20	2437	-26.13	-26.13	8	Pass
n20	2462	-27.6	-27.6	8	Pass
n40	2422	-32.48	-32.48	8	Pass
n40	2437	-32.58	-32.58	8	Pass
n40	2452	-33.32	-33.32	8	Pass



Test Graphs

PSD NVNT b 2412MHz Ant1




PSD NVNT b 2437MHz Ant1





PSD NVNT b 2462MHz Ant1




PSD NVNT g 2412MHz Ant1





PSD NVNT g 2437MHz Ant1



PSD NVNT g 2462MHz Ant1



