



SAR TEST REPORT

For

Arvicom Sarl

CART S+

Test Model: 900.0055.01

Prepared for : Arvicom Sarl
Address : 20 rue du commerce P.O. Box 3895, Foetz, 3895 Luxembourg

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.
Address : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park
Yabianxueziwei, Shajing Street, Baoan District, Shenzhen,
518000, China

Tel : (+86)755-82591330
Fax : (+86)755-82591332
Web : www.LCS-cert.com
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : March 05,2025
Number of tested samples : 1
Sample number : A240826160-1
Serial number : 2402001
Date of Test : March 05,2025 ~ March 14,2025
Date of Report : March 14,2025





SAR TEST REPORT	
Report Reference No.....:	LCSA09064068E
Date Of Issue	March 14,2025
Testing Laboratory Name.....:	Shenzhen LCS Compliance Testing Laboratory Ltd.
Address	101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Testing Location/ Procedure	Full application of Harmonised standards <input checked="" type="checkbox"/> Partial application of Harmonised standards <input type="checkbox"/> Other standard testing method <input type="checkbox"/>
Applicant's Name	Arvicom Sarl
Address	20 rue du commerce P.O. Box 3895,Foetz, 3895 Luxembourg
Test Specification:	
Standard.....:	FCC 47CFR §2.1093, ANSI/IEEE C95.1-2019, IEEE 1528-2013
Test Report Form No.....:	TRF-4-E-102 A/0
TRF Originator.....:	Shenzhen LCS Compliance Testing Laboratory Ltd.
Master TRF	Dated 2014-09
Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.	
This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes noresponsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.	
Test Item Description.....:	CART S+
Trade Mark	CART
Model/Type Reference	900.0055.01
Ratings	Input: PD 5V/3A, 9V/2A, 12V/1.5A, and 20V/1.5A DC 3.7V by Rechargeable Li-ion Battery, 2500mAh
Result	Positive

Compiled by:

Jay zhan

Jay Zhan/ File administrators

Supervised by:

Cary Luo

Cary Luo / Technique principal

Approved by:

Gavin Liang

Gavin Liang/ Manager





SAR -- TEST REPORT

Test Report No. :	LCSA09064068E	March 14,2025 Date of issue
--------------------------	----------------------	--------------------------------

EUT.....	: CART S+
Type/Model.....	: 900.0055.01
Applicant.....	: Arvicom Sarl
Address.....	: 20 rue du commerce P.O. Box 3895,Foetz, 3895 Luxembourg
Telephone.....	: /
Fax.....	: /
Manufacturer.....	: Arvicom Sarl
Address.....	: 20 rue du commerce P.O. Box 3895,Foetz, 3895 Luxembourg
Telephone.....	: /
Fax.....	: /
Factory.....	: Arvicom Sarl
Address.....	: 20 rue du commerce P.O. Box 3895,Foetz, 3895 Luxembourg
Telephone.....	: /
Fax.....	: /

Test Result	Positive
--------------------	-----------------

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.





Revision History

Revision	Issue Date	Revision Content	Revised By
000	March 14,2025	Initial Issue	---





TABLE OF CONTENTS

- 1. TEST STANDARDS AND TEST DESCRIPTION.....6**
 - 1.1. STATEMENT OF COMPLIANCE6
 - 1.2. TEST LOCATION7
 - 1.3. TEST FACILITY7
 - 1.4. TEST LABORATORY ENVIRONMENT7
 - 1.5. PRODUCT DESCRIPTION8
 - 1.6. DUT ANTENNA LOCATIONS(REAR VIEW)10
 - 1.7. TEST SPECIFICATION11
 - 1.8. RF EXPOSURE LIMITS12
 - 1.9. EQUIPMENT LIST13
- 2. SAR MEASUREMENTS SYSTEM CONFIGURATION14**
 - 2.1. SAR MEASUREMENT SYSTEM14
 - 2.2. ISOTROPIC E-FIELD PROBE EX3DV416
 - 2.3. DATA ACQUISITION ELECTRONICS (DAE)17
 - 2.4. SAM TWIN PHANTOM17
 - 2.5. ELI PHANTOM18
 - 2.6. DEVICE HOLDER FOR TRANSMITTERS19
 - 2.7. MEASUREMENT PROCEDURE20
- 3. SAR MEASUREMENT VARIABILITY AND UNCERTAINTY.....24**
 - 3.1. SAR MEASUREMENT VARIABILITY24
 - 3.2. SAR MEASUREMENT UNCERTAINTY24
- 4. SAR SYSTEM VERIFICATION PROCEDURE25**
 - 4.1. TISSUE SIMULATE LIQUID25
 - 4.2. SAR SYSTEM CHECK27
- 5. SAR MEASUREMENT PROCEDURE29**
 - 5.1. CONDUCTED POWER MEASUREMENT29
 - 5.2. WIFI TEST CONFIGURATION29
 - 5.3. POWER REDUCTION32
 - 5.4. POWER DRIFT32
- 6. TEST CONDITIONS AND RESULTS33**
 - 6.1. CONDUCTED POWER RESULTS33
 - 6.2. STAND-ALONE SAR TEST EVALUATION44
 - 6.3. SAR MEASUREMENT RESULTS48
 - 6.4. MULTIPLE TRANSMITTER EVALUATION52
 - 6.5. SAR MEASUREMENT RESULTS54
- APPENDIX A: DETAILED SYSTEM CHECK RESULTS55**
- APPENDIX B: DETAILED TEST RESULTS55**
- APPENDIX C: CALIBRATION CERTIFICATE55**
- APPENDIX D: PHOTOGRAPHS55**





1. TEST STANDARDS AND TEST DESCRIPTION

1.1. Statement of Compliance

The maximum of results of SAR found during testing for 900.0055.01 are follows:

<Highest Reported standalone SAR Summary>

Classment Class	Frequency Band	Body (Report SAR1-g (W/kg))	Body (Report SAR1-g (W/kg))
		(Separation Distance 0mm) ANT0	(Separation Distance 0mm) ANT1
DTS	WIFI2.4G	0.477	0.378
NII	WIFI5.2G	0.462	0.360
	WIFI5.3G	0.434	0.331
	WIFI5.5G	0.338	0.326
	WIFI5.8G	0.328	0.244

Note

1) This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47CFR §2.1093 and ANSI/IEEE C95.1-2019, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013.

<Highest Reported simultaneous SAR Summary>

Exposure Position	Classment Class	Body-worn (Report SAR1-g (W/kg))	Highest Reported Simultaneous Transmission SAR1-g (W/kg)
Body	DTS	0.477	0.855
		0.378	





1.2. Test Location

Company: Shenzhen LCS Compliance Testing Laboratory Ltd.
 Address: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
 Telephone: (+86)755-82591330
 Fax: (+86)755-82591330
 Web: www.LCS-cert.com
 E-mail: webmaster@LCS-cert.com

1.3. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

Site Description
 SAR Lab. : NVLAP Accreditation Code is 600167-0.
 FCC Designation Number is CN5024.
 CAB identifier is CN0071.
 CNAS Registration Number is L4595.
 Test Firm Registration Number: 254912.

1.4. Test Laboratory Environment

Temperature	Min. = 18°C, Max. = 25 °C
Relative humidity	Min. = 30%, Max. = 70%
Ground system resistance	< 0.5 Ω
Atmospheric pressure:	950-1050mbar
Ambient noise is checked and found very low and in compliance with requirement of standards.	
Reflection of surrounding objects is minimized and in compliance with requirement of standards.	





1.5. Product Description

The **Arvicom Sarl's** Model: **900.0055.01** or the "EUT" as referred to in this report; more general information as follows, for more details, refer to the user's manual of the EUT.

EUT	: CART S+
Test Model	: 900.0055.01
Ratings	: Input: PD 5V/3A, 9V/2A, 12V/1.5A, and 20V/1.5A DC 3.7V by Rechargeable Li-ion Battery, 2500mAh
Hardware Version	: V1.0
Software Version	: V1.0
Bluetooth	:
Frequency Range	: 2402MHz~2480MHz
Channel Number	: 79 channels for Bluetooth V5.1 (DSS) 40 channels for Bluetooth V5.1 (DTS)
Channel Spacing	: 1MHz for Bluetooth V5.1 (DSS) 2MHz for Bluetooth V5.1 (DTS)
Modulation Type	: GFSK, $\pi/4$ -DQPSK, 8-DPSK for Bluetooth V5.1 (DSS) GFSK for Bluetooth V5.1 (DTS)
Bluetooth Version	: V5.1
Antenna Description	: Antenna0: FPC Antenna, 4.5dBi (max.)
WIFI(2.4G Band)	:
Frequency Range	: 2412MHz~2462MHz
Channel Number	: 11 Channels for 20MHz bandwidth (2412~2462MHz) 7 Channels for 40MHz bandwidth (2422~2452MHz)
Channel Spacing	: 5MHz
Modulation Type	: IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ax: OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: Antenna0: FPC Antenna, 4.5dBi(Max.) Antenna1: FPC Antenna, 4.5dBi(Max.)
WIFI(5.2G Band)	:
Frequency Range	: 5180MHz~5240MHz
Channel Number	: 4 Channels for 20MHz bandwidth(5180MHz~5240MHz) 2 channels for 40MHz bandwidth(5190MHz~5230MHz) 1 channels for 80MHz bandwidth(5210MHz)
Modulation Type	: IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ax: OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: Antenna0: FPC Antenna, 6.3dBi(Max.) Antenna1: FPC Antenna, 6.3dBi(Max.)
5.3G WLAN	:
Frequency Range	: 5250-5350MHz
Channel Number	: 4 Channels for 20MHz bandwidth(5260MHz-5320MHz)





2 channels for 40MHz bandwidth(5270MHz~5310MHz)
 1 channels for 80MHz bandwidth(5290MHz)

Modulation Type : IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK)
 IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)
 IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
 IEEE 802.11ax: OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)

Antenna Description : Antenna0: FPC Antenna, 6.3dBi(Max.)
 Antenna1: FPC Antenna, 6.3dBi(Max.)

5.5G WLAN

Frequency Range : 5470-5725MHz

Channel Number : 11 Channels for 20MHz bandwidth(5500MHz-5700MHz)
 5 Channels for 40MHz bandwidth(5510MHz-5670MHz)
 2 Channels for 80MHz bandwidth(5530MHz, 5610MHz)

Modulation Type : IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK)
 IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)
 IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
 IEEE 802.11ax: OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)

Antenna Description : Antenna0: FPC Antenna, 6.3dBi(Max.)
 Antenna1: FPC Antenna, 6.3dBi(Max.)

WIFI(5.8G Band)

Frequency Range : 5745MHz~5825MHz

Channel Number : 5 channels for 20MHz bandwidth(5745MHz~5825MHz)
 2 channels for 40MHz bandwidth(5755MHz~5795MHz)
 1 channels for 80MHz bandwidth(5775MHz)


Modulation Type : IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK)
 IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)
 IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
 IEEE 802.11ax: OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)

Antenna Description : Antenna0: FPC Antenna, 6.3dBi(Max.)
 Antenna1: FPC Antenna, 6.3dBi(Max.)

Exposure category : Uncontrolled Environment General Population



1.6. DUT Antenna Locations(Rear View)



According to the WIFI&BT antennas we can draw the conclusion that:

Distance from the antenna to the EUT edge(mm)						
Mode	Front	Back	Left	Right	Top	Bottom
WIFI/BT Antenna 0	5	5	5	335	133	50
WIFI Antenna 1	5	5	5	335	50	133





1.7. Test Specification

Identity	Document Title
FCC 47CFR §2.1093	Radiofrequency Radiation Exposure Evaluation: Portable Devices
ANSI/IEEE C95.1-2019	IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz – 300 GHz.
IEEE 1528-2013	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
KDB 248227 D01	SAR Guidance for IEEE 802 11 Wi-Fi SAR v02r02
KDB 447498 D01	General RF Exposure Guidance v06
KDB 865664 D01	SAR Measurement 100 MHz to 6 GHz v01r04
KDB 865664 D02	RF Exposure Reporting v01r02
KDB 690783 D01	SAR Listings on Grants v01r03





1.8. RF exposure limits

Human Exposure	Uncontrolled Environment General Population	Controlled Environment Occupational
Spatial Peak SAR* (Brain*Trunk)	1.60 mW/g	8.00 mW/g
Spatial Average SAR** (Whole Body)	0.08 mW/g	0.40 mW/g
Spatial Peak SAR*** (Hands/Feet/Ankle/Wrist)	4.00 mW/g	20.00 mW/g

Notes:

* The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time

** The Spatial Average value of the SAR averaged over the whole body.

*** The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation.)





1.9. Equipment list

Test Platform		SPEAG DASY5 Professional				
Description		SAR Test System (Frequency range 300MHz-6GHz)				
Software Reference		DASY52; SEMCAD X				
Hardware Reference						
	Equipment	Manufacturer	Model	Serial Number	Calibration Date	Due date of calibration
<input checked="" type="checkbox"/>	PC	Lenovo	NA	NA	NA ¹	NA ¹
<input checked="" type="checkbox"/>	Twin Phantom	SPEAG	SAM V5.0	1850	NA ¹	NA ¹
<input checked="" type="checkbox"/>	ELI Phantom	SPEAG	ELI V6.0	2010	NA ¹	NA ¹
<input checked="" type="checkbox"/>	DAE	SPEAG	DAE3	373	2025/2/17	2026/2/16
<input checked="" type="checkbox"/>	E-Field Probe	SPEAG	EX3DV4	3805	2025/2/25	2026/2/24
<input checked="" type="checkbox"/>	Validation Kits	SPEAG	D2450V2	808	2023/10/23	2026/10/22
<input checked="" type="checkbox"/>	Validation Kits	SPEAG	D5GHzV2	1046	2023/10/23	2026/10/22
<input checked="" type="checkbox"/>	Agilent Network Analyzer	Agilent	8753E	SU38432944	2024/6/6	2025/6/5
<input checked="" type="checkbox"/>	Dielectric Probe Kit	SPEAG	DAK3.5	1425	2024/6/6	2025/6/5
<input checked="" type="checkbox"/>	Universal Radio Communication Tester	R&S	CMW500	42115	2024/10/08	2025/10/07
<input checked="" type="checkbox"/>	Directional Coupler	MCLI/USA	4426-20	03746	2024/6/6	2025/6/5
<input checked="" type="checkbox"/>	Power meter	Agilent	E4419B	MY45104493	2024/10/08	2025/10/07
<input checked="" type="checkbox"/>	Power meter	Agilent	E4419B	MY45100308	2024/10/08	2025/10/07
<input checked="" type="checkbox"/>	Power sensor	Agilent	E9301H	MY41495616	2024/10/08	2025/10/07
<input checked="" type="checkbox"/>	Power sensor	Agilent	E9301H	MY41495234	2024/10/08	2025/10/07
<input checked="" type="checkbox"/>	Signal Generator	Agilent	E4438C	MY49072627	2024/6/6	2025/6/5
<input checked="" type="checkbox"/>	Broadband Preamplifier	/	BP-01M18G	P190501	2024/6/6	2025/6/5
<input checked="" type="checkbox"/>	DC POWER SUPPLY	I-SHENG	SP-504	NA	2024/6/6	2025/6/5
<input checked="" type="checkbox"/>	Speed reading thermometer	HTC-1	NA	LCS-E-138	2024/6/6	2025/6/5

Note: All the equipments are within the valid period when the tests are performed.

"1": NA as this is not measurement equipment.



2. SAR MEASUREMENTS SYSTEM CONFIGURATION

2.1. SAR Measurement System

This SAR Measurement System uses a Computer-controlled 3-D stepper motor system (SPEAG DASY5 professional system). A E-field probe is used to determine the internal electric fields. The SAR can be obtained from the equation $SAR = \sigma (|E|)^2 / \rho$ where σ and ρ are the conductivity and mass density of the tissue-Simulate.


The DASY5 system for performing compliance tests consists of the following items:

A standard high precision 6-axis robot (Stabile RX family) with controller, teach pendant and software .An arm extension for accommodation the data acquisition electronics (DAE).

A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.

A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.

The Electro-optical converter (EOC) performs the conversion between optical and electrical of the signals for the digital communication to DAE and for the analog signal from the optical surface detection. The EOC is connected to the measurement server.



F-1. SAR Measurement System Configuration






- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the (absolute) accuracy of the probe positioning.
- A computer operating Windows 7.
- DASY5 software.
- Remote control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- The SAM twin phantom enabling testing left-hand, right-hand and Body Worn usage.
- The device holder for handheld mobile phones.
- Tissue simulating liquid mixed according to the given recipes.
- Validation dipole kits allowing to validating the proper functioning of the system.




2.2. Isotropic E-field Probe EX3DV4


	<p>Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)</p>
<p>Calibration</p>	<p>ISO/IEC 17025 calibration service available.</p>
<p>Frequency</p>	<p>10 MHz to > 6 GHz Linearity: ± 0.2 dB (30 MHz to 6 GHz)</p>
<p>Directivity</p>	<p>± 0.3 dB in TSL (rotation around probe axis) ± 0.5 dB in TSL (rotation normal to probe axis)</p>
<p>Dynamic Range</p>	<p>10 μW/g to > 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 μW/g)</p>
<p>Dimensions</p>	<p>Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm</p>
<p>Application</p>	<p>High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields); the only probe that enables compliance testing for frequencies up to 6 GHz with precision of better 30%.</p>
<p>Compatibility</p>	<p>DASY3, DASY4, DASY52 SAR and higher, EASY4/MRI</p>



2.3. Data Acquisition Electronics (DAE)

Model	DAE	
Construction	Signal amplifier, multiplexer, A/D converter and control logic. Serial optical link for communication with DASY4/5 embedded system (fully remote controlled). Two step probe touch detector for mechanical surface detection and emergency robot stop.	
Measurement Range	-100 to +300 mV (16 bit resolution and two range settings: 4mV,400mV)	
Input Offset Voltage	< 5μV (with auto zero)	
Input Bias Current	< 50 f A	
Dimensions	60 x 60 x 68 mm	

2.4. SAM Twin Phantom


Material	Vinylester, glass fiber reinforced (VE-GF)	
Liquid Compatibility	Compatible with all SPEAG tissue simulating liquids (incl. DGBE type)	
Shell Thickness	2 ± 0.2 mm (6 ± 0.2 mm at ear point)	
Dimensions (incl. Wooden Support)	Length: 1000 mm Width: 500 mm Height: adjustable feet	
Filling Volume	approx. 25 liters	
Wooden Support	SPEAG standard phantom table	

The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 and IEC 62209-1. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot.

Twin SAM V5.0 has the same shell geometry and is manufactured from the same material as Twin SAM V4.0, but has reinforced top structure.



2.5. ELI Phantom

Material	Vinylester, glass fiber reinforced (VE-GF)	
Liquid Compatibility	Compatible with all SPEAG tissue simulating liquids (incl. DGBE type)	
Shell Thickness	2.0 ± 0.2 mm (bottom plate)	
Dimensions	Major axis: 600 mm Minor axis: 400 mm	
Filling Volume	approx. 30 liters	
Wooden Support	SPEAG standard phantom table	

Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles.

ELI V5.0 has the same shell geometry and is manufactured from the same material as ELI4, but has reinforced top structure.



2.6. Device Holder for Transmitters



F-2. Device Holder for Transmitters

- The DASY device holder is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear reference points). The rotation centres for both scales are the ear reference point (ERP). Thus the device needs no repositioning when changing the angles.
- The DASY device holder has been made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon=3$ and loss tangent $\delta=0.02$. The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.



2.7. Measurement procedure

2.7.1. Scanning procedure

Step 1: Power reference measurement

The “reference” and “drift” measurements are located at the beginning and end of the batch process. They measure the field drift at one single point in the liquid over the complete procedure.

Step 2: Area scan

The SAR distribution at the exposed side of the head was measured at a distance of 4mm from the inner surface of the shell. The area covered the entire dimension of the head and the horizontal grid spacing was 15mm*15mm or 12mm*12mm or 10mm*10mm. Based on the area scan data, the area of the maximum absorption was determined by spline interpolation.

Step 3: Zoom scan

Around this point, a volume of 32mm*32mm*30mm ($f \leq 2\text{GHz}$), 30mm*30mm*30mm (f for 2-3GHz) and 24mm*24mm*22mm (f for 5-6GHz) was assessed by measuring 5x5x7 points ($f \leq 2\text{GHz}$), 7x7x7 points (f for 2-3GHz) and 7x7x12 points (f for 5-6GHz). On this basis of this data set, the spatial peak SAR value was evaluated with the following procedure:

The data at the surface was extrapolated, since the centre of the dipoles is 2.0mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.2mm. (This can be variable. Refer to the probe specification). The extrapolation was based on a least square algorithm. A polynomial of the fourth order was calculated through the points in z-axes. This polynomial was then used to evaluate the points between the surface and the probe tip. The maximum interpolated value was searched with a straight-forward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1g or 10g) were computed using the 3D-Spline interpolation algorithm. The volume was integrated with the trapezoidal algorithm. One thousand points were interpolated to calculate the average. All neighbouring volumes were evaluated until no neighboring volume with a higher average value was found.

The area and zoom scan resolutions specified in the table below must be applied to the SAR measurements. Probe boundary effect error compensation is required for measurements with the probe tip closer than half a probe tip diameter to the phantom surface. Both the probe tip diameter and sensor offset distance must satisfy measurement protocols; to ensure probe boundary effect errors are minimized and the higher fields closest to the phantom surface can be correctly measured and extrapolated to the phantom surface for computing 1-g SAR. Tolerances of the post-processing algorithms must be verified by the test laboratory for the scan resolutions used in the SAR measurements, according to the reference distribution functions specified in IEEE Std. 1528-2013.



		≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface		5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location		30° ± 1°	20° ± 1°
Maximum area scan spatial resolution: $\Delta x_{Area}, \Delta y_{Area}$		≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
		When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: $\Delta x_{Zoom}, \Delta y_{Zoom}$		≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$	≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{Zoom}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm 3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{Zoom}(n>1)$: between subsequent points	≤ 1.5 · $\Delta z_{Zoom}(n-1)$
Minimum zoom scan volume	x, y, z	≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm

Step 4: Power reference measurement (drift)

The Power Drift Measurement job measures the field at the same location as the most recent power reference measurement job within the same procedure, and with the same settings. The indicated drift is mainly the variation of the DUT’s output power and should vary max. ± 5 %

2.7.2. Data Storage

The DASY software stores the acquired data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors), together with all necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files with the extension “.DAE4”. The software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of incorrect parameter settings. For example, if a measurement has been performed with a wrong crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be re-evaluated. The measured data can be visualized or exported in different units or formats, depending on the selected probe type ([V/m], [A/m], [°C], [m W/g], [m W/cm²], [dBrel], etc.). Some of these units are not available in certain situations or show meaningless results, e.g., a SAR output in a lossless media will always be zero. Raw data can also be exported to perform the evaluation with other software packages.



2.7.3. Data Evaluation by SEMCAD

The SEMCAD software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters:	- Sensitivity	Normi, ai0, ai1, ai2
- Conversion factor	ConvFi	
- Diode compression point	Dcpi	
Device parameters:	- Frequency	f
- Crest factor	cf	
Media parameters:	- Conductivity	ϵ
- Density	ρ	

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the DASY components. In the direct measuring mode of the multimeter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics.

If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot cf / dcp_i$$

With V_i = compensated signal of channel i ($i = x, y, z$)
 U_i = input signal of channel i ($i = x, y, z$)
 cf = crest factor of exciting field (DASY parameter)
 dcp_i = diode compression point (DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

E-field probes:

$$E_i = (V_i / Norm_i \cdot ConvF)^{1/2}$$





H-field probes:

$$H_i = (V_i)^{1/2} \cdot (a_{i0} + a_{i1}f + a_{i2}f^2) / f$$

With V_i = compensated signal of channel i ($i = x, y, z$)

Norm $_i$ = sensor sensitivity of channel i ($i = x, y, z$)

[mV/(V/m)²] for E-field Probes

ConvF = sensitivity enhancement in solution

a_{ij} = sensor sensitivity factors for H-field probes

f = carrier frequency [GHz]

E_i = electric field strength of channel i in V/m

H_i = magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = (E_x^2 + E_y^2 + E_z^2)^{1/2}$$

The primary field data are used to calculate the derived field units.

$$SAR = (E_{tot}^2 \cdot \sigma) / (\epsilon \cdot 1000)$$

with SAR = local specific absorption rate in mW/g

E_{tot} = total field strength in V/m

σ = conductivity in [mho/m] or [Siemens/m]

ϵ = equivalent tissue density in g/cm³

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid. The power flow density is calculated assuming the excitation field to be a free space field.

$$P_{pwe} = E_{tot}^2 / 3770 \text{ or } P_{pwe} = H_{tot}^2 \cdot 37.7$$

with P_{pwe} = equivalent power density of a plane wave in mW/cm²

E_{tot} = total electric field strength in V/m

H_{tot} = total magnetic field strength in A/m



3. SAR measurement variability and uncertainty

3.1. SAR measurement variability

Per KDB865664 D01 SAR measurement 100 MHz to 6 GHz v01r04, SAR measurement variability must be assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. The additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg (~ 10% from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

The same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds.

3.2. SAR measurement uncertainty

Per KDB865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. The equivalent ratio (1.5/1.6) is applied to extremity and occupational exposure conditions.





4. SAR System Verification Procedure

4.1. Tissue Simulate Liquid

4.1.1. Recipes for Tissue Simulate Liquid

The following tables give the recipes for tissue simulating liquids to be used in different frequency bands:

Ingredients (% by weight)	Frequency (MHz)				
	450	700-900	1750-2000	2300-2500	2500-2700
Water	38.56	40.30	55.24	55.00	54.92
Salt (NaCl)	3.95	1.38	0.31	0.2	0.23
Sucrose	56.32	57.90	0	0	0
HEC	0.98	0.24	0	0	0
Bactericide	0.19	0.18	0	0	0
Tween	0	0	44.45	44.80	44.85
Salt: 99+% Pure Sodium Chloride			Sucrose: 98+% Pure Sucrose		
Water: De-ionized, 16 MΩ ⁺ resistivity			HEC: Hydroxyethyl Cellulose		
Tween: Polyoxyethylene (20) sorbitan monolaurate					
HSL5GHz is composed of the following ingredients:					
Water: 50-65%					
Mineral oil: 10-30%					
Emulsifiers: 8-25%					
Sodium salt: 0-1.5%					

Table 1: Recipe of Tissue Simulate Liquid





4.1.2. Measurement for Tissue Simulate Liquid

The dielectric properties for this Tissue Simulate Liquids were measured by using the DAKS. The Conductivity (σ) and Permittivity (ρ) are listed in bellow table. For the SAR measurement given in this report. The temperature variation of the Tissue Simulate Liquids was $22\pm 2^{\circ}\text{C}$.


Tissue Type	Measured Frequency (MHz)	Target Tissue ($\pm 5\%$)		Measured Tissue		Liquid Temp. ($^{\circ}\text{C}$)	Measured Date
		ϵ_r	$\sigma(\text{S/m})$	ϵ_r	$\sigma(\text{S/m})$		
2450 Head	2450	39.2 (37.24~41.16)	1.8 (1.71~1.89)	38.685	1.833	22.5	March 14,2025
5250Head	5250	36.0 (34.20~37.80)	4.66 (4.43~4.89)	34.954	4.621	22.5	March 14,2025
5600Head	5600	35.5 (33.73~37.28)	5.07 (4.82~5.32)	35.578	5.045	22.5	March 14,2025
5750 Head	5750	35.3 (33.54~37.07)	5.27 (5.01~5.53)	36.669	5.433	22.5	March 14,2025

Table 2: Measurement result of Tissue electric parameters



4.2. SAR System Check

The microwave circuit arrangement for system Check is sketched in F-1. The daily system accuracy verification occurs within the flat section of the SAM phantom. A SAR measurement was performed to see if the measured SAR was within +/- 10% from the target SAR values. The tests were conducted on the same days as the measurement of the EUT. The obtained results from the system accuracy verification are displayed in the following table (A power level of 250mW (below 3GHz) or 100mW (3-6GHz) was input to the dipole antenna). During the tests, the ambient temperature of the laboratory was in the range $22\pm 2^{\circ}\text{C}$, the relative humidity was in the range 60% and the liquid depth above the ear reference points was above 15 ± 0.5 cm in all the cases. It is seen that the system is operating within its specification, as the results are within acceptable tolerance of the reference values.



F-1. the microwave circuit arrangement used for SAR system check

4.2.1. Justification for Extended SAR Dipole Calibrations

1) Referring to KDB865664 D01 requirements for dipole calibration, instead of the typical annual calibration recommended by measurement standards, longer calibration intervals of up to three years may be considered when it is demonstrated that the SAR target, impedance and return loss of a dipole have remain stable according to the following requirements. Each measured dipole is expected to evaluate with the following criteria at least on annual interval in Appendix C.

- There is no physical damage on the dipole;
- System check with specific dipole is within 10% of calibrated value;
- Return-loss is within 20% of calibrated measurement;
- Impedance is within 5Ω from the previous measurement.

2) Network analyzer probe calibration against air, distilled water and a shorting block performed before measuring liquid parameters.





4.2.2. Summary System Check Result(s)

Validation Kit		Measured SAR 250mW	Measured SAR 250mW	Measured SAR	Measured SAR	Target SAR (normalized to 1W) (±10%)	Target SAR (normalized to 1W) (±10%)	Liquid Temp. (°C)	Measured Date
				(normalized to 1W)	(normalized to 1W)				
		1g (W/kg)	10g (W/kg)	1g (W/kg)	10g (W/kg)	1-g(W/kg)	10-g(W/kg)		
D2450V2	Head	12.63	5.82	50.52	23.28	53.5 (48.15~58.85)	24.8 (22.32~27.28)	22.5	March 14,2025
Validation Kit		Measured SAR 100mW	Measured SAR 100mW	Measured SAR	Measured SAR	Target SAR (normalized to 1W) (±10%)	Target SAR (normalized to 1W) (±10%)	Liquid Temp. (°C)	Measured Date
				(normalized to 1W)	(normalized to 1W)				
		1g (W/kg)	10g (W/kg)	1g (W/kg)	10g (W/kg)	1-g(W/kg)	10-g(W/kg)		
D5GHzV2	Head (5.25GHz)	8.44	2.32	84.40	23.20	78.1 (70.29~85.91)	22.2 (19.98~24.42)	22.5	March 14,2025
	Head (5.6GHz)	8.21	2.36	82.10	23.60	81.9 (73.71~90.09)	23.1 (20.79~25.41)	22.5	March 14,2025
	Head (5.75GHz)	8.37	2.25	83.70	22.50	77.4 (69.66~85.14)	21.6 (19.44~23.76)	22.5	March 14,2025

Table 3: Please see the Appendix A





5. SAR measurement procedure

The measurement procedures are as follows:

5.1. Conducted power measurement

- a. For WLAN/BT power measurement, use engineering software to configure EUT WLAN/BT continuously Transmission, at maximum RF power in each supported wireless interface and frequency band.
- b. Connect EUT RF port through RF cable to the power meter, and measure WLAN/BT output power.

5.2. WIFI Test Configuration

For WiFi SAR testing, a communication link is set up with the testing software for WiFi mode test. During the test, at the each test frequency channel, the EUT is operated at the RF continuous emission mode. Per KDB 248227D01, a minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. The reported SAR must be scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

5.2.1. Initial Test Position Procedure

For exposure condition with multiple test position, such as handsets operating next to the ear, devices with hotspot mode or IJMPIC mini-tablet, procedures for initial test position can be applied. Using the transmission mode determined by the DSSS procedure or initial test configuration, area scans are measured for all position in an exposure condition. The test position with the highest extrapolated(peak) SAR is used as the initial test position. When reported SAR for the initial test position is $\leq 0.4\text{W/kg}$, no additional testing for the remaining test position is required. Otherwise, SAR is evaluated at the subsequent highest peak SAR position until the reported SAR result is $\leq 0.8\text{W/kg}$ or all test position are measured. For all positions/configurations tested using the initial test position and subsequent test positions, when the reported SAR is $> 0.8\text{W/kg}$, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is $\leq 1.2\text{W/kg}$ or all required channels are tested.

5.2.2. Initial Test Configuration Procedure

An initial test configuration is determined for OFDM transmission modes according to the channel bandwidth, modulation and data rate combination(s) with the highest maximum output power specified for production units in each standalone and aggregated frequency band. SAR is measured using the highest measured maximum output power channel. For configurations with the same specified or measured maximum output power, additional transmission mode and test channel selection procedures are required (see section 5.3.2 of KDB 248227D01). SAR test reduction of subsequent highest output test channels is based on the reported SAR of the initial test configuration. For next to the ear, hotspot mode and CIMC mini-tablet exposure configurations where multiple test positions are required, the initial test position procedure is applied to minimize the number of test positions required for SAR measurement using the initial test configuration transmission mode. For fixed exposure conditions that do not have multiple SAR test positions, SAR is measured in the transmission mode determined by the initial test configuration. When the reported SAR of the initial test configuration is $> 0.8\text{W/kg}$, SAR measurement is required for the subsequent next highest measured output power channel(s) in the initial test configuration until the reported SAR is $\leq 1.2\text{W/kg}$ or all required channels are tested.

5.2.3. Sub Test Configuration Procedure

SAR measurement requirements for the remaining 802 11 transmission mode configurations that have not been tested in the initial test configuration are determined separately for each standalone and aggregated frequency band, in each exposure condition, according to the maximum output power specified for production units.

When the highest reported SAR for the initial test configuration, according to the initial test position or fixed exposure position requirements, is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is $\leq 1.2\text{W/kg}$, SAR is not required for that subsequent test configuration.





5.2.4. WiFi 2.4G SAR Test Procedures

Separate SAR procedures are applied to DSSS and OFDM configurations in the 2.4 GHz band to simplify DSSS test requirements. For 802.11b DSSS SAR measurements, DSSS SAR procedure applies to fixed exposure test position and initial test position procedure applies to multiple exposure test positions.

a) 802.11b DSSS SAR Test Requirements

SAR is measured for 2.4 GHz 802.11b DSSS using either a fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

- 1) When the reported SAR of the highest measured maximum output power channel (section 3.1 of of KD8 248227D01) for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
- 2) When the reported SAR is > 0.8 W/kg, SAR is required for that exposure configuration using the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel; i.e., all channels require testing.

b) 2.4GHz 802.11g/n OFDM SAR Test Exclusion Requirements

When SAR measurement is required for 2.4 GHz 802.11g/n OFDM configurations, the measurement and test reduction procedures for OFDM are applied (section 5.3 of of KD8 248227D01 SAR is not required for the following 2.4 GHz OFDM conditions.

- 1) When KDB Publication 447498 SAR test exclusion applies to the OFDM configuration.
- 2) When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.

c) SAR Test Requirements for OFDM configurations

When SAR measurement is required for 802.11 a/g/n/ac OFDM configurations, each standalone and frequency aggregated band is considered separately for SAR test reduction. When the same transmitter and antenna(s) are used for U-NII-I and U-NII-2A bands, additional SAR test reduction applies. When band gap channels between U-NII-2C band and 5.8 GHz U-NII-3 or §15.247 band are supported, the highest maximum output power transmission mode configuration and maximum output power channel across the bands must be used to determine SAR test reduction, according to the initial test configuration and subsequent test configuration requirements. In applying the initial test configuration and subsequent test configuration procedures, the 802.11 transmission configuration with the highest specified maximum output power and the channel within a test configuration with the highest measured maximum output power should be clearly distinguished to apply the procedures.



5.2.5. U-NII-1 and U-NII-2A Bands

For devices that operate in only one of the U-NII-1 and U-NII-2A bands, the normally required SAR procedures for OFDM configurations are applied. For devices that operate in both U-NII bands using the same transmitter and antenna(s), SAR test reduction is determined according to the following:

- 1) When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition); otherwise, both bands are tested independently for SAR.
- 2) When different maximum output power is specified for the bands, begin SAR measurement in the band with higher specified maximum output power. The highest reported SAR for the tested configuration is adjusted by the ratio of lower to higher specified maximum output power for the two bands. When the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for the band with lower maximum output power in that test configuration; otherwise, both bands are tested independently for SAR.
- 3) The two U-NII bands may be aggregated to support a 160 MHz channel on channel number 50. Without additional testing, the maximum output power for this is limited to the lower of the maximum output power certified for the two bands. When SAR measurement is required for at least one of the bands and the highest reported SAR adjusted by the ratio of specified maximum output power of aggregated to standalone band is > 1.2 W/kg, SAR is required for the 160 MHz channel. This procedure does not apply to an aggregated band with maximum output higher than the standalone band(s); the aggregated band must be tested independently for SAR. SAR is not required when the 160 MHz channel is operating at a reduced maximum power and also qualifies for SAR test exclusion.

5.2.6. U-NII-2C and U-NII-3 Bands

The frequency range covered by these bands is 380 MHz (5.47-5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements. When Terminal Doppler Weather Radar (TOWR) restriction applies, the channels at 5.60-5.65 GHz in U-NII-2C band must be disabled with acceptable mechanisms and documented in the equipment certification to avoid SAR requirements. 10 TOWR restriction does not apply under the new rules; all channels that operate at 5.60-5.65 GHz must be included to apply the SAR test reduction and measurement procedures.

When the same transmitter and antenna(s) are used for U-NII-2C band and U-NII-3 band or 5.8 GHz band of §15.247, the bands may be aggregated to enable additional channels with 20, 40 or 80 MHz bandwidth to span across the band gap, as illustrated in Appendix B. The maximum output power for the additional band gap channels is limited to the power of those certified for the bands. Unless band gap channels are permanently disabled, they must be considered for SAR testing. The frequency range covered by these bands is 380 MHz (5.47-5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements. To maintain SAR measurement accuracy and to facilitate test reduction, the channels in U-NII-2C band above 5.65 GHz may be grouped with the 5.8 GHz channels in U-NII-3 or §15.247 band to enable two SAR probe calibration frequency points to cover the bands, including the band gap channels. 11 When band gap channels are supported and the bands are not aggregated for SAR testing, band gap channels must be considered independently in each band according to the normally required OFDM SAR measurement and probe calibration frequency points requirements.





5.2.7. OFDM Transmission Mode SAR Test Channel Selection Requirements

For 2.4 GHz and 5 GHz bands, When the same maximum output power was specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration with the largest channel bandwidth, lowest order modulation and lowest data rate. When the maximum output power of a channel is the same for equivalent OFDM configurations (for example 802.11a, 802.11n and 802.11ac, or 802.11g and 802.11n, with the same channel bandwidth, modulation, and data rate, etc), the lower order 802.11 mode (i.e., 802.11a is chosen over 802.11n then 802.11ac, or 802.11g is chosen over 802.11n) is used for SAR measurement.

When the maximum output power are the same for multiple test channel, either according to the default or additional power measurement requirement, SAR is measured using the channel closest to the middle of the frequency band or aggregated band. When there are multiple channels with the same maximum output power, SAR is measured using the higher number channel.

5.3. Power Reduction

The product without any power reduction.

5.4. Power Drift

To control the output power stability during the SAR test, SAR system calculates the power drift by measuring the E-field at the same location at the beginning and at the end of the measurement for each test position. This ensures that the power drift during one measurement is within $\pm 0.2\text{dB}$.





6. TEST CONDITIONS AND RESULTS

6.1. Conducted Power Results

According KDB 447498 D01 General RF Exposure Guidance v06 Section 4.1 2) states that “Unless it is specified differently in the published RF exposure KDB procedures, these requirements also apply to test reduction and test exclusion considerations. Time-averaged maximum conducted output power applies to SAR and, as required by § 2.1091(c), time-averaged ERP applies to MPE. When an antenna port is not available on the device to support conducted power measurement, such as FRS and certain Part 15 transmitters with built-in integral antennas, the maximum output power allowed for production units should be used to determine RF exposure test exclusion and compliance.”

6.1.1. Peak Conducted Power Measurement Results(WIFI 2.4G)

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Tune Up (dBm)
NVNT	b	2412	Ant0	15.66	16.00
NVNT	b	2437	Ant0	15.56	16.00
NVNT	b	2462	Ant0	15.35	16.00
NVNT	g	2412	Ant0	14.15	15.00
NVNT	g	2437	Ant0	13.91	14.00
NVNT	g	2462	Ant0	13.87	14.00
NVNT	n20	2412	Ant0	13.65	14.00
NVNT	n20	2437	Ant0	13.54	14.00
NVNT	n20	2462	Ant0	13.38	14.00
NVNT	n40	2422	Ant0	11.96	12.00
NVNT	n40	2437	Ant0	12.44	13.00
NVNT	n40	2452	Ant0	11.92	12.00
NVNT	ax20	2412	Ant0	13.57	14.00
NVNT	ax20	2437	Ant0	13.46	14.00
NVNT	ax20	2462	Ant0	13.3	14.00
NVNT	ax40	2422	Ant0	11.94	12.00
NVNT	ax40	2437	Ant0	12.2	13.00
NVNT	ax40	2452	Ant0	12.8	13.00

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Tune Up (dBm)
NVNT	b	2412	Ant1	14.86	15.00
NVNT	b	2437	Ant1	14.77	15.00
NVNT	b	2462	Ant1	14.55	15.00
NVNT	g	2412	Ant1	13.27	14.00
NVNT	g	2437	Ant1	13.06	14.00
NVNT	g	2462	Ant1	12.98	13.00
NVNT	n20	2412	Ant1	12.54	13.00
NVNT	n20	2437	Ant1	12.26	13.00
NVNT	n20	2462	Ant1	12.24	13.00
NVNT	n40	2422	Ant1	11.17	12.00
NVNT	n40	2437	Ant1	11.42	12.00
NVNT	n40	2452	Ant1	11.02	12.00
NVNT	ax20	2412	Ant1	12.31	13.00
NVNT	ax20	2437	Ant1	12.03	13.00
NVNT	ax20	2462	Ant1	12.02	13.00
NVNT	ax40	2422	Ant1	10.92	11.00
NVNT	ax40	2437	Ant1	11.23	12.00
NVNT	ax40	2452	Ant1	11.85	12.00



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



MIMO


Condition	Mode	Frequency (MHz)	Total Power (dBm)		
			Ant0	Ant1	Ant0+Ant1
NVNT	n20	2412	13.65	12.54	16.14
NVNT	n20	2437	13.54	12.26	15.96
NVNT	n20	2462	13.38	12.24	15.86
NVNT	n40	2422	11.96	11.17	14.59
NVNT	n40	2437	12.44	11.42	14.97
NVNT	n40	2452	11.92	11.02	14.50
NVNT	ax20	2412	13.57	12.31	16.00
NVNT	ax 20	2437	13.46	12.03	15.81
NVNT	ax 20	2462	13.3	12.02	15.72
NVNT	ax 40	2422	11.94	10.92	14.47
NVNT	ax 40	2437	12.2	11.23	14.75
NVNT	ax 40	2452	12.8	11.85	15.36

Note:

- a) Power must be measured at each transmit antenna port according to the DSSS and OFDM transmission configurations in each standalone and aggregated frequency band.
- b) Power measurement is required for the transmission mode configuration with the highest maximum output power specified for production units.
 - 1) When the same highest maximum output power specification applies to multiple transmission modes, the largest channel bandwidth configuration with the lowest order modulation and lowest data rate is measured.
 - 2) When the same highest maximum output power is specified for multiple largest channel bandwidth configurations with the same lowest order modulation or lowest order modulation and lowest data rate, power measurement is required for all equivalent 802.11 configurations with the same maximum output power.
- c) For each transmission mode configuration, power must be measured for the highest and lowest channels; and at the mid-band channel(s) when there are at least 3 channels. For configurations with multiple mid-band channels, due to an even number of channels, both channels should be measured.


ANT0:WIFI 2.4G (802.11b):

Duty cycle=99.16%



ANT1:WIFI 2.4G (802.11b):

Duty cycle=99.16%





6.1.2. Conducted Power Measurement Results(WIFI 5.2G)

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Power (dBm)	Tune Up (dBm)
NVNT	a	5180	Ant0	12.63	0.24	12.87	13.00
NVNT	a	5200	Ant0	12.5	0.24	12.74	13.00
NVNT	a	5240	Ant0	12.98	0.24	13.22	14.00
NVNT	n20	5180	Ant0	11.02	0.12	11.14	12.00
NVNT	n20	5200	Ant0	10.88	0.12	11	12.00
NVNT	n20	5240	Ant0	11.79	0.12	11.91	12.00
NVNT	n40	5190	Ant0	10.83	0.12	10.95	11.00
NVNT	n40	5230	Ant0	10.84	0.12	10.96	11.00
NVNT	ac20	5180	Ant0	11.26	0.12	11.38	12.00
NVNT	ac20	5200	Ant0	10.87	0.12	10.99	11.00
NVNT	ac20	5240	Ant0	11.91	0.12	12.03	12.50
NVNT	ac40	5190	Ant0	9.75	0.12	9.87	10.00
NVNT	ac40	5230	Ant0	10.77	0.12	10.89	11.00
NVNT	ac80	5210	Ant0	8.9	0.25	9.15	10.00
NVNT	ax20	5180	Ant0	11.51	0.12	11.63	12.00
NVNT	ax20	5200	Ant0	11.41	0.12	11.53	12.00
NVNT	ax20	5240	Ant0	10.91	0.12	11.03	12.00
NVNT	ax40	5190	Ant0	10.09	0.12	10.21	11.00
NVNT	ax40	5230	Ant0	9.92	0.12	10.04	11.00
NVNT	ax80	5210	Ant0	9.39	0.25	9.64	10.00

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Power (dBm)	Tune Up (dBm)
NVNT	a	5180	Ant1	11.86	0.24	12.1	13.00
NVNT	a	5200	Ant1	11.74	0.24	11.98	12.00
NVNT	a	5240	Ant1	10.4	0.24	10.64	11.00
NVNT	n20	5180	Ant1	10.33	0.12	10.45	11.00
NVNT	n20	5200	Ant1	9.93	0.12	10.05	11.00
NVNT	n20	5240	Ant1	10.82	0.12	10.94	11.00
NVNT	n40	5190	Ant1	8.85	0.12	8.97	9.00
NVNT	n40	5230	Ant1	9.85	0.12	9.97	10.00
NVNT	ac20	5180	Ant1	10.38	0.12	10.5	11.00
NVNT	ac20	5200	Ant1	10.23	0.12	10.35	11.00
NVNT	ac20	5240	Ant1	10.93	0.12	11.05	12.00
NVNT	ac40	5190	Ant1	8.77	0.12	8.89	9.00
NVNT	ac40	5230	Ant1	9.8	0.12	9.92	10.00
NVNT	ac80	5210	Ant1	8.91	0.25	9.16	10.00
NVNT	ax20	5180	Ant1	10.44	0.12	10.56	11.00
NVNT	ax20	5200	Ant1	10.38	0.12	10.5	11.00
NVNT	ax20	5240	Ant1	10.02	0.12	10.14	11.00
NVNT	ax40	5190	Ant1	9.02	0.24	9.26	10.00
NVNT	ax40	5230	Ant1	9.12	0.24	9.36	10.00
NVNT	ax80	5210	Ant1	8.28	0.47	8.75	9.00





MIMO

Condition	Mode	Frequency (MHz)	Antenna		Total Power (dBm)
			Ant0	Ant1	
NVNT	n20	5180	11.14	10.45	13.82
NVNT	n20	5200	11	10.05	13.56
NVNT	n20	5240	11.91	10.94	14.46
NVNT	n40	5190	10.95	8.97	13.08
NVNT	n40	5230	10.96	9.97	13.50
NVNT	ac20	5180	11.38	10.5	13.97
NVNT	ac20	5200	10.99	10.35	13.69
NVNT	ac20	5240	12.03	11.05	14.58
NVNT	ac40	5190	9.87	8.89	12.42
NVNT	ac40	5230	10.89	9.92	13.44
NVNT	ac80	5210	9.15	9.16	12.17
NVNT	ax20	5180	11.63	10.56	14.14
NVNT	ax20	5200	11.53	10.5	14.06
NVNT	ax20	5240	11.03	10.14	13.62
NVNT	ax40	5190	10.21	9.26	12.77
NVNT	ax40	5230	10.04	9.36	12.72
NVNT	ax80	5210	9.64	8.75	12.23

Note:



- a) Power must be measured at each transmit antenna port according to the DSSS and OFDM transmission configurations in each standalone and aggregated frequency band.
- b) Power measurement is required for the transmission mode configuration with the highest maximum output power specified for production units.
 - 1) When the same highest maximum output power specification applies to multiple transmission modes, the largest channel bandwidth configuration with the lowest order modulation and lowest data rate is measured.
 - 2) When the same highest maximum output power is specified for multiple largest channel bandwidth configurations with the same lowest order modulation or lowest order modulation and lowest data rate, power measurement is required for all equivalent 802.11 configurations with the same maximum output power.
- c) For each transmission mode configuration, power must be measured for the highest and lowest channels; and at the mid-band channel(s) when there are at least 3 channels. For configurations with multiple mid-band channels, due to an even number of channels, both channels should be measured.

ANT0:WIFI 5.2G (802.11a):

Duty cycle= 94.56%

ANT1:WIFI 5.2G (802.11a):

Duty cycle= 94.56%





6.1.3. Conducted Power Measurement Results(WIFI 5.3G)

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Power (dBm)	Tune Up(dBm)
NVNT	a	5260	Ant0	12.43	0.24	12.67	13.00
NVNT	a	5300	Ant0	12.62	0.24	12.86	13.00
NVNT	a	5320	Ant0	12.95	0.24	13.19	14.00
NVNT	n20	5260	Ant0	11.61	0.12	11.73	12.00
NVNT	n20	5300	Ant0	11.01	0.12	11.13	12.00
NVNT	n20	5320	Ant0	11.49	0.12	11.61	12.00
NVNT	n40	5270	Ant0	10.44	0.12	10.56	11.00
NVNT	n40	5310	Ant0	10.1	0.12	10.22	11.00
NVNT	ac20	5260	Ant0	11.62	0.12	11.74	12.00
NVNT	ac20	5300	Ant0	11.07	0.12	11.19	12.00
NVNT	ac20	5320	Ant0	11.41	0.12	11.53	12.00
NVNT	ac40	5270	Ant0	10.49	0.12	10.61	11.00
NVNT	ac40	5310	Ant0	10.11	0.12	10.23	11.00
NVNT	ac80	5290	Ant0	9.76	0.25	10.01	11.00
NVNT	ax20	5260	Ant0	11.59	0.12	11.71	12.00
NVNT	ax20	5300	Ant0	11.46	0.12	11.58	12.00
NVNT	ax20	5320	Ant0	11.59	0.12	11.71	12.00
NVNT	ax40	5270	Ant0	10.39	0.24	10.63	11.00
NVNT	ax40	5310	Ant0	10.87	0.24	11.11	12.00
NVNT	ax80	5290	Ant0	9.42	0.47	9.89	10.00

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Power (dBm)	Tune Up(dBm)
NVNT	a	5260	Ant1	11.16	0.24	11.4	12.00
NVNT	a	5300	Ant1	11.5	0.24	11.74	12.00
NVNT	a	5320	Ant1	11.82	0.24	12.06	13.00
NVNT	n20	5260	Ant1	10.49	0.12	10.61	11.00
NVNT	n20	5300	Ant1	10.95	0.12	11.07	12.00
NVNT	n20	5320	Ant1	10.12	0.12	10.24	11.00
NVNT	n40	5270	Ant1	9.09	0.12	9.21	10.00
NVNT	n40	5310	Ant1	9.69	0.12	9.81	10.00
NVNT	ac20	5260	Ant1	10.52	0.12	10.64	11.00
NVNT	ac20	5300	Ant1	10.88	0.12	11	12.00
NVNT	ac20	5320	Ant1	10.12	0.12	10.24	11.00
NVNT	ac40	5270	Ant1	9.12	0.12	9.24	10.00
NVNT	ac40	5310	Ant1	8.94	0.12	9.06	10.00
NVNT	ac80	5290	Ant1	7.59	0.25	7.84	8.00
NVNT	ax20	5260	Ant1	10.62	0.12	10.74	11.00
NVNT	ax20	5300	Ant1	10.02	0.12	10.14	11.00
NVNT	ax20	5320	Ant1	10.17	0.12	10.29	11.00
NVNT	ax40	5270	Ant1	9.08	0.24	9.32	10.00
NVNT	ax40	5310	Ant1	9.99	0.24	10.23	11.00
NVNT	ax80	5290	Ant1	8.54	0.47	9.01	10.00





MIMO

Condition	Mode	Frequency (MHz)	Total Power (dBm)		
			Ant0	Ant1	Ant0+Ant1
NVNT	n20	5260	11.73	10.61	14.22
NVNT	n20	5300	11.13	11.07	14.11
NVNT	n20	5320	11.61	10.24	13.99
NVNT	n40	5270	10.56	9.21	12.95
NVNT	n40	5310	10.22	9.81	13.03
NVNT	ac20	5260	11.74	10.64	14.24
NVNT	ac20	5300	11.19	11	14.11
NVNT	ac20	5320	11.53	10.24	13.94
NVNT	ac40	5270	10.61	9.24	12.99
NVNT	ac40	5310	10.23	9.06	12.69
NVNT	ac80	5290	10.01	7.84	12.07
NVNT	ax20	5260	11.71	10.74	14.26
NVNT	ax20	5300	11.58	10.14	13.93
NVNT	ax20	5320	11.71	10.29	14.07
NVNT	ax40	5270	10.63	9.32	13.03
NVNT	ax40	5310	11.11	10.23	13.70
NVNT	ax80	5290	9.89	9.01	12.48

Note:


- a) Power must be measured at each transmit antenna port according to the DSSS and OFDM transmission configurations in each standalone and aggregated frequency band.
- b) Power measurement is required for the transmission mode configuration with the highest maximum output power specified for production units.
 - 1) When the same highest maximum output power specification applies to multiple transmission modes, the largest channel bandwidth configuration with the lowest order modulation and lowest data rate is measured.
 - 2) When the same highest maximum output power is specified for multiple largest channel bandwidth configurations with the same lowest order modulation or lowest order modulation and lowest data rate, power measurement is required for all equivalent 802.11 configurations with the same maximum output power.
- c) For each transmission mode configuration, power must be measured for the highest and lowest channels; and at the mid-band channel(s) when there are at least 3 channels. For configurations with multiple mid-band channels, due to an even number of channels, both channels should be measured.

ANT0:WIFI 5.3G (802.11a):

Duty cycle=94.65%

ANT1:WIFI 5.3G (802.11a):

Duty cycle=94.56%



**6.1.4. Conducted Power Measurement Results(WIFI 5.5G)**

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Power (dBm)	Tune Up(dBm)
NVNT	a	5500	Ant0	12.17	0.24	12.41	13.00
NVNT	a	5580	Ant0	12.46	0.24	12.7	13.00
NVNT	a	5700	Ant0	12.35	0.24	12.59	13.00
NVNT	n20	5500	Ant0	11.72	0.12	11.84	12.00
NVNT	n20	5580	Ant0	11.09	0.12	11.21	12.00
NVNT	n20	5700	Ant0	10.99	0.12	11.11	12.00
NVNT	n40	5510	Ant0	10.36	0.12	10.48	11.00
NVNT	n40	5550	Ant0	10.51	0.12	10.63	11.00
NVNT	n40	5670	Ant0	10.83	0.12	10.95	11.00
NVNT	ac20	5500	Ant0	10.76	0.12	10.88	11.00
NVNT	ac20	5580	Ant0	11.06	0.12	11.18	12.00
NVNT	ac20	5700	Ant0	11	0.12	11.12	12.00
NVNT	ac40	5510	Ant0	10.25	0.12	10.37	11.00
NVNT	ac40	5550	Ant0	10.47	0.12	10.59	11.00
NVNT	ac40	5670	Ant0	10.76	0.12	10.88	11.00
NVNT	ac80	5530	Ant0	9.17	0.25	9.42	10.00
NVNT	ac80	5610	Ant0	9.46	0.25	9.71	10.00
NVNT	ax20	5500	Ant0	11.43	0.12	11.55	12.00
NVNT	ax20	5580	Ant0	10.99	0.12	11.11	12.00
NVNT	ax20	5700	Ant0	11.78	0.12	11.9	12.00
NVNT	ax40	5510	Ant0	10.17	0.12	10.29	11.00
NVNT	ax40	5550	Ant0	10.46	0.12	10.58	11.00
NVNT	ax40	5670	Ant0	10.93	0.12	11.05	12.00
NVNT	ax80	5530	Ant0	9.07	0.25	9.32	10.00
NVNT	ax80	5610	Ant0	9.24	0.25	9.49	10.00

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Power (dBm)	Tune Up(dBm)
NVNT	a	5500	Ant1	11.66	0.24	11.9	12.00
NVNT	a	5580	Ant1	11.91	0.24	12.15	13.00
NVNT	a	5700	Ant1	11.46	0.24	11.7	12.00
NVNT	n20	5500	Ant1	10.91	0.12	11.03	12.00
NVNT	n20	5580	Ant1	10.02	0.12	10.14	11.00
NVNT	n20	5700	Ant1	9.95	0.12	10.07	11.00
NVNT	n40	5510	Ant1	9.21	0.12	9.33	10.00
NVNT	n40	5550	Ant1	9.35	0.12	9.47	10.00
NVNT	n40	5670	Ant1	9.69	0.12	9.81	10.00
NVNT	ac20	5500	Ant1	10.79	0.12	10.91	11.00
NVNT	ac20	5580	Ant1	9.95	0.12	10.07	11.00
NVNT	ac20	5700	Ant1	9.96	0.12	10.08	11.00
NVNT	ac40	5510	Ant1	9.21	0.12	9.33	10.00
NVNT	ac40	5550	Ant1	9.46	0.12	9.58	10.00
NVNT	ac40	5670	Ant1	9.71	0.12	9.83	10.00
NVNT	ac80	5530	Ant1	8.22	0.25	8.47	9.00
NVNT	ac80	5610	Ant1	8.34	0.25	8.59	9.00
NVNT	ax20	5500	Ant1	10.44	0.12	10.56	11.00
NVNT	ax20	5580	Ant1	9.9	0.12	10.02	11.00
NVNT	ax20	5700	Ant1	10.77	0.12	10.89	11.00
NVNT	ax40	5510	Ant1	8.86	0.24	9.1	10.00
NVNT	ax40	5550	Ant1	9.26	0.24	9.5	10.00
NVNT	ax40	5670	Ant1	9.19	0.24	9.43	10.00
NVNT	ax80	5530	Ant1	8.29	0.25	8.54	9.00
NVNT	ax80	5610	Ant1	8.46	0.25	8.71	9.00





MIMO

Condition	Mode	Frequency (MHz)	Total Power (dBm)		
			Ant0	Ant1	Ant0+Ant1
NVNT	n20	5500	11.84	11.03	14.46
NVNT	n20	5580	11.21	10.14	13.72
NVNT	n20	5700	11.11	10.07	13.63
NVNT	n40	5510	10.48	9.33	12.95
NVNT	n40	5550	10.63	9.47	13.10
NVNT	n40	5670	10.95	9.81	13.43
NVNT	ac20	5500	10.88	10.91	13.91
NVNT	ac20	5580	11.18	10.07	13.67
NVNT	ac20	5700	11.12	10.08	13.64
NVNT	ac40	5510	10.37	9.33	12.89
NVNT	ac40	5550	10.59	9.58	13.12
NVNT	ac40	5670	10.88	9.83	13.40
NVNT	ac80	5530	9.42	8.47	11.98
NVNT	ac80	5610	9.71	8.59	12.20
NVNT	ax20	5500	11.55	10.56	14.09
NVNT	ax20	5580	11.11	10.02	13.61
NVNT	ax20	5700	11.9	10.89	14.43
NVNT	ax40	5510	10.29	9.1	12.75
NVNT	ax40	5550	10.58	9.5	13.08
NVNT	ax40	5670	11.05	9.43	13.33
NVNT	ax80	5530	9.32	8.54	11.96
NVNT	ax80	5610	9.49	8.71	12.13

Note:

- a) Power must be measured at each transmit antenna port according to the DSSS and OFDM transmission configurations in each standalone and aggregated frequency band.
- b) Power measurement is required for the transmission mode configuration with the highest maximum output power specified for production units.
 - 1) When the same highest maximum output power specification applies to multiple transmission modes, the largest channel bandwidth configuration with the lowest order modulation and lowest data rate is measured.
 - 2) When the same highest maximum output power is specified for multiple largest channel bandwidth configurations with the same lowest order modulation or lowest order modulation and lowest data rate, power measurement is required for all equivalent 802.11 configurations with the same maximum output power.
- c) For each transmission mode configuration, power must be measured for the highest and lowest channels; and at the mid-band channel(s) when there are at least 3 channels. For configurations with multiple mid-band channels, due to an even number of channels, both channels should be measured.

ANT0:WIFI 5.5G (802.11a):

Duty cycle= 94.65%

ANT1:WIFI 5.5G (802.11a):

Duty cycle= 94.65%





6.1.5. Conducted Power Measurement Results(WIFI 5.8G)

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Power (dBm)	Tune Up(dBm)
NVNT	a	5745	Ant0	12.5	0.24	12.74	13.00
NVNT	a	5785	Ant0	12.62	0.24	12.86	13.00
NVNT	a	5825	Ant0	12.15	0.24	12.39	13.00
NVNT	n20	5745	Ant0	11.95	0.12	12.07	13.00
NVNT	n20	5785	Ant0	11.19	0.12	11.31	12.00
NVNT	n20	5825	Ant0	11.67	0.12	11.79	12.00
NVNT	n40	5755	Ant0	10.58	0.12	10.7	11.00
NVNT	n40	5795	Ant0	10.59	0.12	10.71	11.00
NVNT	ac20	5745	Ant0	10.95	0.12	11.07	12.00
NVNT	ac20	5785	Ant0	11.16	0.12	11.28	12.00
NVNT	ac20	5825	Ant0	10.75	0.12	10.87	11.00
NVNT	ac40	5755	Ant0	10.53	0.12	10.65	11.00
NVNT	ac40	5795	Ant0	9.7	0.12	9.82	10.00
NVNT	ac80	5775	Ant0	9.7	0.25	9.95	10.00
NVNT	ax20	5745	Ant0	11.69	0.12	11.81	12.00
NVNT	ax20	5785	Ant0	11.85	0.12	11.97	12.00
NVNT	ax20	5825	Ant0	11.58	0.12	11.7	12.00
NVNT	ax40	5755	Ant0	10.29	0.24	10.53	11.00
NVNT	ax40	5795	Ant0	10.46	0.24	10.7	11.00
NVNT	ax80	5775	Ant0	9.55	0.25	9.8	10.00

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Power (dBm)	Tune Up(dBm)
NVNT	a	5745	Ant1	11.59	0.24	11.83	12.00
NVNT	a	5785	Ant1	10.88	0.24	11.12	12.00
NVNT	a	5825	Ant1	10.33	0.24	10.57	11.00
NVNT	n20	5745	Ant1	9.95	0.12	10.07	11.00
NVNT	n20	5785	Ant1	10.28	0.12	10.4	11.00
NVNT	n20	5825	Ant1	9.8	0.12	9.92	10.00
NVNT	n40	5755	Ant1	9.53	0.12	9.65	10.00
NVNT	n40	5795	Ant1	9.65	0.12	9.77	10.00
NVNT	ac20	5745	Ant1	9.93	0.12	10.05	11.00
NVNT	ac20	5785	Ant1	10.28	0.12	10.4	11.00
NVNT	ac20	5825	Ant1	9.84	0.12	9.96	10.00
NVNT	ac40	5755	Ant1	9.58	0.12	9.7	10.00
NVNT	ac40	5795	Ant1	9.67	0.12	9.79	10.00
NVNT	ac80	5775	Ant1	8.72	0.25	8.97	9.00
NVNT	ax20	5745	Ant1	10.83	0.12	10.95	11.00
NVNT	ax20	5785	Ant1	10.07	0.12	10.19	11.00
NVNT	ax20	5825	Ant1	10.66	0.12	10.78	11.00
NVNT	ax40	5755	Ant1	9.21	0.24	9.45	10.00
NVNT	ax40	5795	Ant1	9.48	0.24	9.72	10.00
NVNT	ax80	5775	Ant1	8.31	0.47	8.78	9.00





MIMO


Condition	Mode	Frequency (MHz)	Antenna		
			Ant0	Ant1	Ant0+Ant1
NVNT	n20	5745	12.07	10.07	14.19
NVNT	n20	5785	11.31	10.4	13.89
NVNT	n20	5825	11.79	9.92	13.97
NVNT	n40	5755	10.7	9.65	13.22
NVNT	n40	5795	10.71	9.77	13.28
NVNT	ac20	5745	11.07	10.05	13.60
NVNT	ac20	5785	11.28	10.4	13.87
NVNT	ac20	5825	10.87	9.96	13.45
NVNT	ac40	5755	10.65	9.7	13.21
NVNT	ac40	5795	9.82	9.79	12.82
NVNT	ac80	5775	9.95	8.97	12.50
NVNT	ax20	5745	11.81	10.95	14.41
NVNT	ax20	5785	11.97	10.19	14.18
NVNT	ax20	5825	11.7	10.78	14.27
NVNT	ax40	5755	10.53	9.45	13.03
NVNT	ax40	5795	10.7	9.72	13.25
NVNT	ax80	5775	9.8	8.78	12.33

Note:

- a) Power must be measured at each transmit antenna port according to the DSSS and OFDM transmission configurations in each standalone and aggregated frequency band.
- b) Power measurement is required for the transmission mode configuration with the highest maximum output power specified for production units.
 - 1) When the same highest maximum output power specification applies to multiple transmission modes, the largest channel bandwidth configuration with the lowest order modulation and lowest data rate is measured.
 - 2) When the same highest maximum output power is specified for multiple largest channel bandwidth configurations with the same lowest order modulation or lowest order modulation and lowest data rate, power measurement is required for all equivalent 802.11 configurations with the same maximum output power.
- c) For each transmission mode configuration, power must be measured for the highest and lowest channels; and at the mid-band channel(s) when there are at least 3 channels. For configurations with multiple mid-band channels, due to an even number of channels, both channels should be measured.


ANT0:WIFI 5.8G (802.11a):

Duty cycle =94.56%



ANT1:WIFI 5.8G (802.11a):

Duty cycle =94.56%





6.1.6. Peak Conducted Power Measurement Results(Bluetooth)

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Tune Up (dBm)
NVNT	1-DH5	2402	Ant0	-0.5	0.00
NVNT	1-DH5	2441	Ant0	-0.08	0.00
NVNT	1-DH5	2480	Ant0	1.24	2.00
NVNT	2-DH5	2402	Ant0	1.32	2.00
NVNT	2-DH5	2441	Ant0	-0.81	0.00
NVNT	2-DH5	2480	Ant0	0.55	1.00
NVNT	3-DH5	2402	Ant0	1.66	2.00
NVNT	3-DH5	2441	Ant0	-0.43	0.00
NVNT	3-DH5	2480	Ant0	0.86	1.00

BLE

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Tune Up (dBm)
NVNT	BLE 1M	2402	Ant0	0.13	1.00
NVNT	BLE 1M	2440	Ant0	0.28	1.00
NVNT	BLE 1M	2480	Ant0	-0.82	0.00
NVNT	BLE 2M	2402	Ant0	0.98	1.00
NVNT	BLE 2M	2440	Ant0	1.12	2.00
NVNT	BLE 2M	2480	Ant0	0.02	1.00



6.2. Stand-alone SAR test evaluation

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and Product specific 10g SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition is satisfied. These test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.

SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm

MHz	5	10	15	20	25	mm
150	39	77	116	155	194	SAR Test Exclusion Threshold (mW)
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	
MHz	30	35	40	45	50	
150	232	271	310	349	387	SAR Test Exclusion Threshold (mW)
300	164	192	219	246	274	
450	134	157	179	201	224	
835	98	115	131	148	164	
900	95	111	126	142	158	
1500	73	86	98	110	122	
1900	65	76	87	98	109	
2450	57	67	77	86	96	
3600	47	55	63	71	79	
5200	39	46	53	59	66	
5400	39	45	52	58	65	
5800	37	44	50	56	62	

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.



The test exclusions are applicable only when the minimum test separation distance is > 50 mm and for transmission frequencies between 100 MHz and 6 GHz.

SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and > 50 mm

MHz	50	60	70	80	90	100	110	120	130	140	150	160	170	180	190	mm
100	474	481	487	494	501	507	514	521	527	534	541	547	554	561	567	mW
150	387	397	407	417	427	437	447	457	467	477	487	497	507	517	527	
300	274	294	314	334	354	374	394	414	434	454	474	494	514	534	554	
450	224	254	284	314	344	374	404	434	464	494	524	554	584	614	644	
835	164	220	275	331	387	442	498	554	609	665	721	776	832	888	943	
900	158	218	278	338	398	458	518	578	638	698	758	818	878	938	998	
1500	122	222	322	422	522	622	722	822	922	1022	1122	1222	1322	1422	1522	
1900	109	209	309	409	509	609	709	809	909	1009	1109	1209	1309	1409	1509	
2450	96	196	296	396	496	596	696	796	896	996	1096	1196	1296	1396	1496	
3600	79	179	279	379	479	579	679	779	879	979	1079	1179	1279	1379	1479	
5200	66	166	266	366	466	566	666	766	866	966	1066	1166	1266	1366	1466	
5400	65	165	265	365	465	565	665	765	865	965	1065	1165	1265	1365	1465	
5800	62	162	262	362	462	562	662	762	862	962	1062	1162	1262	1362	1462	

According to the table above, Standalone SAR exclusion calculation for this device are as below:

ANT	Freq. Band	Frequency (MHz)	Position	Test Separation (mm)	Max Power (dBm)	Max Power (mW)	Exclusion Threshold (mW)	Exclusion (Yes/No)
ANT0	BT	2480	Front side	5	2.00	1.58	10	Yes
		2480	Rear side	5	2.00	1.58	10	Yes
		2480	Left side	5	2.00	1.58	10	Yes
		2480	Right side	335	2.00	1.58	1496	Yes
		2480	Top side	133	2.00	1.58	926	Yes
		2480	Bottom side	50	2.00	1.58	96	Yes
	Wi-Fi 2.4G	2412	Front side	5	16.00	39.81	10	No
		2412	Rear side	5	16.00	39.81	10	No
		2412	Left side	5	16.00	39.81	10	No
		2412	Right side	335	16.00	39.81	1496	Yes
		2412	Top side	133	16.00	39.81	926	Yes
		2412	Bottom side	50	16.00	39.81	96	Yes
	Wi-Fi 5.2G	5240	Front side	5	14.00	25.12	7	No
		5240	Rear side	5	14.00	25.12	7	No
		5240	Left side	5	14.00	25.12	7	No
		5240	Right side	335	14.00	25.12	1466	Yes
		5240	Top side	133	14.00	25.12	896	Yes
		5240	Bottom side	50	14.00	25.12	66	Yes
Wi-Fi 5.3G	5320	Front side	5	14.00	25.12	6	No	
	5320	Rear side	5	14.00	25.12	6	No	





	Wi-Fi 5.2G	5320	Left side	5	14.00	25.12	6	No
		5320	Right side	335	14.00	25.12	1465	Yes
		5320	Top side	133	14.00	25.12	895	Yes
		5320	Bottom side	50	14.00	25.12	65	Yes
		5580	Front side	5	13.00	19.95	6	No
		5580	Rear side	5	13.00	19.95	6	No
	Wi-Fi 5.8G	5580	Left side	5	13.00	19.95	6	No
		5580	Right side	335	13.00	19.95	1462	Yes
		5580	Top side	133	13.00	19.95	892	Yes
		5580	Bottom side	50	13.00	19.95	62	Yes
		5785	Front side	5	13.00	19.95	6	No
		5785	Rear side	5	13.00	19.95	6	No
	Wi-Fi 5.8G	5785	Left side	5	13.00	19.95	6	No
		5785	Right side	335	13.00	19.95	1462	Yes
		5785	Top side	133	13.00	19.95	892	Yes
		5785	Bottom side	50	13.00	19.95	62	Yes

ANT	Freq. Band	Frequency (MHz)	Position	Test Separation (mm)	Max Power (dBm)	Max Power (mW)	Exclusion Threshold (mW)	Exclusion (Yes/No)
ANT1	Wi-Fi 2.4G	2412	Front side	5	15.00	31.62	10	No
		2412	Rear side	5	15.00	31.62	10	No
		2412	Left side	5	15.00	31.62	10	No
		2412	Right side	335	15.00	31.62	1496	Yes
		2412	Top side	50	15.00	31.62	96	Yes
		2412	Bottom side	133	15.00	31.62	926	Yes
	Wi-Fi 5.2G	5180	Front side	5	13.00	19.95	7	No
		5180	Rear side	5	13.00	19.95	7	No
		5180	Left side	5	13.00	19.95	7	No
		5180	Right side	335	13.00	19.95	1466	Yes
		5180	Top side	50	13.00	19.95	66	Yes
		5180	Bottom side	133	13.00	19.95	896	Yes
	Wi-Fi 5.3G	5320	Front side	5	13.00	19.95	6	No
		5320	Rear side	5	13.00	19.95	6	No
		5320	Left side	5	13.00	19.95	6	No
		5320	Right side	335	13.00	19.95	1465	Yes
		5320	Top side	50	13.00	19.95	65	Yes
		5320	Bottom side	133	13.00	19.95	895	Yes
	Wi-Fi 5.5G	5580	Front side	5	13.00	19.95	6	No
		5580	Rear side	5	13.00	19.95	6	No
		5580	Left side	5	13.00	19.95	6	No
		5580	Right side	335	13.00	19.95	1462	Yes
		5580	Top side	50	13.00	19.95	62	Yes
		5580	Bottom side	133	13.00	19.95	892	Yes
	Wi-Fi 5.8G	5745	Front side	5	12.00	15.85	6	No
		5745	Rear side	5	12.00	15.85	6	No
		5745	Left side	5	12.00	15.85	6	No
		5745	Right side	335	12.00	15.85	1462	Yes
		5745	Top side	50	12.00	15.85	62	Yes



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



		5785	Bottom side	133	12.00	15.85	892	Yes
--	--	------	-------------	-----	-------	-------	-----	-----

From what is shown in the table above, we can draw the conclusion that:

ANT0	EUT Sides for SAR Testing							
	Mode	Exposure Condition	Front	Back	Left	Right	Top	Bottom
	BT	Body	N/A	No	No	No	No	No
	WIFI 2.4G	Body	Yes	Yes	Yes	No	No	No
	WIFI 5.2G	Body	Yes	Yes	Yes	No	No	No
	WIFI 5.3G	Body	Yes	Yes	Yes	No	No	No
	WIFI 5.5G	Body	Yes	Yes	Yes	No	No	No
	WIFI 5.8G	Body	Yes	Yes	Yes	No	No	No

ANT1	EUT Sides for SAR Testing							
	Mode	Exposure Condition	Front	Back	Left	Right	Top	Bottom
	WIFI 2.4G	Body	Yes	Yes	Yes	No	No	No
	WIFI 5.2G	Body	Yes	Yes	Yes	No	No	No
	WIFI 5.3G	Body	Yes	Yes	Yes	No	No	No
	WIFI 5.5G	Body	Yes	Yes	Yes	No	No	No
	WIFI 5.8G	Body	Yes	Yes	Yes	No	No	No

EUT Sides for SAR Testing.





6.3. SAR Measurement Results

The calculated SAR is obtained by the following formula:

$$\text{Reported SAR} = \text{Measured SAR} * 10^{(P_{\text{target}} - P_{\text{measured}})/10}$$

$$\text{Scaling factor} = 10^{(P_{\text{target}} - P_{\text{measured}})/10}$$

$$\text{Reported SAR} = \text{Measured SAR} * \text{Scaling factor}$$

Where

P_{target} is the power of manufacturing upper limit;

P_{measured} is the measured power;

Measured SAR is measured SAR at measured power which including power drift)

Reported SAR which including Power Drift and Scaling factor

6.3.1. SAR Results [WIFI 2.4G]

SAR Values [WIFI 2.4G]									
Ch/ Freq. (MHz)	Channel Type	Test Position	Duty Cycle Factor	Conducted Power (dBm)	Maximum Allowed Power (dBm)	PowerDrift (dB)	Scaling Factor	SAR _{1-g} results(W/kg)	
								Measured	Reported
measured / reported SAR numbers - Body (distance 0mm)ANT0									
1/2412	802.11b	Front side	1.008	15.66	16.00	0.08	1.081	0.394	0.430
1/2412	802.11b	Rear side	1.008	15.66	16.00	-0.17	1.081	0.437	0.477
1/2412	802.11b	Left side (1)	1.008	15.66	16.00	-0.03	1.081	0.348	0.380
1/2412	802.11b	Left side (2)	1.008	15.66	16.00	-0.01	1.081	0.362	0.395
1/2412	802.11b	Left side (3)	1.008	15.66	16.00	-0.05	1.081	0.388	0.423
measured / reported SAR numbers - Body (distance 0mm) ANT1									
1/2412	802.11b	Front side	1.008	14.86	15.00	-0.02	1.033	0.324	0.337
1/2412	802.11b	Rear side	1.008	14.86	15.00	-0.14	1.033	0.363	0.378
1/2412	802.11b	Left side (1)	1.008	14.86	15.00	-0.19	1.033	0.289	0.301
1/2412	802.11b	Left side (2)	1.008	14.86	15.00	-0.03	1.033	0.254	0.265
1/2412	802.11b	Left side (3)	1.008	14.86	15.00	0.05	1.033	0.311	0.324

Note:

- 1) The maximum Scaled SAR value is marked in bold. Graph results refer to Appendix B.
- 2) When the highest reported SAR for the initial test configuration is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR test for the other 802.11 modes are not required.
- 3) We have consulted FCC officials for testing according to DKB484321 test method





6.3.2. SAR Results [WIFI 5.2G]

SAR Values [WIFI 5.2G]									
Ch/ Freq. (MHz)	Channel Type	Test Position	Duty Cycle Factor	Conducted Power (dBm)	Maximum Allowed Power (dBm)	PowerDrift (dB)	Scaling Factor	SAR _{1-g} results(W/kg)	
								Measured	Reported
measured / reported SAR numbers - Body (distance 0mm))ANT0									
48/5240	802.11a	Front side	1.058	13.22	14.00	-0.11	1.197	0.333	0.421
48/5240	802.11a	Rear side	1.058	13.22	14.00	-0.18	1.197	0.365	0.462
48/5240	802.11a	Left side (1)	1.058	13.22	14.00	-0.09	1.197	0.254	0.321
48/5240	802.11a	Left side (2)	1.058	13.22	14.00	-0.16	1.197	0.268	0.339
48/5240	802.11a	Left side (3)	1.058	13.22	14.00	0.08	1.197	0.302	0.382
measured / reported SAR numbers - Body (distance 0mm))ANT1									
36/5180	802.11a	Front side	1.058	12.10	13.00	0.17	1.230	0.243	0.315
36/5180	802.11a	Rear side	1.058	12.10	13.00	0.15	1.230	0.277	0.360
36/5180	802.11a	Left side (1)	1.058	12.10	13.00	0.20	1.230	0.212	0.276
36/5180	802.11a	Left side (2)	1.058	12.10	13.00	0.01	1.230	0.201	0.262
36/5180	802.11a	Left side (3)	1.058	12.10	13.00	0.04	1.230	0.236	0.307

Note:

- 1) The maximum Scaled SAR value is marked in bold. Graph results refer to Appendix B.
- 2) When the highest reported SAR for the initial test configuration is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR test for the other 802.11 modes are not required
- 3) When multiple transmission modes (802.11a/g/n/ac) have the same specified maximum output power, largest channel bandwidth, lowest order modulation and lowest data rate, the lowest order 802.11 mode is selected; i.e., 802.11a is chosen over 802.11n then 802.11ac or 802.11g is chosen over 802.11n.
- 4) We have consulted FCC officials for testing according to DKB484321 test method

6.3.3. SAR Results [WIFI 5.3G]

SAR Values [WIFI 5.3G]									
Ch/ Freq. (MHz)	Channel Type	Test Position	Duty Cycle Factor	Conducted Power (dBm)	Maximum Allowed Power (dBm)	PowerDrift (dB)	Scaling Factor	SAR _{1-g} results(W/kg)	
								Measured	Reported
measured / reported SAR numbers - Body (distance 0mm))ANT0									
64/5320	802.11a	Front side	1.057	13.19	14.00	-0.09	1.205	0.332	0.423
64/5320	802.11a	Rear side	1.057	13.19	14.00	-0.11	1.205	0.341	0.434
64/5320	802.11a	Left side (1)	1.057	13.19	14.00	-0.12	1.205	0.269	0.342
64/5320	802.11a	Left side (2)	1.057	13.19	14.00	-0.05	1.205	0.287	0.365
64/5320	802.11a	Left side (3)	1.057	13.19	14.00	-0.17	1.205	0.311	0.396
measured / reported SAR numbers - Body (distance 0mm))ANT1									
64/5320	802.11a	Front side	1.058	12.06	13.00	0.01	1.242	0.222	0.292
64/5320	802.11a	Rear side	1.058	12.06	13.00	-0.18	1.242	0.252	0.331
64/5320	802.11a	Left side (1)	1.058	12.06	13.00	-0.07	1.242	0.208	0.273
64/5320	802.11a	Left side (2)	1.058	12.06	13.00	-0.15	1.242	0.198	0.260
64/5320	802.11a	Left side (3)	1.058	12.06	13.00	0.02	1.242	0.220	0.289

Note:

- 1) The maximum Scaled SAR value is marked in bold. Graph results refer to Appendix B.





- 2) When the highest reported SAR for the initial test configuration is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR test for the other 802.11 modes are not required
- 3) When multiple transmission modes (802.11a/g/n/ac) have the same specified maximum output power, largest channel bandwidth, lowest order modulation and lowest data rate, the lowest order 802.11 mode is selected; i.e., 802.11a is chosen over 802.11n then 802.11ac or 802.11g is chosen over 802.11n.
- 4) We have consulted FCC officials for testing according to DKB484321 test method

6.3.4. SAR Results [WIFI 5.5G]

SAR Values [WIFI 5.5G]									
Ch/ Freq. (MHz)	Channel Type	Test Position	Duty Cycle Factor	Conducted Power (dBm)	Maximum Allowed Power (dBm)	PowerDrift (dB)	Scaling Factor	SAR _{1-g} results(W/kg)	
								Measured	Reported
measured / reported SAR numbers - Body (distance 0mm))ANT0									
116/5580	802.11a	Front side	1.057	12.70	13.00	-0.07	1.072	0.261	0.295
116/5580	802.11a	Rear side	1.057	12.70	13.00	-0.15	1.072	0.299	0.338
116/5580	802.11a	Left side (1)	1.057	12.70	13.00	-0.11	1.072	0.201	0.228
116/5580	802.11a	Left side (2)	1.057	12.70	13.00	-0.12	1.072	0.226	0.256
116/5580	802.11a	Left side (3)	1.057	12.70	13.00	0.04	1.072	0.254	0.288
measured / reported SAR numbers - Body (distance 0mm))ANT1									
116/5580	802.11a	Front side	1.057	12.15	13.00	-0.06	1.216	0.222	0.285
116/5580	802.11a	Rear side	1.057	12.15	13.00	-0.19	1.216	0.254	0.326
116/5580	802.11a	Left side (1)	1.057	12.15	13.00	-0.02	1.216	0.194	0.249
116/5580	802.11a	Left side (2)	1.057	12.15	13.00	-0.18	1.216	0.174	0.224
116/5580	802.11a	Left side (3)	1.057	12.15	13.00	-0.07	1.216	0.206	0.265

Note:

- 1) The maximum Scaled SAR value is marked in bold. Graph results refer to Appendix B.
- 2) When the highest reported SAR for the initial test configuration is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR test for the other 802.11 modes are not required
- 3) When multiple transmission modes (802.11a/g/n/ac) have the same specified maximum output power, largest channel bandwidth, lowest order modulation and lowest data rate, the lowest order 802.11 mode is selected; i.e., 802.11a is chosen over 802.11n then 802.11ac or 802.11g is chosen over 802.11n.
- 4) We have consulted FCC officials for testing according to DKB484321 test method



**6.3.5. SAR Results [WIFI 5.8G]**

SAR Values [WIFI 5.8G]									
Ch/ Freq. (MHz)	Channel Type	Test Position	Duty Cycle Factor	Conducted Power (dBm)	Maximum Allowed Power (dBm)	PowerDrift (dB)	Scaling Factor	SAR _{1-g} results(W/kg)	
								Measured	Reported
measured / reported SAR numbers - Body (distance 0mm))ANT0									
157/5785	802.11a	Front side	1.058	12.86	13.00	0.05	1.033	0.254	0.277
157/5785	802.11a	Rear side	1.058	12.86	13.00	-0.18	1.033	0.300	0.328
157/5785	802.11a	Left side (1)	1.058	12.86	13.00	-0.11	1.033	0.195	0.213
157/5785	802.11a	Left side (2)	1.058	12.86	13.00	-0.19	1.033	0.235	0.257
157/5785	802.11a	Left side (3)	1.058	12.86	13.00	-0.03	1.033	0.248	0.271
measured / reported SAR numbers - Body (distance 0mm))ANT1									
149/5745	802.11a	Front side	1.058	11.83	12.00	-0.01	1.040	0.194	0.213
149/5745	802.11a	Rear side	1.058	11.83	12.00	-0.14	1.040	0.222	0.244
149/5745	802.11a	Left side (1)	1.058	11.83	12.00	0.01	1.040	0.163	0.179
149/5745	802.11a	Left side (2)	1.058	11.83	12.00	-0.03	1.040	0.125	0.137
149/5745	802.11a	Left side (3)	1.058	11.83	12.00	-0.02	1.040	0.187	0.206

Note:

- 1) The maximum Scaled SAR value is marked in bold. Graph results refer to Appendix B.
- 2) When the highest reported SAR for the initial test configuration is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR test for the other 802.11 modes are not required
- 3) When multiple transmission modes (802.11a/g/n/ac) have the same specified maximum output power, largest channel bandwidth, lowest order modulation and lowest data rate, the lowest order 802.11 mode is selected; i.e., 802.11a is chosen over 802.11n then 802.11ac or 802.11g is chosen over 802.11n.
- 4) We have consulted FCC officials for testing according to DKB484321 test method





6.4. Multiple Transmitter Evaluation

6.4.1. Simultaneous SAR SAR test evaluation

NO.	Simultaneous Tx Combination	Body
1	WiFi 2.4G Ant0+WiFi 2.4G Ant1	Yes
2	WiFi 5.2G Ant0+WiFi 5.2G Ant1	Yes
3	WiFi 5.3G Ant0+WiFi 5.3G Ant1	Yes
4	WiFi 5.5G Ant0+WiFi 5.5G Ant1	Yes
5	WiFi 5.8G Ant0+WiFi 5.8G Ant1	Yes
6	WiFi 2.4G Ant1+Bluetooth Ant0	Yes
7	WiFi 5.2G Ant1+Bluetooth Ant0	Yes
8	WiFi 5.3G Ant1+Bluetooth Ant0	Yes
9	WiFi 5.5G Ant1+Bluetooth Ant0	Yes
10	WiFi 5.8G Ant1+Bluetooth Ant0	Yes

Note:

- 1) The device does not support DTM function.





6.4.2. Estimated SAR

When the standalone SAR test exclusion is applied to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to the following to determine simultaneous transmission SAR test exclusion:

• $(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm}) \cdot [\sqrt{f(\text{GHz})/x}] \text{ W/kg}$ for test separation distances $\leq 50 \text{ mm}$;

Where $x = 7.5$ for 1-g SAR, and $x = 18.75$ for 10-g SAR.

When the minimum test separation distance is $< 5 \text{ mm}$, a distance of 5 mm is applied to determine SAR test exclusion.

Estimated SAR Result

Freq. Band	Frequency (GHz)	max. power (dBm)	max. power (mw)	Test Separation (mm)	Estimated
					1g SAR (W/kg)
Bluetooth	2.48	2.0	1.58	5	0.067

6.4.3. Simultaneous Transmission SAR Summation Scenario

Test position		WiFi Antenna SAR _{max} (W/kg)										
		1	2	3	4	5	6	7	8	9	10	11
		WLAN 2.4G	WLAN 2.4G	WLAN 5.2G	WLAN 5.2G	WLAN 5.3G	WLAN 5.3G	WLAN 5.5G	WLAN 5.5G	WLAN 5.8G	WLAN 5.8G	BT
		Ant0	Ant1	Ant0	Ant1	Ant0	Ant1	Ant0	Ant1	Ant0	Ant1	Ant0
Body	Back side	0.477	0.378	0.462	0.360	0.434	0.331	0.338	0.326	0.328	0.244	0.067

Test position		Summed 1g SAR _{max} (W/kg)									
		1+2	3+4	5+6	7+8	9+10	2+11	4+11	6+11	8+11	10+11
Body	Back side	0.855	0.822	0.765	0.664	0.572	0.445	0.427	0.398	0.393	0.311

Note:

2) $\text{MAX. } \Sigma \text{SAR}_{10g} = \text{Unlicensed SAR}_{\text{MAX}} + \text{Licensed SAR}_{\text{MAX}}$





6.5. SAR Measurement Results

When the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. to KDB 865664D01.





APPENDIX A: DETAILED SYSTEM CHECK RESULTS

APPENDIX B: DETAILED TEST RESULTS

APPENDIX C: CALIBRATION CERTIFICATE

APPENDIX D: PHOTOGRAPHS

.....The End of Test Report.....

