




1. Summary of the DUT

Antenna Picture



2. Electrical Specification:

Antenna types	Built-in WIFI Antenna
Frequency	2400-2500 MHz, 5150-5350MHz, 5725-5850MHz
Impedance	50 Ω
VSWR	< 2.0
Peak Gain	2.4GHZ 1.73dbi, 5GHZ 4.45dbi
Efficiency	>35 %
Antenna Material	PCB+同轴线
Connector Type	1.13 MHF-1-Plug

3. Test Condition

3.1	测试项目	测试设备和型号	备注
无源测试	1. Antenna Gain 2. S.W.R 3. Return Loss 4. Radiation Pattern	1. Network analyzer (R&S ZVL6) 2. Network analyzer (HP 8753D)	

3.2 Matching Circuit The matching circuit was Default

Shengtianlong Company Innovation Valley 108, No. 16, Lane 3, Liuxian Second Road, Xingdong Community, Xinan Street, Baoan District, Shenzhen



4. RF Performance

4.1 Passive parameters


Freq. (MHz)	2400	2410	2420	2430	2440	2450	2460	2470	2480	2490	2500
Gain (dBi)	0.58	0.66	1.1	1.02	1.17	1.59	0.72	0.08	0.72	1.19	1.73

Freq. (MHz)	5150	5170	5190	5210	5230	5250	5270	5290	5310	5330	5350
Gain (dBi)	3.13	3.45	3.56	4.11	4.31	4.21	4.1	3.82	3.28	3.19	3.04

Freq. (MHz)	5720	5740	5760	5780	5800	5820	5840	5860	5880
Gain (dBi)	2.51	4.45	3.32	4.18	2.54	4.01	1.41	2.47	1.09


4.2 S Parameter

Frequency (MHz)	2400	2450	2480
Return Loss (dB)	-20.58	-22.74	-15.39
VSWR	1.63	1.28	1.81






4.3 Radiation




Passive -Freq2400.00MHZ

Gain:0.58(dBi)



Passive -Freq2450.00MHZ


Gain: 1.59(dBi)



Passive -Freq2500.00MHZ


Gain: 1.73(dBi)

Shengtianlong Company Innovation Valley 108, No. 16, Lane 3, Liuxian Second Road, Xingdong Community, Xinan Street, Baoan District, Shenzhen




Passive -Freq5150.00MHZ

Gain: 3.13(dBi)




Passive -Freq5230.00MHZ

Gain: 4.31(dBi)




Passive -Freq5350.00MHZ

Gain: 3.04(dBi)




Passive -Freq5720.00MHZ

Gain:2.51(dBi)



Passive -Freq5740.00MHZ

Gain: 4.45(dBi)



Passive -Freq5860.00MHZ

Gain: 2.47(dBi)

5. ME Drawing for the antenna

