



Test Report - FCC Spot-Check

Applicant: VMware LLC

Signature:

A handwritten signature in black ink, appearing to read 'Tim Royer'.

Sr. EMC Engineer
EMC-003838-NE



Name & Title:

Tim Royer, EMC Engineer

Date of Signature

9/11/2024

This test report relates only to the items tested as identified and is not valid for any subsequent changes or modifications made to the equipment under test.

Table of Contents

1. APPLICANT INFORMATION.....	3
1.1 TEST RESULT SUMMARY.....	3
2. LOCATION OF TESTING.....	4
2.1 TEST LABORATORY.....	4
3. TEST SAMPLE(S) (EUT/DUT).....	4
3.1 DESCRIPTION OF THE EUT.....	5
3.2 CONFIGURATION OF EUT.....	6
3.3 TEST SETUP OF EUT.....	6
4. TEST METHODS & APPLICABLE REGULATORY LIMITS.....	7
4.1 TEST METHODS/STANDARDS/GUIDANCE:	7
4.2 APPLIED LIMITS AND REGULATORY LIMITS:.....	7
5. MEASUREMENT UNCERTAINTY.....	7
6. ENVIRONMENTAL CONDITIONS	7
6.1 TEMPERATURE & HUMIDITY.....	7
7. LIST OF TEST EQUIPMENT AND TEST FACILITY.....	8
7.1 LIST OF TEST EQUIPMENT	8
8. TEST RESULTS	9
8.1 RADIATED EMISSIONS.....	10
8.1.1 Radiated Emissions, 830 MHz	11
8.1.1 Radiated Emissions, 1870 MHz.....	12
9. ANNEX-B – TEST SETUP PHOTOGRAPHS	13
10. HISTORY OF TEST REPORT CHANGES.....	13

1. Applicant Information

Applicant: VMware LLC
Address: 3401 Hillview Avenue
Palo Alto, CA 94304

1.1 Test Result Summary

The following test procedure and guidance were used for measuring ANSI C63.26. Full test results are available in this report.

No additions to the test methods were needed. There were no deviations, or exclusions from the test methods. No test results are from external providers or from the customer. The test results relate only to the items tested. Timco does not offer opinions and interpretations, only a pass/fail statement.

Applicable Clauses		
FCC Clauses	Description of the requirements	Result: (Pass, Fail, N/A)
FCC Part 22.983	Radiated Emissions	Pass
FCC Part 24.236	Radiated Emissions	Pass

2. Location of Testing

2.1 Test Laboratory

Timco Engineering Inc. is a subsidiary of Industrial Inspection & Analysis, Inc. ("IIA"). Testing was performed at IIA's permanent laboratory located at 13146 NW 86th Drive, Suite 400, Alachua, Florida 32615.

FCC test firm # 578780

FCC Designation # US1070

FCC site registration is under A2LA certificate # 0955.01

ISED Canada test site registration # 2056A

EU Notified Body # 1177

For all designations see A2LA scope # 0955.01

3. Test Sample(s) (EUT/DUT)

The test sample was received: 8/15/2024

Dates of Testing: 9/11/2024

3.1 Description of the EUT

A description as well as unambiguous identification of the EUT(s) tested. Where more than one sample is required for technical reasons (such as the use of connected units for the purpose of conducted output power testing where the product units will have integral antennas), each specific test shall identify which unit was tested.

Identification	
FCC ID:	2BKLH-EDG7105G
Certified Module FCC ID:	RI7FN990A28
Model(s) #	Edge 710-5G
Firmware version	M0R.100005
Software version	N/A
Serial Number	N/A

Technical Characteristics	
Frequency Range	828 - 844 MHz 1860 – 1900 MHz
Voltage Rating (AC or Batt.)	DC

Antenna Characteristics			
Antenna	Frequency Range	Mode / BW	Antenna Gain
A8PEE-100012	828 - 844 MHz	n/a	2.26 dBi
A8PEE-100012	1860 – 1900 MHz	n/a	2.26 dBi

3.2 Configuration of EUT

Band (MHz)	Mode	Number of Ant.
828 - 844 MHz		
1860 – 1900 MHz	Transmit	1

Operating conditions during Testing:

No modifications of the device under test (including firmware, specific software settings, and input/output signal levels to the EUT).

Peripherals used during Testing:

A laptop provided by the manufacturer was used to program the EUT.

3.3 Test Setup of EUT

Equipment, antenna, and cable arrangement. The setup of the equipment and cable or wire placement on the test site that produces the highest radiated and the highest ac power line conducted emissions shall be shown clearly and described. Information on the orientation of portable equipment during testing shall be included. Drawings or photographs may be used for this purpose.

Test Setups are included in the test report.

4. Test methods & Applicable Regulatory Limits

4.1 Test methods/Standards/Guidance:

Test procedures and guidance for measuring.

- 1) ANSI C63.26
- 2) KDB 996369 D04 Module Integration Guide v01, May 1 2019, Section 3

4.2 Applied Limits and Regulatory Limits:

- 3) FCC CFR 47 Part 22E
- 4) FCC CFR 47 Part 24H

5. Measurement Uncertainty

Parameter	Uncertainty (dB)
Conducted Emissions	± 3.14 dB
Radiated Emissions (9kHz – 30 MHz)	± 3.08 dB
Radiated Emissions (30 – 200 MHz)	± 2.16 dB
Radiated Emissions (200 – 1000 MHz)	± 2.15 dB
Radiated Emissions (1 GHz – 18 GHz)	± 2.14 dB
Radiated Emissions (18 GHz – 40 GHz)	± 2.31 dB

Note: The uncertainties provided in this table represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of K=2.

6. Environmental Conditions

6.1 Temperature & Humidity

Measurements performed at the test site did not exceed the following:

Temperature	23 C +/- 5%
Humidity	55% +/- 5%
Barometric pressure	30.05 inHg

Note: Specific environmental conditions that are applicable to a specific test are available in the test result section.

7. List of Test Equipment and Test Facility

The test equipment used identified by type, manufacturer, serial number, or other identification and the date on which the next calibration or service check is due.

Description of the firmware or software used to operate EUT for testing purposes.

A complete list of all test equipment used shall be included with the test report. The manufacturer's model and serial numbers, and date of last calibration, and calibration interval shall be included. Measurement cable loss, measuring instrument bandwidth and detector function, video bandwidth, if appropriate, and antenna factors shall also be included where applicable.

7.1 List of Test Equipment

Test Equipment						
Type	Device	Manufacturer	Model	SN#	Current Cal	Cal Due
Antenna	Biconical 1057	Eaton	94455-1	1057	11/19/21	11/18/2024
Antenna, NSA	Log-Periodic 1243	Eaton	96005	1243	5/4/21	11/18/2024
Antenna	Double-Ridged Horn/ETS Horn 1	ETS-Lindgren	3117	00035923	5/31/23	11/18/2024
CHAMBER	CHAMBER	Panashield	3M	N/A	12/29/23	12/18/2025
Pre-amp	Pre-amp	RF-LAMBDA	RLNA00M45GA	NA	7/27/22	7/26/2025
Receiver	EMI Test Receiver R&S ESW44	Rohde & Schwarz	ESW44	103049	10/13/21	10/12/2024

Software			
Software	Author	Version	Validation on
ESU Firmware	Rohde & Schwarz	4.43 SP3; BIOS v5.1-24-3	2018
RSCommander	Rohde & Schwarz	1.6.4	2014
ScopeExplorer	LeCroy	v2.25.0.0	2009
Field Strength	Timco	v4.10.7.0	2016

8. Test Results

The results of the test are usually indicated in the form of tables, spectrum analyzer plots, charts, sample calculations, as appropriate for each test procedure.

A description and/or a block diagram of the test setup is usually provided.

The measurement results, along with the appropriate limits for comparison, may be presented in tabular or graphical form. In addition, any variation in the measurement environment may be reported if applicable (e.g., a significant change of temperature that could affect the cable loss and amplifier response).

Unless noted otherwise in the referenced standard, the measurements of **ac power-line conducted emissions and conducted power output** will be reported in units of dB μ V. Unless noted otherwise in the referenced standard, the measurements of **radiated emissions** will be reported in units of decibels, referenced to one microvolt per meter (dB μ V/m) for electric fields, or to one ampere per meter (dBA/m) for magnetic fields, at the distance specified in the appropriate standards or requirements. The measurements of antenna-conducted power for receivers may be reported in units of dB μ V if the impedance of the measuring instrument is also reported. Otherwise, antenna-conducted power will be reported in units of decibels referenced to one milliwatt (dBm). All formulas for data conversions and conversion factors, if used, will be included in this measurement report.

Example:


Freq (MHz)	Meter Reading	+ ACF	+CL	= FS
33	20 dB μ V	+ 10.36 dB/m	+0.40 dB	= 30.36 dB μ V/m @ 3m

$$\text{EIRP} = \text{Pcond (dBm)} + \text{dBi}$$


8.1 Radiated Emissions

Limits from FCC Part 96(e)(ii)


Radiated Test Setup, Below 30 MHz



Radiated Test Setup, 30 – 1000 MHz



Radiated Test Setup, Above 1000 MHz



Radiated Emissions Tabular Data

8.1.1 Radiated Emissions, 830 MHz

Tuned Frequency (MHz)	Emission Frequency (MHz)	Detector	Meter Reading (dB _u V)	Antenna Polarity	Coax Loss (dB)	Antenna Correction Factor (dB/m)	Distance (m)	Field Strength (dB _u V/m)	Field Strength Limit (dB _u V/m)	Margin (dB)
830.00	1660.00	PK	17.80	H	-4.73	28.75	3.00	23.82	40.00	16.18
830.00	1660.00	PK	14.00	V	-4.73	28.75	3.00	20.02	40.00	19.98
830.00	2490.00	PK	14.30	H	-5.96	32.42	3.00	22.76	40.00	17.24
830.00	2490.00	PK	14.50	V	-5.96	32.42	3.00	22.96	40.00	17.04
830.00	3320.00	PK	13.40	H	-6.86	32.75	3.00	21.29	40.00	18.71
830.00	3320.00	PK	13.90	V	-6.86	32.75	3.00	21.79	40.00	18.21
830.00	4150.00	PK	14.40	H	-7.70	33.49	3.00	22.20	40.00	17.80
830.00	4150.00	PK	14.20	V	-7.70	33.49	3.00	22.00	40.00	18.00
830.00	4980.00	PK	18.20	H	-8.42	34.01	3.00	25.79	40.00	14.21
830.00	4980.00	PK	17.40	V	-8.42	34.01	3.00	24.99	40.00	15.01
830.00	5810.00	PK	19.20	H	-9.13	34.93	3.00	27.00	40.00	13.00
830.00	5810.00	PK	18.80	V	-9.13	34.93	3.00	26.60	40.00	13.40
830.00	6640.00	PK	19.30	H	-9.81	35.75	3.00	27.24	40.00	12.76
830.00	6640.00	PK	20.90	V	-9.81	35.75	3.00	28.84	40.00	11.16
830.00	7470.00	PK	20.10	H	-10.33	36.18	3.00	27.95	40.00	12.05
830.00	7470.00	PK	20.00	V	-10.33	36.18	3.00	27.85	40.00	12.15
830.00	8300.00	PK	20.50	H	-10.93	36.07	3.00	27.64	40.00	12.36
830.00	8300.00	PK	14.80	V	-10.93	36.07	3.00	21.94	40.00	18.06

8.1.1 Radiated Emissions, 1870 MHz

Tuned Frequency (MHz)	Emission Frequency (MHz)	Detector	Meter Reading (dBuV)	Antenna Polarity	Coax Loss (dB)	Antenna Correction Factor (dB/m)	Distance (m)	Field Strength (dB μ V/m)	Spurious Limit (dBm)	Margin (dB)
1870.00	3740.00	PK	15.42	H	-7.27	33.15	3.00	41.31	47.00	5.69
1870.00	3740.00	PK	11.62	V	-7.27	33.15	3.00	37.51	47.00	9.49
1870.00	5610.00	PK	11.92	H	-9.01	34.90	3.00	37.81	47.00	9.19
1870.00	5610.00	PK	12.12	V	-9.01	34.90	3.00	38.01	47.00	8.99
1870.00	7480.00	PK	11.02	H	-10.34	36.17	3.00	36.85	47.00	10.15
1870.00	7480.00	PK	11.52	V	-10.34	36.17	3.00	37.35	47.00	9.65
1870.00	9350.00	PK	12.02	H	-11.51	36.37	3.00	36.88	47.00	10.12
1870.00	9350.00	PK	11.82	V	-11.51	36.37	3.00	36.68	47.00	10.32
1870.00	11220.00	PK	15.82	H	-12.71	38.01	3.00	41.12	47.00	5.88
1870.00	11220.00	PK	15.02	V	-12.71	38.01	3.00	40.32	47.00	6.68
1870.00	13090.00	PK	16.82	H	-13.92	39.67	3.00	42.57	47.00	4.43
1870.00	13090.00	PK	16.42	V	-13.92	39.67	3.00	42.17	47.00	4.83
1870.00	14960.00	PK	16.92	H	-14.73	40.19	3.00	42.37	47.00	4.63
1870.00	14960.00	PK	18.52	V	-14.73	40.19	3.00	43.97	47.00	3.03
1870.00	16830.00	PK	17.72	H	-15.89	42.29	3.00	44.11	47.00	2.89
1870.00	16830.00	PK	17.62	V	-15.89	42.29	3.00	44.01	47.00	2.99
1870.00	18700.00	PK	18.12	H	-16.53	15.46	3.00	17.05	47.00	29.95
1870.00	18700.00	PK	12.42	V	-16.53	15.46	3.00	11.35	47.00	35.65

9. ANNEX-B – Test Setup Photographs

Test setup photographs are located in a separate supplementary ANNEX-B document.

10. History of Test Report Changes

Test Report #	Revision #	Description	Date of Issue
TR_15541-24_ PCS_5G SC_1	1	Initial release	9/11/2024
	2	Updated Page 5	10/8/2024



13146 NW 86th Drive, Suite 400, Alachua, Florida 32615
(352) 472-5500 / testing@industrial-ia.com

END OF TEST REPORT
