



Shenzhen GUOREN Certification Technology Service Co., Ltd.

101#, Building K & Building T, The Second Industrial Zone, Jiazitang Community,
Fenghuang Street, Guangming District, Shenzhen, China

RF Exposure evaluation

Report Reference No.....: GRCTR250802012-04

FCC ID.....: 2BLJV-R-W52508

Compiled by


(position+printed name+signature)...: Testing Engineer Jimmy Wang

Supervised by

(position+printed name+signature)...: Project Engineer Kelley Zhang

Approved by

(position+printed name+signature)...: Manager Sam Wang



Date of issue.....: Sep. 03, 2025

Testing Laboratory Name: Shenzhen GUOREN Certification Technology Service Co., Ltd.

Address: 101#, Building K & Building T, The Second Industrial Zone,
Jiazitang Community, Fenghuang Street, Guangming District,
Shenzhen, China

Applicant's name: Shenzhen Dbit Network Equipment Co., Ltd

Address: 4002, Phase II, Qianhai Shima Financial Center, No. 3040 Xinghai
Avenue, Nanshan Street, Qianhai Shenzhen-Hong Kong
Cooperation Zone, Shenzhen, China

Test specification

Standard: 47CFR §2.1091
KDB447498 D01 v06

Shenzhen GUOREN Certification Technology Service Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen GUOREN Certification Technology Service Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen GUOREN Certification Technology Service Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description: AC1200 Dual Band Gigabit Wi-Fi Router

Trade Mark: /

Manufacturer: Shenzhen Dbit Network Equipment Co., Ltd

Model/Type reference.....: T18-21K Pro

Listed Models: /

Hardware Version: V1.0

Software Version: V1.0

Frequency.....: From 2412MHz to 2462MHz,
5180-5240MHz,5260-5320MHz,5500-5700MHz,5745-5825MHz

Ratings: DC 12V From External Circuit

Result.....: PASS

TEST REPORT

Equipment under Test : AC1200 Dual Band Gigabit Wi-Fi Router

Model /Type : T18-21K Pro

Listed Models : /

Applicant : Shenzhen Dbit Network Equipment Co., Ltd

Address : 4002, Phase II, Qianhai Shimao Financial Center, No. 3040 Xinghai Avenue, Nanshan Street, Qianhai Shenzhen-Hong Kong Cooperation Zone, Shenzhen, China

Manufacturer : Shenzhen Dbit Network Equipment Co., Ltd

Address : 4002, Phase II, Qianhai Shimao Financial Center, No. 3040 Xinghai Avenue, Nanshan Street, Qianhai Shenzhen-Hong Kong Cooperation Zone, Shenzhen, China

Test Result:	PASS
--------------	------

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

1. SUMMARY	4
1.1. General Remarks	4
1.2. Product Description	4
1.3. Equipment Under Test	5
1.4. Short description of the Equipment under Test (EUT)	5
1.5. EUT configuration	6
1.6. Modifications	6
2. TEST ENVIRONMENT	7
2.1. Address of the test laboratory	7
2.2. Test Facility	7
2.3. Environmental conditions	7
2.4. Statement of the measurement uncertainty	7
3. METHOD OF MEASUREMENT	9
3.1. Applicable Standard	9
3.2. Limit	9
3.3. MPE Calculation Method	9
3.4. Antenna Information	10
3.5. Manufacturing Tolerance	11
4. EVALUATION RESULT	11
5. CONCLUSION	12

1. SUMMARY

1.1. General Remarks

Date of receipt of test sample	:	Aug. 08, 2025
Testing commenced on	:	Aug. 08, 2025
Testing concluded on	:	Sep. 03, 2025

1.2. Product Description

Product Name:	AC1200 Dual Band Gigabit Wi-Fi Router
Model/Type reference:	T18-21K Pro
Listed Models:	/
Power supply:	DC 12V From External Circuit
Adapter information:	M/N:RD1201000-225MG Input:AC 100-240V 50/60Hz 0.6A Output:12V---1.0A
Testing sample ID:	GRCTR250802012-1# (Engineer sample), GRCTR250802012-2# (Normal sample)

2.4G WIFI:

Supported type:	802.11b/802.11g/802.11n HT20/802.11n HT40
Modulation:	802.11b: DSSS 802.11g/802.11n HT20 /802.11n HT40: OFDM
Operation frequency:	802.11b/802.11g/802.11 HT20: 2412MHz~2462MHz 802.11n HT40: 2422MHz~2452MHz
Channel number:	802.11b/802.11g/802.11n HT20: 11 802.11n HT40: 7
Channel separation:	5MHz
Antenna type:	External antenna
Antenna gain*(Supplied by the customer):	Ant 1: 4.85 dBi Ant 2: 5.12 dBi Directional gain:7.99dBi

5G WIFI:

WLAN	Supported 802.11 a/n/ac
Modulation Type	IEEE 802.11a: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK,BPSK) IEEE 802.11n HT40: OFDM (64QAM, 16QAM, QPSK,BPSK) IEEE 802.11acVHT20/VHT40/VHT80: OFDM(256QAM, 64QAM, 16QAM, QPSK, BPSK)
Operation frequency	IEEE 802.11a:5180-5240MHz,5260-5320MHz,5500-5700MHz,5745-5825MHz IEEE 802.11n HT20: 5180-5240MHz,5260-5320MHz,5500-5700MHz,5745-5825MHz IEEE 802.11n HT40: 5190-5230MHz,5270-5310MHz,5510-5670MHz,5755-5795MHz IEEE 802.11acVHT20: 5180-5240MHz,5260-5320MHz,5500-5700MHz,5745-

	5825MHz IEEE 802.11acVHT40: 5190-5230MHz,5270-5310MHz,5510-5670MHz,5755-5795MHz IEEE 802.11acVHT80:5210MHz,5290MHz,5530MHz,5610MHz,5775MHz
Channel number	4 Channels for 20MHz bandwidth(5180-5240MHz) 4 Channels for 20MHz bandwidth(5260-5320MHz) 11 Channels for 20MHz bandwidth(5500-5700MHz) 5 channels for 20MHz bandwidth(5745-5825MHz) 2 channels for 40MHz bandwidth(5190~5230MHz) 2 channels for 40MHz bandwidth(5270~5310MHz) 5 Channels for 40MHz bandwidth(5510-5670MHz) 2 channels for 40MHz bandwidth(5755~5795MHz) 1 channel for 80MHz bandwidth(5210MHz) 1 channel for 80MHz bandwidth(5290MHz) 1 Channel for 80MHz bandwidth(5530Hz) 1 Channel for 80MHz bandwidth(5610Hz) 1 channel for 80MHz bandwidth(5775MHz)
Antenna type:	External antenna
Antenna gain*(Supplied by the customer):	Ant 1: 5.17 dBi Ant 2: 5.17 dBi Directional gain:8.18
Remark:*When the information provided by the customer was used to calculate test results, if the information provided by the customer is not accurate, shenzhen GUOREN Certification Technology Service Co., Ltd. does not assume any responsibility. The product has two kinds of appearance,appearance 1 had been tested all items.	

According to KDB 662911 D01 Multiple Transmitter Output,Directional Gain Calculations for In-Band Measurements:

If transmit signals are correlated, then

Directional gain = $10 \log[(10^{G_1/20} + 10^{G_2/20} + \dots + 10^{G_N/20})^2 / N_{\text{ANT}}]$ dBi [Note the “20”s in the denominator of each exponent and the square of the sum of terms; the object is to combine the signal levels coherently.]

1.3. Equipment Under Test

Power supply system utilised

Power supply voltage	:	<input type="radio"/> 230V / 50 Hz	<input type="radio"/> 120V / 60Hz
		<input type="radio"/> 12 V DC	<input type="radio"/> 24 V DC
		<input checked="" type="radio"/> Other (specified in blank below)	

DC 12V From External Circuit

1.4. Short description of the Equipment under Test (EUT)

This is a AC1200 Gigabit Dual Band Wi-Fi Router.
For more details, refer to the user's manual of the EUT.

1.5. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

● - supplied by the manufacturer

○ - supplied by the lab

○ /	M/N: /
	Manufacturer: /

1.6. Modifications

No modifications were implemented to meet testing criteria.

2. TEST ENVIRONMENT

2.1. Address of the test laboratory

Shenzhen GUOREN Certification Technology Service Co., Ltd.

101#, Building K & Building T, The Second Industrial Zone, Jiazitang Community, Fenghuang Street, Guangming District, Shenzhen, China

2.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 920798 Designation Number: CN1304

Shenzhen GUOREN Certification Technology Service Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

A2LA-Lab Cert. No.: 6202.01

Shenzhen GUOREN Certification Technology Service Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

ISED#: 27264 CAB identifier: CN0115

Shenzhen GUOREN Certification Technology Service Co., Ltd. has been listed by Innovation, Science and Economic Development Canada to perform electromagnetic emission measurement.

CNAS-Lab Code: L15631

Shenzhen GUOREN Certification Technology Service Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories for the Competence of Testing and Calibration Laboratories.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.10 and CISPR 16-1-4:2010.

2.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

2.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 2 " and is documented in the Shenzhen GUOREN Certification Technology Service Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen GUOREN Certification Technology Service Co., Ltd.:

Test Items	Measurement Uncertainty	Notes
Max output power	0.54 dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

3. Method of measurement

3.1. Applicable Standard

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

KDB447498 D01 v06: RF EXPOSURE PROCEDURES AND EQUIPMENT AUTHORIZATION
POLICIES FOR MOBILE AND PORTABLE DEVICES

3.2. Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

3.3. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

3.4. Antenna Information

EUT can only use antennas certificated as follows provided by manufacturer;

Antenna No.	Model No. of antenna:	Type of antenna:	Gain of the antenna (Max.)	Frequency range:
2.4GWIFI	/	External antenna	Ant 1: 4.85 dBi for 2400-2500MHz Ant 2: 5.12 dBi for 2400-2500MHz	
5GWIFI	/	External antenna	Ant 1: 5.17 dBi for 5000MHz-6000MHz Ant 2: 5.17 dBi for 5000MHz-6000MHz	

3.5. Maximum conducted output power

Test Mode	Frequency[MHz]	Output power PK Ant1(dBm)	Output power PK Ant2(dBm)
11B	2412	12.43	12.80
11B	2437	12.88	12.53
11B	2462	12.07	12.59
11G	2412	13.37	13.70
11G	2437	12.81	13.10
11G	2462	12.00	12.81
11N20SISO	2412	13.34	13.71
11N20SISO	2437	12.68	13.01
11N20SISO	2462	12.06	12.61
11N40SISO	2422	13.66	12.72
11N40SISO	2437	13.23	12.37
11N40SISO	2452	12.77	12.61

Test Mode	Frequency[MHz]	Output power AVG Ant1(dBm)	Output power AVG Ant2(dBm)
11A	5180	13.59	13.59
11A	5220	13.47	13.76
11A	5240	12.27	12.98
11A	5260	13.24	12.69
11A	5300	12.89	13.06
11A	5320	12.84	12.33
11A	5500	12.83	13.12
11A	5580	12.43	13.69
11A	5700	13.11	12.08
11A	5745	12.04	12.23
11A	5785	12.41	12.32
11A	5825	11.99	12.42
11N20SISO	5180	13.14	13.54
11N20SISO	5220	13.19	13.36
11N20SISO	5240	12.72	12.65
11N20SISO	5260	12.61	12.21
11N20SISO	5300	13.64	12.95
11N20SISO	5320	12.77	12.01
11N20SISO	5500	13.20	13.83
11N20SISO	5580	12.58	13.17
11N20SISO	5700	12.89	12.18
11N20SISO	5745	13.16	12.74
11N20SISO	5785	12.33	12.51
11N20SISO	5825	12.12	12.24
11N40SISO	5190	13.96	13.38
11N40SISO	5230	13.03	13.09
11N40SISO	5270	12.30	13.38

11N40SISO	5310	12.63	12.85
11N40SISO	5510	13.38	13.73
11N40SISO	5550	12.44	13.78
11N40SISO	5670	13.00	12.33
11N40SISO	5755	12.38	12.21
11N40SISO	5795	12.25	12.55
11AC20SISO	5180	13.59	13.39
11AC20SISO	5220	13.65	13.59
11AC20SISO	5240	12.42	12.83
11AC20SISO	5260	12.58	12.17
11AC20SISO	5300	13.12	13.50
11AC20SISO	5320	12.45	12.65
11AC20SISO	5500	13.66	14.00
11AC20SISO	5580	12.10	12.81
11AC20SISO	5700	13.05	12.51
11AC20SISO	5745	13.17	13.46
11AC20SISO	5785	12.53	12.91
11AC20SISO	5825	12.18	12.68
11AC40SISO	5190	13.46	13.48
11AC40SISO	5230	12.93	12.88
11AC40SISO	5270	12.41	12.13
11AC40SISO	5310	13.16	12.63
11AC40SISO	5510	13.26	13.36
11AC40SISO	5550	12.38	12.77
11AC40SISO	5670	12.88	12.23
11AC40SISO	5755	12.73	12.25
11AC40SISO	5795	12.44	11.96
11AC80SISO	5210	13.13	13.67
11AC80SISO	5290	12.75	12.36
11AC80SISO	5530	12.72	13.73
11AC80SISO	5610	12.36	12.24
11AC80SISO	5775	11.66	12.23

3.6. Manufacturing Tolerance

Mode	Max. Peak Conducted Output Power (dBm)		Max. tune-up	
	Antenna1	Antenna2	Antenna1	Antenna2
2.4GWIFI	13.66	13.71	14.0 ± 1	14.0 ± 1

Mode	Max. Average Conducted Output Power (dBm)		Max. tune-up	
	Antenna1	Antenna2	Antenna1	Antenna2
UNII-1	13.96	13.76	14.0 ± 1	14.0 ± 1
UNII-2A	13.64	13.5	14.0 ± 1	14.0 ± 1
UNII-2C	13.66	14.00	14.0 ± 1	14.0 ± 1
UNII-3	13.17	13.46	14.0 ± 1	14.0 ± 1

4. Evaluation Result

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r=20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

ANT 1

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
2.4GWIFI	15.0	31.6228	4.85	3.0549	0.0192	1.0000
UNII-1	15.0	31.6228	5.17	3.2885	0.0207	1.0000
UNII-2A	15.0	31.6228	5.17	3.2885	0.0207	1.0000
UNII-2C	15.0	31.6228	5.17	3.2885	0.0207	1.0000
UNII-3	15.0	31.6228	5.17	3.2885	0.0207	1.0000

ANT 2

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
2.4GWIFI	15.0	31.6228	5.12	3.2509	0.0205	1.0000
UNII-1	15.0	31.6228	5.17	3.2885	0.0207	1.0000
UNII-2A	15.0	31.6228	5.17	3.2885	0.0207	1.0000
UNII-2C	15.0	31.6228	5.17	3.2885	0.0207	1.0000
UNII-3	15.0	31.6228	5.17	3.2885	0.0207	1.0000

Remark:

1. Output power including turn-up tolerance;
2. MPE evaluate distance is 20cm from user manual provide by manufacturer.

Simultaneous Evaluation

2.4G WIFI ANT 1 MPE (Ratio)	2.4G WIFI ANT 2 MPE (Ratio)	5G WIFI ANT 1 MPE (Ratio)	5G WIFI ANT 2 MPE (Ratio)	MPE (Ratio)	MPE Limits (Ratio)
0.0192	0.0205	0.0207	0.0207	0.0811	1.0000

5. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

.....End of Report.....