

**TEST REPORT**

2/F., Garment Centre,  
576 Castle Peak Road, Kowloon,  
Hong Kong SAR, China.

Telephone: (852) 2173 8888  
Facsimile: (852) 2785 5487  
www.intertek.com

**Report No.: 25040096HKG-001**

HH Asia Pacific Limited

Application For Original Grant of 47 CFR Part 15 Certification

Coca-Cola LED Speaker

**FCC ID: 2BLLWFIFA26-050****Prepared and Checked by:****Approved by:**

Signed on File

Leung Chun Ning, Peter  
EngineerWong Cheuk Ho, Herbert  
Assistant Manager  
Date: May 21, 2025

---

Intertek's standard Terms and Conditions can be obtained at our website <http://www.intertek.com/terms/>.

The test report only allows to be revised within the retention period unless further standard or the requirement was noticed.

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

© 2017 Intertek

**TEST REPORT****GENERAL INFORMATION**

<b>Grantee:</b>	HH Asia Pacific Limited
<b>Grantee Address:</b>	15th Floor, Plaza 228, 228 Wan Chai Road, Wan Chai, Hong Kong.
<b>FCC Specification Standard:</b>	FCC Part 15, October 1, 2023 Edition
<b>FCC ID:</b>	2BLLWFIFA26-050
<b>FCC Model(s):</b>	FIFA26_050
<b>Type of EUT:</b>	Transceiver
<b>Description of EUT:</b>	Coca-Cola LED Speaker
<b>Brand Name:</b>	Coca-Cola
<b>Serial Number:</b>	Not Labelled
<b>Sample Receipt Date:</b>	April 02, 2025
<b>Date of Test:</b>	April 02, 2025 to April 24, 2025
<b>Report Date:</b>	May 21, 2025
<b>Environmental Conditions:</b>	Temperature: +10 to 40°C Relative Humidity: 10 to 90%
<b>Conclusion:</b>	Test was conducted by client submitted sample. The submitted sample as received complied with the 47 CFR Part 15 Certification.

**TEST REPORT****SUMMARY OF TEST RESULT**

Test Items	FCC Part 15 Section	Results
Transmitter Power Line Conducted Emissions	15.207	Complied
Radiated Emission	15.249, 15.209	Complied
Radiated Emission on the Bandedge		Complied
Radiated Emission in Restricted Bands	15.205	Complied

The equipment under test is found to be complying with the following standards:

FCC Part 15, October 1, 2023 Edition

Note: 1. The EUT uses a permanently attached antenna which, in accordance to section 15.203, is considered sufficient to comply with the provisions of this section.  
2. Pursuant to FCC Part 15 Section 15.215(c), the 20dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over expected variations in temperature and supply voltage were considered.

**TEST REPORT****TABLE OF CONTENTS**

<b>1.0</b>	<b>GENERAL DESCRIPTION</b>	<b>5</b>
1.1	Product Description .....	5
1.2	Related Submittal(s) Grants .....	5
1.3	Test Methodology .....	5
1.4	Test Facility .....	5
<b>2.0</b>	<b>SYSTEM TEST CONFIGURATION</b>	<b>6</b>
2.1	Justification .....	6
2.2	EUT Exercising Software.....	6
2.3	Special Accessories.....	6
2.4	Measurement Uncertainty.....	6
2.5	Support Equipment List and Description.....	6
<b>3.0</b>	<b>EMISSION RESULTS</b>	<b>7</b>
3.1	Field Strength Calculation .....	7
3.2	Radiated Emission Configuration Photograph .....	8
3.3	Radiated Emission Data.....	8
3.4	Conducted Emission Configuration Photograph .....	8
3.5	Conducted Emission Data .....	8
<b>4.0</b>	<b>EQUIPMENT PHOTOGRAPHS</b>	<b>17</b>
<b>5.0</b>	<b>PRODUCT LABELLING</b>	<b>17</b>
<b>6.0</b>	<b>TECHNICAL SPECIFICATIONS</b>	<b>17</b>
<b>7.0</b>	<b>INSTRUCTION MANUAL</b>	<b>17</b>
<b>8.0</b>	<b>MISCELLANEOUS INFORMATION</b>	<b>18</b>
8.1	Radiated Emission on the Bandedge .....	18
8.2	Discussion of Pulse Desensitization.....	23
8.3	Calculation of Average Factor .....	23
8.4	Emissions Test Procedures .....	24
8.5	Occupied Bandwidth .....	27
<b>9.0</b>	<b>CONFIDENTIALITY REQUEST</b>	<b>29</b>
<b>10.0</b>	<b>EQUIPMENT LIST</b>	<b>29</b>

## TEST REPORT

### 1.0 GENERAL DESCRIPTION

#### 1.1 Product Description

The Equipment Under Test (EUT), is a 2.4GHz BT Classic Transceiver for a speaker. The sample supplied operated on 79 channels, normally at 2402 - 2480MHz. The channels are separated with 1MHz spacing.

The EUT is powered by 1 x 3.7V Lithium-ion battery. After switching on EUT, it can be paired up with a smartphone and will be used to play different sound based on the sound received from the paired smartphone.

Antenna Type: Internal, Integral

For electronic filing, the brief circuit description is saved with filename: Descri.pdf.

#### 1.2 Related Submittal(s) Grants

This is a single application for certification of a transceiver.

#### 1.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.10 (2013). All radiated measurements were performed in an 3m Chamber. Preliminary scans were performed in the 3m Chamber only to determine worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the **“Justification Section”** of this Application.

#### 1.4 Test Facility

The 3m Chamber and conducted measurement facility used to collect the radiated data is located at Workshop No. 3, G/F., World-Wide Industrial Centre, 43-47 Shan Mei Street, Fo Tan, Sha Tin, N.T., Hong Kong SAR, China. This test facility and site measurement data have been placed on file with the FCC and IC No. 2042H, CABID is “HKAP01”.

## TEST REPORT

### 2.0 SYSTEM TEST CONFIGURATION

#### 2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.10 (2013).

The device was powered by 3.7VDC (1 x 3.7V Lithium-ion Battery).

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The rear of unit shall be flushed with the rear of the table.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was mounted to a plastic stand if necessary and placed on the wooden turntable, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

#### 2.2 EUT Exercising Software

The EUT exercise program (FCC Assist 1.0.2.2) used during radiated testing was designed to exercise the various system components in a manner similar to a typical use.

#### 2.3 Special Accessories

There are no special accessories necessary for compliance of this product.

#### 2.4 Measurement Uncertainty

Decision Rule for compliance: For FCC/IC standard, the measured value must be within the limits of applicable standard without accounting for the measurement uncertainty. For EN/IEC/HKTA/HKTC standard, conformity rules will be used as per standard directly excepted EN/IEC 61000-3-2, EN/IEC 61000-3-3, HKTA1004, HKCA1008, HKTA1019, HKTA1020, HKTA1041 and HKTA1044.

Uncertainty and Compliance - Unless the standard specifically states that measured values are to be extended by the measurement uncertainty in determining compliance, all compliance determinations are based on the actual measured value.

#### 2.5 Support Equipment List and Description

Description	Remark
HP 820G1 Notebook	Provided by Intertek
31cm USB Type-C Charging Cable	Provided by Applicant

## TEST REPORT

### 3.0 EMISSION RESULTS

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

#### 3.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any), Average Factor (optional) from the measured reading.

The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG - AV$$

where FS = Field Strength in dB $\mu$ V/m

RA = Receiver Amplitude (including preamplifier) in dB $\mu$ V

AF = Antenna Factor in dB

CF = Cable Attenuation Factor in dB

AG = Amplifier Gain in dB

AV = Average Factor in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain.

An example for the calculations in the following table is as follows:

$$FS = RR + LF$$

where FS = Field Strength in dB $\mu$ V/m

RR = RA - AG - AV in dB $\mu$ V

LF = CF + AF in dB

Assume a receiver reading of 52.0 dB $\mu$ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB are added. The amplifier gain of 29.0 dB and average factor of 5.0 dB are subtracted, giving a field strength of 27.0 dB $\mu$ V/m. This value in dB $\mu$ V/m was converted to its corresponding level in  $\mu$ V/m.

RA = 52.0 dB $\mu$ V/m

AF = 7.4 dB

RR = 18.0 dB $\mu$ V

CF = 1.6 dB

LF = 9.0 dB

AG = 29.0 dB

AV = 5.0 dB

FS = RR + LF

FS = 18.0 + 9.0 = 27.0 dB $\mu$ V/m

Level in  $\mu$ V/m = Common Antilogarithm [(27.0 dB $\mu$ V/m)/20] = 22.4  $\mu$ V/m

## TEST REPORT

### 3.2 Radiated Emission Configuration Photograph

The worst case in radiated emission was found at 12400 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: Setup Photos.pdf.

### 3.3 Radiated Emission Data

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgment: Passed by 5.1 dB

### 3.4 Conducted Emission Configuration Photograph

The worst case in line-conducted emission was found at 0.150 MHz

For electronic filing, the worst-case line-conducted configuration photographs are saved with filename: Setup Photos.pdf.

### 3.5 Conducted Emission Data


The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgment: Pass by 3.99 dB

## TEST REPORT

### CONDUCTED EMISSION

Model: FIFA26\_050  
 Date of Test: April 15, 2025  
 Worst-Case Operating Mode: BT Operating



#### EDIT PEAK LIST (Final Measurement Results)

TRACE	FREQUENCY	LEVEL dB <sub>μ</sub> V	DELTA LIMIT dB
1	Quasi Peak 150 kHz	62.00 N	-3.99
2	CISPR Average 168 kHz	41.28 L1	-13.77
1	Quasi Peak 213 kHz	47.34 L1	-15.74
1	Quasi Peak 294 kHz	36.68 N	-23.73
2	CISPR Average 528 kHz	28.45 N	-17.55
1	Quasi Peak 532.5 kHz	32.86 N	-23.13

Note: Measurement Uncertainty is  $\pm 4.2\text{dB}$  at a level of confidence of 95%.

## TEST REPORT

### RADIATED EMISSIONS

Model: FIFA26\_050  
 Date of Test: April 17, 2025  
 Worst-Case Operating Mode: Transmitting (GFSK)

Table 1

Pursuant to FCC Part 15 Section 15.249 Requirement

Lowest Channel

Polari-zation	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Average (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	2402.000	75.5	33	29.4	71.9	94.0	-22.1
H	4804.000	31.3	33	34.9	33.2	54.0	-20.8
H	7206.000	33.0	33	37.9	37.9	54.0	-16.1
V	9608.000	34.9	33	40.4	42.3	54.0	-11.7
H	12010.000	38.6	33	40.5	46.1	54.0	-7.9
H	14412.000	39.0	33	40.0	46.0	54.0	-8.0

Polari-zation	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	2402.000	86.5	33	29.4	82.9	114.0	-31.1
H	4804.000	45.1	33	34.9	47.0	74.0	-27.0
H	7206.000	47.1	33	37.9	52.0	74.0	-22.0
V	9608.000	48.6	33	40.4	56.0	74.0	-18.0
H	12010.000	52.0	33	40.5	59.5	74.0	-14.5
H	14412.000	52.7	33	40.0	59.7	74.0	-14.3

- Notes:
1. Peak Detector Data unless otherwise stated.
  2. Average detector is applied according to ANSI C63.10.
  3. All measurements were made at 3 meters.
  4. Negative value in the margin column shows emission below limit.
  5. Horn antenna is used for the emission over 1000MHz.
  6. Emissions within the restricted band meets the requirement of FCC Part 15 Section 15.205
  7. Measurement Uncertainty is  $\pm 5.3$ dB at a level of confidence of 95%.

## TEST REPORT

### RADIATED EMISSIONS

Model: FIFA26\_050  
 Date of Test: April 17, 2025  
 Worst-Case Operating Mode: Transmitting (GFSK)

Table 2

Pursuant to FCC Part 15 Section 15.249 Requirement

Middle Channel

Polari-zation	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Average (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	2440.000	74.3	33	29.4	70.7	94.0	-23.3
H	4880.000	30.9	33	34.9	32.8	54.0	-21.2
H	7320.000	33.1	33	37.9	38.0	54.0	-16.0
V	9760.000	34.9	33	40.4	42.3	54.0	-11.7
V	12200.000	39.7	33	40.5	47.2	54.0	-6.8
H	14640.000	39.3	33	38.4	44.7	54.0	-9.3

Polari-zation	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	2440.000	85.2	33	29.4	81.6	114.0	-32.4
H	4880.000	44.1	33	34.9	46.0	74.0	-28.0
H	7320.000	46.8	33	37.9	51.7	74.0	-22.3
V	9760.000	48.3	33	40.4	55.7	74.0	-18.3
V	12200.000	53.4	33	40.5	60.9	74.0	-13.1
H	14640.000	53.2	33	38.4	58.6	74.0	-15.4

- Notes:
1. Peak Detector Data unless otherwise stated.
  2. Average detector is applied according to ANSI C63.10.
  3. All measurements were made at 3 meters.
  4. Negative value in the margin column shows emission below limit.
  5. Horn antenna is used for the emission over 1000MHz.
  6. Emissions within the restricted band meets the requirement of FCC Part 15 Section 15.205
  7. Measurement Uncertainty is  $\pm 5.3$ dB at a level of confidence of 95%.

## TEST REPORT

### RADIATED EMISSIONS

Model: FIFA26\_050  
 Date of Test: April 17, 2025  
 Worst-Case Operating Mode: Transmitting (GFSK)

Table 3

Pursuant to FCC Part 15 Section 15.249 Requirement

Highest Channel

Polari-zation	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Average (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	2480.000	76.2	33	29.4	72.6	94.0	-21.4
H	4960.000	34.0	33	34.9	35.9	54.0	-18.1
V	7440.000	33.4	33	37.9	38.3	54.0	-15.7
H	9920.000	34.4	33	40.4	41.8	54.0	-12.2
H	12400.000	40.6	33	40.5	48.1	54.0	-5.9
H	14880.000	38.3	33	38.4	43.7	54.0	-10.3

Polari-zation	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	2480.000	87.2	33	29.4	83.6	114.0	-30.4
H	4960.000	47.6	33	34.9	49.5	74.0	-24.5
V	7440.000	46.8	33	37.9	51.7	74.0	-22.3
H	9920.000	48.1	33	40.4	55.5	74.0	-18.5
H	12400.000	53.7	33	40.5	61.2	74.0	-12.8
H	14880.000	52.0	33	38.4	57.4	74.0	-16.6

- Notes:
1. Peak Detector Data unless otherwise stated.
  2. Average detector is applied according to ANSI C63.10.
  3. All measurements were made at 3 meters.
  4. Negative value in the margin column shows emission below limit.
  5. Horn antenna is used for the emission over 1000MHz.
  6. Emissions within the restricted band meets the requirement of FCC Part 15 Section 15.205
  7. Measurement Uncertainty is  $\pm 5.3$ dB at a level of confidence of 95%.

## TEST REPORT

### RADIATED EMISSIONS

Model: FIFA26\_050  
 Date of Test: April 17, 2025  
 Worst-Case Operating Mode: Transmitting ( $\pi/4$ -DQPSK)

Table 4

Pursuant to FCC Part 15 Section 15.249 Requirement

Lowest Channel

Polari-zation	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Average (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	2402.000	76.4	33	29.4	72.8	94.0	-21.2
H	4804.000	32.2	33	34.9	34.1	54.0	-19.9
V	7206.000	33.9	33	37.9	38.8	54.0	-15.2
H	9608.000	35.8	33	40.4	43.2	54.0	-10.8
H	12010.000	39.5	33	40.5	47.0	54.0	-7.0
H	14412.000	39.9	33	40.0	46.9	54.0	-7.1

Polari-zation	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	2402.000	87.4	33	29.4	83.8	114.0	-30.2
H	4804.000	46.0	33	34.9	47.9	74.0	-26.1
V	7206.000	48.0	33	37.9	52.9	74.0	-21.1
H	9608.000	49.5	33	40.4	56.9	74.0	-17.1
H	12010.000	52.9	33	40.5	60.4	74.0	-13.6
H	14412.000	53.6	33	40.0	60.6	74.0	-13.4

- Notes:
1. Peak Detector Data unless otherwise stated.
  2. Average detector is applied according to ANSI C63.10.
  3. All measurements were made at 3 meters.
  4. Negative value in the margin column shows emission below limit.
  5. Horn antenna is used for the emission over 1000MHz.
  6. Emissions within the restricted band meets the requirement of FCC Part 15 Section 15.205
  7. Measurement Uncertainty is  $\pm 5.3$ dB at a level of confidence of 95%.

## TEST REPORT

### RADIATED EMISSIONS

Model: FIFA26\_050  
 Date of Test: April 17, 2025  
 Worst-Case Operating Mode: Transmitting ( $\pi/4$ -DQPSK)

Table 5

Pursuant to FCC Part 15 Section 15.249 Requirement

Middle Channel

Polari-zation	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Average (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	2440.000	75.2	33	29.4	71.6	94.0	-22.4
H	4880.000	31.8	33	34.9	33.7	54.0	-20.3
V	7320.000	34.0	33	37.9	38.9	54.0	-15.1
V	9760.000	35.8	33	40.4	43.2	54.0	-10.8
H	12200.000	40.6	33	40.5	48.1	54.0	-5.9
V	14640.000	40.2	33	38.4	45.6	54.0	-8.4

Polari-zation	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	2440.000	86.1	33	29.4	82.5	114.0	-31.5
H	4880.000	45.0	33	34.9	46.9	74.0	-27.1
V	7320.000	47.7	33	37.9	52.6	74.0	-21.4
V	9760.000	49.2	33	40.4	56.6	74.0	-17.4
H	12200.000	54.3	33	40.5	61.8	74.0	-12.2
V	14640.000	54.1	33	38.4	59.5	74.0	-14.5

- Notes:
1. Peak Detector Data unless otherwise stated.
  2. Average detector is applied according to ANSI C63.10.
  3. All measurements were made at 3 meters.
  4. Negative value in the margin column shows emission below limit.
  5. Horn antenna is used for the emission over 1000MHz.
  6. Emissions within the restricted band meets the requirement of FCC Part 15 Section 15.205
  7. Measurement Uncertainty is  $\pm 5.3$ dB at a level of confidence of 95%.

## TEST REPORT

### RADIATED EMISSIONS

Model: FIFA26\_050  
 Date of Test: April 17, 2025  
 Worst-Case Operating Mode: Transmitting ( $\pi/4$ -DQPSK)

Table 6

Pursuant to FCC Part 15 Section 15.249 Requirement

Highest Channel

Polari-zation	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Average (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	2480.000	77.0	33	29.4	73.4	94.0	-20.6
H	4960.000	34.8	33	34.9	36.7	54.0	-17.3
H	7440.000	34.2	33	37.9	39.1	54.0	-14.9
H	9920.000	35.2	33	40.4	42.6	54.0	-11.4
H	12400.000	41.4	33	40.5	48.9	54.0	-5.1
V	14880.000	39.1	33	38.4	44.5	54.0	-9.5

Polari-zation	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	2480.000	88.0	33	29.4	84.4	114.0	-29.6
H	4960.000	48.4	33	34.9	50.3	74.0	-23.7
H	7440.000	47.6	33	37.9	52.5	74.0	-21.5
H	9920.000	48.9	33	40.4	56.3	74.0	-17.7
H	12400.000	54.5	33	40.5	62.0	74.0	-12.0
V	14880.000	52.8	33	38.4	58.2	74.0	-15.8

- Notes:
1. Peak Detector Data unless otherwise stated.
  2. Average detector is applied according to ANSI C63.10.
  3. All measurements were made at 3 meters.
  4. Negative value in the margin column shows emission below limit.
  5. Horn antenna is used for the emission over 1000MHz.
  6. Emissions within the restricted band meets the requirement of FCC Part 15 Section 15.205
  7. Measurement Uncertainty is  $\pm 5.3$ dB at a level of confidence of 95%.

## TEST REPORT

### RADIATED EMISSIONS

Model: FIFA26\_050  
 Date of Test: April 17, 2025  
 Worst-Case Operating Mode: BT Operating

Table 7

Pursuant to FCC Part 15 Section 15.209 Requirement

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-amp (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	31.334	31.7	16	10.0	25.7	40.0	-14.3
H	127.970	31.3	16	14.0	29.3	43.5	-14.2
H	479.959	23.4	16	26.0	33.4	46.0	-12.6
H	491.963	21.9	16	26.0	31.9	46.0	-14.1
H	503.966	23.2	16	26.0	33.2	46.0	-12.8
V	832.069	17.0	16	31.0	32.0	46.0	-14.0

- Notes:
1. Peak Detector Data unless otherwise stated.
  2. All measurements were made at 3 meters.
  3. Negative value in the margin column shows emission below limit.
  4. Horn antenna is used for the emission over 1000MHz.
  5. Emissions within the restricted band meets the requirement of FCC Part 15 Section 15.205.
  6. Measurement Uncertainty is  $\pm 5.3$ dB at a level of confidence of 95%.

## TEST REPORT

### 4.0 EQUIPMENT PHOTOGRAPHS

For electronic filing, the photographs are saved with filename: External Photos.pdf and Internal Photos.pdf.

### 5.0 PRODUCT LABELLING

For electronic filing, the FCC ID label artwork and the label location are saved with filename: Label.pdf.

### 6.0 TECHNICAL SPECIFICATIONS

For electronic filing, the block diagram and schematic of the tested EUT are saved with filename: Block.pdf and Circuit.pdf respectively.

### 7.0 INSTRUCTION MANUAL

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: Manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

## TEST REPORT


### 8.0 MISCELLANEOUS INFORMATION

The miscellaneous information includes details of the test procedure and measured bandwidth / calculation of factor such as pulse desensitization and averaging factor (calculation and timing diagram).

#### 8.1 Radiated Emission on the Bandedge

From the following plots, they show that the fundamental emissions are confined in the specified band (2400MHz to 2483.5MHz). In case of the fundamental emissions are within two standard bandwidths from the bandedge, the delta measurement technique is used for determining bandedge compliance. Standard bandwidth is the bandwidth specified by ANSI C63.10 (2013) for frequency being measured.

Emissions radiated outside of the specified frequency bands, except harmonics, are attenuated by 50dB below the level of the fundamental or to the general radiated emissions limits in Section 15.209, whichever is the lesser attenuation, which meet the requirement of Part 15.249(d).





Spectrum Analyzer

Block diagram of Test setup

## TEST REPORT

### PEAK MEASUREMENT (GFSK)



## TEST REPORT

### PEAK MEASUREMENT (GFSK)

Bandedge compliance is determined by applying marker-delta method, i.e. (Bandedge Plot).

#### Lower Bandedge

Peak Resultant Field Strength = Fundamental Emissions (Peak Value) – delta from the plot

$$= 82.9 \text{ dB}\mu\text{V/m} - 48.5 \text{ dB}$$

$$= 34.4 \text{ dB}\mu\text{V/m}$$

Average Resultant Field Strength = Fundamental Emissions (Average Value) – delta from the plot

$$= 71.9 \text{ dB}\mu\text{V/m} - 48.5 \text{ dB}$$

$$= 23.4 \text{ dB}\mu\text{V/m}$$

#### Upper Bandedge

Peak Resultant Field Strength = Fundamental Emissions (Peak Value) – delta from the plot

$$= 83.6 \text{ dB}\mu\text{V/m} - 46.3 \text{ dB}$$

$$= 37.3 \text{ dB}\mu\text{V/m}$$

Average Resultant Field Strength = Fundamental Emissions (Average Value) – delta from the plot



$$= 72.6 \text{ dB}\mu\text{V/m} - 46.3 \text{ dB}$$

$$= 26.3 \text{ dB}\mu\text{V/m}$$

The resultant field strength meets the general radiated emission limit in Section 15.209, which does not exceed 74 dB $\mu$ V/m (Peak Limit) and 54 dB $\mu$ V/m (Average Limit).

## TEST REPORT

### PEAK MEASUREMENT ( $\pi/4$ -DQPSK)



## TEST REPORT

### PEAK MEASUREMENT ( $\pi/4$ -DQPSK)

Bandedge compliance is determined by applying marker-delta method, i.e. (Bandedge Plot).

#### Lower Bandedge

Peak Resultant Field Strength = Fundamental Emissions (Peak Value) – delta from the plot

$$\begin{aligned} &= 83.8 \text{ dB}\mu\text{V/m} - 47.2 \text{ dB} \\ &= 36.6 \text{ dB}\mu\text{V/m} \end{aligned}$$

Average Resultant Field Strength = Fundamental Emissions (Average Value) – delta from the plot

$$\begin{aligned} &= 72.8 \text{ dB}\mu\text{V/m} - 47.2 \text{ dB} \\ &= 25.6 \text{ dB}\mu\text{V/m} \end{aligned}$$

#### Upper Bandedge

Peak Resultant Field Strength = Fundamental Emissions (Peak Value) – delta from the plot

$$\begin{aligned} &= 84.4 \text{ dB}\mu\text{V/m} - 47.6 \text{ dB} \\ &= 36.8 \text{ dB}\mu\text{V/m} \end{aligned}$$

Average Resultant Field Strength = Fundamental Emissions (Average Value) – delta from the plot

$$\begin{aligned} &= 73.4 \text{ dB}\mu\text{V/m} - 47.6 \text{ dB} \\ &= 25.8 \text{ dB}\mu\text{V/m} \end{aligned}$$

The resultant field strength meets the general radiated emission limit in Section 15.209, which does not exceed 74 dB $\mu$ V/m (Peak Limit) and 54 dB $\mu$ V/m (Average Limit).

**TEST REPORT****8.2 Discussion of Pulse Desensitization**

Pulse desensitivity is not applicable for this device. The effective period (Teff) is approximately 625 $\mu$ s for a digital “1” bit which illustrated on technical specification, with a resolution bandwidth (3dB) of 3MHz, so the pulse desensitivity factor is 0dB.

**8.3 Calculation of Average Factor**

Not Applicable

## TEST REPORT

### 8.4 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services Hong Kong Ltd. in the measurements of transmitter operating under the Part 15, Subpart C rules.

The transmitting equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately 0.8m in height above the ground plane for emission measurement at or below 1GHz and 1.5m in height above the ground plane for emission measurement above 1GHz. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjusted through all three orthogonal axis to obtain maximum emission levels. The antenna height and polarization are also varied during the testing to search for maximum signal levels. The height of the antenna is varied from one to four meters.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in Exhibit 8.3.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements were made as described in ANSI C63.10 (2013).



The IF bandwidth used for measurement of radiated signal strength was 100 kHz or greater when frequency is below 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. A discussion of whether pulse desensitivity is applicable to this unit is included in this report (See Exhibit 8.1). Above 1000 MHz, a resolution bandwidth of 3 MHz is used.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the forbidden bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, unless otherwise reported. Measurements taken at a closer distance are so marked.

## TEST REPORT

### 8.4.1 Radiated Emission Test Setup

The figure below shows the test setup, which is utilized to make these measurements.




## TEST REPORT

### 8.4.2 Conducted Emission Test Procedures

For tabletop equipment, the EUT along with its peripherals were placed on a 1.0m(W)×1.5m(L) and 0.8m in height wooden table. For floor-standing equipment, the EUT and all cables were insulated, if required, from the ground plane by up to 12 mm of insulating material. The EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane. The EUT was connected to power mains through a line impedance stabilization network (LISN), which provided 50 ohm coupling impedance for measuring instrument and the chassis ground was bounded to the horizontal ground plane of shielded room. The excess power cable between the EUT and the LISN was bundled.


All connecting cables of EUT and peripherals were moved to find the maximum emission.

### 8.4.3 Conducted Emission Test Setup



## TEST REPORT

### 8.5 Occupied Bandwidth




Spectrum Analyzer

Block diagram of Test setup

#### Occupied Bandwidth Results: (GFSK)

Bluetooth (MHz)	Occupied Bandwidth (kHz)
Low Channel: 2402	840
Middle Channel: 2440	840
High Channel: 2480	848

The worst case is shown as below:




## TEST REPORT

### Occupied Bandwidth Results: ( $\pi/4$ -DQPSK)

Bluetooth (MHz)	Occupied Bandwidth (kHz)
Low Channel: 2402	1160
Middle Channel: 2440	1168
High Channel: 2480	1176

The worst case is shown as below:



## TEST REPORT

### 9.0 CONFIDENTIALITY REQUEST

For electronic filing, a preliminary copy of the confidentiality request is saved with filename: Request.pdf.

### 10.0 EQUIPMENT LIST

#### 1) Radiated Emissions Test

Equipment	EMI Test Receiver (9kHz to 26.5GHz)	Biconical Antenna (30MHz to 300MHz)	Log Periodic Antenna
Registration No.	EW-3156	EW-3242	EW-3243
Manufacturer	ROHDE SCHWARZ	EMCO	EMCO
Model No.	ESR26	3110C	3148B
Calibration Date	January 31, 2024	July 30, 2024	July 30, 2024
Calibration Due Date	May 01, 2025	July 30, 2026	July 30, 2026

Equipment	Double Ridged Guide Antenna (1GHz - 18GHz)	Active Loop Antenna (H-field) (9kHz to 30MHz)	RF Preamplifier (9kHz to 6000MHz)
Registration No.	EW-0194	EW-3326	EW-3006b
Manufacturer	EMCO	EMCO	SCHWARZBECK
Model No.	3115	6502	BBV9718
Calibration Date	May 10, 2023	January 05, 2024	October 20, 2023
Calibration Due Date	May 10, 2025	July 05, 2025	July 20, 2025

Equipment	2.4GHz Notch Filter	14m Double Shield RF Cable (9kHz - 6GHz)	RF Cable 14m (1GHz to 26.5GHz)
Registration No.	EW-3435	EW-2376	EW-2781
Manufacturer	MICROWAVE	RADIALL	GREATBILLION
Model No.	N0324413	n m/br56/bnc m 14m	SMA m/SHF5MPU /SMA m ra14m,26G
Calibration Date	September 26, 2023	September 19, 2023	January 16, 2024
Calibration Due Date	June 26, 2025	June 19, 2025	July 16, 2025

Equipment	12 metre RF Cable (1-40)GHz	Pyramidal Horn Antenna
Registration No.	EW-2774	EW-0905
Manufacturer	GREATBILLION	EMCO
Model No.	SMA m-m ra 12m 40G outdoor	3160-09
Calibration Date	January 16, 2024	December 15, 2023
Calibration Due Date	July 16, 2025	June 15, 2025

**TEST REPORT**

## 2) Conducted Emissions Test

Equipment	14m Double Shield RF Cable (9kHz - 6GHz)	Artificial Mains Network	EMI Test Receiver (9kHz to 3GHz)
Registration No.	EW-2376	EW-3360	EW-3095
Manufacturer	RADIALL	ROHDE SCHWARZ	ROHDE SCHWARZ
Model No.	n m/br56/bnc m 14m	ENV-216	ESCI
Calibration Date	September 19, 2023	April 07, 2024	January 18, 2024
Calibration Due Date	June 19, 2025	July 07, 2025	July 18, 2025

## 3) Bandedge &amp; Bandwidth Measurement

Equipment	EMI Test Receiver (9kHz to 3GHz)
Registration No.	EW-3095
Manufacturer	ROHDE SCHWARZ
Model No.	ESCI
Calibration Date	January 18, 2024
Calibration Due Date	July 18, 2025

## 4) Control Software for Radiated Emission

Software Information	
Software Name	EMC32
Manufacturer	ROHDE SCHWARZ
Software version	10.50.40

**END OF TEST REPORT**