



TEST Report

Applicant: M&M Electronics, S.A.

Address of Applicant: Cocosolito, Colon Free Zone, Main Entrance Warehouse10D and 11D, Panama,03050.

Manufacturer : M&M Electronics, S.A.

Address of Manufacturer : Cocosolito, Colon Free Zone, Main Entrance Warehouse10D and 11D, Panama,03050.

Equipment Under Test (EUT)

Product Name: Q-Book +

Model No.: QL14R5SU8256

Series model: N/A

Trade Mark: N/A

FCC ID: 2BLU9-QL14R5SU

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247

Date of sample receipt: May. 14, 2025

Date of Test: May. 14, 2025 ~ May. 27, 2025

Date of report issued: May. 27, 2025

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.



Report No.: HTT202505587F02

1. Version

Version No.	Date	Description
00	May. 27, 2025	Original

Tested/ Prepared By Heber He **Date:** May. 27, 2025
Project Engineer

Check By: Bruce Zhu **Date:** May. 27, 2025
Reviewer

Approved By : Kevin Yang **Date:** May. 27, 2025
Authorized Signature





2. Contents

Page

1. VERSION.....	2
2. CONTENTS	3
3. TEST SUMMARY	4
4. GENERAL INFORMATION.....	5
4.1. GENERAL DESCRIPTION OF EUT	5
4.2. TEST MODE	7
4.3. DESCRIPTION OF SUPPORT UNITS	7
4.4. DEVIATION FROM STANDARDS	7
4.5. ABNORMALITIES FROM STANDARD CONDITIONS.....	7
4.6. TEST FACILITY	7
4.7. TEST LOCATION	7
4.8. ADDITIONAL INSTRUCTIONS	7
5. TEST INSTRUMENTS LIST.....	7
6. TEST RESULTS AND MEASUREMENT DATA	9
6.1. CONDUCTED EMISSIONS	9
6.2. CONDUCTED PEAK OUTPUT POWER	12
6.3. CHANNEL BANDWIDTH.....	13
6.4. POWER SPECTRAL DENSITY	23
6.5. BAND EDGE	34
6.5.1. <i>Conducted Emission Method</i>	34
6.5.2. <i>Radiated Emission Method</i>	41
6.6. SPURIOUS EMISSION.....	43
6.6.1. <i>Conducted Emission Method</i>	43
6.6.2. <i>Radiated Emission Method</i>	61
6.7. ANTENNA REQUIREMENT	68
7. TEST SETUP PHOTO	69
8. EUT CONSTRUCTIONAL DETAILS	69



3. Test Summary

Test Item	Section	Result
Antenna requirement	FCC part 15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	FCC part 15.207	Pass
Conducted Peak Output Power	FCC part 15.247 (b)(3)	Pass
6dB Bandwidth	FCC part 15.247 (a)(2)	Pass
Power Spectral Density	FCC part 15.247 (e)	Pass
Band Edge	FCC part 15.247(d)	Pass
Spurious Emission	FCC part 15.205/15.209	Pass

Remark: Test according to ANSI C63.10:2013 and RSS-Gen

Pass: The EUT complies with the essential requirements in the standard.

Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	9KHz~30MHz	3.12 dB	(1)
Radiated Emission	30~1000MHz	4.37 dB	(1)
Radiated Emission	1~18GHz	5.40 dB	(1)
Radiated Emission	18-40GHz	5.45 dB	(1)
Conducted Disturbance	0.15~30MHz	2.68 dB	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.



4. General Information

4.1. General Description of EUT

Product Name:	Q-Book +
Model No.:	QL14R5SU8256
Series model:	N/A
Test sample(s) ID:	HTT202505587-1(Engineer sample) HTT202505587-2(Normal sample)
Channel numbers:	802.11b /802.11g /802.11n(HT20): 11 802.11n(HT40) :7
Channel separation:	5MHz
Modulation technology:	802.11b: Direct Sequence Spread Spectrum (DSSS) 802.11g/802.11n(H20)/802.11n(HT40): Orthogonal Frequency Division Multiplexing (OFDM)
Antenna Type:	FPC Antenna
Antenna gain:	1.77 dBi for ANT 1 and 2.86 dBi for ANT 2
Power Supply:	DC 7.6V From Battery and DC 19.0V From External Circuit
Adapter Information:	Model No: GQ48-190237-AU Input: 100-240V~ 50/60Hz 1.5A Max Output: 19.0V $\approx$ 2.37A



Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	Frequency (MHz)	
	802.11b/802.11g/802.11n(HT20)	802.11n(HT40)
Lowest channel	2412MHz	2422MHz
Middle channel	2437MHz	2437MHz
Highest channel	2462MHz	2452MHz

Ant 1

Test Software Version	RTL11ac_8822CE_MP_Tool MP_Tool		
Frequency	2412 MHz	2437MHz	2462 MHz
802.11b	2	2	2
802.11g	3	3	3
802.11n20	3	3	3
Frequency	2422 MHz	2437MHz	2452 MHz
802.11n40	3	3	3

Ant 2

Test Software Version	RTL11ac_8822CE_MP_Tool MP_Tool		
Frequency	2412 MHz	2437MHz	2462 MHz
802.11b	2	2	2
802.11g	3	3	3
802.11n20	3	3	3
Frequency	2422 MHz	2437MHz	2452 MHz
802.11n40	3	3	3



Report No.: HTT202505587F02

4.2. Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode
<i>Remark: During the test, the dutycycle >98%, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.</i>	

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:				
Pre-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.				
Mode	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)
Data rate	1Mbps	6Mbps	MCS 0	MCS 0

4.3. Description of Support Units

None.

4.4. Deviation from Standards

None.

4.5. Abnormalities from Standard Conditions

None.

4.6. Test Facility

The test facility is recognized, certified, or accredited by the following organizations: FCC-Registration No.: 779513 Designation Number: CN1319 Shenzhen HTT Technology Co.,Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements. A2LA-Lab Cert. No.: 6435.01 Shenzhen HTT Technology Co.,Ltd. has been accredited by American Association for Laboratory Accreditation to perform electromagnetic emission measurement. The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.10 and CISPR 16-1-4:2010.
--

4.7. Test Location

All tests were performed at:
Shenzhen HTT Technology Co.,Ltd. 1F, Building B, Huafeng International Robotics Industrial Park, Hangcheng Road,Nanchang Community, Xixiang Street, Bao'an District, Shenzhen, Guangdong, China Tel: 0755-23595200 Fax: 0755-23595201

4.8. Additional Instructions

Test Software	Special AT test command provided by manufacturer to Keep the EUT in continuously transmitting mode and hopping mode
Power level setup	Default

5. Test Instruments list

Item	Test Equipment	Manufacturer	Model No.	Inventory	Cal.Date	Cal.Due date
------	----------------	--------------	-----------	-----------	----------	--------------

Shenzhen HTT Technology Co.,Ltd. Tel: 0755-23595200 Fax: 0755-23595201
1F, Building B, Huafeng International Robotics Industrial Park, Hangcheng Road,Nanchang Community, Xixiang Street, Bao'an District, Shenzhen, Guangdong, China



Report No.: HTT202505587F02

				No.	(mm-dd-yy)	(mm-dd-yy)
1	3m Semi- Anechoic Chamber	Shenzhen C.R.T technology co., LTD	9*6*6	HTT-E028	Aug. 10 2024	Aug. 09 2027
2	Control Room	Shenzhen C.R.T technology co., LTD	4.8*3.5*3.0	HTT-E030	Aug. 10 2024	Aug. 09 2027
3	EMI Test Receiver	Rohde&Schwar	ESCI7	HTT-E022	Apr. 22 2025	Apr. 21 2026
4	Spectrum Analyzer	Rohde&Schwar	FSP	HTT-E037	Apr. 22 2025	Apr. 21 2026
5	Coaxial Cable	ZDecl	ZT26-NJ-NJ-0.6M	HTT-E018	Apr. 22 2025	Apr. 21 2026
6	Coaxial Cable	ZDecl	ZT26-NJ-SMAJ-2M	HTT-E019	Apr. 22 2025	Apr. 21 2026
7	Coaxial Cable	ZDecl	ZT26-NJ-SMAJ-0.6M	HTT-E020	Apr. 22 2025	Apr. 21 2026
8	Coaxial Cable	ZDecl	ZT26-NJ-SMAJ-8.5M	HTT-E021	Apr. 22 2025	Apr. 21 2026
9	Composite logarithmic antenna	Schwarzbeck	VULB 9168	HTT-E017	Apr. 19 2025	Apr. 18 2026
10	Horn Antenna	Schwarzbeck	BBHA9120D	HTT-E016	Apr. 19 2025	Apr. 18 2026
11	Loop Antenna	Zhinan	ZN30900C	HTT-E039	Apr. 19 2025	Apr. 18 2026
12	Horn Antenna	Beijing Hangwei Dayang	OBH100400	HTT-E040	Apr. 19 2025	Apr. 18 2026
13	low frequency Amplifier	Sonoma Instrument	310	HTT-E015	Apr. 22 2025	Apr. 21 2026
14	high-frequency Amplifier	HP	8449B	HTT-E014	Apr. 22 2025	Apr. 21 2026
15	Variable frequency power supply	Shenzhen Anbiao Instrument Co., Ltd	ANB-10VA	HTT-082	Apr. 22 2025	Apr. 21 2026
16	EMI Test Receiver	Rohde & Schwarz	ESCI3	HTT-E043	Apr. 22 2025	Apr. 21 2026
17	Artificial Mains	Rohde & Schwarz	ESH3-Z5	HTT-E006	Apr. 22 2025	Apr. 21 2026
18	Artificial Mains	Rohde & Schwarz	ENV-216	HTT-E038	Apr. 22 2025	Apr. 21 2026
19	Cable Line	Robinson	Z302S-NJ-BNCJ-1.5M	HTT-E001	Apr. 22 2025	Apr. 21 2026
20	Attenuator	Rohde & Schwarz	ESH3-Z2	HTT-E045	Sep. 20 2024	Sep. 19 2025
21	Variable frequency power supply	Shenzhen Yanghong Electric Co., Ltd	YF-650 (5KVA)	HTT-E032	Apr. 22 2025	Apr. 21 2026
22	Control Room	Shenzhen C.R.T technology co., LTD	8*4*3.5	HTT-E029	Aug. 10 2024	Aug. 09 2027
23	DC power supply	Agilent	E3632A	HTT-E023	Apr. 22 2025	Apr. 21 2026
24	EMI Test Receiver	Agilent	N9020A	HTT-E024	Apr. 22 2025	Apr. 21 2026
25	Analog signal generator	Agilent	N5181A	HTT-E025	Apr. 22 2025	Apr. 21 2026
26	Vector signal generator	Agilent	N5182A	HTT-E026	Apr. 22 2025	Apr. 21 2026
27	RF Switch box	Keysight	Switchbox	HTT-E047	Sep. 20 2024	Sep. 19 2025
28	Temperature and humidity meter	Shenzhen Anbiao Instrument Co., Ltd	TH10R	HTT-074	Apr. 21 2025	Apr. 20 2026
29	Radiated Emission Test Software	Farad	EZ-EMC	N/A	N/A	N/A
30	Conducted Emission Test Software	Farad	EZ-EMC	N/A	N/A	N/A
31	RF Test Software	panshanrf	TST	N/A	N/A	N/A

6. Test results and Measurement Data

6.1. Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207						
Test Method:	ANSI C63.10:2013						
Test Frequency Range:	150KHz to 30MHz						
Class / Severity:	Class B						
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto						
Limit:	Frequency range (MHz)		Limit (dBuV)				
			Quasi-peak		Average		
	0.15-0.5		66 to 56*		56 to 46*		
	0.5-5		56		46		
	5-30		60		50		
* Decreases with the logarithm of the frequency.							
Test setup:	Reference Plane <i>Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</i>						
Test procedure:	1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement.						
Test Instruments:	Refer to section 6.0 for details						
Test mode:	Refer to section 5.2 for details						
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar	
Test voltage:	AC 120V, 60Hz						
Test results:	PASS						

Remark: 1. All modes of 802.11b/g/n were tested at Low, Middle, and High channel; only the worst result of 802.11b CH11 was reported as below:


2. Both 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz power supply have been tested, only the worst result of 120 VAC, 60 Hz was reported as below:



Report No.: HTT202505587F02


Measurement data:

Line:



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz		dB	dBuV	dBuV	dB	Detector
1		0.1924	29.54	10.16	39.70	63.93	-24.23	QP
2		0.1924	22.25	10.16	32.41	53.93	-21.52	AVG
3		0.2535	29.99	10.23	40.22	61.64	-21.42	QP
4	*	0.2535	26.17	10.23	36.40	51.64	-15.24	AVG
5		0.4740	24.43	10.09	34.52	56.44	-21.92	QP
6		0.4740	17.85	10.09	27.94	46.44	-18.50	AVG
7		0.6314	23.45	10.22	33.67	56.00	-22.33	QP
8		0.6314	14.80	10.22	25.02	46.00	-20.98	AVG
9		4.1910	21.35	10.16	31.51	56.00	-24.49	QP
10		4.1910	15.22	10.16	25.38	46.00	-20.62	AVG
11		8.4525	22.65	10.10	32.75	60.00	-27.25	QP
12		8.4525	15.27	10.10	25.37	50.00	-24.63	AVG

Neutral:



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz		dB	dBuV	dBuV	dB	Detector
1		0.1995	31.03	10.20	41.23	63.63	-22.40	QP
2		0.1995	24.53	10.20	34.73	53.63	-18.90	AVG
3		0.2490	28.72	10.20	38.92	61.79	-22.87	QP
4		0.2490	24.97	10.20	35.17	51.79	-16.62	AVG
5		0.3120	23.87	10.20	34.07	59.92	-25.85	QP
6		0.3120	19.51	10.20	29.71	49.92	-20.21	AVG
7		0.6360	19.73	10.19	29.92	56.00	-26.08	QP
8		0.6360	11.96	10.19	22.15	46.00	-23.85	AVG
9		4.2900	24.50	10.18	34.68	56.00	-21.32	QP
10	*	4.2900	20.33	10.18	30.51	46.00	-15.49	AVG
11		9.1635	24.60	10.22	34.82	60.00	-25.18	QP
12		9.1635	18.95	10.22	29.17	50.00	-20.83	AVG

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level =Receiver Read level + LISN Factor + Cable Los



6.2. Conducted Peak Output Power

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)					
Test Method:	KDB558074 D01 15.247 Meas Guidance v05r02					
Limit:	30dBm					
Test setup:	Power sensor and Spectrum analyzer  Non-Conducted Table Ground Reference Plane					
Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test results:	Pass					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar

Measurement Data

Mode	TX Type	Frequency (MHz)	Maximum Peak Conducted Output Power (dBm)				Verdict
			ANT1	ANT2	MIMO	Limit	
802.11b	SISO	2412	0.82	1.42	/	<=30	Pass
		2437	0.26	1.94	/	<=30	Pass
		2462	0.82	1.17	/	<=30	Pass
802.11g	SISO	2412	4.63	4.50	/	<=30	Pass
		2437	4.50	3.73	/	<=30	Pass
		2462	4.49	3.50	/	<=30	Pass
802.11n (HT20)	MIMO	2412	4.47	3.80	7.16	<=30	Pass
		2437	4.28	3.05	6.72	<=30	Pass
		2462	4.28	2.76	6.60	<=30	Pass
802.11n (HT40)	MIMO	2422	4.67	3.79	7.26	<=30	Pass
		2437	4.40	3.31	6.90	<=30	Pass
		2452	4.50	3.27	6.94	<=30	Pass
Note1: Antenna Gain: Ant1: 1.77dBi; Ant2: 2.86dBi; Note2: Directional Gain: 2.86dBi							

6.3. Channel Bandwidth

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)					
Test Method:	KDB558074 D01 15.247 Meas Guidance v05r02					
Limit:	>500KHz					
Test setup:						
Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test results:	Pass					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar

Measurement Data

Mode	TX Type	Frequency (MHz)	ANT	6dB Bandwidth (MHz)		Verdict
				Result	Limit	
802.11b	SISO	2412	1	10.143	≥ 0.5	Pass
			2	10.135	≥ 0.5	Pass
		2437	1	10.127	≥ 0.5	Pass
			2	10.143	≥ 0.5	Pass
		2462	1	10.146	≥ 0.5	Pass
			2	10.151	≥ 0.5	Pass
802.11g	SISO	2412	1	15.659	≥ 0.5	Pass
			2	16.341	≥ 0.5	Pass
		2437	1	15.572	≥ 0.5	Pass
			2	16.341	≥ 0.5	Pass
		2462	1	15.700	≥ 0.5	Pass
			2	15.984	≥ 0.5	Pass
802.11n (HT20)	MIMO	2412	1	16.959	≥ 0.5	Pass
			2	16.368	≥ 0.5	Pass
		2437	1	16.967	≥ 0.5	Pass
			2	16.940	≥ 0.5	Pass
		2462	1	16.970	≥ 0.5	Pass
			2	16.320	≥ 0.5	Pass
802.11n (HT40)	MIMO	2422	1	35.353	≥ 0.5	Pass
			2	35.177	≥ 0.5	Pass
		2437	1	35.180	≥ 0.5	Pass
			2	35.147	≥ 0.5	Pass
		2452	1	35.199	≥ 0.5	Pass
			2	35.189	≥ 0.5	Pass

Note:



Report No.: HTT202505587F02


1) Measured peak power spectrum density at difference data rate for each mode and recorded worst case for each mode.




Report No.: HTT202505587F02

Test plot as follows:


802.11b LCH 2412MHz_Ant1 (SISO) NTN



802.11b LCH 2412MHz_Ant2 (SISO) NTN




802.11b MCH 2437MHz_Ant1 (SISO) NTN






Report No.: HTT202505587F02


802.11b MCH 2437MHz Ant2 (SISO) NTNv



802.11b HCH 2462MHz Ant1 (SISO) NTNv




802.11b HCH 2462MHz Ant2 (SISO) NTNv






Report No.: HTT202505587F02


802.11g LCH 2412MHz Ant1 (SISO) NTN



802.11g LCH 2412MHz Ant2 (SISO) NTN




802.11g MCH 2437MHz Ant1 (SISO) NTN






Report No.: HTT202505587F02


802.11g MCH 2437MHz Ant2 (SISO) NTNv



802.11g HCH 2462MHz Ant1 (SISO) NTNv




802.11g HCH 2462MHz Ant2 (SISO) NTNv






Report No.: HTT202505587F02


802.11n(HT20) LCH 2412MHz Ant1 (MIMO) NTNv



802.11n(HT20) LCH 2412MHz Ant2 (MIMO) NTNv




802.11n(HT20) MCH 2437MHz Ant1 (MIMO) NTNv






Report No.: HTT202505587F02


802.11n(HT20) MCH 2437MHz Ant2 (MIMO) NTNv



802.11n(HT20) HCH 2462MHz Ant1 (MIMO) NTNv




802.11n(HT20) HCH 2462MHz Ant2 (MIMO) NTNv






Report No.: HTT202505587F02


802.11n(HT40) LCH 2422MHz Ant1 (MIMO) NTNv



802.11n(HT40) LCH 2422MHz Ant2 (MIMO) NTNv




802.11n(HT40) MCH 2437MHz Ant1 (MIMO) NTNv






Report No.: HTT202505587F02


802.11n(HT40) MCH 2437MHz Ant2 (MIMO) NTNV




802.11n(HT40) HCH 2452MHz Ant1 (MIMO) NTNV



802.11n(HT40) HCH 2452MHz Ant2 (MIMO) NTNV



6.4. Power Spectral Density

Test Requirement:	FCC Part15 C Section 15.247 (e)					
Test Method:	KDB558074 D01 15.247 Meas Guidance v05r02					
Limit:	8dBm/3kHz					
Test setup:						
Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test results:	Pass					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar

Measurement Data

Mode	TX Type	Frequency (MHz)	Maximum PSD (dBm/3kHz)				Verdict
			ANT1	ANT2	MIMO	Limit	
802.11b	SISO	2412	-25.68	-31.03	/	<=8	Pass
		2437	-27.03	-31.57	/	<=8	Pass
		2462	-25.37	-30.50	/	<=8	Pass
802.11g	SISO	2412	-25.37	-28.61	/	<=8	Pass
		2437	-25.34	-29.47	/	<=8	Pass
		2462	-25.67	-30.52	/	<=8	Pass
802.11n (HT20)	MIMO	2412	-25.25	-28.63	-23.69	<=8	Pass
		2437	-25.87	-30.32	-24.54	<=8	Pass
		2462	-25.93	-30.58	-25.13	<=8	Pass
802.11n (HT40)	MIMO	2422	-27.31	-32.02	-26.05	<=8	Pass
		2437	-27.96	-32.62	-26.68	<=8	Pass
		2452	-27.25	-32.97	-26.40	<=8	Pass


Note1: Antenna Gain: Ant1: 1.77dBi; Ant2: 2.86dBi;
Note2: Directional Gain: 2.86dBi




Report No.: HTT202505587F02

Test plot as follows:


802.11b LCH 2412MHz_Ant1 (SISO) NTNv



802.11b LCH 2412MHz_Ant2 (SISO) NTNv




802.11b MCH 2437MHz_Ant1 (SISO) NTNv






Report No.: HTT202505587F02


802.11b_MCH_2437MHz_Ant2 (SISO)_NTNV



802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11b_HCH_2462MHz_Ant2 (SISO)_NTNV






Report No.: HTT202505587F02


802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV



802.11g_LCH_2412MHz_Ant2 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV






Report No.: HTT202505587F02


802.11g_MCH_2437MHz_Ant2 (SISO)_NTNV



802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant2 (SISO)_NTNV






Report No.: HTT202505587F02


802.11n(HT20)_LCH_2412MHz_Ant1 (MIMO)_NTNV



802.11n(HT20)_LCH_2412MHz_Ant2 (MIMO)_NTNV




802.11n(HT20)_LCH_2412MHz_MIMO_NTNV






Report No.: HTT202505587F02


802.11n(HT20)_MCH_2437MHz_Ant1 (MIMO) NTN



802.11n(HT20)_MCH_2437MHz_Ant2 (MIMO) NTN




802.11n(HT20)_MCH_2437MHz_MIMO NTN






Report No.: HTT202505587F02


802.11n(HT20) HCH_2462MHz_Ant1 (MIMO) NTN



802.11n(HT20) HCH_2462MHz_Ant2 (MIMO) NTN




802.11n(HT20) HCH_2462MHz_MIMO NTN







802.11n(HT40)_LCH_2422MHz_Ant1 (MIMO)_NTNV



802.11n(HT40)_LCH_2422MHz_Ant2 (MIMO)_NTNV




802.11n(HT40)_LCH_2422MHz_MIMO_NTNV







802.11n(HT40) MCH_2437MHz_Ant1 (MIMO) NTN



802.11n(HT40) MCH_2437MHz_Ant2 (MIMO) NTN




802.11n(HT40) MCH_2437MHz MIMO NTN







802.11n(HT40) HCH 2452MHz_Ant1 (MIMO) NTN



802.11n(HT40) HCH 2452MHz_Ant2 (MIMO) NTN




802.11n(HT40) HCH 2452MHz MIMO NTN



6.5. Band Edge


6.5.1. Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d)					
Test Method:	KDB558074 D01 15.247 Meas Guidance v05r02					
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.					
Test setup:	 The diagram illustrates the test setup for conducted emission measurement. A Spectrum Analyzer is connected via a red cable to an E.U.T. (Equipment Under Test). Both are placed on a Non-Conducted Table, which is supported by a Ground Reference Plane.					
Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test results:	Pass					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar




Test plot as follows:


802.11b LCH 2412MHz_Ant1 (SISO) NTN



802.11b LCH 2412MHz_Ant2 (SISO) NTN




802.11b HCH 2462MHz_Ant1 (SISO) NTN






Report No.: HTT202505587F02


802.11b HCH 2462MHz Ant2 (SISO) NTN



802.11g LCH 2412MHz Ant1 (SISO) NTN




802.11g LCH 2412MHz Ant2 (SISO) NTN






Report No.: HTT202505587F02


802.11g HCH 2462MHz Ant1 (SISO) NTN



802.11g HCH 2462MHz Ant2 (SISO) NTN




802.11n(HT20) LCH 2412MHz Ant1 (MIMO) NTN






Report No.: HTT202505587F02


802.11n(HT20) LCH 2412MHz Ant2 (MIMO) NTN



802.11n(HT20) HCH 2462MHz Ant1 (MIMO) NTN




802.11n(HT20) HCH 2462MHz Ant2 (MIMO) NTN






Report No.: HTT202505587F02


802.11n(HT40) LCH 2422MHz Ant1 (MIMO) NTN



802.11n(HT40) LCH 2422MHz Ant2 (MIMO) NTN




802.11n(HT40) HCH 2452MHz Ant1 (MIMO) NTN






Report No.: HTT202505587F02

802.11n(HT40) HCH 2452MHz Ant2 (MIMO) NTV



6.5.2. Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209 and 15.205						
Test Method:	ANSI C63.10: 2013						
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.						
Test site:	Measurement Distance: 3m						
Receiver setup:	Frequency	Detector		RBW	VBW	Remark	
	Above 1GHz	Peak		1MHz	3MHz	Peak Value	
		Peak		1MHz	10Hz	Average Value	
Limit:	Frequency			Limit (dBuV/m @3m)		Remark	
	Above 1GHz			54.00		Average Value	
				74.00		Peak Value	
Test setup:							
Test Procedure:	1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.						
Test Instruments:	Refer to section 6.0 for details						
Test mode:	Refer to section 5.2 for details						
Test results:	Pass						
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar	


**Measurement Data**

Remark: During the test, pre-scan the 802.11b/802.11g/802.11n (H20)/802.11n (H40) modulation, and found the 802.11n20 MIMO modulation which it is worse case.

Frequency(MHz):			2412		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2390.00	61.28	PK	74	12.72	62.67	27.2	4.31	32.9	-1.39
2390.00	43.38	AV	54	10.62	44.77	27.2	4.31	32.9	-1.39
Frequency(MHz):			2412		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2390.00	60.50	PK	74	13.50	61.89	27.2	4.31	32.9	-1.39
2390.00	46.74	AV	54	7.26	48.13	27.2	4.31	32.9	-1.39
Frequency(MHz):			2462		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2483.50	57.69	PK	74	16.31	58.62	27.4	4.47	32.8	-0.93
2483.50	43.82	AV	54	10.18	44.75	27.4	4.47	32.8	-0.93
Frequency(MHz):			2462		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2483.50	54.80	PK	74	19.20	55.73	27.4	4.47	32.8	-0.93
2483.50	44.93	AV	54	9.07	45.86	27.4	4.47	32.8	-0.93

6.6. Spurious Emission

6.6.1. Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	KDB558074 D01 15.247 Meas Guidance v05r02
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass
Test environment:	Temp.: 25 °C Humid.: 52% Press.: 1012mbar

Measurement Data:

Mode	TX Type	Frequency (MHz)	ANT	Level of Reference (dBm)
802.11b	SISO	2412	1	-10.98
			2	-16.20
		2437	1	-11.49
			2	-16.76
		2462	1	-11.00
			2	-17.00
802.11g	SISO	2412	1	-11.07
			2	-14.80
		2437	1	-10.56
			2	-15.10
		2462	1	-10.70
			2	-15.40
802.11n (HT20)	MIMO	2412	1	-11.12
			2	-14.38
		2437	1	-10.72
			2	-15.59
		2462	1	-10.75
			2	-15.47
802.11n (HT40)	MIMO	2422	1	-13.86
			2	-17.60




Report No.: HTT202505587F02

		2437	1	-13.73
			2	-17.91
		2452	1	-13.98
			2	-17.86
Note1: Refer to FCC Part 15.247 (d) and ANSI C63.10-2013, the channel contains the maximum PSD level was used to establish the reference level.				




Report No.: HTT202505587F02


802.11b LCH 2412MHz_Ant1 (SISO) NTN



802.11b LCH 2412MHz_Ant2 (SISO) NTN




802.11b MCH 2437MHz_Ant1 (SISO) NTN






Report No.: HTT202505587F02


802.11b MCH 2437MHz_Ant2 (SISO) NTNv



802.11b HCH 2462MHz_Ant1 (SISO) NTNv




802.11b HCH 2462MHz_Ant2 (SISO) NTNv






Report No.: HTT202505587F02


802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV



802.11g_LCH_2412MHz_Ant2 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV






Report No.: HTT202505587F02


802.11g MCH 2437MHz_Ant2 (SISO) NTNv



802.11g HCH 2462MHz_Ant1 (SISO) NTNv




802.11g HCH 2462MHz_Ant2 (SISO) NTNv






Report No.: HTT202505587F02


802.11n(HT20) LCH 2412MHz_Ant1 (MIMO) NTN



802.11n(HT20) LCH 2412MHz_Ant2 (MIMO) NTN




802.11n(HT20) MCH 2437MHz_Ant1 (MIMO) NTN






Report No.: HTT202505587F02


802.11n(HT20) MCH 2437MHz Ant2 (MIMO) NTN



802.11n(HT20) HCH 2462MHz Ant1 (MIMO) NTN




802.11n(HT20) HCH 2462MHz Ant2 (MIMO) NTN






Report No.: HTT202505587F02


802.11n(HT40) LCH 2422MHz_Ant1 (MIMO) NTN



802.11n(HT40) LCH 2422MHz_Ant2 (MIMO) NTN




802.11n(HT40) MCH 2437MHz_Ant1 (MIMO) NTN






Report No.: HTT202505587F02


802.11n(HT40) MCH 2437MHz_Ant2 (MIMO) NTNv



802.11n(HT40) HCH 2452MHz_Ant1 (MIMO) NTNv




802.11n(HT40) HCH 2452MHz_Ant2 (MIMO) NTNv






Report No.: HTT202505587F02


802.11b_LCH_2412MHz_Ant1 (SISO)_NTNV



802.11b_LCH_2412MHz_Ant2 (SISO)_NTNV




802.11b_MCH_2437MHz_Ant1 (SISO)_NTNV






Report No.: HTT202505587F02


802.11b_MCH_2437MHz_Ant2 (SISO)_NTNV



802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11b_HCH_2462MHz_Ant2 (SISO)_NTNV






Report No.: HTT202505587F02


802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV



802.11g_LCH_2412MHz_Ant2 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV






Report No.: HTT202505587F02


802.11g_MCH_2437MHz_Ant2 (SISO)_NTNV



802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant2 (SISO)_NTNV






Report No.: HTT202505587F02


802.11n(HT20)_LCH_2412MHz_Ant1 (MIMO)_NTNV



802.11n(HT20)_LCH_2412MHz_Ant2 (MIMO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant1 (MIMO)_NTNV






Report No.: HTT202505587F02


802.11n(HT20) MCH 2437MHz_Ant2 (MIMO) NTNv



802.11n(HT20) HCH 2462MHz_Ant1 (MIMO) NTNv




802.11n(HT20) HCH 2462MHz_Ant2 (MIMO) NTNv






Report No.: HTT202505587F02


802.11n(HT40)_LCH_2422MHz_Ant1 (MIMO)_NTNV



802.11n(HT40)_LCH_2422MHz_Ant2 (MIMO)_NTNV




802.11n(HT40)_MCH_2437MHz_Ant1 (MIMO)_NTNV






Report No.: HTT202505587F02


802.11n(HT40) MCH_2437MHz_Ant2 (MIMO) NTN




802.11n(HT40) HCH_2452MHz_Ant1 (MIMO) NTN






802.11n(HT40) HCH_2452MHz_Ant2 (MIMO) NTN



6.6.2. Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Limit:	Frequency	Limit (uV/m)	Value	Measurement Distance	
	0.009MHz-0.490MHz	2400/F(KHz)	QP	300m	
	0.490MHz-1.705MHz	24000/F(KHz)	QP	30m	
	1.705MHz-30MHz	30	QP	30m	
	30MHz-88MHz	100	QP	3m	
	88MHz-216MHz	150	QP		
	216MHz-960MHz	200	QP		
	960MHz-1GHz	500	QP		
	Above 1GHz	500	Average		
		5000	Peak		
Test setup:	For radiated emissions from 9kHz to 30MHz				
					

	For radiated emissions from 30MHz to 1GHz  For radiated emissions above 1GHz  
Test Procedure:	1. The EUT was placed on the top of a rotating table (0.8m for below 1G and 1.5m for above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.



Report No.: HTT202505587F02

	5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.					
Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
Test voltage:	AC 120V, 60Hz					
Test results:	Pass					

Remarks:


- 1. This test was performed with EUT in X, Y, Z position and the worse case was found when EUT in X position.*
- 2. All three channels (lowest/middle/highest) of each mode were measured below 1GHz and recorded worst case at 802.11n20 MIMO low channel.*
- 3. Radiated emission test from 9 KHz to 10th harmonic of fundamental was verified, and no emission found except system noise floor in 9 KHz to 30MHz and not recorded in this report.*

Measurement data:


■ **9kHz~30MHz**

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.

Below 1GHz



Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1		50.4089	32.46	-11.37	21.09	40.00	-18.91	peak
2		100.5806	40.71	-14.77	25.94	43.50	-17.56	peak
3		251.1803	40.02	-11.47	28.55	46.00	-17.45	peak
4		419.1080	37.88	-7.31	30.57	46.00	-15.43	peak
5		625.0779	35.96	-3.17	32.79	46.00	-13.21	peak
6	*	801.7862	36.35	0.24	36.59	46.00	-9.41	peak

Final Level =Receiver Read level + Correct Factor



■ Above 1-25GHz

Remark: During the test, pre-scan the 802.11b/802.11g/802.11n (H20)/802.11n (H40) modulation, and found the 802.11n20 MIMO modulation which it is worse case.

802.11n20MIMO:

Frequency(MHz):			2412		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4824.00	59.01	PK	74	14.99	53.19	31.05	6.52	31.75	5.82
4824.00	43.35	AV	54	10.65	37.53	31.05	6.52	31.75	5.82
7236.00	56.95	PK	74	17.05	44.14	36.08	8.18	31.45	12.81
7236.00	47.53	AV	54	6.47	34.72	36.08	8.18	31.45	12.81

Frequency(MHz):			2412		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4824.00	59.53	PK	74	14.47	53.71	31.05	6.52	31.75	5.82
4824.00	42.97	AV	54	11.03	37.15	31.05	6.52	31.75	5.82
7236.00	55.96	PK	74	18.04	43.15	36.08	8.18	31.45	12.81
7236.00	47.06	AV	54	6.94	34.25	36.08	8.18	31.45	12.81

Frequency(MHz):			2437		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4874.00	60.88	PK	74	13.12	54.44	31.25	6.7	31.51	6.44
4874.00	45.62	AV	54	8.38	39.18	31.25	6.7	31.51	6.44
7311.00	56.15	PK	74	17.85	43.01	36.25	8.31	31.42	13.14
7311.00	45.44	AV	54	8.56	32.30	36.25	8.31	31.42	13.14



Report No.: HTT202505587F02

Frequency(MHz):			2437		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre- amplifier (dB)	Correction Factor (dB/m)
4874.00	60.85	PK	74	13.15	54.41	31.25	6.7	31.51	6.44
4874.00	44.73	AV	54	9.27	38.29	31.25	6.7	31.51	6.44
7311.00	56.12	PK	74	17.88	42.98	36.25	8.31	31.42	13.14
7311.00	47.04	AV	54	6.96	33.90	36.25	8.31	31.42	13.14

Frequency(MHz):			2462		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre- amplifier (dB)	Correction Factor (dB/m)
4924.00	60.08	PK	74	13.92	53.21	31.52	6.8	31.45	6.87
4924.00	44.96	AV	54	9.04	38.09	31.52	6.8	31.45	6.87
7386.00	56.31	PK	74	17.69	42.75	36.51	8.4	31.35	13.56
7386.00	47.19	AV	54	6.81	33.63	36.51	8.4	31.35	13.56

Frequency(MHz):			2462		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre- amplifier (dB)	Correction Factor (dB/m)
4924.00	61.89	PK	74	12.11	55.02	31.52	6.8	31.45	6.87
4924.00	45.64	AV	54	8.36	38.77	31.52	6.8	31.45	6.87
7386.00	57.49	PK	74	16.51	43.93	36.51	8.4	31.35	13.56
7386.00	46.78	AV	54	7.22	33.22	36.51	8.4	31.35	13.56

Remark:

(1) Data of measurement within this frequency range shown “---” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

(2) When the test results of Peak Detected below the limits of Average Detected, the Average Detected is not need completed.



6.7. Antenna Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited

FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1) (I):

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

Antenna Connected Construction

The maximum gain of antenna was 1.77 dBi for ANT 1 and 2.86 dBi for ANT 2.

Remark: The antenna gain is provided by the customer, if the data provided by the customer is not accurate, Shenzhen HTT Technology Co., Ltd. does not assume any responsibility.



7. Test Setup Photo

Reference to the **appendix I** for details.

8. EUT Constructional Details

Reference to the **appendix II** for details.

-----End-----