



RF Exposure Evaluation

According to KDB 447498 D01 General RF Exposure Guidance v06 and part 2.1093, Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition(s), listed below, is (are) satisfied.

For 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR, where

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

Here,

The device has been evaluated to meet general RF exposure requirement. The device can be used in portable exposure condition without restriction.

For BR+EDR

Max Conducted Power(dBm)	Tune-up Power(dBm)	Max Tune-up Power(dBm)	Max Power(mW)	Frequency(MHz)	Min. distance(mm)	Calc. thresholds	limit
-2.85	-2(± 1)	-1	0.794	2441	5	0.2481	3.0

For 2.4GWiFi

Max Conducted Power(dBm)	Tune-up Power(dBm)	Max Tune-up Power(dBm)	Max Power(mW)	Frequency(MHz)	Min. distance(mm)	Calc. thresholds	limit
7.26	7(± 1)	8	6.310	2437	5	1.970	3.0

For 5.2GWiFi

Max Conducted Power(dBm)	Tune-up Power(dBm)	Max Tune-up Power(dBm)	Max Power(mW)	Frequency(MHz)	Min. distance(mm)	Calc. thresholds	limit
5.38	5(± 1)	6	3.981	5230	5	1.820	3.0



For 5.8GWiFi

Max Conducted Power(dBm)	Tune-up Power(dBm)	Max Tune-up Power(dBm)	Max Power(mW)	Frequency(MHz)	Min. distance(mm)	Calc. thresholds	limit
5	5(±1)	6	3.981	5785	5	1.915	3.0

Remark: antenna gain= BLE:1.5dBi, 2.4GWiFi:1.5dBi, 5.2GWiFi:1.5dBi, 5.8GWiFi:1.5dBi

The device cannot transmit with 2.4G WI-FI and 5.2, 5.8G WI-FI simultaneously, can transmit with 2.4G WI-FI ,5.2, 5.8G WI-FI and BR+EDR simultaneously.

Calculations for simultaneously transmit

Mode	Ratios	Result	Limit	Result
BR+EDR	0.0827	0.7393	3	PASS
2.4G Wi-Fi	0.6566			

Mode	Ratios	Result	Limit	Result
BR+EDR	0.0827	0.6893	3	PASS
5.2G Wi-Fi	0.6066			

Mode	Ratios	Result	Limit	Result
BR+EDR	0.0827	0.721	3	PASS
5.8G Wi-Fi	0.6383			

Ratios = Power Density / Power density Limit

So a SAR test is not required