

## RF Exposure Evaluation

According to KDB 447498 D01 General RF Exposure Guidance v06 and part 2.1091, Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition(s), listed below, is (are) satisfied.

### Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

#### Limits for Maximum Permissible Exposure (MPE)

| Frequency range (MHz)                                   | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm <sup>2</sup> ) | Averaging time (minutes) |
|---|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| (A) Limits for Occupational/Controlled Exposures        |                               |                               |                                     |                          |
| 0.3–3.0   | 614                           | 1.63                          | *(100)                              | 6                        |
| 3.0–30  | 1842/f                        | 4.89/f                        | *(900/f <sup>2</sup> )              | 6                        |
| 30–300  | 61.4                          | 0.163                         | 1.0                                 | 6                        |
| 300–1500  |                               |                               | f/300                               | 6                        |
| 1500–100,000  |                               |                               | 5                                   | 6                        |
| (B) Limits for General Population/Uncontrolled Exposure |                               |                               |                                     |                          |
| 0.3–1.34  | 614                           | 1.63                          | *(100)                              | 30                       |
| 1.34–30   | 824/f                         | 2.19/f                        | *(180/f <sup>2</sup> )              | 30                       |
| 30–300  | 27.5                          | 0.073                         | 0.2                                 | 30                       |
| 300–1500  |                               |                               | f/1500                              | 30                       |
| 1500–100,000  |                               |                               | 1.0                                 | 30                       |

f = frequency in MHz

Friis transmission formula:  $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

**Pd** = power density in mW/cm<sup>2</sup>, **Pout** = output power to antenna in mW;

**G** = gain of antenna in linear scale, **Pi** = 3.1416;

**R** = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

### Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

### Test Result of RF Exposure Evaluation

| Modulation | Frequency MHz | Output power to antenna (dBm) | Target power W/tolerance (dBm) | Max Output power to antenna (dBm) | Max Output power to antenna (mW) | Power Density at R=20cm (mW/cm <sup>2</sup> ) | Limit (mW/cm <sup>2</sup> ) | Result |
|------------|---------------|-------------------------------|--------------------------------|-----------------------------------|----------------------------------|---|-----------------------------|--------|
| GFSK       | 2402          | -3.19                         | -3±1                           | -2                                | 0.631                            | 0.000186                                      | 1.0                         | PASS   |
|            | 2441          | -2.97                         | -3±1                           | -2                                | 0.631                            | 0.000186                                      | 1.0                         | PASS   |
|            | 2480          | -3.03                         | -3±1                           | -2                                | 0.631                            | 0.000186                                      | 1.0                         | PASS   |
| Π/4-DQPSK  | 2402          | -2.23                         | -2.5±1                         | -1.5                              | 0.708                            | 0.000208                                      | 1.0                         | PASS   |
|            | 2441          | -2.90                         | -2.5±1                         | -1.5                              | 0.708                            | 0.000208                                      | 1.0                         | PASS   |
|            | 2480          | -2.36                         | -2.5±1                         | -1.5                              | 0.708                            | 0.000208                                      | 1.0                         | PASS   |
| 8DPSK      | 2402          | -1.84                         | -2±1                           | -1                                | 0.794                            | 0.000234                                      | 1.0                         | PASS   |
|            | 2441          | -1.79                         | -2±1                           | -1                                | 0.794                            | 0.000234                                      | 1.0                         | PASS   |
|            | 2480          | -1.96                         | -2±1                           | -1                                | 0.794                            | 0.000234                                      | 1.0                         | PASS   |

So a SAR test is not required