

Fasikl Incorporated

TEST REPORT

SCOPE OF WORK

EMC TESTING–Felix-G1

REPORT NUMBER

241119101GZU-002

ISSUE DATE

24-December-2024

[REVISED DATE]

[-----]

PAGES

8

DOCUMENT CONTROL NUMBER

© 2017 INTERTEK



TEST REPORT

Applicant Name & : Fasikl Incorporated
Address : 8500 Normandale Lake Blvd, Suite 400, Bloomington, MN 55437, USA
Manufacturing Site : Same as applicant
Intertek Report No: 241119101GZU-002
FCC ID: 2BMCX-FELIX2


Test standards

47 CFR PART 1, Subpart I, Section 1.1310
KDB 680106 D01 Wireless Power Transfer v04

Sample Description

Product : Wireless Charger
Model No. : Felix-G1
Electrical Rating : Input: DC 5V/1A
Serial No. : Not Labeled
Date Received : 19 November 2024
Date Test : 11 December 2024
Conducted

Prepared and Checked By



Elena Lei

Project Engineer

Approved By:



Dean Liu

Sr. Project Engineer

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

TEST REPORT

CONTENT

TEST REPORT **1**

CONTENT **3**

1.0 TEST RESULT SUMMARY **4**

2.0 GENERAL DESCRIPTION **5**

 2.1 PRODUCT DESCRIPTION 5

 2.2 TEST FACILITY 5

 2.3 EUT EXERCISING SOFTWARE 5

 2.4 SPECIAL ACCESSORIES 5

 2.5 EQUIPMENT MODIFICATION 5

 2.6 SUPPORT EQUIPMENT LIST AND DESCRIPTION 6

3.0 EMF TEST **7**

 3.1 STANDARD REQUIREMENT 7

 3.2 TEST DATA 8

4.0 TEST EQUIPMENT LIST **8**

TEST REPORT

1.0 TEST RESULT SUMMARY

Classification of EUT: Class B

Test Item	Standard	Result
EMF	47 CFR PART 1, Subpart I, Section 1.1310	PASS

Remark:

When determining the test results, measurement uncertainty of tests has been considered.

TEST REPORT

2.0 General Description

2.1 Product Description

Operating Frequency	325KHz
Type of Modulation:	Load modulation
Antenna Type	Inductive loop coil antenna
Power Supply:	DC 5V/1A by Adapter
Power cord:	N/A

2.2 Test Facility

Room102/104, No 203, KeZhu Road, Science City, GETDD Guangzhou, China

A2LA Certificate Number 0078.10

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch is accredited by A2LA and Listed in FCC website. FCC accredited test labs may perform both Certification testing under Parts 15 and 18 and Declaration of Conformity testing.

2.3 EUT Exercising Software

Once it's powered, it keeps transmitting.

2.4 Special Accessories

N/A

2.5 Equipment Modification

Any modifications installed previous to testing by Fasikl Incorporated will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd. Guangzhou Branch.

TEST REPORT

2.6 Support Equipment List and Description

This product was tested with corresponding support equipment as below:
Support equipment

Description	Model No.	Rating	Supplied by
Felix™ NeuroAI™ Wristband	FELIX-G1	DC5V,1A	applicant
Adapter	CH-P002	100-240~, 50/60Hz,	Intertek

Remark: Felix™ NeuroAI™ Wristband was the client devices, it's selected such that the EUT was fully exercised at maximum power from its transmitter. It will be sold together.

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above evaluated respectively

Pre-test mode	Description	
Standby Mode	kept transmitting continuously	
Charging Mode	CH: Low	Felix™ NeuroAI™ Wristband client is charging at 1% battery power, 50% and 99% battery power respectively, keep transmitting continuously.
	CH: Middle	
	CH: High	

TEST REPORT

3.0 EMF TEST

3.1 Standard Requirement

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.1m normally can be maintained between the user and the device.

(a) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S)(mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	--	--	F/300	6
1500-100000	--	--	5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S)(mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	F/1500	30
1500-100000	--	--	1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

TEST REPORT

3.2 Test Data

Input Voltage: 120V/60Hz
Ambient Condition: 25°C, 54.6%RH

Test distance: 20 cm surrounding the device, and 20 cm away from the surface from the coil.

H-Filed Strength:

Test Position	Probe Measure Result (A/m)			50% Limit (A/m)	Limit (A/m)
	Mobile in 1% battery power	Mobile in 50% battery power	Mobile in 99% battery power		
Side 1	0.072	0.064	0.069	0.815	1.63
Side 2	0.077	0.072	0.068	0.815	1.63
Side 3	0.081	0.073	0.077	0.815	1.63
Side 4	0.082	0.069	0.076	0.815	1.63
Top	0.079	0.073	0.075	0.815	1.63

MPE ratio:
 $0.082 \text{ (A/m)} / 0.815 \text{ (A/m)} = 0.1006$

4.0 Test Equipment List

Equip. No.	Equipment	Model	Manufacturer	Cal. date	Due date
EM007-03	Exposure Level Tester	ELT-400	NARDA	11/03/2024	10/03/2025

*****End of the test report*****