

RF Exposure Evaluation

REQUIREMENT

KDB447498 D01 General RF Exposure Guidance v06, Clause 4.3.1(a)

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$

Where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

TEST RESULT

☒ Passed ☐ Not Applicable

| Radio Type | Frequency range (MHz) | Conducted Power (dBm) | Maximum Tune-up (dBm) | Calculating data | Limit | Result |
|------------|-----------------------|-----------------------|-----------------------|------------------|-------|--------|
| GFSK       | 2403-2479             | -1.67                 | -1.50                 | 0.2199           | 3.00  | Pass   |

Note:

- 1) The maximum antenna gain is 1.80dBi
- 2) The exposure evaluation safety distance is 5mm.