

|            |                         |
|------------|-------------------------|
| Test Mode: | TX(5.3G) - 802.11n-HT20 |
|------------|-------------------------|

| Polar                              | Frequency | Reading Level | Correct Factor | Measurement | Limits   | Over   | Detector Type |
|------------------------------------|-----------|---------------|----------------|-------------|----------|--------|---------------|
| (H/V)                              | (MHz)     | (dBuV/m)      | (dB)           | (dBuV/m)    | (dBuV/m) | (dB)   |               |
| Low Channel (5260 MHz)-Above 1G    |           |               |                |             |          |        |               |
| Vertical                           | 4434.019  | 74.65         | -20.73         | 53.92       | 68.20    | -14.28 | PK            |
| Vertical                           | 4434.019  | 59.98         | -20.73         | 39.25       | 54.00    | -14.75 | AV            |
| Vertical                           | 10520.085 | 62.06         | -9.12          | 52.94       | 68.20    | -15.26 | PK            |
| Vertical                           | 10520.085 | 49.82         | -9.12          | 40.70       | 54.00    | -13.30 | AV            |
| Vertical                           | 15780.127 | 60.83         | -7.77          | 53.06       | 74.00    | -20.94 | PK            |
| Vertical                           | 15780.127 | 49.15         | -7.77          | 41.38       | 54.00    | -12.62 | AV            |
| Horizontal                         | 4434.132  | 74.29         | -20.73         | 53.56       | 68.20    | -14.64 | PK            |
| Horizontal                         | 4434.132  | 59.87         | -20.73         | 39.14       | 54.00    | -14.86 | AV            |
| Horizontal                         | 10520.084 | 61.45         | -9.12          | 52.33       | 68.20    | -15.87 | PK            |
| Horizontal                         | 10520.084 | 49.52         | -9.12          | 40.40       | 54.00    | -13.60 | AV            |
| Horizontal                         | 15780.136 | 60.81         | -7.77          | 53.04       | 74.00    | -20.96 | PK            |
| Horizontal                         | 15780.136 | 49.17         | -7.77          | 41.40       | 54.00    | -12.60 | AV            |
| Middle Channel (5280 MHz)-Above 1G |           |               |                |             |          |        |               |
| Vertical                           | 4592.127  | 72.60         | -20.42         | 52.19       | 74.00    | -21.81 | PK            |
| Vertical                           | 4592.127  | 59.72         | -20.42         | 39.31       | 54.00    | -14.69 | AV            |
| Vertical                           | 10560.119 | 64.05         | -9.06          | 54.99       | 68.20    | -13.21 | PK            |
| Vertical                           | 10560.119 | 49.24         | -9.06          | 40.18       | 54.00    | -13.82 | AV            |
| Vertical                           | 15840.115 | 62.76         | -7.75          | 55.01       | 74.00    | -18.99 | PK            |
| Vertical                           | 15840.115 | 49.18         | -7.75          | 41.43       | 54.00    | -12.57 | AV            |
| Horizontal                         | 4592.096  | 73.06         | -20.42         | 52.64       | 74.00    | -21.36 | PK            |
| Horizontal                         | 4592.096  | 59.69         | -20.42         | 39.28       | 54.00    | -14.72 | AV            |
| Horizontal                         | 10560.044 | 62.62         | -9.06          | 53.56       | 68.20    | -14.64 | PK            |
| Horizontal                         | 10560.044 | 49.33         | -9.06          | 40.27       | 54.00    | -13.73 | AV            |
| Horizontal                         | 15840.101 | 64.92         | -7.75          | 57.17       | 74.00    | -16.83 | PK            |
| Horizontal                         | 15840.101 | 49.44         | -7.75          | 41.69       | 54.00    | -12.31 | AV            |
| High Channel (5320 MHz)-Above 1G   |           |               |                |             |          |        |               |
| Vertical                           | 4739.000  | 70.27         | -20.12         | 50.15       | 74.00    | -23.85 | PK            |
| Vertical                           | 4739.000  | 59.06         | -20.12         | 38.94       | 54.00    | -15.06 | AV            |
| Vertical                           | 10640.069 | 64.25         | -8.94          | 55.31       | 68.20    | -12.89 | PK            |
| Vertical                           | 10640.069 | 49.92         | -8.94          | 40.98       | 54.00    | -13.02 | AV            |
| Vertical                           | 15960.069 | 64.63         | -7.71          | 56.92       | 74.00    | -17.08 | PK            |
| Vertical                           | 15960.069 | 49.54         | -7.71          | 41.83       | 54.00    | -12.17 | AV            |
| Horizontal                         | 4739.004  | 73.82         | -20.12         | 53.69       | 74.00    | -20.31 | PK            |
| Horizontal                         | 4739.004  | 59.12         | -20.12         | 39.00       | 54.00    | -15.00 | AV            |
| Horizontal                         | 10640.125 | 62.09         | -8.94          | 53.15       | 68.20    | -15.05 | PK            |
| Horizontal                         | 10640.125 | 49.25         | -8.94          | 40.31       | 54.00    | -13.69 | AV            |
| Horizontal                         | 15960.033 | 63.82         | -7.71          | 56.11       | 74.00    | -17.89 | PK            |
| Horizontal                         | 15960.033 | 49.58         | -7.71          | 41.87       | 54.00    | -12.13 | AV            |

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

|            |                         |
|------------|-------------------------|
| Test Mode: | TX(5.3G) - 802.11n-HT40 |
|------------|-------------------------|

| Polar                              | Frequency | Reading Level | Correct Factor | Measurement | Limits   | Over   | Detector Type |
|------------------------------------|-----------|---------------|----------------|-------------|----------|--------|---------------|
| (H/V)                              | (MHz)     | (dBuV/m)      | (dB)           | (dBuV/m)    | (dBuV/m) | (dB)   |               |
| Low Channel (5270 MHz)-Above 1G    |           |               |                |             |          |        |               |
| Vertical                           | 4434.007  | 73.40         | -20.73         | 52.66       | 68.20    | -15.54 | PK            |
| Vertical                           | 4434.007  | 59.62         | -20.73         | 38.89       | 54.00    | -15.11 | AV            |
| Vertical                           | 10540.133 | 61.15         | -9.09          | 52.06       | 68.20    | -16.14 | PK            |
| Vertical                           | 10540.133 | 49.99         | -9.09          | 40.90       | 54.00    | -13.10 | AV            |
| Vertical                           | 15810.095 | 63.95         | -7.76          | 56.19       | 74.00    | -17.81 | PK            |
| Vertical                           | 15810.095 | 49.78         | -7.76          | 42.02       | 54.00    | -11.98 | AV            |
| Horizontal                         | 4434.109  | 73.35         | -20.73         | 52.62       | 74.00    | -21.38 | PK            |
| Horizontal                         | 4434.109  | 59.69         | -20.73         | 38.96       | 54.00    | -15.04 | AV            |
| Horizontal                         | 10540.106 | 64.52         | -9.09          | 55.43       | 68.20    | -12.77 | PK            |
| Horizontal                         | 10540.106 | 49.16         | -9.09          | 40.07       | 54.00    | -13.93 | AV            |
| Horizontal                         | 15810.069 | 60.33         | -7.76          | 52.57       | 74.00    | -21.43 | PK            |
| Horizontal                         | 15810.069 | 49.93         | -7.76          | 42.17       | 54.00    | -11.83 | AV            |
| Middle Channel (5310 MHz)-Above 1G |           |               |                |             |          |        |               |
| Vertical                           | 4739.023  | 71.88         | -20.12         | 51.76       | 68.20    | -16.44 | PK            |
| Vertical                           | 4739.023  | 59.40         | -20.12         | 39.28       | 54.00    | -14.72 | AV            |
| Vertical                           | 10620.043 | 64.66         | -8.97          | 55.69       | 68.20    | -12.51 | PK            |
| Vertical                           | 10620.043 | 49.34         | -8.97          | 40.37       | 54.00    | -13.63 | AV            |
| Vertical                           | 15930.010 | 61.25         | -7.72          | 53.53       | 74.00    | -20.47 | PK            |
| Vertical                           | 15930.010 | 49.61         | -7.72          | 41.89       | 54.00    | -12.11 | AV            |
| Horizontal                         | 4739.038  | 72.91         | -20.12         | 52.79       | 68.20    | -15.41 | PK            |
| Horizontal                         | 4739.038  | 59.10         | -20.12         | 38.98       | 54.00    | -15.02 | AV            |
| Horizontal                         | 10620.011 | 63.01         | -8.97          | 54.04       | 68.20    | -14.16 | PK            |
| Horizontal                         | 10620.011 | 49.79         | -8.97          | 40.82       | 54.00    | -13.18 | AV            |
| Horizontal                         | 15930.161 | 64.01         | -7.72          | 56.29       | 74.00    | -17.71 | PK            |
| Horizontal                         | 15930.161 | 49.74         | -7.72          | 42.02       | 54.00    | -11.98 | AV            |

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

|            |                          |
|------------|--------------------------|
| Test Mode: | TX(5.3G) - 802.11ac-HT20 |
|------------|--------------------------|

| Polar                              | Frequency | Reading Level | Correct Factor | Measurement | Limits   | Over   | Detector Type |
|------------------------------------|-----------|---------------|----------------|-------------|----------|--------|---------------|
| (H/V)                              | (MHz)     | (dBuV/m)      | (dB)           | (dBuV/m)    | (dBuV/m) | (dB)   |               |
| Low Channel (5260 MHz)-Above 1G    |           |               |                |             |          |        |               |
| Vertical                           | 4434.194  | 71.91         | -20.73         | 51.18       | 68.20    | -17.02 | PK            |
| Vertical                           | 4434.194  | 59.68         | -20.73         | 38.95       | 54.00    | -15.05 | AV            |
| Vertical                           | 10520.097 | 61.94         | -9.12          | 52.82       | 68.20    | -15.38 | PK            |
| Vertical                           | 10520.097 | 49.48         | -9.12          | 40.36       | 54.00    | -13.64 | AV            |
| Vertical                           | 15780.064 | 62.26         | -7.77          | 54.49       | 74.00    | -19.51 | PK            |
| Vertical                           | 15780.064 | 49.25         | -7.77          | 41.48       | 54.00    | -12.52 | AV            |
| Horizontal                         | 4434.042  | 74.40         | -20.73         | 53.67       | 68.20    | -14.53 | PK            |
| Horizontal                         | 4434.042  | 59.76         | -20.73         | 39.03       | 54.00    | -14.97 | AV            |
| Horizontal                         | 10520.060 | 63.31         | -9.12          | 54.19       | 68.20    | -14.01 | PK            |
| Horizontal                         | 10520.060 | 49.39         | -9.12          | 40.27       | 54.00    | -13.73 | AV            |
| Horizontal                         | 15780.186 | 60.34         | -7.77          | 52.57       | 74.00    | -21.43 | PK            |
| Horizontal                         | 15780.186 | 49.28         | -7.77          | 41.51       | 54.00    | -12.49 | AV            |
| Middle Channel (5280 MHz)-Above 1G |           |               |                |             |          |        |               |
| Vertical                           | 4592.150  | 74.19         | -20.42         | 53.77       | 74.00    | -20.23 | PK            |
| Vertical                           | 4592.150  | 59.12         | -20.42         | 38.70       | 54.00    | -15.30 | AV            |
| Vertical                           | 10560.189 | 60.93         | -9.06          | 51.87       | 68.20    | -16.33 | PK            |
| Vertical                           | 10560.189 | 49.90         | -9.06          | 40.84       | 54.00    | -13.16 | AV            |
| Vertical                           | 15840.054 | 61.29         | -7.75          | 53.54       | 74.00    | -20.46 | PK            |
| Vertical                           | 15840.054 | 49.86         | -7.75          | 42.11       | 54.00    | -11.89 | AV            |
| Horizontal                         | 4592.190  | 71.35         | -20.42         | 50.93       | 74.00    | -23.07 | PK            |
| Horizontal                         | 4592.190  | 59.30         | -20.42         | 38.88       | 54.00    | -15.12 | AV            |
| Horizontal                         | 10560.074 | 62.55         | -9.06          | 53.49       | 68.20    | -14.71 | PK            |
| Horizontal                         | 10560.074 | 49.49         | -9.06          | 40.43       | 54.00    | -13.57 | AV            |
| Horizontal                         | 15840.121 | 61.02         | -7.75          | 53.27       | 74.00    | -20.73 | PK            |
| Horizontal                         | 15840.121 | 49.76         | -7.75          | 42.01       | 54.00    | -11.99 | AV            |
| High Channel (5320 MHz)-Above 1G   |           |               |                |             |          |        |               |
| Vertical                           | 4739.199  | 70.21         | -20.12         | 50.09       | 74.00    | -23.91 | PK            |
| Vertical                           | 4739.199  | 59.98         | -20.12         | 39.86       | 54.00    | -14.14 | AV            |
| Vertical                           | 10640.057 | 61.59         | -8.94          | 52.65       | 68.20    | -15.55 | PK            |
| Vertical                           | 10640.057 | 49.45         | -8.94          | 40.51       | 54.00    | -13.49 | AV            |
| Vertical                           | 15960.156 | 64.07         | -7.71          | 56.36       | 74.00    | -17.64 | PK            |
| Vertical                           | 15960.156 | 49.40         | -7.71          | 41.69       | 54.00    | -12.31 | AV            |
| Horizontal                         | 4739.079  | 73.05         | -20.12         | 52.93       | 74.00    | -21.07 | PK            |
| Horizontal                         | 4739.079  | 59.37         | -20.12         | 39.24       | 54.00    | -14.76 | AV            |
| Horizontal                         | 10640.124 | 62.64         | -8.94          | 53.70       | 68.20    | -14.50 | PK            |
| Horizontal                         | 10640.124 | 49.41         | -8.94          | 40.47       | 54.00    | -13.53 | AV            |
| Horizontal                         | 15960.136 | 63.60         | -7.71          | 55.89       | 74.00    | -18.11 | PK            |
| Horizontal                         | 15960.136 | 49.58         | -7.71          | 41.87       | 54.00    | -12.13 | AV            |

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

|            |                          |
|------------|--------------------------|
| Test Mode: | TX(5.3G) - 802.11ac-HT40 |
|------------|--------------------------|

| Polar                              | Frequency | Reading Level | Correct Factor | Measurement | Limits   | Over   | Detector Type |
|------------------------------------|-----------|---------------|----------------|-------------|----------|--------|---------------|
| (H/V)                              | (MHz)     | (dBuV/m)      | (dB)           | (dBuV/m)    | (dBuV/m) | (dB)   |               |
| Low Channel (5270 MHz)-Above 1G    |           |               |                |             |          |        |               |
| Vertical                           | 4434.041  | 70.53         | -20.73         | 49.79       | 68.20    | -18.41 | PK            |
| Vertical                           | 4434.041  | 59.09         | -20.73         | 38.36       | 54.00    | -15.64 | AV            |
| Vertical                           | 10540.050 | 61.41         | -9.09          | 52.32       | 68.20    | -15.88 | PK            |
| Vertical                           | 10540.050 | 49.11         | -9.09          | 40.02       | 54.00    | -13.98 | AV            |
| Vertical                           | 15810.041 | 61.49         | -7.76          | 53.73       | 74.00    | -20.27 | PK            |
| Vertical                           | 15810.041 | 49.40         | -7.76          | 41.64       | 54.00    | -12.36 | AV            |
| Horizontal                         | 4434.121  | 70.53         | -20.73         | 49.80       | 74.00    | -24.20 | PK            |
| Horizontal                         | 4434.121  | 59.46         | -20.73         | 38.73       | 54.00    | -15.27 | AV            |
| Horizontal                         | 10540.164 | 61.31         | -9.09          | 52.22       | 68.20    | -15.98 | PK            |
| Horizontal                         | 10540.164 | 49.68         | -9.09          | 40.59       | 54.00    | -13.41 | AV            |
| Horizontal                         | 15810.137 | 64.18         | -7.76          | 56.42       | 74.00    | -17.58 | PK            |
| Horizontal                         | 15810.137 | 49.18         | -7.76          | 41.42       | 54.00    | -12.58 | AV            |
| Middle Channel (5310 MHz)-Above 1G |           |               |                |             |          |        |               |
| Vertical                           | 4739.028  | 72.66         | -20.12         | 52.54       | 68.20    | -15.66 | PK            |
| Vertical                           | 4739.028  | 59.76         | -20.12         | 39.63       | 54.00    | -14.37 | AV            |
| Vertical                           | 10620.160 | 63.58         | -8.97          | 54.61       | 68.20    | -13.59 | PK            |
| Vertical                           | 10620.160 | 49.75         | -8.97          | 40.78       | 54.00    | -13.22 | AV            |
| Vertical                           | 15930.023 | 62.69         | -7.72          | 54.97       | 74.00    | -19.03 | PK            |
| Vertical                           | 15930.023 | 49.62         | -7.72          | 41.90       | 54.00    | -12.10 | AV            |
| Horizontal                         | 4739.053  | 72.87         | -20.12         | 52.74       | 68.20    | -15.46 | PK            |
| Horizontal                         | 4739.053  | 59.33         | -20.12         | 39.21       | 54.00    | -14.79 | AV            |
| Horizontal                         | 10620.021 | 62.30         | -8.97          | 53.33       | 68.20    | -14.87 | PK            |
| Horizontal                         | 10620.021 | 49.01         | -8.97          | 40.04       | 54.00    | -13.96 | AV            |
| Horizontal                         | 15930.179 | 62.97         | -7.72          | 55.25       | 74.00    | -18.75 | PK            |
| Horizontal                         | 15930.179 | 49.84         | -7.72          | 42.12       | 54.00    | -11.88 | AV            |

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

|            |                          |
|------------|--------------------------|
| Test Mode: | TX(5.3G) - 802.11ax-HT20 |
|------------|--------------------------|

| Polar                              | Frequency | Reading Level | Correct Factor | Measurement | Limits   | Over   | Detector Type |
|------------------------------------|-----------|---------------|----------------|-------------|----------|--------|---------------|
| (H/V)                              | (MHz)     | (dBuV/m)      | (dB)           | (dBuV/m)    | (dBuV/m) | (dB)   |               |
| Low Channel (5260 MHz)-Above 1G    |           |               |                |             |          |        |               |
| Vertical                           | 4434.037  | 72.33         | -20.73         | 51.60       | 68.20    | -16.60 | PK            |
| Vertical                           | 4434.037  | 59.61         | -20.73         | 38.88       | 54.00    | -15.12 | AV            |
| Vertical                           | 10520.132 | 63.83         | -9.12          | 54.71       | 68.20    | -13.49 | PK            |
| Vertical                           | 10520.132 | 49.78         | -9.12          | 40.66       | 54.00    | -13.34 | AV            |
| Vertical                           | 15780.156 | 64.17         | -7.77          | 56.40       | 74.00    | -17.60 | PK            |
| Vertical                           | 15780.156 | 49.58         | -7.77          | 41.81       | 54.00    | -12.19 | AV            |
| Horizontal                         | 4434.064  | 73.94         | -20.73         | 53.21       | 68.20    | -14.99 | PK            |
| Horizontal                         | 4434.064  | 59.68         | -20.73         | 38.95       | 54.00    | -15.05 | AV            |
| Horizontal                         | 10520.164 | 63.47         | -9.12          | 54.35       | 68.20    | -13.85 | PK            |
| Horizontal                         | 10520.164 | 49.15         | -9.12          | 40.03       | 54.00    | -13.97 | AV            |
| Horizontal                         | 15780.189 | 62.72         | -7.77          | 54.95       | 74.00    | -19.05 | PK            |
| Horizontal                         | 15780.189 | 49.86         | -7.77          | 42.09       | 54.00    | -11.91 | AV            |
| Middle Channel (5280 MHz)-Above 1G |           |               |                |             |          |        |               |
| Vertical                           | 4592.092  | 70.75         | -20.42         | 50.33       | 74.00    | -23.67 | PK            |
| Vertical                           | 4592.092  | 59.94         | -20.42         | 39.52       | 54.00    | -14.48 | AV            |
| Vertical                           | 10560.125 | 60.59         | -9.06          | 51.53       | 68.20    | -16.67 | PK            |
| Vertical                           | 10560.125 | 49.88         | -9.06          | 40.82       | 54.00    | -13.18 | AV            |
| Vertical                           | 15840.097 | 64.46         | -7.75          | 56.71       | 74.00    | -17.29 | PK            |
| Vertical                           | 15840.097 | 49.55         | -7.75          | 41.80       | 54.00    | -12.20 | AV            |
| Horizontal                         | 4592.054  | 73.41         | -20.42         | 53.00       | 74.00    | -21.00 | PK            |
| Horizontal                         | 4592.054  | 59.75         | -20.42         | 39.34       | 54.00    | -14.66 | AV            |
| Horizontal                         | 10560.004 | 64.86         | -9.06          | 55.80       | 68.20    | -12.40 | PK            |
| Horizontal                         | 10560.004 | 49.95         | -9.06          | 40.89       | 54.00    | -13.11 | AV            |
| Horizontal                         | 15840.132 | 62.44         | -7.75          | 54.69       | 74.00    | -19.31 | PK            |
| Horizontal                         | 15840.132 | 49.95         | -7.75          | 42.20       | 54.00    | -11.80 | AV            |
| High Channel (5320 MHz)-Above 1G   |           |               |                |             |          |        |               |
| Vertical                           | 4739.053  | 73.77         | -20.12         | 53.65       | 74.00    | -20.35 | PK            |
| Vertical                           | 4739.053  | 59.83         | -20.12         | 39.71       | 54.00    | -14.29 | AV            |
| Vertical                           | 10640.143 | 64.25         | -8.94          | 55.31       | 68.20    | -12.89 | PK            |
| Vertical                           | 10640.143 | 49.46         | -8.94          | 40.52       | 54.00    | -13.48 | AV            |
| Vertical                           | 15960.128 | 63.98         | -7.71          | 56.27       | 74.00    | -17.73 | PK            |
| Vertical                           | 15960.128 | 49.02         | -7.71          | 41.31       | 54.00    | -12.69 | AV            |
| Horizontal                         | 4739.176  | 72.17         | -20.12         | 52.05       | 74.00    | -21.95 | PK            |
| Horizontal                         | 4739.176  | 59.61         | -20.12         | 39.49       | 54.00    | -14.51 | AV            |
| Horizontal                         | 10640.174 | 63.41         | -8.94          | 54.47       | 68.20    | -13.73 | PK            |
| Horizontal                         | 10640.174 | 49.39         | -8.94          | 40.45       | 54.00    | -13.55 | AV            |
| Horizontal                         | 15960.136 | 64.61         | -7.71          | 56.90       | 74.00    | -17.10 | PK            |
| Horizontal                         | 15960.136 | 49.94         | -7.71          | 42.23       | 54.00    | -11.77 | AV            |

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

|            |                          |
|------------|--------------------------|
| Test Mode: | TX(5.3G) - 802.11ax-HT40 |
|------------|--------------------------|

| Polar                              | Frequency | Reading Level | Correct Factor | Measurement | Limits   | Over   | Detector Type |
|------------------------------------|-----------|---------------|----------------|-------------|----------|--------|---------------|
| (H/V)                              | (MHz)     | (dBuV/m)      | (dB)           | (dBuV/m)    | (dBuV/m) | (dB)   |               |
| Low Channel (5270 MHz)-Above 1G    |           |               |                |             |          |        |               |
| Vertical                           | 4434.097  | 72.72         | -20.73         | 51.99       | 68.20    | -16.21 | PK            |
| Vertical                           | 4434.097  | 59.29         | -20.73         | 38.56       | 54.00    | -15.44 | AV            |
| Vertical                           | 10540.029 | 60.97         | -9.09          | 51.88       | 68.20    | -16.32 | PK            |
| Vertical                           | 10540.029 | 49.51         | -9.09          | 40.42       | 54.00    | -13.58 | AV            |
| Vertical                           | 15810.135 | 62.19         | -7.76          | 54.43       | 74.00    | -19.57 | PK            |
| Vertical                           | 15810.135 | 49.64         | -7.76          | 41.88       | 54.00    | -12.12 | AV            |
| Horizontal                         | 4434.120  | 73.15         | -20.73         | 52.42       | 74.00    | -21.58 | PK            |
| Horizontal                         | 4434.120  | 59.55         | -20.73         | 38.82       | 54.00    | -15.18 | AV            |
| Horizontal                         | 10540.140 | 63.26         | -9.09          | 54.17       | 68.20    | -14.03 | PK            |
| Horizontal                         | 10540.140 | 49.96         | -9.09          | 40.87       | 54.00    | -13.13 | AV            |
| Horizontal                         | 15810.024 | 61.70         | -7.76          | 53.94       | 74.00    | -20.06 | PK            |
| Horizontal                         | 15810.024 | 49.41         | -7.76          | 41.65       | 54.00    | -12.35 | AV            |
| Middle Channel (5310 MHz)-Above 1G |           |               |                |             |          |        |               |
| Vertical                           | 4739.034  | 72.12         | -20.12         | 52.00       | 68.20    | -16.20 | PK            |
| Vertical                           | 4739.034  | 59.27         | -20.12         | 39.15       | 54.00    | -14.85 | AV            |
| Vertical                           | 10620.168 | 60.95         | -8.97          | 51.98       | 68.20    | -16.22 | PK            |
| Vertical                           | 10620.168 | 49.14         | -8.97          | 40.17       | 54.00    | -13.83 | AV            |
| Vertical                           | 15930.135 | 63.34         | -7.72          | 55.62       | 74.00    | -18.38 | PK            |
| Vertical                           | 15930.135 | 49.72         | -7.72          | 42.00       | 54.00    | -12.00 | AV            |
| Horizontal                         | 4739.115  | 74.51         | -20.12         | 54.39       | 68.20    | -13.81 | PK            |
| Horizontal                         | 4739.115  | 59.35         | -20.12         | 39.23       | 54.00    | -14.77 | AV            |
| Horizontal                         | 10620.008 | 60.59         | -8.97          | 51.62       | 68.20    | -16.58 | PK            |
| Horizontal                         | 10620.008 | 49.76         | -8.97          | 40.79       | 54.00    | -13.21 | AV            |
| Horizontal                         | 15930.045 | 63.78         | -7.72          | 56.06       | 74.00    | -17.94 | PK            |
| Horizontal                         | 15930.045 | 49.05         | -7.72          | 41.33       | 54.00    | -12.67 | AV            |

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

|            |                    |
|------------|--------------------|
| Test Mode: | TX(5.6G) - 802.11a |
|------------|--------------------|

| Polar                              | Fre-<br>quency | Reading<br>Level | Correct<br>Factor | Measure-<br>ment | Limits   | Over   | Detector<br>Type |
|------------------------------------|----------------|------------------|-------------------|------------------|----------|--------|------------------|
| (H/V)                              | (MHz)          | (dBuV/m)         | (dB)              | (dBuV/m)         | (dBuV/m) | (dB)   |                  |
| Low Channel (5500 MHz)-Above 1G    |                |                  |                   |                  |          |        |                  |
| Vertical                           | 4434.141       | 71.97            | -20.73            | 51.24            | 68.20    | -16.96 | PK               |
| Vertical                           | 4434.141       | 59.70            | -20.73            | 38.97            | 54.00    | -15.03 | AV               |
| Vertical                           | 11000.079      | 63.67            | -8.40             | 55.27            | 68.20    | -12.93 | PK               |
| Vertical                           | 11000.079      | 49.56            | -8.40             | 41.16            | 54.00    | -12.84 | AV               |
| Vertical                           | 16500.124      | 62.03            | -6.09             | 55.94            | 74.00    | -18.06 | PK               |
| Vertical                           | 16500.124      | 49.74            | -6.09             | 43.65            | 54.00    | -10.35 | AV               |
| Horizontal                         | 4434.086       | 74.81            | -20.73            | 54.08            | 68.20    | -14.12 | PK               |
| Horizontal                         | 4434.086       | 59.54            | -20.73            | 38.81            | 54.00    | -15.19 | AV               |
| Horizontal                         | 11000.043      | 63.92            | -8.40             | 55.52            | 68.20    | -12.68 | PK               |
| Horizontal                         | 11000.043      | 49.79            | -8.40             | 41.39            | 54.00    | -12.61 | AV               |
| Horizontal                         | 16500.050      | 61.36            | -6.09             | 55.27            | 74.00    | -18.73 | PK               |
| Horizontal                         | 16500.050      | 49.41            | -6.09             | 43.32            | 54.00    | -10.68 | AV               |
| middle Channel (5580 MHz)-Above 1G |                |                  |                   |                  |          |        |                  |
| Vertical                           | 4592.148       | 73.68            | -20.42            | 53.27            | 74.00    | -20.73 | PK               |
| Vertical                           | 4592.148       | 59.99            | -20.42            | 39.57            | 54.00    | -14.43 | AV               |
| Vertical                           | 11160.198      | 61.77            | -8.53             | 53.24            | 68.20    | -14.96 | PK               |
| Vertical                           | 11160.198      | 49.89            | -8.53             | 41.36            | 54.00    | -12.64 | AV               |
| Vertical                           | 16740.137      | 64.48            | -5.31             | 59.17            | 74.00    | -14.83 | PK               |
| Vertical                           | 16740.137      | 49.01            | -5.31             | 43.70            | 54.00    | -10.30 | AV               |
| Horizontal                         | 4592.087       | 72.50            | -20.42            | 52.09            | 74.00    | -21.91 | PK               |
| Horizontal                         | 4592.087       | 59.67            | -20.42            | 39.25            | 54.00    | -14.75 | AV               |
| Horizontal                         | 11160.065      | 64.71            | -8.53             | 56.18            | 68.20    | -12.02 | PK               |
| Horizontal                         | 11160.065      | 49.92            | -8.53             | 41.39            | 54.00    | -12.61 | AV               |
| Horizontal                         | 16740.110      | 64.23            | -5.31             | 58.92            | 74.00    | -15.08 | PK               |
| Horizontal                         | 16740.110      | 49.93            | -5.31             | 44.62            | 54.00    | -9.38  | AV               |
| High Channel (5700 MHz)-Above 1G   |                |                  |                   |                  |          |        |                  |
| Vertical                           | 4739.008       | 71.08            | -20.12            | 50.96            | 74.00    | -23.04 | PK               |
| Vertical                           | 4739.008       | 59.24            | -20.12            | 39.11            | 54.00    | -14.89 | AV               |
| Vertical                           | 11400.050      | 63.71            | -8.72             | 54.99            | 68.20    | -13.21 | PK               |
| Vertical                           | 11400.050      | 49.74            | -8.72             | 41.02            | 54.00    | -12.98 | AV               |
| Vertical                           | 17100.027      | 61.61            | -3.92             | 57.69            | 74.00    | -16.31 | PK               |
| Vertical                           | 17100.027      | 49.29            | -3.92             | 45.37            | 54.00    | -8.63  | AV               |
| Horizontal                         | 4739.162       | 74.33            | -20.12            | 54.21            | 74.00    | -19.79 | PK               |
| Horizontal                         | 4739.162       | 59.26            | -20.12            | 39.13            | 54.00    | -14.87 | AV               |
| Horizontal                         | 11400.179      | 61.14            | -8.72             | 52.42            | 68.20    | -15.78 | PK               |
| Horizontal                         | 11400.179      | 49.70            | -8.72             | 40.98            | 54.00    | -13.02 | AV               |
| Horizontal                         | 17100.110      | 60.58            | -3.92             | 56.66            | 74.00    | -17.34 | PK               |
| Horizontal                         | 17100.110      | 49.92            | -3.92             | 46.00            | 54.00    | -8.00  | AV               |

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

|            |                         |
|------------|-------------------------|
| Test Mode: | TX(5.6G) - 802.11n-HT20 |
|------------|-------------------------|

| Polar                              | Fre-<br>quency | Reading<br>Level | Correct<br>Factor | Measure-<br>ment | Limits   | Over   | Detector<br>Type |
|------------------------------------|----------------|------------------|-------------------|------------------|----------|--------|------------------|
| (H/V)                              | (MHz)          | (dBuV/m)         | (dB)              | (dBuV/m)         | (dBuV/m) | (dB)   |                  |
| Low Channel (5500 MHz)-Above 1G    |                |                  |                   |                  |          |        |                  |
| Vertical                           | 4434.144       | 71.91            | -20.73            | 51.18            | 68.20    | -17.02 | PK               |
| Vertical                           | 4434.144       | 59.59            | -20.73            | 38.86            | 54.00    | -15.14 | AV               |
| Vertical                           | 11000.006      | 62.28            | -8.40             | 53.88            | 68.20    | -14.32 | PK               |
| Vertical                           | 11000.006      | 49.87            | -8.40             | 41.47            | 54.00    | -12.53 | AV               |
| Vertical                           | 16500.057      | 61.34            | -6.09             | 55.25            | 74.00    | -18.75 | PK               |
| Vertical                           | 16500.057      | 49.21            | -6.09             | 43.12            | 54.00    | -10.88 | AV               |
| Horizontal                         | 4434.103       | 71.81            | -20.73            | 51.08            | 68.20    | -17.12 | PK               |
| Horizontal                         | 4434.103       | 59.28            | -20.73            | 38.55            | 54.00    | -15.45 | AV               |
| Horizontal                         | 11000.107      | 62.17            | -8.40             | 53.77            | 68.20    | -14.43 | PK               |
| Horizontal                         | 11000.107      | 49.79            | -8.40             | 41.39            | 54.00    | -12.61 | AV               |
| Horizontal                         | 16500.125      | 64.65            | -6.09             | 58.56            | 74.00    | -15.44 | PK               |
| Horizontal                         | 16500.125      | 49.17            | -6.09             | 43.08            | 54.00    | -10.92 | AV               |
| middle Channel (5580 MHz)-Above 1G |                |                  |                   |                  |          |        |                  |
| Vertical                           | 4592.10        | 73.31            | -20.42            | 52.90            | 74.00    | -21.10 | PK               |
| Vertical                           | 4592.10        | 59.42            | -20.42            | 39.00            | 54.00    | -15.00 | AV               |
| Vertical                           | 11160.07       | 64.38            | -8.53             | 55.85            | 68.20    | -12.35 | PK               |
| Vertical                           | 11160.07       | 49.89            | -8.53             | 41.36            | 54.00    | -12.64 | AV               |
| Vertical                           | 16740.15       | 64.32            | -5.31             | 59.01            | 74.00    | -14.99 | PK               |
| Vertical                           | 16740.15       | 49.57            | -5.31             | 44.26            | 54.00    | -9.74  | AV               |
| Horizontal                         | 4592.20        | 70.89            | -20.42            | 50.47            | 74.00    | -23.53 | PK               |
| Horizontal                         | 4592.20        | 59.48            | -20.42            | 39.06            | 54.00    | -14.94 | AV               |
| Horizontal                         | 11160.12       | 63.46            | -8.53             | 54.93            | 68.20    | -13.27 | PK               |
| Horizontal                         | 11160.12       | 49.24            | -8.53             | 40.71            | 54.00    | -13.29 | AV               |
| Horizontal                         | 16740.09       | 61.27            | -5.31             | 55.96            | 74.00    | -18.04 | PK               |
| Horizontal                         | 16740.09       | 49.79            | -5.31             | 44.48            | 54.00    | -9.52  | AV               |
| High Channel (5700 MHz)-Above 1G   |                |                  |                   |                  |          |        |                  |
| Vertical                           | 4739.102       | 70.97            | -20.12            | 50.84            | 74.00    | -23.16 | PK               |
| Vertical                           | 4739.102       | 59.74            | -20.12            | 39.62            | 54.00    | -14.38 | AV               |
| Vertical                           | 11400.086      | 61.52            | -8.72             | 52.80            | 68.20    | -15.40 | PK               |
| Vertical                           | 11400.086      | 49.69            | -8.72             | 40.97            | 54.00    | -13.03 | AV               |
| Vertical                           | 17100.103      | 63.50            | -3.92             | 59.58            | 74.00    | -14.42 | PK               |
| Vertical                           | 17100.103      | 49.34            | -3.92             | 45.42            | 54.00    | -8.58  | AV               |
| Horizontal                         | 4739.167       | 74.16            | -20.12            | 54.04            | 74.00    | -19.96 | PK               |
| Horizontal                         | 4739.167       | 59.26            | -20.12            | 39.14            | 54.00    | -14.86 | AV               |
| Horizontal                         | 11400.049      | 62.39            | -8.72             | 53.67            | 68.20    | -14.53 | PK               |
| Horizontal                         | 11400.049      | 49.65            | -8.72             | 40.93            | 54.00    | -13.07 | AV               |
| Horizontal                         | 17100.117      | 63.58            | -3.92             | 59.66            | 74.00    | -14.34 | PK               |
| Horizontal                         | 17100.117      | 49.46            | -3.92             | 45.54            | 54.00    | -8.46  | AV               |

Note: PK value is lower than the Average value limit, So average didn't record.  
The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.  
Emission level (dBuV/m) = 20 log Emission level (uV/m).  
Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

|            |                         |
|------------|-------------------------|
| Test Mode: | TX(5.6G) - 802.11n-HT40 |
|------------|-------------------------|

| Polar                              | Fre-<br>quency | Reading<br>Level | Correct<br>Factor | Measure-<br>ment | Limits   | Over   | Detector<br>Type |
|------------------------------------|----------------|------------------|-------------------|------------------|----------|--------|------------------|
| (H/V)                              | (MHz)          | (dBuV/m)         | (dB)              | (dBuV/m)         | (dBuV/m) | (dB)   |                  |
| Low Channel (5510 MHz)-Above 1G    |                |                  |                   |                  |          |        |                  |
| Vertical                           | 4434.113       | 71.93            | -20.73            | 51.20            | 68.20    | -17.00 | PK               |
| Vertical                           | 4434.113       | 63.31            | -20.73            | 42.57            | 54.00    | -11.43 | AV               |
| Vertical                           | 11020.134      | 63.68            | -8.42             | 55.26            | 68.20    | -12.94 | PK               |
| Vertical                           | 11020.134      | 43.93            | -8.42             | 35.51            | 54.00    | -18.49 | AV               |
| Vertical                           | 16530.048      | 63.35            | -5.99             | 57.36            | 74.00    | -16.64 | PK               |
| Vertical                           | 16530.048      | 43.49            | -5.99             | 37.50            | 54.00    | -16.50 | AV               |
| Horizontal                         | 4434.145       | 74.90            | -20.73            | 54.17            | 74.00    | -19.83 | PK               |
| Horizontal                         | 4434.145       | 63.39            | -20.73            | 42.66            | 54.00    | -11.34 | AV               |
| Horizontal                         | 11020.136      | 52.07            | -8.42             | 43.65            | 68.20    | -24.55 | PK               |
| Horizontal                         | 11020.136      | 41.26            | -8.42             | 32.84            | 54.00    | -21.16 | AV               |
| Horizontal                         | 16530.162      | 60.04            | -5.99             | 54.05            | 74.00    | -19.95 | PK               |
| Horizontal                         | 16530.162      | 43.80            | -5.99             | 37.81            | 54.00    | -16.19 | AV               |
| middle Channel (5550 MHz)-Above 1G |                |                  |                   |                  |          |        |                  |
| Vertical                           | 4592.004       | 71.95            | -20.42            | 51.54            | 74.00    | -22.46 | PK               |
| Vertical                           | 4592.004       | 63.64            | -20.42            | 43.22            | 54.00    | -10.78 | AV               |
| Vertical                           | 11100.158      | 63.65            | -8.40             | 55.25            | 68.20    | -12.95 | PK               |
| Vertical                           | 11100.158      | 43.10            | -8.40             | 34.70            | 54.00    | -19.30 | AV               |
| Vertical                           | 16650.149      | 61.01            | -5.60             | 55.41            | 74.00    | -18.59 | PK               |
| Vertical                           | 16650.149      | 43.78            | -5.60             | 38.18            | 54.00    | -15.82 | AV               |
| Horizontal                         | 4592.042       | 72.17            | -20.42            | 51.75            | 74.00    | -22.25 | PK               |
| Horizontal                         | 4592.042       | 63.97            | -20.42            | 43.56            | 54.00    | -10.44 | AV               |
| Horizontal                         | 11100.058      | 53.90            | -8.40             | 45.50            | 68.20    | -22.70 | PK               |
| Horizontal                         | 11100.058      | 41.82            | -8.40             | 33.42            | 54.00    | -20.58 | AV               |
| Horizontal                         | 16650.152      | 64.43            | -5.60             | 58.83            | 74.00    | -15.17 | PK               |
| Horizontal                         | 16650.152      | 41.94            | -5.60             | 36.34            | 54.00    | -17.66 | AV               |
| High Channel (5670 MHz)-Above 1G   |                |                  |                   |                  |          |        |                  |
| Vertical                           | 4739.109       | 71.27            | -20.12            | 51.15            | 68.20    | -17.05 | PK               |
| Vertical                           | 4739.109       | 63.39            | -20.12            | 43.27            | 54.00    | -10.73 | AV               |
| Vertical                           | 11340.020      | 63.71            | -8.67             | 55.04            | 68.20    | -13.16 | PK               |
| Vertical                           | 11340.020      | 43.91            | -8.67             | 35.24            | 54.00    | -18.76 | AV               |
| Vertical                           | 17010.173      | 62.27            | -4.41             | 57.86            | 74.00    | -16.14 | PK               |
| Vertical                           | 17010.173      | 43.51            | -4.41             | 39.10            | 54.00    | -14.90 | AV               |
| Horizontal                         | 4739.169       | 72.00            | -20.12            | 51.88            | 68.20    | -16.32 | PK               |
| Horizontal                         | 4739.169       | 63.60            | -20.12            | 43.48            | 54.00    | -10.52 | AV               |
| Horizontal                         | 11340.113      | 50.41            | -8.67             | 41.74            | 68.20    | -26.46 | PK               |
| Horizontal                         | 11340.113      | 43.16            | -8.67             | 34.49            | 54.00    | -19.51 | AV               |
| Horizontal                         | 17010.038      | 60.30            | -4.41             | 55.89            | 74.00    | -18.11 | PK               |
| Horizontal                         | 17010.038      | 43.84            | -4.41             | 39.43            | 54.00    | -14.57 | AV               |

Note: PK value is lower than the Average value limit, So average didn't record.  
The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.  
Emission level (dBuV/m) = 20 log Emission level (uV/m).  
Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

|            |                          |
|------------|--------------------------|
| Test Mode: | TX(5.6G) - 802.11ac-HT20 |
|------------|--------------------------|

| Polar<br>(H/V)                     | Fre-<br>quency<br>(MHz) | Reading<br>Level<br>(dBuV/m) | Correct<br>Factor<br>(dB) | Measure-<br>ment<br>(dBuV/m) | Limits<br>(dBuV/m) | Over<br>(dB) | Detector<br>Type |
|------------------------------------|-------------------------|------------------------------|---------------------------|------------------------------|--------------------|--------------|------------------|
| Low Channel (5500 MHz)-Above 1G    |                         |                              |                           |                              |                    |              |                  |
| Vertical                           | 4434.088                | 70.18                        | -20.73                    | 49.45                        | 68.20              | -18.75       | PK               |
| Vertical                           | 4434.088                | 59.74                        | -20.73                    | 39.01                        | 54.00              | -14.99       | AV               |
| Vertical                           | 11000.086               | 62.91                        | -8.40                     | 54.51                        | 68.20              | -13.69       | PK               |
| Vertical                           | 11000.086               | 49.90                        | -8.40                     | 41.50                        | 54.00              | -12.50       | AV               |
| Vertical                           | 16500.087               | 60.49                        | -6.09                     | 54.40                        | 74.00              | -19.60       | PK               |
| Vertical                           | 16500.087               | 49.32                        | -6.09                     | 43.23                        | 54.00              | -10.77       | AV               |
| Horizontal                         | 4434.056                | 73.64                        | -20.73                    | 52.90                        | 68.20              | -15.30       | PK               |
| Horizontal                         | 4434.056                | 59.61                        | -20.73                    | 38.88                        | 54.00              | -15.12       | AV               |
| Horizontal                         | 11000.040               | 64.50                        | -8.40                     | 56.10                        | 68.20              | -12.10       | PK               |
| Horizontal                         | 11000.040               | 49.55                        | -8.40                     | 41.15                        | 54.00              | -12.85       | AV               |
| Horizontal                         | 16500.163               | 61.16                        | -6.09                     | 55.07                        | 74.00              | -18.93       | PK               |
| Horizontal                         | 16500.163               | 49.83                        | -6.09                     | 43.74                        | 54.00              | -10.26       | AV               |
| middle Channel (5580 MHz)-Above 1G |                         |                              |                           |                              |                    |              |                  |
| Vertical                           | 4592.16                 | 72.67                        | -20.42                    | 52.25                        | 74.00              | -21.75       | PK               |
| Vertical                           | 4592.16                 | 59.28                        | -20.42                    | 38.86                        | 54.00              | -15.14       | AV               |
| Vertical                           | 11160.03                | 62.55                        | -8.53                     | 54.02                        | 68.20              | -14.18       | PK               |
| Vertical                           | 11160.03                | 49.26                        | -8.53                     | 40.73                        | 54.00              | -13.27       | AV               |
| Vertical                           | 16740.13                | 63.40                        | -5.31                     | 58.09                        | 74.00              | -15.91       | PK               |
| Vertical                           | 16740.13                | 49.84                        | -5.31                     | 44.53                        | 54.00              | -9.47        | AV               |
| Horizontal                         | 4592.04                 | 74.19                        | -20.42                    | 53.78                        | 74.00              | -20.22       | PK               |
| Horizontal                         | 4592.04                 | 59.81                        | -20.42                    | 39.40                        | 54.00              | -14.60       | AV               |
| Horizontal                         | 11160.15                | 64.28                        | -8.53                     | 55.75                        | 68.20              | -12.45       | PK               |
| Horizontal                         | 11160.15                | 49.49                        | -8.53                     | 40.96                        | 54.00              | -13.04       | AV               |
| Horizontal                         | 16740.16                | 60.10                        | -5.31                     | 54.79                        | 74.00              | -19.21       | PK               |
| Horizontal                         | 16740.16                | 49.20                        | -5.31                     | 43.89                        | 54.00              | -10.11       | AV               |
| High Channel (5700 MHz)-Above 1G   |                         |                              |                           |                              |                    |              |                  |
| Vertical                           | 4739.102                | 72.33                        | -20.12                    | 52.21                        | 74.00              | -21.79       | PK               |
| Vertical                           | 4739.102                | 59.94                        | -20.12                    | 39.82                        | 54.00              | -14.18       | AV               |
| Vertical                           | 11400.058               | 63.85                        | -8.72                     | 55.13                        | 68.20              | -13.07       | PK               |
| Vertical                           | 11400.058               | 49.46                        | -8.72                     | 40.74                        | 54.00              | -13.26       | AV               |
| Vertical                           | 17100.058               | 62.99                        | -3.92                     | 59.07                        | 74.00              | -14.93       | PK               |
| Vertical                           | 17100.058               | 49.81                        | -3.92                     | 45.89                        | 54.00              | -8.11        | AV               |
| Horizontal                         | 4739.178                | 73.17                        | -20.12                    | 53.05                        | 74.00              | -20.95       | PK               |
| Horizontal                         | 4739.178                | 59.71                        | -20.12                    | 39.59                        | 54.00              | -14.41       | AV               |
| Horizontal                         | 11400.084               | 64.67                        | -8.72                     | 55.95                        | 68.20              | -12.25       | PK               |
| Horizontal                         | 11400.084               | 49.27                        | -8.72                     | 40.55                        | 54.00              | -13.45       | AV               |
| Horizontal                         | 17100.139               | 63.87                        | -3.92                     | 59.95                        | 74.00              | -14.05       | PK               |
| Horizontal                         | 17100.139               | 49.19                        | -3.92                     | 45.27                        | 54.00              | -8.73        | AV               |

Note: PK value is lower than the Average value limit, So average didn't record.  
The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.  
Emission level (dBuV/m) = 20 log Emission level (uV/m).  
Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

|            |                          |
|------------|--------------------------|
| Test Mode: | TX(5.6G) - 802.11ac-HT40 |
|------------|--------------------------|

| Polar                              | Fre-<br>quency | Reading<br>Level | Correct<br>Factor | Measure-<br>ment | Limits   | Over   | Detector<br>Type |
|------------------------------------|----------------|------------------|-------------------|------------------|----------|--------|------------------|
| (H/V)                              | (MHz)          | (dBuV/m)         | (dB)              | (dBuV/m)         | (dBuV/m) | (dB)   |                  |
| Low Channel (5510 MHz)-Above 1G    |                |                  |                   |                  |          |        |                  |
| Vertical                           | 4434.199       | 72.91            | -20.73            | 52.17            | 68.20    | -16.03 | PK               |
| Vertical                           | 4434.199       | 63.13            | -20.73            | 42.40            | 54.00    | -11.60 | AV               |
| Vertical                           | 11020.104      | 61.20            | -8.42             | 52.78            | 68.20    | -15.42 | PK               |
| Vertical                           | 11020.104      | 43.72            | -8.42             | 35.30            | 54.00    | -18.70 | AV               |
| Vertical                           | 16530.087      | 61.83            | -5.99             | 55.84            | 74.00    | -18.16 | PK               |
| Vertical                           | 16530.087      | 43.99            | -5.99             | 38.00            | 54.00    | -16.00 | AV               |
| Horizontal                         | 4434.200       | 74.61            | -20.73            | 53.88            | 74.00    | -20.12 | PK               |
| Horizontal                         | 4434.200       | 63.11            | -20.73            | 42.38            | 54.00    | -11.62 | AV               |
| Horizontal                         | 11020.062      | 52.14            | -8.42             | 43.72            | 68.20    | -24.48 | PK               |
| Horizontal                         | 11020.062      | 44.02            | -8.42             | 35.60            | 54.00    | -18.40 | AV               |
| Horizontal                         | 16530.101      | 63.22            | -5.99             | 57.23            | 74.00    | -16.77 | PK               |
| Horizontal                         | 16530.101      | 44.20            | -5.99             | 38.21            | 54.00    | -15.79 | AV               |
| middle Channel (5550 MHz)-Above 1G |                |                  |                   |                  |          |        |                  |
| Vertical                           | 4592.076       | 74.01            | -20.42            | 53.59            | 74.00    | -20.41 | PK               |
| Vertical                           | 4592.076       | 63.65            | -20.42            | 43.23            | 54.00    | -10.77 | AV               |
| Vertical                           | 11100.019      | 63.00            | -8.40             | 54.60            | 68.20    | -13.60 | PK               |
| Vertical                           | 11100.019      | 43.31            | -8.40             | 34.91            | 54.00    | -19.09 | AV               |
| Vertical                           | 16650.193      | 61.45            | -5.60             | 55.85            | 74.00    | -18.15 | PK               |
| Vertical                           | 16650.193      | 43.88            | -5.60             | 38.28            | 54.00    | -15.72 | AV               |
| Horizontal                         | 4592.025       | 72.22            | -20.42            | 51.81            | 74.00    | -22.19 | PK               |
| Horizontal                         | 4592.025       | 63.89            | -20.42            | 43.48            | 54.00    | -10.52 | AV               |
| Horizontal                         | 11100.068      | 54.70            | -8.40             | 46.30            | 68.20    | -21.90 | PK               |
| Horizontal                         | 11100.068      | 40.09            | -8.40             | 31.69            | 54.00    | -22.31 | AV               |
| Horizontal                         | 16650.083      | 61.21            | -5.60             | 55.61            | 74.00    | -18.39 | PK               |
| Horizontal                         | 16650.083      | 40.69            | -5.60             | 35.09            | 54.00    | -18.91 | AV               |
| High Channel (5670 MHz)-Above 1G   |                |                  |                   |                  |          |        |                  |
| Vertical                           | 4739.121       | 72.81            | -20.12            | 52.69            | 68.20    | -15.51 | PK               |
| Vertical                           | 4739.121       | 63.43            | -20.12            | 43.31            | 54.00    | -10.69 | AV               |
| Vertical                           | 11340.197      | 60.15            | -8.67             | 51.48            | 68.20    | -16.72 | PK               |
| Vertical                           | 11340.197      | 43.01            | -8.67             | 34.34            | 54.00    | -19.66 | AV               |
| Vertical                           | 17010.067      | 62.42            | -4.41             | 58.01            | 74.00    | -15.99 | PK               |
| Vertical                           | 17010.067      | 43.44            | -4.41             | 39.03            | 54.00    | -14.97 | AV               |
| Horizontal                         | 4739.143       | 74.67            | -20.12            | 54.55            | 68.20    | -13.65 | PK               |
| Horizontal                         | 4739.143       | 63.30            | -20.12            | 43.18            | 54.00    | -10.82 | AV               |
| Horizontal                         | 11340.062      | 54.21            | -8.67             | 45.54            | 68.20    | -22.66 | PK               |
| Horizontal                         | 11340.062      | 40.88            | -8.67             | 32.21            | 54.00    | -21.79 | AV               |
| Horizontal                         | 17010.146      | 61.15            | -4.41             | 56.74            | 74.00    | -17.26 | PK               |
| Horizontal                         | 17010.146      | 41.62            | -4.41             | 37.21            | 54.00    | -16.79 | AV               |

Note: PK value is lower than the Average value limit, So average didn't record.  
The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.  
Emission level (dBuV/m) = 20 log Emission level (uV/m).  
Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

|            |                          |
|------------|--------------------------|
| Test Mode: | TX(5.6G) - 802.11ax-HT20 |
|------------|--------------------------|

| Polar<br>(H/V)                     | Fre-<br>quency<br>(MHz) | Reading<br>Level<br>(dBuV/m) | Correct<br>Factor<br>(dB) | Measure-<br>ment<br>(dBuV/m) | Limits<br>(dBuV/m) | Over<br>(dB) | Detector<br>Type |
|------------------------------------|-------------------------|------------------------------|---------------------------|------------------------------|--------------------|--------------|------------------|
| Low Channel (5500 MHz)-Above 1G    |                         |                              |                           |                              |                    |              |                  |
| Vertical                           | 4434.166                | 70.38                        | -20.73                    | 49.65                        | 68.20              | -18.55       | PK               |
| Vertical                           | 4434.166                | 59.88                        | -20.73                    | 39.15                        | 54.00              | -14.85       | AV               |
| Vertical                           | 11000.087               | 62.59                        | -8.40                     | 54.19                        | 68.20              | -14.01       | PK               |
| Vertical                           | 11000.087               | 49.73                        | -8.40                     | 41.33                        | 54.00              | -12.67       | AV               |
| Vertical                           | 16500.087               | 61.58                        | -6.09                     | 55.49                        | 74.00              | -18.51       | PK               |
| Vertical                           | 16500.087               | 49.88                        | -6.09                     | 43.79                        | 54.00              | -10.21       | AV               |
| Horizontal                         | 4434.113                | 73.40                        | -20.73                    | 52.67                        | 68.20              | -15.53       | PK               |
| Horizontal                         | 4434.113                | 59.94                        | -20.73                    | 39.21                        | 54.00              | -14.79       | AV               |
| Horizontal                         | 11000.084               | 60.90                        | -8.40                     | 52.50                        | 68.20              | -15.70       | PK               |
| Horizontal                         | 11000.084               | 49.97                        | -8.40                     | 41.57                        | 54.00              | -12.43       | AV               |
| Horizontal                         | 16500.106               | 63.82                        | -6.09                     | 57.73                        | 74.00              | -16.27       | PK               |
| Horizontal                         | 16500.106               | 49.02                        | -6.09                     | 42.93                        | 54.00              | -11.07       | AV               |
| middle Channel (5580 MHz)-Above 1G |                         |                              |                           |                              |                    |              |                  |
| Vertical                           | 4592.18                 | 73.33                        | -20.42                    | 52.91                        | 74.00              | -21.09       | PK               |
| Vertical                           | 4592.18                 | 59.56                        | -20.42                    | 39.14                        | 54.00              | -14.86       | AV               |
| Vertical                           | 11160.04                | 61.75                        | -8.53                     | 53.22                        | 68.20              | -14.98       | PK               |
| Vertical                           | 11160.04                | 49.98                        | -8.53                     | 41.45                        | 54.00              | -12.55       | AV               |
| Vertical                           | 16740.15                | 62.60                        | -5.31                     | 57.29                        | 74.00              | -16.71       | PK               |
| Vertical                           | 16740.15                | 49.58                        | -5.31                     | 44.27                        | 54.00              | -9.73        | AV               |
| Horizontal                         | 4592.03                 | 70.32                        | -20.42                    | 49.90                        | 74.00              | -24.10       | PK               |
| Horizontal                         | 4592.03                 | 59.03                        | -20.42                    | 38.61                        | 54.00              | -15.39       | AV               |
| Horizontal                         | 11160.11                | 62.75                        | -8.53                     | 54.22                        | 68.20              | -13.98       | PK               |
| Horizontal                         | 11160.11                | 49.39                        | -8.53                     | 40.86                        | 54.00              | -13.14       | AV               |
| Horizontal                         | 16740.03                | 60.53                        | -5.31                     | 55.22                        | 74.00              | -18.78       | PK               |
| Horizontal                         | 16740.03                | 49.99                        | -5.31                     | 44.68                        | 54.00              | -9.32        | AV               |
| High Channel (5700 MHz)-Above 1G   |                         |                              |                           |                              |                    |              |                  |
| Vertical                           | 4739.121                | 71.43                        | -20.12                    | 51.31                        | 74.00              | -22.69       | PK               |
| Vertical                           | 4739.121                | 59.55                        | -20.12                    | 39.43                        | 54.00              | -14.57       | AV               |
| Vertical                           | 11400.140               | 61.02                        | -8.72                     | 52.30                        | 68.20              | -15.90       | PK               |
| Vertical                           | 11400.140               | 49.08                        | -8.72                     | 40.36                        | 54.00              | -13.64       | AV               |
| Vertical                           | 17100.098               | 60.33                        | -3.92                     | 56.41                        | 74.00              | -17.59       | PK               |
| Vertical                           | 17100.098               | 49.92                        | -3.92                     | 46.00                        | 54.00              | -8.00        | AV               |
| Horizontal                         | 4739.052                | 70.18                        | -20.12                    | 50.06                        | 74.00              | -23.94       | PK               |
| Horizontal                         | 4739.052                | 59.78                        | -20.12                    | 39.66                        | 54.00              | -14.34       | AV               |
| Horizontal                         | 11400.167               | 62.03                        | -8.72                     | 53.31                        | 68.20              | -14.89       | PK               |
| Horizontal                         | 11400.167               | 49.59                        | -8.72                     | 40.87                        | 54.00              | -13.13       | AV               |
| Horizontal                         | 17100.146               | 61.68                        | -3.92                     | 57.76                        | 74.00              | -16.24       | PK               |
| Horizontal                         | 17100.146               | 49.22                        | -3.92                     | 45.30                        | 54.00              | -8.70        | AV               |

Note: PK value is lower than the Average value limit, So average didn't record.  
The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.  
Emission level (dBuV/m) = 20 log Emission level (uV/m).  
Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

|            |                          |
|------------|--------------------------|
| Test Mode: | TX(5.6G) - 802.11ax-HT40 |
|------------|--------------------------|

| Polar                              | Fre-<br>quency | Reading<br>Level | Correct<br>Factor | Measure-<br>ment | Limits   | Over   | Detector<br>Type |
|------------------------------------|----------------|------------------|-------------------|------------------|----------|--------|------------------|
| (H/V)                              | (MHz)          | (dBuV/m)         | (dB)              | (dBuV/m)         | (dBuV/m) | (dB)   |                  |
| Low Channel (5510 MHz)-Above 1G    |                |                  |                   |                  |          |        |                  |
| Vertical                           | 4434.096       | 70.29            | -20.73            | 49.56            | 68.20    | -18.64 | PK               |
| Vertical                           | 4434.096       | 63.05            | -20.73            | 42.32            | 54.00    | -11.68 | AV               |
| Vertical                           | 11020.137      | 63.27            | -8.42             | 54.85            | 68.20    | -13.35 | PK               |
| Vertical                           | 11020.137      | 43.29            | -8.42             | 34.87            | 54.00    | -19.13 | AV               |
| Vertical                           | 16530.163      | 63.23            | -5.99             | 57.24            | 74.00    | -16.76 | PK               |
| Vertical                           | 16530.163      | 43.68            | -5.99             | 37.69            | 54.00    | -16.31 | AV               |
| Horizontal                         | 4434.142       | 71.01            | -20.73            | 50.28            | 74.00    | -23.72 | PK               |
| Horizontal                         | 4434.142       | 63.29            | -20.73            | 42.56            | 54.00    | -11.44 | AV               |
| Horizontal                         | 11020.095      | 50.26            | -8.42             | 41.84            | 68.20    | -26.36 | PK               |
| Horizontal                         | 11020.095      | 41.98            | -8.42             | 33.56            | 54.00    | -20.44 | AV               |
| Horizontal                         | 16530.099      | 64.46            | -5.99             | 58.47            | 74.00    | -15.53 | PK               |
| Horizontal                         | 16530.099      | 42.23            | -5.99             | 36.24            | 54.00    | -17.76 | AV               |
| middle Channel (5550 MHz)-Above 1G |                |                  |                   |                  |          |        |                  |
| Vertical                           | 4592.133       | 74.39            | -20.42            | 53.97            | 74.00    | -20.03 | PK               |
| Vertical                           | 4592.133       | 63.15            | -20.42            | 42.74            | 54.00    | -11.26 | AV               |
| Vertical                           | 11100.091      | 64.10            | -8.40             | 55.70            | 68.20    | -12.50 | PK               |
| Vertical                           | 11100.091      | 43.72            | -8.40             | 35.32            | 54.00    | -18.68 | AV               |
| Vertical                           | 16650.064      | 62.29            | -5.60             | 56.69            | 74.00    | -17.31 | PK               |
| Vertical                           | 16650.064      | 43.40            | -5.60             | 37.80            | 54.00    | -16.20 | AV               |
| Horizontal                         | 4592.008       | 74.98            | -20.42            | 54.57            | 74.00    | -19.43 | PK               |
| Horizontal                         | 4592.008       | 63.03            | -20.42            | 42.61            | 54.00    | -11.39 | AV               |
| Horizontal                         | 11100.016      | 50.23            | -8.40             | 41.83            | 68.20    | -26.37 | PK               |
| Horizontal                         | 11100.016      | 44.87            | -8.40             | 36.47            | 54.00    | -17.53 | AV               |
| Horizontal                         | 16650.148      | 62.41            | -5.60             | 56.81            | 74.00    | -17.19 | PK               |
| Horizontal                         | 16650.148      | 44.81            | -5.60             | 39.21            | 54.00    | -14.79 | AV               |
| High Channel (5670 MHz)-Above 1G   |                |                  |                   |                  |          |        |                  |
| Vertical                           | 4739.016       | 74.47            | -20.12            | 54.34            | 68.20    | -13.86 | PK               |
| Vertical                           | 4739.016       | 63.36            | -20.12            | 43.24            | 54.00    | -10.76 | AV               |
| Vertical                           | 11340.014      | 61.25            | -8.67             | 52.58            | 68.20    | -15.62 | PK               |
| Vertical                           | 11340.014      | 43.11            | -8.67             | 34.44            | 54.00    | -19.56 | AV               |
| Vertical                           | 17010.188      | 63.11            | -4.41             | 58.70            | 74.00    | -15.30 | PK               |
| Vertical                           | 17010.188      | 43.97            | -4.41             | 39.56            | 54.00    | -14.44 | AV               |
| Horizontal                         | 4739.163       | 74.84            | -20.12            | 54.72            | 68.20    | -13.48 | PK               |
| Horizontal                         | 4739.163       | 63.78            | -20.12            | 43.66            | 54.00    | -10.34 | AV               |
| Horizontal                         | 11340.176      | 52.04            | -8.67             | 43.37            | 68.20    | -24.83 | PK               |
| Horizontal                         | 11340.176      | 43.92            | -8.67             | 35.25            | 54.00    | -18.75 | AV               |
| Horizontal                         | 17010.013      | 61.96            | -4.41             | 57.55            | 74.00    | -16.45 | PK               |
| Horizontal                         | 17010.013      | 40.74            | -4.41             | 36.33            | 54.00    | -17.67 | AV               |

Note: PK value is lower than the Average value limit, So average didn't record.  
The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.  
Emission level (dBuV/m) = 20 log Emission level (uV/m).  
Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

|            |                      |
|------------|----------------------|
| Test Mode: | TX (5.8G) -- 802.11a |
|------------|----------------------|

| Polar                              | Frequency | Reading Level | Correct Factor | Measurement | Limits   | Over   | Detector Type |
|------------------------------------|-----------|---------------|----------------|-------------|----------|--------|---------------|
| (H/V)                              | (MHz)     | (dBuV/m)      | (dB)           | (dBuV/m)    | (dBuV/m) | (dB)   |               |
| Low Channel (5745 MHz)-Above 1G    |           |               |                |             |          |        |               |
| Vertical                           | 4679.124  | 72.84         | -20.24         | 52.59       | 74.00    | -21.41 | PK            |
| Vertical                           | 4679.124  | 59.20         | -20.24         | 38.96       | 54.00    | -15.04 | AV            |
| Vertical                           | 11490.168 | 63.11         | -8.79          | 54.32       | 68.20    | -13.88 | PK            |
| Vertical                           | 11490.168 | 49.42         | -8.79          | 40.63       | 54.00    | -13.37 | AV            |
| Vertical                           | 17235.177 | 58.47         | -3.18          | 55.29       | 68.20    | -12.91 | PK            |
| Vertical                           | 17235.177 | 44.81         | -3.18          | 41.63       | 54.00    | -12.37 | AV            |
| Horizontal                         | 4679.022  | 70.04         | -20.73         | 49.31       | 74.00    | -24.69 | PK            |
| Horizontal                         | 4679.022  | 59.99         | -20.73         | 39.26       | 54.00    | -14.74 | AV            |
| Horizontal                         | 11490.172 | 61.35         | -8.79          | 52.56       | 68.20    | -15.64 | PK            |
| Horizontal                         | 11490.172 | 49.52         | -8.79          | 40.73       | 54.00    | -13.27 | AV            |
| Horizontal                         | 17235.178 | 56.98         | -3.18          | 53.80       | 68.20    | -14.40 | PK            |
| Horizontal                         | 17235.178 | 44.43         | -3.18          | 41.25       | 54.00    | -12.75 | AV            |
| Middle Channel (5785 MHz)-Above 1G |           |               |                |             |          |        |               |
| Vertical                           | 4592.085  | 72.78         | -20.42         | 52.36       | 74.00    | -21.64 | PK            |
| Vertical                           | 4592.085  | 59.18         | -20.42         | 38.77       | 54.00    | -15.23 | AV            |
| Vertical                           | 11570.016 | 61.46         | -8.86          | 52.60       | 68.20    | -15.60 | PK            |
| Vertical                           | 11570.016 | 49.32         | -8.86          | 40.46       | 54.00    | -13.54 | AV            |
| Vertical                           | 17355.052 | 58.38         | -2.52          | 55.86       | 68.20    | -12.34 | PK            |
| Vertical                           | 17355.052 | 44.32         | -2.52          | 41.80       | 54.00    | -12.20 | AV            |
| Horizontal                         | 4592.118  | 70.51         | -20.42         | 50.10       | 74.00    | -23.90 | PK            |
| Horizontal                         | 4592.118  | 60.00         | -20.42         | 39.58       | 54.00    | -14.42 | AV            |
| Horizontal                         | 11570.048 | 61.68         | -8.86          | 52.82       | 68.20    | -15.38 | PK            |
| Horizontal                         | 11570.048 | 49.43         | -8.86          | 40.57       | 54.00    | -13.43 | AV            |
| Horizontal                         | 17355.171 | 55.76         | -2.52          | 53.24       | 68.20    | -14.96 | PK            |
| Horizontal                         | 17355.171 | 44.12         | -2.52          | 41.60       | 54.00    | -12.40 | AV            |
| High Channel (5825 MHz)-Above 1G   |           |               |                |             |          |        |               |
| Vertical                           | 6039.006  | 70.05         | -18.93         | 51.12       | 68.20    | -17.08 | PK            |
| Vertical                           | 6039.006  | 59.35         | -18.93         | 40.42       | 54.00    | -13.58 | AV            |
| Vertical                           | 11650.010 | 61.28         | -8.92          | 52.36       | 74.00    | -21.64 | PK            |
| Vertical                           | 11650.010 | 49.71         | -8.92          | 40.79       | 54.00    | -13.21 | AV            |
| Vertical                           | 17475.112 | 59.77         | -1.86          | 57.91       | 68.20    | -10.29 | PK            |
| Vertical                           | 17475.112 | 44.97         | -1.86          | 43.11       | 54.00    | -10.89 | AV            |
| Horizontal                         | 6039.036  | 74.14         | -18.93         | 55.21       | 68.20    | -12.99 | PK            |
| Horizontal                         | 6039.036  | 59.01         | -18.93         | 40.08       | 54.00    | -13.92 | AV            |
| Horizontal                         | 11650.166 | 62.26         | -8.92          | 53.34       | 74.00    | -20.66 | PK            |
| Horizontal                         | 11650.166 | 49.19         | -8.92          | 40.27       | 54.00    | -13.73 | AV            |
| Horizontal                         | 17475.108 | 59.42         | -1.86          | 57.56       | 68.20    | -10.64 | PK            |
| Horizontal                         | 17475.108 | 44.90         | -1.86          | 43.04       | 54.00    | -10.96 | AV            |

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode: TX (5.8G) --802.11n-HT20

| Polar                              | Frequency | Reading Level | Correct Factor | Measurement | Limits   | Over   | Detector Type |
|------------------------------------|-----------|---------------|----------------|-------------|----------|--------|---------------|
| (H/V)                              | (MHz)     | (dBuV/m)      | (dB)           | (dBuV/m)    | (dBuV/m) | (dB)   |               |
| Low Channel (5745 MHz)-Above 1G    |           |               |                |             |          |        |               |
| Vertical                           | 4679.100  | 73.24         | -20.24         | 53.00       | 74.00    | -21.00 | PK            |
| Vertical                           | 4679.100  | 59.44         | -20.24         | 39.20       | 54.00    | -14.80 | AV            |
| Vertical                           | 11490.198 | 64.71         | -8.79          | 55.92       | 68.20    | -12.28 | PK            |
| Vertical                           | 11490.198 | 49.20         | -8.79          | 40.41       | 54.00    | -13.59 | AV            |
| Vertical                           | 17235.030 | 55.18         | -3.18          | 52.00       | 68.20    | -16.20 | PK            |
| Vertical                           | 17235.030 | 44.83         | -3.18          | 41.65       | 54.00    | -12.35 | AV            |
| Horizontal                         | 4679.064  | 74.13         | -20.24         | 53.88       | 74.00    | -20.12 | PK            |
| Horizontal                         | 4679.064  | 59.56         | -20.24         | 39.32       | 54.00    | -14.68 | AV            |
| Horizontal                         | 11490.111 | 62.08         | -8.79          | 53.29       | 68.20    | -14.91 | PK            |
| Horizontal                         | 11490.111 | 49.46         | -8.79          | 40.67       | 54.00    | -13.33 | AV            |
| Horizontal                         | 17235.152 | 57.03         | -3.18          | 53.85       | 68.20    | -14.35 | PK            |
| Horizontal                         | 17235.152 | 44.91         | -3.18          | 41.73       | 54.00    | -12.27 | AV            |
| Middle Channel (5785 MHz)-Above 1G |           |               |                |             |          |        |               |
| Vertical                           | 4592.137  | 74.59         | -20.42         | 54.17       | 74.00    | -19.83 | PK            |
| Vertical                           | 4592.137  | 59.94         | -20.42         | 39.52       | 54.00    | -14.48 | AV            |
| Vertical                           | 11570.092 | 61.06         | -8.86          | 52.20       | 68.20    | -16.00 | PK            |
| Vertical                           | 11570.092 | 49.78         | -8.86          | 40.92       | 54.00    | -13.08 | AV            |
| Vertical                           | 17355.073 | 58.08         | -2.52          | 55.56       | 68.20    | -12.64 | PK            |
| Vertical                           | 17355.073 | 44.88         | -2.52          | 42.36       | 54.00    | -11.64 | AV            |
| Horizontal                         | 4592.078  | 74.69         | -20.42         | 54.27       | 74.00    | -19.73 | PK            |
| Horizontal                         | 4592.078  | 59.15         | -20.42         | 38.74       | 54.00    | -15.26 | AV            |
| Horizontal                         | 11570.025 | 60.70         | -8.86          | 51.84       | 68.20    | -16.36 | PK            |
| Horizontal                         | 11570.025 | 49.05         | -8.86          | 40.19       | 54.00    | -13.81 | AV            |
| Horizontal                         | 17355.051 | 56.73         | -2.52          | 54.21       | 68.20    | -13.99 | PK            |
| Horizontal                         | 17355.051 | 44.61         | -2.52          | 42.09       | 54.00    | -11.91 | AV            |
| High Channel (5825 MHz)-Above 1G   |           |               |                |             |          |        |               |
| Vertical                           | 6039.086  | 74.64         | -18.93         | 55.70       | 68.20    | -12.50 | PK            |
| Vertical                           | 6039.086  | 59.63         | -18.93         | 40.69       | 54.00    | -13.31 | AV            |
| Vertical                           | 11650.077 | 60.07         | -8.92          | 51.15       | 74.00    | -22.85 | PK            |
| Vertical                           | 11650.077 | 49.52         | -8.92          | 40.60       | 54.00    | -13.40 | AV            |
| Vertical                           | 17475.109 | 55.25         | -1.86          | 53.39       | 68.20    | -14.81 | PK            |
| Vertical                           | 17475.109 | 44.40         | -1.86          | 42.54       | 54.00    | -11.46 | AV            |
| Horizontal                         | 6039.118  | 71.62         | -18.93         | 52.68       | 68.20    | -15.52 | PK            |
| Horizontal                         | 6039.118  | 59.33         | -18.93         | 40.40       | 54.00    | -13.60 | AV            |
| Horizontal                         | 11650.146 | 61.37         | -8.92          | 52.45       | 74.00    | -21.55 | PK            |
| Horizontal                         | 11650.146 | 49.23         | -8.92          | 40.31       | 54.00    | -13.69 | AV            |
| Horizontal                         | 17475.021 | 58.64         | -1.86          | 56.78       | 68.20    | -11.42 | PK            |
| Horizontal                         | 17475.021 | 44.25         | -1.86          | 42.39       | 54.00    | -11.61 | AV            |

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

|            |                           |
|------------|---------------------------|
| Test Mode: | TX (5.8G) -- 802.11n-HT40 |
|------------|---------------------------|

| Polar                              | Frequency | Reading Level | Correct Factor | Measurement | Limits   | Over   | Detector Type |
|------------------------------------|-----------|---------------|----------------|-------------|----------|--------|---------------|
| (H/V)                              | (MHz)     | (dBuV/m)      | (dB)           | (dBuV/m)    | (dBuV/m) | (dB)   |               |
| Low Channel (5755 MHz)-Above 1G    |           |               |                |             |          |        |               |
| Vertical                           | 4679.007  | 73.82         | -20.24         | 53.58       | 74.00    | -20.42 | PK            |
| Vertical                           | 4679.007  | 59.20         | -20.24         | 38.95       | 54.00    | -15.05 | AV            |
| Vertical                           | 11510.179 | 60.42         | -8.81          | 51.61       | 74.00    | -22.39 | PK            |
| Vertical                           | 11510.179 | 49.42         | -8.81          | 40.61       | 54.00    | -13.39 | AV            |
| Vertical                           | 17265.105 | 56.22         | -3.01          | 53.21       | 68.20    | -14.99 | PK            |
| Vertical                           | 17265.105 | 44.44         | -3.01          | 41.43       | 54.00    | -12.57 | AV            |
| Horizontal                         | 4679.149  | 73.51         | -20.24         | 53.27       | 74.00    | -20.73 | PK            |
| Horizontal                         | 4679.149  | 59.60         | -20.24         | 39.36       | 54.00    | -14.64 | AV            |
| Horizontal                         | 11510.116 | 64.67         | -8.81          | 55.86       | 74.00    | -18.14 | PK            |
| Horizontal                         | 11510.116 | 49.20         | -8.81          | 40.39       | 54.00    | -13.61 | AV            |
| Horizontal                         | 17265.069 | 55.43         | -3.01          | 52.42       | 68.20    | -15.78 | PK            |
| Horizontal                         | 17265.069 | 44.92         | -3.01          | 41.91       | 54.00    | -12.09 | AV            |
| Middle Channel (5795 MHz)-Above 1G |           |               |                |             |          |        |               |
| Vertical                           | 6039.150  | 74.87         | -18.93         | 55.93       | 68.20    | -12.27 | PK            |
| Vertical                           | 6039.150  | 59.79         | -18.93         | 40.86       | 54.00    | -13.14 | AV            |
| Vertical                           | 11590.137 | 61.74         | -8.87          | 52.87       | 74.00    | -21.13 | PK            |
| Vertical                           | 11590.137 | 49.41         | -8.87          | 40.54       | 54.00    | -13.46 | AV            |
| Vertical                           | 17385.151 | 56.33         | -2.35          | 53.98       | 68.20    | -14.22 | PK            |
| Vertical                           | 17385.151 | 44.41         | -2.35          | 42.06       | 54.00    | -11.94 | AV            |
| Horizontal                         | 6039.157  | 74.32         | -18.93         | 55.39       | 68.20    | -12.81 | PK            |
| Horizontal                         | 6039.157  | 59.72         | -18.93         | 40.78       | 54.00    | -13.22 | AV            |
| Horizontal                         | 11590.076 | 61.72         | -8.87          | 52.85       | 74.00    | -21.15 | PK            |
| Horizontal                         | 11590.076 | 49.79         | -8.87          | 40.92       | 54.00    | -13.08 | AV            |
| Horizontal                         | 17385.135 | 58.07         | -2.35          | 55.72       | 68.20    | -12.48 | PK            |
| Horizontal                         | 17385.135 | 44.38         | -2.35          | 42.03       | 54.00    | -11.97 | AV            |

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode: TX (5.8G) --802.11ac-HT20

| Polar                              | Frequency | Reading Level | Correct Factor | Measurement | Limits   | Over   | Detector Type |
|------------------------------------|-----------|---------------|----------------|-------------|----------|--------|---------------|
| (H/V)                              | (MHz)     | (dBuV/m)      | (dB)           | (dBuV/m)    | (dBuV/m) | (dB)   |               |
| Low Channel (5745 MHz)-Above 1G    |           |               |                |             |          |        |               |
| Vertical                           | 4679.087  | 72.93         | -20.24         | 52.69       | 74.00    | -21.31 | PK            |
| Vertical                           | 4679.087  | 59.20         | -20.24         | 38.96       | 54.00    | -15.04 | AV            |
| Vertical                           | 11490.188 | 60.95         | -8.79          | 52.16       | 68.20    | -16.04 | PK            |
| Vertical                           | 11490.188 | 49.09         | -8.79          | 40.30       | 54.00    | -13.70 | AV            |
| Vertical                           | 17235.185 | 59.86         | -3.18          | 56.68       | 68.20    | -11.52 | PK            |
| Vertical                           | 17235.185 | 44.73         | -3.18          | 41.55       | 54.00    | -12.45 | AV            |
| Horizontal                         | 4679.131  | 70.90         | -20.24         | 50.66       | 74.00    | -23.34 | PK            |
| Horizontal                         | 4679.131  | 59.02         | -20.24         | 38.78       | 54.00    | -15.22 | AV            |
| Horizontal                         | 11490.128 | 61.20         | -8.79          | 52.41       | 68.20    | -15.79 | PK            |
| Horizontal                         | 11490.128 | 49.87         | -8.79          | 41.08       | 54.00    | -12.92 | AV            |
| Horizontal                         | 17235.121 | 55.08         | -3.18          | 51.90       | 68.20    | -16.30 | PK            |
| Horizontal                         | 17235.121 | 44.58         | -3.18          | 41.40       | 54.00    | -12.60 | AV            |
| Middle Channel (5785 MHz)-Above 1G |           |               |                |             |          |        |               |
| Vertical                           | 4592.016  | 72.12         | -20.42         | 51.70       | 74.00    | -22.30 | PK            |
| Vertical                           | 4592.016  | 59.66         | -20.42         | 39.24       | 54.00    | -14.76 | AV            |
| Vertical                           | 11570.109 | 63.07         | -8.86          | 54.21       | 68.20    | -13.99 | PK            |
| Vertical                           | 11570.109 | 49.99         | -8.86          | 41.13       | 54.00    | -12.87 | AV            |
| Vertical                           | 17355.114 | 55.94         | -2.52          | 53.42       | 68.20    | -14.78 | PK            |
| Vertical                           | 17355.114 | 44.92         | -2.52          | 42.40       | 54.00    | -11.60 | AV            |
| Horizontal                         | 4592.086  | 72.92         | -20.42         | 52.50       | 74.00    | -21.50 | PK            |
| Horizontal                         | 4592.086  | 59.46         | -20.42         | 39.04       | 54.00    | -14.96 | AV            |
| Horizontal                         | 11570.171 | 63.44         | -8.86          | 54.58       | 68.20    | -13.62 | PK            |
| Horizontal                         | 11570.171 | 49.24         | -8.86          | 40.38       | 54.00    | -13.62 | AV            |
| Horizontal                         | 17355.093 | 57.44         | -2.52          | 54.92       | 68.20    | -13.28 | PK            |
| Horizontal                         | 17355.093 | 44.61         | -2.52          | 42.09       | 54.00    | -11.91 | AV            |
| High Channel (5825 MHz)-Above 1G   |           |               |                |             |          |        |               |
| Vertical                           | 6039.094  | 74.43         | -18.93         | 55.50       | 68.20    | -12.70 | PK            |
| Vertical                           | 6039.094  | 59.84         | -18.93         | 40.91       | 54.00    | -13.09 | AV            |
| Vertical                           | 11650.124 | 64.94         | -8.92          | 56.02       | 74.00    | -17.98 | PK            |
| Vertical                           | 11650.124 | 49.15         | -8.92          | 40.23       | 54.00    | -13.77 | AV            |
| Vertical                           | 17475.128 | 55.60         | -1.86          | 53.74       | 68.20    | -14.46 | PK            |
| Vertical                           | 17475.128 | 44.27         | -1.86          | 42.41       | 54.00    | -11.59 | AV            |
| Horizontal                         | 6039.051  | 71.67         | -18.93         | 52.74       | 68.20    | -15.46 | PK            |
| Horizontal                         | 6039.051  | 59.75         | -18.93         | 40.82       | 54.00    | -13.18 | AV            |
| Horizontal                         | 11650.166 | 61.49         | -8.92          | 52.57       | 74.00    | -21.43 | PK            |
| Horizontal                         | 11650.166 | 49.37         | -8.92          | 40.45       | 54.00    | -13.55 | AV            |
| Horizontal                         | 17475.062 | 55.06         | -1.86          | 53.20       | 68.20    | -15.00 | PK            |
| Horizontal                         | 17475.062 | 45.00         | -1.86          | 43.14       | 54.00    | -10.86 | AV            |

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

|             |                            |
|-------------|----------------------------|
| Test Mode : | TX (5.8G) -- 802.11ac-HT40 |
|-------------|----------------------------|

| Polar<br>(H/V)                     | Frequency<br>(MHz) | Reading<br>Level<br>(dBuV/m) | Correct<br>Factor<br>(dB) | Measure-<br>ment<br>(dBuV/m) | Limits<br>(dBuV/m) | Over<br>(dB) | Detector<br>Type |
|------------------------------------|--------------------|------------------------------|---------------------------|------------------------------|--------------------|--------------|------------------|
| Low Channel (5755 MHz)-Above 1G    |                    |                              |                           |                              |                    |              |                  |
| Vertical                           | 4679.128           | 73.50                        | -20.24                    | 53.26                        | 74.00              | -20.74       | PK               |
| Vertical                           | 4679.128           | 59.93                        | -20.24                    | 39.69                        | 54.00              | -14.31       | AV               |
| Vertical                           | 11510.130          | 64.09                        | -8.81                     | 55.28                        | 74.00              | -18.72       | PK               |
| Vertical                           | 11510.130          | 49.04                        | -8.81                     | 40.23                        | 54.00              | -13.77       | AV               |
| Vertical                           | 17265.089          | 57.49                        | -3.01                     | 54.48                        | 68.20              | -13.72       | PK               |
| Vertical                           | 17265.089          | 44.29                        | -3.01                     | 41.28                        | 54.00              | -12.72       | AV               |
| Horizontal                         | 4679.030           | 71.76                        | -20.24                    | 51.52                        | 74.00              | -22.48       | PK               |
| Horizontal                         | 4679.030           | 59.83                        | -20.24                    | 39.59                        | 54.00              | -14.41       | AV               |
| Horizontal                         | 11510.159          | 64.55                        | -8.81                     | 55.74                        | 74.00              | -18.26       | PK               |
| Horizontal                         | 11510.159          | 49.25                        | -8.81                     | 40.44                        | 54.00              | -13.56       | AV               |
| Horizontal                         | 17265.192          | 55.00                        | -3.01                     | 51.99                        | 68.20              | -16.21       | PK               |
| Horizontal                         | 17265.192          | 44.66                        | -3.01                     | 41.65                        | 54.00              | -12.35       | AV               |
| Middle Channel (5795 MHz)-Above 1G |                    |                              |                           |                              |                    |              |                  |
| Vertical                           | 6039.146           | 72.64                        | -18.93                    | 53.71                        | 68.20              | -14.49       | PK               |
| Vertical                           | 6039.146           | 59.92                        | -18.93                    | 40.99                        | 54.00              | -13.01       | AV               |
| Vertical                           | 11590.059          | 61.43                        | -8.87                     | 52.56                        | 74.00              | -21.44       | PK               |
| Vertical                           | 11590.059          | 49.65                        | -8.87                     | 40.78                        | 54.00              | -13.22       | AV               |
| Vertical                           | 17385.162          | 58.21                        | -2.35                     | 55.86                        | 68.20              | -12.34       | PK               |
| Vertical                           | 17385.162          | 44.86                        | -2.35                     | 42.51                        | 54.00              | -11.49       | AV               |
| Horizontal                         | 6039.095           | 70.74                        | -18.93                    | 51.81                        | 68.20              | -16.39       | PK               |
| Horizontal                         | 6039.095           | 59.84                        | -18.93                    | 40.91                        | 54.00              | -13.09       | AV               |
| Horizontal                         | 11590.140          | 61.34                        | -8.87                     | 52.47                        | 74.00              | -21.53       | PK               |
| Horizontal                         | 11590.140          | 49.65                        | -8.87                     | 40.78                        | 54.00              | -13.22       | AV               |
| Horizontal                         | 17385.196          | 56.61                        | -2.35                     | 54.26                        | 68.20              | -13.94       | PK               |
| Horizontal                         | 17385.196          | 44.89                        | -2.35                     | 42.54                        | 54.00              | -11.46       | AV               |

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode: TX (5.8G) --802.11ax-HT20

| Polar                              | Frequency | Reading Level | Correct Factor | Measurement | Limits   | Over   | Detector Type |
|------------------------------------|-----------|---------------|----------------|-------------|----------|--------|---------------|
| (H/V)                              | (MHz)     | (dBuV/m)      | (dB)           | (dBuV/m)    | (dBuV/m) | (dB)   |               |
| Low Channel (5745 MHz)-Above 1G    |           |               |                |             |          |        |               |
| Vertical                           | 4679.113  | 71.70         | -20.24         | 51.46       | 74.00    | -22.54 | PK            |
| Vertical                           | 4679.113  | 59.92         | -20.24         | 39.68       | 54.00    | -14.32 | AV            |
| Vertical                           | 11490.193 | 61.24         | -8.79          | 52.45       | 68.20    | -15.75 | PK            |
| Vertical                           | 11490.193 | 49.52         | -8.79          | 40.73       | 54.00    | -13.27 | AV            |
| Vertical                           | 17235.006 | 59.54         | -3.18          | 56.36       | 68.20    | -11.84 | PK            |
| Vertical                           | 17235.006 | 44.91         | -3.18          | 41.73       | 54.00    | -12.27 | AV            |
| Horizontal                         | 4679.172  | 74.43         | -20.24         | 54.19       | 74.00    | -19.81 | PK            |
| Horizontal                         | 4679.172  | 59.16         | -20.24         | 38.91       | 54.00    | -15.09 | AV            |
| Horizontal                         | 11490.156 | 61.66         | -8.79          | 52.87       | 68.20    | -15.33 | PK            |
| Horizontal                         | 11490.156 | 49.75         | -8.79          | 40.96       | 54.00    | -13.04 | AV            |
| Horizontal                         | 17235.147 | 56.29         | -3.18          | 53.11       | 68.20    | -15.09 | PK            |
| Horizontal                         | 17235.147 | 44.79         | -3.18          | 41.61       | 54.00    | -12.39 | AV            |
| Middle Channel (5785 MHz)-Above 1G |           |               |                |             |          |        |               |
| Vertical                           | 4592.183  | 73.30         | -20.42         | 52.88       | 74.00    | -21.12 | PK            |
| Vertical                           | 4592.183  | 59.17         | -20.42         | 38.75       | 54.00    | -15.25 | AV            |
| Vertical                           | 11570.051 | 63.30         | -8.86          | 54.44       | 68.20    | -13.76 | PK            |
| Vertical                           | 11570.051 | 49.85         | -8.86          | 40.99       | 54.00    | -13.01 | AV            |
| Vertical                           | 17355.006 | 56.40         | -2.52          | 53.88       | 68.20    | -14.32 | PK            |
| Vertical                           | 17355.006 | 44.81         | -2.52          | 42.29       | 54.00    | -11.71 | AV            |
| Horizontal                         | 4592.011  | 72.06         | -20.42         | 51.64       | 74.00    | -22.36 | PK            |
| Horizontal                         | 4592.011  | 59.17         | -20.42         | 38.76       | 54.00    | -15.24 | AV            |
| Horizontal                         | 11570.192 | 60.05         | -8.86          | 51.19       | 68.20    | -17.01 | PK            |
| Horizontal                         | 11570.192 | 49.12         | -8.86          | 40.26       | 54.00    | -13.74 | AV            |
| Horizontal                         | 17355.050 | 57.40         | -2.52          | 54.88       | 68.20    | -13.32 | PK            |
| Horizontal                         | 17355.050 | 44.16         | -2.52          | 41.64       | 54.00    | -12.36 | AV            |
| High Channel (5825 MHz)-Above 1G   |           |               |                |             |          |        |               |
| Vertical                           | 6039.142  | 70.66         | -18.93         | 51.73       | 68.20    | -16.47 | PK            |
| Vertical                           | 6039.142  | 59.06         | -18.93         | 40.13       | 54.00    | -13.87 | AV            |
| Vertical                           | 11650.026 | 64.31         | -8.92          | 55.39       | 74.00    | -18.61 | PK            |
| Vertical                           | 11650.026 | 49.01         | -8.92          | 40.09       | 54.00    | -13.91 | AV            |
| Vertical                           | 17475.168 | 58.14         | -1.86          | 56.28       | 68.20    | -11.92 | PK            |
| Vertical                           | 17475.168 | 44.42         | -1.86          | 42.56       | 54.00    | -11.44 | AV            |
| Horizontal                         | 6039.184  | 71.87         | -18.93         | 52.94       | 68.20    | -15.26 | PK            |
| Horizontal                         | 6039.184  | 59.93         | -18.93         | 40.99       | 54.00    | -13.01 | AV            |
| Horizontal                         | 11650.148 | 63.78         | -8.92          | 54.86       | 74.00    | -19.14 | PK            |
| Horizontal                         | 11650.148 | 49.12         | -8.92          | 40.20       | 54.00    | -13.80 | AV            |
| Horizontal                         | 17475.069 | 59.64         | -1.86          | 57.78       | 68.20    | -10.42 | PK            |
| Horizontal                         | 17475.069 | 44.75         | -1.86          | 42.89       | 54.00    | -11.11 | AV            |

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

|             |                            |
|-------------|----------------------------|
| Test Mode : | TX (5.8G) -- 802.11ax-HT40 |
|-------------|----------------------------|

| Polar<br>(H/V)                     | Frequency<br>(MHz) | Reading<br>Level<br>(dBuV/m) | Correct<br>Factor<br>(dB) | Measure-<br>ment<br>(dBuV/m) | Limits<br>(dBuV/m) | Over<br>(dB) | Detector<br>Type |
|------------------------------------|--------------------|------------------------------|---------------------------|------------------------------|--------------------|--------------|------------------|
| Low Channel (5755 MHz)-Above 1G    |                    |                              |                           |                              |                    |              |                  |
| Vertical                           | 4679.047           | 73.21                        | -20.24                    | 52.97                        | 74.00              | -21.03       | PK               |
| Vertical                           | 4679.047           | 59.89                        | -20.24                    | 39.65                        | 54.00              | -14.35       | AV               |
| Vertical                           | 11510.131          | 64.11                        | -8.81                     | 55.30                        | 74.00              | -18.70       | PK               |
| Vertical                           | 11510.131          | 49.69                        | -8.81                     | 40.88                        | 54.00              | -13.12       | AV               |
| Vertical                           | 17265.175          | 56.94                        | -3.01                     | 53.93                        | 68.20              | -14.27       | PK               |
| Vertical                           | 17265.175          | 44.39                        | -3.01                     | 41.38                        | 54.00              | -12.62       | AV               |
| Horizontal                         | 4679.141           | 72.01                        | -20.24                    | 51.77                        | 74.00              | -22.23       | PK               |
| Horizontal                         | 4679.141           | 59.67                        | -20.24                    | 39.42                        | 54.00              | -14.58       | AV               |
| Horizontal                         | 11510.180          | 60.47                        | -8.81                     | 51.66                        | 74.00              | -22.34       | PK               |
| Horizontal                         | 11510.180          | 49.43                        | -8.81                     | 40.62                        | 54.00              | -13.38       | AV               |
| Horizontal                         | 17265.022          | 55.02                        | -3.01                     | 52.01                        | 68.20              | -16.19       | PK               |
| Horizontal                         | 17265.022          | 44.32                        | -3.01                     | 41.31                        | 54.00              | -12.69       | AV               |
| Middle Channel (5795 MHz)-Above 1G |                    |                              |                           |                              |                    |              |                  |
| Vertical                           | 6039.125           | 74.66                        | -18.93                    | 55.73                        | 68.20              | -12.47       | PK               |
| Vertical                           | 6039.125           | 59.95                        | -18.93                    | 41.01                        | 54.00              | -12.99       | AV               |
| Vertical                           | 11590.131          | 61.07                        | -8.87                     | 52.20                        | 74.00              | -21.80       | PK               |
| Vertical                           | 11590.131          | 49.22                        | -8.87                     | 40.35                        | 54.00              | -13.65       | AV               |
| Vertical                           | 17385.071          | 55.08                        | -2.35                     | 52.73                        | 68.20              | -15.47       | PK               |
| Vertical                           | 17385.071          | 44.71                        | -2.35                     | 42.36                        | 54.00              | -11.64       | AV               |
| Horizontal                         | 6039.004           | 73.61                        | -18.93                    | 54.68                        | 68.20              | -13.52       | PK               |
| Horizontal                         | 6039.004           | 59.06                        | -18.93                    | 40.13                        | 54.00              | -13.87       | AV               |
| Horizontal                         | 11590.062          | 60.13                        | -8.87                     | 51.26                        | 74.00              | -22.74       | PK               |
| Horizontal                         | 11590.062          | 49.26                        | -8.87                     | 40.39                        | 54.00              | -13.61       | AV               |
| Horizontal                         | 17385.060          | 59.14                        | -2.35                     | 56.79                        | 68.20              | -11.41       | PK               |
| Horizontal                         | 17385.060          | 44.16                        | -2.35                     | 41.81                        | 54.00              | -12.19       | AV               |

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Antenna 2

Between 1GHz – 40GHz

|            |                    |
|------------|--------------------|
| Test Mode: | TX(5.1G) - 802.11a |
|------------|--------------------|

| Polar                              | Frequency | Reading Level | Correct Factor | Measurement | Limits   | Over   | Detector Type |
|------------------------------------|-----------|---------------|----------------|-------------|----------|--------|---------------|
| (H/V)                              | (MHz)     | (dBuV/m)      | (dB)           | (dBuV/m)    | (dBuV/m) | (dB)   |               |
| Low Channel (5180 MHz)-Above 1G    |           |               |                |             |          |        |               |
| Vertical                           | 4434.162  | 71.82         | -20.73         | 51.09       | 68.20    | -17.11 | PK            |
| Vertical                           | 4434.162  | 59.85         | -20.73         | 39.12       | 54.00    | -14.88 | AV            |
| Vertical                           | 10360.024 | 63.83         | -9.36          | 54.47       | 68.20    | -13.73 | PK            |
| Vertical                           | 10360.024 | 49.05         | -9.36          | 39.69       | 54.00    | -14.31 | AV            |
| Vertical                           | 15540.005 | 64.50         | -7.84          | 56.66       | 74.00    | -17.34 | PK            |
| Vertical                           | 15540.005 | 49.06         | -7.84          | 41.22       | 54.00    | -12.78 | AV            |
| Horizontal                         | 4434.025  | 72.03         | -20.73         | 51.30       | 68.20    | -16.90 | PK            |
| Horizontal                         | 4434.025  | 59.14         | -20.73         | 38.41       | 54.00    | -15.59 | AV            |
| Horizontal                         | 10360.107 | 60.17         | -9.36          | 50.81       | 68.20    | -17.39 | PK            |
| Horizontal                         | 10360.107 | 49.14         | -9.36          | 39.78       | 54.00    | -14.22 | AV            |
| Horizontal                         | 15540.164 | 61.07         | -7.84          | 53.23       | 74.00    | -20.77 | PK            |
| Horizontal                         | 15540.164 | 49.48         | -7.84          | 41.64       | 54.00    | -12.36 | AV            |
| Middle Channel (5200 MHz)-Above 1G |           |               |                |             |          |        |               |
| Vertical                           | 4592.162  | 72.47         | -20.42         | 52.05       | 74.00    | -21.95 | PK            |
| Vertical                           | 4592.162  | 59.44         | -20.42         | 39.03       | 54.00    | -14.97 | AV            |
| Vertical                           | 10400.100 | 62.01         | -9.30          | 52.71       | 68.20    | -15.49 | PK            |
| Vertical                           | 10400.100 | 49.02         | -9.30          | 39.72       | 54.00    | -14.28 | AV            |
| Vertical                           | 15600.037 | 61.85         | -7.82          | 54.03       | 74.00    | -19.97 | PK            |
| Vertical                           | 15600.037 | 49.46         | -7.82          | 41.64       | 54.00    | -12.36 | AV            |
| Horizontal                         | 4592.113  | 73.88         | -20.42         | 53.46       | 74.00    | -20.54 | PK            |
| Horizontal                         | 4592.113  | 59.09         | -20.42         | 38.68       | 54.00    | -15.32 | AV            |
| Horizontal                         | 10400.015 | 64.99         | -9.30          | 55.69       | 68.20    | -12.51 | PK            |
| Horizontal                         | 10400.015 | 49.88         | -9.30          | 40.58       | 54.00    | -13.42 | AV            |
| Horizontal                         | 15600.113 | 64.26         | -7.82          | 56.44       | 74.00    | -17.56 | PK            |
| Horizontal                         | 15600.113 | 49.16         | -7.82          | 41.34       | 54.00    | -12.66 | AV            |
| High Channel (5240 MHz)-Above 1G   |           |               |                |             |          |        |               |
| Vertical                           | 4739.018  | 70.14         | -20.12         | 50.02       | 74.00    | -23.98 | PK            |
| Vertical                           | 4739.018  | 59.40         | -20.12         | 39.28       | 54.00    | -14.72 | AV            |
| Vertical                           | 10480.090 | 61.25         | -9.18          | 52.07       | 68.20    | -16.13 | PK            |
| Vertical                           | 10480.090 | 49.70         | -9.18          | 40.52       | 54.00    | -13.48 | AV            |
| Vertical                           | 15720.086 | 61.11         | -7.78          | 53.33       | 74.00    | -20.67 | PK            |
| Vertical                           | 15720.086 | 49.20         | -7.78          | 41.42       | 54.00    | -12.58 | AV            |
| Horizontal                         | 4739.003  | 72.78         | -20.12         | 52.66       | 74.00    | -21.34 | PK            |
| Horizontal                         | 4739.003  | 59.14         | -20.12         | 39.01       | 54.00    | -14.99 | AV            |
| Horizontal                         | 10480.183 | 64.61         | -9.18          | 55.43       | 68.20    | -12.77 | PK            |
| Horizontal                         | 10480.183 | 49.19         | -9.18          | 40.01       | 54.00    | -13.99 | AV            |
| Horizontal                         | 15720.055 | 62.17         | -7.78          | 54.39       | 74.00    | -19.61 | PK            |
| Horizontal                         | 15720.055 | 49.18         | -7.78          | 41.40       | 54.00    | -12.60 | AV            |

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

|            |                         |
|------------|-------------------------|
| Test Mode: | TX(5.1G) - 802.11n-HT20 |
|------------|-------------------------|

| Polar                              | Frequency | Reading Level | Correct Factor | Measurement | Limits   | Over   | Detector Type |
|------------------------------------|-----------|---------------|----------------|-------------|----------|--------|---------------|
| (H/V)                              | (MHz)     | (dBuV/m)      | (dB)           | (dBuV/m)    | (dBuV/m) | (dB)   |               |
| Low Channel (5180 MHz)-Above 1G    |           |               |                |             |          |        |               |
| Vertical                           | 4434.175  | 70.18         | -20.73         | 49.45       | 68.20    | -18.75 | PK            |
| Vertical                           | 4434.175  | 59.01         | -20.73         | 38.27       | 54.00    | -15.73 | AV            |
| Vertical                           | 10360.113 | 64.44         | -9.36          | 55.08       | 68.20    | -13.12 | PK            |
| Vertical                           | 10360.113 | 49.53         | -9.36          | 40.17       | 54.00    | -13.83 | AV            |
| Vertical                           | 15540.067 | 60.80         | -7.84          | 52.96       | 74.00    | -21.04 | PK            |
| Vertical                           | 15540.067 | 49.25         | -7.84          | 41.41       | 54.00    | -12.59 | AV            |
| Horizontal                         | 4434.027  | 73.13         | -20.73         | 52.40       | 68.20    | -15.80 | PK            |
| Horizontal                         | 4434.027  | 59.95         | -20.73         | 39.22       | 54.00    | -14.78 | AV            |
| Horizontal                         | 10360.132 | 61.15         | -9.36          | 51.79       | 68.20    | -16.41 | PK            |
| Horizontal                         | 10360.132 | 49.39         | -9.36          | 40.03       | 54.00    | -13.97 | AV            |
| Horizontal                         | 15540.014 | 64.51         | -7.84          | 56.67       | 74.00    | -17.33 | PK            |
| Horizontal                         | 15540.014 | 49.52         | -7.84          | 41.68       | 54.00    | -12.32 | AV            |
| Middle Channel (5200 MHz)-Above 1G |           |               |                |             |          |        |               |
| Vertical                           | 4592.161  | 73.10         | -20.42         | 52.69       | 74.00    | -21.31 | PK            |
| Vertical                           | 4592.161  | 59.92         | -20.42         | 39.50       | 54.00    | -14.50 | AV            |
| Vertical                           | 10400.169 | 63.67         | -9.30          | 54.37       | 68.20    | -13.83 | PK            |
| Vertical                           | 10400.169 | 49.46         | -9.30          | 40.16       | 54.00    | -13.84 | AV            |
| Vertical                           | 15600.140 | 61.39         | -7.82          | 53.57       | 74.00    | -20.43 | PK            |
| Vertical                           | 15600.140 | 49.57         | -7.82          | 41.75       | 54.00    | -12.25 | AV            |
| Horizontal                         | 4592.165  | 73.07         | -20.42         | 52.66       | 74.00    | -21.34 | PK            |
| Horizontal                         | 4592.165  | 59.90         | -20.42         | 39.49       | 54.00    | -14.51 | AV            |
| Horizontal                         | 10400.071 | 64.41         | -9.30          | 55.11       | 68.20    | -13.09 | PK            |
| Horizontal                         | 10400.071 | 49.89         | -9.30          | 40.59       | 54.00    | -13.41 | AV            |
| Horizontal                         | 15600.012 | 60.98         | -7.82          | 53.16       | 74.00    | -20.84 | PK            |
| Horizontal                         | 15600.012 | 49.77         | -7.82          | 41.95       | 54.00    | -12.05 | AV            |
| High Channel (5240 MHz)-Above 1G   |           |               |                |             |          |        |               |
| Vertical                           | 4739.112  | 70.45         | -20.12         | 50.33       | 74.00    | -23.67 | PK            |
| Vertical                           | 4739.112  | 59.06         | -20.12         | 38.94       | 54.00    | -15.06 | AV            |
| Vertical                           | 10480.182 | 60.94         | -9.18          | 51.76       | 68.20    | -16.44 | PK            |
| Vertical                           | 10480.182 | 49.52         | -9.18          | 40.34       | 54.00    | -13.66 | AV            |
| Vertical                           | 15720.132 | 62.13         | -7.78          | 54.35       | 74.00    | -19.65 | PK            |
| Vertical                           | 15720.132 | 49.74         | -7.78          | 41.96       | 54.00    | -12.04 | AV            |
| Horizontal                         | 4739.150  | 74.32         | -20.12         | 54.19       | 74.00    | -19.81 | PK            |
| Horizontal                         | 4739.150  | 59.10         | -20.12         | 38.98       | 54.00    | -15.02 | AV            |
| Horizontal                         | 10480.102 | 60.84         | -9.18          | 51.66       | 68.20    | -16.54 | PK            |
| Horizontal                         | 10480.102 | 49.41         | -9.18          | 40.23       | 54.00    | -13.77 | AV            |
| Horizontal                         | 15720.200 | 60.68         | -7.78          | 52.90       | 74.00    | -21.10 | PK            |
| Horizontal                         | 15720.200 | 49.48         | -7.78          | 41.70       | 54.00    | -12.30 | AV            |

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

|            |                         |
|------------|-------------------------|
| Test Mode: | TX(5.1G) - 802.11n-HT40 |
|------------|-------------------------|

| Polar                              | Frequency | Reading Level | Correct Factor | Measurement | Limits   | Over   | Detector Type |
|------------------------------------|-----------|---------------|----------------|-------------|----------|--------|---------------|
| (H/V)                              | (MHz)     | (dBuV/m)      | (dB)           | (dBuV/m)    | (dBuV/m) | (dB)   |               |
| Low Channel (5190 MHz)-Above 1G    |           |               |                |             |          |        |               |
| Vertical                           | 4434.045  | 73.16         | -20.73         | 52.43       | 68.20    | -15.77 | PK            |
| Vertical                           | 4434.045  | 59.96         | -20.73         | 39.23       | 54.00    | -14.77 | AV            |
| Vertical                           | 10380.031 | 62.12         | -9.33          | 52.79       | 68.20    | -15.41 | PK            |
| Vertical                           | 10380.031 | 49.02         | -9.33          | 39.69       | 54.00    | -14.31 | AV            |
| Vertical                           | 15570.003 | 61.44         | -7.83          | 53.61       | 74.00    | -20.39 | PK            |
| Vertical                           | 15570.003 | 49.97         | -7.83          | 42.14       | 54.00    | -11.86 | AV            |
| Horizontal                         | 4434.140  | 74.25         | -20.73         | 53.52       | 74.00    | -20.48 | PK            |
| Horizontal                         | 4434.140  | 59.35         | -20.73         | 38.62       | 54.00    | -15.38 | AV            |
| Horizontal                         | 10380.067 | 61.94         | -9.33          | 52.61       | 68.20    | -15.59 | PK            |
| Horizontal                         | 10380.067 | 49.48         | -9.33          | 40.15       | 54.00    | -13.85 | AV            |
| Horizontal                         | 15570.169 | 64.47         | -7.83          | 56.64       | 74.00    | -17.36 | PK            |
| Horizontal                         | 15570.169 | 49.33         | -7.83          | 41.50       | 54.00    | -12.50 | AV            |
| Middle Channel (5230 MHz)-Above 1G |           |               |                |             |          |        |               |
| Vertical                           | 4739.198  | 71.10         | -20.12         | 50.98       | 68.20    | -17.22 | PK            |
| Vertical                           | 4739.198  | 59.36         | -20.12         | 39.24       | 54.00    | -14.76 | AV            |
| Vertical                           | 10460.144 | 61.07         | -9.21          | 51.86       | 68.20    | -16.34 | PK            |
| Vertical                           | 10460.144 | 49.67         | -9.21          | 40.46       | 54.00    | -13.54 | AV            |
| Vertical                           | 15690.193 | 62.35         | -7.79          | 54.56       | 74.00    | -19.44 | PK            |
| Vertical                           | 15690.193 | 49.95         | -7.79          | 42.16       | 54.00    | -11.84 | AV            |
| Horizontal                         | 4739.180  | 71.50         | -20.12         | 51.38       | 68.20    | -16.82 | PK            |
| Horizontal                         | 4739.180  | 59.65         | -20.12         | 39.53       | 54.00    | -14.47 | AV            |
| Horizontal                         | 10460.189 | 63.34         | -9.21          | 54.13       | 68.20    | -14.07 | PK            |
| Horizontal                         | 10460.189 | 49.37         | -9.21          | 40.16       | 54.00    | -13.84 | AV            |
| Horizontal                         | 15690.045 | 64.80         | -7.79          | 57.01       | 74.00    | -16.99 | PK            |
| Horizontal                         | 15690.045 | 49.77         | -7.79          | 41.98       | 54.00    | -12.02 | AV            |

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

|            |                          |
|------------|--------------------------|
| Test Mode: | TX(5.1G) - 802.11ac-HT20 |
|------------|--------------------------|

| Polar                              | Frequency | Reading Level | Correct Factor | Measurement | Limits   | Over   | Detector Type |
|------------------------------------|-----------|---------------|----------------|-------------|----------|--------|---------------|
| (H/V)                              | (MHz)     | (dBuV/m)      | (dB)           | (dBuV/m)    | (dBuV/m) | (dB)   |               |
| Low Channel (5180 MHz)-Above 1G    |           |               |                |             |          |        |               |
| Vertical                           | 4434.084  | 72.05         | -20.73         | 51.32       | 68.20    | -16.88 | PK            |
| Vertical                           | 4434.084  | 59.73         | -20.73         | 39.00       | 54.00    | -15.00 | AV            |
| Vertical                           | 10360.059 | 64.68         | -9.36          | 55.32       | 68.20    | -12.88 | PK            |
| Vertical                           | 10360.059 | 49.56         | -9.36          | 40.20       | 54.00    | -13.80 | AV            |
| Vertical                           | 15540.149 | 60.47         | -7.84          | 52.63       | 74.00    | -21.37 | PK            |
| Vertical                           | 15540.149 | 49.22         | -7.84          | 41.38       | 54.00    | -12.62 | AV            |
| Horizontal                         | 4434.039  | 71.02         | -20.73         | 50.29       | 68.20    | -17.91 | PK            |
| Horizontal                         | 4434.039  | 59.06         | -20.73         | 38.32       | 54.00    | -15.68 | AV            |
| Horizontal                         | 10360.184 | 62.32         | -9.36          | 52.96       | 68.20    | -15.24 | PK            |
| Horizontal                         | 10360.184 | 49.27         | -9.36          | 39.91       | 54.00    | -14.09 | AV            |
| Horizontal                         | 15540.087 | 63.33         | -7.84          | 55.49       | 74.00    | -18.51 | PK            |
| Horizontal                         | 15540.087 | 49.79         | -7.84          | 41.95       | 54.00    | -12.05 | AV            |
| Middle Channel (5200 MHz)-Above 1G |           |               |                |             |          |        |               |
| Vertical                           | 4592.178  | 70.86         | -20.42         | 50.45       | 74.00    | -23.55 | PK            |
| Vertical                           | 4592.178  | 59.76         | -20.42         | 39.35       | 54.00    | -14.65 | AV            |
| Vertical                           | 10400.136 | 64.20         | -9.30          | 54.90       | 68.20    | -13.30 | PK            |
| Vertical                           | 10400.136 | 49.72         | -9.30          | 40.42       | 54.00    | -13.58 | AV            |
| Vertical                           | 15600.047 | 60.68         | -7.82          | 52.86       | 74.00    | -21.14 | PK            |
| Vertical                           | 15600.047 | 49.01         | -7.82          | 41.19       | 54.00    | -12.81 | AV            |
| Horizontal                         | 4592.107  | 74.40         | -20.42         | 53.99       | 74.00    | -20.01 | PK            |
| Horizontal                         | 4592.107  | 59.25         | -20.42         | 38.84       | 54.00    | -15.16 | AV            |
| Horizontal                         | 10400.104 | 60.73         | -9.30          | 51.43       | 68.20    | -16.77 | PK            |
| Horizontal                         | 10400.104 | 49.40         | -9.30          | 40.10       | 54.00    | -13.90 | AV            |
| Horizontal                         | 15600.199 | 64.21         | -7.82          | 56.39       | 74.00    | -17.61 | PK            |
| Horizontal                         | 15600.199 | 49.78         | -7.82          | 41.96       | 54.00    | -12.04 | AV            |
| High Channel (5240 MHz)-Above 1G   |           |               |                |             |          |        |               |
| Vertical                           | 4739.180  | 74.09         | -20.12         | 53.97       | 74.00    | -20.03 | PK            |
| Vertical                           | 4739.180  | 59.89         | -20.12         | 39.77       | 54.00    | -14.23 | AV            |
| Vertical                           | 10480.111 | 62.99         | -9.18          | 53.81       | 68.20    | -14.39 | PK            |
| Vertical                           | 10480.111 | 49.34         | -9.18          | 40.16       | 54.00    | -13.84 | AV            |
| Vertical                           | 15720.001 | 60.46         | -7.78          | 52.68       | 74.00    | -21.32 | PK            |
| Vertical                           | 15720.001 | 49.47         | -7.78          | 41.69       | 54.00    | -12.31 | AV            |
| Horizontal                         | 4739.019  | 73.37         | -20.12         | 53.25       | 74.00    | -20.75 | PK            |
| Horizontal                         | 4739.019  | 59.21         | -20.12         | 39.09       | 54.00    | -14.91 | AV            |
| Horizontal                         | 10480.039 | 63.98         | -9.18          | 54.80       | 68.20    | -13.40 | PK            |
| Horizontal                         | 10480.039 | 49.44         | -9.18          | 40.26       | 54.00    | -13.74 | AV            |
| Horizontal                         | 15720.089 | 62.60         | -7.78          | 54.82       | 74.00    | -19.18 | PK            |
| Horizontal                         | 15720.089 | 49.85         | -7.78          | 42.07       | 54.00    | -11.93 | AV            |

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

|            |                          |
|------------|--------------------------|
| Test Mode: | TX(5.1G) - 802.11ac-HT40 |
|------------|--------------------------|

| Polar                              | Frequency | Reading Level | Correct Factor | Measurement | Limits   | Over   | Detector Type |
|------------------------------------|-----------|---------------|----------------|-------------|----------|--------|---------------|
| (H/V)                              | (MHz)     | (dBuV/m)      | (dB)           | (dBuV/m)    | (dBuV/m) | (dB)   |               |
| Low Channel (5190 MHz)-Above 1G    |           |               |                |             |          |        |               |
| Vertical                           | 4434.079  | 71.07         | -20.73         | 50.34       | 68.20    | -17.86 | PK            |
| Vertical                           | 4434.079  | 59.09         | -20.73         | 38.35       | 54.00    | -15.65 | AV            |
| Vertical                           | 10380.012 | 62.76         | -9.33          | 53.43       | 68.20    | -14.77 | PK            |
| Vertical                           | 10380.012 | 49.24         | -9.33          | 39.91       | 54.00    | -14.09 | AV            |
| Vertical                           | 15570.100 | 60.39         | -7.83          | 52.56       | 74.00    | -21.44 | PK            |
| Vertical                           | 15570.100 | 49.12         | -7.83          | 41.29       | 54.00    | -12.71 | AV            |
| Horizontal                         | 4434.037  | 74.78         | -20.73         | 54.05       | 74.00    | -19.95 | PK            |
| Horizontal                         | 4434.037  | 59.59         | -20.73         | 38.85       | 54.00    | -15.15 | AV            |
| Horizontal                         | 10380.033 | 61.69         | -9.33          | 52.36       | 68.20    | -15.84 | PK            |
| Horizontal                         | 10380.033 | 49.30         | -9.33          | 39.97       | 54.00    | -14.03 | AV            |
| Horizontal                         | 15570.007 | 61.75         | -7.83          | 53.92       | 74.00    | -20.08 | PK            |
| Horizontal                         | 15570.007 | 49.16         | -7.83          | 41.33       | 54.00    | -12.67 | AV            |
| Middle Channel (5230 MHz)-Above 1G |           |               |                |             |          |        |               |
| Vertical                           | 4739.062  | 73.33         | -20.12         | 53.20       | 68.20    | -15.00 | PK            |
| Vertical                           | 4739.062  | 59.23         | -20.12         | 39.10       | 54.00    | -14.90 | AV            |
| Vertical                           | 10460.154 | 60.00         | -9.21          | 50.79       | 68.20    | -17.41 | PK            |
| Vertical                           | 10460.154 | 49.59         | -9.21          | 40.38       | 54.00    | -13.62 | AV            |
| Vertical                           | 15690.087 | 64.23         | -7.79          | 56.44       | 74.00    | -17.56 | PK            |
| Vertical                           | 15690.087 | 49.39         | -7.79          | 41.60       | 54.00    | -12.40 | AV            |
| Horizontal                         | 4739.137  | 74.24         | -20.12         | 54.12       | 68.20    | -14.08 | PK            |
| Horizontal                         | 4739.137  | 59.19         | -20.12         | 39.07       | 54.00    | -14.93 | AV            |
| Horizontal                         | 10460.077 | 64.03         | -9.21          | 54.82       | 68.20    | -13.38 | PK            |
| Horizontal                         | 10460.077 | 49.36         | -9.21          | 40.15       | 54.00    | -13.85 | AV            |
| Horizontal                         | 15690.198 | 64.44         | -7.79          | 56.65       | 74.00    | -17.35 | PK            |
| Horizontal                         | 15690.198 | 49.19         | -7.79          | 41.40       | 54.00    | -12.60 | AV            |

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

|            |                          |
|------------|--------------------------|
| Test Mode: | TX(5.1G) - 802.11ax-HT20 |
|------------|--------------------------|

| Polar                              | Frequency | Reading Level | Correct Factor | Measurement | Limits   | Over   | Detector Type |
|------------------------------------|-----------|---------------|----------------|-------------|----------|--------|---------------|
| (H/V)                              | (MHz)     | (dBuV/m)      | (dB)           | (dBuV/m)    | (dBuV/m) | (dB)   |               |
| Low Channel (5180 MHz)-Above 1G    |           |               |                |             |          |        |               |
| Vertical                           | 4434.151  | 70.05         | -20.73         | 49.32       | 68.20    | -18.88 | PK            |
| Vertical                           | 4434.151  | 59.54         | -20.73         | 38.81       | 54.00    | -15.19 | AV            |
| Vertical                           | 10360.030 | 60.33         | -9.36          | 50.97       | 68.20    | -17.23 | PK            |
| Vertical                           | 10360.030 | 49.25         | -9.36          | 39.89       | 54.00    | -14.11 | AV            |
| Vertical                           | 15540.114 | 62.02         | -7.84          | 54.18       | 74.00    | -19.82 | PK            |
| Vertical                           | 15540.114 | 49.69         | -7.84          | 41.85       | 54.00    | -12.15 | AV            |
| Horizontal                         | 4434.028  | 71.46         | -20.73         | 50.73       | 68.20    | -17.47 | PK            |
| Horizontal                         | 4434.028  | 59.19         | -20.73         | 38.46       | 54.00    | -15.54 | AV            |
| Horizontal                         | 10360.081 | 64.84         | -9.36          | 55.48       | 68.20    | -12.72 | PK            |
| Horizontal                         | 10360.081 | 49.02         | -9.36          | 39.66       | 54.00    | -14.34 | AV            |
| Horizontal                         | 15540.141 | 64.48         | -7.84          | 56.64       | 74.00    | -17.36 | PK            |
| Horizontal                         | 15540.141 | 50.00         | -7.84          | 42.16       | 54.00    | -11.84 | AV            |
| Middle Channel (5200 MHz)-Above 1G |           |               |                |             |          |        |               |
| Vertical                           | 4592.159  | 71.41         | -20.42         | 51.00       | 74.00    | -23.00 | PK            |
| Vertical                           | 4592.159  | 59.69         | -20.42         | 39.27       | 54.00    | -14.73 | AV            |
| Vertical                           | 10400.021 | 63.79         | -9.30          | 54.49       | 68.20    | -13.71 | PK            |
| Vertical                           | 10400.021 | 49.26         | -9.30          | 39.96       | 54.00    | -14.04 | AV            |
| Vertical                           | 15600.115 | 63.42         | -7.82          | 55.60       | 74.00    | -18.40 | PK            |
| Vertical                           | 15600.115 | 49.09         | -7.82          | 41.27       | 54.00    | -12.73 | AV            |
| Horizontal                         | 4592.024  | 72.56         | -20.42         | 52.14       | 74.00    | -21.86 | PK            |
| Horizontal                         | 4592.024  | 59.07         | -20.42         | 38.66       | 54.00    | -15.34 | AV            |
| Horizontal                         | 10400.010 | 61.79         | -9.30          | 52.49       | 68.20    | -15.71 | PK            |
| Horizontal                         | 10400.010 | 49.97         | -9.30          | 40.67       | 54.00    | -13.33 | AV            |
| Horizontal                         | 15600.146 | 62.00         | -7.82          | 54.18       | 74.00    | -19.82 | PK            |
| Horizontal                         | 15600.146 | 49.17         | -7.82          | 41.35       | 54.00    | -12.65 | AV            |
| High Channel (5240 MHz)-Above 1G   |           |               |                |             |          |        |               |
| Vertical                           | 4739.009  | 70.97         | -20.12         | 50.85       | 74.00    | -23.15 | PK            |
| Vertical                           | 4739.009  | 59.18         | -20.12         | 39.06       | 54.00    | -14.94 | AV            |
| Vertical                           | 10480.101 | 63.31         | -9.18          | 54.13       | 68.20    | -14.07 | PK            |
| Vertical                           | 10480.101 | 49.57         | -9.18          | 40.39       | 54.00    | -13.61 | AV            |
| Vertical                           | 15720.074 | 60.49         | -7.78          | 52.71       | 74.00    | -21.29 | PK            |
| Vertical                           | 15720.074 | 49.96         | -7.78          | 42.18       | 54.00    | -11.82 | AV            |
| Horizontal                         | 4739.131  | 71.30         | -20.12         | 51.18       | 74.00    | -22.82 | PK            |
| Horizontal                         | 4739.131  | 59.92         | -20.12         | 39.80       | 54.00    | -14.20 | AV            |
| Horizontal                         | 10480.053 | 64.70         | -9.18          | 55.52       | 68.20    | -12.68 | PK            |
| Horizontal                         | 10480.053 | 49.10         | -9.18          | 39.92       | 54.00    | -14.08 | AV            |
| Horizontal                         | 15720.110 | 63.96         | -7.78          | 56.18       | 74.00    | -17.82 | PK            |
| Horizontal                         | 15720.110 | 49.77         | -7.78          | 41.99       | 54.00    | -12.01 | AV            |

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

|            |                          |
|------------|--------------------------|
| Test Mode: | TX(5.1G) - 802.11ax-HT40 |
|------------|--------------------------|

| Polar                              | Frequency | Reading Level | Correct Factor | Measurement | Limits   | Over   | Detector Type |
|------------------------------------|-----------|---------------|----------------|-------------|----------|--------|---------------|
| (H/V)                              | (MHz)     | (dBuV/m)      | (dB)           | (dBuV/m)    | (dBuV/m) | (dB)   |               |
| Low Channel (5190 MHz)-Above 1G    |           |               |                |             |          |        |               |
| Vertical                           | 4434.039  | 73.56         | -20.73         | 52.82       | 68.20    | -15.38 | PK            |
| Vertical                           | 4434.039  | 59.14         | -20.73         | 38.41       | 54.00    | -15.59 | AV            |
| Vertical                           | 10380.087 | 64.21         | -9.33          | 54.88       | 68.20    | -13.32 | PK            |
| Vertical                           | 10380.087 | 49.88         | -9.33          | 40.55       | 54.00    | -13.45 | AV            |
| Vertical                           | 15570.117 | 61.87         | -7.83          | 54.04       | 74.00    | -19.96 | PK            |
| Vertical                           | 15570.117 | 49.46         | -7.83          | 41.63       | 54.00    | -12.37 | AV            |
| Horizontal                         | 4434.102  | 71.89         | -20.73         | 51.16       | 74.00    | -22.84 | PK            |
| Horizontal                         | 4434.102  | 59.94         | -20.73         | 39.21       | 54.00    | -14.79 | AV            |
| Horizontal                         | 10380.191 | 62.44         | -9.33          | 53.11       | 68.20    | -15.09 | PK            |
| Horizontal                         | 10380.191 | 49.63         | -9.33          | 40.30       | 54.00    | -13.70 | AV            |
| Horizontal                         | 15570.164 | 62.32         | -7.83          | 54.49       | 74.00    | -19.51 | PK            |
| Horizontal                         | 15570.164 | 49.13         | -7.83          | 41.30       | 54.00    | -12.70 | AV            |
| Middle Channel (5230 MHz)-Above 1G |           |               |                |             |          |        |               |
| Vertical                           | 4739.172  | 74.91         | -20.12         | 54.79       | 68.20    | -13.41 | PK            |
| Vertical                           | 4739.172  | 59.54         | -20.12         | 39.42       | 54.00    | -14.58 | AV            |
| Vertical                           | 10460.153 | 62.45         | -9.21          | 53.24       | 68.20    | -14.96 | PK            |
| Vertical                           | 10460.153 | 49.18         | -9.21          | 39.97       | 54.00    | -14.03 | AV            |
| Vertical                           | 15690.063 | 62.63         | -7.79          | 54.84       | 74.00    | -19.16 | PK            |
| Vertical                           | 15690.063 | 49.73         | -7.79          | 41.94       | 54.00    | -12.06 | AV            |
| Horizontal                         | 4739.178  | 70.16         | -20.12         | 50.04       | 68.20    | -18.16 | PK            |
| Horizontal                         | 4739.178  | 59.48         | -20.12         | 39.36       | 54.00    | -14.64 | AV            |
| Horizontal                         | 10460.024 | 64.67         | -9.21          | 55.46       | 68.20    | -12.74 | PK            |
| Horizontal                         | 10460.024 | 49.27         | -9.21          | 40.06       | 54.00    | -13.94 | AV            |
| Horizontal                         | 15690.016 | 61.76         | -7.79          | 53.97       | 74.00    | -20.03 | PK            |
| Horizontal                         | 15690.016 | 49.21         | -7.79          | 41.42       | 54.00    | -12.58 | AV            |

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

|            |                    |
|------------|--------------------|
| Test Mode: | TX(5.3G) - 802.11a |
|------------|--------------------|

| Polar                              | Frequency | Reading Level | Correct Factor | Measurement | Limits   | Over   | Detector Type |
|------------------------------------|-----------|---------------|----------------|-------------|----------|--------|---------------|
| (H/V)                              | (MHz)     | (dBuV/m)      | (dB)           | (dBuV/m)    | (dBuV/m) | (dB)   |               |
| Low Channel (5260 MHz)-Above 1G    |           |               |                |             |          |        |               |
| Vertical                           | 4434.174  | 73.81         | -20.73         | 53.07       | 68.20    | -15.13 | PK            |
| Vertical                           | 4434.174  | 59.46         | -20.73         | 38.73       | 54.00    | -15.27 | AV            |
| Vertical                           | 10520.028 | 63.41         | -9.12          | 54.29       | 68.20    | -13.91 | PK            |
| Vertical                           | 10520.028 | 49.18         | -9.12          | 40.06       | 54.00    | -13.94 | AV            |
| Vertical                           | 15780.083 | 62.11         | -7.77          | 54.34       | 74.00    | -19.66 | PK            |
| Vertical                           | 15780.083 | 49.98         | -7.77          | 42.21       | 54.00    | -11.79 | AV            |
| Horizontal                         | 4434.053  | 72.88         | -20.73         | 52.15       | 68.20    | -16.05 | PK            |
| Horizontal                         | 4434.053  | 59.71         | -20.73         | 38.98       | 54.00    | -15.02 | AV            |
| Horizontal                         | 10520.151 | 62.73         | -9.12          | 53.61       | 68.20    | -14.59 | PK            |
| Horizontal                         | 10520.151 | 49.36         | -9.12          | 40.24       | 54.00    | -13.76 | AV            |
| Horizontal                         | 15780.143 | 61.41         | -7.77          | 53.64       | 74.00    | -20.36 | PK            |
| Horizontal                         | 15780.143 | 49.41         | -7.77          | 41.64       | 54.00    | -12.36 | AV            |
| Middle Channel (5280 MHz)-Above 1G |           |               |                |             |          |        |               |
| Vertical                           | 4592.157  | 71.65         | -20.42         | 51.23       | 74.00    | -22.77 | PK            |
| Vertical                           | 4592.157  | 59.79         | -20.42         | 39.38       | 54.00    | -14.62 | AV            |
| Vertical                           | 10560.037 | 64.38         | -9.06          | 55.32       | 68.20    | -12.88 | PK            |
| Vertical                           | 10560.037 | 49.90         | -9.06          | 40.84       | 54.00    | -13.16 | AV            |
| Vertical                           | 15840.026 | 63.33         | -7.75          | 55.58       | 74.00    | -18.42 | PK            |
| Vertical                           | 15840.026 | 49.41         | -7.75          | 41.66       | 54.00    | -12.34 | AV            |
| Horizontal                         | 4592.165  | 73.69         | -20.42         | 53.28       | 74.00    | -20.72 | PK            |
| Horizontal                         | 4592.165  | 59.71         | -20.42         | 39.30       | 54.00    | -14.70 | AV            |
| Horizontal                         | 10560.053 | 64.30         | -9.06          | 55.24       | 68.20    | -12.96 | PK            |
| Horizontal                         | 10560.053 | 49.83         | -9.06          | 40.77       | 54.00    | -13.23 | AV            |
| Horizontal                         | 15840.164 | 64.69         | -7.75          | 56.94       | 74.00    | -17.06 | PK            |
| Horizontal                         | 15840.164 | 49.70         | -7.75          | 41.95       | 54.00    | -12.05 | AV            |
| High Channel (5320 MHz)-Above 1G   |           |               |                |             |          |        |               |
| Vertical                           | 4739.178  | 70.01         | -20.12         | 49.89       | 74.00    | -24.11 | PK            |
| Vertical                           | 4739.178  | 59.60         | -20.12         | 39.48       | 54.00    | -14.52 | AV            |
| Vertical                           | 10640.141 | 63.12         | -8.94          | 54.18       | 68.20    | -14.02 | PK            |
| Vertical                           | 10640.141 | 49.23         | -8.94          | 40.29       | 54.00    | -13.71 | AV            |
| Vertical                           | 15960.197 | 63.79         | -7.71          | 56.08       | 74.00    | -17.92 | PK            |
| Vertical                           | 15960.197 | 49.90         | -7.71          | 42.19       | 54.00    | -11.81 | AV            |
| Horizontal                         | 4739.110  | 74.94         | -20.12         | 54.82       | 74.00    | -19.18 | PK            |
| Horizontal                         | 4739.110  | 59.32         | -20.12         | 39.20       | 54.00    | -14.80 | AV            |
| Horizontal                         | 10640.067 | 63.52         | -8.94          | 54.58       | 68.20    | -13.62 | PK            |
| Horizontal                         | 10640.067 | 49.37         | -8.94          | 40.43       | 54.00    | -13.57 | AV            |
| Horizontal                         | 15960.139 | 64.61         | -7.71          | 56.90       | 74.00    | -17.10 | PK            |
| Horizontal                         | 15960.139 | 49.60         | -7.71          | 41.89       | 54.00    | -12.11 | AV            |

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

|            |                         |
|------------|-------------------------|
| Test Mode: | TX(5.3G) - 802.11n-HT20 |
|------------|-------------------------|

| Polar                              | Frequency | Reading Level | Correct Factor | Measurement | Limits   | Over   | Detector Type |
|------------------------------------|-----------|---------------|----------------|-------------|----------|--------|---------------|
| (H/V)                              | (MHz)     | (dBuV/m)      | (dB)           | (dBuV/m)    | (dBuV/m) | (dB)   |               |
| Low Channel (5260 MHz)-Above 1G    |           |               |                |             |          |        |               |
| Vertical                           | 4434.132  | 70.91         | -20.73         | 50.18       | 68.20    | -18.02 | PK            |
| Vertical                           | 4434.132  | 59.28         | -20.73         | 38.55       | 54.00    | -15.45 | AV            |
| Vertical                           | 10520.093 | 64.92         | -9.12          | 55.80       | 68.20    | -12.40 | PK            |
| Vertical                           | 10520.093 | 49.77         | -9.12          | 40.65       | 54.00    | -13.35 | AV            |
| Vertical                           | 15780.062 | 63.33         | -7.77          | 55.56       | 74.00    | -18.44 | PK            |
| Vertical                           | 15780.062 | 49.72         | -7.77          | 41.95       | 54.00    | -12.05 | AV            |
| Horizontal                         | 4434.184  | 72.14         | -20.73         | 51.41       | 68.20    | -16.79 | PK            |
| Horizontal                         | 4434.184  | 59.04         | -20.73         | 38.31       | 54.00    | -15.69 | AV            |
| Horizontal                         | 10520.036 | 61.28         | -9.12          | 52.16       | 68.20    | -16.04 | PK            |
| Horizontal                         | 10520.036 | 49.39         | -9.12          | 40.27       | 54.00    | -13.73 | AV            |
| Horizontal                         | 15780.186 | 62.95         | -7.77          | 55.18       | 74.00    | -18.82 | PK            |
| Horizontal                         | 15780.186 | 49.02         | -7.77          | 41.25       | 54.00    | -12.75 | AV            |
| Middle Channel (5280 MHz)-Above 1G |           |               |                |             |          |        |               |
| Vertical                           | 4592.034  | 71.81         | -20.42         | 51.39       | 74.00    | -22.61 | PK            |
| Vertical                           | 4592.034  | 59.38         | -20.42         | 38.97       | 54.00    | -15.03 | AV            |
| Vertical                           | 10560.189 | 64.23         | -9.06          | 55.17       | 68.20    | -13.03 | PK            |
| Vertical                           | 10560.189 | 49.43         | -9.06          | 40.37       | 54.00    | -13.63 | AV            |
| Vertical                           | 15840.120 | 60.05         | -7.75          | 52.30       | 74.00    | -21.70 | PK            |
| Vertical                           | 15840.120 | 49.38         | -7.75          | 41.63       | 54.00    | -12.37 | AV            |
| Horizontal                         | 4592.132  | 74.92         | -20.42         | 54.50       | 74.00    | -19.50 | PK            |
| Horizontal                         | 4592.132  | 59.85         | -20.42         | 39.43       | 54.00    | -14.57 | AV            |
| Horizontal                         | 10560.141 | 62.86         | -9.06          | 53.80       | 68.20    | -14.40 | PK            |
| Horizontal                         | 10560.141 | 49.52         | -9.06          | 40.46       | 54.00    | -13.54 | AV            |
| Horizontal                         | 15840.176 | 64.50         | -7.75          | 56.75       | 74.00    | -17.25 | PK            |
| Horizontal                         | 15840.176 | 49.06         | -7.75          | 41.31       | 54.00    | -12.69 | AV            |
| High Channel (5320 MHz)-Above 1G   |           |               |                |             |          |        |               |
| Vertical                           | 4739.058  | 74.90         | -20.12         | 54.78       | 74.00    | -19.22 | PK            |
| Vertical                           | 4739.058  | 59.76         | -20.12         | 39.64       | 54.00    | -14.36 | AV            |
| Vertical                           | 10640.101 | 64.95         | -8.94          | 56.01       | 68.20    | -12.19 | PK            |
| Vertical                           | 10640.101 | 49.90         | -8.94          | 40.96       | 54.00    | -13.04 | AV            |
| Vertical                           | 15960.126 | 63.57         | -7.71          | 55.86       | 74.00    | -18.14 | PK            |
| Vertical                           | 15960.126 | 49.08         | -7.71          | 41.37       | 54.00    | -12.63 | AV            |
| Horizontal                         | 4739.183  | 71.43         | -20.12         | 51.31       | 74.00    | -22.69 | PK            |
| Horizontal                         | 4739.183  | 59.13         | -20.12         | 39.01       | 54.00    | -14.99 | AV            |
| Horizontal                         | 10640.053 | 63.53         | -8.94          | 54.59       | 68.20    | -13.61 | PK            |
| Horizontal                         | 10640.053 | 49.75         | -8.94          | 40.81       | 54.00    | -13.19 | AV            |
| Horizontal                         | 15960.133 | 64.40         | -7.71          | 56.69       | 74.00    | -17.31 | PK            |
| Horizontal                         | 15960.133 | 49.85         | -7.71          | 42.14       | 54.00    | -11.86 | AV            |

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.