

Datasheet of PCBC Device

Printed Circuit Board with Ceramic Antenna

2400-2500 MHz

P/N: YSM3Y10

Shenzhen Yongxin Communication Technology Co., Ltd.

507, Kangheshan Building, Shahe West Road, Shuguang Community,
Xili Street, Nanshan District, Shenzhen

*Contents in this sheet are subject to change without prior notice.

PCBC Antenna 3216 Size

1. Features


Antenna Frequency for 2400-2500 MHz

2. Applications

For Miniaturized Bluetooth System


3. Shapes & Dimensions(Unit : mm)


1). Component (Unit : mm):




Symbols	L	W	T	A
Dimensions	3.2+/-0.2	1.6+/-0.2	1.0+/-0.1	0.4+/-0.1

2). PCB Top View (Unit : mm) :






4. Evaluation Board and Matching Circuits




5. Electrical Characteristics

Part Number	YSM3Y10	
Central Frequency	2450	MHz
Bandwidth	±50 (Min.)	MHz
Return Loss	-10 (Max)	dB
Peak Gain	3.12	dBi
Impedance	50	Ohm
Polarization	Linear	
Azimuth Beamwidth	Omni-directional	

6. Return Loss




7. Radiation Pattern & Efficiency




Frequency (MHz)	2400	2450	2500
Efficiency (dB)	-2.01	-1.43	-1.74
Efficiency (%)	63	72	67
Gain (dBi)	3.01	3.12	2.73

8. Reflow Soldering Standard Condition



9. Packaging and Dimensions 3216 (3.2*1.6mm)

◆ Plastic Tape




W	Ao	Bo	Ko	P	F	E	D0	D1	Po	P2	t
8.0	1.85	3.51	1.59	4.00	3.50	1.75	1.50	0.00	4.00	2.00	0.25
±0.30	±0.05	±0.10	±0.10	±0.05	±0.05	±0.10	±0.10	±0.10	±0.10	±0.05	±0.05

◆ Remarks for Package

Reserve a length of 150~200mm for the trailer of the carrier and 250~300 mm for the leader of the carrier and further 250mm of cover tape at the leading part of the carrier.

◆ Reel (3000 pcs/Reel)



Tape Width(mm)	A(mm)	B(mm)	C(mm)	D(mm)	Chip/Reel(pcs)
8	9.0±0.5	60±2	13.5±0.5	178±2	3000

◆ Storage Period

Oxidizable Material, 12 months in vacuum sealed bag, please repack within 168 hours by re-seal the package treatment after using.

Storage Temperature Range : <30 degree C, Humidity : <60%RH

10. Dependability Test

Test item	Test condition / Test method	Specification
Solderability IEC 60068-2-58 GB/T2423.28	*Solder bath temperature: $240\pm5^{\circ}\text{C}$ *Immersion time: 2 ± 0.5 sec Solder: Sn96.5Ag3.0Gu0.5 for lead-free.	At least 95% of a surface of each terminal electrode must be covered by fresh solder.
Leaching (Resistance to dissolution of metallization) JIS C5101	*Solder bath temperature: $260\pm5^{\circ}\text{C}$ *Leaching immersion time: 10 ± 1 sec Solder : Sn96.5 Ag3.0 Gu0.5 for lead-free.	Loss of metallization on the edges of each electrode shall not exceed 25%.
Resistance to soldering heat IEC 60068-2-58 GB/T2423.28	*Preheating temperature: $120\sim150^{\circ}\text{C}$, 1 minute. *Solder temperature: $260\pm5^{\circ}\text{C}$ *Immersion time: 10 ± 1 sec Solder: Sn96.5Ag3.0Gu0.5 for lead-free Measurement to be made after keeping at room temperature for 24 ± 2 hrs.	No mechanical damage. Electrical specification shall satisfy the descriptions in electrical characteristics at the room temperature. Loss of metallization on the edges of each electrode shall not exceed 25%.
Drop Test IEC 60068-2-32 GB/T2423.8 Customer's specification.	*Height : 50 cm *Test Surface: Rigid surface of concrete or steel. *Times : 6 surfaces for each units ; 2 times for each side.	No mechanical damage. Electrical specification shall satisfy the descriptions in electrical characteristics at the room temperature.
Vibration IEC 60068-2-6 GB/T 2423.10	*Frequency : 10Hz~55Hz~10Hz(1min) *Total amplitude : 1.5mm *Test times: 6hrs.(Two hrs each in three mutually perpendicular directions)	No mechanical damage. Electrical specification shall satisfy the descriptions in electrical characteristics at the room temperature.

Adhesive Strength of Termination IEC60068-2-21 GB/T 2423.6	*Pressurizing force : 5N(≤ 0603) ; 10N(>0603) *Test time:10 \pm 1 sec	No remarkable damage or removal of the termination.
Bending test IEC 60068-2-21 GB/T 2423.29	The middle part of substrate shall be pressurized by means of the pressurizing rod at a rate of about 1 mm/s per second until the deflection becomes 2mm and then pressure shall be maintained for 10 \pm 1 sec. Measurement to be made after keeping at room temperature for 24 \pm 2 hours.	No mechanical damage. Electrical specification shall satisfy the descriptions in electrical characteristics at the room temperature.
Temperature cycle IEC60068-2-14 GB/T 2423.22	30 minutes at -40 \pm 2 $^{\circ}$ C. 10~15 minutes at room temperature. 30minutes at +85 \pm 2 $^{\circ}$ C. 10~15 minutes at room temperature. Total 100 continuous cycles Measurement to be made after keeping at room temperature for 24 \pm 2 hrs.	No mechanical damage. Electrical specification shall satisfy the descriptions in electrical characteristics at the room temperature.
High temperature IEC 60068-2-2 GB/T2423.2	*Temperature: 85 \pm 2 $^{\circ}$ C. *Test duration: 500+24/-0 hours. Measurement to be made after keeping at room temperature for 24 \pm 2 hrs.	No mechanical damage. Electrical specification shall satisfy the descriptions in electrical characteristics.
Humidity (steady conditions) IEC60068-2-3 GB/T 2423.3	*Humidity : 85 \pm 5%R.H. *Temperature: 85 \pm 2 $^{\circ}$ C. *Time : 500+24/-0 hrs. Measurement to be made after keeping at room temperature for 24 \pm 2 hrs ※ 200hrs measuring the first data then 300hrs data.	No mechanical damage. Electrical specification shall satisfy the descriptions in electrical characteristics at the room temperature.
Low temperature IEC 60068-2-1 GB/T2423.1	*Temperature: -40 \pm 2 $^{\circ}$ C. *Test duration: 500+24/-0 hours Measurement to be made after keeping at room temperature for 24 \pm 2 hrs.	No mechanical damage. Electrical specification shall satisfy the descriptions in electrical characteristics at the room temperature.