

RF Exposure Evaluation Report

Product : RingConn Gen 2 Smart Ring
Trade mark : RingConn
Model/Type reference : See section 3.2
Serial Number : N/A
Report Number : EED32R80466501
FCC ID : 2BONNJZRCA-01
Date of Issue : May 09, 2025
Test Standards : 47 CFR Part 1.1307
47 CFR Part 1.1310
47 CFR Part 2.1091
47 CFR Part 2.1093
KDB 447498 D04 Interim General RF
Exposure Guidance v01
Test result : PASS

Prepared for:

Guangdong Jiu Zhi Technology Co., Ltd.
Rm 3, 14F, Bldg 2, chongwen Park, Nanshan, Shenzhen, China

Prepared by:

Centre Testing International Group Co., Ltd.
Hongwei Industrial Zone, Bao'an 70 District,
Shenzhen, Guangdong, China
TEL: +86-755-3368 3668
FAX: +86-755-3368 3385

Compiled by:

Keven Tan.

Reviewed by:

Frazer Li

Keven Tan

Frazer Li

Approved by:

Aaron Ma

Date:

May 09, 2025

Aaron Ma

Check No.:2652020425



1 Version

Version No.	Date	Description
00	May 09, 2025	Original

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION	4
3.2 GENERAL DESCRIPTION OF EUT	4
3.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	4
3.4 TEST LOCATION	6
3.5 DEVIATION FROM STANDARDS	6
3.6 ABNORMALITIES FROM STANDARD CONDITIONS	6
3.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER	6
4 SAR EVALUATION	7
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT	7
4.1.1 Limits	7
4.1.2 Test Procedure	7
4.1.3 EUT RF Exposure Evaluation	8

3 General Information

3.1 Client Information

Applicant:	Guangdong Jiu Zhi Technology Co., Ltd.
Address of Applicant:	Rm 3, 14F, Bldg 2, chongwen Park, Nanshan, Shenzhen, China
Manufacturer:	Guangdong Jiu Zhi Technology Co., Ltd.
Address of Manufacturer:	Rm 3, 14F, Bldg 2, chongwen Park, Nanshan, Shenzhen, China
Factory:	Guangdong Jiu Zhi Technology Co., Ltd.
Address of Factory:	Rm 3, 14F, Bldg 2, chongwen Park, Nanshan, Shenzhen, China

3.2 General Description of EUT

Product Name:	RingConn Gen 2 Smart Ring
Model No.:	RCA-01, RCA-01-6、RCA-01-7、RCA-01-8、RCA-01-9、RCA-01-10、RCA-01-11、RCA-01-12、RCA-01-13、RCA-01-14
Test Model No.:	RCA-01
Trade mark:	RingConn

3.3 Product Specification subjective to this standard

Frequency Range:	2402MHz~2480MHz	
Modulation Type:	GFSK	
Test Power Grade:	Default	
Test Software of EUT:	sscom5.13.1.exe	
Antenna Type:	Ceramic Antenna	
Antenna Gain:	2.5dBi	
Power Supply:	Battery:	DC 3.85V
Sample Received Date:	Apr. 11, 2025	
Sample tested Date:	Apr. 11, 2025 to Apr. 21, 2025	

Remark:

Model No.: RCA-01, RCA-01-6、RCA-01-7、RCA-01-8、RCA-01-9、RCA-01-10、RCA-01-11、RCA-01-12、RCA-01-13、RCA-01-14

Only the model RCA-01 was tested, The PCB of different models are consistent, only the shell size is different, The differences between different models are shown in the table below:

Model	inner diameter	Smart Ring colour
RCA-01	19.0×7.8mm	Shiny Silver; Matte Black; Rose Gold; Shiny Gold.
RCA-01-6	16.5×7.8mm	Shiny Silver; Matte Black; Rose Gold; Shiny Gold.
RCA-01-7	17.4×7.8mm	Shiny Silver; Matte Black; Rose Gold; Shiny Gold.
RCA-01-8	18.2×7.8mm	Shiny Silver; Matte Black; Rose Gold; Shiny Gold.
RCA-01-9	19.0×7.8mm	Shiny Silver; Matte Black; Rose Gold; Shiny Gold.
RCA-01-10	19.9×7.8mm	Shiny Silver; Matte Black; Rose Gold; Shiny Gold.
RCA-01-11	20.7×7.8mm	Shiny Silver; Matte Black; Rose Gold; Shiny Gold.
RCA-01-12	21.5×7.8mm	Shiny Silver; Matte Black; Rose Gold; Shiny Gold.
RCA-01-13	22.3×7.8mm	Shiny Silver; Matte Black; Rose Gold; Shiny Gold.
RCA-01-14	23.1×7.8mm	Shiny Silver; Matte Black; Rose Gold; Shiny Gold.

3.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

3.5 Deviation from Standards

None.

3.6 Abnormalities from Standard Conditions

None.

3.7 Other Information Requested by the Customer

None.

4 SAR Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Limits

The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold P_{th} (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by Formula

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B.1).

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

The 1 mW Blanket Exemption of § 1.1307(b)(3)(i)(A) applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power of no more than 1 mW, regardless of separation distance.

4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.1.3 EUT RF Exposure Evaluation

For Stand alone:

Frequency (MHz)	Estimation distance (cm)	Max. Conducted Output power (dBm)	Antenna Gain (dBi)	ERP (dBm)	ERP (mW)	Limit (mW)	MPE ratio	Result
2480	0.5	-4.11	2.50	-3.76	0.4207	2.7172	0.1548	Pass

Note:

① EIRP=conducted power+antenna gain;

② ERP=EIRP-2.15;

③ EIRP(dBm) = Field strength of the fundamental signal(dBuV/m@3m) – 95.23;

④ ERP(mW) = $10^{(ERP \text{ (dBm)}/10)}$;

⑤ The estimation distance is 0.5cm;

⑥ The test data please refer to the report of EED32R80466501 and only the worst case data was recorded in the report.

Statement

1. This report is considered invalid without approved signature, special seal and the seal on the perforation;
2. The Company Name shown on Report and Address, the sample(s) and sample information was/were provided by the applicant who should be responsible for the authenticity which CTI hasn't verified;
3. The result(s) shown in this report refer(s) only to the sample(s) tested;
4. Unless otherwise stated, the decision rule for conformity reporting is based on Binary Statement for Simple Acceptance Rule stated in ILAC-G8:09/2019/CNAS-GL015:2022;
5. Without written approval of CTI, this report can't be reproduced except in full;

*** End of Report ***