

Report No: FCS202504530H01

Issued for

Applicant:	Shenzhen Utour Innov Tech Co., Ltd.				
Address:	Room 303, Unit 1, No. 3000054 Xinhu Road, Niuhu Community, Guanlan Street, Longhua District, Shenzhen City				
Product Name:	Al Streaming Rearview Mirror				
Brand Name:	N/A				
Model Name:	Т600				
Series Model:	T600S, C3, C3 Pro, C3M, C3M Pro				
FCC ID:	2BPII-T600				
Test Standard:	FCC 47CFR §2.1091				
Issued By: Flux Compliance Service Laboratory					

Add: Room 105 Floor Bao hao Technology Building 1 NO.15 Gong ye West Road Hi-Tech

Industrial, Song shan lake Dongguan

Tel: 769-27280901 Fax:769-27280901 http://www.FCS-lab.com



Report No.: FCS202504530H01



TEST RESULT CERTIFICATION						
Applicant's Name:	Shenzhen Utour Innov Tech Co., Ltd.					
Address:	Room 303, Unit 1, No. 3000054 Xinhu Road, Niuhu Community, Guanlan Street, Longhua District, Shenzhen City					
Manufacture's Name:	Shenzhen Utour Innov Tech Co., Ltd.					
Address:	Room 303, Unit 1, No. 3000054 Xinhu Road, Niuhu Community, Guanlan Street, Longhua District, Shenzhen City					
Product Description						
Product Name:	Al Streaming Rearview Mirror					
Brand Name:	N/A					
Model Name:	T600					
Series Model:	T600S, C3, C3 Pro, C3M, C3M Pro					
Test Standards:	FCC 47CFR §2.1091 447498 D01 Interim General RF Exposure Guidance v06					
show that the equipment under te applicable only to the tested samp This report shall not be reproduce	ed except in full, without the written approval of Flux Compliance tmay be altered or revised by Flux Compliance Service Laboratory,					
Date (s) of performance of tests.:	April 21, 2025 ~ April 25, 2025					
Date of Issue:	April 25, 2025					
Test Result:	Pass					
Tested by	: Scott shen					
	(Scott Shen)					
Reviewed by	: Dute Our					
	(Duke Qian)					
	MUTUSHOO!					

Approved by

(Jack Wang)





TABLE OF CONTENTS

Report No.: FCS202504530H01

1. GENERAL INFORMATION	5
1.1 GENERAL DESCRIPTION OF THE EUT	5
1.2 TEST FACTORY	6
2. FCC 47CFR § 2.1091 REQUIREMENT	7
2.1 TEST STANDARDS	7
2.2 LIMIT	7
2.3 TEST RESULT	9





Revision History

Rev.	Issue Date	Contents
00	April 25, 2025	Initial Issue



1. GENERAL INFORMATION

1.1 GENERAL DESCRIPTION OF THE EUT

Product Name	Al Streaming Rearview Mirror			
Brand	N/A			
Model Number	T600			
Series Model(s)	T600S, C3, C3 Pro, C3M, C3M Pro			
Model Difference	Only different of model name.			
Product Description	Operation Frequency: 2.4G WiFi: Modulation Type: 802.11b/g/n20: 2412~2462 MHz 2.4G WiFi: 802.11b(DSSS): CCK,DQPSK,DBPSK 802.11g(OFDM): BPSK,QPSK,16-QAM,64-Q 802.11n(OFDM): BPSK,QPSK,16-QAM,64-Q Antenna gain: 2.7 dBi Antenna Designation: PIFA antenna			
Power Supply	DC 5V/2.4A			
Hardware version number	V1.0			
Software version number	V1.0			





1.2 TEST FACTORY

Company Name:	Flux Compliance Service Laboratory
Address:	Room 105 Floor Bao hao Technology Building 1 NO.15 Gong ye West Road Hi-Tech Industrial, Song shan lake Dongguan
Telephone:	+86-769-27280901
Fax:	+86-769-27280901

FCC Test Firm Registration Number: 514908

Designation number: CN0127

A2LA accreditation number: 5545.01

ISED Number: 25801 CAB ID: CN0097



2. FCC 47CFR §2.1091 REQUIREMENT

2.1 TEST STANDARDS

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure requirement

KDB447498 D01v06: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies

The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The gain of the antennas used in the product is extracted from the Antenna data sheets provided and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis Transmission formula is far field assumption, the calculated result of that is an over-prediction for near field power density. It is taken as worst case to specify the safety range.

2.2 LIMIT

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of the human exposure to radio-frequency (RF) radiation as specified in 1.1307 (b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range	Electric Field	Magnetic Field	Power Density			
(MHz)	Strength (V/m)	Strength (A/m)	(mW/cm²)			
Limits for Occupational	/ controlled Exposures					
300 - 1500			F/300			
1500 – 100000			5.0			
Limits for General population / Uncontrolled Exposure						
300 - 1500			F/1500			
1500 - 100000			1.0			

F= Frequency in MHz





Friss Formula

Friss Transmission Formula: $Pd = (Pout * G) / (4*pi*r^2)$

Where

Pd = power density in mW/cm² aaa

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = Distance between observation point and the center of radiator in cm

If we know the maximum gain of the antenna and the total output power to the antenna, through calculation, we will know MPE value at distance 20cm.

Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. Warning statement to the user for keeping at least 20cm or more separation distance from the antenna should be included in the User manual. So, this device is classified as Mobile device.



2.3 TEST RESULT

Turn up

2.4G WiFi_Conducted	Mode	Frequency(MHz)		
Target (dBm)	Apt 1 902 11b	2412	2437	2462
	Ant 1_802.11b	13	13	13
	Ant 1_802.11g	2412	2437	2462
		17	17	17
	A = 1.4. 000 44 = /UT00)	2412	2437	2462
	Ant 1_802.11n(HT20)	17	17	17
Tolerance ± (dB)			1	

Modulation Type	Output power		Antenna Gain	Antenna Gain	MPE	MPE Limits
	dBm	mW	(dBi)	(linear)	(mW/cm2)	(mW/cm2)
2.4G WLAN	18	63.10	2.7	1.862	0.02337	1

Results: PASS, NO SAR required.

* * * * * END OF THE REPORT * * * *