



Shenzhen Shuodian Electronic Technology Co.,Ltd
Page number 1-10

SPECIFICATION

for

2.4G-380B-SMA 2.4G rubber rod antenna

Customer No.

Product No.

SD-2.4G-380B-SMA 2.4G glue rod antenna-70MM

Author: XiaofengZeng Review: Liming

Release Date: 2025.3.1

ShenZhen Shuodian Electronic Technology Co., Ltd

Room 201, Building 2, Nantaiyun Chuanggu Park, Tangwei Community, Fenghuang Street,
Guangming District, Shenzhen City, Guangdong Province

E-mail: sz_shuodian@163.com

Tel: 0755-86006322

Fax: 0755-86006323

Shenzhen Shuodian Electronic Technology Co.,Ltd



Contents

SPECIFICATION	1
SHENZHEN SHUODIAN ELECTRONIC TECHNOLOGY CO., LTD	1
CONTENTS	2
1. BILATERAL CONFIRMATION PAGE	3
2. GENERAL	4
3. GENERAL PRODUCT SPECIFICATIONS	4
4. SPECIFICATION DETIALS	5
4.1 MECHANICAL PROPERTIES	5
4.2 ELECTRIC PERFORMANCE	7
5. PRODUCT PACKAGING	10
6. DOCUMENT RESUME	10



1. Bilateral Confirmation page

1.1 Customer signature

Customer:

Seapartment/post	Sign	Date
Hardware Engineer/RD		
Mechanical/MD		
Project Manager/PM		
Commercial/Puchasing		
Checker		

1.2 Signature of ShuoDian Technology company

Seapartment/post	Sign	Date
Antenna Engineer/RD		
Mechanical/MD		
Project Manager/PM		
QA		
Checker		



2. General

2.1 Scope of application

This specification is only applicable to 2.4G-380B-SMA 2.4G rubber rod antenna

2.2 Operating temperature range

Temperature range of this product: -20 ~ +65 °C

2.3 Storage temperature range:

This product is stored at - 30 ~ + 75 °C

3. General product specifications

NO.	ITEMS	DETAILS
1	Type	2.4G-380B-SMA 2.4G rubber rod antenna
2	Operating Frequency Band	2400-2500MHz
3	VSWR	≤ 2.0
4	Impedance	50Ω
5	Antenna Type	External antenna
6	Antenna composition	Glue rod antenna
7	Entity Picture	



4. Specification Detials

4.1 Mechanical Properties

4.11 Product Composition:

4.12 Apperance

Good appearance without scars 、 dirt、 protuberances, etc.

4.13 Antenna Picture and Structure Dimension

Productdrawings:



Page number 6-10

Shenzhen Shuodian Electronic Technology Co.,Ltd



4.2 Electric Performance

4.21 Test condition



Environment:	Equipment:
Temperature: 10℃——+30℃	Network Analyzer: KEYSIGHT E5071C
Humidity: ≤80% (+40℃)	Multi-probe microwave anechoic
Atmospher: 750mmkg±30mmkg	chamber

4.22 Test Data for Electrical Performance:

4.22.1 S11 of the Antenna:

Marker (MHZ)	2400	2450	2500
Returnloss	-11.6	-23.7	-15.4
VSWR	1.7	1.1	1.4








4. 22. 2 Passive gain、 efficiency and Radiation Pattern:

Frequency (MHz)	2400	2410	2420	2430	2440	2450	2460	2470	2480	2490	2500
Gain (dBi)	0.42	0.79	1.12	1.52	1.88	2.00	1.96	2.03	2.29	2.35	2.19
Efficient (%)	56.01	58.88	61.59	63.38	65.58	67.99	69.07	72.04	70.91	70.95	71.00

Radiation Pattern 2450MHz

@2450MHz





5. Product Packaging

Manner of packing:

Packed in self sealed bags, 100 pcs each.

6. Document Resume

Document No.	
Release Date	2025/3/1
Author	XiofengZeng
Review	LiMing

Revised History

Date	Version	Revised Record
2025/3/1	1.00	New Project