



Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

RF Exposure evaluation

Report Reference No.....: CTA25070900204

FCC ID.....: 2BQZB-G1688-08

Compiled by

(position+printed name+signature) : File administrators Zoey Cao

Supervised by

(position+printed name+signature) : Project Engineer Ace Chai

Approved by

(position+printed name+signature) : RF Manager Eric Wang

Date of issue: Jul. 25, 2025

Testing Laboratory Name.....: Shenzhen CTA Testing Technology Co., Ltd.

Address.....: Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

Applicant's name.....: Shenzhen GPD Technology Co., Ltd.

Address.....: 1006, Block 4D, Software Industry Base, High-Tech Industrial Park, Shenzhen, 518000, China

Standard.....: 47CFR §1.1310

47CFR §2.1093

KDB447498 D01 General RF Exposure Guidance v06

Shenzhen CTA Testing Technology Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTA Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTA Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description: Mini Computer

Trade Mark: N/A

Manufacturer: Shenzhen GPD Technology Co., Ltd.

Model/Type reference: G1688-08

Listed Models: N/A

Ratings: Input: 20V $\overline{\text{---}}$ 2.25A

Battery: 7.7V 3580mAh 27.57Wh

Result: PASS

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

Tel:+86-755 2322 5875 E-mail:cta@cta-test.cn Web:http://www.cta-test.cn

TEST REPORT

Equipment under Test : Mini Computer

Model /Type : G1688-08

Listed Models : N/A

Applicant : **Shenzhen GPD Technology Co., Ltd.**

Address : 1006, Block 4D, Software Industry Base, High-Tech Industrial Park,
Shenzhen, 518000, China

Manufacturer : **Shenzhen GPD Technology Co., Ltd.**

Address : 1006, Block 4D, Software Industry Base, High-Tech Industrial Park,
Shenzhen, 518000, China

Test Result:	PASS
---------------------	-------------

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of
the test laboratory.

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China
Tel:+86-755 2322 5875 E-mail:cta@cta-test.cn Web:http://www.cta-test.cn

Contents

1	TEST STANDARDS	4
2	SUMMARY	5
2.1	General Remarks	5
2.2	Product Description	5
2.3	Special Accessories	6
2.4	Modifications	6
3	TEST ENVIRONMENT	7
3.1	Address of the test laboratory	7
3.2	Test Facility	7
3.3	Statement of the measurement uncertainty	7
4	Test limit	8
4.1	Requirement	8
4.2	Conducted Power Results	8
4.3	Manufacturing tolerance	11
4.4	Evaluation Result	11
4.5	Simultaneous Transmission for SAR Exclusion	12
5	Conclusion	12

1 TEST STANDARDS

The tests were performed according to following standards:

[ANSI C95.1-1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[FCC KDB 447498 D01 General RF Exposure Guidance v06](#): Mobile and Portable Device, RF Exposure, Equipment Authorization Procedures.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1093](#): Radiofrequency radiation exposure evaluation: portable devices

2 SUMMARY

2.1 General Remarks

Date of receipt of test sample	:	Jul. 09, 2025
Testing commenced on	:	Jul. 09, 2025
Testing concluded on	:	Jul. 25, 2025

2.2 Product Description

Product Name:	Mini Computer			
Model/Type reference:	G1688-08			
Power supply:	Input: 20V $\equiv$ 2.25A Battery: 7.7V 3580mAh 27.57Wh			
Hardware version:	V1.0			
Software version:	V1.0			
Testing sample ID:	CTA250709002-1# (Engineer sample) CTA250709002-2# (Normal sample)			
Bluetooth :				
Supported Type:	Bluetooth BR/EDR			
Modulation:	GFSK, π /4DQPSK, 8DPSK			
Operation frequency:	2402MHz~2480MHz			
Channel number:	79			
Channel separation:	1MHz			
Antenna type:	PIFA Antenna			
Antenna gain:	-1.06 dBi			
2.4GWIFI :				
Supported type:	802.11b/802.11g/802.11n/ax(H20)/ 802.11n/ax(H40)			
Modulation:	802.11b: DSSS 802.11g/802.11n(H20)/ 802.11n(H40): OFDM 802.11ax(H20)/ 802.11ax(H40): OFDMA			
Operation frequency:	802.11b/802.11g/802.11n/ax(H20): 2412MHz~2462MHz 802.11n/ax(H40): 2422MHz~2452MHz			
Channel number:	802.11b/802.11g/802.11n/ax(H20): 11 802.11n/ax(H40):7			
Channel separation:	5MHz			
Antenna type:	PIFA antenna			
Antenna gain:	ANT1: -1.06 dBi ANT2: 2.66 dBi			
5GWIFI				
Supported type:	20MHz system	40MHz system	80MHz system	160MHz system

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

Tel:+86-755 2322 5875 E-mail:cta@cta-test.cn Web:http://www.cta-test.cn

	802.11a 802.11n 802.11ac 802.11ax	802.11n 802.11ac 802.11ax	802.11ac 802.11ax	N/A
Operation frequency:	5180MHz-5240MHz 5745MHz-5825MHz	5190MHz-5230MHz 5755MHz-5795MHz	5210MHz 5775MHz	N/A
Modulation:	OFDM OFDMA	OFDM OFDMA	OFDM OFDMA	N/A
Channel number:	9	4	2	N/A
Channel separation:	20MHz	40MHz	80MHz	N/A
Antenna type:	PIFA Antenna			
Antenna gain:	ANT1: 2.61 dBi for 5180-5240MHz, -2.23 dBi for 5745-5825MHz ANT2: 0.80 dBi for 5180-5240MHz, 0.84 dBi for 5745-5825MHz			

2.3 Special Accessories

The following is the EUT test of the auxiliary equipment provided by the laboratory:

Description	Manufacturer	Model	Technical Parameters	Certificate	Provided by
Adapter	/	/	Input: AC 100-240V 50/60Hz Output: DC 20V 2.25A	/	/

2.4 Modifications

No modifications were implemented to meet testing criteria.

3 TEST ENVIRONMENT

3.1 Address of the test laboratory

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community,
Fuhai Street, Bao'an District, Shenzhen, China

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 517856 Designation Number: CN1318

Shenzhen CTA Testing Technology Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

A2LA-Lab Cert. No.: 6534.01

Shenzhen CTA Testing Technology Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.10 and CISPR 16-1-4:2010.

3.3 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 2" and is documented in the Shenzhen CTA Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen CTA Testing Technology Co., Ltd. :

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	9KHz~30MHz	3.02 dB	(1)
Radiated Emission	30~1000MHz	4.06 dB	(1)
Radiated Emission	1~18GHz	5.14 dB	(1)
Radiated Emission	18-40GHz	5.38 dB	(1)
Conducted Disturbance	0.15~30MHz	2.14 dB	(1)
Output Peak power	30MHz~18GHz	0.55 dB	(1)
Power spectral density	/	0.57 dB	(1)
Spectrum bandwidth	/	1.1%	(1)
Radiated spurious emission (30MHz-1GHz)	30~1000MHz	4.10 dB	(1)
Radiated spurious emission (1GHz-18GHz)	1~18GHz	4.32 dB	(1)
Radiated spurious emission (18GHz-40GHz)	18-40GHz	5.54 dB	(1)
Time	/	± 2%	(1)

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

Tel:+86-755 2322 5875 E-mail:cta@cta-test.cn Web:http://www.cta-test.cn

4 Test limit

4.1 Requirement

According to KDB447498 D01 General RF Exposure Guidance v06 Section 4.3.1 Standalone SAR test exclusion considerations: “Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition, listed below, is satisfied. These test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.²² The minimum test separation distance is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander (see 5) of section 4.1). To qualify for SAR test exclusion, the test separation distances applied must be fully explained and justified by the operating configurations and exposure conditions of the transmitter and applicable host platform requirements, typically in the SAR measurement or SAR analysis report, according to the required published RF exposure KDB procedures. When no other RF exposure testing or reporting is required, a statement of justification and compliance must be included in the equipment approval, in lieu of the SAR report, to qualify for the SAR test exclusion. When required, the device specific conditions described in the other published RF exposure KDB procedures must be satisfied before applying these SAR test exclusion provisions; for example, handheld PTT two-way radios, handsets, laptops & tablets etc.²³ “

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f \text{ (GHz)}}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where:}$$

- f (GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

4.2 Conducted Power Results

Type	Channel	Output power (dBm)
GFSK	00	-2.02
	39	-0.90
	78	-2.02
$\pi/4$ DQPSK	00	-0.60
	39	0.39
	78	-1.30
8DPSK	00	-0.34
	39	0.20
	78	-0.71

ANT1

Type	Channel	Output power PK (dBm)
802.11b	01	4.83
	06	4.36
	11	4.38
802.11g	01	4.78
	06	4.18
	11	4.26
802.11n(HT20)	01	4.46
	06	4.86
	11	4.52
802.11n(HT40)	03	3.29
	06	3.49
	09	3.64
802.11ax(HT20)	01	4.65
	06	4.27
	11	4.24
802.11ax(HT40)	03	3.12
	06	3.25
	09	3.19

ANT2

Type	Channel	Output power PK (dBm)
802.11b	01	4.44
	06	4.76
	11	4.85
802.11g	01	4.79
	06	4.14
	11	4.42
802.11n(HT20)	01	4.66
	06	4.34
	11	4.26
802.11n(HT40)	03	3.24
	06	3.11
	09	3.53
802.11ax(HT20)	01	4.15
	06	4.61

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

Tel:+86-755 2322 5875 E-mail:cta@cta-test.cn Web:http://www.cta-test.cn

	11	4.33
802.11ax(HT40)	03	3.51
	06	3.13
	09	3.46

ANT1

Test Mode	Antenna	Freq(MHz)	Result [dBm]
11A	Ant1	5180	3.50
		5220	3.21
		5240	3.46
		5745	2.62
		5785	2.07
		5825	2.32
11N20SISO	Ant1	5180	3.78
		5220	2.00
		5240	2.99
		5745	2.29
		5785	2.00
11N40SISO	Ant1	5825	2.05
		5190	3.60
		5230	3.51
		5755	2.68
11AC20SISO	Ant1	5795	2.38
		5180	3.69
		5220	3.18
		5240	3.50
		5745	2.85
11AC40SISO	Ant1	5785	2.30
		5825	2.43
		5190	3.92
		5230	3.67
11AC80SISO	Ant1	5755	2.86
		5795	2.58
		5210	4.14
11AX20SISO	Ant1	5775	3.05
		5180	3.54
		5220	3.13
		5240	3.40
		5745	2.70
11AX40SISO	Ant1	5785	1.51
		5825	2.10
		5190	3.34
		5230	3.22
11AX80SISO	Ant1	5755	2.43
		5795	2.21
		5210	3.84
		5775	2.79

ANT2

Test Mode	Antenna	Freq(MHz)	Result [dBm]
11A	Ant1	5180	3.88
		5220	3.21
		5240	3.08
		5745	2.56
		5785	2.07
		5825	1.21
11N20SISO	Ant1	5180	3.86
		5220	3.69
		5240	3.56
		5745	1.78
		5785	1.12

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

Tel:+86-755 2322 5875 E-mail:cta@cta-test.cn Web:http://www.cta-test.cn

		5825	1.87
11N40SISO	Ant1	5190	3.11
		5230	3.20
		5755	1.11
		5795	1.52
		5180	2.80
11AC20SISO	Ant1	5220	2.87
		5240	2.53
		5745	2.01
		5785	1.18
		5825	1.78
11AC40SISO	Ant1	5190	2.50
		5230	2.50
		5755	1.20
		5795	1.51
11AC80SISO	Ant1	5210	2.43
		5775	1.96
11AX20SISO	Ant1	5180	2.43
		5220	2.31
		5240	2.02
		5745	1.52
		5785	0.94
11AX40SISO	Ant1	5825	1.62
		5190	1.68
		5230	1.78
		5755	1.73
11AX80SISO	Ant1	5795	1.24
		5210	2.25
		5775	1.96

4.3 Manufacturing tolerance

Mode		Max. Peak Conducted Output Power (dBm)	Max. tune-up
BR/EDR		0.39	0.0 ± 1
2.4GWIFI	ANT1	4.86	5.0 ± 1
	ANT2	4.85	5.0 ± 1
5.2GWIFI	ANT1	4.14	4.0 ± 1
	ANT2	3.88	3.0 ± 1
5.8GWIFI	ANT1	3.05	3.0 ± 1
	ANT2	2.56	3.0 ± 1

4.4 Evaluation Result

Evaluation Results

Band/Mode	f (GHz)	Antenna Distance (mm)	RF output power (including tune-up tolerance)		SAR Test Exclusion Threshold	SAR Test Exclusion Threshold Limit	SAR Test Exclusion
			dBm	mW			
BR/EDR	2.450	5	1.0	1.2589	0.3941	3.0	Yes
2.4GWIFI ANT1	2.450	5	6.0	3.9811	1.2463	3.0	Yes
2.4GWIFI ANT2	2.450	5	6.0	3.9811	1.2463	3.0	Yes
5.2GWIFI ANT1	5.20	5	5.0	3.1623	1.4422	3.0	Yes
5.2GWIFI ANT2	5.20	5	4.0	2.5119	1.1456	3.0	Yes
5.8GWIFI ANT1	5.80	5	4.0	2.5119	1.2099	3.0	Yes
5.8GWIFI ANT2	5.80	5	4.0	2.5119	1.2099	3.0	Yes

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

Tel: +86-755 2322 5875 E-mail: cta@cta-test.cn Web: http://www.cta-test.cn

4.5 Simultaneous Transmission for SAR Exclusion

The sample 2.4G/5.2G/5.8GWIFI support MIMO, they supports difference antenna, need consider simultaneous transmission;

Σ of (the highest measured or estimated $SAR_{ant1} + SAR_{ant2}$) = (1.4422+1.2463) = 2.6885 < 3.0;

5 Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 D01v06

***** End of Report *****