

FCC PART 15.247 TEST REPORT

For

DDM Brands LLC

1616 NW, 84TH Ave. Miami, Florida, U.S.A 33126

FCC ID: A4JC50

Report Type: Original Report	Product Type: 2G mobile phone
Test Engineer: <u>Xiangguang Kong</u> <i>Xiangguang Kong</i>	
Report Number: <u>RSZ151223011-00B</u>	
Report Date: <u>2015-12-30</u>	
Reviewed By: <u>Candy Li</u> <i>Candy Li</i> RF Engineer	
Prepared By: Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
SPECIAL ACCESSORIES.....	6
EQUIPMENT MODIFICATIONS	6
SUPPORT EQUIPMENT LIST AND DETAILS	6
EXTERNAL I/O CABLE.....	6
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS.....	8
FCC§15.247 (i), §1.1307 (b) (1) &§2.1093 – RF EXPOSURE	9
APPLICABLE STANDARD	9
FCC §15.203 – ANTENNA REQUIREMENT	10
APPLICABLE STANDARD	10
ANTENNA CONNECTOR CONSTRUCTION	10
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	11
APPLICABLE STANDARD	11
MEASUREMENT UNCERTAINTY.....	11
EUT SETUP.....	11
EMI TEST RECEIVER SETUP.....	12
TEST PROCEDURE	12
TEST EQUIPMENT LIST AND DETAILS.....	12
CORRECTED FACTOR & MARGIN CALCULATION	12
TEST RESULTS SUMMARY	13
TEST DATA	13
FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS.....	16
APPLICABLE STANDARD	16
MEASUREMENT UNCERTAINTY.....	16
EUT SETUP.....	16
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	17
TEST PROCEDURE	17
CORRECTED AMPLITUDE & MARGIN CALCULATION	18
TEST EQUIPMENT LIST AND DETAILS.....	18
TEST RESULTS SUMMARY	18
TEST DATA	19
FCC §15.247(a) (1)-CHANNEL SEPARATION TEST	21
APPLICABLE STANDARD	21
TEST PROCEDURE	21
TEST EQUIPMENT LIST AND DETAILS.....	21
TEST DATA	21

FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH.....	28
APPLICABLE STANDARD	28
TEST PROCEDURE	28
TEST EQUIPMENT LIST AND DETAILS.....	28
TEST DATA	28
FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST	34
APPLICABLE STANDARD	34
TEST PROCEDURE	34
TEST EQUIPMENT LIST AND DETAILS.....	34
TEST DATA	34
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME).....	37
APPLICABLE STANDARD	37
TEST PROCEDURE	37
TEST EQUIPMENT LIST AND DETAILS.....	37
TEST DATA	37
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT	53
APPLICABLE STANDARD	53
TEST PROCEDURE	53
TEST EQUIPMENT LIST AND DETAILS.....	53
TEST DATA	53
FCC §15.247(d) - BAND EDGES TESTING	55
APPLICABLE STANDARD	55
TEST PROCEDURE	55
TEST EQUIPMENT LIST AND DETAILS.....	55
TEST DATA	55
PRODUCT SIMILARITY DECLARATION LETTE.....	60

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *DDM Brands LLC*'s product, model number: *CM50B003 (FCC ID: A4JC50)* or the "EUT" in this report was a *2G mobile phone*, which was measured approximately: 86 mm (L) × 44 mm (W) × 18 mm (H), rated with input voltage: DC 3.7 V battery or DC 5.0 V from adapter.

Adapter Information:

Model: XAA-L1J5-011C5010

Input: AC 100-240V, 50-60Hz, 0.2A

Output: DC 5.0V, 0.5A

Note: The series product, model *C50*, *CC50*, *CC50B003*, *CC50003*, *CM50003* and *CM50B003*, they are electrically identical and the difference between them is only the model number. Model *CM50B003* was selected for fully testing, which was explained in the attached product similarity declaration letter.

**All measurement and test data in this report was gathered from production sample serial number: 1507502 (Assigned by Shenzhen BACL). The EUT supplied by the applicant was received on 2015-12-23.*

Objective

This test report is prepared on behalf of *DDM Brands LLC* in accordance with Part 2-Subpart J, Part 15-Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 22H & 24E PCE and Part 15B JBP submissions with FCC ID: A4JC50.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement uncertainty with radiated emission is 5.91 dB for 30MHz-1GHz, and 4.92 dB for above 1GHz, 1.95dB for conducted measurement.

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on October 31, 2013. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.10-2013.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode.

EUT Exercise Software

No exercise software was made to the EUT tested.

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
TESCOM	Bluetooth Tester	TC-3000B	3000B630010

External I/O Cable

Cable Description	Length (m)	From Port	To
Un-shielding Detachable USB Cable	1.0	EUT	Adapter

Block Diagram of Test Setup

For conducted emission:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207(a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209 & §15.247(d)	Radiated Emissions	Compliance
§15.247(a)(1)	20 dB Emission Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band edges	Compliance

FCC§15.247 (i), §1.1307 (b) (1) &§2.1093 – RF EXPOSURE

Applicable Standard

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

1. $f(\text{GHz})$ is the RF channel transmit frequency in GHz.

2. Power and distance are rounded to the nearest mW and mm before calculation.

3. The result is rounded to one decimal place for comparison.

4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

For worst case:

Frequency (MHz)	Tune-up power (dBm)	Tune-up power (mW)	Distance (mm)	Calculated value	Threshold (1-g SAR)	SAR Test Exclusion
2480	-0.40	0.91	5.0	0.29	3.0	Yes

Result: No Standalone SAR test is required

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has one internal antenna arrangement for bluetooth, which was permanently attached and the antenna gain is 0.8 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)


Measurement Uncertainty

Input quantities to be considered for conducted disturbance measurements maybe receiver reading, attenuation of the connection between LISN and receiver, LISN voltage division factor, LISN VDF frequency interpolation and receiver related input quantities, etc.

Based on CISPR 16-4-2:2011, the expended combined standard uncertainty of conducted disturbance test at Bay Area Compliance Laboratories Corp. (Shenzhen) is shown as below. And the uncertainty will not be taken into consideration for the test data recorded in the report.

Port	Expanded Measurement uncertainty
AC Mains	3.26 dB (k=2, 95% level of confidence)
CAT 3	3.70 dB (k=2, 95% level of confidence)
CAT 5	3.86 dB (k=2, 95% level of confidence)
CAT 6	4.64 dB (k=2, 95% level of confidence)

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS30	100176	2015-06-03	2016-06-02
Rohde & Schwarz	LISN	ENV216	3560.6650.12-101613-Yb	2015-12-01	2016-12-01
Rohde & Schwarz	LISN	ESH2-Z5	892107/021	2015-06-09	2016-06-09
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2015-05-14	2016-05-13
Rohde & Schwarz	CE Test software	EMC 32	V8.53	NCR	NCR

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Correction Factor} = \text{LISN VDF} + \text{Cable Loss} + \text{Transient Limiter Attenuation}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, the worst margin reading as below:

14.8 dB at 0.470830 MHz in the **Line** conducted mode

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(L_m)} \leq L_{\text{lim}} + U_{\text{cispr}}$$

In BACL, $U_{(L_m)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data

Environmental Conditions


Temperature:	23 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by Xiangguang Kong on 2015-12-29.


EUT operation mode: Transmitting & Charging

AC 120V/60 Hz, Line

EMI Auto Test L



Frequency (MHz)	Corrected Amplitude (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/Ave./QP)
0.153500	46.2	20.0	65.8	19.6	QP
0.153500	31.6	20.0	55.8	24.2	Ave.
0.174500	47.7	20.0	64.7	17.1	QP
0.174500	35.1	20.0	54.7	19.6	Ave.
0.245500	44.0	20.0	61.9	17.9	QP
0.245500	33.2	20.0	51.9	18.7	Ave.
0.470830	41.7	19.9	56.5	14.8	QP
0.470830	31.2	19.9	46.5	15.3	Ave.
0.762450	39.0	19.9	56.0	17.0	QP
0.762450	25.9	19.9	46.0	20.1	Ave.
0.931810	37.9	20.0	56.0	18.1	QP
0.931810	25.6	20.0	46.0	20.4	Ave.

AC 120V/60 Hz, Neutral**EMI Auto Test N**

Frequency (MHz)	Corrected Amplitude (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/Ave./QP)
0.225500	40.5	20.0	62.6	22.1	QP
0.225500	35.2	20.0	52.6	17.4	Ave.
0.344870	40.1	19.9	59.1	19.0	QP
0.344870	31.6	19.9	49.1	17.5	Ave.
0.423610	39.3	19.9	57.4	18.1	QP
0.423610	30.3	19.9	47.4	17.1	Ave.
0.600910	34.4	19.9	56.0	21.6	QP
0.600910	23.9	19.9	46.0	22.1	Ave.
0.719170	34.9	19.9	56.0	21.1	QP
0.719170	23.1	19.9	46.0	22.9	Ave.
0.912410	30.9	20.0	56.0	25.1	QP
0.912410	19.7	20.0	46.0	26.3	Ave.

Note:

- 1) Correction Factor = LISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation
- 2) Corrected Amplitude = Reading + Correction Factor
- 3) Margin = Limit – Corrected Amplitude

FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS

Applicable Standard

FCC §15.205; §15.209; §15.247(d)


Measurement Uncertainty


All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on CISPR 16-4-2:2011, the expanded combined standard uncertainty of radiation emissions at Bay Area Compliance Laboratories Corp. (Shenzhen) is 5.91 dB for 30MHz-1GHz, and 4.92 dB for above 1GHz. And this uncertainty will not be taken into consideration for the test data recorded in the report.

EUT Setup

Below 1 GHz:



Above 1GHz:

The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1 MHz	3 MHz	/	PK
	1 MHz	10 Hz	/	Ave.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode for frequency range of 30 MHz -1 GHz and peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Amplifier	HP8447E	1937A01046	2015-05-06	2016-05-05
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2015-11-03	2016-11-03
Sunol Sciences	Bi-log Antenna	JB1	A040904-2	2014-12-07	2017-12-06
Mini	Amplifier	ZVA-183-S+	5969001149	2015-04-23	2016-04-22
A.H. System	Horn Antenna	SAS-200/571	135	2015-02-10	2016-02-10
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2015-12-11	2016-12-11
the electro-Mechanics Co.	Horn Antenna	3116	9510-2270	2013-10-14	2016-10-13
TDK	Chamber	Chamber A	2#	2015-10-15	2018-10-15
TDK	Chamber	Chamber B	1#	2015-07-22	2016-07-22
DUCOMMUN	Pre-amplifier	ALN-22093530-01	991373-01	2015-08-03	2016-08-03
R&S	Auto test Software	EMC32	V9.10	NCR	NCR

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

11.99 dB at 7206.00 MHz in the Vertical polarization for Low Channel

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(L_m)} \leq L_{lim} + U_{cispr}$$

In BACL, $U_{(L_m)}$ is less than $+ U_{cispr}$, if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data**Environmental Conditions**

Temperature:	23 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by Xiangguang Kong on 2015-12-29.

EUT operation mode: Transmitting

30 MHz -25 GHz: (Scan with GFSK, $\pi/4$ -DQPSK, 8-DPSK mode, the worst case is BDR Mode (GFSK))

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Low Channel (2402 MHz)									
144.68	40.87	QP	194	1.4	H	-13.6	27.27	43.5	16.23
2402.00	73.75	PK	101	1.6	H	4.97	78.72	/	/
2402.00	53.69	Ave.	101	1.6	H	4.97	58.66	/	/
2402.00	76.27	PK	136	2.4	V	4.97	81.24	/	/
2402.00	56.00	Ave.	136	2.4	V	4.97	60.97	/	/
2388.55	32.89	PK	138	1.4	V	4.97	37.86	74	36.14
2388.55	15.41	Ave.	138	1.4	V	4.97	20.38	54	33.62
2386.63	34.46	PK	91	1.5	V	4.97	39.43	74	34.57
2386.63	15.41	Ave.	91	1.5	V	4.97	20.38	54	33.62
2496.66	32.13	PK	129	1.2	V	6.29	38.42	74	35.58
2496.66	13.48	Ave.	129	1.2	V	6.29	19.77	54	34.23
4804.00	43.42	PK	304	1.7	V	11.91	55.33	74	18.67
4804.00	20.52	Ave.	304	1.7	V	11.91	32.43	54	21.57
7206.00	44.61	PK	53	2.4	V	17.40	62.01	74	11.99
7206.00	23.02	Ave.	53	2.4	V	17.40	40.42	54	13.58
9608.00	31.35	PK	98	1.5	H	22.54	53.89	74	20.11
9608.00	15.41	Ave.	98	1.5	H	22.54	37.95	54	16.05

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Middle Channel (2441 MHz)									
144.68	39.98	QP	92	1.7	H	-13.6	26.38	43.5	17.12
2441.00	71.73	PK	144	2.3	H	4.97	76.70	/	/
2441.00	51.56	Ave.	144	2.3	H	4.97	56.53	/	/
2441.00	75.05	PK	89	1.4	V	4.97	80.02	/	/
2441.00	54.04	Ave.	89	1.4	V	4.97	59.01	/	/
2386.79	32.87	PK	65	2.4	V	4.97	37.84	74	36.16
2386.79	15.41	Ave.	65	2.4	V	4.97	20.38	54	33.62
2487.79	32.82	PK	258	1.1	V	6.29	39.11	74	34.89
2487.79	13.48	Ave.	258	1.1	V	6.29	19.77	54	34.23
2485.38	32.17	PK	188	2.3	V	6.29	38.46	74	35.54
2485.38	13.48	Ave.	188	2.3	V	6.29	19.77	54	34.23
4882.00	39.47	PK	198	2.5	V	12.49	51.96	74	22.04
4882.00	17.00	Ave.	198	2.5	V	12.49	29.49	54	24.51
7323.00	42.65	PK	89	1.2	V	17.72	60.37	74	13.63
7323.00	19.50	Ave.	89	1.2	V	17.72	37.22	54	16.78
9764.00	30.75	PK	221	2.0	V	23.60	54.35	74	19.65
9764.00	15.33	Ave.	221	2.0	V	23.60	38.93	54	15.07
High Channel (2480 MHz)									
144.68	40.32	QP	270	2.2	H	-13.6	26.72	43.5	16.78
2480.00	70.91	PK	26	1.7	H	6.29	77.20	/	/
2480.00	50.41	Ave.	26	1.7	H	6.29	56.70	/	/
2480.00	74.86	PK	77	1.3	V	6.29	81.15	/	/
2480.00	53.63	Ave.	77	1.3	V	6.29	59.92	/	/
2385.03	33.10	PK	54	1.2	V	4.97	38.07	74	35.93
2385.03	15.41	Ave.	54	1.2	V	4.97	20.38	54	33.62
2483.50	43.81	PK	252	2.1	V	6.29	50.10	74	23.90
2483.50	18.34	Ave.	252	2.1	V	6.29	24.63	54	29.37
2483.79	42.65	PK	13	1.7	V	6.29	48.94	74	25.06
2483.79	17.00	Ave.	13	1.7	V	6.29	23.29	54	30.71
4960.00	36.28	PK	25	1.6	V	14.91	51.19	74	22.81
4960.00	16.41	Ave.	25	1.6	V	14.91	31.32	54	22.68
7440.00	38.00	PK	63	1.1	V	18.01	56.01	74	17.99
7440.00	17.00	Ave.	63	1.1	V	18.01	35.01	54	18.99
9920.00	30.11	PK	260	2.1	V	23.60	53.71	74	20.29
9920.00	15.10	Ave.	260	2.1	V	23.60	38.70	54	15.30

Note:

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Corrected Factor + Reading

Margin = Limit - Corrected. Amplitude

FCC §15.247(a) (1)-CHANNEL SEPARATION TEST**Applicable Standard**

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Set the EUT in transmitting mode, maxhold the channel.
2. Set the adjacent channel of the EUT and maxhold another trace.
3. Measure the channel separation.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2015-12-11	2016-12-11

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	24 °C
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Xiangguang Kong on 2015-12-24.


EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table and plots


Mode	Channel	Frequency (MHz)	Channel Separation (MHz)	$\geq$ Limit (MHz)	Result
BDR (GFSK)	Low	2402	1.004	0.632	Pass
	Adjacent	2403			
	Middle	2441	0.998	0.631	Pass
	Adjacent	2442			
	High	2480	0.998	0.631	Pass
	Adjacent	2479			
EDR ($\pi/4$-DQPSK)	Low	2402	1.004	0.861	Pass
	Adjacent	2403			
	Middle	2441	1.004	0.860	Pass
	Adjacent	2442			
	High	2480	1.004	0.856	Pass
	Adjacent	2479			
EDR (8DPSK)	Low	2402	0.998	0.842	Pass
	Adjacent	2403			
	Middle	2441	0.998	0.842	Pass
	Adjacent	2442			
	High	2480	1.004	0.841	Pass
	Adjacent	2479			

Note: Limit = 20 dB bandwidth *2/3


BDR (GFSK): Low Channel




BDR (GFSK): Middle Channel





BDR (GFSK): High Channel




EDR ($\pi/4$ -DQPSK): Low Channel




EDR ($\pi/4$ -DQPSK): Middle ChannelEDR ($\pi/4$ -DQPSK): High Channel


EDR (8DPSK): Low Channel



EDR (8DPSK): Middle Channel



EDR (8DPSK): High Channel



FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH**Applicable Standard**

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2015-12-11	2016-12-11

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**


Temperature:	24 °C
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Xiangguang Kong on 2015-12-24.


EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table and plots


Mode	Channel	Frequency (MHz)	20 dB Emission Bandwidth (MHz)
BDR (GFSK)	Low	2402	0.950
	Middle	2441	0.950
	High	2480	0.950
EDR ($\pi/4$-DQPSK)	Low	2402	1.358
	Middle	2441	1.354
	High	2480	1.354
EDR (8DPSK)	Low	2402	1.287
	Middle	2441	1.287
	High	2480	1.296



BDR (GFSK): Low Channel


BDR (GFSK): Middle Channel




BDR (GFSK): High Channel



EDR ($\pi/4$ -DQPSK): Low ChannelEDR ($\pi/4$ -DQPSK): Middle Channel

EDR ($\pi/4$ -DQPSK): High Channel

EDR (8DPSK): Low Channel



Ref Lvl 20.5 dBm Marker 1 [T1 ndB] ndB 20.00 dB RBW 30 kHz RF Att 20 dB

20.5 dBm BW 1.28737475 MHz SWT 6.5 ms Unit dBm

10.5 dB Offset

1MAX

Marker 1 [T1 ndB] ndB 20.00 dB

Marker 2 [T2 -25.30 dBm] -25.30 dBm

Marker 3 [T3 -25.50 dBm] -25.50 dBm

Marker 4 [T4 -25.30 dBm] -25.30 dBm

Marker 5 [T5 -25.50 dBm] -25.50 dBm

Marker 6 [T6 -25.30 dBm] -25.30 dBm

Marker 7 [T7 -25.50 dBm] -25.50 dBm

Marker 8 [T8 -25.30 dBm] -25.30 dBm

Marker 9 [T9 -25.50 dBm] -25.50 dBm

Marker 10 [T10 -25.30 dBm] -25.30 dBm

Marker 11 [T11 -25.50 dBm] -25.50 dBm

Marker 12 [T12 -25.30 dBm] -25.30 dBm

Marker 13 [T13 -25.50 dBm] -25.50 dBm

Marker 14 [T14 -25.30 dBm] -25.30 dBm

Marker 15 [T15 -25.50 dBm] -25.50 dBm

Marker 16 [T16 -25.30 dBm] -25.30 dBm

Marker 17 [T17 -25.50 dBm] -25.50 dBm

Marker 18 [T18 -25.30 dBm] -25.30 dBm

Marker 19 [T19 -25.50 dBm] -25.50 dBm

Marker 20 [T20 -25.30 dBm] -25.30 dBm

Marker 21 [T21 -25.50 dBm] -25.50 dBm

Marker 22 [T22 -25.30 dBm] -25.30 dBm

Marker 23 [T23 -25.50 dBm] -25.50 dBm

Marker 24 [T24 -25.30 dBm] -25.30 dBm

Marker 25 [T25 -25.50 dBm] -25.50 dBm

Marker 26 [T26 -25.30 dBm] -25.30 dBm

Marker 27 [T27 -25.50 dBm] -25.50 dBm

Marker 28 [T28 -25.30 dBm] -25.30 dBm

Marker 29 [T29 -25.50 dBm] -25.50 dBm

Marker 30 [T30 -25.30 dBm] -25.30 dBm

Marker 31 [T31 -25.50 dBm] -25.50 dBm

Marker 32 [T32 -25.30 dBm] -25.30 dBm

Marker 33 [T33 -25.50 dBm] -25.50 dBm

Marker 34 [T34 -25.30 dBm] -25.30 dBm

Marker 35 [T35 -25.50 dBm] -25.50 dBm

Marker 36 [T36 -25.30 dBm] -25.30 dBm

Marker 37 [T37 -25.50 dBm] -25.50 dBm

Marker 38 [T38 -25.30 dBm] -25.30 dBm

Marker 39 [T39 -25.50 dBm] -25.50 dBm

Marker 40 [T40 -25.30 dBm] -25.30 dBm

Marker 41 [T41 -25.50 dBm] -25.50 dBm

Marker 42 [T42 -25.30 dBm] -25.30 dBm

Marker 43 [T43 -25.50 dBm] -25.50 dBm

Marker 44 [T44 -25.30 dBm] -25.30 dBm

Marker 45 [T45 -25.50 dBm] -25.50 dBm

Marker 46 [T46 -25.30 dBm] -25.30 dBm

Marker 47 [T47 -25.50 dBm] -25.50 dBm

Marker 48 [T48 -25.30 dBm] -25.30 dBm

Marker 49 [T49 -25.50 dBm] -25.50 dBm

Marker 50 [T50 -25.30 dBm] -25.30 dBm

Marker 51 [T51 -25.50 dBm] -25.50 dBm

Marker 52 [T52 -25.30 dBm] -25.30 dBm

Marker 53 [T53 -25.50 dBm] -25.50 dBm

Marker 54 [T54 -25.30 dBm] -25.30 dBm

Marker 55 [T55 -25.50 dBm] -25.50 dBm

Marker 56 [T56 -25.30 dBm] -25.30 dBm

Marker 57 [T57 -25.50 dBm] -25.50 dBm

Marker 58 [T58 -25.30 dBm] -25.30 dBm

Marker 59 [T59 -25.50 dBm] -25.50 dBm

Marker 60 [T60 -25.30 dBm] -25.30 dBm

Marker 61 [T61 -25.50 dBm] -25.50 dBm

Marker 62 [T62 -25.30 dBm] -25.30 dBm

Marker 63 [T63 -25.50 dBm] -25.50 dBm

Marker 64 [T64 -25.30 dBm] -25.30 dBm

Marker 65 [T65 -25.50 dBm] -25.50 dBm

Marker 66 [T66 -25.30 dBm] -25.30 dBm

Marker 67 [T67 -25.50 dBm] -25.50 dBm

Marker 68 [T68 -25.30 dBm] -25.30 dBm

Marker 69 [T69 -25.50 dBm] -25.50 dBm

Marker 70 [T70 -25.30 dBm] -25.30 dBm

Marker 71 [T71 -25.50 dBm] -25.50 dBm

Marker 72 [T72 -25.30 dBm] -25.30 dBm

Marker 73 [T73 -25.50 dBm] -25.50 dBm

Marker 74 [T74 -25.30 dBm] -25.30 dBm

Marker 75 [T75 -25.50 dBm] -25.50 dBm

Marker 76 [T76 -25.30 dBm] -25.30 dBm

Marker 77 [T77 -25.50 dBm] -25.50 dBm

Marker 78 [T78 -25.30 dBm] -25.30 dBm

Marker 79 [T79 -25.50 dBm] -25.50 dBm

Marker 80 [T80 -25.30 dBm] -25.30 dBm

Marker 81 [T81 -25.50 dBm] -25.50 dBm

Marker 82 [T82 -25.30 dBm] -25.30 dBm

Marker 83 [T83 -25.50 dBm] -25.50 dBm

Marker 84 [T84 -25.30 dBm] -25.30 dBm

Marker 85 [T85 -25.50 dBm] -25.50 dBm

Marker 86 [T86 -25.30 dBm] -25.30 dBm

Marker 87 [T87 -25.50 dBm] -25.50 dBm

Marker 88 [T88 -25.30 dBm] -25.30 dBm

Marker 89 [T89 -25.50 dBm] -25.50 dBm

Marker 90 [T90 -25.30 dBm] -25.30 dBm

Marker 91 [T91 -25.50 dBm] -25.50 dBm

Marker 92 [T92 -25.30 dBm] -25.30 dBm

Marker 93 [T93 -25.50 dBm] -25.50 dBm

Marker 94 [T94 -25.30 dBm] -25.30 dBm

Marker 95 [T95 -25.50 dBm] -25.50 dBm

Marker 96 [T96 -25.30 dBm] -25.30 dBm

Marker 97 [T97 -25.50 dBm] -25.50 dBm

Marker 98 [T98 -25.30 dBm] -25.30 dBm

Marker 99 [T99 -25.50 dBm] -25.50 dBm

Marker 100 [T100 -25.30 dBm] -25.30 dBm

Marker 101 [T101 -25.50 dBm] -25.50 dBm

Marker 102 [T102 -25.30 dBm] -25.30 dBm

Marker 103 [T103 -25.50 dBm] -25.50 dBm

Marker 104 [T104 -25.30 dBm] -25.30 dBm

Marker 105 [T105 -25.50 dBm] -25.50 dBm

Marker 106 [T106 -25.30 dBm] -25.30 dBm

Marker 107 [T107 -25.50 dBm] -25.50 dBm

Marker 108 [T108 -25.30 dBm] -25.30 dBm

Marker 109 [T109 -25.50 dBm] -25.50 dBm

Marker 110 [T110 -25.30 dBm] -25.30 dBm

Marker 111 [T111 -25.50 dBm] -25.50 dBm

Marker 112 [T112 -25.30 dBm] -25.30 dBm

Marker 113 [T113 -25.50 dBm] -25.50 dBm

Marker 114 [T114 -25.30 dBm] -25.30 dBm

Marker 115 [T115 -25.50 dBm] -25.50 dBm

Marker 116 [T116 -25.30 dBm] -25.30 dBm

Marker 117 [T117 -25.50 dBm] -25.50 dBm

Marker 118 [T118 -25.30 dBm] -25.30 dBm

Marker 119 [T119 -25.50 dBm] -25.50 dBm

Marker 120 [T120 -25.30 dBm] -25.30 dBm

Marker 121 [T121 -25.50 dBm] -25.50 dBm

Marker 122 [T122 -25.30 dBm] -25.30 dBm

Marker 123 [T123 -25.50 dBm] -25.50 dBm

Marker 124 [T124 -

10.5 dB Offset

Ref Lvl 20.5 dBm

Marker 1 [T1 ndB] 20.00 dB

RBW 30 kHz

RF Att 20 dB

VBW 100 kHz

SWT 6.5 ms

Unit dBm

1 [T1] -5.26 dBm

2.48017415 GHz

ndB 20.00 dB

BW 1.29619238 MHz

T1 [T1] -25.49 dBm

2.47935852 GHz

T2 [T1] -25.29 dBm

2.48065471 GHz

1MAX

1MAX

Center 2.48 GHz

220 kHz/

Span 2.2 MHz

Date: 24.DEC.2015 19:26:08

FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST**Applicable Standard**

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the max-hold function record the quantity of the channel.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2015-12-11	2016-12-11

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	24 °C
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa


The testing was performed by Xiangguang Kong on 2015-12-24.



EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table and plots

Mode	Frequency Range (MHz)	Number of Hopping Channel (CH)	Limit (CH)
BDR (GFSK)	2400-2483.5	79	≥ 15
EDR ($\pi/4$ -DQPSK)	2400-2483.5	79	≥ 15
EDR (8DPSK)	2400-2483.5	79	≥ 15

BDR (GFSK): Number of Hopping Channels



EDR ($\pi/4$ -DQPSK): Number of Hopping Channels**EDR (8DPSK): Number of Hopping Channels**

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWEELL TIME)**Applicable Standard**

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT was worked in channel hopping; Spectrum SPAN was set as 0. Sweep was set as 0.4 X channel no. (s), the quantity of pulse was get from single sweep. In addition, the time of single pulses was tested.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2015-12-11	2016-12-11

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	24 °C
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa


The testing was performed by Xiangguang Kong on 2015-12-24.

EUT operation mode: Transmitting


Test Result: Compliance. Please refer to following table and plots

Mode		Channel	Pulse Width (ms)	Dwell Time (S)	Limit (S)	Result
BDR (GFSK)	DH 1	Low	0.396	0.127	0.4	Pass
		Middle	0.396	0.127	0.4	Pass
		High	0.396	0.127	0.4	Pass
		Note: DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	DH 3	Low	1.671	0.267	0.4	Pass
		Middle	1.671	0.267	0.4	Pass
		High	1.671	0.267	0.4	Pass
		Note: DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	DH 5	Low	2.943	0.314	0.4	Pass
		Middle	2.943	0.314	0.4	Pass
		High	2.943	0.314	0.4	Pass
		Note: DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				
EDR ($\pi/4$ -DQPSK)	2DH 1	Low	0.396	0.127	0.4	Pass
		Middle	0.396	0.127	0.4	Pass
		High	0.396	0.127	0.4	Pass
		Note: 2DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	2DH 3	Low	1.671	0.267	0.4	Pass
		Middle	1.671	0.267	0.4	Pass
		High	1.671	0.267	0.4	Pass
		Note: 2DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	2DH 5	Low	2.943	0.314	0.4	Pass
		Middle	2.943	0.314	0.4	Pass
		High	2.943	0.314	0.4	Pass
		Note: 2DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				
EDR (8DPSK)	3DH 1	Low	0.396	0.127	0.4	Pass
		Middle	0.396	0.127	0.4	Pass
		High	0.396	0.127	0.4	Pass
		Note: 3DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	3DH 3	Low	1.659	0.265	0.4	Pass
		Middle	1.659	0.265	0.4	Pass
		High	1.659	0.265	0.4	Pass
		Note: 3DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	3DH 5	Low	2.943	0.314	0.4	Pass
		Middle	2.943	0.314	0.4	Pass
		High	2.943	0.314	0.4	Pass
		Note: 3DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				

BDR (GFSK): Pulse time, Low Channel, DH1



Pulse time, Middle Channel, DH1



Ref Lvl 20.5 dBm

Marker 1 [T1] -54.08 dBm

RBW 1 MHz

VBW 3 MHz

SWT 800 μ s

RF Att 20 dB

Unit dBm

10.5 dB Offset

1 [T1] -54.08 dBm

2 [T1] -8.216433 μ s

3 [T1] -8.18 dB

4 [T1] 395.991984 μ s

TR

Center 2.48 GHz

80 μ s/

Date: 24.DEC.2015 20:15:52

Ref Lvl 20.5 dBm

Delta 1 [T1] 2.21 dB

1.670541 ms

RBW 1 MHz

VBW 3 MHz

SWT 3 ms

RF Att 20 dB

Unit dBm

10.5 dB Offset

TR

Center 2.402 GHz

300 us/

-53.88 dBm

-20.246481 us

2.21 dB

1.670541 ms

1 A


SGL

TRG


1MA

Date: 24.DEC.2015 20:22:01


Pulse time, Middle Channel, DH3



Pulse time, High Channel, DH3




Pulse time, Low Channel, DH5




Date: 24.DEC.2015 20:23:08

Pulse time, Middle Channel, DH5




Date: 24.DEC.2015 20:23:19


Pulse time, High Channel, DH5




EDR ($\pi/4$ -DQPSK): Pulse time, Low Channel, 2DH1




Pulse time, Middle Channel, 2DH1




Pulse time, High Channel, 2DH1




Pulse time, Low Channel, 2DH3




Pulse time, Middle Channel, 2DH3




Pulse time, High Channel, 2DH3



Pulse time, Low Channel, 2DH5




Pulse time, Middle Channel, 2DH5




Date: 24.DEC.2015 20:24:19

Pulse time, High Channel, 2DH5




Date: 24.DEC.2015 20:23:58


EDR (8DPSK): Pulse time, Low Channel, 3DH1




Pulse time, Middle Channel, 3DH1



Pulse time, High Channel, 3DH1



Pulse time, Low Channel, 3DH3



Ref Lvl 20.5 dBm Delta 1 [T1] 3.52 dB RBW 1 MHz RF Att 20 dB

20.5 dBm 1.658517 ms SWB 3 MHz Unit dBm

10.5 dB Offset

TR

1 [T1] -52.90 dBm

1 [T1] -20.240481 us

1.658517 ms

Center 2.441 GHz 300 MHz

Date: 24.DEC.2015 20:19:50

Ref Lvl 20.5 dBm

Delta 1 [T1] -2.86 dB

1.658517 ms

RBW 1 MHz

VBW 3 MHz

SWT 3 ms

RF Att 20 dB

Unit dBm

10.5 dB Offset

20.5

10

0

-10

-20

-30

-40

-50

-60

-70

-79.5

Center 2.48 GHz

300 500 MHz

1 [T1] -52.65 dBm

1 [T1] -20.240481 us

1 [T1] -2.86 dB

1.658517 ms

TR

A


SGL

TRG


1MA

Date: 24.DEC.2015 20:19:40


Pulse time, Low Channel, 3DH5



Pulse time, Middle Channel, 3DH5



Pulse time, High Channel, 3DH5



FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT**Applicable Standard**

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

Test Procedure

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Power Meter	N1912A	MY5000448	2015-11-03	2016-11-03
HP	Power Sensor	N1921A	MY54210016	2015-11-03	2016-11-03

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	24 °C
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Xiangguang Kong on 2015-12-24.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table.

Mode	Channel	Frequency (MHz)	Peak Output Power		Limit (mW)
			(dBm)	(mW)	
BDR (GFSK)	Low	2402	-2.26	0.594	1000
	Middle	2441	-2.20	0.603	1000
	High	2480	-2.01	0.630	1000
EDR ($\pi/4$-DQPSK)	Low	2402	-1.39	0.726	1000
	Middle	2441	-1.01	0.793	1000
	High	2480	-0.82	0.828	1000
EDR (8DPSK)	Low	2402	-1.06	0.783	1000
	Middle	2441	-0.61	0.869	1000
	High	2480	-0.42	0.908	1000

FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2015-12-11	2016-12-11

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions


Temperature:	24 °C
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Xiangguang Kong on 2015-12-24.


EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following plots.


BDR (GFSK): Band Edge-Left Side





BDR (GFSK): Band Edge-Right Side




EDR ($\pi/4$ -DQPSK): Band Edge-Left Side



EDR ($\pi/4$ -DQPSK): Band Edge-Right Side**EDR (8DPSK): Band Edge-Left Side**

BDR (8DPSK): Band Edge-Right Side



PRODUCT SIMILARITY DECLARATION LETTER



DDM Brands LLC
Address: 1616 NW, 84TH Ave. Miami, Florida, U.S.A 33126
Tel: +1 3057750325 Fax: +1 3057750325

Product Similarity Declaration

December 31, 2015

To Whom It May Concern,

We, DDM Brands LLC, hereby declare that we have a product named as 2G mobile phone (Model number: CM50B003) was tested by BACL, meanwhile, for our marketing purpose, we would like to list a series models (C50, CC50, CC50B003, CC50003, CM50003) on reports and certificate, all the models are identical schematics, only named differently.

No other changes are made to them

We confirm that all information above is true, and we'll be responsible for all the consequences. Please contact me if you have any question.

Sincerely,

Signature:

Luis Sosa

CEO

***** END OF REPORT *****