

# FCC TEST REPORT (15.247)

**REPORT NO.:** RF150508C06A-6  
**MODEL:** WT2  
**FCC ID:** A4R-WT2  
**RECEIVED:** May 08, 2015  
**TESTED:** Jun. 10, 2015 ~ Aug. 15, 2015  
**ISSUED:** Aug. 05, 2016

**APPLICANT:** Google Inc.

**ADDRESS:** 1600 Amphitheatre Parkway Mountain View California  
United States 94043

**ISSUED BY:** Bureau Veritas Consumer Products Services (H.K.)  
Ltd., Taoyuan Branch

**LAB ADDRESS:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New  
Taipei City, Taiwan ( R.O.C )

**TEST LOCATION:** No. 19, Hwa Ya 2nd Rd, Wen Hwa Vil., Kwei Shan  
Dist., Taoyuan City 33383, Taiwan (R.O.C.)

This report should not be used by the client to claim  
product certification, approval, or endorsement by  
TAF or any government agencies.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

## TABLE OF CONTENTS

|                                                                                             |    |
|---------------------------------------------------------------------------------------------|----|
| Preface .....                                                                               | 3  |
| RELEASE CONTROL RECORD .....                                                                | 4  |
| 1. CERTIFICATION .....                                                                      | 5  |
| 2. SUMMARY OF TEST RESULTS .....                                                            | 6  |
| 2.1 MEASUREMENT UNCERTAINTY .....                                                           | 6  |
| 3. GENERAL INFORMATION .....                                                                | 7  |
| 3.1 GENERAL DESCRIPTION OF EUT .....                                                        | 7  |
| 3.2 DESCRIPTION OF TEST MODES .....                                                         | 8  |
| 3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL .....                               | 9  |
| 3.3 DESCRIPTION OF SUPPORT UNITS .....                                                      | 10 |
| 3.3.1 CONFIGURATION OF SYSTEM UNDER TEST .....                                              | 10 |
| 3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS .....                                          | 11 |
| 4. TEST TYPES AND RESULTS (FOR 2.4GHz BAND) .....                                           | 12 |
| 4.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT .....                                        | 12 |
| 4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT .....                            | 12 |
| 4.1.2 TEST INSTRUMENTS .....                                                                | 13 |
| 4.1.3 TEST PROCEDURES .....                                                                 | 14 |
| 4.1.4 DEVIATION FROM TEST STANDARD .....                                                    | 14 |
| 4.1.5 TEST SETUP .....                                                                      | 15 |
| 4.1.6 EUT OPERATING CONDITIONS .....                                                        | 15 |
| 4.1.7 TEST RESULTS .....                                                                    | 16 |
| 4.2 CONDUCTED EMISSION MEASUREMENT .....                                                    | 29 |
| 4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT .....                                        | 29 |
| 4.2.2 TEST INSTRUMENTS .....                                                                | 29 |
| 4.2.3 TEST PROCEDURES .....                                                                 | 30 |
| 4.2.4 DEVIATION FROM TEST STANDARD .....                                                    | 30 |
| 4.2.5 TEST SETUP .....                                                                      | 31 |
| 4.2.6 EUT OPERATING CONDITIONS .....                                                        | 31 |
| 4.2.7 TEST RESULTS .....                                                                    | 32 |
| 4.3 CONDUCTED OUTPUT POWER .....                                                            | 34 |
| 4.3.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT .....                                    | 34 |
| 4.3.2 TEST SETUP .....                                                                      | 34 |
| 4.3.3 TEST INSTRUMENTS .....                                                                | 34 |
| 4.3.4 TEST PROCEDURES .....                                                                 | 34 |
| 4.3.5 DEVIATION FROM TEST STANDARD .....                                                    | 34 |
| 4.3.6 EUT OPERATING CONDITIONS .....                                                        | 34 |
| 4.3.7 TEST RESULTS .....                                                                    | 35 |
| 5. PHOTOGRAPHS OF THE TEST CONFIGURATION .....                                              | 36 |
| 6. INFORMATION ON THE TESTING LABORATORIES .....                                            | 37 |
| 7. APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB ..... | 38 |

## Preface

To whom it may concern,

We hereby declare that the integrated module-end product (FCC ID: A4R-WT2) is identical to the integrated module-end product (FCC ID: A4R-WT1) in the WLAN layout of the circuit, components and transmit power levels. The difference is only to add LTE function into the integrated module-end product and change the model name from WT1 to WT2.

Based on the similarity between both modules, we hereby request to leverage the all test data of FCC ID: A4R-WT1 described as below to demonstrate the compliance of FCC ID: A4R-WT2 for part 15C.

The list of reference details (Re-use the test data from the original integrated module-end product):

| Equipment Class | Reference FCC ID | Reference to the test sections from FCC test report RF150508C06-6 |                                            |
|-----------------|------------------|-------------------------------------------------------------------|--------------------------------------------|
| DTS             | A4R-WT1          | 4.1                                                               | Radiated Emission and Bandedge Measurement |
|                 |                  | 4.2                                                               | Conducted Emission Measurement             |
|                 |                  | 4.3                                                               | Conducted Output Power                     |



## RELEASE CONTROL RECORD

| ISSUE NO.      | REASON FOR CHANGE | DATE ISSUED   |
|----------------|-------------------|---------------|
| RF150508C06A-6 | Original release  | Aug. 05, 2016 |

## 1. CERTIFICATION

**PRODUCT**  
**NAME/DESCRIPTION:** Connectivity Bridge

**MODEL:** WT2

**BRAND:** Google

**APPLICANT:** Google Inc.

**TESTED:** Jun. 10, 2015 ~ Aug. 15, 2015

**TEST SAMPLE:** Identical Prototype

**STANDARDS:** **FCC Part 15, Subpart C (Section 15.247)**  
ANSI C63.10-2013

The above equipment (model: WT2) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**PREPARED BY** : Evonne Liu , **DATE** : Aug. 05, 2016  
Evonne Liu / Specialist

**APPROVED BY** : Stanley Wu , **DATE** : Aug. 05, 2016  
Stanley Wu / Assistant Manager

## 2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

| APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247) |                             |                |                                                                                  |
|-----------------------------------------------------------|-----------------------------|----------------|----------------------------------------------------------------------------------|
| STANDARD SECTION                                          | TEST TYPE                   | RESULT         | REMARK                                                                           |
| 15.207                                                    | AC Power Conducted Emission | PASS           | Meet the requirement of limit. Minimum passing margin is -17.51dB at 0.49799MHz. |
| 15.205 & 15.209                                           | Radiated Emissions          | PASS           | Meet the requirement of limit. Minimum passing margin is -1.11dB at 2488MHz.     |
| 15.247(d)                                                 | Band Edge Measurement       | Not Applicable | Refer to Note                                                                    |
| 15.247(d)                                                 | Antenna Port Emission       | Not Applicable | Refer to Note                                                                    |
| 15.247(a)(2)                                              | 6dB bandwidth               | Not Applicable | Refer to Note                                                                    |
| 15.247(b)                                                 | Conducted power             | PASS           | Meet the requirement of limit.                                                   |
| 15.247(e)                                                 | Power Spectral Density      | Not Applicable | Refer to Note                                                                    |
| 15.203                                                    | Antenna Requirement         | Not Applicable | Refer to Note                                                                    |

### NOTE:

- Only the test item for conducted power, conducted and radiated emission had been tested for this addendum and the conducted data is referring to module report (Report No.: RF140407E07).

### 2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

| MEASUREMENT         | FREQUENCY       | UNCERTAINTY |
|---------------------|-----------------|-------------|
| Conducted emissions | 9kHz~30MHz      | 2.44 dB     |
| Radiated emissions  | 9kHz ~ 30MHz    | 2.14 dB     |
|                     | 30MHz ~ 200MHz  | 2.93 dB     |
|                     | 200MHz ~1000MHz | 2.95 dB     |
|                     | 1GHz ~ 18GHz    | 2.26 dB     |
|                     | 18GHz ~ 40GHz   | 1.94 dB     |

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k = 2$ .

### 3. GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

|                                 |                                                                                                                                  |
|---------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| <b>PRODUCT NAME/DESCRIPTION</b> | Connectivity Bridge                                                                                                              |
| <b>MODEL</b>                    | WT2                                                                                                                              |
| <b>POWER SUPPLY</b>             | 5.0Vdc (adapter)                                                                                                                 |
| <b>MODULATION TYPE</b>          | CCK, DQPSK, DBPSK for DSSS<br>64QAM, 16QAM, QPSK, BPSK for OFDM                                                                  |
| <b>MODULATION TECHNOLOGY</b>    | DSSS, OFDM                                                                                                                       |
| <b>TRANSFER RATE</b>            | 802.11b: 11.0 / 5.5 / 2.0 / 1.0 Mbps<br>802.11g: 54.0 / 48.0 / 36.0 / 24.0 / 18.0 / 12.0 / 9.0 / 6.0 Mbps<br>802.11n: up to MCS7 |
| <b>OPERATING FREQUENCY</b>      | 2412 ~ 2462MHz                                                                                                                   |
| <b>NUMBER OF CHANNEL</b>        | 11 for 802.11b, 802.11g, 802.11n (20MHz)<br>7 for 802.11n (40MHz)                                                                |
| <b>OUTPUT POWER</b>             | 621.628mW                                                                                                                        |
| <b>ANTENNA TYPE</b>             | FPCB antenna with 4.06dBi gain                                                                                                   |
| <b>ANTENNA CONNECTOR</b>        | NA                                                                                                                               |
| <b>DATA CABLE</b>               | Refer to Note as below                                                                                                           |
| <b>I/O PORTS</b>                | Refer to user's manual                                                                                                           |
| <b>ACCESSORY DEVICES</b>        | Refer to Note as below                                                                                                           |

**NOTE:**

1. The EUT contains following accessory devices.

| ITEM        | BRAND     | MODEL      | SPECIFICATION                                   |
|-------------|-----------|------------|-------------------------------------------------|
| Adapter     | TPT       | MII050200  | I/P: 100-240Vac, 50-60Hz, 0.3A<br>O/P: 5Vdc, 2A |
| WWAN Module | Telit     | LE910-NAG  | --                                              |
| WiFi Module | AzureWave | AW-CM389NF | --                                              |

2. The EUT incorporates a MIMO function. Physically, the EUT provides two completed transmitters and two receivers.

| MODULATION MODE | TX FUNCTION |
|-----------------|-------------|
| 802.11b         | 2TX         |
| 802.11g         | 2TX         |
| 802.11n (20MHz) | 2TX         |
| 802.11n (40MHz) | 2TX         |

3. The above EUT information is declared by the manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

## 3.2 DESCRIPTION OF TEST MODES

### FOR 2.4GHz:

11 channels are provided for 802.11b, 802.11g and 802.11n (20MHz):

| CHANNEL | FREQUENCY | CHANNEL | FREQUENCY |
|---------|-----------|---------|-----------|
| 1       | 2412MHz   | 7       | 2442MHz   |
| 2       | 2417MHz   | 8       | 2447MHz   |
| 3       | 2422MHz   | 9       | 2452MHz   |
| 4       | 2427MHz   | 10      | 2457MHz   |
| 5       | 2432MHz   | 11      | 2462MHz   |
| 6       | 2437MHz   |         |           |

7 channels are provided for 802.11n (40MHz):

| CHANNEL | FREQUENCY | CHANNEL | FREQUENCY |
|---------|-----------|---------|-----------|
| 3       | 2422MHz   | 7       | 2442MHz   |
| 4       | 2427MHz   | 8       | 2447MHz   |
| 5       | 2432MHz   | 9       | 2452MHz   |
| 6       | 2437MHz   |         |           |

### 3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

#### WLAN 2.4GHz:

| EUT CONFIGURE MODE | APPLICABLE TO |       |     |      | DESCRIPTION |
|--------------------|---------------|-------|-----|------|-------------|
|                    | RE $\geq$ 1G  | RE<1G | PLC | APCM |             |
| -                  | √             | √     | √   | √    | -           |

Where **RE $\geq$ 1G:** Radiated Emission above 1GHz

**RE<1G:** Radiated Emission below 1GHz

**PLC:** Power Line Conducted Emission

**APCM:** Antenna Port Conducted Measurement

#### **RADIATED EMISSION TEST (ABOVE 1GHz):**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT CONFIGURE MODE | MODE            | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TECHNOLOGY | MODULATION TYPE | DATA RATE (Mbps) |
|--------------------|-----------------|-------------------|----------------|-----------------------|-----------------|------------------|
| -                  | 802.11b         | 1 to 11           | 1, 6, 11       | DSSS                  | DBPSK           | 1.0              |
| -                  | 802.11g         | 1 to 11           | 1, 6, 11       | OFDM                  | BPSK            | 6.0              |
| -                  | 802.11n (20MHz) | 1 to 11           | 1, 6, 11       | OFDM                  | BPSK            | MCS0             |
| -                  | 802.11n (40MHz) | 3 to 9            | 3, 6, 9        | OFDM                  | BPSK            | MCS0             |

#### **RADIATED EMISSION TEST (BELOW 1GHz):**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT CONFIGURE MODE | MODE            | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TECHNOLOGY | MODULATION TYPE | DATA RATE (Mbps) |
|--------------------|-----------------|-------------------|----------------|-----------------------|-----------------|------------------|
| -                  | 802.11n (20MHz) | 1 to 11           | 11             | OFDM                  | BPSK            | MCS0             |

#### **POWER LINE CONDUCTED EMISSION TEST:**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT CONFIGURE MODE | MODE            | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TECHNOLOGY | MODULATION TYPE | DATA RATE (Mbps) |
|--------------------|-----------------|-------------------|----------------|-----------------------|-----------------|------------------|
| -                  | 802.11n (20MHz) | 1 to 11           | 11             | OFDM                  | BPSK            | MCS0             |

#### ANTENNA PORT CONDUCTED MEASUREMENT:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT CONFIGURE MODE | MODE            | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TECHNOLOGY | MODULATION TYPE | DATA RATE (Mbps) |
|--------------------|-----------------|-------------------|----------------|-----------------------|-----------------|------------------|
| -                  | 802.11b         | 1 to 11           | 1, 6, 11       | DSSS                  | DBPSK           | 1.0              |
| -                  | 802.11g         | 1 to 11           | 1, 6, 11       | OFDM                  | BPSK            | 6.0              |
| -                  | 802.11n (20MHz) | 1 to 11           | 1, 6, 11       | OFDM                  | BPSK            | MCS0             |


#### TEST CONDITION:

| APPLICABLE TO | ENVIRONMENTAL CONDITIONS | INPUT POWER  | TESTED BY     |
|---------------|--------------------------|--------------|---------------|
| RE $\geq$ 1G  | 25deg. C, 65%RH          | 120Vac, 60Hz | Karl Lee      |
| RE<1G         | 25deg. C, 65%RH          | 120Vac, 60Hz | Charles Hsiao |
| PLC           | 25deg. C, 65%RH          | 120Vac, 60Hz | Toby Tian     |
| APCM          | 25deg. C, 65%RH          | 120Vac, 60Hz | Taylor Liu    |

### 3.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units.

#### 3.3.1 CONFIGURATION OF SYSTEM UNDER TEST



### 3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C (15.247)**

**558074 D01 DTS Meas Guidance v03r05**

**662911 D01 Multiple Transmitter Output v02r01**

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

**NOTE:** The EUT has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

## 4. TEST TYPES AND RESULTS (FOR 2.4GHz BAND)

### 4.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT

#### 4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

| FREQUENCIES (MHz) | FIELD STRENGTH (microvolts/meter) | MEASUREMENT DISTANCE (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009 ~ 0.490     | 2400/F(kHz)                       | 300                           |
| 0.490 ~ 1.705     | 24000/F(kHz)                      | 30                            |
| 1.705 ~ 30.0      | 30                                | 30                            |
| 30 ~ 88           | 100                               | 3                             |
| 88 ~ 216          | 150                               | 3                             |
| 216 ~ 960         | 200                               | 3                             |
| Above 960         | 500                               | 3                             |

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

#### 4.1.2 TEST INSTRUMENTS

| DESCRIPTION & MANUFACTURER                     | MODEL NO.      | SERIAL NO.          | DATE OF CALIBRATION | DUE DATE OF CALIBRATION |
|------------------------------------------------|----------------|---------------------|---------------------|-------------------------|
| Test Receiver<br>Agilent                       | N9038A         | MY51210203          | Jan.21, 2015        | Jan.21, 2016            |
| Spectrum Analyzer<br>Agilent                   | N9010A         | MY52220314          | Sep.03, 2014        | Sep.02, 2015            |
| Spectrum Analyzer<br>ROHDE & SCHWARZ           | FSU43          | 101261              | Dec. 10, 2014       | Dec. 09, 2015           |
| BILOG Antenna<br>SCHWARZBECK                   | VULB9168       | 9168-472            | Feb. 04, 2015       | Feb. 04, 2016           |
| HORN Antenna<br>SCHWARZBECK                    | BBHA 9120 D    | 9120D-969           | Feb. 09, 2015       | Feb. 09, 2016           |
| HORN Antenna<br>SCHWARZBECK                    | BBHA 9170      | 9170-480            | Feb. 04, 2015       | Feb. 04, 2016           |
| Preamplifier<br>EMCI                           | EMC 012645     | 980115              | Dec. 12, 2014       | Dec. 11, 2015           |
| Preamplifier<br>EMCI                           | EMC 184045     | 980116              | Jan. 09, 2015       | Jan. 08, 2016           |
| Preamplifier<br>EMCI                           | EMC 330H       | 980112              | Dec. 27, 2014       | Dec. 26, 2015           |
| RF signal cable<br>HUBER+SUHNNER               | SUCOFLEX 104   | 309219/4<br>2950114 | Oct. 18, 2014       | Oct. 17, 2015           |
| RF signal cable<br>HUBER+SUHNNER               | SUCOFLEX 104   | 250130/4            | Oct. 18, 2014       | Oct. 17, 2015           |
| RF signal cable<br>Worken                      | RG-213         | NA                  | Nov. 07, 2014       | Nov. 06, 2015           |
| Software<br>BV ADT                             | E3<br>6.120103 | NA                  | NA                  | NA                      |
| Antenna Tower<br>MF                            | MFA-440H       | NA                  | NA                  | NA                      |
| Turn Table<br>MF                               | MFT-201SS      | NA                  | NA                  | NA                      |
| Antenna Tower & Turn<br>Table Controller<br>MF | MF-7802        | NA                  | NA                  | NA                      |
| Bluetooth Tester                               | CBT            | 100980              | Feb. 10, 2015       | Feb. 09, 2016           |
| Power Meter                                    | ML2495A        | 1232002             | Sep. 17, 2014       | Sep. 16, 2015           |
| Power Sensor                                   | MA2411B        | 1207325             | Sep. 17, 2014       | Sep. 16, 2015           |

- NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The calibration interval of the loop antenna is 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
3. The test was performed in HwaYa Chamber 10.
4. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
5. The FCC Site Registration No. is 690701.
6. The IC Site Registration No. is IC 7450F-10.

#### 4.1.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Height of receiving antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

**NOTE:**


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 1kHz (Duty cycle < 98%) or 10Hz (Duty cycle > 98%) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

#### 4.1.4 DEVIATION FROM TEST STANDARD


No deviation.

#### 4.1.5 TEST SETUP

<Frequency Range 30MHz ~ 1GHz>



<Frequency Range above 1GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.1.6 EUT OPERATING CONDITIONS

- Placed the EUT on a testing table.
- Use the software to control the EUT under transmission condition continuously at specific channel frequency.

#### 4.1.7 TEST RESULTS

##### ABOVE 1GHz WORST-CASE DATA

802.11b

| EUT TEST CONDITION       |                 | MEASUREMENT DETAIL |                           |
|--------------------------|-----------------|--------------------|---------------------------|
| CHANNEL                  | Channel 1       | FREQUENCY RANGE    | 1GHz ~ 25GHz              |
| INPUT POWER              | 120Vac, 60 Hz   | DETECTOR FUNCTION  | Peak (PK)<br>Average (AV) |
| ENVIRONMENTAL CONDITIONS | 25deg. C, 65%RH | TESTED BY          | Karl Lee                  |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                         |                   |                |             |                       |                 |                    |                     |                      |         |
|-----------------------------------------------------|-------------------------|-------------------|----------------|-------------|-----------------------|-----------------|--------------------|---------------------|----------------------|---------|
| FREQ. (MHz)                                         | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB/m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK  |
| 2384                                                | 41.3                    | 39.61             | 54             | -12.7       | 31.78                 | 5.4             | 35.49              | 166                 | 193                  | Average |
| 2384                                                | 56.35                   | 54.66             | 74             | -17.65      | 31.78                 | 5.4             | 35.49              | 166                 | 193                  | Peak    |
| 2412                                                | 101.2                   | 99.43             |                |             | 31.81                 | 5.43            | 35.47              | 166                 | 193                  | Average |
| 2412                                                | 104.9                   | 103.13            |                |             | 31.81                 | 5.43            | 35.47              | 166                 | 193                  | Peak    |
| 2490                                                | 40.69                   | 38.68             | 54             | -13.31      | 31.9                  | 5.53            | 35.42              | 166                 | 193                  | Average |
| 2490                                                | 56.85                   | 54.84             | 74             | -17.15      | 31.9                  | 5.53            | 35.42              | 166                 | 193                  | Peak    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                         |                   |                |             |                       |                 |                    |                     |                      |         |
| FREQ. (MHz)                                         | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB/m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK  |
| 2360                                                | 40.36                   | 38.73             | 54             | -13.64      | 31.76                 | 5.37            | 35.5               | 119                 | 266                  | Average |
| 2360                                                | 55.94                   | 54.31             | 74             | -18.06      | 31.76                 | 5.37            | 35.5               | 119                 | 266                  | Peak    |
| 2412                                                | 99.65                   | 97.88             |                |             | 31.81                 | 5.43            | 35.47              | 119                 | 266                  | Average |
| 2412                                                | 102.15                  | 100.38            |                |             | 31.81                 | 5.43            | 35.47              | 119                 | 266                  | Peak    |
| 2490                                                | 40.8                    | 38.79             | 54             | -13.2       | 31.9                  | 5.53            | 35.42              | 119                 | 266                  | Average |
| 2490                                                | 55.8                    | 53.79             | 74             | -18.2       | 31.9                  | 5.53            | 35.42              | 119                 | 266                  | Peak    |

#### REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
- 2412MHz: Fundamental frequency.

| EUT TEST CONDITION       |                 | MEASUREMENT DETAIL |                           |
|--------------------------|-----------------|--------------------|---------------------------|
| CHANNEL                  | Channel 6       | FREQUENCY RANGE    | 1GHz ~ 25GHz              |
| INPUT POWER              | 120Vac, 60 Hz   | DETECTOR FUNCTION  | Peak (PK)<br>Average (AV) |
| ENVIRONMENTAL CONDITIONS | 25deg. C, 65%RH | TESTED BY          | Karl Lee                  |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                               |                         |                   |                |                             |                       |                          |                           |                            |         |
|-----------------------------------------------------|-------------------------------|-------------------------|-------------------|----------------|-----------------------------|-----------------------|--------------------------|---------------------------|----------------------------|---------|
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB/m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2390                                                | 40.06                         | 38.33                   | 54                | -13.94         | 31.8                        | 5.4                   | 35.47                    | 142                       | 159                        | Average |
| 2390                                                | 55.84                         | 54.11                   | 74                | -18.16         | 31.8                        | 5.4                   | 35.47                    | 142                       | 159                        | Peak    |
| 2437                                                | 100.66                        | 98.81                   |                   |                | 31.85                       | 5.46                  | 35.46                    | 142                       | 159                        | Average |
| 2437                                                | 103.98                        | 102.13                  |                   |                | 31.85                       | 5.46                  | 35.46                    | 142                       | 159                        | Peak    |
| 2488                                                | 40.76                         | 38.75                   | 54                | -13.24         | 31.9                        | 5.53                  | 35.42                    | 142                       | 159                        | Average |
| 2488                                                | 56.43                         | 54.42                   | 74                | -17.57         | 31.9                        | 5.53                  | 35.42                    | 142                       | 159                        | Peak    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                               |                         |                   |                |                             |                       |                          |                           |                            |         |
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB/m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2374                                                | 42.03                         | 40.37                   | 54                | -11.97         | 31.78                       | 5.37                  | 35.49                    | 119                       | 159                        | Average |
| 2374                                                | 55.71                         | 54.05                   | 74                | -18.29         | 31.78                       | 5.37                  | 35.49                    | 119                       | 159                        | Peak    |
| 2437                                                | 98.87                         | 97.02                   |                   |                | 31.85                       | 5.46                  | 35.46                    | 119                       | 159                        | Average |
| 2437                                                | 101.29                        | 99.44                   |                   |                | 31.85                       | 5.46                  | 35.46                    | 119                       | 159                        | Peak    |
| 2492                                                | 40.64                         | 38.62                   | 54                | -13.36         | 31.9                        | 5.53                  | 35.41                    | 119                       | 159                        | Average |
| 2492                                                | 56.88                         | 54.86                   | 74                | -17.12         | 31.9                        | 5.53                  | 35.41                    | 119                       | 159                        | Peak    |

**REMARKS:**

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
- 2437MHz: Fundamental frequency.

| EUT TEST CONDITION       |                 | MEASUREMENT DETAIL |                           |
|--------------------------|-----------------|--------------------|---------------------------|
| CHANNEL                  | Channel 11      | FREQUENCY RANGE    | 1GHz ~ 25GHz              |
| INPUT POWER              | 120Vac, 60 Hz   | DETECTOR FUNCTION  | Peak (PK)<br>Average (AV) |
| ENVIRONMENTAL CONDITIONS | 25deg. C, 65%RH | TESTED BY          | Karl Lee                  |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                         |                   |                |             |                       |                 |                    |                     |                      |         |
|-----------------------------------------------------|-------------------------|-------------------|----------------|-------------|-----------------------|-----------------|--------------------|---------------------|----------------------|---------|
| FREQ. (MHz)                                         | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB/m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK  |
| 2390                                                | 40.07                   | 38.34             | 54             | -13.93      | 31.8                  | 5.4             | 35.47              | 141                 | 193                  | Average |
| 2390                                                | 55.63                   | 53.9              | 74             | -18.37      | 31.8                  | 5.4             | 35.47              | 141                 | 193                  | Peak    |
| 2462                                                | 100.17                  | 98.24             |                |             | 31.87                 | 5.5             | 35.44              | 141                 | 193                  | Average |
| 2462                                                | 103.82                  | 101.89            |                |             | 31.87                 | 5.5             | 35.44              | 141                 | 193                  | Peak    |
| 2490                                                | 40.99                   | 38.98             | 54             | -13.01      | 31.9                  | 5.53            | 35.42              | 141                 | 193                  | Average |
| 2490                                                | 55.64                   | 53.63             | 74             | -18.36      | 31.9                  | 5.53            | 35.42              | 141                 | 193                  | Peak    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                         |                   |                |             |                       |                 |                    |                     |                      |         |
| FREQ. (MHz)                                         | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB/m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK  |
| 2378                                                | 40.1                    | 38.44             | 54             | -13.9       | 31.78                 | 5.37            | 35.49              | 119                 | 259                  | Average |
| 2378                                                | 55.65                   | 53.99             | 74             | -18.35      | 31.78                 | 5.37            | 35.49              | 119                 | 259                  | Peak    |
| 2462                                                | 98.93                   | 97                |                |             | 31.87                 | 5.5             | 35.44              | 119                 | 259                  | Average |
| 2462                                                | 101.22                  | 99.29             |                |             | 31.87                 | 5.5             | 35.44              | 119                 | 259                  | Peak    |
| 2484                                                | 41.34                   | 39.38             | 54             | -12.66      | 31.88                 | 5.5             | 35.42              | 119                 | 259                  | Average |
| 2484                                                | 55.93                   | 53.97             | 74             | -18.07      | 31.88                 | 5.5             | 35.42              | 119                 | 259                  | Peak    |

**REMARKS:**

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
- 2462MHz: Fundamental frequency.

# 802.11g

| EUT TEST CONDITION       |                 | MEASUREMENT DETAIL |                           |
|--------------------------|-----------------|--------------------|---------------------------|
| CHANNEL                  | Channel 1       | FREQUENCY RANGE    | 1GHz ~ 25GHz              |
| INPUT POWER              | 120Vac, 60 Hz   | DETECTOR FUNCTION  | Peak (PK)<br>Average (AV) |
| ENVIRONMENTAL CONDITIONS | 25deg. C, 65%RH | TESTED BY          | Karl Lee                  |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                         |                   |                |             |                       |                 |                    |                     |                      |         |
|-----------------------------------------------------|-------------------------|-------------------|----------------|-------------|-----------------------|-----------------|--------------------|---------------------|----------------------|---------|
| FREQ. (MHz)                                         | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB/m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK  |
| 2390                                                | 51.14                   | 49.41             | 54             | -2.86       | 31.8                  | 5.4             | 35.47              | 114                 | 162                  | Average |
| 2390                                                | 66.9                    | 65.17             | 74             | -7.1        | 31.8                  | 5.4             | 35.47              | 114                 | 162                  | Peak    |
| 2412                                                | 97.05                   | 95.28             |                |             | 31.81                 | 5.43            | 35.47              | 166                 | 193                  | Average |
| 2412                                                | 104.26                  | 102.49            |                |             | 31.81                 | 5.43            | 35.47              | 166                 | 193                  | Peak    |
| 2486                                                | 40.72                   | 38.73             | 54             | -13.28      | 31.88                 | 5.53            | 35.42              | 166                 | 193                  | Average |
| 2486                                                | 55.97                   | 53.98             | 74             | -18.03      | 31.88                 | 5.53            | 35.42              | 166                 | 193                  | Peak    |
| 4824                                                | 42.73                   | 34.6              | 54             | -11.27      | 33.97                 | 8.26            | 34.1               | 101                 | 224                  | Average |
| 4824                                                | 53.46                   | 45.33             | 74             | -20.54      | 33.97                 | 8.26            | 34.1               | 101                 | 224                  | Peak    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                         |                   |                |             |                       |                 |                    |                     |                      |         |
| FREQ. (MHz)                                         | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB/m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK  |
| 2390                                                | 45.12                   | 43.39             | 54             | -8.88       | 31.8                  | 5.4             | 35.47              | 119                 | 266                  | Average |
| 2390                                                | 59.59                   | 57.86             | 74             | -14.41      | 31.8                  | 5.4             | 35.47              | 119                 | 266                  | Peak    |
| 2412                                                | 94.64                   | 92.87             |                |             | 31.81                 | 5.43            | 35.47              | 119                 | 266                  | Average |
| 2412                                                | 102.27                  | 100.5             |                |             | 31.81                 | 5.43            | 35.47              | 119                 | 266                  | Peak    |
| 2498                                                | 41.44                   | 39.42             | 54             | -12.56      | 31.9                  | 5.53            | 35.41              | 119                 | 266                  | Average |
| 2498                                                | 57.11                   | 55.09             | 74             | -16.89      | 31.9                  | 5.53            | 35.41              | 119                 | 266                  | Peak    |
| 4824                                                | 43.57                   | 35.44             | 54             | -10.43      | 33.97                 | 8.26            | 34.1               | 100                 | 298                  | Average |
| 4824                                                | 54.8                    | 46.67             | 74             | -19.2       | 33.97                 | 8.26            | 34.1               | 100                 | 298                  | Peak    |

## REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
- 2412MHz: Fundamental frequency.

| EUT TEST CONDITION       |                 | MEASUREMENT DETAIL |                           |
|--------------------------|-----------------|--------------------|---------------------------|
| CHANNEL                  | Channel 6       | FREQUENCY RANGE    | 1GHz ~ 25GHz              |
| INPUT POWER              | 120Vac, 60 Hz   | DETECTOR FUNCTION  | Peak (PK)<br>Average (AV) |
| ENVIRONMENTAL CONDITIONS | 25deg. C, 65%RH | TESTED BY          | Karl Lee                  |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                               |                         |                   |                |                             |                       |                          |                           |                            |         |
|-----------------------------------------------------|-------------------------------|-------------------------|-------------------|----------------|-----------------------------|-----------------------|--------------------------|---------------------------|----------------------------|---------|
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB/m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2390                                                | 50.83                         | 49.1                    | 54                | -3.17          | 31.8                        | 5.4                   | 35.47                    | 154                       | 159                        | Average |
| 2390                                                | 65.34                         | 63.61                   | 74                | -8.66          | 31.8                        | 5.4                   | 35.47                    | 154                       | 159                        | Peak    |
| 2437                                                | 101.96                        | 100.11                  |                   |                | 31.85                       | 5.46                  | 35.46                    | 142                       | 159                        | Average |
| 2437                                                | 109.45                        | 107.6                   |                   |                | 31.85                       | 5.46                  | 35.46                    | 142                       | 159                        | Peak    |
| 2484                                                | 47.69                         | 45.73                   | 54                | -6.31          | 31.88                       | 5.5                   | 35.42                    | 142                       | 159                        | Average |
| 2484                                                | 63.62                         | 61.66                   | 74                | -10.38         | 31.88                       | 5.5                   | 35.42                    | 142                       | 159                        | Peak    |
| 4874                                                | 47.99                         | 39.8                    | 54                | -6.01          | 33.98                       | 8.27                  | 34.06                    | 100                       | 211                        | Average |
| 4874                                                | 59.3                          | 51.11                   | 74                | -14.7          | 33.98                       | 8.27                  | 34.06                    | 100                       | 211                        | Peak    |
| 7311                                                | 49.87                         | 39.38                   | 54                | -4.13          | 35.54                       | 9.95                  | 35                       | 107                       | 0                          | Average |
| 7311                                                | 61.05                         | 50.56                   | 74                | -12.95         | 35.54                       | 9.95                  | 35                       | 107                       | 0                          | Peak    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                               |                         |                   |                |                             |                       |                          |                           |                            |         |
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB/m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2390                                                | 48.66                         | 46.93                   | 54                | -5.34          | 31.8                        | 5.4                   | 35.47                    | 105                       | 159                        | Average |
| 2390                                                | 63.81                         | 62.08                   | 74                | -10.19         | 31.8                        | 5.4                   | 35.47                    | 105                       | 159                        | Peak    |
| 2437                                                | 99.29                         | 97.44                   |                   |                | 31.85                       | 5.46                  | 35.46                    | 105                       | 159                        | Average |
| 2437                                                | 107.46                        | 105.61                  |                   |                | 31.85                       | 5.46                  | 35.46                    | 105                       | 159                        | Peak    |
| 2484                                                | 44.72                         | 42.76                   | 54                | -9.28          | 31.88                       | 5.5                   | 35.42                    | 105                       | 159                        | Average |
| 2484                                                | 59.55                         | 57.59                   | 74                | -14.45         | 31.88                       | 5.5                   | 35.42                    | 105                       | 159                        | Peak    |
| 4874                                                | 48.18                         | 39.99                   | 54                | -5.82          | 33.98                       | 8.27                  | 34.06                    | 112                       | 295                        | Average |
| 4874                                                | 59.92                         | 51.73                   | 74                | -14.08         | 33.98                       | 8.27                  | 34.06                    | 112                       | 295                        | Peak    |
| 7311                                                | 47.87                         | 37.38                   | 54                | -6.13          | 35.54                       | 9.95                  | 35                       | 100                       | 244                        | Average |
| 7311                                                | 58.3                          | 47.81                   | 74                | -15.7          | 35.54                       | 9.95                  | 35                       | 100                       | 244                        | Peak    |

**REMARKS:**

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
- 2437MHz: Fundamental frequency.

| EUT TEST CONDITION       |                 | MEASUREMENT DETAIL |                           |
|--------------------------|-----------------|--------------------|---------------------------|
| CHANNEL                  | Channel 11      | FREQUENCY RANGE    | 1GHz ~ 25GHz              |
| INPUT POWER              | 120Vac, 60 Hz   | DETECTOR FUNCTION  | Peak (PK)<br>Average (AV) |
| ENVIRONMENTAL CONDITIONS | 25deg. C, 65%RH | TESTED BY          | Karl Lee                  |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                               |                         |                   |                |                             |                       |                          |                           |                            |         |
|-----------------------------------------------------|-------------------------------|-------------------------|-------------------|----------------|-----------------------------|-----------------------|--------------------------|---------------------------|----------------------------|---------|
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB/m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2376                                                | 40.18                         | 38.52                   | 54                | -13.82         | 31.78                       | 5.37                  | 35.49                    | 123                       | 77                         | Average |
| 2376                                                | 55.28                         | 53.62                   | 74                | -18.72         | 31.78                       | 5.37                  | 35.49                    | 123                       | 77                         | Peak    |
| 2462                                                | 96.42                         | 94.49                   |                   |                | 31.87                       | 5.5                   | 35.44                    | 123                       | 77                         | Average |
| 2462                                                | 104.48                        | 102.55                  |                   |                | 31.87                       | 5.5                   | 35.44                    | 123                       | 77                         | Peak    |
| 2484                                                | 52.58                         | 50.62                   | 54                | -1.42          | 31.88                       | 5.5                   | 35.42                    | 123                       | 79                         | Average |
| 2484                                                | 68.1                          | 66.14                   | 74                | -5.9           | 31.88                       | 5.5                   | 35.42                    | 123                       | 79                         | Peak    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                               |                         |                   |                |                             |                       |                          |                           |                            |         |
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB/m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2358                                                | 40.08                         | 38.45                   | 54                | -13.92         | 31.76                       | 5.37                  | 35.5                     | 119                       | 259                        | Average |
| 2358                                                | 56.24                         | 54.61                   | 74                | -17.76         | 31.76                       | 5.37                  | 35.5                     | 119                       | 259                        | Peak    |
| 2462                                                | 94.34                         | 92.41                   |                   |                | 31.87                       | 5.5                   | 35.44                    | 119                       | 259                        | Average |
| 2462                                                | 102.93                        | 101                     |                   |                | 31.87                       | 5.5                   | 35.44                    | 119                       | 259                        | Peak    |
| 2484                                                | 49.28                         | 47.32                   | 54                | -4.72          | 31.88                       | 5.5                   | 35.42                    | 119                       | 259                        | Average |
| 2484                                                | 67.4                          | 65.44                   | 74                | -6.6           | 31.88                       | 5.5                   | 35.42                    | 119                       | 259                        | Peak    |

**REMARKS:**

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
- 2462MHz: Fundamental frequency.

### 802.11n (20MHz)

| EUT TEST CONDITION       |                 | MEASUREMENT DETAIL |                           |
|--------------------------|-----------------|--------------------|---------------------------|
| CHANNEL                  | Channel 1       | FREQUENCY RANGE    | 1GHz ~ 25GHz              |
| INPUT POWER              | 120Vac, 60 Hz   | DETECTOR FUNCTION  | Peak (PK)<br>Average (AV) |
| ENVIRONMENTAL CONDITIONS | 25deg. C, 65%RH | TESTED BY          | Karl Lee                  |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                         |                   |                |             |                       |                 |                    |                     |                      |         |
|-----------------------------------------------------|-------------------------|-------------------|----------------|-------------|-----------------------|-----------------|--------------------|---------------------|----------------------|---------|
| FREQ. (MHz)                                         | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB/m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK  |
| 2390                                                | 51.14                   | 49.41             | 54             | -2.86       | 31.8                  | 5.4             | 35.47              | 114                 | 162                  | Average |
| 2390                                                | 65.27                   | 63.54             | 74             | -8.73       | 31.8                  | 5.4             | 35.47              | 114                 | 162                  | Peak    |
| 2412                                                | 95.96                   | 94.19             |                |             | 31.81                 | 5.43            | 35.47              | 166                 | 193                  | Average |
| 2412                                                | 103.1                   | 101.33            |                |             | 31.81                 | 5.43            | 35.47              | 166                 | 193                  | Peak    |
| 2484                                                | 40.63                   | 38.67             | 54             | -13.37      | 31.88                 | 5.5             | 35.42              | 166                 | 193                  | Average |
| 2484                                                | 56.17                   | 54.21             | 74             | -17.83      | 31.88                 | 5.5             | 35.42              | 166                 | 193                  | Peak    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                         |                   |                |             |                       |                 |                    |                     |                      |         |
| FREQ. (MHz)                                         | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB/m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK  |
| 2388                                                | 46.47                   | 44.76             | 54             | -7.53       | 31.8                  | 5.4             | 35.49              | 119                 | 159                  | Average |
| 2388                                                | 59.08                   | 57.37             | 74             | -14.92      | 31.8                  | 5.4             | 35.49              | 119                 | 159                  | Peak    |
| 2412                                                | 93.21                   | 91.44             |                |             | 31.81                 | 5.43            | 35.47              | 119                 | 159                  | Average |
| 2412                                                | 101.18                  | 99.41             |                |             | 31.81                 | 5.43            | 35.47              | 119                 | 159                  | Peak    |
| 2494                                                | 44.78                   | 42.76             | 54             | -9.22       | 31.9                  | 5.53            | 35.41              | 119                 | 159                  | Average |
| 2494                                                | 56.01                   | 53.99             | 74             | -17.99      | 31.9                  | 5.53            | 35.41              | 119                 | 159                  | Peak    |

#### REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
- 2412MHz: Fundamental frequency.

| EUT TEST CONDITION       |                 | MEASUREMENT DETAIL |                           |
|--------------------------|-----------------|--------------------|---------------------------|
| CHANNEL                  | Channel 6       | FREQUENCY RANGE    | 1GHz ~ 25GHz              |
| INPUT POWER              | 120Vac, 60 Hz   | DETECTOR FUNCTION  | Peak (PK)<br>Average (AV) |
| ENVIRONMENTAL CONDITIONS | 25deg. C, 65%RH | TESTED BY          | Karl Lee                  |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                         |                   |                |             |                       |                 |                    |                     |                      |         |
|-----------------------------------------------------|-------------------------|-------------------|----------------|-------------|-----------------------|-----------------|--------------------|---------------------|----------------------|---------|
| FREQ. (MHz)                                         | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB/m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK  |
| 2390                                                | 51.91                   | 50.18             | 54             | -2.09       | 31.8                  | 5.4             | 35.47              | 153                 | 160                  | Average |
| 2390                                                | 65.54                   | 63.81             | 74             | -8.46       | 31.8                  | 5.4             | 35.47              | 153                 | 160                  | Peak    |
| 2437                                                | 101.08                  | 99.23             |                |             | 31.85                 | 5.46            | 35.46              | 142                 | 159                  | Average |
| 2437                                                | 109.82                  | 107.97            |                |             | 31.85                 | 5.46            | 35.46              | 142                 | 159                  | Peak    |
| 2486                                                | 52.87                   | 50.88             | 54             | -1.13       | 31.88                 | 5.53            | 35.42              | 108                 | 188                  | Average |
| 2486                                                | 70.07                   | 68.08             | 74             | -3.93       | 31.88                 | 5.53            | 35.42              | 108                 | 188                  | Peak    |
| 4874                                                | 48.42                   | 40.23             | 54             | -5.58       | 33.98                 | 8.27            | 34.06              | 100                 | 211                  | Average |
| 4874                                                | 59.71                   | 51.52             | 74             | -14.29      | 33.98                 | 8.27            | 34.06              | 100                 | 211                  | Peak    |
| 7311                                                | 49.67                   | 39.18             | 54             | -4.33       | 35.54                 | 9.95            | 35                 | 107                 | 360                  | Average |
| 7311                                                | 60.47                   | 49.98             | 74             | -13.53      | 35.54                 | 9.95            | 35                 | 107                 | 360                  | Peak    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                         |                   |                |             |                       |                 |                    |                     |                      |         |
| FREQ. (MHz)                                         | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB/m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK  |
| 2390                                                | 46.39                   | 44.66             | 54             | -7.61       | 31.8                  | 5.4             | 35.47              | 119                 | 159                  | Average |
| 2390                                                | 59.98                   | 58.25             | 74             | -14.02      | 31.8                  | 5.4             | 35.47              | 119                 | 159                  | Peak    |
| 2437                                                | 99.12                   | 97.27             |                |             | 31.85                 | 5.46            | 35.46              | 119                 | 159                  | Average |
| 2437                                                | 107.17                  | 105.32            |                |             | 31.85                 | 5.46            | 35.46              | 119                 | 159                  | Peak    |
| 2492                                                | 46                      | 43.98             | 54             | -8          | 31.9                  | 5.53            | 35.41              | 119                 | 159                  | Average |
| 2492                                                | 62.97                   | 60.95             | 74             | -11.03      | 31.9                  | 5.53            | 35.41              | 119                 | 159                  | Peak    |
| 4874                                                | 48.14                   | 39.95             | 54             | -5.86       | 33.98                 | 8.27            | 34.06              | 112                 | 295                  | Average |
| 4874                                                | 58.43                   | 50.24             | 74             | -15.57      | 33.98                 | 8.27            | 34.06              | 112                 | 295                  | Peak    |
| 7311                                                | 48.69                   | 38.2              | 54             | -5.31       | 35.54                 | 9.95            | 35                 | 104                 | 238                  | Average |
| 7311                                                | 59.12                   | 48.63             | 74             | -14.88      | 35.54                 | 9.95            | 35                 | 104                 | 238                  | Peak    |

**REMARKS:**

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
- 2437MHz: Fundamental frequency.

| EUT TEST CONDITION       |                 | MEASUREMENT DETAIL |                           |
|--------------------------|-----------------|--------------------|---------------------------|
| CHANNEL                  | Channel 11      | FREQUENCY RANGE    | 1GHz ~ 25GHz              |
| INPUT POWER              | 120Vac, 60 Hz   | DETECTOR FUNCTION  | Peak (PK)<br>Average (AV) |
| ENVIRONMENTAL CONDITIONS | 25deg. C, 65%RH | TESTED BY          | Karl Lee                  |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                               |                         |                   |                |                             |                       |                          |                           |                            |         |
|-----------------------------------------------------|-------------------------------|-------------------------|-------------------|----------------|-----------------------------|-----------------------|--------------------------|---------------------------|----------------------------|---------|
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB/m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2372                                                | 40.04                         | 38.38                   | 54                | -13.96         | 31.78                       | 5.37                  | 35.49                    | 123                       | 77                         | Average |
| 2372                                                | 55.22                         | 53.56                   | 74                | -18.78         | 31.78                       | 5.37                  | 35.49                    | 123                       | 77                         | Peak    |
| 2462                                                | 95.05                         | 93.12                   |                   |                | 31.87                       | 5.5                   | 35.44                    | 123                       | 77                         | Average |
| 2462                                                | 103.05                        | 101.12                  |                   |                | 31.87                       | 5.5                   | 35.44                    | 123                       | 77                         | Peak    |
| 2488                                                | 52.89                         | 50.88                   | 54                | -1.11          | 31.9                        | 5.53                  | 35.42                    | 123                       | 79                         | Average |
| 2488                                                | 71.42                         | 69.41                   | 74                | -2.58          | 31.9                        | 5.53                  | 35.42                    | 123                       | 79                         | Peak    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                               |                         |                   |                |                             |                       |                          |                           |                            |         |
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB/m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2322                                                | 39.94                         | 38.43                   | 54                | -14.06         | 31.73                       | 5.3                   | 35.52                    | 119                       | 259                        | Average |
| 2322                                                | 56.24                         | 54.73                   | 74                | -17.76         | 31.73                       | 5.3                   | 35.52                    | 119                       | 259                        | Peak    |
| 2462                                                | 92.91                         | 90.98                   |                   |                | 31.87                       | 5.5                   | 35.44                    | 119                       | 259                        | Average |
| 2462                                                | 100.46                        | 98.53                   |                   |                | 31.87                       | 5.5                   | 35.44                    | 119                       | 259                        | Peak    |
| 2484                                                | 48.62                         | 46.66                   | 54                | -5.38          | 31.88                       | 5.5                   | 35.42                    | 119                       | 259                        | Average |
| 2484                                                | 67.21                         | 65.25                   | 74                | -6.79          | 31.88                       | 5.5                   | 35.42                    | 119                       | 259                        | Peak    |

**REMARKS:**

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
- 2462MHz: Fundamental frequency.

# 802.11n (40MHz)

| EUT TEST CONDITION       |                 | MEASUREMENT DETAIL |                           |
|--------------------------|-----------------|--------------------|---------------------------|
| CHANNEL                  | Channel 3       | FREQUENCY RANGE    | 1GHz ~ 25GHz              |
| INPUT POWER              | 120Vac, 60 Hz   | DETECTOR FUNCTION  | Peak (PK)<br>Average (AV) |
| ENVIRONMENTAL CONDITIONS | 25deg. C, 65%RH | TESTED BY          | Karl Lee                  |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                         |                   |                |             |                       |                 |                    |                     |                      |         |
|-----------------------------------------------------|-------------------------|-------------------|----------------|-------------|-----------------------|-----------------|--------------------|---------------------|----------------------|---------|
| FREQ. (MHz)                                         | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB/m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK  |
| 2390                                                | 51.68                   | 49.95             | 54             | -2.32       | 31.8                  | 5.4             | 35.47              | 114                 | 162                  | Average |
| 2390                                                | 63.66                   | 61.93             | 74             | -10.34      | 31.8                  | 5.4             | 35.47              | 114                 | 162                  | Peak    |
| 2422                                                | 92.85                   | 91.05             |                |             | 31.83                 | 5.43            | 35.46              | 142                 | 159                  | Average |
| 2422                                                | 100.82                  | 99.02             |                |             | 31.83                 | 5.43            | 35.46              | 142                 | 159                  | Peak    |
| 2500                                                | 42.18                   | 40.16             | 54             | -11.82      | 31.9                  | 5.53            | 35.41              | 142                 | 159                  | Average |
| 2500                                                | 55.92                   | 53.9              | 74             | -18.08      | 31.9                  | 5.53            | 35.41              | 142                 | 159                  | Peak    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                         |                   |                |             |                       |                 |                    |                     |                      |         |
| FREQ. (MHz)                                         | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB/m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK  |
| 2390                                                | 49.67                   | 47.94             | 54             | -4.33       | 31.8                  | 5.4             | 35.47              | 122                 | 159                  | Average |
| 2390                                                | 61.77                   | 60.04             | 74             | -12.23      | 31.8                  | 5.4             | 35.47              | 122                 | 159                  | Peak    |
| 2422                                                | 90.11                   | 88.31             |                |             | 31.83                 | 5.43            | 35.46              | 122                 | 159                  | Average |
| 2422                                                | 98.79                   | 96.99             |                |             | 31.83                 | 5.43            | 35.46              | 122                 | 159                  | Peak    |
| 2496                                                | 41.22                   | 39.2              | 54             | -12.78      | 31.9                  | 5.53            | 35.41              | 122                 | 159                  | Average |
| 2496                                                | 55.95                   | 53.93             | 74             | -18.05      | 31.9                  | 5.53            | 35.41              | 122                 | 159                  | Peak    |

## REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
- 2422MHz: Fundamental frequency.

| EUT TEST CONDITION       |                 | MEASUREMENT DETAIL |                           |
|--------------------------|-----------------|--------------------|---------------------------|
| CHANNEL                  | Channel 6       | FREQUENCY RANGE    | 1GHz ~ 25GHz              |
| INPUT POWER              | 120Vac, 60 Hz   | DETECTOR FUNCTION  | Peak (PK)<br>Average (AV) |
| ENVIRONMENTAL CONDITIONS | 25deg. C, 65%RH | TESTED BY          | Karl Lee                  |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                               |                         |                   |                |                             |                       |                          |                           |                            |         |
|-----------------------------------------------------|-------------------------------|-------------------------|-------------------|----------------|-----------------------------|-----------------------|--------------------------|---------------------------|----------------------------|---------|
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB/m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2390                                                | 50.76                         | 49.03                   | 54                | -3.24          | 31.8                        | 5.4                   | 35.47                    | 113                       | 159                        | Average |
| 2390                                                | 66.09                         | 64.36                   | 74                | -7.91          | 31.8                        | 5.4                   | 35.47                    | 113                       | 159                        | Peak    |
| 2437                                                | 96.29                         | 94.44                   |                   |                | 31.85                       | 5.46                  | 35.46                    | 142                       | 159                        | Average |
| 2437                                                | 103.24                        | 101.39                  |                   |                | 31.85                       | 5.46                  | 35.46                    | 142                       | 159                        | Peak    |
| 2484                                                | 50.16                         | 48.2                    | 54                | -3.84          | 31.88                       | 5.5                   | 35.42                    | 108                       | 188                        | Average |
| 2484                                                | 66.67                         | 64.71                   | 74                | -7.33          | 31.88                       | 5.5                   | 35.42                    | 108                       | 188                        | Peak    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                               |                         |                   |                |                             |                       |                          |                           |                            |         |
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB/m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2390                                                | 47.45                         | 45.72                   | 54                | -6.55          | 31.8                        | 5.4                   | 35.47                    | 105                       | 169                        | Average |
| 2390                                                | 58.1                          | 56.37                   | 74                | -15.9          | 31.8                        | 5.4                   | 35.47                    | 105                       | 169                        | Peak    |
| 2437                                                | 93.27                         | 91.42                   |                   |                | 31.85                       | 5.46                  | 35.46                    | 105                       | 169                        | Average |
| 2437                                                | 101.13                        | 99.28                   |                   |                | 31.85                       | 5.46                  | 35.46                    | 105                       | 169                        | Peak    |
| 2484                                                | 48.03                         | 46.07                   | 54                | -5.97          | 31.88                       | 5.5                   | 35.42                    | 105                       | 169                        | Average |
| 2484                                                | 56.42                         | 54.46                   | 74                | -17.58         | 31.88                       | 5.5                   | 35.42                    | 105                       | 169                        | Peak    |

**REMARKS:**

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
- 2437MHz: Fundamental frequency.

| EUT TEST CONDITION       |                 | MEASUREMENT DETAIL |                           |
|--------------------------|-----------------|--------------------|---------------------------|
| CHANNEL                  | Channel 9       | FREQUENCY RANGE    | 1GHz ~ 25GHz              |
| INPUT POWER              | 120Vac, 60 Hz   | DETECTOR FUNCTION  | Peak (PK)<br>Average (AV) |
| ENVIRONMENTAL CONDITIONS | 25deg. C, 65%RH | TESTED BY          | Karl Lee                  |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                               |                         |                   |                |                             |                       |                          |                           |                            |         |
|-----------------------------------------------------|-------------------------------|-------------------------|-------------------|----------------|-----------------------------|-----------------------|--------------------------|---------------------------|----------------------------|---------|
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB/m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2362                                                | 40.75                         | 39.12                   | 54                | -13.25         | 31.76                       | 5.37                  | 35.5                     | 123                       | 77                         | Average |
| 2362                                                | 55.13                         | 53.5                    | 74                | -18.87         | 31.76                       | 5.37                  | 35.5                     | 123                       | 77                         | Peak    |
| 2452                                                | 91.27                         | 89.4                    |                   |                | 31.85                       | 5.46                  | 35.44                    | 123                       | 77                         | Average |
| 2452                                                | 99.01                         | 97.14                   |                   |                | 31.85                       | 5.46                  | 35.44                    | 123                       | 77                         | Peak    |
| 2486                                                | 50.67                         | 48.68                   | 54                | -3.33          | 31.88                       | 5.53                  | 35.42                    | 123                       | 79                         | Average |
| 2486                                                | 67.33                         | 65.34                   | 74                | -6.67          | 31.88                       | 5.53                  | 35.42                    | 123                       | 79                         | Peak    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                               |                         |                   |                |                             |                       |                          |                           |                            |         |
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB/m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2350                                                | 40.93                         | 39.36                   | 54                | -13.07         | 31.74                       | 5.33                  | 35.5                     | 119                       | 259                        | Average |
| 2350                                                | 55.56                         | 53.99                   | 74                | -18.44         | 31.74                       | 5.33                  | 35.5                     | 119                       | 259                        | Peak    |
| 2452                                                | 89.43                         | 87.56                   |                   |                | 31.85                       | 5.46                  | 35.44                    | 119                       | 259                        | Average |
| 2452                                                | 97.11                         | 95.24                   |                   |                | 31.85                       | 5.46                  | 35.44                    | 119                       | 259                        | Peak    |
| 2484                                                | 49.36                         | 47.4                    | 54                | -4.64          | 31.88                       | 5.5                   | 35.42                    | 119                       | 259                        | Average |
| 2484                                                | 62.1                          | 60.14                   | 74                | -11.9          | 31.88                       | 5.5                   | 35.42                    | 119                       | 259                        | Peak    |

**REMARKS:**

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
- 2452MHz: Fundamental frequency.

**BELOW 1GHz WORST-CASE DATA:**

**802.11n (20MHz)**

| EUT TEST CONDITION       |                 | MEASUREMENT DETAIL |                           |
|--------------------------|-----------------|--------------------|---------------------------|
| CHANNEL                  | Channel 11      | FREQUENCY RANGE    | 30MHz ~ 1GHz              |
| INPUT POWER              | 120Vac, 60 Hz   | DETECTOR FUNCTION  | Peak (PK)<br>Average (AV) |
| ENVIRONMENTAL CONDITIONS | 25deg. C, 65%RH | TESTED BY          | Charles Hsiao             |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                               |                         |                   |                |                             |                       |                          |                           |                            |        |
|-----------------------------------------------------|-------------------------------|-------------------------|-------------------|----------------|-----------------------------|-----------------------|--------------------------|---------------------------|----------------------------|--------|
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB/m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK |
| 96.42                                               | 30.38                         | 51.72                   | 43.5              | -13.12         | 9.42                        | 1.28                  | 32.04                    | 120                       | 154                        | Peak   |
| 161.76                                              | 31.33                         | 51.42                   | 43.5              | -12.17         | 10.65                       | 1.52                  | 32.26                    | 161                       | 125                        | Peak   |
| 283.26                                              | 21.86                         | 38.18                   | 46                | -24.14         | 13.77                       | 2.03                  | 32.12                    | 186                       | 175                        | Peak   |
| 336.4                                               | 20.82                         | 34.92                   | 46                | -25.18         | 15.8                        | 2.19                  | 32.09                    | 164                       | 168                        | Peak   |
| 786.5                                               | 23.82                         | 28.58                   | 46                | -22.18         | 24.05                       | 3.27                  | 32.08                    | 120                       | 115                        | Peak   |
| 925.1                                               | 27.35                         | 28.91                   | 46                | -18.65         | 26.2                        | 3.53                  | 31.29                    | 174                       | 154                        | Peak   |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                               |                         |                   |                |                             |                       |                          |                           |                            |        |
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB/m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK |
| 54.57                                               | 32.65                         | 56.65                   | 40                | -7.35          | 7.33                        | 0.9                   | 32.23                    | 165                       | 174                        | Peak   |
| 90.48                                               | 28.93                         | 50.59                   | 43.5              | -14.57         | 8.94                        | 1.11                  | 31.71                    | 187                       | 165                        | Peak   |
| 163.65                                              | 20.11                         | 40.34                   | 43.5              | -23.39         | 10.51                       | 1.52                  | 32.26                    | 152                       | 158                        | Peak   |
| 337.1                                               | 17.23                         | 31.32                   | 46                | -28.77         | 15.8                        | 2.19                  | 32.08                    | 117                       | 147                        | Peak   |
| 699.7                                               | 23.89                         | 29.77                   | 46                | -22.11         | 23.1                        | 3.11                  | 32.09                    | 169                       | 211                        | Peak   |
| 881.7                                               | 24.4                          | 27.63                   | 46                | -21.6          | 24.88                       | 3.49                  | 31.6                     | 165                       | 216                        | Peak   |

**REMARKS:** Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor

Margin value = Emission level – Limit value

## 4.2 CONDUCTED EMISSION MEASUREMENT

### 4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

| FREQUENCY OF EMISSION (MHz) | CONDUCTED LIMIT (dB $\mu$ V) |          |
|-----------------------------|------------------------------|----------|
|                             | Quasi-peak                   | Average  |
| 0.15 ~ 0.5                  | 66 to 56                     | 56 to 46 |
| 0.5 ~ 5                     | 56                           | 46       |
| 5 ~ 30                      | 60                           | 50       |

- NOTE:** 1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

### 4.2.2 TEST INSTRUMENTS

| DESCRIPTION & MANUFACTURER              | MODEL NO.                | SERIAL NO.     | DATE OF CALIBRATION | DUE DATE OF CALIBRATION |
|-----------------------------------------|--------------------------|----------------|---------------------|-------------------------|
| Test Receiver<br>ROHDE & SCHWARZ        | ESCI                     | 100613         | Nov. 11, 2014       | Nov. 10, 2015           |
| RF signal cable<br>Woken                | 5D-FB                    | Cable-HYC01-01 | Dec. 26, 2014       | Dec. 25, 2015           |
| LISN<br>ROHDE & SCHWARZ<br>(EUT)        | ESH3-Z5                  | 835239/001     | Mar. 02, 2015       | Mar. 01, 2016           |
| LISN<br>ROHDE & SCHWARZ<br>(Peripheral) | ESH3-Z5                  | 100311         | Jul. 21, 2014       | Jul. 20, 2015           |
| Software<br>ADT                         | BV ADT_Cond_<br>V7.3.7.3 | NA             | NA                  | NA                      |

- NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Shielded Room 1.
3. The VCCI Site Registration No. is C-2040.

#### 4.2.3 TEST PROCEDURES


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

**NOTE:** All modes of operation were investigated and the worst-case emissions are reported.

#### 4.2.4 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.2.5 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
  2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.2.6 EUT OPERATING CONDITIONS

Same as section 4.1.6.

#### 4.2.7 TEST RESULTS


##### CONDUCTED WORST-CASE DATA :

|                 |                |                                          |                                      |
|-----------------|----------------|------------------------------------------|--------------------------------------|
| Frequency Range | 150kHz ~ 30MHz | Detector Function & Resolution Bandwidth | Quasi-Peak (QP) / Average (AV), 9kHz |
| Input Power     | 120Vac, 60Hz   | Environmental Conditions                 | 25°C, 65%RH                          |
| Tested by       | Toby Tian      | Test Date                                | 2015/6/18                            |

| Phase Of Power : Line (L) |                 |                        |                      |       |                       |       |              |       |             |        |
|---------------------------|-----------------|------------------------|----------------------|-------|-----------------------|-------|--------------|-------|-------------|--------|
| No                        | Frequency (MHz) | Correction Factor (dB) | Reading Value (dBuV) |       | Emission Level (dBuV) |       | Limit (dBuV) |       | Margin (dB) |        |
|                           |                 |                        | Q.P.                 | AV.   | Q.P.                  | AV.   | Q.P.         | AV.   | Q.P.        | AV.    |
| 1                         | 0.18508         | 0.06                   | 35.85                | 23.77 | 35.91                 | 23.83 | 64.25        | 54.25 | -28.35      | -30.43 |
| 2                         | 0.22820         | 0.06                   | 33.99                | 24.39 | 34.05                 | 24.45 | 62.51        | 52.51 | -28.46      | -28.06 |
| 3                         | 0.50581         | 0.06                   | 36.52                | 26.78 | 36.58                 | 26.84 | 56.00        | 46.00 | -19.42      | -19.16 |
| 4                         | 0.64657         | 0.07                   | 34.08                | 24.23 | 34.15                 | 24.30 | 56.00        | 46.00 | -21.85      | -21.70 |
| 5                         | 4.35325         | 0.21                   | 30.54                | 21.60 | 30.75                 | 21.81 | 56.00        | 46.00 | -25.25      | -24.19 |
| 6                         | 9.68258         | 0.44                   | 33.20                | 23.66 | 33.64                 | 24.10 | 60.00        | 50.00 | -26.36      | -25.90 |

##### Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




|                 |                |                                          |                                      |
|-----------------|----------------|------------------------------------------|--------------------------------------|
| Frequency Range | 150kHz ~ 30MHz | Detector Function & Resolution Bandwidth | Quasi-Peak (QP) / Average (AV), 9kHz |
| Input Power     | 120Vac, 60Hz   | Environmental Conditions                 | 25°C, 65%RH                          |
| Tested by       | Toby Tian      | Test Date                                | 2015/6/18                            |

| Phase Of Power : Neutral (N) |                 |                        |                      |              |                       |              |              |              |               |               |
|------------------------------|-----------------|------------------------|----------------------|--------------|-----------------------|--------------|--------------|--------------|---------------|---------------|
| No                           | Frequency (MHz) | Correction Factor (dB) | Reading Value (dBuV) |              | Emission Level (dBuV) |              | Limit (dBuV) |              | Margin (dB)   |               |
|                              |                 |                        | Q.P.                 | AV.          | Q.P.                  | AV.          | Q.P.         | AV.          | Q.P.          | AV.           |
| 1                            | 0.17346         | 0.05                   | 40.46                | 30.15        | 40.51                 | 30.20        | 64.79        | 54.79        | -24.28        | -24.59        |
| 2                            | 0.21256         | 0.05                   | 36.68                | 26.83        | 36.73                 | 26.88        | 63.10        | 53.10        | -26.37        | -26.22        |
| <b>3</b>                     | <b>0.49799</b>  | <b>0.06</b>            | <b>34.24</b>         | <b>28.46</b> | <b>34.30</b>          | <b>28.52</b> | <b>56.03</b> | <b>46.03</b> | <b>-21.73</b> | <b>-17.51</b> |
| 4                            | 0.63093         | 0.07                   | 31.07                | 22.40        | 31.14                 | 22.47        | 56.00        | 46.00        | -24.86        | -23.53        |
| 5                            | 4.80681         | 0.22                   | 27.91                | 21.60        | 28.13                 | 21.82        | 56.00        | 46.00        | -27.87        | -24.18        |
| 6                            | 9.18992         | 0.39                   | 31.50                | 22.88        | 31.89                 | 23.27        | 60.00        | 50.00        | -28.11        | -26.73        |

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



### 4.3 CONDUCTED OUTPUT POWER

#### 4.3.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

Per KDB 662911 D01 Multiple Transmitter Output v02r01 Method of conducted output power measurement on IEEE 802.11 devices,


Array Gain = 0 dB (i.e., no array gain) for  $NANT \leq 4$ ;

Array Gain = 0 dB (i.e., no array gain) for channel widths  $\geq 40$  MHz for any NANT;

Array Gain =  $5 \log(NANT/NSS)$  dB or 3 dB, whichever is less for 20-MHz channel widths with  $NANT \geq 5$ .

For power measurements on all other devices: Array Gain =  $10 \log(NANT/NSS)$  dB.

#### 4.3.2 TEST SETUP



#### 4.3.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

#### 4.3.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the peak power level.

#### 4.3.5 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

#### 4.3.7 TEST RESULTS

##### FOR 2TX USE

##### 802.11b

| CHAN. | FREQ.<br>(MHz) | PEAK POWER (dBm) |         | TOTAL<br>POWER<br>(mW) | TOTAL<br>POWER<br>(dBm) | LIMIT<br>(dBm) | PASS / FAIL |
|-------|----------------|------------------|---------|------------------------|-------------------------|----------------|-------------|
|       |                | CHAIN 0          | CHAIN 1 |                        |                         |                |             |
| 1     | 2412           | 15.37            | 16.21   | 76.218                 | 18.82                   | 30             | PASS        |
| 6     | 2437           | 14.86            | 15.45   | 65.695                 | 18.18                   | 30             | PASS        |
| 11    | 2462           | 5.00             | 15.43   | 38.076                 | 15.81                   | 30             | PASS        |

##### 802.11g

| CHAN. | FREQ.<br>(MHz) | PEAK POWER (dBm) |         | TOTAL<br>POWER<br>(mW) | TOTAL<br>POWER<br>(dBm) | LIMIT<br>(dBm) | PASS / FAIL |
|-------|----------------|------------------|---------|------------------------|-------------------------|----------------|-------------|
|       |                | CHAIN 0          | CHAIN 1 |                        |                         |                |             |
| 1     | 2412           | 23.39            | 23.14   | 424.336                | 26.28                   | 30             | PASS        |
| 6     | 2437           | 24.93            | 24.92   | <b>621.628</b>         | 27.94                   | 30             | PASS        |
| 11    | 2462           | 22.53            | 23.14   | 385.124                | 25.86                   | 30             | PASS        |

##### 802.11n (20MHz)

| CHAN. | FREQ.<br>(MHz) | PEAK POWER (dBm) |         | TOTAL<br>POWER<br>(mW) | TOTAL<br>POWER<br>(dBm) | LIMIT<br>(dBm) | PASS / FAIL |
|-------|----------------|------------------|---------|------------------------|-------------------------|----------------|-------------|
|       |                | CHAIN 0          | CHAIN 1 |                        |                         |                |             |
| 1     | 2412           | 21.58            | 21.53   | 286.113                | 24.57                   | 30             | PASS        |
| 6     | 2437           | 24.88            | 24.95   | 620.218                | 27.93                   | 30             | PASS        |
| 11    | 2462           | 20.88            | 20.68   | 239.412                | 23.79                   | 30             | PASS        |

##### 802.11n (40MHz)

| CHAN. | FREQ.<br>(MHz) | PEAK POWER (dBm) |         | TOTAL<br>POWER<br>(mW) | TOTAL<br>POWER<br>(dBm) | LIMIT<br>(dBm) | PASS / FAIL |
|-------|----------------|------------------|---------|------------------------|-------------------------|----------------|-------------|
|       |                | CHAIN 0          | CHAIN 1 |                        |                         |                |             |
| 3     | 2422           | 18.85            | 19.72   | 170.492                | 22.32                   | 30             | PASS        |
| 6     | 2437           | 22.40            | 21.76   | 323.749                | 25.10                   | 30             | PASS        |
| 9     | 2452           | 18.04            | 18.50   | 134.474                | 21.29                   | 30             | PASS        |

## 5. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).

## 6. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab:**

Tel: 886-2-26052180

Fax: 886-2-26051924

**Hsin Chu EMC/RF/Telecom Lab:**

Tel: 886-3-5935343

Fax: 886-3-5935342

**Hwa Ya EMC/RF/Safety Lab:**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.

## **7. APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB**

No any modifications are made to the EUT by the lab during the test.

**---END---**