



FCC RADIO TEST REPORT

FCC ID : A4RGGH2X
Equipment : Phone
Model Name : GGH2X, GC15S
Applicant : Google LLC
1600 Amphitheatre Parkway,
Mountain View, CA 94043 USA
Standard : FCC Part 15 Subpart C §15.247

The product was received on Feb. 05, 2024 and testing was performed from Feb. 07, 2024 to May 27, 2024. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

Sporton International Inc. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT	7
1.3 Testing Location	7
1.4 Applicable Standards.....	7
2 Test Configuration of Equipment Under Test	8
2.1 Carrier Frequency and Channel	8
2.2 Test Mode.....	9
2.3 Connection Diagram of Test System.....	12
2.4 Support Unit used in test configuration and system	13
2.5 EUT Operation Test Setup	13
2.6 Measurement Results Explanation Example.....	13
3 Test Result	14
3.1 6dB and 99% Bandwidth Measurement	14
3.2 Output Power Measurement.....	15
3.3 Power Spectral Density Measurement	16
3.4 Conducted Band Edges and Spurious Emission Measurement	17
3.5 Radiated Band Edges and Spurious Emission Measurement	18
3.6 AC Conducted Emission Measurement.....	22
3.7 Antenna Requirements	24
4 List of Measuring Equipment.....	25
5 Measurement Uncertainty	27
Appendix A. Conducted Test Results	
Appendix B. AC Conducted Emission Test Result	
Appendix C. Radiated Spurious Emission	
Appendix D. Radiated Spurious Emission Plots	
Appendix E. Duty Cycle Plots	
Appendix F. Setup Photographs	



History of this test report

Report No.	Version	Description	Issue Date
FR3D2001C	01	Initial issue of report	May 10, 2024
FR3D2001C	02	Revise section 1, section 2, section 3.5.1, Appendix A and Appendix C This report is an updated version, replacing the report issued on May 10, 2024.	May 24, 2024
FR3D2001C	03	Revise List of Measuring Equipment Appendix A, C and D This report is an updated version, replacing the report issued on May 24, 2024.	May 28, 2024

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(2)	6dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Reporting only	-
3.2	15.247(b)	Power Output Measurement	Pass	-
3.3	15.247(e)	Power Spectral Density	Pass	-
3.4	15.247(d)	Conducted Band Edges	Pass	-
		Conducted Spurious Emission	Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	Pass	1.56 dB under the limit at 2390.00 MHz
3.6	15.207	AC Conducted Emission	Pass	11.41 dB under the limit at 0.18 MHz
3.7	15.203	Antenna Requirement	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

1. The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.
2. The GGH2X and GC15S are 100% identical in Hardware / Software to each other, and only have different model names for marketing segmentation. The test sample are all model GGH2X.

Reviewed by: William Chen

Report Producer: Wilda Wei

1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature
General Specs GSM/WCDMA/LTE/5G NR, Bluetooth, BLE, BLE channel sounding, Thread, Wi-Fi 802.11be, UWB, NFC, WPC Rx, NTN and GNSS.
Antenna Type WLAN: <Ant. 3> : IFA Antenna <Ant. 4> : ILA Antenna

EUT Information List	
S/N	Performed Test Item
41251FDKD000B1	RF Conducted Measurement
41251FDKD0007K	Radiated Spurious Emission
	Conducted Emission

Antenna information (Open mode)		
2400 MHz ~ 2483.5 MHz	Peak Gain (dBi)	Ant. 3: -3.3
		Ant. 4: -3.5

Antenna information (Close mode)		
2400 MHz ~ 2483.5 MHz	Peak Gain (dBi)	Ant. 3: -4.3
		Ant. 4: -1.2

Remark: The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.

1.1.1 Antenna Directional Gain

<For CDD Mode>

Follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01 F2)f)ii)

Directional gain = G_{ANT} + Array Gain, where Array Gain is as follows:

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$.

G_{ANT} is set equal to the gain of the antenna having the highest gain.

For PSD measurements, the directional gain calculation.

$$DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$$

where

Each antenna is driven by no more than one spatial stream;

N_{SS} = the number of independent spatial streams of data;

N_{ANT} = the total number of antennas

$g_{j,k} = 10^{G_k/20}$ if the k th antenna is being fed by spatial stream j , or zero if it is not;
 G_k is the gain in dBi of the k th antenna.

As minimum $N_{SS}=1$ is supported by EUT, the formula can be simplified as:

Directional gain = $10 \cdot \log[(10^{G_1/20} + 10^{G_2/20} + \dots + 10^{G_N/20})^2 / N_{ANT}]$ dBi

Where G_1, G_2, \dots, G_N denote single antenna gain.

The directional gain "DG" is calculated as following table.

			DG for Power	DG for PSD	Power Limit Reduction	PSD Limit Reduction
	Ant 3 (dBi)	Ant 4 (dBi)	(dBi)	(dBi)	(dB)	(dB)
2.4GHz	-3.30	-1.20	-1.20	0.82	0.00	0.00

Calculation example:

If a device has two antenna, $G_{ANT3} = -3.30$ dBi; $G_{ANT4} = -1.2$ dBi

Directional gain of power measurement = $\max(-3.30, -1.2) + 0 = -1.2$ dBi

Directional gain of PSD derived from formula which is

$$10 \times \log \left\{ \left[10^{(-3.30 \text{ dBi} / 20)} + 10^{(-1.2 \text{ dBi} / 20)} \right]^2 / 2 \right\}$$

$$= 0.82 \text{ dBi}$$

Power and PSD limit reduction = Composite gain – 6dBi, (min = 0)

Note: The antenna gain is from both open mode and close mode with highest number.



1.2 Modification of EUT

No modifications made to the EUT during the testing.

1.3 Testing Location

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No.
	TH05-HY, CO07-HY, 03CH23-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW3786

1.4 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 15.247 Meas Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01.
- ♦ FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ♦ ANSI C63.10-2013

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.



2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT (Open and Close) and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape) and accessory (Adapter or Earphone), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and find open mode X plane with Adapter as worst plane.
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	8	2447
	2	2417	9	2452
	3	2422	10	2457
	4	2427	11	2462
	5	2432	12	2467
	6	2437	13	2472
	7	2442		

2.2 Test Mode

This device supports WiFi 802.11be 20MHz bandwidth for 2.4GHz.

This device supports 26/52/106/242 single tone RU modes for 802.11ax/be modes and the 242-tone RU modes are covered by 20MHz channels.

The PSD of partial RU modes are reduced to be smaller than full RU according to TCB workshop interim guidance Oct. 2022.

The 802.11ax/be modes are investigated among full RU and single RU modes for emission spot check and the 11ax modes are covered by 11be modes.

The PSD and power of partial RU are less than full RU configurations so the full RU is chosen as main test configuration.

The SISO mode conducted power is covered by MIMO mode per chain, so only the MIMO mode is chosen as main test configuration.

The power of 802.11n, 802.11ac and 802.11ax modes are less than 802.11be mode, so all conducted and radiated tests are covered by 802.11be mode.

The final test modes include the worst data rates for each modulation shown in the table below.

Single Antenna

Modulation	Data Rate
802.11b	1 Mbps

MIMO Antenna

Modulation	Data Rate
802.11g	6 Mbps
802.11n HT20 (Covered by EHT20)	MCS0
802.11n VHT20 (Covered by EHT20)	MCS0
802.11ax HE20 (Covered by EHT20)	MCS0
802.11be EHT20	MCS0

Test Cases	
AC Conducted Emission	Mode 1 : WLAN (2.4GHz) 11B Channel 6 TX + USB Cable 1 (Charging from AC Adapter)
Remark: <ol style="list-style-type: none"> For Radiated Test Cases, the tests were performed with USB Cable 1. During the preliminary test, both charging modes (Adapter mode and WPC Rx Charging mode) were verified. It is determined that the adaptor mode is the worst case for official test. 	



Index of MRU and puncture mode mapping

Small MRU

MRU	26T	52T	106T
52T+26T	70	71	72
106T+26T	82	83	

Large MRU

484+242-tone MRU			
2	1	4	3
80MHz puncture 20			
8	4	2	1

(High Frequency) ----- (Low Frequency)

484+242-tone MRU							
2	1	4	3	6	5	8	7
160MHz puncture 20							
128	64	32	16	8	4	2	1

(High Frequency) ----- (Low Frequency)

996+484-tone MRU			
2	1	4	3
160MHz puncture 40			
192	48	12	3

(High Frequency) ----- (Low Frequency)

Note: The RF waveform is identical for large MRU and puncture modes.

<Ant. 3>

Ch. #	2400-2483.5 MHz
	802.11b
Low	01
Middle	06
High	11
	12
	13

<Ant. 4>

Ch. #	2400-2483.5 MHz
	802.11b
Low	01
Middle	06
High	11
	12
	13


MIMO <Ant. 3+4>

Ch. #	2400-2483.5 MHz	
	802.11g	802.11be EHT20
Low	01	01
Middle	06	06
High	11	11
	12	12
	13	13


Remark: For radiation spurious emission, the modulation and the data rate picked for testing are determined by the Max. RF conducted power.

2.3 Connection Diagram of Test System

<AC Conducted Emission Mode>



<WLAN Tx Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Adapter	Chicony	G9BR1	N/A	N/A	N/A

2.5 EUT Operation Test Setup

The RF test items, utility "WLAN_DUT_Control_GUI_11-29-23.exe" was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW) $\geq 3 * RBW$.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5 MHz, the limit for output power is 30 dBm. If transmitting antenna with directional gain greater than 6 dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.


3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.2.3 Test Procedures

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G
2. The RF output of EUT is connected to the power meter by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Measure the conducted output power and record the results in the test report.
5. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

3.2.4 Test Setup



3.2.5 Test Result of Average Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8 dBm in any 3 kHz band at any time interval of continuous transmission.

3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.


3.3.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

Method (c): Measure and add $10 \log(N_{ANT})$ dB.

With this technique, spectrum measurements are performed at each output of the device, but rather than summing the spectra or the spectral peaks across the outputs, the quantity $10 \log(N_{ANT})$ dB is added to each spectrum value before comparing to the emission limit. The addition of $10 \log(N_{ANT})$ dB serves to apportion the emission limit among the N_{ANT} outputs so that each output is permitted to contribute no more than $1/N_{ANT}^{th}$ of the PSD limit .

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.


3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.4.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Please refer to Appendix A.

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required shall be 30dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.5.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT is arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
4. The EUT is set 3 meters away from the receiving antenna, which is mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as “-”.


7. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as “-”.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW = 100 kHz for $f < 1$ GHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3 MHz for $f \geq 1$ GHz for peak measurement.

For average measurement:


 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz




For radiated emissions from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which starts from 9 kHz to 30 MHz, is pre-scanned and the result which is 20 dB lower than the limit line is not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result comes out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

3.5.7 Duty Cycle

Please refer to Appendix E.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C and D.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.6.3 Test Procedures

1. The EUT is placed 0.4 meter away from the conducting wall of the shielding room, and is kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both Line and Neutral shall be tested in order to find out the maximum conducted emission.
7. The frequency range from 150 kHz to 30 MHz is scanned.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9kHz~30MHz	Sep. 12, 2023	Feb. 07, 2024~ May 27, 2024	Sep. 11, 2024	Radiation (03CH23-HY)
Bilog Antenna with 6dB pad	TESEQ & WOKEN	CBL 6111D & 00802N1D-06	62028 & 003	N/A	Oct. 15, 2023	Feb. 07, 2024~ May 27, 2024	Oct. 14, 2024	Radiation (03CH23-HY)
Amplifier	SONOMA	310N	421582	N/A	Jul. 15, 2023	Feb. 07, 2024~ May 27, 2024	Jul. 14, 2024	Radiation (03CH23-HY)
Double Ridged Guide Horn Antenna	RFSPIN	DRH18-E	LE2C05A18EN	1GHz~18GHz	Jul. 12, 2023	Feb. 07, 2024~ May 27, 2024	Jul. 11, 2024	Radiation (03CH23-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA9170	1225	18GHz-40GHz	Jul. 10, 2023	Feb. 07, 2024~ May 27, 2024	Jul. 09, 2024	Radiation (03CH23-HY)
Amplifier	EMEC	EM01G18GA	060877	N/A	Sep. 28, 2023	Feb. 07, 2024~ May 27, 2024	Sep. 27, 2024	Radiation (03CH23-HY)
Preamplifier	EMEC	EM18G40G	060871	18-40GHz	Aug. 30, 2023	Feb. 07, 2024~ May 27, 2024	Aug. 29, 2024	Radiation (03CH23-HY)
Signal Analyzer	Keysight	N9010B	MY62170337	N/A	Aug. 17, 2023	Feb. 07, 2024~ May 27, 2024	Aug. 16, 2024	Radiation (03CH23-HY)
Hygrometer	TECPEL	DTM-303B	TP211542	N/A	Oct. 30, 2023	Feb. 07, 2024~ May 27, 2024	Oct. 29, 2024	Radiation (03CH23-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	N/A	Feb. 07, 2024~ May 27, 2024	N/A	Radiation (03CH23-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	Feb. 07, 2024~ May 27, 2024	N/A	Radiation (03CH23-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	Feb. 07, 2024~ May 27, 2024	N/A	Radiation (03CH23-HY)
Software	Audix	E3 6.09824_20191 22	RK-002348	N/A	N/A	Feb. 07, 2024~ May 27, 2024	N/A	Radiation (03CH23-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	803951/2	9kHz~30MHz	Mar. 07, 2023	Feb. 07, 2024~ Mar. 05, 2024	Mar. 06, 2024	Radiation (03CH23-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	803951/2	9kHz~30MHz	Mar. 06, 2024	Mar. 06, 2024~ May 27, 2024	Mar. 05, 2025	Radiation (03CH23-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	804395/2	N/A	Nov. 27, 2023	Feb. 07, 2024~ May 27, 2024	Nov. 26, 2024	Radiation (03CH23-HY)
RF Cable	EMC	EMC101Y	231115/231119 /231122	N/A	Nov. 27, 2023	Feb. 07, 2024~ May 27, 2024	Nov. 26, 2024	Radiation (03CH23-HY)
AC Power Source	ACPOWER	AFC-11003G	F317040033	N/A	N/A	Mar. 20, 2024~ Mar. 22, 2024	N/A	Conduction (CO07-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Mar. 20, 2024~ Mar. 22, 2024	N/A	Conduction (CO07-HY)
Pulse Limiter	SCHWARZBE CK	VTSD 9561-F N	9561-F N00373	9kHz-200MHz	Oct. 20, 2023	Mar. 20, 2024~ Mar. 22, 2024	Oct. 19, 2024	Conduction (CO07-HY)
RF Cable	HUBER + SUHNER	RG 214/U	1358175	9kHz~30MHz	Mar. 15, 2023	Mar. 20, 2024~ Mar. 22, 2024	Mar. 14, 2024	Conduction (CO07-HY)
Two-Line V-Network	TESEQ	NNB 51	45051	N/A	Mar. 10, 2024	Mar. 20, 2024~ Mar. 22, 2024	Mar. 09, 2025	Conduction (CO07-HY)
Four-Line V-Network	TESEQ	NNB 52	36122	N/A	Mar. 07, 2024	Mar. 20, 2024~ Mar. 22, 2024	Mar. 06, 2025	Conduction (CO07-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102317	9kHz~3.6GHz	Sep. 20, 2023	Mar. 20, 2024~ Mar. 22, 2024	Sep. 19, 2024	Conduction (CO07-HY)



Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Hygrometer	TECPEL	DTM-303A	TP201996	N/A	Nov. 07, 2023	Feb. 20, 2024~ Feb. 28, 2024	Nov. 06, 2024	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	15I00041SNO 10 (NO:248)	10MHz~6GHz	Jun. 05, 2023	Feb. 20, 2024~ Feb. 28, 2024	Jun. 04, 2024	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101566	10Hz~40GHz	Aug. 23, 2023	Feb. 20, 2024~ Feb. 28, 2024	Aug. 22, 2024	Conducted (TH05-HY)

5 Measurement Uncertainty

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.44 dB
---	---------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	6.50 dB
---	---------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 6000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.60 dB
---	---------

Uncertainty of Radiated Emission Measurement (6000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.60 dB
---	---------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.30 dB
---	---------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Mina Liu	Temperature:	21~25	°C
Test Date:	2024/2/20~2024/2/28	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

2.4GHz Band Single Antenna										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)		6dB BW (MHz)		6dB BW Limit (MHz)	Pass/Fail
					Ant3	Ant4	Ant3	Ant4		
11b	1Mbps	1	1	2412	13.09	13.09	9.04	9.03	0.50	Pass
11b	1Mbps	1	6	2437	12.99	12.89	8.52	9.01	0.50	Pass
11b	1Mbps	1	11	2462	13.14	12.99	8.56	8.05	0.50	Pass
11b	1Mbps	1	12	2467	12.94	13.49	8.05	9.02	0.50	Pass
11b	1Mbps	1	13	2472	12.94	12.79	8.55	8.54	0.50	Pass

2.4GHz Band MIMO										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)		6dB BW (MHz)		6dB BW Limit (MHz)	Pass/Fail
					Ant3	Ant4	Ant3	Ant4		
11g	6Mbps	2	1	2412	16.78	16.68	15.62	15.11	0.50	Pass
11g	6Mbps	2	6	2437	18.18	18.03	15.12	15.12	0.50	Pass
11g	6Mbps	2	11	2462	16.73	16.78	15.36	15.10	0.50	Pass
11g	6Mbps	2	12	2467	16.63	16.48	15.16	15.15	0.50	Pass
11g	6Mbps	2	13	2472	16.63	16.43	15.13	15.42	0.50	Pass

TEST RESULTS DATA
Average Output Power

2.4GHz Band Single Antenna																
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Average Conducted Power (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail
					Ant3	Ant4	SUM	Ant3	Ant4	Ant3	Ant4	Ant3	Ant4	Ant3	Ant4	
11b	1Mbps	1	1	2412	22.35	21.65		30.00	30.00	-3.3	-1.2	19.05	20.45	36.00	36.00	Pass
11b	1Mbps	1	6	2437	23.85	23.95		30.00	30.00	-3.3	-1.2	20.55	22.75	36.00	36.00	Pass
11b	1Mbps	1	11	2462	22.55	22.95		30.00	30.00	-3.3	-1.2	19.25	21.75	36.00	36.00	Pass
11b	1Mbps	1	12	2467	21.05	21.45		30.00	30.00	-3.3	-1.2	17.75	20.25	36.00	36.00	Pass
11b	1Mbps	1	13	2472	18.55	16.35		30.00	30.00	-3.3	-1.2	15.25	15.15	36.00	36.00	Pass

2.4GHz Band MIMO																
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Average Conducted Power (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail
					Ant3	Ant4	SUM	Ant3	Ant4	Ant3	Ant4	Ant3	Ant4	Ant3	Ant4	
11g	6Mbps	2	1	2412	18.65	19.25	21.97	30.00		-1.2		20.77		36.00		Pass
11g	6Mbps	2	6	2437	21.75	21.85	24.81	30.00		-1.2		23.61		36.00		Pass
11g	6Mbps	2	11	2462	17.95	18.85	21.43	30.00		-1.2		20.23		36.00		Pass
11g	6Mbps	2	12	2467	15.85	16.45	19.17	30.00		-1.2		17.97		36.00		Pass
11g	6Mbps	2	13	2472	10.05	10.75	13.42	30.00		-1.2		12.22		36.00		Pass
HT20	MCS0	2	1	2412	17.45	18.15	20.82	30.00		-1.2		19.62		36.00		Pass
HT20	MCS0	2	6	2437	20.65	20.85	23.76	30.00		-1.2		22.56		36.00		Pass
HT20	MCS0	2	11	2462	15.45	16.45	18.99	30.00		-1.2		17.79		36.00		Pass
HT20	MCS0	2	12	2467	14.25	14.95	17.62	30.00		-1.2		16.42		36.00		Pass
HT20	MCS0	2	13	2472	12.35	12.65	15.51	30.00		-1.2		14.31		36.00		Pass
VHT20	MCS0	2	1	2412	17.45	18.15	20.82	30.00		-1.2		19.62		36.00		Pass
VHT20	MCS0	2	6	2437	20.65	20.85	23.76	30.00		-1.2		22.56		36.00		Pass
VHT20	MCS0	2	11	2462	15.45	16.45	18.99	30.00		-1.2		17.79		36.00		Pass
VHT20	MCS0	2	12	2467	14.25	14.95	17.62	30.00		-1.2		16.42		36.00		Pass
VHT20	MCS0	2	13	2472	12.35	12.65	15.51	30.00		-1.2		14.31		36.00		Pass

Note: Measured power (dBm) has offset with cable loss.

TEST RESULTS DATA
Peak Power Spectral Density

2.4GHz Band Single Antenna												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm/3kHz)			DG (dBi)		Peak PSD Limit (dBm/3kHz)		Pass/Fail
					Ant3	Ant4	Worse + 3.01	Ant3	Ant4	Ant3	Ant4	
11b	1Mbps	1	1	2412	-0.18	-0.29		-3.3	-1.2	8.00	8.00	Pass
11b	1Mbps	1	6	2437	-2.97	-2.57		-3.3	-1.2	8.00	8.00	Pass
11b	1Mbps	1	11	2462	-0.11	-2.45		-3.3	-1.2	8.00	8.00	Pass
11b	1Mbps	1	12	2467	-1.34	1.15		-3.3	-1.2	8.00	8.00	Pass
11b	1Mbps	1	13	2472	-4.31	-2.52		-3.3	-1.2	8.00	8.00	Pass

2.4GHz Band MIMO												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm/3kHz)			DG (dBi)		Peak PSD Limit (dBm/3kHz)		Pass/Fail
					Ant3	Ant4	Worse + 3.01	Ant3	Ant4	Ant3	Ant4	
11g	6Mbps	2	1	2412	-5.41	-4.82	-1.81	0.82		8.00		Pass
11g	6Mbps	2	6	2437	-2.68	-2.53	0.48	0.82		8.00		Pass
11g	6Mbps	2	11	2462	-6.40	-5.98	-2.97	0.82		8.00		Pass
11g	6Mbps	2	12	2467	-8.64	-7.43	-4.42	0.82		8.00		Pass
11g	6Mbps	2	13	2472	-14.29	-13.27	-10.26	0.82		8.00		Pass

Measured power density (dBm) has offset with cable loss.

TEST RESULTS DATA
Average Output Power

2.4GHz Band MIMO																	
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	RU Config	Average Conducted Power (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail
						Ant3	Ant4	SUM	Ant3	Ant4	Ant3	Ant4	Ant3	Ant4	Ant3	Ant4	
HE20	MCS0	2	1	2412	Full	17.45	18.15	20.82	30.00		-1.2		19.62		36.00		Pass
HE20	MCS0	2	6	2437	Full	20.65	20.85	23.76	30.00		-1.2		22.56		36.00		Pass
HE20	MCS0	2	11	2462	Full	15.45	16.45	18.99	30.00		-1.2		17.79		36.00		Pass
HE20	MCS0	2	12	2467	Full	14.25	14.95	17.62	30.00		-1.2		16.42		36.00		Pass
HE20	MCS0	2	13	2472	Full	12.35	12.65	15.51	30.00		-1.2		14.31		36.00		Pass

Note: Measured power (dBm) has offset with cable loss.

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

2.4GHz Band MIMO											
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	RU Config.	99% Occupied BW (MHz)		6dB BW (MHz)		6dB BW Limit (MHz)	Pass/Fail
						Ant3	Ant4	Ant3	Ant4		
EHT20	MCS0	2	1	2412	Full	18.98	18.98	18.87	18.75	0.50	Pass
EHT20	MCS0	2	6	2437	Full	19.28	19.23	18.57	18.63	0.50	Pass
EHT20	MCS0	2	11	2462	Full	18.98	18.98	18.86	18.87	0.50	Pass
EHT20	MCS0	2	12	2467	Full	18.98	18.93	18.43	18.27	0.50	Pass
EHT20	MCS0	2	13	2472	Full	18.93	18.93	18.80	18.22	0.50	Pass

TEST RESULTS DATA
Average Output Power

2.4GHz Band MIMO																	
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	RU Config.	Average Conducted Power (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail
						Ant3	Ant4	SUM	Ant3	Ant4	Ant3	Ant4	Ant3	Ant4	Ant3	Ant4	
EHT20	MCS0	2	1	2412	Full	17.55	18.25	20.92	30.00		-1.2		19.72	36.00		Pass	
EHT20	MCS0	2	1	2412	26/0	8.75	9.25	12.02	30.00		-1.2		10.82	36.00		Pass	
EHT20	MCS0	2	1	2412	52/37	10.75	11.35	14.07	30.00		-1.2		12.87	36.00		Pass	
EHT20	MCS0	2	1	2412	106/53	13.05	14.05	16.59	30.00		-1.2		15.39	36.00		Pass	
EHT20	MCS0	2	1	2412	52T+26T/70	11.65	12.55	15.13	30.00		-1.2		13.93	36.00		Pass	
EHT20	MCS0	2	1	2412	106T+26T/82	14.05	14.95	17.53	30.00		-1.2		16.33	36.00		Pass	
EHT20	MCS0	2	6	2437	Full	20.75	20.95	23.86	30.00		-1.2		22.66	36.00		Pass	
EHT20	MCS0	2	6	2437	4/26	14.05	14.55	17.32	30.00		-1.2		16.12	36.00		Pass	
EHT20	MCS0	2	6	2437	52/38	16.75	17.05	19.91	30.00		-1.2		18.71	36.00		Pass	
EHT20	MCS0	2	6	2437	106/53	19.25	19.15	22.21	30.00		-1.2		21.01	36.00		Pass	
EHT20	MCS0	2	6	2437	52T+26T/71	17.25	17.55	20.41	30.00		-1.2		19.21	36.00		Pass	
EHT20	MCS0	2	6	2437	106T+26T/83	19.65	20.35	23.02	30.00		-1.2		21.82	36.00		Pass	
EHT20	MCS0	2	11	2462	Full	15.55	16.55	19.09	30.00		-1.2		17.89	36.00		Pass	
EHT20	MCS0	2	11	2462	8/26	6.55	7.85	10.26	30.00		-1.2		9.06	36.00		Pass	
EHT20	MCS0	2	11	2462	52/40	9.55	10.55	13.09	30.00		-1.2		11.89	36.00		Pass	
EHT20	MCS0	2	11	2462	106/54	11.85	12.85	15.39	30.00		-1.2		14.19	36.00		Pass	
EHT20	MCS0	2	11	2462	52T+26T/72	10.55	11.15	13.87	30.00		-1.2		12.67	36.00		Pass	
EHT20	MCS0	2	11	2462	106T+26T/83	13.05	13.25	16.16	30.00		-1.2		14.96	36.00		Pass	
EHT20	MCS0	2	12	2467	Full	14.35	15.05	17.72	30.00		-1.2		16.52	36.00		Pass	
EHT20	MCS0	2	12	2467	8/26	5.55	5.05	8.32	30.00		-1.2		7.12	36.00		Pass	
EHT20	MCS0	2	12	2467	52/40	9.05	9.65	12.37	30.00		-1.2		11.17	36.00		Pass	
EHT20	MCS0	2	12	2467	106/54	11.85	12.45	15.17	30.00		-1.2		13.97	36.00		Pass	
EHT20	MCS0	2	12	2467	52T+26T/72	10.05	10.55	13.32	30.00		-1.2		12.12	36.00		Pass	
EHT20	MCS0	2	12	2467	106T+26T/83	12.05	12.55	15.32	30.00		-1.2		14.12	36.00		Pass	
EHT20	MCS0	2	13	2472	Full	12.45	12.75	15.61	30.00		-1.2		14.41	36.00		Pass	
EHT20	MCS0	2	13	2472	8/26	4.65	3.05	6.93	30.00		-1.2		5.73	36.00		Pass	
EHT20	MCS0	2	13	2472	52/40	6.65	7.05	9.86	30.00		-1.2		8.66	36.00		Pass	
EHT20	MCS0	2	13	2472	106/54	9.05	9.45	12.26	30.00		-1.2		11.06	36.00		Pass	
EHT20	MCS0	2	13	2472	52T+26T/72	7.95	8.05	11.01	30.00		-1.2		9.81	36.00		Pass	
EHT20	MCS0	2	13	2472	106T+26T/83	9.55	9.65	12.61	30.00		-1.2		11.41	36.00		Pass	

Note: Measured power (dBm) has offset with cable loss.

TEST RESULTS DATA
Peak Power Spectral Density


2.4GHz Band MIMO													
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	RU Config.	Peak PSD (dBm/3kHz)			DG (dBi)		Peak PSD Limit (dBm/3kHz)		Pass/Fail
						Ant3	Ant4	Worse + 3.01	Ant3	Ant4	Ant3	Ant4	
EHT20	MCS0	2	1	2412	Full	-9.84	-9.52	-6.51	0.82		8.00		Pass
EHT20	MCS0	2	1	2412	26/0	-10.25	-9.71	-6.70	0.82		8.00		Pass
EHT20	MCS0	2	1	2412	52/37	-10.15	-9.81	-6.80	0.82		8.00		Pass
EHT20	MCS0	2	1	2412	106/53	-10.15	-9.77	-6.76	0.82		8.00		Pass
EHT20	MCS0	2	1	2412	52T+26T/70	-9.97	-10.04	-6.96	0.82		8.00		Pass
EHT20	MCS0	2	1	2412	106T+26T/82	-10.05	-9.80	-6.79	0.82		8.00		Pass
EHT20	MCS0	2	6	2437	Full	-4.68	-4.28	-1.27	0.82		8.00		Pass
EHT20	MCS0	2	6	2437	4/26	-4.83	-4.56	-1.55	0.82		8.00		Pass
EHT20	MCS0	2	6	2437	52/38	-4.80	-4.60	-1.59	0.82		8.00		Pass
EHT20	MCS0	2	6	2437	106/53	-4.74	-4.69	-1.68	0.82		8.00		Pass
EHT20	MCS0	2	6	2437	52T+26T/71	-4.57	-4.94	-1.56	0.82		8.00		Pass
EHT20	MCS0	2	6	2437	106T+26T/83	-4.86	-4.46	-1.45	0.82		8.00		Pass
EHT20	MCS0	2	11	2462	Full	-11.51	-10.60	-7.59	0.82		8.00		Pass
EHT20	MCS0	2	11	2462	8/26	-11.60	-10.96	-7.95	0.82		8.00		Pass
EHT20	MCS0	2	11	2462	52/40	-11.67	-10.65	-7.64	0.82		8.00		Pass
EHT20	MCS0	2	11	2462	106/54	-11.70	-10.75	-7.74	0.82		8.00		Pass
EHT20	MCS0	2	11	2462	52T+26T/72	-11.83	-10.73	-7.72	0.82		8.00		Pass
EHT20	MCS0	2	11	2462	106T+26T/83	-11.59	-10.78	-7.77	0.82		8.00		Pass
EHT20	MCS0	2	12	2467	Full	-12.71	-11.16	-8.15	0.82		8.00		Pass
EHT20	MCS0	2	12	2467	8/26	-11.52	-11.98	-8.51	0.82		8.00		Pass
EHT20	MCS0	2	12	2467	52/40	-11.38	-11.73	-8.37	0.82		8.00		Pass
EHT20	MCS0	2	12	2467	106/54	-11.56	-11.35	-8.34	0.82		8.00		Pass
EHT20	MCS0	2	12	2467	52T+26T/72	-11.57	-11.73	-8.56	0.82		8.00		Pass
EHT20	MCS0	2	12	2467	106T+26T/83	-11.65	-11.43	-8.42	0.82		8.00		Pass
EHT20	MCS0	2	13	2472	Full	-13.79	-13.28	-10.27	0.82		8.00		Pass
EHT20	MCS0	2	13	2472	8/26	-13.56	-13.83	-10.55	0.82		8.00		Pass
EHT20	MCS0	2	13	2472	52/40	-13.95	-13.39	-10.38	0.82		8.00		Pass
EHT20	MCS0	2	13	2472	106/54	-13.53	-13.62	-10.52	0.82		8.00		Pass
EHT20	MCS0	2	13	2472	52T+26T/72	-13.83	-13.50	-10.49	0.82		8.00		Pass
EHT20	MCS0	2	13	2472	106T+26T/83	-13.58	-13.76	-10.57	0.82		8.00		Pass

Measured power density (dBm) has offset with cable loss.

6dB and 99% Occupied Bandwidth

SISO <ANT. 3>


<802.11b>



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

MIMO <Ant. 3+4 (3)>


<802.11g>



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.




<802.11be EHT20>



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

SISO <Ant. 4>

<802.11b>




Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.




MIMO <Ant. 3+4 (4)>

<802.11g>




<802.11be EHT20>




**Power Spectral Density(dBm/3kHz)**

<802.11b>




<802.11g>





<802.11be EHT20>






Band Edges and Spurious Emission

Number of TX = 1, Ant. 3 (Measured)


Test Mode : 802.11b

Test Channel : 01


100kHz PSD reference Level




Low Channel Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz






Test Mode : 802.11b


Test Channel : 06

100kHz PSD reference Level




Middle Channel Plot

Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11b

Test Channel : 11


100kHz PSD reference Level




High Channel Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11b

Test Channel : 12


100kHz PSD reference Level




Low Channel Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11b

Test Channel : 13


100kHz PSD reference Level




Middle Channel Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11g

Test Channel : 01


100kHz PSD reference Level




Low Channel Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz






Test Mode : 802.11g


Test Channel : 06

100kHz PSD reference Level




Middle Channel Plot

Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11g

Test Channel : 11


100kHz PSD reference Level




High Channel Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11g

Test Channel : 12


100kHz PSD reference Level




Low Channel Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11g

Test Channel : 13


100kHz PSD reference Level




Middle Channel Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11be EHT20_Full RU

Test Channel : 01


100kHz PSD reference Level




Low Channel Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz






Test Mode : 802.11be EHT20_Full RU


Test Channel : 06

100kHz PSD reference Level




Middle Channel Plot

Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11be EHT20_Full RU

Test Channel : 11


100kHz PSD reference Level




High Channel Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11be EHT20_Full RU

Test Channel : 12


100kHz PSD reference Level




Low Channel Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11be EHT20_Full RU

Test Channel : 13


100kHz PSD reference Level




Middle Channel Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz






Number of TX = 1, Ant. 4 (Measured)


Test Mode : 802.11b

Test Channel : 01


100kHz PSD reference Level




Low Channel Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz






Test Mode : 802.11b


Test Channel : 06

100kHz PSD reference Level




Middle Channel Plot

Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11b

Test Channel : 11


100kHz PSD reference Level




High Channel Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11b

Test Channel : 12


100kHz PSD reference Level




Low Channel Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11b

Test Channel : 13


100kHz PSD reference Level




Middle Channel Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11g

Test Channel : 01


100kHz PSD reference Level




Low Channel Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz






Test Mode : 802.11g


Test Channel : 06

100kHz PSD reference Level



Middle Channel Plot

Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz

