

Maximum Permissible Exposure(MPE) Report

1. Applicable Standard

FCC Part §1.1310

2. Requirements

Limits For Maximum Permissible Exposure (MPE)				
Frequency range (MHz)	Electric field strength(V/m)	Magnetic field Strength(A/m)	Power density (mw/cm ²)	Averaging time (minutes)
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.0173	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

3. MPE Calculation

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = Power density (In appropriate units, e.g., mW/cm²)

P = Power input to the antenna (In appropriate units, e.g., mW)

G = Power gain og the antenna in the direction of interest relative to an isotropic radiator, the power gain factor,

Is normally numeric gain

R =Distance tp the center of radiation of the antenna(In appropriate units, e.g., cm

4. Test Result

Operation Bands	Frequency (MHz)	Max. Output power(dBm)	Cable loss (dB)	Power to Antenna(mW)	Antenna gain	
					Isotropic	Numeric
UL1850-1910	1875.26	17.76	2.9	30.62	10	10.00
UL1710-1755	1736.28	18.74	2.55	41.59	10	10.00
UL824-869	842.03	21.27	1.95	85.51	9	7.94
UL698-716	710.12	21.07	1.9	82.60	9	7.94
UL776-787	778.50	21.13	1.9	83.75	9	7.94
DL1930-1990	1957.6	0.80	1.8	0.79	10	10.00
DL2110-2155	2131.87	-0.77	1.9	0.54	10	10.00
DL869-894	887.45	-1.34	1.35	0.54	9	7.94
DL728-746	733.00	-3.03	1.3	0.37	9	7.94
DL746-757	749.61	4.67	1.3	2.17	9	7.94

Operation Bands	Power (mW)	Antenna gain(G)	Measure Distance(cm)	Power density (mW/cm ²)	MPE limit (mW/cm ²)
UL1850-1910	30.62	10.00	20	0.061	1.0
UL1710-1755	41.59	10.00	20	0.083	1.0
UL824-869	85.51	7.94	20	0.135	0.56
UL698-716	82.60	7.94	20	0.130	0.47
UL776-787	83.75	7.94	20	0.132	0.52
DL1930-1990	0.79	10.00	20	0.002	1.0
DL2110-2155	0.54	10.00	20	0.001	1.0
DL869-894	0.54	7.94	20	0.001	0.58
DL728-746	0.37	7.94	20	0.001	0.49
DL746-757	2.17	7.94	20	0.003	0.50

Results: PASS