

TUNE-UP PROCEDURE

This exhibit contains the tune-up procedure as it will appear in the Configuration Service Software (CSS) manual.

The following adjustments comprise the total transmitter alignment:

1. Reference Oscillator
2. Transmitter Power Output
3. Transmit Deviation Control
4. Reference Modulation Compensation

Note: All adjustments are factory pre-set and do not require alignment under normal operating conditions. In the event alignment is needed, refer servicing to qualified radio maintenance personnel only.

TEST EQUIPMENT

<u>Description</u>	<u>Recommended model</u>
1. Service Monitor	Motorola R-2001 or equivalent
2. PC with CSS	

TRANSMITTER ALIGNMENT PROCEDURE

CSS/RSS Port: A 9-pin D connector is provided on the station control module front panel to allow service personnel to connect a PC loaded with the Configuration Service Software (CSS) and perform programming and maintenance tasks via this TIA RS-232 port. The following pages of this exhibit will show the important alignment screens.

EXHIBIT DESCRIPTION

- | | |
|----|--|
| 9A | Reference Oscillator Alignment Screen |
| 9B | Transmitter Power Output Alignment Screen |
| 9C | Transmitter Deviation Alignment Screen |
| 9D | Reference Modulation Compensation Alignment Screen |

All adjustments are software controlled and are pre-set at the factory. Certain station operating parameters can be changed via man-machine interface (MMI) commands, within predetermined limits. Examples include transmit / receiver operating frequencies and power level.