



Company: Motorola
Model Tested: 5700AP
Report Number: 13185

1250 Peterson Dr., Wheeling, IL 60090

FCC Rules and Regulations / Intentional Radiators

Operational in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz, Bands

Part 15, Subpart C, Section 15.247

THE FOLLOWING "MEETS" THE ABOVE TEST SPECIFICATION

Formal Name: Canopy 5700 with Lense Antenna

Kind of Equipment: Wireless Digital FSK Transceiver

Test Configuration: The Canopy Radio (AP) is connected to a 24V power supply via shielded Ethernet cable and a sectorized antenna via a 50 ohm RF cable.

Model Number(s): 5700xx

Model(s) Tested: 5700AP

Serial Number(s): 0A003EFAC08B

Date of Tests: April 16, 2007

Test Conducted For: Motorola
1299 E. Algonquin Road
Schaumburg, Illinois 60196

NOTICE: "This report must not be used by the client to claim product endorsement by NVLAP or any agency of the U.S. Government". Please see the "Additional Description of Equipment Under Test" page listed inside of this report.

© Copyright 1983- 2006 D.L.S. Electronic Systems, Inc

COPYRIGHT NOTICE

This report or any portion their of, may not be reproduced or modified in any form without the expressed written consent of D.L.S. Electronic Systems, Inc.



Company: Motorola
Model Tested: 5700AP
Report Number: 13185

1250 Peterson Dr., Wheeling, IL 60090

SIGNATURE PAGE

Report By:

Aron C. Rowe
Test Engineer
EMC-001375-NE

Reviewed By:

William Stumpf
OATS Manager

Approved By:

Brian Mattson
General Manager

Company Official:

Motorola



Company: Motorola
Model Tested: 5700AP
Report Number: 13185

1250 Peterson Dr., Wheeling, IL 60090

TABLE OF CONTENTS


i.	Cover Page	1
ii.	Signature Page	2
iii.	Table of Contents.....	3
iv.	NVLAP Certificate of Accreditation	4
1.0	Summary of Test Report.....	5
2.0	Introduction.....	5
3.0	Object.....	5
4.0	Test Set-Up	6
5.0	Test Equipment	6
6.0	Ambient Measurements	7
7.0	Description of Test Sample.....	8
8.0	Additional Description of Test Sample.....	9
9.0	Photo Information and Test Set-Up	10
10.0	Radiated Photos Taken During Testing	11
11.0	Results of Tests	13
12.0	Conclusion	13
	TABLE 1 – EQUIPMENT LIST	14
	Appendix A – Electric Field Radiated Emissions Test.....	16
1.0	Conducted Emission Measurements	17
2.0	Spurious Emissions at the Antenna Terminals	18
3.0	Restricted Bands	19
4.0	Restricted Band Compliance.....	19
4.0	Data and Graph(s) taken showing the Restricted Band Compliance.....	20
5.0	Field Strength of Fundamental and Spurious Emission Measurements	24
5.0	Radiated Data and Graph(s) taken for Fundamental Emission.....	26
5.0	Radiated Data and Graph(s) taken for the Spurious Emission	30



1250 Peterson Dr., Wheeling, IL 60090

Company: Motorola
Model Tested: 5700AP
Report Number: 13185

United States Department of Commerce
National Institute of Standards and Technology



Certificate of Accreditation to ISO/IEC 17025:1999

NVLAP LAB CODE: 100276-0

D.I.S. Electronic Systems, Inc.
Wheeling, IL

is recognized by the National Voluntary Laboratory Accreditation Program for conformance with criteria set forth in
NIST Handbook 150:2001 and all requirements of ISO/IEC 17025:1999.
Accreditation is granted for specific services, listed on the Scope of Accreditation, for:

ELECTROMAGNETIC COMPATIBILITY AND TELECOMMUNICATIONS



2006-10-01 through 2007-09-30
Effective dates

Daryl S. Bruce
For the National Institute of Standards and Technology

NVLAP-01C (REV. 2005-05-19)



Company: Motorola
Model Tested: 5700AP
Report Number: 13185

1250 Peterson Dr., Wheeling, IL 60090

1.0 SUMMARY OF TEST REPORT

It was found that the Canopy 5700 with Lens Antenna, Model Number(s) 5700AP, "meets" the radio interference radiated emission requirements of the FCC "Rules and Regulations", Part 15, Subpart C, Section 15.247 for operational in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz, Bands. See DLS Test Report 12688 for the conducted emissions test data made on October 9, 10, 13 & 14, 2006.

2.0 INTRODUCTION

On April 16, 2007, a series of radio frequency interference measurements was performed on Canopy 5700 with Lens Antenna, Model Number(s) 5700AP, Serial Number: 0A003EFAC08B. The tests were performed according to the procedures of the FCC as stated in the "Methods of Measurement of Radio-Noise Emissions for Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz" found in the American National Standards Institute, ANSI C63.4-2003. Tests were performed by personnel of D.L.S. Electronic Systems, Inc. who are responsible to Donald L. Sweeney, Senior EMC Engineer.

D.L.S. Electronic Systems, Inc. is a full service EMC/Safety Testing Laboratory accredited to ISO 17025. NVLAP Certificate and Scope can be viewed at <http://www.dlsemc.com/certificate>. Our facilities are registered with the FCC, Industry Canada, and VCCI.

3.0 OBJECT

The purpose of this series of tests was to determine if the test sample could meet the radio frequency interference emission requirements of the FCC "Rules and Regulations", Part 15, Subpart C, Sections 15.205, 15.209 & 15.247 for Intentional Radiators operating in the Bands 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.



Company: Motorola
Model Tested: 5700AP
Report Number: 13185

1250 Peterson Dr., Wheeling, IL 60090

4.0 TEST SET-UP

All emission tests were performed at D.L.S. Electronic Systems, Inc. and set up according to the American National Standards Institute, ANSI C63.4-2003, Section 8, (Figures 11a and 11b).

All radiated emissions tests were performed with the test item placed on a 80 cm high rotating non-conductive table, located in the test room. Equipment normally operated on the floor was placed on a metal covered turntable which is flush with the surrounding conducting ground plane. The ground plane has an electrical isolation layer over its surface approximately 7 mm thick. The EUT is separated from the turntable ground plane by a non-conductive layer. The equipment under test was set up according to ANSI C63.4-2003, Sections 6 and 8.

5.0 TEST EQUIPMENT (Bandwidths and Detector Function)

All preliminary data below 1000 MHz was automatically plotted using the HP Spectrum Analyzer or ESI 26/40 Fixed Tuned Receiver. The data was taken using Peak, Quasi-Peak or the Average Detector Functions as required. This information was then used to determine the frequencies of maximum emissions. Above 1000 MHz, final data was taken using the Average Detector.

Below 1000 MHz, final data was taken using the HP Spectrum Analyzer and/or ESI 26/40 Fixed Tuned Receiver. These plots were made using the Peak or Quasi-Peak Detector functions, with manual measurements performed on the questionable frequencies using the Quasi-Peak or the Average Detector Function of the Analyzer or ESI 26/40 Fixed Tuned Receiver as required. Above 1000 MHz, final data was taken using the Average Detector on the Spectrum Analyzer.

The bandwidths shown below are specified by ANSI C63.4-2003, Section 4.2.

Frequency Range	Bandwidth (-6 dB)
10 to 150 kHz	200 Hz
150 kHz to 30 MHz	9 kHz
30 MHz to 1 GHz	120 kHz
Above 1 GHz	1 MHz

A list of the equipment used can be found in Table 1. All primary equipment was calibrated against known reference standards with a verified traceable path to NIST.



Company: Motorola
Model Tested: 5700AP
Report Number: 13185

1250 Peterson Dr., Wheeling, IL 60090

6.0 AMBIENT MEASUREMENTS

For emissions measurements, broadband antennas and an EMI Test Receiver with a panoramic spectrum display are used. First the frequency range is scanned and displayed on the test receiver display. Next the scanned frequency range is divided into smaller ranges, and then it is manually tuned through to determine the emissions from the EUT. A headset or loudspeaker is connected to the test receiver's AM/FM demodulated output as an aid in detecting ambient signals and finding frequencies of significant emission from the EUT. If there is any doubt as to the source of the emission, it is further investigated by rotating the EUT, or by disconnecting the power from the EUT.

The EUT is set up in its typical configuration and operated in its various modes. For tabletop systems, cables are manipulated within the range of likely configurations. For floor-standing equipment, the cables are located in the same manner as the user would install them and no further manipulation is made. If the manner of cable installation is not known, or if it changes with each installation, cables or wires for floor-standing equipment shall be manipulated to the extent possible to produce the maximum level of emissions. For each mode of operation, the frequency spectrum is monitored. Variations in antenna height, antenna polarization, EUT azimuth, and cable or wire placement (each variable within bounds specified elsewhere) are explored to produce the emissions that have the highest amplitude relative to the limit. These methods are performed to the specifications in MP-5 or ANSI C63.4-2003, as appropriate.



Company: Motorola
Model Tested: 5700AP
Report Number: 13185

1250 Peterson Dr., Wheeling, IL 60090

7.0 DESCRIPTION OF TEST SAMPLE: (See also Paragraph 8.0)

7.1 Description:

The Canopy 5700 Super Advanced Logic Wireless Digital FSK Radio is designed for use in the 5.8 GHz Band (5735 MHz - 5840 MHz) with 6 separate 20 MHz channels. The radio works in conjunction with a 24 VDC power supply. It has an adjustable output power based on the gain of the antenna that is connected to it. Canopy is a point to multi-point wireless Ethernet distribution system. The back hauls (BH) are point to point links used for connecting multi-point access points to wired Ethernet feeds (Internet Service Providers points of presence, ISP POP).

7.2 PHYSICAL DIMENSIONS OF EQUIPMENT UNDER TEST

Length: 2.75" x Width: 8" x Height: 0.6"

7.3 LINE FILTER USED:

NA

7.4 INTERNAL CLOCK FREQUENCIES:

Switching Power Supply Frequencies:

150 kHz & 132 kHz

Clock Frequencies:

20 MHz, 25 MHz, 40 MHz, 62.5 MHz, 80 MHz, 125 MHz & 160 MHz

7.5 DESCRIPTION OF ALL CIRCUIT BOARDS:

1. Radio SAL5.7 GHz ISS. C	PN: 84-71276n01 iss.c
2. Power Supply PSA15R	PN: ACPSSW-09A
3. Lense Antenna	PN: AN500



Company: Motorola
Model Tested: 5700AP
Report Number: 13185

1250 Peterson Dr., Wheeling, IL 60090

8.0 ADDITIONAL DESCRIPTION OF TEST SAMPLE:
(See also Paragraph 7.0)

1: There were no additional descriptions noted at the time of test.

NOTE:

The Low, Mid and High Channels were tested in continuous transmit and continuous receive.

I certify that the above, as described in paragraph 7.0, describes the equipment tested and will be manufactured as stated.

By: _____ Signature _____ Title _____

For: _____ Company _____ Date _____



Company: Motorola
Model Tested: 5700AP
Report Number: 13185

1250 Peterson Dr., Wheeling, IL 60090

9.0 PHOTO INFORMATION AND TEST SET-UP

Item 0 Canopy 5700

Model Number: 5700AP Serial Number: 0A003EFAC08B
Lense Antenna
PN: AN500


Item 1 Shielded CAT 5 Ethernet Cable with Metal Shells. 100'



Company: Motorola
Model Tested: 5700AP
Report Number: 13185

1250 Peterson Dr., Wheeling, IL 60090

10.0 RADIATED PHOTOS TAKEN DURING TESTING




RADIATED EMISSIONS
FRONT VIEW



Company: Motorola
Model Tested: 5700AP
Report Number: 13185

1250 Peterson Dr., Wheeling, IL 60090

10.0 RADIATED PHOTOS TAKEN DURING TESTING (CON'T)



RADIATED EMISSIONS
REAR VIEW



Company: Motorola
Model Tested: 5700AP
Report Number: 13185

1250 Peterson Dr., Wheeling, IL 60090

11.0 RESULTS OF TESTS

The radio interference emission charts can be seen on the pages at the end of this report. Data sheets indicating the test measurements taken during testing can also be found at the end of this report.

12.0 CONCLUSION

It was found that the Canopy 5700 with Lense Antenna, Model Number(s) 5700AP "meets" the radio interference radiated emission requirements of the FCC "Rules and Regulations", Part 15, Subpart C, Section 15.247 for operational in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz, Bands. See DLS Test Report 12688 for the conducted emissions test data made on October 9, 10, 13 & 14, 2006.



Company: Motorola
Model Tested: 5700AP
Report Number: 13185

1250 Peterson Dr., Wheeling, IL 60090

TABLE 1 – EQUIPMENT LIST

Test Equipment	Manufacturer	Model Number	Serial Number	Frequency Range	Cal Due Dates
Receiver	Rohde & Schwarz	ESI 26	837491/010	20 Hz – 26 GHz	11/07
Receiver	Rohde & Schwarz	ESI 40	837808/006	20 Hz – 40 GHz	12/07
Receiver	Rohde & Schwarz	ESI 40	837808/005	20 Hz – 40 GHz	12/07
Antenna	EMCO	3104C	00054891	20 MHz – 200 MHz	2/08
Antenna	Electrometrics	LPA-25	1114	200 MHz – 1 GHz	3/07
Antenna	EMCO	3104C	00054892	20 MHz – 200 MHz	3/07
Antenna	Electrometrics	3146	1205	200 MHz – 1 GHz	3/07
Antenna	EMCO	3104C	97014785	20 MHz – 200 MHz	2/08
Antenna	EMCO	3146	97024895	200 MHz – 1 GHz	3/07
Antenna	EMCO	3115	2479	1 GHz – 18 GHz	8/07
Antenna	EMCO	3115	99035731	1 GHz – 18 GHz	4/07
Antenna	EMCO	3116	2549	18 GHz – 40 GHz	5/07
Antenna	EMCO	3116	35017	18 GHz – 40 GHz	5/07
Antenna	Rohde & Schwarz	HUF-Z1	829381001	20 MHz – 1 GHz	2/08
Antenna	Rohde & Schwarz	HUF-Z1	829381005	20 MHz – 1 GHz	8/07

All primary equipment is calibrated against known reference standards with a verified traceable path to NIST.



Company: Motorola
Model Tested: 5700AP
Report Number: 13185

1250 Peterson Dr., Wheeling, IL 60090

TABLE 1 – EQUIPMENT LIST

Test Equipment	Manufacturer	Model Number	Serial Number	Frequency Range	Cal Due Dates
LISN	Solar	8012-50-R-24-BNC	8305116	10 MHz – 30 MHz	8/07
LISN	Solar	8012-50-R-24-BNC	814548	10 MHz – 30 MHz	8/07
LISN	Solar	9252-50-R-24-BNC	961019	10 MHz – 30 MHz	12/07
LISN	Solar	9252-50-R-24-BNC	971612	10 MHz – 30 MHz	10/07
LISN	Solar	9252-50-R-24-BNC	92710620	10 MHz – 30 MHz	7/07

All primary equipment is calibrated against known reference standards with a verified traceable path to NIST.



1250 Peterson Dr., Wheeling, IL 60090

Company: Motorola
Model Tested: 5700AP
Report Number: 13185

APPENDIX A

TEST PROCEDURE

Part 15, Subpart C, Section 15.247 (a-h)

OPERATION WITHIN THE BAND 902-928 MHz,

2400-2483.5 MHz AND 5725-5857 MHz



Company: Motorola
Model Tested: 5700AP
Report Number: 13185

1250 Peterson Dr., Wheeling, IL 60090

APPENDIX A

1.0 CONDUCTED EMISSION MEASUREMENTS

If applicable, the conducted emissions were measured over the frequency range from 150 kHz to 30 MHz in accordance with the power line measurements as specified in the American National Standards Institute, ANSI C63.4-2003, Section 12. Since the device is operated from the public utility lines, the 115 Vac 60 Hz power leads, high and low sides, were to be measured by connecting the measuring equipment to the appropriate meter terminal of the LISN. All signals were then recorded. The allowed levels for Intentional Radiators cannot exceed the following:

Frequency of Emissions (MHz)	Conducted Limits (dBuV)	
	Quasi Peak	Average
.15 to .5	66 to 56	56 to 46
.5 to 5	56	46
5 to 30	60	50

NOTE:

See DLS Test Report 12688 for the data and graphs made on October 9, 10, 13 & 14, 2006 for the actual measurements made:



Company: Motorola
Model Tested: 5700AP
Report Number: 13185

1250 Peterson Dr., Wheeling, IL 60090

APPENDIX A

2.0 SPURIOUS EMISSIONS AT ANTENNA TERMINALS – PART 15.247(c)

Spurious conducted emissions were measured at the antenna terminals. Plots were made showing the amplitude of each harmonic emission with the equipment operated. As shown by the radiated charts there was no reason to believe that there were any spurious emissions other than the harmonics that were individually investigated when doing the conducted test at the antenna terminals. Measurements were made up to the 10th harmonic of the fundamental.

The allowed emissions for transmitters operating in the 5725 MHz - 5850 MHz bands for Canopy 5700 with Lens Antenna equipment are found under Part 15, Section 15.247(c). This paragraph states that in any 100 kHz bandwidth outside the frequency band which the spread spectrum intentional radiator is operating, the radio frequency power produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

NOTE:

See DLS Test Report 12688 for the data and graphs made on October 9, 10, 13 & 14, 2006 for the actual measurements made:



Company: Motorola
Model Tested: 5700AP
Report Number: 13185

1250 Peterson Dr., Wheeling, IL 60090

APPENDIX A

3.0 RESTRICTED BANDS

As stated in Section 15.205a, the fundamental emission from the Canopy 5700 with Lens Antenna shall not fall within any of the bands listed below:

Frequency in MHz	Frequency in MHz	Frequency in MHz	Frequency in GHz
.0900 to .1100	162.0125 to 167.17	2310.0 to 2390	9.30 to 9.50
.4900 to .5100	167.7200 to 173.20	2483.5 to 2500	10.60 to 12.70
2.1735 to 2.1905	240.000 to 285.00	2655.0 to 2900	13.25 to 13.40
8.362 to 8.3660	322.200 to 335.40	3260.0 to 3267	14.47 to 14.50
13.36 to 13.410	399.900 to 410.00	3332.0 to 3339	15.35 to 16.20
25.50 to 25.670	608.000 to 614.00	3345.8 to 3358	17.70 to 21.40
37.50 to 38.250	960.000 to 1240.00	3600.0 to 4400	22.01 to 23.13
73.00 to 75.500	1300.000 to 1427.00	4500.0 to 5250	23.60 to 24.00
108.00 to 121.94	1435.000 to 1626.50	5350.0 to 5450	31.20 to 31.80
123.00 to 138.00	1660.000 to 1710.00	7250.0 to 7750	36.43 to 36.50
149.90 to 150.00	1718.800 to 1722.20	8025.0 to 8500	ABOVE 38.60
156.70 to 156.90	2200.000 to 2300.00	9000.0 to 9200	

NOTE:

The noise floor within the Restricted Bands for the EMC Receiver and HP Spectrum Analyzer will typically lay 20 dB below the limit.

4.0 RESTRICTED BAND COMPLIANCE

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the attenuation below the general limits specified in 15.209 is not required.

The field strength of any **radiated emissions** which fall within the restricted bands shall not exceed the general radiated emissions limits as stated Section 15.209.

NOTE: See the following page(s) for the graph(s) made showing compliance for Restricted Band:



Company: Motorola
Model Tested: 5700AP
Report Number: 13185

1250 Peterson Dr., Wheeling, IL 60090

APPENDIX A

DATA AND GRAPH(S) TAKEN SHOWING THE RESTRICTED BAND COMPLIANCE

PART 15.247(c)



Company: Motorola
Model Tested: 5700AP
Report Number: 13185

1250 Peterson Dr., Wheeling, IL 60090

Radiated Spurious Emissions in Restricted Bands

Tested at a 3 Meter Distance – 1 GHz to 18 GHz

Tested at a 1 Meter Distance – 18 GHz to 40 GHz

EUT: Canopy 5700
Manufacturer: Motorola
Operating Condition: 68 deg F; 29% R.H.
Test Site: Site 2
Operator: Craig Brandt
Test Specification: FCC Part 15.247
Comment: Continuous Transmit
Date: 04/16/2007

Notes: All other restricted band emissions at least 20 dB under the limit.

Channel: Low (5735 MHz)

Frequency (GHz)	Measurement Type	Ant. Pol.	Level (dBuV)	Antenna Factor (dB/m)	System Loss (dB)	Total Level (dBuV/m)	Duty Cycle Correction (dB)	Final Corrected (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant. Height (m)	EUT Angle (deg)	Comment
11.47	Average	Vert	38.34	38.77	-33.0	44.1	---	44.1	54.0	9.9	1.00	135	Res. Band
11.47	Max Peak	Vert	49.14	38.77	-33.0	54.9	---	54.9	74.0	19.1	1.00	135	Res. Band
11.47	Average	Horz	36.12	38.77	-33.0	41.9	---	41.9	54.0	12.1	1.30	170	Res. Band
11.47	Max Peak	Horz	47.24	38.77	-33.0	53.0	---	53.0	74.0	21.0	1.30	170	Res. Band
22.94	Average	Vert	52.34	46.24	-37.8	60.8	---	60.8	64.0	3.2	1.30	0	Res. Band
22.94	Max Peak	Vert	58.71	46.24	-37.8	67.2	---	67.2	84.0	16.8	1.30	0	Res. Band
22.94	Average	Horz	50.41	46.24	-37.8	58.9	---	58.9	64.0	5.1	1.10	315	Res. Band
22.94	Max Peak	Horz	60.01	46.24	-37.8	68.6	---	68.6	84.0	15.4	1.10	315	Res. Band



Company: Motorola
Model Tested: 5700AP
Report Number: 13185

1250 Peterson Dr., Wheeling, IL 60090

Radiated Spurious Emissions in Restricted Bands

Tested at a 3 Meter Distance – 1 GHz to 18 GHz

Tested at a 1 Meter Distance – 18 GHz to 40 GHz

EUT: Canopy 5700
Manufacturer: Motorola
Operating Condition: 68 deg F; 29% R.H.
Test Site: Site 2
Operator: Craig Brandt
Test Specification: FCC Part 15.247
Comment: Continuous Transmit
Date: 04/16/2007

Notes: All other restricted band emissions at least 20 dB under the limit.

Channel: Mid (5775 MHz)

Frequency (GHz)	Measurement Type	Ant. Pol.	Level (dBuV)	Antenna Factor (dB/m)	System Loss (dB)	Total Level (dBuV/m)	Duty Cycle Correction (dB)	Final Corrected (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant. Height (m)	EUT Angle (deg)	Comment
11.55	Average	Vert	40.18	38.83	-33.0	46.0	---	46.0	54.0	8.0	1.00	135	Res. Band
11.55	Max Peak	Vert	51.02	38.83	-33.0	56.8	---	56.8	74.0	17.2	1.00	135	Res. Band
11.55	Average	Horz	38.46	38.83	-33.0	44.3	---	44.3	54.0	9.7	2.50	225	Res. Band
11.55	Max Peak	Horz	50.24	38.83	-33.0	56.0	---	56.0	74.0	18.0	2.50	225	Res. Band
23.10	Average	Vert	50.14	46.22	-37.3	59.1	---	59.1	64.0	4.9	1.30	0	Res. Band
23.10	Max Peak	Vert	56.65	46.22	-37.3	65.6		65.6	84.0	18.4	1.30	0	Res. Band
23.10	Average	Horz	49.95	46.22	-37.3	58.9	---	58.9	64.0	5.1	1.40	20	Res. Band
23.10	Max Peak	Horz	59.75	46.22	-37.3	63.9		68.7	84.0	15.3	1.40	20	Res. Band



Company: Motorola
Model Tested: 5700AP
Report Number: 13185

1250 Peterson Dr., Wheeling, IL 60090

Radiated Spurious Emissions in Restricted Bands

Tested at a 3 Meter Distance – 1 GHz to 18 GHz

Tested at a 1 Meter Distance – 18 GHz to 40 GHz

EUT: Canopy 5700
Manufacturer: Motorola
Operating Condition: 68 deg F; 29% R.H.
Test Site: Site 2
Operator: Craig Brandt
Test Specification: FCC Part 15.247
Comment: Continuous Transmit
Date: 04/16/2007

Notes: All other restricted band emissions at least 20 dB under the limit.

Channel: High (5840 MHz)



Company: Motorola
Model Tested: 5700AP
Report Number: 13185

1250 Peterson Dr., Wheeling, IL 60090

APPENDIX A

5.0 FIELD STRENGTH OF FUNDAMENTAL AND SPURIOUS EMISSION MEASUREMENTS

The radiated measurements made at D.L.S. Electronic Systems, Inc., for the Canopy 5700 with Lens Antenna, Model Number: 5700AP, are shown in tabulated and graph form. Preliminary radiation measurements were performed at a 3 meter test distance with the limits adjusted linearly when required. The frequency range from 30 MHz to over 960 MHz, depending upon the fundamental frequency as stated in Part 15.33a, was automatically scanned and plotted at various angles.

Measurements for the Canopy 5700 with Lens Antenna were made up to 40000 MHz, in accordance with Section 15.33a for Intentional Radiators with a fundamental frequency of 5800 MHz. For intentional radiators, the frequency range to be investigated is determined by the lowest radio frequency generated by the device without going below 30 MHz, up to at least the tenth harmonic of the highest fundamental frequency or 10 GHz, whichever is lower. At those frequencies where significant signals were detected, measurements were made over the entire frequency range specified in FCC Part 15, Subpart C, Section 15.247 at the open field test site, located at Genoa City, Wisconsin, FCC file number **31040/SIT**. When required, levels were extrapolated from 10 meters to 3 meters using a linear extrapolation.

All signals in the frequency range of 30 MHz to 2000 MHz were measured with a Biconical Antenna or tuned dipoles and from 200 MHz to 1000 MHz, a Log Periodic or Tuned Dipoles were used. From 1000 MHz to 25 GHz Horn Antennas were used. During the test the equipment was rotated and the antenna was raised and lowered from 1 meter to 4 meters to find the maximum level of emissions. In order to find maximum emissions, the cables were moved through all the positions the equipment would be expected to experience in the field. The EUT, peripheral equipment and cables were configured to meet the conditions in ANSI C63.4-2003, Clauses 6 & 8. Tests were made with the receive antenna(s) in both the horizontal and vertical planes of polarization. In each case, the table was rotated to find the maximum emissions.



Company: Motorola
Model Tested: 5700AP
Report Number: 13185

1250 Peterson Dr., Wheeling, IL 60090

APPENDIX A

5.0 FIELD STRENGTH OF FUNDAMENTAL AND SPURIOUS EMISSION MEASUREMENTS (CON'T)

As stated in Section 15.247(b) the allowed maximum peak output power of the transmitter shall not exceed 1 Watt. In any 100 kHz bandwidth outside these frequency bands (the power that is produced by the modulation products of the spreading sequence), the information sequence and the carrier frequency shall be either at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Attenuation below the general limits specified in 15.209 is not required.

Field strength limits are at a distance of 3 meters. The emission limits shown are based on measurement instrumentation employing an average detector.

Emissions radiated outside of the specified frequency bands, except for harmonics are attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

Preliminary radiated emission measurements were performed at a 3 meter test distance. The frequency range from 30 MHz to 1000 MHz was automatically scanned and plotted at various angles.

NOTE:

All radiated emissions measurements were made at a test room temperature of **68°F** at **29%** relative humidity and **68°F** at **31%** relative humidity.



1250 Peterson Dr., Wheeling, IL 60090

Company: Motorola
Model Tested: 5700AP
Report Number: 13185

RADIATED DATA AND GRAPH(S) TAKEN FOR
FIELD STRENGTH OF FUNDAMENTAL
EMISSION MEASUREMENTS

PART 15.247



Company: Motorola
Model Tested: 5700AP
Report Number: 13185

1250 Peterson Dr., Wheeling, IL 60090

DLS Electronic Systems, Inc.

Company: Motorola
Operator: Craig Brandt
Date of test: 04-16-2007
Temperature: 68 deg. F
Humidity: 29% R.H.

EIRP - Substitution Method

Model: Canopy 5700								
Channel: Low								
Frequency and Polarization (MHz)	Max. Field Strength of EUT @ 3 meters (dBuV/m)	Output of Signal Generator when field strength equals that of EUT (dBm)	Correction factor for cable between Signal Gen. and subst. antenna (dB)	Gain of subst. antenna (dBi)	Strength of emission [EIRP] (dBm)	Limit (dBm)	Margin (dB)	Strength of emission [EIRP] (W)
5735 vertical	136.59	30.30	3.44	10.73	37.59			5.74
5735 horizontal	128.15	22.60	3.44	10.73	29.89			0.97

EIRP = Signal generator output - cable loss + antenna gain

ERP_(ref. to 1/2λ dipole) = Signal generator output - cable loss + antenna gain - 2.15



Company: Motorola
Model Tested: 5700AP
Report Number: 13185

1250 Peterson Dr., Wheeling, IL 60090

DLS Electronic Systems, Inc.

Company: Motorola
Operator: Craig Brandt
Date of test: 04-16-2007
Temperature: 68 deg. F
Humidity: 29% R.H.

EIRP - Substitution Method

Model: Canopy 5700								
Channel: Mid								
Frequency and Polarization (MHz)	Max. Field Strength of EUT @ 3 meters (dBuV/m)	Output of Signal Generator when field strength equals that of EUT (dBm)	Correction factor for cable between Signal Gen. and subst. antenna (dB)	Gain of subst. antenna (dBi)	Strength of emission [EIRP] (dBm)	Limit (dBm)	Margin (dB)	Strength of emission [EIRP] (W)
5775 vertical	136.12	30.10	3.45	10.79	37.44			5.55
5775 horizontal	128.59	22.80	3.45	10.79	30.14			1.03

EIRP = Signal generator output - cable loss + antenna gain

ERP_(ref. to 1/2λ dipole) = Signal generator output - cable loss + antenna gain - 2.15



Company: Motorola
Model Tested: 5700AP
Report Number: 13185

1250 Peterson Dr., Wheeling, IL 60090

DLS Electronic Systems, Inc.

Company: Motorola
Operator: Craig Brandt
Date of test: 04-16-2007
Temperature: 68 deg. F
Humidity: 29% R.H.

EIRP - Substitution Method

Model: Canopy 5700								
Channel: High								
Frequency and Polarization (MHz)	Max. Field Strength of EUT @ 3 meters (dBuV/m)	Output of Signal Generator when field strength equals that of EUT (dBm)	Correction factor for cable between Signal Gen. and subst. antenna (dB)	Gain of subst. antenna (dBi)	Strength of emission [EIRP] (dBm)	Limit (dBm)	Margin (dB)	Strength of emission [EIRP] (W)
5840 vertical	135.16	28.60	3.47	10.88	36.01			3.99
5840 horizontal	127.99	22.00	3.47	10.88	29.41			0.87

EIRP = Signal generator output - cable loss + antenna gain

ERP_(ref. to 1/2λ dipole) = Signal generator output - cable loss + antenna gain - 2.15



Company: Motorola
Model Tested: 5700AP
Report Number: 13185

1250 Peterson Dr., Wheeling, IL 60090

RADIATED DATA AND GRAPH(S) TAKEN FOR

FIELD STRENGTH OF

SPURIOUS EMISSION MEASUREMENTS

PART 15.247

Electric Field Strength

EUT: Canopy 5700
Manufacturer: Motorola
Operating Condition: 68 degF; 31% R.H.
Test Site: D.L.S. O.F. Site 2
Operator: Craig B
Test Specification: Transmit and Receive modes
Comment: Low, Mid and High channels
Date: 04/18/2007


TEXT: "Site 2 Mid 3M"

Short Description: Test Set-up Vert30-1000MHz
TEST EQUIPMENT: Receiver --- Rohde&Schwarz ESI 26 SN: 837460/002

Antennas ---
Biconical -- EMCO 3104C SN: 0005-4892
Log Periodic -- Electro Metrics LPA-25 SN: 1205
Pre-Amp --- Rohde&Schwarz TS-PR10 SN: 032001/004

TEST SET-UP: EUT Measured at 3 Meters with VERTICAL Antenna Polarization

Level [dB μ V/m]



Legend:
MES A4183_F1V_Quasi-Peak
+ MES A4183_F1V_Peak_List
LIM FCC Class B LIM QP/AV
Voltage Amplitude FCC Class B

MEASUREMENT RESULT: "A4183_F1V_Final"

4/18/2007	11:30AM	Frequency	Level	Antenna Factor	System Loss	Total Level	Limit	Margin	Height Ant.	Eut Angle	Final Detector	Comment
MHz		dB μ V	dB μ V	dB μ V/m	dB μ V/m	dB μ V/m	dB μ V/m	dB	m	deg		
562.480000	43.37	18.25	-20.0	41.6	46.0	4.4	1.60	1.80	QUASI-PEAK	None		
719.980000	39.32	21.09	-19.1	41.3	46.0	4.7	2.20	1.70	QUASI-PEAK	None		
624.980000	41.11	19.17	-19.8	40.5	46.0	5.5	1.50	1.80	QUASI-PEAK	None		
559.980000	40.75	18.26	-20.1	38.9	46.0	7.1	1.60	1.90	QUASI-PEAK	None		
43.780000	45.50	11.13	-24.4	32.2	40.0	7.8	1.00	3.0	QUASI-PEAK	None		
759.980000	34.25	21.06	-18.6	36.7	46.0	9.3	1.20	1.90	QUASI-PEAK	None		
499.980000	39.76	17.64	-21.0	36.4	46.0	9.6	1.00	1.80	QUASI-PEAK	None		
749.980000	34.22	20.60	-18.7	36.1	46.0	9.9	2.00	1.70	QUASI-PEAK	None		
919.980000	30.88	22.51	-17.6	35.7	46.0	10.3	1.00	2.25	QUASI-PEAK	None		
812.490000	32.28	21.37	-18.3	35.3	46.0	10.7	1.00	2.00	QUASI-PEAK	None		
599.970000	35.66	18.84	-19.9	34.6	46.0	11.4	1.50	1.80	QUASI-PEAK	None		
959.980000	27.11	22.90	-17.3	32.7	46.0	13.3	1.60	1.90	QUASI-PEAK	None		
437.480000	37.61	15.91	-21.2	32.3	46.0	13.7	1.00	2.00	QUASI-PEAK	None		
999.980000	28.66	23.66	-17.0	35.3	53.9	18.6	1.50	1.80	QUASI-PEAK	None		

Electric Field Strength


EUT: Canopy 5700
Manufacturer: Motorola
Operating Condition: 68 degF; 31% R.H.
Test Site: D.L.S. O.F. Site 2
Operator: Craig B
Test Specification: Transmit and Receive modes
Comment: Low, Mid and High channels
Date: 04/18/2007

TEXT: "Site 2 MidH 3M"

Short Description: Test Set-up Horz30-1000MHz
TEST EQUIPMENT: Receiver --- Rohde&Schwarz ESI 26 SN: 837460/002

Antennas ---
Biconical -- EMCO 3104C SN: 0005-4892
Log Periodic -- Electro Metrics LPA-25 SN: 1205
Pre-Amp --- Rohde&Schwarz TS-PR10 SN: 032001/004

TEST SET-UP: EUT Measured at 3 Meters with HORIZONTAL Antenna Polarization



MEASUREMENT RESULT: "A4183_F1H_Final"

4/18/2007	11:34AM	Antenna	System	Total	Margin	Height	EUT	Final	Comment
Frequency	Level	Factor	Loss	Level	dB	Ant.	Angle	Detector	
MHz	dB μ V	dB μ V/m	dB	dB μ V/m	dB	m	deg		
719.980000	27.43	21.09	-19.1	29.4	46.0	16.6	1.40	350	QUASI-PEAK