


MOTOROLA


TESTING CERT #2518.01

**FCC ID: ABZ99FT3083
DECLARATION OF COMPLIANCE MPE ASSESSMENT**

Networks & Enterprise
EME Test Laboratory
8000 West Sunrise Blvd
Fort Lauderdale, FL. 33322

Date of Report: 8/15/07
Report Revision: Rev. O
Report ID: MPE rpt_XPR4550_VHF –
 Rev O_070815_SR5135

Responsible Engineer: Kim Uong (Principle Staff EME Eng.)
Date/s Tested: 7/19/07 – 8/13/07
Manufacturer/Location: Motorola, Penang
Date submitted for test: 7/5/07
DUT Description: XPR4550 VHF 25W MINI-U GPS
Test TX mode(s): CW
Max. Power output: 30W, 50% Duty Cycle (PTT)
TX Frequency Bands: 136-174 MHz
Signaling type: FM
Model(s) Tested: PMUD2039A
Model(s) Certified: PMUD2039A
Serial Number(s): 038THL0202
Classification: Occupational Controlled (Operator); General Population/Uncontrolled (Passengers/Bystanders)
Rule Part(s): 2.1091 (d)

**Approved Accessories:**

Antenna(s):
 HAD4006A (136-144MHz 1/4 Wave 0dBd, Mini-U connector)
 HAD4007A (146-150.8MHz 1/4 Wave 0dBd, Mini-U connector)
 HAD4008A (150.8-162MHz 1/4 Wave 0dBd, Mini-U connector)
 HAD4009A (162-174MHz 1/4 Wave 0dBd, Mini-U connector)
 HAD4014A (146-172MHz 5/8 Wave 3.0dBd, Mini-U connector)
 RAD4198A (136-144MHz 1/4 Wave 0dBd, BNC connector)
 RAD4199A (146-150.8MHz 1/4 Wave 0dBd, BNC connector)
 RAD4200A (150.8-162MHz 1/4 Wave 0dBd, BNC connector)
 RAD4201A (162-174MHz 1/4 Wave 0dBd, BNC connector)
 RAD4214A (Combo GPS/VHF - 136-144MHz 1/4 Wave 0dBd , Mini-U connector)
 RAD4215A (Combo GPS/VHF - 146-150.8MHz 1/4 Wave 0dBd, Mini-U connector)
 RAD4216A (Combo GPS/VHF - 150.8-162MHz 1/4 Wave 0dBd, Mini-U connector)
 RAD4217A (Combo GPS/VHF - 162-174MHz 1/4 Wave 0dBd, Mini-U connector)
 RAD4218A (Combo GPS/VHF - 146-172MHz 5/8 Wave 3.0dBd, Mini-U connector)
 RAD4219A (Combo GPS/VHF - 136-144MHz 1/4 Wave 0dBd, BNC connector)
 RAD4220A (Combo GPS/VHF - 146-150.8MHz 1/4 Wave 0dBd, BNC connector)
 RAD4221A (Combo GPS/VHF - 150.8-162MHz 1/4 Wave 0dBd, BNC connector)
 RAD4222A (Combo GPS/VHF - 162-174MHz 1/4 Wave 0dBd, BNC connector)

Final RF Exposure Results:**Mobile max calculated 1-g Avg. SAR: 0.16 mW/g**

Based on the information and the testing results provided herein, the undersigned certifies that when used as stated in the operating instructions supplied, said product complies with the national and international reference standards and guidelines listed in section 3.0 of this report. This report shall not be reproduced without written approval from an officially designated representative of the Motorola EME Laboratory.

Signature on file – Deanna Zakharia

 Deanna Zakharia – N&E EME Lab Senior Resource Manager,
 Laboratory Director,

Approval Date: 8/15/2007
Certification Date: 8/15/2007
Certification No.: L1070806P

TABLE OF CONTENTS

1.0	Product and System Description
2.0	Additional Options and Accessories
3.0	Measurement and Limit Standards
4.0	Data Collection Consideration
5.0	Measurement System Uncertainty Levels
6.0	Method of Measurement
6.1	EME measurements made with trunk mounted antenna(s)
6.1.1	External vehicle EME measurement
6.1.2	Internal vehicle EME measurement
6.2	EME measurements made with roof mounted antenna
6.2.1	External vehicle EME measurements
6.2.2	Internal vehicle EME measurement
7.0	Test Site
8.0	Measurement System/Equipment
9.0	Test Unit Description
10.0	Test Set-Up Description
11.0	Test Results Summary
12.0	Conclusion

APPENDIX A: Illustration of Antenna Location and Test Distances

APPENDIX B: Meter/Probe Calibration Certificates

APPENDIX C: Photos of Assessed Antennas

APPENDIX D: Detailed MPE Measurement Data

APPENDIX E: SAR Simulation Results

REVISION HISTORY

Date	Revision	Comments
8/15/07	O	Initial release

1.0 Product and System Description

FCC ID: ABZ99FT3083, model PMUD2039A is a mobile transceiver that utilizes both analog and digital two-way radio communications and also includes GPS capability. The modulation scheme used for analog is narrowband Frequency Modulation (FM). The modulation scheme used for digital is 4 Level Frequency Shift Keying (4FSK) and Time Division Multiple Access (TDMA). TDMA is used to allocate portions of the RF signal by dividing time into two slots. Transmission from a unit or base station is accommodated in time-slot lengths of 30 milliseconds and frame lengths of 60 milliseconds.

The intended use of the radio is Push-To-Talk (PTT) while the device is properly installed in a vehicle with an external antenna mounted at the center of the roof or trunk.

This device will be marketed to and used by employees solely for work-related operations, such as public safety agencies, e.g. police, fire and emergency medical. User training is the responsibility of these agencies which can be expected to employ the usage instructions, safety information and operational cautions set forth in the user's manual, instructional sessions or other means.

Accordingly this product is classified as Occupational/Controlled Exposure. However, In accordance with FCC requirements, the passengers inside the vehicle and the bystanders external to the vehicle are evaluated to the General Population/Uncontrolled Exposure Limits.

(Note that "By-standers" as used herein mean people other than operator)

2.0 Additional Options and Accessories:

All antennas are listed on front cover page.

Note 1: Antennas have optional mini-U and BNC radio termination connectors and therefore only mini-U was tested.

3.0 Measurement and Limit Standards

Measurements were performed according to the recommended guidelines in IEEE/ANSI C95.3-2002 and compared to FCC Limits Per 47 CFR 2.1091 (d) for General Population/Uncontrolled RF Exposure.

For test frequencies ranging from 136-174MHz the MPE (Maximum Permissible Exposure) limit to electromagnetic energy in equivalent plane wave free-space power density is 0.20mW/cm².

4.0 Data Collection Consideration

Power density testing was performed with DUT installed in a 1991 Ford Taurus (4-door). Measurement data was taken with the vehicles' electrical system powered by an equivalent source equal to the car running at idle and the vehicle battery measuring 13.8 volts.

5.0 Measurement System Uncertainty Levels

The information below presents an estimate of the possible errors that are associated with the measurement system.

Uncertainty Budget for Near Field Probe Measurements

	Tol. (\pm %)	Prob. Dist.	Divisor	u_i (\pm %)
Measurement System				
Survey Meter Calibration	3.0	N	1.00	3.0
Repeatability Accuracy	7.0	N	1.00	7.0
Combined Standard Uncertainty		RSS		7.6
Expanded Uncertainty		$k=2$		15

6.0 Method of Measurement

6.1 EME measurements made with trunk mounted antenna(s)

(For reference, see Illustration of antenna location and test distances in appendix A)

6.1.1 External vehicle EME measurement

(Antenna mounted at trunk center)

MPE measurements for by-stander conditions are determined by taking the average of (10) measurements in a 2m vertical line for each of the (3) test locations indicated in appendix A with 20cm increments at the test distance of 60cm from the antenna under test. The measurement probe sensor is rotated 180° at each of the ten incremental measurements to ensure the highest result is captured. These measurements are representative of persons other than the operator standing next to the vehicle.

The offered antennas mounted at the center of the trunk were assessed at the rear of the vehicle while maintaining a twenty (20) centimeter separation distance between the probe sensor and vehicle body. The worst case (Power Density) antenna/frequency was then tested at a 45° radial at the corner of the trunk, and 90° radial at the side of the trunk.

For the current test vehicle, the antenna to probe sensor separation distance is 60cm (directly behind vehicle), 99.5cm (45 degree radial) and 104cm (90 degree radial).

6.1.2 Internal vehicle EME measurement (Antenna mounted at trunk center)

While rotating survey meter probe through 180 degrees to ensure that the highest level is found, scans were performed inside of the vehicle, at both front and back seating areas, across the TX band to ascertain the highest level at the head. After the highest level is found, scans were performed vertically making two (2) additional measurements within an area approximately 40cm wide (representing the width of a person) so as to have a total of three (3) measured points, indicated below, that are averaged.

- a) Head area
- b) Chest area
- c) Lower Trunk area

6.2 EME measurements made with roof mounted antenna(s)

(For reference, see Illustration of antenna location and test distances in appendix A).

6.2.1 External vehicle EME measurement (Antenna mounted at roof center)

MPE measurements for by-stander conditions are determined by taking the average of (10) measurements in a 2m vertical line for the test location indicated in appendix A with 20cm increments at the test distance of 60cm from the antenna under test. The measurement probe sensor is rotated 180° at each of the ten incremental measurements to ensure the highest result is captured. These measurements are representative of persons other than the operator standing next to the vehicle.

Note: Actual test distance was 110cm (60cm from antenna to roof edge; 30cm from roof edge to edge of car door; 20cm vertical test line to car door); this is the closest distance that can be achieved to an antenna mounted to the center of the vehicle used for MPE compliance assessment.

6.2.2 Internal vehicle EME measurement (Antenna mounted at roof center)

While rotating survey meter probe through 180 degrees to ensure that the highest level is found, scans were performed inside of the vehicle, both at the front and back seating areas, across the TX band to ascertain the highest level in each location. After the highest level is found, two (2) additional measurements were performed vertically within an area approximately 40cm wide (representing the width of a person) so as to have a total of three (3) measured points as indicated below that are averaged.

- a) Head area
- b) Chest area
- c) Lower Trunk area

7.0 Test Site

The test site is the Motorola open area test site located at 8000 W. Sunrise Blvd., Plantation, FL. 33322.

8.0 Measurement System/Equipment

Equipment Type	Model #	SN	Calibration Due Date
Automobile	1991 Ford Taurus, 4-Door		
Survey Meter	NARDA Model 8718	01122	4/30/08
Probe - E-Field (Electric Field)	NARDA Model 8722B	12023	4/30/08
Probe - H-Field (Magnetic Field)	NARDA Model 8731	03006	4/30/08

9.0 Test Unit Description

Measurements were performed on PMUD2039A with serial numbers 038THL0202. The tested frequencies and associated power outputs are presented below.

Frequency (MHz)	Po (W)
136	29.1
148.4	29.3
156.4	28.6
159	29.5
172	29.6
174	29.4

10.0 Test Set-Up Description

The following are the mobile antenna test configurations used for this product.
(for reference, see Illustration of antenna location and test distances in the appendix A)

- a) The $\frac{1}{4}$ wave 0dB_d gain antennas (HAD4006A, HAD4007A, HAD4008A, HAD4009A, RAD4214A, RAD4215A, RAD4216A and RAD4217A) and 5/8 wave 3.0dB_d gain antennas (HAD4014A and RAD4218A) were assessed while mounted at the center of the roof of the test vehicle.
- b) The $\frac{1}{4}$ wave 0dB_d gain antennas (HAD4006A, HAD4007A, HAD4008A, HAD4009A, RAD4214A, RAD4215A, RAD4216A and RAD4217A) and 5/8 wave 3.0dB_d gain antennas (HAD4014A and RAD4218A) were assessed while mounted at the center of the trunk of the test vehicle.

Assessments were made internal and external to the test vehicle at the specified distances and test locations indicated in sections 6.0, 11.0, and appendix A.

11.0 Test Results Summary

Appendix D presents detailed MPE measurement information for each test configuration; person external or internal to the vehicle, TX frequency, antenna (location, model and gain), distance from antenna to probe sensor, E/H field measurements, calibration factor, MPE average over body, initial power, power density calc, power density max calc, IEEE/FCC controlled and uncontrolled limits, and maximum output power.

The Average over Body test methodology is consistent with IEEE/ANSI C95.3-2002 guidelines.

The MPE test measurements were done at 100% duty cycle test mode, then the final calculated results are based on a 50% actual duty cycle which is in accordance with the User Manual instructions.

External to vehicle - 10 measurements are averaged over the body (*Body_Avg*).

Internal to vehicle - 3 measurements are averaged over the body (*Body_Avg*).

Narda Survey Meter measures in percent of the controlled limit. Therefore the averages over the body used in the calculations below reflect percentages.

MPE results are based on a Push-To-Talk (PTT) 50% duty cycle in CW mode.

Therefore;

$$\text{Average_over_Body} = \text{Body_Avg} * \text{Controlled_Limit}$$

$$\text{Pwr_Density_Calc} = \text{Average_over_Body} * \text{Duty_Cycle}$$

$$\text{Pwr_Density_Max_Calc} = \text{Pwr_Density_Calc} * \frac{\text{Max_Output_Power}}{\text{Initial_Output_Power}}$$

Note; For *Initial Output Power* > *Max_Output_Power*, *Max_Output_Power* / *Initial Output Power* = 1

The tables below summarizes the MPE results of the E/H field test configurations for the PMUD2039A mobile radio. See appendices A and D respectively for test positions and detailed MPE measurement data.

TABLE 1: E-Field

Tables	Antenna Model	Antenna Location	Test Frequency (MHz)	E/H Field	Passenger / By-stander	Max Calc Pwr Density (mW/cm^2)	% of Uncontrolled Limit
Roof Mount							
1	HAD4006A	Roof	136	E	By-stander	0.03	15%
2	HAD4006A	Roof	136	E	Passenger	0.03	15%
3	HAD4007A	Roof	148.4	E	By-stander	0.02	10%
4	HAD4007A	Roof	148.4	E	Passenger	0.02	10%
5	HAD4008A	Roof	156.4	E	By-stander	0.02	10%
6	HAD4008A	Roof	156.4	E	Passenger	0.02	10%
7	HAD4009A	Roof	174	E	By-stander	0.02	10%
8	HAD4009A	Roof	174	E	Passenger	0.03	15%
9	HAD4014A	Roof	148.4	E	By-stander	0.01	5%
10	HAD4014A	Roof	148.4	E	Passenger	0.00	0%
11	HAD4014A	Roof	159	E	By-stander	0.02	10%
12	HAD4014A	Roof	159	E	Passenger	0.01	5%
13	HAD4014A	Roof	172	E	By-stander	0.01	5%
14	HAD4014A	Roof	172	E	Passenger	0.00	0%
15	RAD4214A	Roof	136	E	By-stander	0.03	15%
16	RAD4214A	Roof	136	E	Passenger	0.03	15%
17	RAD4215A	Roof	148.4	E	By-stander	0.02	10%
18	RAD4215A	Roof	148.4	E	Passenger	0.02	10%
19	RAD4216A	Roof	156.4	E	By-stander	0.02	10%
20	RAD4216A	Roof	156.4	E	Passenger	0.02	10%
21	RAD4217A	Roof	174	E	By-stander	0.03	15%
22	RAD4217A	Roof	174	E	Passenger	0.01	5%
23	RAD4218A	Roof	148.4	E	By-stander	0.02	10%
24	RAD4218A	Roof	148.4	E	Passenger	0.01	5%
25	RAD4218A	Roof	159	E	By-stander	0.02	10%
26	RAD4218A	Roof	159	E	Passenger	0.01	5%
27	RAD4218A	Roof	172	E	By-stander	0.02	10%
28	RAD4218A	Roof	172	E	Passenger	0.01	5%

TABLE 1: E-Field (continued)

Tables	Antenna Model	Antenna Location	Test Frequency (MHz)	E/H Field	Passenger / By-stander	Max Calc Pwr Density (mW/cm^2)	% of Uncontrolled Limit
Trunk Mount							
57	HAD4006A	Trunk	136	E	By-stander	0.06	30%
58	HAD4006A	Trunk	136	E	Passenger	0.09	45%
59	HAD4007A	Trunk	148.4	E	By-stander	0.06	30%
60	HAD4007A	Trunk	148.4	E	Passenger	0.08	40%
61	HAD4008A	Trunk	156.4	E	By-stander	0.06	30%
62	HAD4008A	Trunk	156.4	E	Passenger	0.07	35%
63	HAD4009A	Trunk	174	E	By-stander	0.05	25%
64	HAD4009A	Trunk	174	E	Passenger	0.09	45%
65	HAD4014A	Trunk	148.4	E	By-stander	0.01	5%
66	HAD4014A	Trunk	148.4	E	Passenger	0.00	0%
67	HAD4014A	Trunk	159	E	By-stander	0.07	35%
68	HAD4014A	Trunk	159	E	Passenger	0.02	10%
69	HAD4014A	Trunk	172	E	By-stander	0.01	5%
70	HAD4014A	Trunk	172	E	Passenger	0.00	0%
71	RAD4214A	Trunk	136	E	By-stander	0.06	30%
72	RAD4214A	Trunk	136	E	Passenger	0.08	40%
73	RAD4215A	Trunk	148.4	E	By-stander	0.06	30%
74	RAD4215A	Trunk	148.4	E	Passenger	0.06	30%
75	RAD4216A	Trunk	156.4	E	By-stander	0.06	30%
76	RAD4216A	Trunk	156.4	E	Passenger	0.05	25%
77	RAD4217A	Trunk	174	E	By-stander	0.04	20%
78	RAD4217A	Trunk	174	E	Passenger	0.07	35%
79	RAD4218A	Trunk	148.4	E	By-stander	0.05	25%
80	RAD4218A	Trunk	148.4	E	Passenger	0.06	30%
81	RAD4218A	Trunk	159	E	By-stander	0.05	25%
82	RAD4218A	Trunk	159	E	Passenger	0.07	35%
83	RAD4218A	Trunk	172	E	By-stander	0.04	20%
84	RAD4218A	Trunk	172	E	Passenger	0.06	30%
45 Degree From Trunk							
85	HAD4014A	Trunk	159	E	By-stander	0.03	15%
90 Degree From Trunk							
86	HAD4014A	Trunk	159	E	By-stander	0.03	15%

TABLE 2: H-Field

Tables	Antenna Model	Antenna Location	Test Frequency (MHz)	E/H Field	Passenger / By-stander	Max Calc Pwr Density (mW/cm^2)	% of Uncontrolled Limit
Roof Mount							
29	HAD4006A	Roof	136	H	By-stander	0.05	25%
30	HAD4006A	Roof	136	H	Passenger	0.08	40%
31	HAD4007A	Roof	148.4	H	By-stander	0.09	45%
32	HAD4007A	Roof	148.4	H	Passenger	0.09	45%
33	HAD4008A	Roof	156.4	H	By-stander	0.09	45%
34	HAD4008A	Roof	156.4	H	Passenger	0.07	35%
35	HAD4009A	Roof	174	H	By-stander	0.09	45%
36	HAD4009A	Roof	174	H	Passenger	0.03	15%
37	HAD4014A	Roof	148.4	H	By-stander	0.05	25%
38	HAD4014A	Roof	148.4	H	Passenger	0.04	20%
39	HAD4014A	Roof	159	H	By-stander	0.06	30%
40	HAD4014A	Roof	159	H	Passenger	0.04	20%
41	HAD4014A	Roof	172	H	By-stander	0.04	20%
42	HAD4014A	Roof	172	H	Passenger	0.04	20%
43	RAD4214A	Roof	136	H	By-stander	0.07	35%
44	RAD4214A	Roof	136	H	Passenger	0.09	45%
45	RAD4215A	Roof	148.4	H	By-stander	0.10	50%
46	RAD4215A	Roof	148.4	H	Passenger	0.02	10%
47	RAD4216A	Roof	156.4	H	By-stander	0.08	40%
48	RAD4216A	Roof	156.4	H	Passenger	0.04	20%
49	RAD4217A	Roof	174	H	By-stander	0.08	40%
50	RAD4217A	Roof	174	H	Passenger	0.02	10%
51	RAD4218A	Roof	148.4	H	By-stander	0.07	35%
52	RAD4218A	Roof	148.4	H	Passenger	0.01	5%
53	RAD4218A	Roof	159	H	By-stander	0.06	30%
54	RAD4218A	Roof	159	H	Passenger	0.04	20%
55	RAD4218A	Roof	172	H	By-stander	0.06	30%
56	RAD4218A	Roof	172	H	Passenger	0.04	20%

TABLE 2: H-Field (continued)

Tables	Antenna Model	Antenna Location	Test Frequency (MHz)	E/H Field	Passenger / By-stander	Max Calc Pwr Density (mW/cm^2)	% of Uncontrolled Limit
Trunk Mount							
87	HAD4006A	Trunk	136	H	By-stander	0.10	50%
88	HAD4006A	Trunk	136	H	Passenger	0.19	95%
89	HAD4007A	Trunk	148.4	H	By-stander	0.19	95%
90	HAD4007A	Trunk	148.4	H	Passenger	0.19	95%
91	HAD4008A	Trunk	156.4	H	By-stander	0.15	75%
92	HAD4008A	Trunk	156.4	H	Passenger	0.07	35%
93	HAD4009A	Trunk	174	H	By-stander	0.12	60%
94	HAD4009A	Trunk	174	H	Passenger	0.05	25%
95	HAD4014A	Trunk	148.4	H	By-stander	0.05	25%
96	HAD4014A	Trunk	148.4	H	Passenger	0.04	20%
*97	HAD4014A	Trunk	159	H	By-stander	0.20	100%
98	HAD4014A	Trunk	159	H	Passenger	0.05	25%
99	HAD4014A	Trunk	172	H	By-stander	0.07	35%
100	HAD4014A	Trunk	172	H	Passenger	0.03	15%
101	RAD4214A	Trunk	136	H	By-stander	0.09	45%
102	RAD4214A	Trunk	136	H	Passenger	0.19	95%
103	RAD4215A	Trunk	148.4	H	By-stander	0.12	60%
104	RAD4215A	Trunk	148.4	H	Passenger	0.13	65%
105	RAD4216A	Trunk	156.4	H	By-stander	0.12	60%
106	RAD4216A	Trunk	156.4	H	Passenger	0.08	40%
107	RAD4217A	Trunk	174	H	By-stander	0.10	50%
108	RAD4217A	Trunk	174	H	Passenger	0.03	15%
109	RAD4218A	Trunk	148.4	H	By-stander	0.10	50%
110	RAD4218A	Trunk	148.4	H	Passenger	0.09	45%
111	RAD4218A	Trunk	159	H	By-stander	0.13	65%
112	RAD4218A	Trunk	159	H	Passenger	0.03	15%
113	RAD4218A	Trunk	172	H	By-stander	0.10	50%
114	RAD4218A	Trunk	172	H	Passenger	0.00	0%
45 Degree From Trunk							
115	HAD4014A	Trunk	159	H	By-stander	0.07	35%
90 Degree From Trunk							
116	HAD4014A	Trunk	159	H	By-stander	0.07	35%

* Meet or exceed the specification limit of 0.2mW/cm².

12.0 Conclusion



Depending on the test frequency, the PMUD2039A mobile assessments were performed with an output power range of 28.6W – 29.6W. The highest power density results for the PMUD2039A VHF mobile device scaled to the maximum allowable power output is 0.20mW/cm^2 for the internal, and 0.19mW/cm^2 for the external to the vehicle.

These MPE results demonstrate compliance to the FCC/IEEE Occupational/Controlled Exposure limit.

FCC rules require compliance for passengers and bystanders to the FCC General Population/Uncontrolled limits. Although MPE is a convenient method of demonstrating compliance, SAR is recognized as the "basic restriction". For those configurations exceeding the MPE limit noted in section 11.0 table, compliance to the FCC SAR General Population/Uncontrolled limit of 1.6mW/g is demonstrated in Appendix E via SAR computational analysis.

The computation results show that this device, when used with the specified antennas, exhibit a maximum 1-g average SAR of 0.16mW/g .

APPENDIX A
Antenna Location Drawing with Test Locations Identified



APPENDIX B
Meter/Probe Calibration Certificates

CERTIFICATION OF CALIBRATION CONFORMANCE

LIBERTY LABS, INC. 1346 Yellowwood Road Kimballton, IA 51543
 EMAIL: mhoward@liberty-labs.com TEL: (712) 773-2199 FAX: (712)773-2299

This probe has been individually calibrated using IEEE Standard for Calibration of Electromagnetic Field Sensors and Probes, Excluding Antennas, from 9 kHz to 40 GHz; IEEE Std. 1309-1996. All results of this calibration relate only to the items that were calibrated.

ACCREDITATION NOTES:

A complete copy of the scope of our A2LA accreditation is available upon request.

Instrumentation Environment: TEMP: 23°C RH: 35%
 Calibration Environment: TEMP: 23°C RH: 35%
 Barometric Pressure (inches): 29.85
 CERTIFICATE NO.: 2007041704
 CLIENT: Lockheed Martin IMC, Bldg. 5100, Stennis Space Center, MS, 39529, USA
 MANUFACTURER: Narda
 MODEL NUMBER: 8722B & 8718
 SERIAL NUMBER: 12023 & 01122
 ASSET NUMBER: PRNRA002 & RFNRA001
 DATE OF CALIBRATION: Monday, April 30, 2007
 NAME OF CALIBRATING ORGANIZATION Liberty Labs, Inc.
 CALIBRATED BY: DSG *DSG*
 RE-CERTIFICATION DATE: 1 year from calibration date. This is a recommended recalibration interval but there are any number of factors that may cause the calibration item to drift out of calibration before the recommended interval has expired. Customer has been contacted concerning re-certification interval and documentation has been received and is on-file.

RECEIVED STATUS

Received in tolerance:

RETURNED STATUS

Returned in tolerance:

Returned limited cal.:

NOTES: Below 1-GHz Liberty Labs uses a transfer standard calibrated to IEEE1309 Standards. Liberty Labs uses this transfer standard via the substitute method outlined in IEEE 1309 in a triplate test cell to calibrate probes. The uncertainty between the TEM and Triplate is minimal in this application. Client declined isotropic response testing. In/Out of tolerance based on alignment/mounting position and not on manufacturer's specifications. A probe position document is included with this certificate.

L
L, Inc.

This report is not to be reproduced, except in full, without written approval of Liberty Labs, Inc.

Michael W. Howard

ENGINEER IN CHARGE
 MICHAEL W. HOWARD
 NARTE CERTIFIED EMC ENGINEER, NO. EM C-000102-NE

ispb-position

Page 1 of 4



Probe01.txt

Date of Calibration: 30-April-2007
Date Printed: Monday, April 30, 2007
Customer Name: Lockheed Martin IMC
Probe Manufacturer: Narda
Probe Model: 8722B & 8718
Probe Serial No.: 12023 & 01122
Temperature (Deg C): 23
Humidity (%): 35
Notes: Calibrated with 8718 Monitor, s/n 01122.
CAL CERT #: 2007041704

Correction Factors		
Frequency in MHz	Multiplier	dB
1	3.15	9.96
15	1.11	0.87
30	0.74	-2.66
75	0.60	-4.44
100	0.62	-4.15
150	0.47	-6.56
200	0.57	-4.85
250	0.67	-3.45
300	0.66	-3.57
400	0.68	-3.40
500	0.62	-4.16
600	0.42	-7.62
700	0.40	-8.05
800	0.44	-7.12
900	1.14	1.10
1000	0.64	-3.85
2000	0.65	-3.71
2450	0.76	-2.40
3000	0.83	-1.57
3500	1.18	1.41
4000	1.08	0.67
5000	0.76	-2.37
5500	0.88	-1.07
6000	0.99	-0.08
7000	0.72	-2.83
10000	0.93	-0.64
10500	0.72	-2.80
11000	0.70	-3.07

CERTIFICATION OF CALIBRATION CONFORMANCE

LIBERTY LABS, INC. 1346 Yellowwood Road Kimballton, IA 51543
 EMAIL: mhoward@liberty-labs.com TEL: (712) 773-2199 FAX: (712)773-2299

This probe has been individually calibrated using IEEE Standard for Calibration of Electromagnetic Field Sensors and Probes, Excluding Antennas, from 9 kHz to 40 GHz; IEEE Std. 1309-1996. All results of this calibration relate only to the items that were calibrated.

ACCREDITATION NOTES:

A complete copy of the scope of our A2LA accreditation is available upon request.

Instrumentation Environment: TEMP: 23°C RH: 35%
 Calibration Environment: TEMP: 23°C RH: 35%

Barometric Pressure (inches): 29.85

CERTIFICATE NO.: 2007041703

CLIENT: Lockheed Martin IMC, Bldg. 5100, Stennis Space Center, MS, 39529, USA

MANUFACTURER: Narda

MODEL NUMBER: 8731 & 8718

SERIAL NUMBER: 03006 & 01122

ASSET NUMBER: PRNRH003 & RFNRA001

DATE OF CALIBRATION: Monday, April 30, 2007

NAME OF CALIBRATING ORGANIZATION Liberty Labs, Inc.

CALIBRATED BY: DSG *DSG*

RE-CERTIFICATION DATE: 1 year from calibration date. This is a recommended recalibration interval but there are any number of factors that may cause the calibration item to drift out of calibration before the recommended interval has expired. Customer has been contacted concerning re-certification interval and documentation has been received and is on-file.

RECEIVED STATUS

Received in tolerance:

RETURNED STATUS

Returned in tolerance:

Returned limited cal.:

NOTES: Below 1-GHz Liberty Labs uses a transfer standard calibrated to IEEE1309 Standards. Liberty Labs uses this transfer standard via the substitute method outlined in IEEE-1309 in a triplate test cell to calibrate probes. The uncertainty between the TEM and Triplate is minimal in this application. Client declined isotropic response testing. In/Out of tolerance based on alignment/mounting position and not on manufacturer's specifications. A probe position document is included with this certificate.

LL, Inc.

This report is not to be reproduced, except in full, without written approval of Liberty Labs, Inc.

Michael W. Howard

ENGINEER IN CHARGE
 MICHAEL W. HOWARD
 NARTE CERTIFIED EMC ENGINEER, NO. EM C-000102-NE

ispb-position

Page 1 of 4



Probe01.txt

Date of Calibration: 30-April-2007
Date Printed: Monday, April 30, 2007
Customer Name: Lockheed Martin IMC
Probe Manufacturer: Narda
Probe Model: 8731 & 8718
Probe Serial No.: 03006 & 01122
Temperature (Deg C): 23
Humidity (%): 35
Notes:
CAL CERT #: 2007041703

Correction Factors for mW/cm²


Frequency in MHz	Multiplier	in dB
10	0.54	-5.32
15	0.63	-4.05
30	1.46	3.27
50	1.34	2.54
75	0.51	-5.92
100	0.67	-3.42
150	1.29	2.23
200	0.87	-1.25
250	0.91	-0.86
300	1.70	4.62

APPENDIX C

Photos of Assessed Antenna



Antenna kit numbers, from left to right;
HAD4006A, HAD4007A, HAD4008A, HAD4009A and HAD4014A



GPS Base – Side View



GPS Base – Top View



Antenna kit numbers, from left to right (all antenna kit numbers below include GPS Base PMAN4004A);
RAD4216A, RAD4217A, RAD4218A, RAD4214A and RAD4215A

APPENDIX D

Detailed MPE Measurement Data

Note: (*) Calc. Power Density has been adjusted for test frequencies 148.4MHz, 156.4MHz, and 159MHz due to the Narda meter can not go lower than 0.5 correction factor.

----- E- Fields -----

Table 1

Table 2

Internal Vehicle MPE Assessment @ 136 MHz										
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)		Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)
						Back	Front			
Roof (cnt)	HAD4006A	2.15	Highest Reading	E	0.51	0.053	0.017	29.1	0.026	0.03
Measurement Grid										
Test Position		% of Control Limit Head		% of Control Limit Chest		% of Control Limit Lower Trunk		IEEE Controlled Limit:		1.00
Back Seat		4.4%		4.0%		7.4%		IEEE Uncontrolled Limit:		0.20
Front Seat		2.2%		1.5%		1.3%		RF Po (*Max):		30.0

*Table 3

External Vehicle MPE Assessment @						148.4 MHz					
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)		
Roof (cnt)	HAD4007A	2.15	60 (actual 110 cm)	E	0.47	0.048	29.3	0.023	0.02		
Measurement Grid											
Test Position	Height (cm)	% of Control Limit		Test Position	Height (cm)	% of Control Limit		IEEE Controlled Limit	IEEE Uncontrolled Limit		
1	20	1.5%		6	120	6.0%		1.00	0.20		
2	40	2.0%		7	140	7.9%		RF Po (*Max)	30.0		
3	60	2.3%		8	160	7.8%					
4	80	2.3%		9	180	7.5%					
5	100	3.9%		10	200	7.1%					

*Table 4

Internal Vehicle MPE Assessment @ 148.4 MHz										
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)		Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)
						Back	Front			
Roof (cnt)	HAD4007A	2.15	Highest Reading	E	0.47	0.051	0.019	29.3	0.024	0.02
Measurement Grid										
Test Position		% of Control Limit Head		% of Control Limit Chest		% of Control Limit Lower Trunk		IEEE Controlled Limit:		
Back Seat		8.6%		5.6%		1.1%		IEEE Uncontrolled Limit:		
Front Seat		1.3%		2.5%		1.8%		RF Po (*Max):		

*Table 5

External Vehicle MPE Assessment @ 156.4 MHz											
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)		
Roof (cnt)	HAD4008A	2.15	60 (actual 110 cm)	E	0.48	0.047	28.6	0.023	0.02		
Measurement Grid											
Test Position	Height (cm)	% of Control Limit		Test Position	Height (cm)	% of Control Limit		IEEE Controlled Limit	IEEE Uncontrolled Limit		
1	20	1.5%		6	120	5.7%		1.00	0.20		
2	40	1.6%		7	140	6.8%		RF Po (*Max)	30.0		
3	60	2.0%		8	160	8.2%					
4	80	2.4%		9	180	7.7%					
5	100	3.9%		10	200	7.3%					

*Table 6

Internal Vehicle MPE Assessment @ 156.4 MHz										
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)		Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)
						Back	Front			
Roof (cnt)	HAD4008A	2.15	Highest Reading	E	0.48	0.036	0.014	28.6	0.017	0.02
Measurement Grid										
Test Position	% of Control Limit Head		% of Control Limit Chest		% of Control Limit Lower Trunk		IEEE Controlled Limit:		1.00	
Back Seat	6.1%		3.2%		1.4%		IEEE Uncontrolled Limit:		0.20	
Front Seat	1.4%		1.6%		1.2%		RF Po (*Max):		30.0	

Table 7

External Vehicle MPE Assessment @ 174 MHz								
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)
Roof (cnt)	HAD4009A	2.15	60 (actual 110 cm)	E	0.52	0.042	29.4	0.021
Measurement Grid								
Test Position	Height (cm)	% of Control Limit	Test Position	Height (cm)	% of Control Limit	IEEE Controlled Limit	IEEE Uncontrolled Limit	
1	20	1.5%	6	120	3.5%	1.00	0.20	
2	40	1.9%	7	140	5.4%			
3	60	1.9%	8	160	8.0%			
4	80	1.6%	9	180	8.4%			RF Po (*Max)
5	100	2.2%	10	200	8.0%		30.0	

Table 8

Internal Vehicle MPE Assessment @ 174 MHz								
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)
						Back		
Roof (cnt)	HAD4009A	2.15	Highest Reading	E	0.52	0.053	0.066	29.4
Measurement Grid								
Test Position	% of Control Limit Head	% of Control Limit Chest	% of Control Limit Lower Trunk	IEEE Controlled Limit:			1.00	
Back Seat	4.4%	5.1%	6.3%	IEEE Uncontrolled Limit:			0.20	
Front Seat	4.0%	9.9%	5.8%			RF Po (*Max):	30.0	

*Table 9

External Vehicle MPE Assessment @ 148.4 MHz								
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)
Roof (cnt)	HAD4014A	5.15	60 (actual 110 cm)	E	0.47	0.014	29.3	0.006
Measurement Grid								
Test Position	Height (cm)	% of Control Limit	Test Position	Height (cm)	% of Control Limit	IEEE Controlled Limit	IEEE Uncontrolled Limit	
1	20	0.66%	6	120	0.85%	1.00	0.20	
2	40	0.71%	7	140	1.40%			
3	60	0.95%	8	160	1.90%			
4	80	0.90%	9	180	2.50%			RF Po (*Max)
5	100	0.93%	10	200	2.90%		30.0	

*Table 10

Internal Vehicle MPE Assessment @ 148.4 MHz										
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)		Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)
						Back	Front			
Roof (cnt)	HAD4014A	5.15	Highest Reading	E	0.47	0.004	0.005	29.3	0.002	0.00
Measurement Grid										
Test Position		% of Control Limit Head		% of Control Limit Chest		% of Control Limit Lower Trunk		IEEE Controlled Limit:		
Back Seat		0.47%		0.36%		0.33%		IEEE Uncontrolled Limit:		
Front Seat		0.33%		0.36%		0.67%		RF Po (*Max):		

*Table 11

External Vehicle MPE Assessment @ 159 MHz											
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)		
Roof (cnt)	HAD4014A	5.15	60 (actual 110 cm)	E	0.49	0.031	29.5	0.015	0.02		
Measurement Grid											
Test Position	Height (cm)	% of Control Limit		Test Position	Height (cm)	% of Control Limit		IEEE Controlled Limit	IEEE Uncontrolled Limit		
1	20	1.0%		6	120	2.3%		1.00	0.20		
2	40	1.0%		7	140	3.3%		RF Po (*Max)	30.0		
3	60	1.0%		8	160	4.4%					
4	80	1.0%		9	180	6.6%					
5	100	1.4%		10	200	8.8%					

*Table 12

Internal Vehicle MPE Assessment @ 159 MHz										
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)	
Roof (cnt)	HAD4014A	5.15	Highest Reading	E	0.49	0.012	0.009	29.5	0.006	0.01
Measurement Grid										
Test Position		% of Control Limit Head		% of Control Limit Chest		% of Control Limit Lower Trunk		IEEE Controlled Limit:		
Back Seat		1.9%		1.1%		0.7%		IEEE Uncontrolled Limit:		
Front Seat		0.8%		1.0%		1.0%		RF Po (*Max):		

Table 13

External Vehicle MPE Assessment @ 172 MHz								
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)
Roof (cnt)	HAD4014A	5.15	60 (actual 110 cm)	E	0.51	0.011	29.6	0.005
Measurement Grid								
Test Position	Height (cm)	% of Control Limit	Test Position	Height (cm)	% of Control Limit	IEEE Controlled Limit	IEEE Uncontrolled Limit	
1	20	1.0%	6	120	0.9%	1.00	0.20	
2	40	0.9%	7	140	1.0%			
3	60	1.2%	8	160	1.1%			
4	80	0.9%	9	180	1.3%			RF Po (*Max)
5	100	0.9%	10	200	1.5%		30.0	

Table 14

Internal Vehicle MPE Assessment @ 172 MHz								
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)
						Back		
Roof (cnt)	HAD4014A	5.15	Highest Reading	E	0.51	0.007	0.009	29.6
Measurement Grid								
Test Position		% of Control Limit Head	% of Control Limit Chest		% of Control Limit Lower Trunk	IEEE Controlled Limit:		1.00
Back Seat		0.8%	0.6%		0.8%	IEEE Uncontrolled Limit:		0.20
Front Seat		0.7%	1.0%		0.9%	RF Po (*Max):		30.0

Table 15

External Vehicle MPE Assessment @ 136 MHz								
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)
Roof (cnt)	RAD4214A	2.15	60 (actual 110 cm)	E	0.51	0.057	29.1	0.028
Measurement Grid								
Test Position	Height (cm)	% of Control Limit	Test Position	Height (cm)	% of Control Limit	IEEE Controlled Limit	IEEE Uncontrolled Limit	
1	20	1.6%	6	120	7.4%	1.00	0.20	
2	40	1.8%	7	140	10.2%			
3	60	2.7%	8	160	9.8%			
4	80	3.6%	9	180	8.5%			RF Po (*Max)
5	100	4.4%	10	200	6.6%		30.0	

Table 16

Internal Vehicle MPE Assessment @ 136 MHz										
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)		
						Back/Front seats (mW/cm^2)				
Back	Front									
Roof (cnt)	RAD4214A	2.15	Highest Reading	E	0.51	0.067	0.019	29.1	0.034	0.03

Measurement Grid								
Test Position		% of Control Limit Head		% of Control Limit Chest		% of Control Limit Lower Trunk		IEEE Controlled Limit:
Back Seat		5.6%		5.1%		9.4%		IEEE Uncontrolled Limit:
Front Seat		2.8%		1.6%		1.3%		RF Po (*Max):

*Table 17

External Vehicle MPE Assessment @ 148.4 MHz									
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	
Roof (cnt)	RAD4215A	2.15	60 (actual 110 cm)	E	0.47	0.051	29.3	0.024	0.02

Measurement Grid								
Test Position	Height (cm)	% of Control Limit	Test Position	Height (cm)	% of Control Limit	IEEE Controlled Limit	IEEE Uncontrolled Limit	RF Po (*Max)
1	20	0.8%	6	120	6.1%	1.00	0.20	
2	40	1.3%	7	140	9.0%			
3	60	1.8%	8	160	9.4%			
4	80	1.7%	9	180	8.8%			
5	100	3.6%	10	200	8.0%		30.0	

*Table 18

Internal Vehicle MPE Assessment @ 148.4 MHz										
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)		
						Back/Front seats (mW/cm^2)				
Back	Front									
Roof (cnt)	RAD4215A	2.15	Highest Reading	E	0.47	0.042	0.010	29.3	0.020	0.02

Measurement Grid								
Test Position		% of Control Limit Head		% of Control Limit Chest		% of Control Limit Lower Trunk		IEEE Controlled Limit:
Back Seat		9.3%		2.5%		0.7%		IEEE Uncontrolled Limit:
Front Seat		1.3%		1.1%		0.7%		RF Po (*Max):

*Table 19

External Vehicle MPE Assessment @ 156.4 MHz									
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)
Roof (cnt)	RAD4216A	2.15	60 (actual 110 cm)	E	0.48	0.049	28.6	0.023	0.02
Measurement Grid									
Test Position	Height (cm)	% of Control Limit		Test Position	Height (cm)	% of Control Limit		IEEE Controlled Limit	IEEE Uncontrolled Limit
1	20	1.2%		6	120	6.5%		1.00	0.20
2	40	1.4%		7	140	7.5%			
3	60	1.4%		8	160	8.0%			
4	80	2.1%		9	180	8.5%			
5	100	4.6%		10	200	7.7%			
								RF Po (*Max):	30.0

*Table 20

Internal Vehicle MPE Assessment @ 156.4 MHz										
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)	
						Back				
Roof (cnt)	RAD4216A	2.15	Highest Reading	E	0.48	0.037	0.012	28.6	0.018	0.02
Measurement Grid										
Test Position	% of Control Limit Head		% of Control Limit Chest		% of Control Limit Lower Trunk		IEEE Controlled Limit:		1.00	
Back Seat	6.8%		2.6%		1.6%		IEEE Uncontrolled Limit:		0.20	
Front Seat	1.3%		1.6%		0.8%			RF Po (*Max):	30.0	

Table 21

External Vehicle MPE Assessment @ 174 MHz									
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)
Roof (cnt)	RAD4217A	2.15	60 (actual 110 cm)	E	0.52	0.049	29.4	0.025	0.03
Measurement Grid									
Test Position	Height (cm)	% of Control Limit		Test Position	Height (cm)	% of Control Limit		IEEE Controlled Limit	IEEE Uncontrolled Limit
1	20	1.4%		6	120	5.4%		1.00	0.20
2	40	1.4%		7	140	7.3%			
3	60	1.7%		8	160	8.6%			
4	80	1.9%		9	180	9.5%			
5	100	3.6%		10	200	8.3%			30.0
								RF Po (*Max):	

Table 22

Internal Vehicle MPE Assessment @ 174 MHz										
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)		Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)
						Back	Front			
Roof (cnt)	RAD4217A	2.15	Highest Reading	E	0.52	0.026	0.015	29.4	0.013	0.01
Measurement Grid										
Test Position		% of Control Limit Head		% of Control Limit Chest		% of Control Limit Lower Trunk		IEEE Controlled Limit:		
Back Seat		3.4%		2.2%		2.1%		IEEE Uncontrolled Limit:		
Front Seat		1.6%		1.7%		1.2%		RF Po (*Max):		
								30.0		

*Table 23

External Vehicle MPE Assessment @ 148.4 MHz											
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)		
Roof (cnt)	RAD4218A	5.15	60 (actual 110 cm)	E	0.47	0.047	29.3	0.022	0.02		
Measurement Grid											
Test Position	Height (cm)	% of Control Limit		Test Position	Height (cm)	% of Control Limit		IEEE Controlled Limit	IEEE Uncontrolled Limit		
1	20	1.2%		6	120	4.4%		1.00	0.20		
2	40	1.4%		7	140	6.4%		RF Po (*Max)	30.0		
3	60	2.2%		8	160	7.6%					
4	80	1.8%		9	180	9.3%					
5	100	2.6%		10	200	9.6%					

*Table 24

Internal Vehicle MPE Assessment @ 148.4 MHz										
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)		Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)
						Back	Front			
Roof (cnt)	RAD4218A	5.15	Highest Reading	E	0.47	0.027	0.010	29.3	0.013	0.01
Measurement Grid										
Test Position		% of Control Limit Head		% of Control Limit Chest		% of Control Limit Lower Trunk		IEEE Controlled Limit:		
Back Seat		5.3%		1.9%		1.0%		IEEE Uncontrolled Limit:		
Front Seat		1.0%		1.3%		0.7%		RF Po (*Max):		
								30.0		

*Table 25

External Vehicle MPE Assessment @ 159 MHz												
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)				
Roof (cnt)	RAD4218A	5.15	60 (actual 110 cm)	E	0.49	0.045	29.5	0.022				
Measurement Grid												
Test Position	Height (cm)	% of Control Limit		Test Position	Height (cm)	% of Control Limit		IEEE Controlled Limit				
1	20	1.0%		6	120	4.0%		1.00				
2	40	0.9%		7	140	5.6%						
3	60	1.4%		8	160	7.7%						
4	80	1.5%		9	180	9.7%						
5	100	2.8%		10	200	10.1%						
RF Po (*Max)												
30.0												

*Table 26

Internal Vehicle MPE Assessment @ 159 MHz								
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)
						Back		
Roof (cnt)	RAD4218A	5.15	Highest Reading	E	0.49	0.024	0.008	29.5
Measurement Grid								
Test Position	% of Control Limit Head		% of Control Limit Chest		% of Control Limit Lower Trunk		IEEE Controlled Limit:	
Back Seat	3.8%		2.0%		1.3%		IEEE Uncontrolled Limit:	
Front Seat	0.9%		1.0%		0.6%		RF Po (*Max):	
								30.0

Table 27

External Vehicle MPE Assessment @ 172 MHz												
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)				
Roof (cnt)	RAD4218A	5.15	60 (actual 110 cm)	E	0.51	0.038	29.6	0.019				
Measurement Grid												
Test Position	Height (cm)	% of Control Limit		Test Position	Height (cm)	% of Control Limit		IEEE Controlled Limit				
1	20	1.2%		6	120	2.8%		1.00				
2	40	1.2%		7	140	4.0%						
3	60	1.5%		8	160	6.7%						
4	80	1.8%		9	180	7.6%						
5	100	1.9%		10	200	8.8%						
RF Po (*Max)												
30.0												

Table 28

Internal Vehicle MPE Assessment @ 172 MHz										
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)		Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)
						Back	Front			
Roof (cnt)	RAD4218A	5.15	Highest Reading	E	0.51	0.016	0.008	29.6	0.008	0.01
Measurement Grid										
Test Position		% of Control Limit Head		% of Control Limit Chest		% of Control Limit Lower Trunk		IEEE Controlled Limit:		
Back Seat		2.2%		1.4%		1.1%		IEEE Uncontrolled Limit:		
Front Seat		0.8%		1.0%		0.6%		RF Po (*Max):		

----- H - Fields -----

Table 29

External Vehicle MPE Assessment @ 136 MHz											
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)		
Roof (cnt)	HAD4006A	2.15	60 (actual 110 cm)	H	1.12	0.093	29.1	0.046	0.05		
Measurement Grid											
Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)		Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)		IEEE Controlled Limit	IEEE Uncontrolled Limit		
1	20	0.058		6	120	0.110		1.00	0.20		
2	40	0.045		7	140	0.100		RF Po (*Max)			
3	60	0.066		8	160	0.070					
4	80	0.110		9	180	0.140					
5	100	0.120		10	200	0.110		30.0			

Table 30

Internal Vehicle MPE Assessment @ 136 MHz										
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)		Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)
						Back	Front			
Roof (cnt)	HAD4006A	2.15	Highest Reading	H	1.12	0.150	0.063	29.1	0.075	0.08
Measurement Grid										
Test Position		Meas. Pwr. Density Head (mW/cm^2)		Meas. Pwr. Density Chest (mW/cm^2)		Meas. Pwr. Density Lower Trunk (mW/cm^2)		IEEE Controlled Limit:		
Back Seat		0.140		0.130		0.180		IEEE Uncontrolled Limit:		
Front Seat		0.061		0.066		0.063		RF Po (*Max):		

Table 31

External Vehicle MPE Assessment @ 148.4 MHz									
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	
Roof (cnt)	HAD4007A	2.15	60 (actual 110 cm)	H	1.27	0.170	29.3	0.085	
Measurement Grid									
Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)		Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)		IEEE Controlled Limit	
1	20	0.120		6	120	0.160		1.00	
2	40	0.120		7	140	0.240		RF Po (*Max)	
3	60	0.140		8	160	0.210			
4	80	0.180		9	180	0.170			
5	100	0.170		10	200	0.190		30.0	

Table 32

Internal Vehicle MPE Assessment @ 148.4 MHz								
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)
Roof (cnt)	HAD4007A	2.15	Highest Reading	H	1.27	0.177	0.120	29.3
Measurement Grid								
Test Position	Meas. Pwr. Density Head (mW/cm^2)		Meas. Pwr. Density Chest (mW/cm^2)		Meas. Pwr. Density Lower Trunk (mW/cm^2)		IEEE Controlled Limit:	
Back Seat	0.170		0.140		0.220		IEEE Uncontrolled Limit:	
Front Seat	0.070		0.100		0.190		RF Po (*Max):	

Table 33

External Vehicle MPE Assessment @ 156.4 MHz									
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	
Roof (cnt)	HAD4008A	2.15	60 (actual 110 cm)	H	1.24	0.168	28.6	0.084	
Measurement Grid									
Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)		Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)		IEEE Controlled Limit	
1	20	0.100		6	120	0.180		1.00	
2	40	0.110		7	140	0.240		RF Po (*Max)	
3	60	0.130		8	160	0.210			
4	80	0.160		9	180	0.210			
5	100	0.170		10	200	0.170		30.0	

Table 34

Internal Vehicle MPE Assessment @ 156.4 MHz										
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)		Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)
						Back	Front			
Roof (cnt)	HAD4008A	2.15	Highest Reading	H	1.24	0.130	0.093	28.6	0.065	0.07
Measurement Grid										
Test Position		Meas. Pwr. Density Head (mW/cm^2)		Meas. Pwr. Density Chest (mW/cm^2)		Meas. Pwr. Density Lower Trunk (mW/cm^2)		IEEE Controlled Limit:		
Back Seat		0.140		0.120		0.130		IEEE Uncontrolled Limit:		
Front Seat		0.100		0.100		0.080		RF Po (*Max):		
30.0										

Table 35

External Vehicle MPE Assessment @ 174 MHz											
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)		
Roof (cnt)	HAD4009A	2.15	60 (actual 110 cm)	H	1.09	0.170	29.4	0.085	0.09		
Measurement Grid											
Test Position	Height (cm)	Meas. Pwr. Density Head (mW/cm^2)		Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)		IEEE Controlled Limit	IEEE Uncontrolled Limit		
1	20	0.120		6	120	0.150		1.00	0.20		
2	40	0.110		7	140	0.240		RF Po (*Max)			
3	60	0.120		8	160	0.250					
4	80	0.110		9	180	0.260					
5	100	0.150		10	200	0.190			30.0		

Table 36

Internal Vehicle MPE Assessment @ 174 MHz										
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)		Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)
						Back	Front			
Roof (cnt)	HAD4009A	2.15	Highest Reading	H	1.09	0.067	0.051	29.4	0.033	0.03
Measurement Grid										
Test Position	Meas. Pwr. Density Head (mW/cm^2)		Meas. Pwr. Density Chest (mW/cm^2)		Meas. Pwr. Density Lower Trunk (mW/cm^2)		IEEE Controlled Limit:		1.00	
Back Seat	0.070		0.060		0.070		IEEE Uncontrolled Limit:		0.20	
Front Seat	0.050		0.061		0.043		RF Po (*Max):		30.0	

Table 37

External Vehicle MPE Assessment @ 148.4 MHz									
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)
Roof (cnt)	HAD4014A	5.15	60 (actual 110 cm)	H	1.27	0.088	29.3	0.044	0.05
Measurement Grid									
Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)	Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)	IEEE Controlled Limit	IEEE Uncontrolled Limit		
1	20	0.077	6	120	0.087	1.00	0.20		
2	40	0.076	7	140	0.100				
3	60	0.083	8	160	0.120				
4	80	0.081	9	180	0.076			RF Po (*Max)	
5	100	0.100	10	200	0.082		30.0		

Table 38

Internal Vehicle MPE Assessment @ 148.4 MHz										
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)		Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)
						Back	Front			
Roof (cnt)	HAD4014A	5.15	Highest Reading	H	1.27	0.075	0.075	29.3	0.038	0.04
Measurement Grid										
Test Position	Meas. Pwr. Density Head (mW/cm^2)	Meas. Pwr. Density Chest (mW/cm^2)	Meas. Pwr. Density Lower Trunk (mW/cm^2)			IEEE Controlled Limit:			1.00	
Back Seat	0.058	0.071	0.097			IEEE Uncontrolled Limit:			0.20	
Front Seat	0.066	0.093	0.065				RF Po (*Max):		30.0	

Table 39

External Vehicle MPE Assessment @ 159 MHz									
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)
Roof (cnt)	HAD4014A	5.15	60 (actual 110 cm)	H	1.21	0.113	29.5	0.056	0.06
Measurement Grid									
Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)	Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)	IEEE Controlled Limit	IEEE Uncontrolled Limit		
1	20	0.051	6	120	0.100	1.00	0.20		
2	40	0.090	7	140	0.100				
3	60	0.077	8	160	0.150				
4	80	0.096	9	180	0.160			RF Po (*Max)	
5	100	0.094	10	200	0.210		30.0		

Table 40

Internal Vehicle MPE Assessment @ 159 MHz										
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)		Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)
						Back	Front			
Roof (cnt)	HAD4014A	5.15	Highest Reading	H	1.21	0.079	0.056	29.5	0.040	0.04
Measurement Grid										
Test Position		Meas. Pwr. Density Head (mW/cm^2)		Meas. Pwr. Density Chest (mW/cm^2)		Meas. Pwr. Density Lower Trunk (mW/cm^2)		IEEE Controlled Limit:		1.00
Back Seat		0.058		0.069		0.110		IEEE Uncontrolled Limit:		0.20
Front Seat		0.025		0.058		0.085		RF Po (*Max):		30.0

Table 41

External Vehicle MPE Assessment @ 172 MHz											
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)			
Roof (cnt)	HAD4014A	5.15	60 (actual 110 cm)	H	1.11	0.085	29.6	0.043	0.04		
Measurement Grid											
Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)		Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)		IEEE Controlled Limit	IEEE Uncontrolled Limit		
1	20	0.084		6	120	0.100		1.00	0.20		
2	40	0.100		7	140	0.086		RF Po (*Max)	30.0		
3	60	0.100		8	160	0.082					
4	80	0.090		9	180	0.062					
5	100	0.098		10	200	0.049					

Table 42

Internal Vehicle MPE Assessment @ 172 MHz										
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)		
Roof (cnt)	HAD4014A	5.15	Highest Reading	H	1.11	0.071	0.064	29.6	0.035	0.04
Measurement Grid						IEEE Controlled Limit:				
Test Position		Meas. Pwr. Density Head (mW/cm^2)		Meas. Pwr. Density Chest (mW/cm^2)		Meas. Pwr. Density Lower Trunk (mW/cm^2)		RF Po (*Max):		
Back Seat		0.041		0.072		0.099		IEEE Uncontrolled Limit:		0.20
Front Seat		0.058		0.058		0.075		RF Po (*Max):		30.0

Table 43

External Vehicle MPE Assessment @ 136 MHz								
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)
Roof (cnt)	RAD4214A	2.15	60 (actual 110 cm)	H	1.12	0.135	29.1	0.068
Measurement Grid								
Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)	Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)	IEEE Controlled Limit	IEEE Uncontrolled Limit	
1	20	0.080	6	120	0.170	1.00	0.20	
2	40	0.110	7	140	0.160			
3	60	0.140	8	160	0.110			
4	80	0.140	9	180	0.150			RF Po (*Max)
5	100	0.150	10	200	0.140			30.0

Table 44

Internal Vehicle MPE Assessment @ 136 MHz								
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)
Roof (cnt)	RAD4214A	2.15	Highest Reading	H	1.12	0.173	0.137	29.1
Measurement Grid								
Test Position		Meas. Pwr. Density Head (mW/cm^2)	Meas. Pwr. Density Chest (mW/cm^2)		Meas. Pwr. Density Lower Trunk (mW/cm^2)	IEEE Controlled Limit:		1.00
Back Seat		0.190	0.150		0.180	IEEE Uncontrolled Limit:		0.20
Front Seat		0.160	0.130		0.120	RF Po (*Max):		30.0

Table 45

External Vehicle MPE Assessment @ 148.4 MHz								
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)
Roof (cnt)	RAD4215A	2.15	60 (actual 110 cm)	H	1.27	0.189	29.3	0.095
Measurement Grid								
Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)	Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)	IEEE Controlled Limit	IEEE Uncontrolled Limit	
1	20	0.090	6	120	0.210	1.00	0.20	
2	40	0.120	7	140	0.230			
3	60	0.180	8	160	0.200			
4	80	0.160	9	180	0.240			RF Po (*Max)
5	100	0.210	10	200	0.250			30.0

Table 46

Internal Vehicle MPE Assessment @ 148.4 MHz										
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)				
						Back	Front	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	
Roof (cnt)	RAD4215A	2.15	Highest Reading	H	1.27	0.037	0.003	29.3	0.018	0.02

Measurement Grid									
Test Position		Meas. Pwr. Density Head (mW/cm^2)	Meas. Pwr. Density Chest (mW/cm^2)	Meas. Pwr. Density Lower Trunk (mW/cm^2)	IEEE Controlled Limit:			1.00	
Back Seat		0.080	0.020	0.010	IEEE Uncontrolled Limit:			0.20	
Front Seat		0.003	0.006	0.000				RF Po (*Max):	30.0

Table 47

External Vehicle MPE Assessment @ 156.4 MHz									
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	
Roof (cnt)	RAD4216A	2.15	60 (actual 110 cm)	H	1.24	0.156	28.6	0.078	0.08

Measurement Grid								
Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)	Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)	IEEE Controlled Limit	IEEE Uncontrolled Limit	
1	20	0.080	6	120	0.170	1.00	0.20	
2	40	0.080	7	140	0.200			
3	60	0.080	8	160	0.190			
4	80	0.140	9	180	0.230			
5	100	0.150	10	200	0.240			30.0

Table 48

Internal Vehicle MPE Assessment @ 156.4 MHz										
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)				
						Back	Front	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	
Roof (cnt)	RAD4216A	2.15	Highest Reading	H	1.24	0.078	0.064	28.6	0.039	0.04

Measurement Grid									
Test Position		Meas. Pwr. Density Head (mW/cm^2)	Meas. Pwr. Density Chest (mW/cm^2)	Meas. Pwr. Density Lower Trunk (mW/cm^2)	IEEE Controlled Limit:			1.00	
Back Seat		0.047	0.092	0.096	IEEE Uncontrolled Limit:			0.20	
Front Seat		0.064	0.052	0.076				RF Po (*Max):	30.0

Table 49

External Vehicle MPE Assessment @ 174 MHz								
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)
Roof (cnt)	RAD4217A	2.15	60 (actual 110 cm)	H	1.09	0.162	29.4	0.081
Measurement Grid								
Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)	Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)	IEEE Controlled Limit	IEEE Uncontrolled Limit	
1	20	0.100	6	120	0.210	1.00	0.20	
2	40	0.080	7	140	0.220			
3	60	0.110	8	160	0.240			
4	80	0.100	9	180	0.260			RF Po (*Max)
5	100	0.130	10	200	0.170			30.0

Table 50

Internal Vehicle MPE Assessment @ 174 MHz								
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)
						Back		
Roof (cnt)	RAD4217A	2.15	Highest Reading	H	1.09	0.045	0.036	29.4
Measurement Grid								
Test Position	Meas. Pwr. Density Head (mW/cm^2)	Meas. Pwr. Density Chest (mW/cm^2)	Meas. Pwr. Density Lower Trunk (mW/cm^2)	IEEE Controlled Limit:				1.00
Back Seat	0.052	0.033	0.050	IEEE Uncontrolled Limit:				0.20
Front Seat	0.005	0.021	0.083			RF Po (*Max):		30.0

Table 51

External Vehicle MPE Assessment @ 148.4 MHz								
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)
Roof (cnt)	RAD4218A	5.15	60 (actual 110 cm)	H	1.27	0.128	29.3	0.064
Measurement Grid								
Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)	Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)	IEEE Controlled Limit	IEEE Uncontrolled Limit	
1	20	0.100	6	120	0.130	1.00	0.20	
2	40	0.060	7	140	0.160			
3	60	0.100	8	160	0.160			
4	80	0.120	9	180	0.190			RF Po (*Max)
5	100	0.100	10	200	0.160			30.0

Table 52

Internal Vehicle MPE Assessment @ 148.4 MHz										
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)		
						Back				
Roof (cnt)	RAD4218A	5.15	Highest Reading	H	1.27	0.021	0.004	29.3	0.010	0.01

Measurement Grid								
Test Position		Meas. Pwr. Density Head (mW/cm^2)	Meas. Pwr. Density Chest (mW/cm^2)	Meas. Pwr. Density Lower Trunk (mW/cm^2)	IEEE Controlled Limit:		IEEE Uncontrolled Limit:	
Back Seat		0.021	0.000	0.041	IEEE Controlled Limit:		IEEE Uncontrolled Limit:	
Front Seat		0.000	0.013	0.000			RF Po (*Max):	

Table 53

External Vehicle MPE Assessment @ 159 MHz									
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	
Roof (cnt)	RAD4218A	5.15	60 (actual 110 cm)	H	1.21	0.117	29.5	0.059	0.06

Measurement Grid								
Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)	Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)	IEEE Controlled Limit	IEEE Uncontrolled Limit	RF Po (*Max)
1	20	0.130	6	120	0.120	1.00	0.20	
2	40	0.100	7	140	0.100			
3	60	0.080	8	160	0.160			
4	80	0.110	9	180	0.130			
5	100	0.100	10	200	0.140			30.0

Table 54

Internal Vehicle MPE Assessment @ 159 MHz										
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)		
						Back				
Roof (cnt)	RAD4218A	5.15	Highest Reading	H	1.21	0.083	0.060	29.5	0.042	0.04

Measurement Grid								
Test Position		Meas. Pwr. Density Head (mW/cm^2)	Meas. Pwr. Density Chest (mW/cm^2)	Meas. Pwr. Density Lower Trunk (mW/cm^2)	IEEE Controlled Limit:		IEEE Uncontrolled Limit:	
Back Seat		0.090	0.080	0.080				
Front Seat		0.060	0.070	0.050			RF Po (*Max):	

Table 55

External Vehicle MPE Assessment @ 172 MHz								
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)
Roof (cnt)	RAD4218A	5.15	60 (actual 110 cm)	H	1.11	0.119	29.6	0.060
Measurement Grid								
Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)	Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)	IEEE Controlled Limit	IEEE Uncontrolled Limit	
1	20	0.090	6	120	0.150	1.00	0.20	
2	40	0.090	7	140	0.110			
3	60	0.140	8	160	0.150			
4	80	0.120	9	180	0.100			RF Po (*Max)
5	100	0.100	10	200	0.140			30.0

Table 56

Internal Vehicle MPE Assessment @ 172 MHz								
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)
						Back		
Roof (cnt)	RAD4218A	5.15	Highest Reading	H	1.11	0.072	0.083	29.6
Measurement Grid								
Test Position	Meas. Pwr. Density Head (mW/cm^2)	Meas. Pwr. Density Chest (mW/cm^2)	Meas. Pwr. Density Lower Trunk (mW/cm^2)	IEEE Controlled Limit:				1.00
Back Seat	0.061	0.098	0.057	IEEE Uncontrolled Limit:				0.20
Front Seat	0.050	0.088	0.110			RF Po (*Max):		30.0

----- E - Fields -----

Table 57

External Vehicle MPE Assessment @ 136 MHz								
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)
Trunk (cnt)	HAD4006A	2.15	60 (actual 60 cm)	E	0.51	0.108	29.1	0.054
Measurement Grid								
Test Position	Height (cm)	% of Control Limit	Test Position	Height (cm)	% of Control Limit	IEEE Controlled Limit	IEEE Uncontrolled Limit	
1	20	1.3%	6	120	20.7%	1.00	0.20	
2	40	1.9%	7	140	20.4%			
3	60	4.0%	8	160	16.0%			
4	80	8.9%	9	180	10.7%			RF Po (*Max)
5	100	15.9%	10	200	8.0%			30.0

Table 58

Internal Vehicle MPE Assessment @ 136 MHz										
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)		Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)
						Back	Front			
Trunk (cnt)	HAD4006A	2.15	Highest Reading	E	0.51	0.165	0.050	29.1	0.083	0.09
Measurement Grid										
Test Position		% of Control Limit Head		% of Control Limit Chest		% of Control Limit Lower Trunk		IEEE Controlled Limit:		1.00
Back Seat		23.0%		11.7%		14.9%		IEEE Uncontrolled Limit:		0.20
Front Seat		6.7%		5.7%		2.5%		RF Po (*Max):		30.0

*Table 59

External Vehicle MPE Assessment @ 148.4 MHz													
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)				
Trunk (cnt)	HAD4007A	2.15	60 (actual 60 cm)	E	0.47	0.134	29.3	0.063	0.06				
Measurement Grid													
Test Position	Height (cm)	% of Control Limit		Test Position	Height (cm)	% of Control Limit		IEEE Controlled Limit	IEEE Uncontrolled Limit				
1	20	2.4%		6	120	26.3%		1.00	0.20				
2	40	4.3%		7	140	22.9%		RF Po (*Max)		30.0			
3	60	8.6%		8	160	16.0%							
4	80	14.1%		9	180	10.3%							
5	100	21.4%		10	200	7.8%							

*Table 60

Internal Vehicle MPE Assessment @ 148.4 MHz										
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)		Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)
						Back	Front			
Trunk (cnt)	HAD4007A	2.15	Highest Reading	E	0.47	0.159	0.021	29.3	0.075	0.08
Measurement Grid										
Test Position	% of Control Limit Head		% of Control Limit Chest		% of Control Limit Lower Trunk		IEEE Controlled Limit:		1.00	
Back Seat	29.3%		14.1%		4.4%		IEEE Uncontrolled Limit:		0.20	
Front Seat	1.7%		2.4%		2.2%		RF Po (*Max):		30.0	

*Table 61

External Vehicle MPE Assessment @ 156.4 MHz								
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)
Trunk (cnt)	HAD4008A	2.15	60 (actual 60 cm)	E	0.48	0.117	28.6	0.056
Measurement Grid								
Test Position	Height (cm)	% of Control Limit	Test Position	Height (cm)	% of Control Limit	IEEE Controlled Limit	IEEE Uncontrolled Limit	
1	20	2.5%	6	120	22.6%	1.00	0.20	
2	40	4.9%	7	140	17.5%			
3	60	9.3%	8	160	11.5%			
4	80	14.1%	9	180	7.5%			RF Po (*Max)
5	100	21.5%	10	200	6.0%		30.0	

*Table 62

Internal Vehicle MPE Assessment @ 156.4 MHz								
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)
						Back		
Trunk (cnt)	HAD4008A	2.15	Highest Reading	E	0.48	0.133	0.052	28.6
Measurement Grid								
Test Position	% of Control Limit Head	% of Control Limit Chest	% of Control Limit Lower Trunk	IEEE Controlled Limit:			1.00	
Back Seat	23.7%	11.0%	5.1%	IEEE Uncontrolled Limit:			0.20	
Front Seat	3.5%	5.3%	6.8%			RF Po (*Max):	30.0	

Table 63

External Vehicle MPE Assessment @ 174 MHz								
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)
Trunk (cnt)	HAD4009A	2.15	60 (actual 60 cm)	E	0.52	0.090	29.4	0.045
Measurement Grid								
Test Position	Height (cm)	% of Control Limit	Test Position	Height (cm)	% of Control Limit	IEEE Controlled Limit	IEEE Uncontrolled Limit	
1	20	1.0%	6	120	17.3%	1.00	0.20	
2	40	2.1%	7	140	13.9%			
3	60	5.2%	8	160	10.1%			
4	80	11.2%	9	180	6.7%			RF Po (*Max)
5	100	17.0%	10	200	5.2%		30.0	

Table 64

Internal Vehicle MPE Assessment @ 174 MHz										
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)		Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)
						Back	Front			
Trunk (cnt)	HAD4009A	2.15	Highest Reading	E	0.52	0.184	0.033	29.4	0.092	0.09
Measurement Grid										
Test Position		% of Control Limit Head		% of Control Limit Chest		% of Control Limit Lower Trunk		IEEE Controlled Limit:		
Back Seat		22.8%		16.5%		15.9%		IEEE Uncontrolled Limit:		
Front Seat		2.9%		4.1%		2.8%		RF Po (*Max):		

*Table 65

External Vehicle MPE Assessment @ 148.4 MHz											
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)		
Trunk (cnt)	HAD4014A	5.15	60 (actual 60 cm)	E	0.47	0.021	29.3	0.010	0.01		
Measurement Grid											
Test Position	Height (cm)	% of Control Limit		Test Position	Height (cm)	% of Control Limit		IEEE Controlled Limit	IEEE Uncontrolled Limit		
1	20	0.6%		6	120	2.5%		1.00	0.20		
2	40	0.6%		7	140	3.9%		RF Po (*Max)	30.0		
3	60	0.6%		8	160	3.9%					
4	80	0.8%		9	180	3.6%					
5	100	1.4%		10	200	3.1%					

*Table 66

Internal Vehicle MPE Assessment @ 148.4 MHz										
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)	
Trunk (cnt)	HAD4014A	5.15	Highest Reading	E	0.47	0.010	0.005	29.3	0.005	0.00
Measurement Grid										
Test Position	% of Control Limit Head		% of Control Limit Chest		% of Control Limit Lower Trunk		IEEE Controlled Limit:		1.00	
Back Seat	1.5%		1.0%		0.6%		IEEE Uncontrolled Limit:		0.20	
Front Seat	0.5%		0.5%		0.4%		RF Po (*Max):		30.0	

*Table 67

External Vehicle MPE Assessment @ 159 MHz								
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)
Trunk (cnt)	HAD4014A	5.15	60 (actual 60 cm)	E	0.49	0.134	29.5	0.066
Measurement Grid								
Test Position	Height (cm)	% of Control Limit	Test Position	Height (cm)	% of Control Limit	IEEE Controlled Limit	IEEE Uncontrolled Limit	
1	20	1.3%	6	120	19.6%	1.00	0.20	
2	40	1.0%	7	140	26.2%			
3	60	1.5%	8	160	23.9%			
4	80	4.6%	9	180	23.4%			RF Po (*Max)
5	100	9.2%	10	200	23.4%			30.0

*Table 68

Internal Vehicle MPE Assessment @ 159 MHz								
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)
						Back		
Trunk (cnt)	HAD4014A	5.15	Highest Reading	E	0.49	0.043	0.017	29.5
Measurement Grid								
Test Position	% of Control Limit Head	% of Control Limit Chest	% of Control Limit Lower Trunk	IEEE Controlled Limit:			1.00	
Back Seat	7.3%	4.0%	1.6%	IEEE Uncontrolled Limit:			0.20	
Front Seat	1.8%	1.6%	1.7%			RF Po (*Max):	30.0	

Table 69

External Vehicle MPE Assessment @ 172 MHz								
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)
Trunk (cnt)	HAD4014A	5.15	60 (actual 60 cm)	E	0.51	0.020	29.6	0.010
Measurement Grid								
Test Position	Height (cm)	% of Control Limit	Test Position	Height (cm)	% of Control Limit	IEEE Controlled Limit	IEEE Uncontrolled Limit	
1	20	0.6%	6	120	2.2%	1.00	0.20	
2	40	0.6%	7	140	2.9%			
3	60	1.1%	8	160	2.5%			
4	80	1.4%	9	180	2.8%			RF Po (*Max)
5	100	2.0%	10	200	3.5%			30.0

Table 70

Internal Vehicle MPE Assessment @ 172 MHz										
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)				
						Back	Front	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	
Trunk (cnt)	HAD4014A	5.15	Highest Reading	E	0.51	0.005	0.004	29.6	0.002	0.00
Measurement Grid										
Test Position		% of Control Limit Head		% of Control Limit Chest		% of Control Limit Lower Trunk		IEEE Controlled Limit:		
Back Seat		0.5%		0.4%		0.5%		IEEE Uncontrolled Limit:		
Front Seat		0.4%		0.5%		0.4%		RF Po (*Max):		
30.0										

Table 71

External Vehicle MPE Assessment @ 136 MHz											
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)			
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)			
Trunk (cnt)	RAD4214A	2.15	60 (actual 60 cm)	E	0.51	0.108	29.1	0.054	0.06		
Measurement Grid											
Test Position	Height (cm)	% of Control Limit		Test Position	Height (cm)	% of Control Limit		IEEE Controlled Limit	IEEE Uncontrolled Limit		
1	20	2.9%		6	120	17.6%		1.00	0.20		
2	40	3.8%		7	140	18.7%		RF Po (*Max)	30.0		
3	60	7.6%		8	160	16.2%					
4	80	10.7%		9	180	10.0%					
5	100	13.9%		10	200	6.6%					

Table 72

Internal Vehicle MPE Assessment @ 136 MHz										
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)				
						Back	Front	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	
Trunk (cnt)	RAD4214A	2.15	Highest Reading	E	0.51	0.163	0.074	29.1	0.082	0.08
Measurement Grid										
Test Position		% of Control Limit Head		% of Control Limit Chest		% of Control Limit Lower Trunk		IEEE Controlled Limit:		
Back Seat		17.7%		12.1%		19.2%		IEEE Uncontrolled Limit:		
Front Seat		8.9%		9.5%		3.9%		RF Po (*Max):		
30.0										

*Table 73

External Vehicle MPE Assessment @ 148.4 MHz									
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)
Trunk (cnt)	RAD4215A	2.15	60 (actual 60 cm)	E	0.47	0.119	29.3	0.056	0.06
Measurement Grid									
Test Position	Height (cm)	% of Control Limit		Test Position	Height (cm)	% of Control Limit		IEEE Controlled Limit	IEEE Uncontrolled Limit
1	20	2.8%		6	120	22.3%		1.00	0.20
2	40	4.8%		7	140	20.3%			
3	60	7.7%		8	160	13.4%			
4	80	12.1%		9	180	9.7%			RF Po (*Max)
5	100	18.8%		10	200	6.7%			30.0

*Table 74

Internal Vehicle MPE Assessment @ 148.4 MHz									
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)
						Back			
Trunk (cnt)	RAD4215A	2.15	Highest Reading	E	0.47	0.132	0.014	29.3	0.062
Measurement Grid									
Test Position	% of Control Limit Head		% of Control Limit Chest		% of Control Limit Lower Trunk		IEEE Controlled Limit:		1.00
Back Seat	25.5%		11.2%		3.0%		IEEE Uncontrolled Limit:		0.20
Front Seat	1.2%		1.6%		1.3%			RF Po (*Max):	30.0

*Table 75

External Vehicle MPE Assessment @ 156.4 MHz									
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)
Trunk (cnt)	RAD4216A	2.15	60 (actual 60 cm)	E	0.48	0.124	28.6	0.059	0.06
Measurement Grid									
Test Position	Height (cm)	% of Control Limit		Test Position	Height (cm)	% of Control Limit		IEEE Controlled Limit	IEEE Uncontrolled Limit
1	20	4.0%		6	120	21.4%		1.00	0.20
2	40	6.7%		7	140	18.9%			
3	60	9.6%		8	160	12.9%			
4	80	12.9%		9	180	9.7%			RF Po (*Max)
5	100	20.4%		10	200	7.4%			30.0

*Table 76

Internal Vehicle MPE Assessment @ 156.4 MHz										
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)	
						Back				
Trunk (cnt)	RAD4216A	2.15	Highest Reading	E	0.48	0.103	0.035	28.6	0.049	0.05

Measurement Grid									
Test Position		% of Control Limit Head		% of Control Limit Chest		% of Control Limit Lower Trunk		IEEE Controlled Limit:	
Back Seat		18.2%		8.9%		3.8%		IEEE Uncontrolled Limit:	
Front Seat		2.9%		3.6%		4.1%		RF Po (*Max):	

Table 77

External Vehicle MPE Assessment @ 174 MHz									
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	
Trunk (cnt)	RAD4217A	2.15	60 (actual 60 cm)	E	0.52	0.088	29.4	0.044	0.04

Measurement Grid								
Test Position	Height (cm)	% of Control Limit	Test Position	Height (cm)	% of Control Limit	IEEE Controlled Limit	IEEE Uncontrolled Limit	RF Po (*Max)
1	20	2.3%	6	120	15.6%	1.00	0.20	
2	40	2.5%	7	140	13.3%			
3	60	4.7%	8	160	10.9%			
4	80	8.6%	9	180	7.3%			
5	100	16.1%	10	200	6.4%			30.0

Table 78

Internal Vehicle MPE Assessment @ 174 MHz										
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)		
Trunk (cnt)	RAD4217A	2.15	Highest Reading	E	0.52	0.135	0.035	29.4	0.068	0.07

Measurement Grid								
Test Position		% of Control Limit Head		% of Control Limit Chest		% of Control Limit Lower Trunk		IEEE Controlled Limit:
Back Seat		17.3%		13.4%		9.8%		1.00
Front Seat		2.7%		4.9%		3.0%		0.20

*Table 79

External Vehicle MPE Assessment @ 148.4 MHz									
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)
Trunk (cnt)	RAD4218A	5.15	60 (actual 60 cm)	E	0.47	0.100	29.3	0.047	0.05
Measurement Grid									
Test Position	Height (cm)	% of Control Limit		Test Position	Height (cm)	% of Control Limit		IEEE Controlled Limit	IEEE Uncontrolled Limit
1	20	1.9%		6	120	16.8%		1.00	0.20
2	40	2.2%		7	140	18.0%			
3	60	3.4%		8	160	14.7%			
4	80	6.9%		9	180	13.6%			RF Po (*Max)
5	100	11.9%		10	200	10.4%			30.0

*Table 80

Internal Vehicle MPE Assessment @ 148.4 MHz										
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)		Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)
						Back	Front			
Trunk (cnt)	RAD4218A	5.15	Highest Reading	E	0.47	0.123	0.013	29.3	0.058	0.06
Measurement Grid										
Test Position		% of Control Limit Head		% of Control Limit Chest		% of Control Limit Lower Trunk		IEEE Controlled Limit:		
Back Seat		23.7%		9.5%		3.6%		IEEE Uncontrolled Limit:		
Front Seat		1.4%		1.4%		1.1%		RF Po (*Max):		
								30.0		

*Table 81

External Vehicle MPE Assessment @ 159 MHz									
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)
Trunk (cnt)	RAD4218A	5.15	60 (actual 60 cm)	E	0.49	0.110	29.5	0.054	0.05
Measurement Grid									
Test Position	Height (cm)	% of Control Limit		Test Position	Height (cm)	% of Control Limit		IEEE Controlled Limit	IEEE Uncontrolled Limit
1	20	1.8%		6	120	18.1%		1.00	0.20
2	40	2.2%		7	140	20.6%			
3	60	3.9%		8	160	17.6%			
4	80	7.1%		9	180	14.8%			RF Po (*Max)
5	100	13.7%		10	200	10.4%			30.0

*Table 82

Internal Vehicle MPE Assessment @ 159 MHz										
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)	
						Back				
Trunk (cnt)	RAD4218A	5.15	Highest Reading	E	0.49	0.144	0.029	29.5	0.071	0.07
Measurement Grid										
Test Position		% of Control Limit Head		% of Control Limit Chest		% of Control Limit Lower Trunk		IEEE Controlled Limit:		
Back Seat		24.7%		12.8%		5.8%		IEEE Uncontrolled Limit:		
Front Seat		2.5%		2.5%		3.6%		RF Po (*Max):		

Table 83

External Vehicle MPE Assessment @ 172 MHz											
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)		
Trunk (cnt)	RAD4218A	5.15	60 (actual 60 cm)	E	0.51	0.079	29.6	0.039	0.04		
Measurement Grid											
Test Position	Height (cm)	% of Control Limit		Test Position	Height (cm)	% of Control Limit		IEEE Controlled Limit	IEEE Uncontrolled Limit		
1	20	1.8%		6	120	11.8%		1.00	0.20		
2	40	2.1%		7	140	13.0%		RF Po (*Max)			
3	60	2.3%		8	160	12.6%					
4	80	4.4%		9	180	12.3%					
5	100	8.9%		10	200	9.4%		30.0			

Table 84

Internal Vehicle MPE Assessment @ 172 MHz										
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)	
						Back				
Trunk (cnt)	RAD4218A	5.15	Highest Reading	E	0.51	0.112	0.022	29.6	0.056	0.06
Measurement Grid										
Test Position		% of Control Limit Head		% of Control Limit Chest		% of Control Limit Lower Trunk		IEEE Controlled Limit:		
Back Seat		15.1%		12.2%		6.4%		IEEE Uncontrolled Limit:		
Front Seat		2.0%		2.5%		2.0%		RF Po (*Max):		

----- 45 degree -----

*Table 85

External Vehicle MPE Assessment @ 159 MHz								
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)
Trunk (cnt)	HAD4014A	5.15	60 (actual 99.5 cm)	E	0.49	0.0520	29.5	0.025
Measurement Grid								
Test Position	Height (cm)	% of Control Limit	Test Position	Height (cm)	% of Control Limit	IEEE Controlled Limit	IEEE Uncontrolled Limit	RF Po (*Max)
1	20	2.1%	6	120	4.7%	1.00	0.20	
2	40	2.3%	7	140	6.8%			
3	60	2.0%	8	160	9.7%			
4	80	1.8%	9	180	9.9%			
5	100	2.8%	10	200	9.9%			30.0

----- 90 degree -----

*Table 86

External Vehicle MPE Assessment @ 159 MHz								
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)
Trunk (cnt)	HAD4014A	5.15	60 (actual 104 cm)	E	0.49	0.052	29.5	0.025
Measurement Grid								
Test Position	Height (cm)	% of Control Limit	Test Position	Height (cm)	% of Control Limit	IEEE Controlled Limit	IEEE Uncontrolled Limit	RF Po (*Max)
1	20	1.9%	6	120	5.0%	1.00	0.20	
2	40	1.9%	7	140	6.6%			
3	60	1.8%	8	160	9.5%			
4	80	2.5%	9	180	9.5%			
5	100	3.7%	10	200	9.6%			30.0

----- H - Fields -----

Table 87

External Vehicle MPE Assessment @ 136 MHz								
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)
Trunk (cnt)	HAD4006A	2.15	60 (actual 60 cm)	H	1.12	0.191	29.1	0.096
Measurement Grid								
Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)	Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)	IEEE Controlled Limit	IEEE Uncontrolled Limit	RF Po (*Max)
1	20	0.090	6	120	0.380	1.00	0.20	
2	40	0.090	7	140	0.210			
3	60	0.150	8	160	0.110			
4	80	0.260	9	180	0.140			
5	100	0.410	10	200	0.071			30.0

Table 88

Internal Vehicle MPE Assessment @ 136 MHz										
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)		Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)
						Back	Front			
Trunk (cnt)	HAD4006A	2.15	Highest Reading	H	1.12	0.360	0.107	29.1	0.180	0.19
Measurement Grid										
Test Position		Meas. Pwr. Density Head (mW/cm^2)		Meas. Pwr. Density Chest (mW/cm^2)		Meas. Pwr. Density Lower Trunk (mW/cm^2)		IEEE Controlled Limit:		
Back Seat		0.310		0.340		0.430		IEEE Uncontrolled Limit:		
Front Seat		0.130		0.100		0.090		RF Po (*Max):		
30.0										

Table 89

External Vehicle MPE Assessment @ 148.4 MHz											
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)		
Trunk (cnt)	HAD4007A	2.15	60 (actual 60 cm)	H	1.27	0.370	29.3	0.185	0.19		
Measurement Grid											
Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)		Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)		IEEE Controlled Limit	IEEE Uncontrolled Limit		
1	20	0.220		6	120	0.730		1.00	0.20		
2	40	0.230		7	140	0.410		RF Po (*Max)			
3	60	0.340		8	160	0.180					
4	80	0.590		9	180	0.140					
5	100	0.760		10	200	0.100		30.0			

Table 90

Internal Vehicle MPE Assessment @ 148.4 MHz										
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)	
Trunk (cnt)	HAD4007A	2.15	Highest Reading	H	1.27	0.363	0.094	29.3	0.182	0.19
Measurement Grid										
Test Position	Meas. Pwr. Density Head (mW/cm^2)		Meas. Pwr. Density Chest (mW/cm^2)		Meas. Pwr. Density Lower Trunk (mW/cm^2)		IEEE Controlled Limit:		1.00	
Back Seat	0.630		0.250		0.210		IEEE Uncontrolled Limit:		0.20	
Front Seat	0.120		0.093		0.069		RF Po (*Max):		30.0	

Table 91

External Vehicle MPE Assessment @ 156.4 MHz								
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)
Trunk (cnt)	HAD4008A	2.15	60 (actual 60 cm)	H	1.24	0.285	28.6	0.142
Measurement Grid								
Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)	Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)	IEEE Controlled Limit	IEEE Uncontrolled Limit	
1	20	0.050	6	120	0.600	1.00	0.20	
2	40	0.090	7	140	0.350			
3	60	0.290	8	160	0.110			
4	80	0.650	9	180	0.070			RF Po (*Max)
5	100	0.570	10	200	0.068		30.0	

Table 92

Internal Vehicle MPE Assessment @ 156.4 MHz								
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)
						Back		
Trunk (cnt)	HAD4008A	2.15	Highest Reading	H	1.24	0.138	0.105	28.6
Measurement Grid								
Test Position	Meas. Pwr. Density Head (mW/cm^2)	Meas. Pwr. Density Chest (mW/cm^2)	Meas. Pwr. Density Lower Trunk (mW/cm^2)	IEEE Controlled Limit:			1.00	
Back Seat	0.270	0.100	0.045	IEEE Uncontrolled Limit:			0.20	
Front Seat	0.160	0.100	0.056			RF Po (*Max):	30.0	

Table 93

External Vehicle MPE Assessment @ 174 MHz								
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)
Trunk (cnt)	HAD4009A	2.15	60 (actual 60 cm)	H	1.09	0.232	29.4	0.116
Measurement Grid								
Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)	Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)	IEEE Controlled Limit	IEEE Uncontrolled Limit	
1	20	0.078	6	120	0.510	1.00	0.20	
2	40	0.100	7	140	0.390			
3	60	0.220	8	160	0.180			
4	80	0.300	9	180	0.052			RF Po (*Max)
5	100	0.460	10	200	0.026		30.0	

Table 94

Internal Vehicle MPE Assessment @ 174 MHz										
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)	
						Back				
Trunk (cnt)	HAD4009A	2.15	Highest Reading	H	1.09	0.100	0.023	29.4	0.050	0.05

Measurement Grid									
Test Position		Meas. Pwr. Density Head (mW/cm^2)		Meas. Pwr. Density Chest (mW/cm^2)		Meas. Pwr. Density Lower Trunk (mW/cm^2)		IEEE Controlled Limit: 1.00	
Back Seat		0.140		0.093		0.066		IEEE Uncontrolled Limit: 0.20	
Front Seat		0.019		0.030		0.020		RF Po (*Max): 30.0	

Table 95

External Vehicle MPE Assessment @ 148.4 MHz									
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)
Trunk (cnt)	HAD4014A	5.15	60 (actual 60 cm)	H	1.27	0.090	29.3	0.045	0.05

Measurement Grid											
Test Position	Height (cm)	Meas. Pwr. Density Head (mW/cm^2)		Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)		IEEE Controlled Limit	IEEE Uncontrolled Limit		
1	20	0.100		6	120	0.055		1.00	0.20		
2	40	0.170		7	140	0.060		RF Po (*Max)	30.0		
3	60	0.140		8	160	0.069					
4	80	0.160		9	180	0.071					
5	100	0.010		10	200	0.060					

Table 96

Internal Vehicle MPE Assessment @ 148.4 MHz										
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)	
Trunk (cnt)	HAD4014A	5.15	Highest Reading	H	1.27	0.077	0.038	29.3	0.038	0.04

Measurement Grid									
Test Position		Meas. Pwr. Density Head (mW/cm^2)		Meas. Pwr. Density Chest (mW/cm^2)		Meas. Pwr. Density Lower Trunk (mW/cm^2)		IEEE Controlled Limit: 1.00	
Back Seat		0.056		0.076		0.098		IEEE Uncontrolled Limit: 0.20	
Front Seat		0.026		0.027		0.062		RF Po (*Max): 30.0	

Table 97

External Vehicle MPE Assessment @ 159 MHz								
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)
Trunk (cnt)	HAD4014A	5.15	60 (actual 60 cm)	H	1.21	0.390	29.5	0.195
Measurement Grid								
Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)	Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)	IEEE Controlled Limit	IEEE Uncontrolled Limit	
1	20	0.095	6	120	0.130	1.00	0.20	
2	40	0.110	7	140	0.510			
3	60	0.110	8	160	1.000			
4	80	0.140	9	180	1.100			RF Po (*Max)
5	100	0.086	10	200	0.620		30.0	

Table 98

Internal Vehicle MPE Assessment @ 159 MHz								
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)
						Back		
Trunk (cnt)	HAD4014A	5.15	Highest Reading	H	1.21	0.107	0.092	29.5
Measurement Grid								
Test Position	Meas. Pwr. Density Head (mW/cm^2)	Meas. Pwr. Density Chest (mW/cm^2)	Meas. Pwr. Density Lower Trunk (mW/cm^2)	IEEE Controlled Limit:				1.00
Back Seat	0.120	0.100	0.100	IEEE Uncontrolled Limit:				0.20
Front Seat	0.099	0.081	0.095			RF Po (*Max):		30.0

Table 99

External Vehicle MPE Assessment @ 172 MHz								
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)
Trunk (cnt)	HAD4014A	5.15	60 (actual 60 cm)	H	1.11	0.144	29.6	0.072
Measurement Grid								
Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)	Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)	IEEE Controlled Limit	IEEE Uncontrolled Limit	
1	20	0.130	6	120	0.140	1.00	0.20	
2	40	0.190	7	140	0.170			
3	60	0.170	8	160	0.140			
4	80	0.130	9	180	0.150			RF Po (*Max)
5	100	0.110	10	200	0.110		30.0	

Table 100

Internal Vehicle MPE Assessment @ 172 MHz										
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)		
						Back/Front seats (mW/cm^2)				
Trunk (cnt)	HAD4014A	5.15	Highest Reading	H	1.11	0.062	0.049	29.6	0.031	0.03
Measurement Grid										
Test Position		Meas. Pwr. Density Head (mW/cm^2)	Meas. Pwr. Density Chest (mW/cm^2)	Meas. Pwr. Density Lower Trunk (mW/cm^2)	IEEE Controlled Limit:			1.00		
Back Seat		0.065	0.063	0.059	IEEE Uncontrolled Limit:			0.20		
Front Seat		0.041	0.046	0.060			RF Po (*Max):	30.0		

Table 101

External Vehicle MPE Assessment @ 136 MHz									
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	
Trunk (cnt)	RAD4214A	2.15	60 (actual 60 cm)	H	1.12	0.179	29.1	0.090	0.09
Measurement Grid									
Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)	Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)	IEEE Controlled Limit		IEEE Uncontrolled Limit	
1	20	0.064	6	120	0.250	1.00		0.20	
2	40	0.170	7	140	0.140			RF Po (*Max)	
3	60	0.190	8	160	0.100				
4	80	0.320	9	180	0.100				
5	100	0.350	10	200	0.110	30.0			

Table 102

Internal Vehicle MPE Assessment @ 136 MHz										
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)		
						Back/Front seats (mW/cm^2)				
Trunk (cnt)	RAD4214A	2.15	Highest Reading	H	1.12	0.377	0.046	29.1	0.188	0.19
Measurement Grid										
Test Position		Meas. Pwr. Density Head (mW/cm^2)	Meas. Pwr. Density Chest (mW/cm^2)	Meas. Pwr. Density Lower Trunk (mW/cm^2)	IEEE Controlled Limit:			1.00		
Back Seat		0.320	0.350	0.460	IEEE Uncontrolled Limit:			0.20		
Front Seat		0.030	0.080	0.027			RF Po (*Max):	30.0		

Table 103

External Vehicle MPE Assessment @ 148.4 MHz								
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)
Trunk (cnt)	RAD4215A	2.15	60 (actual 60 cm)	H	1.27	0.242	29.3	0.121
Measurement Grid								
Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)	Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)	IEEE Controlled Limit	IEEE Uncontrolled Limit	
1	20	0.069	6	120	0.510	1.00	0.20	
2	40	0.130	7	140	0.300			
3	60	0.260	8	160	0.110			
4	80	0.440	9	180	0.081			RF Po (*Max)
5	100	0.500	10	200	0.018		30.0	

Table 104

Internal Vehicle MPE Assessment @ 148.4 MHz								
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)
						Back		
Trunk (cnt)	RAD4215A	2.15	Highest Reading	H	1.27	0.257	0.002	29.3
Measurement Grid								
Test Position	Meas. Pwr. Density Head (mW/cm^2)	Meas. Pwr. Density Chest (mW/cm^2)	Meas. Pwr. Density Lower Trunk (mW/cm^2)	IEEE Controlled Limit:				1.00
Back Seat	0.480	0.130	0.160	IEEE Uncontrolled Limit:				0.20
Front Seat	0.006	0.000	0.000				RF Po (*Max):	30.0

Table 105

External Vehicle MPE Assessment @ 156.4 MHz								
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)
Trunk (cnt)	RAD4216A	2.15	60 (actual 60 cm)	H	1.24	0.234	28.6	0.117
Measurement Grid								
Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)	Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)	IEEE Controlled Limit	IEEE Uncontrolled Limit	
1	20	0.074	6	120	0.510	1.00	0.20	
2	40	0.100	7	140	0.190			
3	60	0.310	8	160	0.067			
4	80	0.500	9	180	0.060			RF Po (*Max)
5	100	0.510	10	200	0.023		30.0	

Table 106

Internal Vehicle MPE Assessment @ 156.4 MHz								
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)
						Back		
Trunk (cnt)	RAD4216A	2.15	Highest Reading	H	1.24	0.148	0.041	28.6
Measurement Grid								
Test Position		Meas. Pwr. Density Head (mW/cm^2)	Meas. Pwr. Density Chest (mW/cm^2)	Meas. Pwr. Density Lower Trunk (mW/cm^2)	IEEE Controlled Limit:			1.00
Back Seat		0.250	0.130	0.064	IEEE Uncontrolled Limit:			0.20
Front Seat		0.081	0.039	0.002			RF Po (*Max):	30.0

Table 107

External Vehicle MPE Assessment @ 174 MHz								
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)
Trunk (cnt)	RAD4217A	2.15	60 (actual 60 cm)	H	1.09	0.197	29.4	0.099
Measurement Grid								
Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)	Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)	IEEE Controlled Limit		IEEE Uncontrolled Limit
1	20	0.058	6	120	0.450	1.00		0.20
2	40	0.100	7	140	0.300			RF Po (*Max)
3	60	0.160	8	160	0.160			
4	80	0.250	9	180	0.120			
5	100	0.330	10	200	0.046	30.0		

Table 108

Internal Vehicle MPE Assessment @ 174 MHz								
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)
						Back		
Trunk (cnt)	RAD4217A	2.15	Highest Reading	H	1.09	0.054	0.000	29.4
Measurement Grid								
Test Position		Meas. Pwr. Density Head (mW/cm^2)	Meas. Pwr. Density Chest (mW/cm^2)	Meas. Pwr. Density Lower Trunk (mW/cm^2)	IEEE Controlled Limit:			1.00
Back Seat		0.056	0.035	0.071	IEEE Uncontrolled Limit:			0.20
Front Seat		0.000	0.000	0.000	RF Po (*Max):		30.0	

Table 109

External Vehicle MPE Assessment @ 148.4 MHz									
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)
Trunk (cnt)	RAD4218A	5.15	60 (actual 60 cm)	H	1.27	0.187	29.3	0.094	0.10
Measurement Grid									
Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)	Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)	IEEE Controlled Limit	IEEE Uncontrolled Limit		
1	20	0.150	6	120	0.280	1.00	0.20		
2	40	0.110	7	140	0.340				
3	60	0.160	8	160	0.170				
4	80	0.180	9	180	0.120			RF Po (*Max)	
5	100	0.240	10	200	0.120				30.0

Table 110

Internal Vehicle MPE Assessment @ 148.4 MHz										
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)	
						Back				
Trunk (cnt)	RAD4218A	5.15	Highest Reading	H	1.27	0.175	0.001	29.3	0.088	0.09
Measurement Grid										
Test Position	Meas. Pwr. Density Head (mW/cm^2)	Meas. Pwr. Density Chest (mW/cm^2)	Meas. Pwr. Density Lower Trunk (mW/cm^2)				IEEE Controlled Limit:		1.00	
Back Seat	0.320	0.110	0.096				IEEE Uncontrolled Limit:		0.20	
Front Seat	0.002	0.000	0.000				RF Po (*Max):		30.0	

Table 111

External Vehicle MPE Assessment @ 159 MHz									
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	Pwr. Density Max Calc. (mW/cm^2)
Trunk (cnt)	RAD4218A	5.15	60 (actual 60 cm)	H	1.21	0.262	29.5	0.131	0.13
Measurement Grid									
Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)	Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)	IEEE Controlled Limit	IEEE Uncontrolled Limit		
1	20	0.028	6	120	0.420	1.00	0.20		
2	40	0.023	7	140	0.540				
3	60	0.100	8	160	0.550				
4	80	0.170	9	180	0.330			RF Po (*Max)	
5	100	0.320	10	200	0.140				30.0

Table 112

Internal Vehicle MPE Assessment @ 159 MHz									
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)			
						Back	Front	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)
Trunk (cnt)	RAD4218A	5.15	Highest Reading	H	1.21	0.050	0.000	29.5	0.025
Measurement Grid									
Test Position		Meas. Pwr. Density Head (mW/cm^2)		Meas. Pwr. Density Chest (mW/cm^2)		Meas. Pwr. Density Lower Trunk (mW/cm^2)		IEEE Controlled Limit:	
Back Seat		0.150		0.000		0.000		IEEE Uncontrolled Limit:	
Front Seat		0.000		0.000		0.000		RF Po (*Max):	
30.0									

Table 113

External Vehicle MPE Assessment @ 172 MHz									
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)	
Trunk (cnt)	RAD4218A	5.15	60 (actual 60 cm)	H	1.11	0.198	29.6	0.099	
Measurement Grid									
Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)		Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)		IEEE Controlled Limit	
1	20	0.065		6	120	0.240		1.00	
2	40	0.048		7	140	0.440		0.20	
3	60	0.093		8	160	0.460			
4	80	0.093		9	180	0.310			
5	100	0.130		10	200	0.100		RF Po (*Max): 30.0	

Table 114

Internal Vehicle MPE Assessment @ 172 MHz									
Antenna Location	Antenna	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head, Chest, Lower Trunk Back/Front seats (mW/cm^2)			
						Back	Front	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)
Trunk (cnt)	RAD4218A	5.15	Highest Reading	H	1.11	0.000	0.000	29.6	0.000
Measurement Grid									
Test Position		Meas. Pwr. Density Head (mW/cm^2)		Meas. Pwr. Density Chest (mW/cm^2)		Meas. Pwr. Density Lower Trunk (mW/cm^2)		IEEE Controlled Limit:	
Back Seat		0.000		0.000		0.000		IEEE Uncontrolled Limit:	
Front Seat		0.000		0.000		0.000		RF Po (*Max):	
30.0									

----- 45 degree -----

Table 115

External Vehicle MPE Assessment @ 159 MHz								
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)
Trunk (cnt)	HAD4014A	2.15	60 (actual 99.5 cm)	H	1.21	0.147	29.5	0.074
Measurement Grid								
Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)	Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)	IEEE Controlled Limit	IEEE Uncontrolled Limit	
1	20	0.037	6	120	0.100	1.00	0.20	
2	40	0.087	7	140	0.210			
3	60	0.062	8	160	0.240			
4	80	0.085	9	180	0.320			RF Po (*Max)
5	100	0.093	10	200	0.240		30.0	

----- 90 degree -----

Table 116

External Vehicle MPE Assessment @ 159 MHz								
Antenna Location	Antenna Model	Gain (dBi)	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Body (mW/cm^2)	Initial Power (W)	Pwr. Density Calc. (mW/cm^2)
Trunk (cnt)	HAD4014A	2.15	60 (actual 104 cm)	H	1.21	0.143	29.5	0.071
Measurement Grid								
Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)	Test Position	Height (cm)	Meas. Pwr. Density (mW/cm^2)	IEEE Controlled Limit	IEEE Uncontrolled Limit	
1	20	0.150	6	120	0.100	1.00	0.20	
2	40	0.100	7	140	0.150			
3	60	0.100	8	160	0.190			
4	80	0.060	9	180	0.280			RF Po (*Max)
5	100	0.076	10	200	0.220		30.0	

APPENDIX E
SAR Simulation Result



COMPUTATIONAL EME COMPLIANCE ASSESSMENT OF THE VHF MOBILE RADIO, MODEL #PMUD2039A

August 8, 2007

Jagadish Nadakuduti, Giorgi Bit-Babik, Ph.D., and Antonio Faraone, Ph.D.

Motorola Corporate EME Research Lab, Plantation, Florida

Introduction

This report summarizes the computational [numerical modeling] analysis performed to document compliance of the VHF, Model Number PMUD2039A, Mobile Radio and vehicle-mounted antennas with the Federal Communications Commission (FCC) guidelines for human exposure to radio frequency (RF) emissions. The radio operates in the 136 - 174 MHz frequency band.

This computational analysis supplements the measurements conducted to evaluate the FCC *maximum permissible exposure* (MPE) limits for this mobile device. The test condition that did not conform with applicable MPE limits was analyzed to determine whether that condition complied with the *specific absorption rate* (SAR) limits for general public exposure (1.6 W/kg averaged over 1 gram of tissue and 0.08 W/kg averaged over the whole body) set forth in FCC guidelines, which are based on the IEEE C95.1-1999 standard [1]. In total 2 independent simulations have been performed. Those two simulations are addressing exposure of bystander to the VHF mobile radios with trunk-mount gain antenna. For all simulations a commercial code based on Finite-Difference-Time-Domain (FDTD) methodology was employed to carry out the computational analysis. It is well established and recognized within the scientific community that SAR is the primary dosimetric quantity used to evaluate the human body's absorption of RF energy and that MPEs are in fact derived from SAR.

Accordingly, the SAR computations provide a scientifically valid and more relevant estimate of human exposure to RF energy.

Method

The simulation code employed is XFDTD™ v6.3, by Remcom Inc., State College, PA. This computational suite features a heterogeneous full body standing model (High Fidelity Body Mesh), derived from the so-called Visible Human [2], discretized in 5 mm voxels. The dielectric properties of 23 body tissues are automatically assigned by XFDTD™ at any specific frequency. The “seated” man model was obtained from the standing model by modifying the articulation angles at the hips and the knees. Details of the computational method and model are provided in the Appendix to this report, following the structure outlined in Appendix B.III of the Supplement C to the FCC OET Bulletin 65.

The car model has been imported into XFDTD™ from the CAD file of a sedan car having dimensions 4.98 m (L) x 1.85 m (W) x 1.18 m (H), and discretized in 5mm voxels. For the car model the wheels and part of the hood were omitted in order to fit within the computational memory available. These omissions would not be expected to affect the exposure calculations in any event.

For bystander exposure, the antenna position is 26 cm from the end of the trunk, so as to replicate the experimental conditions used in MPE measurements. Figures 1 and 2 show one of the XFDTD™ computational models used for bystander exposure. According to the latest IEEE 1528.2 draft standard (February 19, 2007) for bystander exposure simulations from vehicle mount antennas the lossy dielectric slab with 30 cm thickness, dielectric constant of 8 and conductivity of 0.01 S/m has been introduced in the computational model to properly account for the effect of the ground (pavement) on exposure.




Figure 1: Bystander model exposed to a trunk-mount VHF antenna operating: Bystander is located behind the car replicating the measurement condition.




Figure 2: Side and top view of bystander exposure model. The dielectric slab under the car is introduced to model the ground (pavement) effect on exposure.

The computational code employs a time-harmonic excitation to produce a steady state electromagnetic field in the exposed body. Subsequently, the corresponding SAR distribution is automatically processed in order to determine the whole-body and 1-g average SAR. The maximum output power from mobile radio antenna is 30 W *rms*. Since the ohmic losses in the cable and in the car materials, as well as the mismatch losses at the antenna feed-point, are neglected, and source-based time averaging (50% talk time) is employed, all computational results are normalized to half of it, i.e., 15 W *rms* net output power.

Results of SAR computations for bystanders

The test conditions requiring SAR computations are summarized in Table I, together with other relevant information and the SAR results. With trunk mount antennas, the bystander is placed next to the trunk straight back from the car at a distance of 60 cm from the antenna while maintaining at least 20 cm from the vehicle body, so as to replicate the conditions used in MPE measurements. Two cases of bystander - facing towards or away from the car - were simulated individually.

Table I: Results of the SAR computations for bystander exposure (50% talk-time) at the corner of the trunk at a separation distance of 60 cm from the trunk-mount antenna while maintaining at least 20 cm from the vehicle body.

Antenna Kit #	Antenna length		Freq [MHz]	Bystander exposure	SAR [W/kg]	
	Physical	XFDTD			1-g	WB
HAD4014A	116.8 cm	117 cm	159	Front	0.119	0.00467
HAD4014A	116.8cm	117 cm	159	Back	0.159	0.00483

The SAR distribution in the bystander model in the exposure condition that gave highest 1-g SAR is reported in Figure 3 (159 MHz, bystander facing away from the car, HAD4014A antenna). The same condition produced highest whole body average SAR.






Figure 3. SAR distribution at 159 MHz in the bystander located at the back of the trunk, produced by the trunk-mount HAD4014A antenna. The contour plot for SAR distribution in the figure is relative to the plane where the peak 1-g average SAR for this exposure condition occurs.

The two pictures below show the E and H field distributions in the plane of the antenna corresponding to the condition represented in Figure 3.



a)



b)

Figure 8. (a) E-field distribution in the plane of the antenna corresponding to exposure condition of Figure 3, and (b) H-field distribution corresponding to exposure condition of Figure 3.

The overall maximum peak 1-g SAR in all simulated conditions is 0.159 W/kg, less than the 1.6 W/kg limit, while the maximum whole-body average SAR is 0.00483 W/kg, less than the 0.08 W/kg limit.

Conclusions

Under the test conditions described for evaluating passenger and bystander exposure to the RF electromagnetic fields emitted by vehicle-mounted antennas used in conjunction with this mobile radio product, the present analysis shows that the computed SAR values are compliant with the FCC exposure limits for the general public.

References

- [1] IEEE Standard C95.1-1999. *IEEE Standard for Safety Levels with Respect to Human Exposure to RF Electromagnetic Fields, 3 kHz to 300 GHz.*
- [2] http://www.nlm.nih.gov/research/visible/visible_human.html

APPENDIX: SPECIFIC INFORMATION FOR SAR COMPUTATIONS

This appendix follows the structure outlined in Appendix B.III of the Supplement C to the FCC OET Bulletin 65. Most of the information regarding the code employed to perform the numerical computations has been adapted from the XFDTD™ v5.3 and v6.3 User Manuals. Remcom Inc., owner of XFDTD™, is kindly acknowledged for the help provided.

1) Computational resources


- a) A distributed Linux based multi-CPU computer cluster equipped with AMD 64-bit Opteron processors was employed for all simulations.
- b) The memory requirement was close to 3 GB in all cases. Using the above-mentioned system with four processors operating concurrently, the typical simulation would run for 2 hours.

2) FDTD algorithm implementation and validation

- a) We employed a commercial code (XFDTD™ v6.3, by Remcom Inc.) that implements the Yee's FDTD formulation [1]. The solution domain was discretized according to a rectangular grid with a uniform 5 mm step in all directions. Sub-gridding was not used. Liao's absorbing boundary conditions [2] are set at the domain boundary to simulate free space radiation processes. The excitation is a lumped voltage generator with 50-ohm source impedance. The code allows selecting *wire objects* without specifying their radius. We used a wire to represent the antenna. The car body is modeled by solid metal. We did not employ the “thin wire” algorithm in XFDTD™ since the antenna radius was never smaller than one-fifth the voxel dimension. In fact, the XFDTD™ manual specifies that “Thin Wire materials may be used in special situations where a wire with a radius much smaller than the cell size is required... in cases where the wire radius is important to the calculation and is less than approximately 1/5 the cell size, the thin wire material may be used to accurately simulate the correct wire dimensions.” The voxel size in all our simulations was 5 mm, and the antenna radius is always at least 1 mm (1 mm for the short quarter-wave antennas and 1.5 mm for the long gain antennas), so there was no need to specify a “thin wire” material. Because the field impinges on the bystander or passenger model at a distance of several tens of voxels from the antenna, the details of antenna wire modeling are not expected to have significant impact on the exposure level.
- b) XFDTD™ is one of the most widely employed commercial codes for electromagnetic simulations. It has gone through extensive validation and has proven its accuracy over time in many different applications. One example is provided in [3].


We carried out a validation of the code algorithm by running the canonical test case involving a half-wave wire dipole. The dipole is 0.475 times the free space wavelength at 160 MHz, i.e., 88.5 cm long. The discretization used in the model was uniform in all directions and equal to 5 mm, so the dipole was 177 cells long. Also in this case, the “thin

“wire” model was not needed. The following picture shows XFDTD™ outputs regarding the antenna feed-point impedance ($72.6 - j 11.6$ ohm), as well as qualitative distributions of the total E and H fields near the dipole. The radiation pattern is shown as well (one lobe in elevation). As expected, the 3 dB beamwidth is about 78 degrees.



We also compared the XFDTD™ result with the results derived from NEC [4], which is a code based on the method of moments. In this case, we used a dipole with radius 1

mm, length 88.5 cm, and the discretization is 5 mm. The corresponding input impedance at 160 MHz is 69.5-j10.5 ohm. Its frequency dependence is reported in the following figure.



This validation ensures that the input impedance calculation is carried out correctly in XFDTD™, thereby enabling accurate estimates of the radiated power. It further ensures that the wire model employed in XFDTD™, which we used to model the antennas, produces physically meaningful current and fields distributions. Both these aspects ensure that the field quantities are correctly computed both in terms of absolute amplitude and relative distribution.

3) Computational parameters

a) The following table reports the main parameters of the FDTD model employed to perform our computational analysis:

PARAMETER	X	Y	Z
Voxel size	5 mm	5 mm	5 mm
Maximum domain dimensions employed for passenger computations with the trunk-mount antennas	387	1015	347
Maximum domain dimensions employed for bystander computations with the trunk-mount antennas	475	1092	491
Time step	Exactly equal to Courant limit (typically 10 μ s at this frequency, with the body model)		
Objects separation from FDTD boundary (voxels)	>10	>10	>10
Number of time steps for passenger at VHF frequencies	At least 6000 in all simulations		
Number of time steps for bystander at VHF frequencies	At least 8000 in all simulations		
Excitation	Sinusoidal (not less than 9-10 periods)		

4) Phantom model implementation and validation

a) The FDTD mesh of a male human body was created using digitized data in the form of transverse color images. The data is from the *visible human project* sponsored by the National Library of Medicine (NLM) and is available via the Internet (http://www.nlm.nih.gov/research/visible/visible_human.html). The male data set consists of MRI, CT and anatomical images. Axial MRI images of the head and neck and longitudinal sections of the rest of the body are available at 4 mm intervals. The MRI images have 256 pixel by 256 pixel resolution. Each pixel has 12 bits of gray tone resolution. The CT data consists of axial CT scans of the entire body taken at 1 mm intervals at a resolution of 512 pixels by 512 pixels where each pixel is made up of 12 bits of gray tone. The axial anatomical images are 2048 pixels by 1216 pixels where each pixel is defined by 24 bits of color. The anatomical cross sections are also at 1 mm intervals and coincide with the CT axial images. There are 1871 cross sections. The XFDTD™ High Fidelity Body Mesh uses 5x5x5 mm cells and has dimensions 136 x 87 x 397. Dr. Michael Smith and Dr. Chris Collins of the Milton S. Hershey Medical Center, Hershey, Pa, created the High Fidelity Body mesh. Details of body model creation are given in the *methods* section in [5]. The body mesh contains 23 tissues materials. Measured values for the tissue parameters for a broad frequency range are included with the mesh data. The correct values are interpolated from the table of measured data and entered into the appropriate mesh variables. The tissue conductivity and permittivity variation *vs.* frequency is included in the XFDTD™ calculation by a multiple-pole approximation to the Cole-Cole approximated tissue parameters reported by Camelia Gabriel, Ph.D., and Sami Gabriel, M. Sc. (<http://www.brooks.af.mil/AFRL/HED/hedr/reports/dielectric/home.html>).

- a) The XFDTD™ High Fidelity Body Mesh model correctly represents the anatomical structure and the dielectric properties of body tissues, so it is appropriate for determining the highest exposure expected for normal device operation.
- b) One example of the accuracy of XFDTD™ for computing SAR has been provided in [6]. The study reported in [6] is relative to a large-scale benchmark of measurement and computational tools carried out within the IEEE Standards Coordinating Committee 34, Sub-Committee 2.

5) Tissue dielectric parameters

- a) The following table reports the dielectric properties used by XFDTD™ for the 23 body tissue materials in the High Fidelity Body Mesh at 450 MHz.

#	Tissue	ϵ_r	σ (S/m)	Density (kg/m ³)
1	skin	41.5	0.57	1125
2	tendon, pancreas, prostate, aorta, liver, other	50.3	0.76	1151
3	fat, yellow marrow	5.02	0.05	943

4	cortical bone	13.4	0.11	1850
5	cancellous bone	21.0	0.23	1080
6	blood	57.2	1.72	1057
7	muscle, heart, spleen, colon, tongue	63.5	0.99	1059
8	gray matter, cerebellum	54.1	0.88	1035.5
9	white matter	39.7	0.54	1027.4
10	CSF	68.9	2.32	1000
11	sclera/cornea	54.4	1.04	1151
12	vitreous humor	68.3	1.56	1000
13	bladder	17.6	0.31	1132
14	nerve	35.5	0.50	1112
15	cartilage	43.4	0.66	1171
16	gall bladder bile	76.5	1.62	928
17	thyroid	59.8	0.82	1035.5
18	stomach/esophagus	74.4	1.13	1126
19	lung	52.8	0.72	563
20	kidney	57.0	1.16	1147
21	testis	65.2	1.13	1158
22	lens	51.9	0.71	1163
23	small intestine	73.7	2.07	1153

Similarly, the table below reports the tissue dielectric properties at 155 MHz (mid-band for this VHF mobile radio product).

#	Tissue	ϵ_r	σ (S/m)	Density (kg/m ³)
1	skin	50.5	0.49	1125
2	tendon, pancreas, prostate, aorta, liver, other	59.3	0.63	1151
3	fat, yellow marrow	5.8	0.04	943
4	cortical bone	15.5	0.08	1850
5	cancellous bone	26.0	0.17	1080
6	blood	64.5	1.65	1057
7	muscle, heart, spleen, colon, tongue	73.6	0.84	1059
8	gray matter, cerebellum	71.5	0.73	1035.5
9	white matter	51.4	0.41	1027.4
10	CSF	73.9	2.29	1000
11	sclera/cornea	61.8	0.94	1151
12	vitreous humor	68.6	1.52	1000
13	bladder	19.1	0.28	1132
14	nerve	44.0	0.41	1112
15	cartilage	53.8	0.53	1171
16	gall bladder bile	86.6	1.49	928
17	thyroid	65.9	0.71	1035.5
18	stomach/esophagus	78.5	1.03	1126
19	lung	52.3	0.59	563

20	kidney	72.9	1.02	1147
21	testis	72.6	0.99	1158
22	lens	57.3	0.61	1163
23	small intestine	89.5	1.85	1153



b) The tissue types and dielectric parameters used in the SAR computation are appropriate for determining the highest exposure expected for normal device operation, because they are derived from measurements performed on real biological tissues (<http://www.brooks.af.mil/AFRL/HED/hedr/reports/dielectric/home.html>).

c) The tabulated list of the dielectric parameters used in phantom models is provided at point 5(a). As regards the device (car plus antenna), we used perfect electric conductors.

6) Transmitter model implementation and validation

a) The essential features that must be modeled correctly for the particular test device model to be valid are:

- Car body. We developed one very similar to the car used for MPE measurements, so as to be able to correlate measured and simulated field values. The model was imported in XFDTD™ from a CAD model that is commercially available at <http://www.3dcadbrowser.com/>
- Antenna. We used a straight wire, even when the gain antenna has a base coil for tuning. All the coil does is compensating for excess capacitance due to the antenna being slightly longer than half a wavelength. We do not need to do that in the model, as we used normalization with respect to the net radiated power, which is determined by the input resistance only. In this way, we neglect mismatch losses and artificially produce an overestimation of the SAR, thereby introducing a conservative bias in the model. In case of low profile vertical monopole antenna (HAE6016A) which has an additional horizontal metal circular disk at the tip, the disk was included in the model and well represented in 5 mm resolution mesh.
- Antenna location. We used the same location, relative to the edge of the car trunk, the backseat, or the roof, used in the MPE measurements. The following pictures show a lateral and a perspective view of the whole model (XFDTD™ does not show wires in this type of view, that is why the antenna is not visible).






The car model is constituted by perfect electric conductor and does not include wheels in order to reduce its complexity. The passenger model is surrounded by air, as the seat, which is made out of poorly conductive fabrics, is not included in the computational model. The pavement has not been included in the model. The passenger and bystander models were validated for similar antenna and frequency conditions by comparing the MPE measurements at two VHF frequencies (146 MHz and 164 MHz) for antennas used for a VHF mobile radio analyzed previously in 2003 (FCC ID#ABZ99FT3046). The corresponding MPE measurements are reported in the compliance report relative to FCC ID#ABZ99FT3046. The comparison results are presented below, according to following definitions for the equivalent power densities (based on E or H-field):

$$S_E = \frac{|\mathbf{E}|^2}{2\eta}, \quad S_H = \frac{\eta}{2} |\mathbf{H}|^2, \quad \eta = 377 \Omega$$

Passenger with 17.5 cm monopole antenna (HAE4002A 421.5 MHz)

The following figure of the test model shows the car model, where the yellow dots individuate the back seat, as it can be observed from the other figure showing the cross section of the passenger. The comparison has been performed by taking the average of the computed steady-state field values at the six dotted locations, corresponding to the head, chest, and legs along the yellow dots line, and comparing them with the average of the MPE measurements performed at the head, chest and legs locations. Such a comparison is carried out at the same rms power level (22 W, including the 50% duty factor) used in the MPE measurements.





The equivalent power density (S) is computed from the E-field and the H-field separately. The following table reports the E-field values computed by XFDTD™ at the six locations, and the corresponding power density.

Location Number	E-field, V/m	Eq. Power Density 1.0 V source	Scaled Power Dens. 22 W output, mW/cm^2
1	5.83E-01	4.51E-04	4.41E-01
2	6.31E-01	5.28E-04	5.16E-01
3	6.50E-01	5.60E-04	5.48E-01
4	5.50E-01	4.01E-04	3.92E-01
5	4.50E-01	2.69E-04	2.63E-01
6	7.80E-01	8.07E-04	7.89E-01
Equivalent average Power Density			4.92E-01

Location Number	B-field, Weber/m ²	Eq. Power Density 1.0 V source	Scaled Power Dens. 22 W output, mW/cm ²
1	2.26E-09	0.00061	5.96E-01
2	9.00E-10	0.00010	9.45E-02
3	1.20E-09	0.00017	1.68E-01
4	2.20E-09	0.00058	5.65E-01
5	1.90E-09	0.00043	4.21E-01
6	9.00E-10	0.00010	9.45E-02
Equivalent average Power Density			3.23E-01

The input impedance is $36.2+j24.8$ ohm, therefore the radiated power (considering the mismatch to the 50 ohm unitary voltage source) is 2.25E-3 W, therefore a factor equal to 9779 is required to scale up to 22 W radiated. The corresponding scaled-up power densities are reported in the tables above, which show that the simulation overestimates the average power density from the MPE measurements (0.29 mW/cm^2), as derived from the measured E-field reported in the following table:


Position	SE (meas), 22 W output mW/cm^2
Head	0.38
Chest	0.33
Lower Trunk	0.16

The simulations tend to overestimate the average power density levels, which is understandable since there are no ohmic losses and perfect impedance matching is enforced in the computational models. Based on these results, we conclude that the simulation will produce slight exposure overestimates (about 12%).

- b) Descriptions and illustrations showing the correspondence between the modeled test device and the actual device, with respect to shape, size, dimensions and near-field radiating characteristics, are found in the main report.
- c) Verification that the test device model is equivalent to the actual device for predicting the SAR distributions descends from the fact that the car and antenna size and location in the numerical model correspond to those used in the measurements.
- d) The peak SAR is in the neck region for the passenger, which is in line with MPE measurements and predictions.

Passenger with 63.5 cm monopole antenna (HAE6010A 425 MHz)

The following figures show the car model with the field distribution in the horizontal planes where the MPE measurements have been performed. The comparison has been performed by taking the average of the computed steady-state field values at the three locations, corresponding to the head, chest, and lower trunk, and comparing them with the average of the MPE measurements performed at the head, chest and lower trunk locations. Such a comparison is carried out at the same rms power level (61.5 W, including the 50% duty factor) used in the MPE measurements.



The equivalent power density (S) is computed from the E-field. The following table reports the E-field values computed by XFDTD™ at the three locations, and the corresponding power density.

Location Number	E-field, V/m	Eq. Power Density 1.0 V source	Scaled Power Dens. 61.5 W output, mW/cm ²
1	2.10E-01	5.85E-05	0.561
2	3.66E-01	1.78E-04	1.70
3	1.72E-01	3.92E-04	0.376
Equivalent average Power Density			0.88


The corresponding scaled-up power densities are reported in the tables above, which show that the simulation overestimates the average power density from the MPE measurements (0.52 mW/cm^2), as derived from the measured E-field reported in the following table:


Position	SE (meas), 60 W output mW/cm ²
Head	0.72
Chest	0.64
Lower Trunk	0.19

The simulations tend to overestimate the average power density levels, which is understandable since there are no ohmic losses and perfect impedance matching is enforced in the computational models. Based on these results, we conclude that the simulation will produce exposure overestimates (about 69%).

Bystander with 29 cm monopole antenna (HAE6013A 425 MHz)

The following figures show the E-field and H-field distributions across a vertical plane passing for the antenna and cutting the car in half. As done in the measurements, the MPE is computed from both E-field and H-field distributions, along the yellow dotted line at 10 points spaced 20 cm apart from each other up to 2 m in height. These lines and the field evaluation points are approximately indicated in the figures. The E-field and H-field distributions in the vertical plane placed at 90 cm from the antenna, behind the case, are shown as well. The points where the fields are sampled to determine the equivalent power density (S) are approximately indicated by the white dots. A picture of the antenna is not reported because it is identical to the HAE6013A.






The following table reports the field values computed by XFDTD™ and the corresponding power density values. The average exposure levels are computed as well.


Height (cm)	E (V/m)	S_E (W/m ²)	H (A/m)	S_H (W/m ²)
0	1.05E-01	1.46E-05	2.90E-05	1.589E-05
20	1.14E-01	1.72E-05	2.90E-05	1.598E-05
40	1.16E-01	1.78E-05	3.14E-05	1.871E-05
60	1.39E-01	2.56E-05	3.75E-05	2.669E-05
80	2.03E-01	5.47E-05	5.03E-05	4.795E-05
100	2.73E-01	9.88E-05	7.23E-05	9.923E-05
120	2.94E-01	1.15E-04	8.17E-05	1.266E-04
140	2.65E-01	9.31E-05	7.32E-05	1.016E-04
160	2.12E-01	5.96E-05	5.73E-05	6.219E-05
180	1.60E-01	3.40E-05	4.32E-05	3.531E-05
Average S_E		5.302E-05	Average S_H	


Since the conducted power during the MPE measurement was 123 W the calculated power density was then scaled up for 61.5 W radiated power (taking into account 50% talk time). This model does not include the mismatch loss, loss in the cable and finite conductivity of the car surface and as represents a conservative model for exposure assessment. The scaled-up power density values for 61.5 W radiated power are 5.67 W/m² (E), and 5.88 W/m² (H), that correspond to 0.57 mW/cm² (E), and 0.59 mW/cm² (H). Measurements yielded average power density of 0.309 mW/cm² (E), which shows that the calculated power density is overestimated. The following graph shows a comparison between the measured power density and the simulated one, based on E or H fields, normalized to 61.5 W radiated power.



Bystander with 63.5 cm monopole antenna (HAE6010A 425 MHz)

The following figures show the E-field and H-field distributions across a vertical plane passing for the antenna and cutting the car in half. As done in the measurements, the MPE is computed from both E-field and H-field distributions, along the yellow dotted line at 10 points spaced 20 cm apart from each other up to 2 m in height. These lines and the field evaluation points are approximately indicated in the figures. The E-field and H-field distributions in the vertical plane placed at 90 cm from the antenna, behind the case, are shown as well. The points where the fields are sampled to determine the equivalent power density (S) are approximately indicated by the white dots. A picture of the antenna is not reported because it is identical to the HAE6010A.






The following table reports the field values computed by XFDTD™ and the corresponding power density values. The average exposure levels are computed as well.

Height (cm)	E (V/m)	S_E (W/m ²)	H (A/m)	S_H (W/m ²)
0	1.32E-01	2.31E-05	4.51E-10	2.43E-05
20	1.49E-01	2.94E-05	4.82E-10	2.77E-05
40	1.58E-01	3.31E-05	5.44E-10	3.53E-05
60	1.71E-01	3.88E-05	5.79E-10	4.00E-05
80	2.10E-01	5.85E-05	6.78E-10	5.48E-05
100	2.12E-01	5.96E-05	7.60E-10	6.89E-05
120	1.67E-01	3.70E-05	4.86E-10	2.82E-05
140	1.83E-01	4.44E-05	5.57E-10	3.70E-05
160	2.50E-01	8.29E-05	8.62E-10	8.86E-05
180	2.68E-01	9.53E-05	9.75E-10	1.13E-04
Average S_E		5.38E-05	Average S_H	



Since the conducted power during the MPE measurement was 123 W the calculated power density was then scaled up for 61.5 W radiated power (taking into account 50% talk time). This model does not include the mismatch loss, loss in the cable and finite conductivity of the car surface and as represents a conservative model for exposure assessment. The scaled-up power density values for 61.5 W radiated power are 5.25 W/m² (E), and 5.06 W/m² (H), that correspond to 0.52 mW/cm² (E), and 0.51 mW/cm² (H). Measurements yielded average power density of 0.204 mW/cm² (E), which shows that the calculated power density is overestimated. The following graph shows a comparison between the measured power density and the simulated one, based on E or H

fields, normalized to 61.5 W radiated power.




Passenger with 43 cm monopole antenna (HAD4009A 164 MHz)

The following figures of the test model show the empty car model, where the yellow dotted line represents the back seat, as it can be observed from the right-hand side figure showing the passenger. The comparison has been performed by taking the computed steady-state field values at the locations corresponding to the head, chest, and legs along the yellow line and comparing them with the corresponding measurements. Such a comparison is carried out at the same rms power level (56.5 W) used in the measurements. Steady-state E-field and H-field distributions at a vertical plane transverse to the car and crossing the passenger's head are displayed as well. Finally, a picture of the antenna is shown.



The highest exposure occurs in the middle of the backseat, which is also the case in the measurements. Therefore, the field values were determined on the yellow line centered at the middle of the backseat, approximately at the three locations that are shown by white dots. In actuality, the line is inclined so as to follow the inclination of the passenger's

back, as shown previously.




Because the peak exposure occurs in the center of the back seat, that was where we placed the passenger model to perform the SAR evaluations presented in the report. However, it can be observed that the H-field distribution features peaks near the lateral edges of the rear window. That is the reason why we also carried out one SAR computation by placing the passenger laterally in the back seat, in order to determine whether the SAR would be higher in this case.

As done in the measurements, the equivalent power density (S) is computed from the E-field, the H-field being much lower. The following table reports the E-field values computed by XFDTD™ at the three locations, and the corresponding power density.

Location	E-field magnitude (V/m)	S (W/m ²)
Head	1.10	1.33E-03
Chest	0.70	3.32E-04
Lower Trunk area	0.52	1.62E-04
Average S		6.07E-04


The input impedance is 32.4-j4.8 ohm, therefore the radiated power (considering the mismatch to the 50 ohm unitary voltage source) is 2.38E-3 W. The scaled-up power density for 56.5 W radiated power is 14.4 W/m², corresponding to 1.44 mW/cm². Measurements gave an average of 1.29 mW/cm², which is in agreement considering conservativeness of simulations model. The following table and the graph show a comparison between the simulated power density and the measured one (see also MPE report in FCC ID#ABZ99FT3046, Table 43), normalized to 56.5 W radiated.


Position	SE (meas) mW/cm ²	SE (FDTD) mW/cm ²
Head	2.98	3.15
Chest	0.74	0.79
Lower Trunk	0.14	0.39



Bystander with 48 cm monopole antenna (HAD4007A 146 MHz)

The following figures show the E-field and H-field distributions across a vertical plane passing for the antenna and cutting the car in half. As done in the measurements, the MPE is computed from both E-field and H-field distributions, along the yellow dotted line at 10 points spaced 20 cm apart from each other up to 2 m in height. These lines and the field evaluation points are approximately indicated in the figures. The E-field and H-field distributions in the vertical plane placed at 60 cm from the antenna, behind the case, are shown as well. The points where the fields are sampled to determine the equivalent power density (S) are approximately indicated by the white dots. A picture of the antenna is not reported because it is identical to the HAD4009A except for the length.






The following table reports the field values computed by XFDTD™ and the corresponding power density values. The average exposure levels are computed as well.

Height (cm)	E (V/m)	S_E (W/m ²)	H (A/m)	S_H (W/m ²)	
20	2.12E-01	5.96E-05	5.21E-04	5.12E-05	
40	3.86E-01	1.98E-04	8.59E-04	1.39E-04	
60	4.48E-01	2.66E-04	1.36E-03	3.49E-04	
80	5.36E-01	3.81E-04	1.77E-03	5.88E-04	
100	6.17E-01	5.05E-04	1.88E-03	6.65E-04	
120	6.32E-01	5.30E-04	1.61E-03	4.87E-04	
140	5.65E-01	4.23E-04	1.15E-03	2.48E-04	
160	4.47E-01	2.65E-04	7.21E-04	9.80E-05	
180	3.30E-01	1.44E-04	4.07E-04	3.13E-05	
200	2.35E-01	7.32E-05	1.93E-04	6.99E-06	
Average S_E		2.85E-04	Average S_H		2.66E-04

The input impedance is $27.9-j14.3$ ohm, therefore the radiated power (considering the mismatch to the 50 ohm unitary voltage source) is $2.22E-3$ W. The scaled-up power density values for 53.2 W radiated power are 6.81 W/m² (E), and 6.38 W/m² (H), that correspond to 0.68 mW/cm² (E), and 0.64 mW/cm² (H). Measurements yielded average power density of 0.664 mW/cm² (E), and 0.471 mW/cm² (H), i.e., which are in good agreement with the simulations. The following table and graph show a comparison between the simulated power density and the measured one, based on E (see MPE report in FCC ID#ABZ99FT3046, Table 1) or H fields (see MPE report in FCC ID#ABZ99FT3046, Table 13), normalized to 53.2 W radiated.

Height (cm)	SE (meas) mW/cm ²	SE (FDTD) mW/cm ²	SH (meas) mW/cm ²	SH (FDTD) mW/cm ²	Avg SE meas mW/cm ²	Avg SE FDTD mW/cm ²	Avg SH meas mW/cm ²	Avg SH FDTD mW/cm ²
20	0.19	0.14	0.2	0.12	0.664	0.681	0.471	0.638
40	0.37	0.47	0.23	0.33				
60	0.55	0.64	0.3	0.84				
80	0.68	0.91	0.56	1.41				
100	1.02	1.21	1.07	1.59				
120	1.15	1.27	1.1	1.17				
140	1.04	1.01	0.56	0.59				
160	0.79	0.63	0.24	0.23				
180	0.5	0.35	0.23	0.07				
200	0.35	0.18	0.22	0.02				




7) Test device positioning

- A description of the device test positions used in the SAR computations is provided in the SAR report.
- Illustrations showing the separation distances between the test device and the phantom for the tested configurations are provided in the SAR report.

8) Steady state termination procedures

a) The criteria used to determine that sinusoidal steady-state conditions have been reached throughout the computational domain for terminating the computations are based on the monitoring of field points to make sure they converge. For at least one passenger and one bystander exposure condition, we placed one “field sensor” near the antenna, others between the body and the domain boundary at different locations, and one inside the head of the model. In all simulations, isotropic E-field sensors were placed at opposite corners of the computational domain. We used isotropic E and H field “sensors”, meaning that all three components of the fields are monitored at these points. The following figures show an example of the time waveforms at the field point sensors in the in two opposite points in the computational domain. We selected points near the lowest and highest grid index points. They are shown together in the figure. The highest field levels are observed for the higher index point, as it is closer to the antenna. In all cases, the field reaches the steady-state after a few cycles.



b) 6000 time steps were used, with a time step approximately equal to 10 ps (meeting the Courant criterion), which corresponds to 10 wave periods at 146 MHz. 4000 time steps were used, with a time step approximately equal to 10 ps (meeting the Courant criterion), which corresponds to 18 wave periods at 450 MHz.

c) The XFDTD™ algorithm determines the field phasors by using the so-called “two-equations two-unknowns” method. Details of the algorithm are explained in [7].

9) Computing peak SAR from field components

a) The twelve E-field phasors at the edges of each Yee voxel are combined to yield the SAR associated to that voxel. In particular, the average is performed on the SAR values computed at the 12 edges of each voxel. Notice that in XFDTD™ the dielectric tissue properties are assigned to the voxel edges, thereby allowing said averaging procedure.

b) The IEEE Standards Coordinating Committee 34, Sub-Committee 2 draft standard P1529 (June 2000) discusses several algorithms for volumetric SAR averaging. It states that “It is observed that while the 12 components algorithm is the most appropriate from the mathematical point of view, the differences in 1g SAR calculated with either the 12 or 6 component methods are negligible for practical mesh resolutions (below 5mm). On the

other hand, it is shown that the 3 components approach may lead to significant errors.” XFDTD™ employs the 12-component method, which is the one recommended in the draft standard, thus providing the best achievable accuracy.

10) One-gram averaged SAR procedures

- a) XFDTD™ computes the Specific Absorption Rate (SAR) in each complete cell containing lossy dielectric material and with a non-zero material density. To be considered a complete cell, the twelve cell edges must belong to lossy dielectric materials. The averaging calculation uses an interpolation scheme for finding the averages. Cubical spaces centered on a cell are formed and the mass and average SAR of the sample cubes are found. The size of the sample cubes increases until the total mass of the enclosed exceeds either 1 or 10 grams. The mass and average SAR value of each cube is saved and used to interpolate the average SAR values at either 1 or 10 grams. The interpolation is performed using two methods (polynomial fit and rational function fit) and the one with the lowest error is chosen. The sample cube must meet some conditions to be considered valid. The cube may contain some non-tissue cells, but some checks are performed on the distribution of the non-tissue cells. A valid cube will not contain an entire side or corner of non-tissue cells.
- b) The sample cube increases in odd-numbered steps (1x1x1, 3x3x3, 5x5x5, etc) to remain centered on the desired cell. Since the visible human model employed herein has 5 mm resolution, the one-gram SAR is computed by averaging first over 1x1x1 voxels, corresponding to 0.125 cm³ (not enough yet), and then over a 3x3x3 voxel cube, corresponding to about 3.4 cm³, which is enough to include 1-g, and finally over a 5x5x5 voxel cube, corresponding to about 15.6 cm³, which includes 10-g. The 1-g average SAR is computed by interpolating these three data points. This procedure is repeated in the surroundings of each voxel that is constituted by lossy materials, so as to determine the 1-g and/or 10-g SAR distributions.
- c) As mentioned at points 10(a) and 10(b), the 1- gram average SAR is determined by interpolating the average SAR for the 1x1x1 , 3x3x3, and the 5x5x5 data points, corresponding to 0.125 cm³, 3.4 cm³, and 15.6 cm³, respectively. Because the interpolation is carried out across three data points, the error introduced should be negligible because the interpolating curve crosses exactly the data points.

11) Total computational uncertainty – We derived an estimate for the uncertainty of FDTD methods in evaluating SAR by referring to [6]. In Fig. 7 in [6] it is shown that the deviation between SAR estimates using the XFDTD™ code and those measured with a compliance system are typically within 10% when the probe is away from the phantom surface so that boundary effects are negligible. In that example, the simulated SAR always exceeds the measured SAR.

As discussed in 6(a), a conservative bias has been introduced in the model so as to reduce concerns regarding the computational uncertainty related to the car modeling, antenna modeling, and phantom modeling. The results of the comparison between measurements

and simulations presented in 6(a) suggest that the present model produces an overestimate of the exposure between 4% and 36%. Such a conservative bias should eliminate the need for including uncertainty considerations in the SAR assessment.

12) Test results for determining SAR compliance

a) Illustrations showing the SAR distribution of dominant peak locations produced by the test transmitter, with respect to the phantom and test device, are provided in the SAR report.

b) The input impedance and the total power radiated under the impedance match conditions that occur at the test frequency are provided by XFDTD™. XFDTD™ computes the input impedance by following the method outlined in [8], which consists in performing the integration of the steady-state magnetic field around the feed point edge to compute the steady-state feed point current (I), which is then used to divide the feed-gap steady-state voltage (V). The net *rms* radiated power is computed as

$$P_{XFDTD} = \frac{1}{2} \operatorname{Re} \{ VI^* \}$$

Both the input impedance and the net *rms* radiated power are provided by XFDTD™ at the end of each individual simulation.

We normalize the SAR to such a power, thereby obtaining SAR per radiated Watt (*normalized SAR*) values for the whole body and the 1-g SAR. Finally, we multiply such normalized SAR values times the max power rating of the device under test. In this way, we obtain the exposure metrics for 100% talk-time, i.e., without applying source-based time averaging.

c) For mobile radios, 50% source-based time averaging is applied by multiplying the SAR values determined at point 12(b) times a 0.5 factor.

REFERENCES

- [1] K. S. Yee, "Numerical Solution of Initial Boundary Value Problems Involving Maxwell's Equations in Isotropic Media," *IEEE Transactions on Antennas and Propagation*, vol. 14, no. 3, 302-307, March 1966.
- [2] Z. P. Liao, H. L. Wong, G. P. Yang, and Y. F. Yuan, "A transmitting boundary for transient wave analysis," *Scientia Sinica*, vol. 28, no. 10, pp 1063-1076, Oct. 1984.
- [3] Validation exercise: Mie sphere. Remcom Inc. (enclosed PDF)



Remcom.pdf

[4] NEC-Win PRO™ v 1.1, Nittany Scientific, Inc., Riverton, UT.

[5] C. M. Collins and M. B. Smith, "Calculations of B1 distribution, SNR, and SAR for a surface coil against an anatomically-accurate human body model," *Magn. Reson. Med.*, 45:692-699, 2001. (enclosed TIF)



Collins & Smith.pdf

[6] Martin Siegbahn and Christer Törnevik, "Measurements and FDTD Computations of the IEEE SCC 34 Spherical Bowl and Dipole Antenna," Report to the IEEE Standards Coordinating Committee 34, Sub-Committee 2, 1998. (enclosed PDF)



Ericsson.pdf

[7] C. M. Furse and O. P. Gandhi, "Calculation of electric fields and currents induced in a millimeter-resolution human model at 60 Hz using the FDTD method with a novel time-to-frequency-domain conversion," *Antennas and Propagation Society International Symposium*, 1996. (enclosed PDF)



Furse & Gandhi.pdf

[8] *The Finite Difference Time Domain Method for Electromagnetics*, Chapter 14.2, by K. S. Kunz and R. J. Luebbers, CRC Press, Boca Raton, Florida, 1993.