

DRAFT: May 10, 2005  
ITPD-04-F125A

Federal Communications Commission  
7435 Oakland Mills Road  
Columbia, MD 21046 USA

Subject: Authority to Act as FCC Agent and Request for Confidentiality / Panasonic Mobile Personal Computer  
Model CF-29 Family With Alps BT, Intel WLAN and Siemens EGPRS  
TCB Certification for FCC ID: ACJ9TGCF-295A

To Whom It May Concern:

On behalf of Panasonic Corporation of North America, we hereby authorize PCTEST Engineering Laboratory, Inc., to act on our behalf in matters relating to FCC equipment authorization, including the signing of documents relating to these matters. Any and all acts carried out by PCTEST on our behalf shall have the same effect as acts of our own.

This project represents Mobile Notebook Computer Model CF-29mk3 Family with CPU type Pentium-M-1.4 GHz to be marketed under FCC ID: ACJ9TGCF-295A. This product will be marketed with three transmitters: (1) Alps Blue Tooth Module and Daughter Board Model UGXZ1 with Part 15C operation within 2402~2480 MHz at 18.2mW; (2) Intel WLAN (a+b+g) Module, Model WM3B2915ABG with Part 15C operation within 2412~2462 and 5745~5825 MHz at 233 and 103 mW; and Part 15E operation within 5180~5240 and 5260~5320 MHz at 54 and 125 mW; and (3) Siemens EGPRS Module, Model MC75 with Part 22H operation within 824.2~848.8MHz at 1.12 watts ERP; and 1850.2~1909.8 MHz at 1.06 watts EIRP. The worst-case RF exposure evaluation for maximum permissive exposure measured at 20cm spacing at 1880 MHz was 0.098 mW/cm<sup>2</sup>, while the maximum limit at this frequency is 1.00 mW/cm<sup>2</sup>.

This PC contains the following antennas with antenna gains: (1) BT Inverted-F type with 1.47 dBi (2) WLAN Main TX/RX Inverted-F type with 1.86dBi and WLAN Aux TX/RX with 2.86dBi; and (3) EGPRS Whip with 2.15dBi. The PC's main User Manual gives all FCC required notices and warning, including general RF Exposure Warning. The provided Supplemental User Manual for WLAN gives additional warning notice about NII operation for indoor use only.

This PC contains two unique pass-thru antenna connectors on bottom enclosure, which connect to optional Car Mounter Model CF-WEB291. The Car Mounter has 2 unique antenna passive pass-thru connectors, which are hard-wired connected to rear panel's 2 external TNC antenna connectors. This Car Mounter is marketed to only non-general consumers, such as police, fire and military, and must be professionally installed following provided instructions. The instructions recommend usage of Radiall/Larsen WLAN antenna type MS3E2400TNC, which is provided with connecting cable and advice max antenna dBi gain for external licensed radio service antenna. The basic portable PC's User Manual contains all general RF exposure warning notices, which include notice that PC was approved for portable operation, and unless otherwise advised in separate supplemental instructions for individual wireless transmitter(s), requires minimum 1.5 cm spacing. The mobile PC's User Manual contains all general RF exposure warning notices, which include notice that PC was approved for mobile operation and requires min 20 cm spacing.

In accordance with provisions of Section 0.457(d) of FCC's Rules and Section 552(b)(4) of Freedom of Information Act, we request confidentiality for transceivers exhibits for Operation Description, Parts List & Tune-Up Procedure, Block Diagram(s) and Schematic Diagram(s). The BT and WLAN are not user adjustable and do not have any Tune-Up Procedure. These exhibits contain proprietary, confidential and trade secrets material, which would not be routinely made available for public inspection.

Sincerely yours,

Richard Mullen  
Group Manager