

5.8. RF EXPOSURE REQUIREMENTS [§§ 1.1310 & 2.1091] [RSS Gen Sec 5.6 & RSS-102]

5.8.1. Limits

§ 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b).

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
30-300	61.4	0.163	1.0	6
(B) Limits for General Population/Uncontrolled Exposure				
30-300	27.5	0.073	0.2	30

f = frequency in MHz

* = Plane-wave equivalent power density

Note 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient

through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

Note 2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

[RSS Gen Sec 5.6 & RSS-102]

RF Field Strength Limits for Controlled Use Devices (Controlled Environment)

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Reference Period (minutes)
100-6000	$15.60 f^{0.25}$	$0.04138 f^{0.25}$	$0.6455 f^{0.5}$	6
Note: f is frequency in MHz.				

Table 4: RF Field Strength Limits for Devices Used by the General Public (Uncontrolled Environment)

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Reference Period (minutes)
48-300	22.06	0.05852	1.291	6
Note: f is frequency in MHz.				

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: 20ICOM-522_FCC80
May 6, 2020

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

5.8.2. Method of Measurements

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi \cdot r^2} = \frac{EIRP}{4\pi \cdot r^2}$$

Where,
P: power input to the antenna in mW
EIRP: Equivalent (effective) isotropic radiated power.
S: power density mW/cm²
G: numeric gain of antenna relative to isotropic radiator
r: distance to centre of radiation in cm

$$r = \sqrt{\frac{PG}{4\pi \cdot S}} = \sqrt{\frac{EIRP}{4\pi \cdot S}}$$

FCC radio frequency exposure limits may be exceeded at distances closer than r cm from the antenna of this device.

Evaluation of RF Exposure Compliance Requirements

Maximum RF Power conducted, P_{conducted}[W] :	25
Maximum Antenna Gain, G[dBi] :	9
Maximum EIRP, P_{EIRP}[W] :	198.6
User-based time-average for PTT	50%
FCC MPE Limit for Occupational/Controlled Exposure, S_{controlled}[mW/cm²] :	1.0
ISED MPE Limit for Occupational/Controlled Exposure, S_{controlled}[mW/cm²]: 0.6455f^{0.5}	0.75277
Min Calculated RF Safety Distance for Occupational/Controlled Exposure, r_{safety_controlled}[cm]: FCC	45
Min Calculated RF Safety Distance for Occupational/Controlled Exposure, r_{safety_controlled}[m]: ISED	0.52
FCC MPE Limit for General Population/Un-controlled Exposure, S_{UNcontrolled}[mW/cm²] :	0.2
ISED MPE Limit for General Population/Un-controlled Exposure, S_{UNcontrolled}[mW/cm²]: 0.6455f^{0.5}	0.1291
Min Calculated RF Safety Distance for General populaton/Uncontrolled Exposure, r_{safety_uncontrolled}[cm]: FCC	199
Min Calculated RF Safety Distance for General populaton/Uncontrolled Exposure, r_{safety_uncontrolled}[m]: ISED	2.48

User manual specified distance (MPE Radius)=300cm
Calculated power density S for this distance=0.0878 mW/Cm² (0.88 W/m²)

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: 20ICOM-522_FCC80
May 6, 2020

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)