



FCC


CANADA


IC-F52D-UL




LMR for Haz. Loc. CL I Div 1 Grp C D, CL II Div 1 Grp E F G, CL III. CL I Div 2 Grp A B C D. T3C. Tamb=-20°C to +60°C. INTRINSICALLY SAFE when used with Model BP-292UL battery pack.


⚠ Use with UL Listed ICOM batteries and ACC. See Instruction Manual.




FCC ID:AFJ395100
Contains
FCC ID:AFJ381510




SERIAL NO.
0 0 0 0 0 0 0 0
Icom Inc.
MADE IN JAPAN


Model: IC-F52D-UL




LMR for Haz. Loc. CL I Div 1 Grp C D, CL II Div 1 Grp E F G, CL III. CL I Div 2 Grp A B C D. T3C. Tamb=-20°C to +60°C. INTRINSICALLY SAFE when used with Model BP-292UL battery pack.


⚠ Use with UL Listed ICOM batteries and ACC. See Instruction Manual.




IC:202D-395100
HVIN:395100-03
Contains **IC:202D-381510**




SERIAL NO.
0 0 0 0 0 0 0 0
Icom Inc.
MADE IN JAPAN



Restricted to occupational use to satisfy FCC RF exposure limits. See user manual for operating requirements.



Restricted to occupational use to satisfy FCC RF exposure limits. See user manual for operating requirements.


 UL certification has not been obtained, UL Listing mark is not printed.
 The contents may change after obtaining the certification.

See Pictures.pdf for serial plates photographs.

Serial Plate Location

