

MFA M. Flom Associates, Inc. - Global Compliance Center
3356 North San Marcos Place, Suite 107, Chandler, Arizona 85225-7176
www.mflom.com general@mflom.com (480) 926-3100, FAX: 926-3598

September 14th, 2000

FEDERAL COMMUNICATIONS COMMISSION
Via Electronic Filing
Attention: Frank Coperich

Applicant: ICOM INCORPORATED: FCC ID: AFJIC-F30G EA 98380
Reference: Correspondence 15634

Item 1: Should SAR testing be performed for the front-of-the face or body-worn device?

Item 2: Depending on the answer to Item 1, the Manual will be revised.

Item 3. This information is generic, and should not have been included. It will be deleted.

Item 4. To advise us if SAR evaluation is necessary:

a. type of antenna is $\frac{1}{4}$ wave "rubber ducky" and only 1 is required.

b. maximum antenna gain = 0db reference to dipole

c. cannot sustain continuous operation

d. applicant advises 5% Tx. 5% Rx and 90% standby

e. no

f. Minimum separation distance will be stated in the Manual. Statement will be 3.8 cm (1 $\frac{1}{2}$ inches)

g. no

h. Manual will have statement to indicate minimum separation distances for front-of-the face and body-worn positions.

We will await your decision as requested concerning compliance.

Personal regards,


MORTON FLOM, P. Eng.

mf;mgf
cc: Applicant; c/o USA office