



FCC PART 15C TEST REPORT FOR CERTIFICATION
On Behalf of

Sony Corporation

Bluetooth Module

Model Number: BTMS3

FCC ID: AK8BTMS3

Prepared for : Sony Corporation
1-7-1 Konan, Minato-ku, Tokyo, 108-0075 Japan

Prepared By : Audix Technology (Shenzhen) Co., Ltd.
No. 6, Ke Feng Rd., 52 Block,
Shenzhen Science & Industrial Park,
Nantou, Shenzhen, Guangdong, China

Tel: (0755) 26639496

Report Number : ACS-F12264
Date of Test : Nov.17~Dec.05, 2012
Date of Report : Jan.07, 2013

TABLE OF CONTENTS

Description	Page
1. SUMMARY OF STANDARDS AND RESULTS	1-1
1.1. Description of Standards and Results.....	1-1
2. GENERAL INFORMATION	2-1
2.1. Description of Device (EUT)	2-1
2.2. Tested Supporting System Details	2-2
2.3. EUT Configuration and operation conditions for test.....	2-2
2.4. Test Facility.....	2-3
2.5. Measurement Uncertainty (95% confidence levels, k=2)	2-3
3. POWER LINE CONDUCTED EMISSION MEASUREMENT.....	3-1
3.1. Test Equipment	3-1
3.2. Block Diagram of Test Setup.....	3-1
3.3. Power Line Conducted Emission Test Limits.....	3-1
3.4. Configuration of EUT on Test	3-1
3.5. Operating Condition of EUT.....	3-2
3.6. Test Procedure.....	3-2
3.7. Conducted Emission at Mains Terminals Test Results	3-2
4. RADIATED EMISSION MEASUREMENT	4-1
4.1. Test Equipment	4-1
4.2. Block Diagram of Test Setup.....	4-1
4.3. Radiated Emission Limit Standard: FCC 15.209	4-2
4.4. EUT Configuration on Test.....	4-2
4.5. Operating Condition of EUT.....	4-3
4.6. Test Procedure.....	4-3
4.7. Radiated Emission Test Results	4-3
5. CONDUCTED SPURIOUS EMISSIONS	5-1
5.1. Test Equipment	5-1
5.2. Limit.....	5-1
5.3. Test Procedure.....	5-1
5.4. Test result	5-1
6. CARRIER FREQUENCY SEPARATION TEST	6-1
6.1. Test Equipment	6-1
6.2. Limit.....	6-1
6.3. Test Results	6-1
7. 20 DB BANDWIDTH TEST	7-1
7.1. Test Equipment	7-1
7.2. Limit.....	7-1
7.3. Test Results	7-1
8. NUMBER OF HOPPING FREQUENCY TEST	8-1
8.1. Test Equipment	8-1
8.2. Limit.....	8-1
8.3. Test Results	8-1
9. DWELL TIME.....	9-1
9.1. Test Equipment	9-1

9.2.	Limit.....	9-1
9.3.	Test Results	9-1
10.	MAXIMUM PEAK OUTPUT POWER TEST.....	10-1
10.1.	Test Equipment	10-1
10.2.	Limit.....	10-1
10.3.	Test Procedure.....	10-1
10.4.	Test Results	10-2
11.	BAND EDGE COMPLIANCE TEST	11-1
11.1.	Test Equipment	11-1
11.2.	Limit.....	11-1
11.3.	Test Produce	11-1
11.4.	Test Results	11-1
12.	DEVIATION TO TEST SPECIFICATIONS	12-1
13.	PHOTOGRAPH OF TEST.....	13-1
13.1.	Photos of Conducted Disturbance at Mains Terminals Test	13-1
13.2.	Photos of Radiated Emission Test (30-1000MHz).....	13-2
14.	PHOTOS OF THE EUT	14-1



FCC ID:AK8BTMS3

TEST REPORT CERTIFICATION

Applicant : Sony Corporation
Manufacturer : Sony Corporation
EUT Description : Bluetooth Module
FCC ID : AK8BTMS3
(A) MODEL NO. : BTMS3
(B) SERIAL NO. : N/A
(C) POWER SUPPLY : DC 3.3V
(D) TEST VOLTAGE : DC 3.3V

Tested for comply with:
FCC Rules and Regulations Part 15 Subpart C: 2011
Test procedure used:
ANSI C63.10:2009

The device described above is tested by AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. to confirm comply with all the FCC Part 15 Subpart C requirements. The test results are contained in this test report and AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. is assumed full responsibility for the accuracy and completeness of these tests. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC and IC requirements. This report contains data that are not covered by the NVLAP accreditation.

This Report is made under FCC Part 2.1075. No modifications were required during testing to bring this product into compliance.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of AUDIX TECHNOLOGY (SHENZHEN) CO., LTD.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

Date of Test : Nov.17~ Dec.05, 2012 Report of date: Jan.07,2013

Prepared by : Julia Zhu Reviewed by : Sunny Lu/ Assistant Manager

Approved & Authorized Signer : Ken Lu / Manager
Stamp only for EMC Dept. Report
Signature: Ken Lu 1/8 13

1. SUMMARY OF STANDARDS AND RESULTS

1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below.

EMISSION		
Description of Test Item	Standard	Results
Power Line Conducted Emission Test	FCC Part 15: 15.207 ANSI C63.10 :2009	PASS
Radiated Emission Test	FCC Part 15: 15.209 FCC Part 15: 15.247(d) ANSI C63.10 :2009	PASS
Conducted Spurious Emissions	FCC Part 15: 15.247(a)(1) ANSI C63.10 :2009	PASS
Carrier Frequency Separation Test	FCC Part 15: 15.247(a)(1) ANSI C63.10 :2009	PASS
20dB Bandwidth Test	FCC Part 15: 15.215 ANSI C63.10 :2009	PASS
Number Of Hopping Frequency Test	FCC Part 15: 15.247(a)(1)(iii) ANSI C63.10 :2009	PASS
Dwell Time Test	FCC Part 15: 15.247(a)(1)(iii) ANSI C63.10 :2009	PASS
Maximum Peak Output Power Test	FCC Part 15: 15.247(b)(1)\ ANSI C63.10 :2009	PASS
Band Edge Compliance Test	FCC Part 15: 15.247(d) ANSI C63.10 :2009	PASS
N/A is an abbreviation for Not Applicable.		

2. GENERAL INFORMATION


2.1. Description of Device (EUT)

Product Name	: Bluetooth Module
Model Number	: BTMS3
FCC ID	: AK8BTMS3
Radio	: Bluetooth V3.0 +EDR
Operation frequency	: 2402MHz-2480MHz
Antenna	: Integral Antenna, -1.72dBi PK gain
Modulation	: GFSK, $\pi/4$ DQPSK, 8-DPSK Note: $\pi/4$ DQPSK modulation is same type modulation with 8-DPSK, and according exploratory test, 8-DPSK will have worse emissions, so the final test were only performed with GFSK and 8-DPSK modulation.
Power Supply	: DC 3.3V
Applicant	: Sony Corporation 1-7-1 Konan, Minato-ku, Tokyo, 108-0075 Japan
Power Adapter	: Manufacturer: SONY Model No.: AC-E1530 Cable: Shielded, Detachable, 1.8 m
Date of Test	: Nov.17~Dec.04, 2012
Date of Receipt	: Nov.15, 2012
Sample Type	: Prototype production

2.2. Tested Supporting System Details

No.	Description	ACS No.	Manufacturer	Model	Serial Number	Approved type
1	Personal Audio System	----	Sony	SRS-BTX500	----	----

2.3. EUT Configuration and operation conditions for test.



(EUT: Bluetooth Module)

2.4. Test Facility

Site Description

Name of Firm : Audix Technology (Shenzhen) Co., Ltd.
No. 6, Ke Feng Rd., 52 Block, Shenzhen
Science & Industrial Park, Nantou,
Shenzhen, Guangdong, China

3m Anechoic Chamber : Certificated by FCC, USA
Registration Number: 90454
Valid Date: Feb.22, 2015

3m & 10m Anechoic Chamber : Certificated by FCC, USA
Registration Number: 794232
Valid Date: Dec.30, 2012

EMC Lab. : Certificated by Industry Canada
Registration Number: IC 5183A-1
Valid Date: Jun.13, 2014

Certificated by DAkkS, Germany
Registration No: D-PL-12151-01-01
Valid Date: Feb.01, 2014

Accredited by NVLAP, USA
NVLAP Code: 200372-0
Valid Date: Mar.31, 2013

2.5. Measurement Uncertainty (95% confidence levels, k=2)


Test Item	Uncertainty
Uncertainty for Conduction emission test in No. 1 Conduction	3.48dB(9KHz to 150KHz)
	3.06dB (150KHz to 30MHz)
Uncertainty for Radiation Emission test in 3m chamber	3.6 dB(30~200MHz, Polarize: H)
	3.8 dB(30~200MHz, Polarize: V)
	4.2 dB(200M~1GHz, Polarize: H)
	3.8 dB(200M~1GHz, Polarize: V)
Uncertainty for Radiation Emission test in 3m chamber (1GHz-18GHz)	3.1dB (Distance: 3m Polarize: V)
	3.7 dB (Distance: 3m Polarize: H)
Uncertainty for Radiated Spurious Emission test in RF chamber	3.57 dB
Uncertainty for Conduction Spurious emission test	2.00 dB
Uncertainty for Output power test	0.73 dB
Uncertainty for Bandwidth test	83 kHz
Uncertainty for DC power test	0.038 %
Uncertainty for test site temperature and humidity	0.6°C
	3%

3. POWER LINE CONDUCTED EMISSION MEASUREMENT

3.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Test Receiver	Rohde & Schwarz	ESHS10	838693/001	Oct.31, 12	1 Year
2.	L.I.S.N.#1	Rohde & Schwarz	ESH2-Z5	834066/011	Oct.31, 12	1 Year
3.	L.I.S.N.#3	Kyoritsu	KNW-242C	8-1920-1	May.08, 12	1 Year
4.	Terminator	Hubersuhner	50Ω	No. 1	May.08, 12	1 Year
5.	Terminator	Hubersuhner	50Ω	No. 2	May.08, 12	1 Year
6.	RF Cable	Fujikura	3D-2W	No.1	May.08, 12	1 Year
7.	Coaxial Switch	Anritsu	MP59B	M50564	May.08, 12	1 Year
8.	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100341	May.08, 12	1 Year
9.	Horn Antenna	EMCO	3116	00060089	Nov.25,11	1.5 Year

3.2. Block Diagram of Test Setup



3.3. Power Line Conducted Emission Test Limits

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. * Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

3.4. Configuration of EUT on Test

The following equipment are installed on Power Line Conducted Emission Test to meet the commission requirement and operating regulations in a manner which tends to maximize its emission characteristics in a normal application.

3.4.1. Bluetooth Module (EUT)

Model Number : BTMS3
Serial Number : N/A

3.5. Operating Condition of EUT

- 3.5.1. Setup the EUT and simulator as shown as Section 3.2.
- 3.5.2. Turn on the power of all equipment.
- 3.5.3. Let the EUT work in test mode (TX Mode) and measure it.

3.6. Test Procedure


The EUT was placed on a non-metallic table, 80cm above the ground plane. The EUT Power connected to the power mains through a line impedance stabilization network (L.I.S.N. 1#). this provided a 50-ohm coupling impedance for the EUT (Please refer to the block diagram of the test setup and photographs). Both sides of power line were checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.4-2009 on conducted Emission test.

The bandwidth of test receiver (R&S TEST RECEIVER ESHS10) is set at 9kHz.

The frequency range from 150kHz to 30MHz is checked. The test result are reported on Section 3.7.

3.7. Conducted Emission at Mains Terminals Test Results

PASS. (All emissions not reported below are too low against the prescribed limits.)




Trace: (Discrete)

Site no	:1#conduction	Data No	:5
Dis./Ant.	** 2012 KNW-242C-VA		
Limit	:FCC PART 15 C		
Env./Ins.	:23.9°C/61%	Engineer	:Leo-Li
EUT	:Bluetooth Module		
Power supply	:DC 3.3V		
Test Mode	:Tx Mode(BT)		
	M/N:BTMS3		

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.15000	0.08	9.94	23.78	33.80	66.00	32.20	QP
2	0.20970	0.06	9.95	22.31	32.32	63.22	30.90	QP
3	0.50820	0.05	9.95	30.14	40.14	56.00	15.86	QP
4	0.62760	0.06	9.95	22.62	32.63	56.00	23.37	QP
5	1.314	0.06	9.94	16.15	26.15	56.00	29.85	QP
6	2.747	0.09	9.94	13.62	23.65	56.00	32.35	QP

Remarks: 1.Emission Level=LISN Factor+Cable Loss(Include 10dB pulse limit)+Reading.
 2.If the average limit is met when using a quasi-peak detector. the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.



Trace: (Discrete)

Site no :1#conduction Data No :6
 Dis./Ant. :** 2012 KNW-242C-VB
 Limit :FCC PART 15 C
 Env./Ins. :23.9°C/61% Engineer :Leo-Li
 EUT :Bluetooth Module
 Power supply :DC 3.3V
 Test Mode :Tx Mode(BT)
 M/N:BTMS3

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBUV)	Emission Level (dBUV)	Limits (dBUV)	Margin (dB)	Remark
1	0.15000	0.09	9.94	22.19	32.22	66.00	33.78	QP
2	0.20970	0.10	9.95	19.98	30.03	63.22	33.19	QP
3	0.50820	0.10	9.95	29.88	39.93	56.00	16.07	QP
4	1.762	0.24	9.94	19.57	29.75	56.00	26.25	QP
5	2.389	0.26	9.94	17.76	27.96	56.00	28.04	QP
6	3.822	0.27	9.94	15.30	25.51	56.00	30.49	QP

Remarks: 1. Emission Level=LISN Factor+Cable Loss(Include 10dB pulse limit)+Reading.
 2. If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.

4. RADIATED EMISSION MEASUREMENT

4.1. Test Equipment

Frequency rang: 30~1000MHz


Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	3#Chamber	AUDIX	N/A	N/A	Nov.24,12	1 Year
2	EMI Spectrum	Agilent	E4407B	MY41440292	May.08, 12	1 Year
3	Test Receiver	Rohde & Schwarz	ESVS10	834468/011	May.08, 12	1 Year
4	Amplifier	HP	8447D	2648A04738	May.08, 12	1 Year
5	Bilog Antenna	Schaffner	CBL6111C	2598	Dec.26, 10	2.0 Year
6	RF Cable	MIYAZAKI	CFD400-NL	3# Chamber No.1	May.08, 12	1 Year
7	Coaxial Switch	Anritsu	MP59B	M74389	May.08, 12	1 Year

Frequency rang: above 1000MHz


Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Spectrum Analyzer	Agilent	E4407B	MY41440292	May.08, 12	1 Year
2	Horn Antenna	EMCO	3115	9510-4580	June.05, 12	1 Year
3	Amplifier	Agilent	8449B	3008A00863	May.08, 12	1 Year
4	RF Cable	Hubersuhner	SUCOFLEX106	77980/6	May.08, 12	1 Year
5	RF Cable	Hubersuhner	SUCOFLEX106	77977/6	May.08, 12	1 Year

4.2. Block Diagram of Test Setup

For frequency range 30MHz-1000MHz



For frequency range 1GHz-25GHz



4.3. Radiated Emission Limit Standard: FCC 15.209

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		$\mu\text{V}/\text{m}$	$\text{dB}(\mu\text{V})/\text{m}$
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000MHz	3	74.0 $\text{dB}(\mu\text{V})/\text{m}$ (Peak) 54.0 $\text{dB}(\mu\text{V})/\text{m}$ (Average)	

Remark : (1) Emission level $\text{dB}\mu\text{V} = 20 \log$ Emission level $\mu\text{V}/\text{m}$

- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.
- (4) The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

4.4.EUT Configuration on Test

The following equipment are installed on Radiated Emission Test to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

4.4.1. Bluetooth Module (EUT)

Model Number : BTMS3
Serial Number : N/A

4.5. Operating Condition of EUT

- 4.5.1. Setup the EUT and simulator as shown as Section 3.2.
- 4.5.2. Turned on the power of all equipment.
- 4.5.3. Let EUT work in Tx mode.

4.6. Test Procedure

The EUT and its simulators are placed on a turn table, which is 0.8 meter high above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarization of the antenna is set on Test. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.10-2009 on radiated emission Test.

This test was performed with EUT in X, Y, Z position, and the worse case was found when EUT in X position as the test photo indicated.

The bandwidth of the EMI test receiver (R&S ESVS10) is set at 120kHz for frequency range from 30MHz to 1000 MHz.

The bandwidth of the Spectrum's RBW is set at 1MHz and VBW is set at 3MHz for peak emissions measurement above 1GHz

This device is pulse Modulated, a duty cycle factor was used to calculated average level based measured peak level.

The frequency range from 30MHz to 10th harmonic (25GHz) are checked. and no any emissions were found from 18GHz to 25 GHz, So the radiated emissions from 18GHz to 25GHz were not record.



4.7. Radiated Emission Test Results


PASS.

All the emissions from 30MHz to 25GHz were comply with the 15.209 Limit.

Note: The duty cycle factor for calculate average level is 9.0dB, and average limit is 20dB below peak limit, so if peak measured level comply with peak limit, the average level was deemed to comply with average limit.

Duty cycle: $0.4383 \text{ ms} / 1.235 \text{ ms} * 100\% = 35\%$
 Duty cycle factor = $20 \log (1/\text{duty cycle}) = 9.00$






Frequency: 30MHz~1GHz

Data: 21

File: E:\2012 Report Data\SONY\ACS1202376.EM6 (24)

Date: 2012-12-05




Site no. : 3m Chamber
 Dis. / Ant. : 3m 2012 CBL6111C 2598
 Limit : FCC PART 15 C (3M)
 Env. / Ins. : 24°C/56%
 EUT : Bluetooth Module
 Power supply : DC 3.3V
 Test Mode : Tx Mode (BT)
 M/N:BTMS3

Data no. : 21
 Ant. pol. : HORIZONTAL
 Engineer : Leo-Li

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	204.600	9.69	1.08	17.10	27.87	43.50	15.63	QP
2	289.960	13.62	1.25	8.40	23.27	46.00	22.73	QP
3	503.360	19.16	1.85	4.59	25.60	46.00	20.40	QP
4	565.440	19.91	2.01	5.56	27.48	46.00	18.52	QP
5	631.400	20.75	2.21	5.68	28.64	46.00	17.36	QP
6	798.240	22.75	2.70	4.20	29.65	46.00	16.35	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber	Data no. : 22
Dis. / Ant. : 3m 2012 CBL6111C 2598	Ant. pol. : VERTICAL
Limit : FCC PART 15 C (3M)	
Env. / Ins. : 24°C/56%	Engineer : Leo-Li
EUT : Bluetooth Module	
Power supply : DC 3.3V	
Test Mode : Tx Mode(BT)	
M/N:BTMS3	


No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	41.640	12.44	0.57	13.03	26.04	40.00	13.96	QP
2	86.260	7.72	0.79	18.34	26.85	40.00	13.15	QP
3	131.850	11.36	0.91	13.05	25.32	43.50	18.18	QP
4	144.460	11.17	0.94	12.50	24.61	43.50	18.89	QP
5	565.440	19.91	2.01	5.43	27.35	46.00	18.65	QP
6	798.240	22.75	2.70	3.95	29.40	46.00	16.60	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.


Frequency: 1GHz~18GHz

Data: 1 File: E:\2012 Report\Si\sony\ACS12Q2376.EM6 (68)

Date: 2012-11-22



Site no.	: 3m Chamber	Data no.	: 1
Dis. / Ant.	: 3m 2012 3115 (4580)	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23°C/54%	Engineer	: Leo-Li
EUT	: Bluetooth Module		
Power supply	: DC 3.3V		
Test mode	: Tx Mode GFSK 2402MHz		
M/N	: BTMS3		




Site no. : 3m Chamber Data no. : 2
 Dis. / Ant. : 3m 2012 3115 (4580) Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54% Engineer : Leo-Li
 EUT : Bluetooth Module
 Power supply : DC 3.3V
 Test mode : Tx Mode GFSK 2402MHz
 M/N : BTMS3


	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.000	26.77	6.02	35.92	90.48	87.35	74.00	-13.35	Peak
2	4804.000	32.47	8.67	35.72	48.27	53.69	74.00	20.31	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.



Site no.	: 3m Chamber	Data no.	: 3
Dis. / Ant.	: 3m 2012 3115 (4580)	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23°C/54%	Engineer	: Leo-Li
EUT	: Bluetooth Module		
Power supply	: DC 3.3V		
Test mode	: Tx Mode GFSK 2402MHz		
M/N	: BTMS3		




Site no. : 3m Chamber Data no. : 4
 Dis. / Ant. : 3m 2012 3115 (4580) Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54% Engineer : Leo-Li
 EUT : Bluetooth Module
 Power supply : DC 3.3V
 Test mode : Tx Mode GFSK 2402MHz
 M/N : BTMS3


	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2402.000	26.77	6.02	35.92	89.98	86.85	74.00	-12.85	Peak
2	4804.000	32.47	8.67	35.72	40.41	45.83	74.00	28.17	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber	Data no. : 7
Dis. / Ant. : 3m 2012 3115 (4580)	Ant. pol. : VERTICAL
Limit : FCC PART 15C PEAK	Engineer : Leo-Li
Env. / Ins. : 23°C/54%	
EUT : Bluetooth Module	
Power supply : DC 3.3V	
Test mode : Tx Mode GFSK 2441MHz	
M/N : BTMS3	




```

Site no.      : 3m Chamber           Data no.   : 8
Dis. / Ant.   : 3m 2012 3115 (4580) Ant. pol.  : VERTICAL
Limit        : FCC PART 15C PEAK
Env. / Ins.   : 23*C/54%           Engineer   : Leo-Li
EUT          : Bluetooth Module
Power supply  : DC 3.3V
Test mode    : Tx Mode GFSK 2441MHz
M/N         : BTMS3
    
```


	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2441.000	27.02	6.09	35.92	89.52	86.71	74.00	-12.71	Peak
2	4882.000	32.64	8.74	35.69	45.48	51.17	74.00	22.83	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.



Site no.	: 3m Chamber	Data no.	: 9
Dis. / Ant.	: 3m 2012 3115 (4580)	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23°C/54%	Engineer	: Leo-Li
EUT	: Bluetooth Module		
Power supply	: DC 3.3V		
Test mode	: Tx Mode GFSK 2441MHz		
M/N	: BTMS3		




Site no. : 3m Chamber Data no. : 10
 Dis. / Ant. : 3m 2012 3115 (4580) Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23*C/54% Engineer : Leo-Li
 EUT : Bluetooth Module
 Power supply : DC 3.3V
 Test mode : Tx Mode GFSK 2441MHz
 M/N : BTMS3


	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2441.000	27.02	6.09	35.92	86.89	84.08	74.00	-10.08	Peak
2	4882.000	32.64	8.74	35.69	43.47	49.16	74.00	24.84	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.



Site no.	: 3m Chamber	Data no.	: 11
Dis. / Ant.	: 3m 2012 3115 (4580)	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23°C/54%	Engineer	: Leo-Li
EUT	: Bluetooth Module		
Power supply	: DC 3.3V		
Test mode	: Tx Mode GFSK 2480MHz		
M/N	: BTMS3		




Site no. : 3m Chamber Data no. : 12
 Dis. / Ant. : 3m 2012 3115 (4580) Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54% Engineer : Leo-Li
 EUT : Bluetooth Module
 Power supply : DC 3.3V
 Test mode : Tx Mode GFSK 2480MHz
 M/N : BTMS3

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.000	27.27	6.15	35.92	79.36	76.86	74.00	-2.86	Peak
2	4960.000	32.81	8.81	35.66	49.21	55.17	74.00	18.83	Peak


Remarks:

- Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
- The emission levels that are 20dB below the official limit are not reported.

Frequency (MHz)	Peak level (dBuV/m)	Duty cycle factor (dB)	AV level (dBuV/m)	Limit(dBuV/m)	Conclusion
4960	55.17	9.00	46.17	54	Pass



Site no.	: 3m Chamber	Data no.	: 13
Dis. / Ant.	: 3m 2012 3115 (4580)	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK	Engineer	: Leo-Li
Env. / Ins.	: 23°C/54%		
EUT	: Bluetooth Module		
Power supply	: DC 3.3V		
Test mode	: Tx Mode GFSK 2480MHz		
M/N	: BTMS3		




```

Site no.      : 3m Chamber           Data no.   : 14
Dis. / Ant.  : 3m 2012 3115 (4580)  Ant. pol.  : HORIZONTAL
Limit        : FCC PART 15C PEAK
Env. / Ins.  : 23*C/54%             Engineer   : Leo-Li
EUT          : Bluetooth Module
Power supply : DC 3.3V
Test mode    : Tx Mode GFSK 2480MHz
M/N         : BTMS3
    
```


	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	27.27	6.15	35.92	85.21	82.71	74.00	-8.71	Peak
2	32.81	8.81	35.66	45.67	51.63	74.00	22.37	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.



Site no.	: 3m Chamber	Data no.	: 19
Dis. / Ant.	: 3m 2012 3115 (4580)	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23°C/54%	Engineer	: Leo-Li
EUT	: Bluetooth Module		
Power supply	: DC 3.3V		
Test mode	: Tx Mode 8-DPSK 2480MHz		
M/N	: BTMS3		




Site no.	: 3m Chamber	Data no.	: 20
Dis. / Ant.	: 3m 2012 3115 (4580)	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23°C/54%	Engineer	: Leo-Li
EUT	: Bluetooth Module		
Power supply	: DC 3.3V		
Test mode	: Tx Mode 8-DPSK 2480MHz		
M/N	: BTMS3		


	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.000	27.27	6.15	35.92	84.75	82.25	74.00	-8.25	Peak
2	4960.000	32.81	8.81	35.66	45.54	51.50	74.00	22.50	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.



Site no.	: 3m Chamber	Data no.	: 21
Dis. / Ant.	: 3m 2012 3115 (4580)	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK	Engineer	: Leo-Li
Env. / Ins.	: 23°C/54%		
EUT	: Bluetooth Module		
Power supply	: DC 3.3V		
Test mode	: Tx Mode 8-DPSK 2480MHz		
M/N	: BTMS3		




Site no. : 3m Chamber Data no. : 22
 Dis. / Ant. : 3m 2012 3115 (4580) Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54% Engineer : Leo-Li
 EUT : Bluetooth Module
 Power supply : DC 3.3V
 Test mode : Tx Mode 8-DPSK 2480MHz
 M/N : BTMS3


	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.000	27.27	6.15	35.92	85.76	83.26	74.00	-9.26	Peak
2	4960.000	32.81	8.81	35.66	43.53	49.49	74.00	24.51	Peak

Remarks:

- Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
- The emission levels that are 20dB below the official limit are not reported.



Site no.	: 3m Chamber	Data no.	: 23
Dis. / Ant.	: 3m 2012 3115 (4580)	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK	Engineer	: Leo-Li
Env. / Ins.	: 23°C/54%		
EUT	: Bluetooth Module		
Power supply	: DC 3.3V		
Test mode	: Tx Mode 8-DPSK 2441MHz		
M/N	: BTMS3		




Site no. : 3m Chamber Data no. : 24
 Dis. / Ant. : 3m 2012 3115 (4580) Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54% Engineer : Leo-Li
 EUT : Bluetooth Module
 Power supply : DC 3.3V
 Test mode : Tx Mode 8-DPSK 2441MHz
 M/N : BTMS3


	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.000	27.27	6.15	35.92	86.41	83.91	74.00	-9.91	Peak
2	4882.000	32.64	8.74	35.69	43.41	49.10	74.00	24.90	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.



Site no.	: 3m Chamber	Data no.	: 25
Dis. / Ant.	: 3m 2012 3115 (4580)	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23°C/54%	Engineer	: Leo-Li
EUT	: Bluetooth Module		
Power supply	: DC 3.3V		
Test mode	: Tx Mode 8-DPSK 2441MHz		
M/N	: BTMS3		




Site no. : 3m Chamber Data no. : 26
 Dis. / Ant. : 3m 2012 3115 (4580) Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54% Engineer : Leo-Li
 EUT : Bluetooth Module
 Power supply : DC 3.3V
 Test mode : Tx Mode 8-DPSK 2441MHz
 M/N : BTMS3


	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2441.000	27.02	6.09	35.92	87.87	85.06	74.00	-11.06	Peak
2	4882.000	32.64	8.74	35.69	44.05	49.74	74.00	24.26	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.



Site no.	: 3m Chamber	Data no.	: 27
Dis. / Ant.	: 3m 2012 3115 (4580)	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23°C/54%	Engineer	: Leo-Li
EUT	: Bluetooth Module		
Power supply	: DC 3.3V		
Test mode	: Tx Mode 8-DPSK 2402MHz		
M/N	: BTMS3		




Site no. : 3m Chamber Data no. : 28
 Dis. / Ant. : 3m 2012 3115 (4580) Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54% Engineer : Leo-Li
 EUT : Bluetooth Module
 Power supply : DC 3.3V
 Test mode : Tx Mode 8-DPSK 2402MHz
 M/N : BTMS3


	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.000	26.77	6.02	35.92	89.67	86.54	74.00	-12.54	Peak
2	4804.000	32.47	8.67	35.72	44.72	50.14	74.00	23.86	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.



Site no.	: 3m Chamber	Data no.	: 29
Dis. / Ant.	: 3m 2012 3115 (4580)	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK	Engineer	: Leo-Li
Env. / Ins.	: 23°C/54%		
EUT	: Bluetooth Module		
Power supply	: DC 3.3V		
Test mode	: Tx Mode 8-DPSK 2402MHz		
M/N	: BTMS3		



Site no. : 3m Chamber Data no. : 30
 Dis. / Ant. : 3m 2012 3115 (4580) Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54% Engineer : Leo-Li
 EUT : Bluetooth Module
 Power supply : DC 3.3V
 Test mode : Tx Mode 8-DPSK 2402MHz
 M/N : BTMS3

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.000	26.77	6.02	35.92	88.15	85.02	74.00	-11.02	Peak
2	4804.000	32.47	8.67	35.72	44.32	49.74	74.00	24.26	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

5. CONDUCTED SPURIOUS EMISSIONS

5.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analyzer	Agilent	E4446A	US44300459	May.08,12	1 Year
2.	Attenuator	Agilent	8491B	MY39262165	May.08,12	1 Year
3.	RF Cable	Hubersuhner	SUCOFLEX102	28618/2	May.08,12	1Year

5.2. Limit

In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.



5.3. Test Procedure



The transmitter output was connected to a spectrum analyzer, The resolution bandwidth is set to 100 kHz, The video bandwidth is set to 300 kHz and measure all the emissions detected.

5.4. Test result


PASS (The testing data was attached in the next pages.)

GFSK
2402MHz






2441MHz




Copyright 2000-2005 Agilent Technologies




Copyright 2000-2005 Agilent Technologies


2480MHz



Copyright 2000-2005 Agilent Technologies




Copyright 2000-2005 Agilent Technologies





Copyright 2000-2005 Agilent Technologies


8-DPSK

2402MHz






Copyright 2000-2005 Agilent Technologies









2441MHz











Hopping on GFSK





Copyright 2000-2005 Agilent Technologies



Copyright 2000-2005 Agilent Technologies

8-DPSK



6. CARRIER FREQUENCY SEPARATION TEST

6.1. Test Equipment


Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Spectrum Analyzer	Agilent	E4446A	US44300459	May.08, 12	1 Year

6.2. Limit

Frequency hopping systems shall have hopping channel carrier frequency separated by a minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

6.3. Test Results.

EUT: Bluetooth Module		
M/N: BTMS3		
Test date: 2012-12-02	Pressure: 101.2±1.0 kpa	Humidity: 52.3±3.0%
Tested by: Leo-Li	Test site: RF Site	Temperature: 23.2±0.6°C
Channel separation		Conclusion
1.00MHz		PASS



7. 20 DB BANDWIDTH TEST

7.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum	Agilent	E4446A	US44300459	May.08, 12	1 Year

7.2. Limit

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

7.3. Test Results

EUT: Bluetooth Module		
M/N: BTMS3		
Test date: 2012-11-23	Pressure: 101.2 ± 1.0 kpa	Humidity: 50.8 ± 3.0%
Tested by: Leo-Li	Test site: RF Site	Temperature: 21.4 ± 0.6°C


Cable loss: 1 dB		Attenuator loss: 20 dB	
Test Mode	CH (MHz)	20dB bandwidth (KHz)	Limit (KHz)
GFSK	2402	800.696	N/A
	2441	789.078	N/A
	2480	840.144	N/A
8-DPSK	2402	1207	N/A
	2441	1203	N/A
	2480	1198	N/A
Conclusion: PASS			

GFSK


Test Frequency: 2402MHz



Test Frequency: 2441MHz




Test Frequency: 2480MHz




8-DPSK


Test Frequency: 2402MHz



Test Frequency: 2441MHz



Test Frequency: 2480MHz



8. NUMBER OF HOPPING FREQUENCY TEST

8.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Spectrum	Agilent	E4446A	US44300459	May.08, 12	1 Year



8.2. Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels

8.3. Test Results

EUT: Bluetooth Module		
M/N: BTMS3		
Test date: 2012-11-23	Pressure: 101.2 ± 1.0 kpa	Humidity: $50.8 \pm 3.0\%$
Tested by: Leo-Li	Test site: RF Site	Temperature: $21.4 \pm 0.6^\circ\text{C}$

Number of channel	Limit	Conclusion
79	≥ 15	PASS



9. DWELL TIME

9.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Spectrum	Agilent	E4446A	US44300459	May.08, 12	1 Year

9.2. Limit

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

9.3. Test Results



EUT: Bluetooth Module		
M/N: BTMS3		
Test date: 2012-11-23	Pressure: 101.2 ± 1.0 kpa	Humidity: 50.8 ± 3.0%
Tested by: Leo-Li	Test site: RF Site	Temperature: 21.4 ± 0.6°C

Mode		dwell time	Limit	Conclusion
GFSK	DH1	$51\text{hops}/5\text{s} * 0.4 * 79\text{channels} * 0.435 = 140.209\text{ms}$	<400ms	PASS
	DH3	$26\text{hops}/5\text{s} * 0.4 * 79\text{channels} * 1.77 = 290.8464\text{ms}$	<400ms	PASS
	DH5	$17\text{hops}/5\text{s} * 0.4 * 79\text{channels} * 3.05\text{ms} = 327.692\text{ms}$	<400ms	PASS
8-DPSK	DH1	$51\text{hops}/5\text{s} * 0.4 * 79\text{channels} * 0.4483\text{ms} = 144.4961\text{ms}$	<400ms	PASS
	DH3	$25\text{hops}/5\text{s} * 0.4 * 79\text{channels} * 1.702\text{ms} = 268.916\text{ms}$	<400ms	PASS
	DH5	$18\text{hops}/5\text{s} * 0.4 * 79\text{channels} * 2.975\text{ms} = 338.436\text{ms}$	<400ms	PASS



Note: All the lower levels were signal from receiver's, and should not considered in here.

GFSK



DH 1





DH 3





DH 5



DH 3



DH 5



10. MAXIMUM PEAK OUTPUT POWER TEST

10.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum	Agilent	E4446A	US44300459	May.08, 12	1 Year
2.	Amp	HP	8449B	3008A08495	May.08, 12	1 Year
3.	Antenna	EMCO	3115	9510-4580	May.31, 12	1Year
4.	HF Cable	Hubersuhne	Sucoflex104	-	May.08, 12	1 Year
5	Power Meter	Anritsu	ML2487A	6K00002472	May.08, 12	1Year
6	Power Sensor	Anritsu	MA2491A	033005	May.08, 12	1Year

10.2. Limit

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

10.3. Test Procedure


1. Connected the EUT's antenna port to spectrum analyzer.
2. Set the RBW> Bandwidth of test Frequency and put the test Frequency, Set the Span large enough to capture the entire signal
3. Use a peak detector on max hold
4. Reading the value from the Spectrum analyzer

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.


10.4. Test Results

EUT: Bluetooth Module			
M/N: BTMS3			
Test date: 2012-11-23		Pressure: 101.2±1.0 kpa	Humidity: 52.3±3.0%
Tested by: Leo-Li		Test site: RF site	Temperature: 22.1±0.6 °C
Cable loss: 1dB		Attenuator loss: 20 dB	
Test Mode	CH (MHz)	Peak output Power (dBm)	Limit (dBm)
GFSK	2402	2.89	30
	2441	3.02	30
	2480	3.01	30
8-DPSK	2402	2.26	30
	2441	2.47	30
	2480	2.48	30
Conclusion: PASS			


GFSK
2402MHz



2441MHz




2480MHz




8-DPSK


2402MHz



2441MHz



2480MHz



11. BAND EDGE COMPLIANCE TEST

11.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum	Agilent	E4446A	US44300459	May.08, 12	1 Year
2.	Amp	HP	8449B	3008A08495	May.08, 12	1 Year
3.	Antenna	EMCO	3115	4580	May.08, 12	1 Year
4.	HF Cable	Hubersuhne	Sucoflex104	-	May.08, 12	1 Year

11.2. Limit

All the lower and upper band-edges emissions appearing within 2310MHz to 2390MHz and 2483.5MHz to 2500MHz restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

11.3. Test Produce

For upper band emissions that are up to two bandwidths(2MHz) away (2483.5MHz to 2485.5MHz) from the band-edge use below produce:

1. Choose a spectrum analyzer span that encompasses both the peak of the fundamental emission and the band-edge emission under investigation. Set the analyzer RBW to 100KHz and with a video bandwidth 300KHz. Record the peak levels of the fundamental emission and the relevant band-edge emission, Observe the stored trace and measure the amplitude delta between the peak of the fundamental and the peak of the band-edge emission. This is not a field strength measurement, it is only a relative measurement to determine the amount by which the emission drops at the band edge relative to the highest fundamental emission level.
2. Subtract the delta measured in step (1) from the maximum field strengths measured in clause 4 .The resultant field strengths are then used to determine band-edge compliance as required by Section 15.205


For emissions above two bandwidths away from the band-edge use below produce:

1. The EUT is placed on a turntable, which is 0.8m above the ground plane and worked at highest radiated power.
2. The turntable was rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upperband-edges of the emission:
 - (a) PEAK: RBW=1MHz ;VBW=3MHz, PK detector, Sweep=AUTO
 - (b) This is pulse Modulation device a duty cycle factor was used to calculate average level based measured peak level.

11.4. Test Results

Pass (The testing data was attached in the next pages.)

Note: If the PK measured levels comply with average limit, then the average level were deemed to comply with average limit.




Site no. : 3m Chamber Data no. : 5
 Dis. / Ant. : 3m 2012 3115 (4580) Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54% Engineer : Leo-Li
 EUT : Bluetooth Module
 Power supply : DC 3.3V
 Test mode : Tx Mode GFSK 2402MHz
 M/N : BTMS3

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.000	26.70	6.00	35.92	44.40	41.18	74.00	32.82	Peak
2	2400.000	26.76	6.02	35.92	55.44	52.30	74.00	21.70	Peak
3	2401.960	26.77	6.02	35.92	90.05	86.92	74.00	-12.92	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 6
 Dis. / Ant. : 3m 2012 3115 (4580) Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54% Engineer : Leo-Li
 EUT : Bluetooth Module
 Power supply : DC 3.3V
 Test mode : Tx Mode GFSK 2402MHz
 M/N : BTMS3

	Ant. Factor	Cable loss	Amp. Factor	Reading	Emission Level	Limits	Margin	Remark
Freq. (MHz)	(dB/m)	(dB)	(dB)	(dBUV)	(dBUV/m)	(dBUV/m)	(dB)	
1 2390.000	26.70	6.00	35.92	44.30	41.08	74.00	32.92	Peak
2 2400.000	26.76	6.02	35.92	56.90	53.76	74.00	20.24	Peak
3 2402.150	26.77	6.02	35.92	89.64	86.51	74.00	-12.51	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 15
 Dis. / Ant. : 3m 2012 3115 (4580) Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54% Engineer : Leo-Li
 EUT : Bluetooth Module
 Power supply : DC 3.3V
 Test mode : Tx Mode GFSK 2480MHz
 M/N : BTMS3

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2479.805	27.27	6.15	35.92	79.32	76.82	74.00	-2.82	Peak
2	2483.500	27.29	6.16	35.92	44.76	42.29	74.00	31.71	Peak
3	2494.160	27.36	6.18	35.92	47.94	45.56	74.00	28.44	Peak
4	2500.000	27.40	6.19	35.93	43.83	41.49	74.00	32.51	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 16
 Dis. / Ant. : 3m 2012 3115 (4580) Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54% Engineer : Leo-Li
 EUT : Bluetooth Module
 Power supply : DC 3.3V
 Test mode : Tx Mode GFSK 2480MHz
 M/N : BTMS3

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.871	27.27	6.15	35.92	85.06	82.56	74.00	-8.56	Peak
2	2483.500	27.29	6.16	35.92	45.35	42.88	74.00	31.12	Peak
3	2492.906	27.35	6.18	35.92	46.35	43.96	74.00	30.04	Peak
4	2500.000	27.40	6.19	35.93	43.99	41.65	74.00	32.35	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 17
 Dis. / Ant. : 3m 2012 3115 (4580) Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54% Engineer : Leo-Li
 EUT : Bluetooth Module
 Power supply : DC 3.3V
 Test mode : Tx Mode 8-DPSK 2480MHz
 M/N : BTMS3

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.871	27.27	6.15	35.92	84.82	82.32	74.00	-8.32	Peak
2	2483.500	27.29	6.16	35.92	44.16	41.69	74.00	32.31	Peak
3	2496.734	27.38	6.18	35.92	45.83	43.47	74.00	30.53	Peak
4	2500.000	27.40	6.19	35.93	44.25	41.91	74.00	32.09	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 18
 Dis. / Ant. : 3m 2012 3115 (4580) Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54% Engineer : Leo-Li
 EUT : Bluetooth Module
 Power supply : DC 3.3V
 Test mode : Tx Mode 8-DPSK 2480MHz
 M/N : BTMS3

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.069	27.27	6.15	35.92	85.28	82.78	74.00	-8.78	Peak
2	2483.500	27.29	6.16	35.92	46.36	43.89	74.00	30.11	Peak
3	2495.876	27.37	6.18	35.92	49.03	46.66	74.00	27.34	Peak
4	2500.000	27.40	6.19	35.93	44.54	42.20	74.00	31.80	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 31
 Dis. / Ant. : 3m 2012 3115 (4580) Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54% Engineer : Leo-Li
 EUT : Bluetooth Module
 Power supply : DC 3.3V
 Test mode : Tx Mode 8-DPSK 2402MHz
 M/N : BTMS3

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2366.525	26.55	5.96	35.92	46.04	42.63	74.00	31.37	Peak
2	2390.000	26.70	6.00	35.92	43.99	40.77	74.00	33.23	Peak
3	2400.000	26.76	6.02	35.92	62.86	59.72	74.00	14.28	Peak
4	2401.960	26.77	6.02	35.92	89.50	86.37	74.00	-12.37	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 32
 Dis. / Ant. : 3m 2012 3115 (4580) Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54% Engineer : Leo-Li
 EUT : Bluetooth Module
 Power supply : DC 3.3V
 Test mode : Tx Mode 8-DPSK 2402MHz
 M/N : BTMS3

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2347.335	26.42	5.93	35.92	45.96	42.39	74.00	31.61	Peak
2	2390.000	26.70	6.00	35.92	44.15	40.93	74.00	33.07	Peak
3	2400.000	26.76	6.02	35.92	64.17	61.03	74.00	12.97	Peak
4	2402.150	26.77	6.02	35.92	88.32	85.19	74.00	-11.19	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

12.DEVIATION TO TEST SPECIFICATIONS

[NONE]