



# RADIO TEST REPORT

Test Report No. : 28BE0065-HO-02-A

Applicant : Sony Computer Entertainment Inc.  
Type of Equipment : PLAYSTATION®3  
Model No. : CECHH01  
FCC ID : AK8CBEH1300  
Test standard : FCC Part 15 Subpart C 2007  
Section 15.207, Section 15.247  
Test Result : Complied

1. This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
2. The results in this report apply only to the sample tested.
3. This sample tested is in compliance with the above regulation.
4. The test results in this report are traceable to the national or international standards.

Date of test:

September 8 to 21, 2007

Tested by:

*T. Shimada*

Takumi Shimada  
EMC Services

*K. Adachi*

Kenichi Adachi  
EMC Services

Approved by :

*H. Shimoji*

Hironobu Shimoji  
Assistant Manager of  
EMC Services



NVLAP LAB CODE: 200572-0

This laboratory is accredited by the NVLAP LAB CODE 200572-0, U.S.A. The tests reported herein have been performed in accordance with its terms of accreditation.  
\*As for the range of Accreditation in NVLAP, you may refer to the WEB address, <http://uljapan.co.jp/emc/nvlap.htm>

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

MF060b (18.06.07)

<b>CONTENTS</b>	<b>PAGE</b>
<b>SECTION 1: Client information .....</b>	<b>3</b>
<b>SECTION 2: Equipment under test (E.U.T.).....</b>	<b>3</b>
<b>SECTION 3: Test specification, procedures &amp; results.....</b>	<b>5</b>
<b>SECTION 4: Operation of E.U.T. during testing .....</b>	<b>8</b>
<b>SECTION 5: Conducted Emission.....</b>	<b>11</b>
<b>SECTION 6: Spurious Emission .....</b>	<b>12</b>
<b>SECTION 7: Bandwidth .....</b>	<b>13</b>
<b>SECTION 8: Maximum Peak Output Power .....</b>	<b>13</b>
<b>SECTION 9: Peak Power Density.....</b>	<b>13</b>
<b>APPENDIX 1: Photographs of test setup .....</b>	<b>14</b>
<b>Conducted Emission .....</b>	<b>14</b>
<b>Spurious Emission (Radiated) .....</b>	<b>15</b>
<b>Worst Case Position (Horizontal: Y-axis/ Vertical:X-axis) .....</b>	<b>16</b>
<b>APPENDIX 2: Data of EMI test.....</b>	<b>19</b>
<b>Conducted Emission .....</b>	<b>19</b>
<b>6dB Bandwidth .....</b>	<b>26</b>
<b>Maximum Peak Output Power.....</b>	<b>29</b>
<b>Radiated Spurious Emission (below 1GHz).....</b>	<b>33</b>
<b>Radiated Spurious Emission (above 1GHz).....</b>	<b>40</b>
<b>Conducted Spurious Emission.....</b>	<b>47</b>
<b>Conducted emission Band Edge compliance.....</b>	<b>54</b>
<b>Power Density .....</b>	<b>55</b>
<b>99% Occupied Bandwidth .....</b>	<b>58</b>
<b>APPENDIX 3: Test instruments .....</b>	<b>60</b>

## **SECTION 1: Client information**

Company Name	Sony Computer Entertainment Inc.
Brand Name	SONY
Address	2-6-21 Minamiaoyama, Minato-ku, Tokyo, 107-0062, Japan
Telephone Number	+81-3-6438-8023
Facsimile Number	+81-3-6438-8642
Contact Person	Akiko Tsukada

## **SECTION 2: Equipment under test (E.U.T.)**

### **2.1 Identification of E.U.T.**

Type of Equipment	PLAYSTATION®3
Model No	CECHH01
Serial No	1020135
Rating	AC 120V, 60Hz
Country of Manufacture	JAPAN/CHINA
Receipt Date of Sample	September 9, 2007
Condition of EUT	Engineering prototype (Not for Sale: This sample is equivalent to mass-produced items.)
Modification of EUT	No modification by the test lab.

### **2.2 Product Description**

Model: CECHH01, referred to as the EUT in this report, is a PLAYSTATION®3.

The EUT contains Bluetooth (Ver. 2.0+EDR) module and IEEE802.11b/g WLAN module. Those modules do not transmit simultaneously.

Clock Frequencies are CPU: 3.2GHz(CPU), 66MHz(ATA), 133MHz(ATA), 33MHz(PCI), and 750MHz(SATA1).

---

**UL Japan, Inc.**

**Head Office EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

**Bluetooth (Ver. 2.0+EDR)**

Equipment Type	Transceiver	
Frequency of Operation	2402-2480MHz	
Type of Modulation	FHSS (GFSK, $\pi/4$ -DQPSK, 8DPSK)	
Bandwidth & Channel spacing	1MHz & 1MHz	
Power Supply (inner)	DC3.3V	
Antenna Type	ANT1: Reverse F Antenna (manufacturer: SMK / AMP)	ANT2: Dipole Antenna
Antenna Gain	ANT1: 1.85dBi (max)	ANT2: 1.13 dBi (max)
Antenna Connector Type	ANT1: N/A	ANT2: N/A

For Bluetooth part, please see UL Japan, Inc. Test Report Number: 28BE0065-HO-02-B.

**IEEE802.11b/g WLAN**

Equipment Type	Transceiver	
Frequency of Operation	2412-2462MHz	
Type of Modulation	DSSS/OFDM	
Bandwidth & Channel spacing	20MHz & 5MHz	
Power Supply (inner)	DC 3.3V/DC1.3V	
Antenna Type	ANT0: Reverse F Antenna	ANT1: Reverse F Antenna
Antenna Gain	ANT0: 0.86dBi (max)	ANT1: 1.12dBi (max)
Antenna Connector Type	ANT0: U.FL	ANT1: N/A

---

**UL Japan, Inc.**

**Head Office EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

**SECTION 3: Test specification, procedures & results**

**3.1 Test Specification**

Test Specification : FCC Part15 Subpart C: 2007  
Title : FCC 47CFR Part15 Radio Frequency Device Subpart C Intentional Radiators  
Section 15.207 Conducted limits  
Section 15.247 Operation within the bands 902-928MHz, 2400-2483.5MHz, and 5725-5850MHz

**3.2 Procedures and results**

No.	Item	Test Procedure	Specification	Remarks	Deviation	Worst margin	Results
1	Conducted emission	FCC: ANSI C63.4:2003 7. AC powerline conducted emission measurements IC: RSS-Gen 7.2.2	FCC: Section 15.207 IC: RSS-Gen 7.2.2	-	N/A	6.2dB 0.20010MHz AV, Phase: N	Complied
2	6dB Bandwidth	FCC: ANSI C63.4:2003 13. Measurement of intentional radiators IC: RSS-Gen 4.6.2	FCC: Section 15.247(a)(2) IC: RSS-210 A8.2(a)	Conducted	N/A	See data.	Complied
3	Maximum Peak Output Power	FCC: ANSI C63.4:2003 13. Measurement of intentional radiators IC: RSS-Gen 4.8	FCC: Section 15.247(b)(3) IC: RSS-210 A8.4(4)	Conducted	N/A		Complied
4	Restricted Band Edges	FCC: ANSI C63.4:2003 13. Measurement of intentional radiators IC: -	FCC: Section 15.247 (d) IC: RSS-210 A8.5	Conducted/ Radiated	N/A		Complied
5	Power Density	FCC: ANSI C63.4:2003 13. Measurement of intentional radiators IC: -	FCC: Section 15.247 (e) IC: RSS-210 A8.2(b)	Conducted	N/A		Complied
6	Spurious Emission	FCC: ANSI C63.4:2003 13. Measurement of intentional radiators IC: RSS-Gen 4.9 RSS-Gen 4.10	FCC: Section15.247(d) IC: RSS-210 A8.5 RSS-Gen 7.2.1 and 7.2.3	Conducted/ Radiated	N/A		[Tx] 4.5dB 2390.00MHz AV, Vert. [Rx] 6.7dB 35.072MHz, QP Vert.

Note: UL Japan, Inc.'s EMI Work Procedures No.QPM05 and QPM15.

\*These tests were also referred to "Guidance on Measurement of Digital Transmission Systems Operating under Section15.247".  
\*These tests were performed without any deviations from test procedure except for additions or exclusions.

**UL Japan, Inc.**  
**Head Office EMC Lab.**  
4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN  
Telephone : +81 596 24 8116  
Facsimile : +81 596 24 8124

### 3.3 Addition to standards

No.	Item	Test Procedure	Specification	Remarks	Deviation	Worst margin	Results
1	99% Occupied Band Width	IC: RSS-Gen 4.6.1	IC: RSS-Gen 4.6.1	Conducted	N/A	N/A	N/A

### 3.4 Uncertainty

The following uncertainties have been calculated to provide a confidence level of 95% using a coverage factor k=2.

#### Conducted Emission

The measurement uncertainty for this test is  $\pm 2.66$ dB.

The data listed in this test report has enough margin, more than the site margin.

#### Spurious Emission (Radiated)

The measurement uncertainty for this test using Biconical antenna is  $\pm 4.59$ dB(3m).

The measurement uncertainty for this test using Logperiodic antenna is  $\pm 4.62$ dB(3m).

The measurement uncertainty for this test using Horn antenna is  $\pm 5.27$ dB.

**(Tx)** The data listed in this report meets the limits unless the uncertainty is taken into consideration.

**(Rx)** The data listed in this test report has enough margin, more than the site margin.

#### Other test except Conducted Emission and Spurious Emission (Radiated)

The measurement uncertainty for this test is  $\pm 3.0$ dB.

---

**UL Japan, Inc.**

**Head Office EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

### 3.5 Test Location

UL Japan, Inc. Head Office EMC Lab. \*NVLAP Lab. code: 200572-0  
4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN  
Telephone: +81 596 24 8116 Facsimile: +81 596 24 8124

	FCC Registration Number	IC Registration Number	Width x Depth x Height (m)	Size of reference ground plane (m) / horizontal conducting plane	Other rooms
No.1 semi-anechoic chamber	313583	IC4247	19.2 x 11.2 x 7.7m	7.0 x 6.0m	No.1 Power source room
No.2 semi-anechoic chamber	655103	IC4247-2	7.5 x 5.8 x 5.2m	4.0 x 4.0m	-
No.3 semi-anechoic chamber	148738	IC4247-3	12.0 x 8.5 x 5.9m	6.8 x 5.75m	No.3 Preparation room
No.3 shielded room	-	-	4.0 x 6.0 x 2.7m	N/A	-
No.4 semi-anechoic chamber	134570	IC4247-4	12.0 x 8.5 x 5.9m	6.8 x 5.75m	No.4 Preparation room
No.4 shielded room	-	-	4.0 x 6.0 x 2.7m	N/A	-
No.5 semi-anechoic chamber	-	-	6.0 x 6.0 x 3.9m	6.0 x 6.0m	-
No.6 shielded room	-	-	4.0 x 4.5 x 2.7m	4.75 x 5.4 m	-
No.6 measurement room	-	-	4.75 x 5.4 x 3.0m	4.75 x 4.15 m	-
No.7 shielded room	-	-	4.7 x 7.5 x 2.7m	4.7 x 7.5m	-
No.8 measurement room	-	-	3.1 x 5.0 x 2.7m	N/A	-

\* Size of vertical conducting plane (for Conducted Emission test) : 2.0 x 2.0m for No.1, No.2, No.3, and No.4 semi-anechoic chambers and No.3 and No.4 shielded rooms.

### 3.6 Test set up, Test instruments and Data of EMI

Refer to APPENDIX 1 to 3.

## **SECTION 4: Operation of E.U.T. during testing**

### **4.1 Operating Modes**

The mode used for test : [IEEE 802.11b / IEEE 802.11g : DSSS / OFDM]

<b>Test</b>	<b>Mode</b>	<b>Tested frequency</b>	<b>Tested antenna</b>
Conducted emission	IEEE802.11b Transmitting (Tx), 11Mbps, PN9 IEEE802.11g Transmitting (Tx), 54Mbps, PN9	2412MHz 2437MHz 2462MHz	ANT0
	----- IEEE802.11b/g Receiving (Rx)	2437MHz	ANT0
6dB Bandwidth Maximum Peak Output Power Power Density 99% Occupied Bandwidth	IEEE802.11b Transmitting (Tx), 2Mbps, PN9	2412MHz	ANT1
	IEEE802.11g Transmitting (Tx), 12Mbps, PN9	2437MHz 2462MHz	
	----- IEEE802.11b/g Receiving (Rx)	2437MHz	
Spurious Emission (Radiated)	IEEE802.11b Transmitting (Tx), 11Mbps, PN9 IEEE802.11g Transmitting (Tx), 54Mbps, PN9	2412MHz 2437MHz 2462MHz	ANT0
	----- IEEE802.11b/g Receiving (Rx)	2437MHz	ANT0
Spurious Emission (Conducted)	IEEE802.11b Transmitting (Tx), 2Mbps, PN9	2412MHz	ANT1
	IEEE802.11g Transmitting (Tx), 12Mbps, PN9	2437MHz 2462MHz	
	----- IEEE802.11b/g Receiving (Rx)	2437MHz	
Restricted Band Edge (Radiated)	IEEE802.11b Transmitting (Tx), 11Mbps, PN9 IEEE802.11g Transmitting (Tx), 54Mbps, PN9	2412MHz 2462MHz	ANT0
	----- IEEE802.11b/g Receiving (Rx)	2437MHz	ANT1
Restricted Band Edge (Conducted)	IEEE802.11b Transmitting (Tx), 2Mbps, PN9	2412MHz	ANT1
	IEEE802.11g Transmitting (Tx), 12Mbps, PN9	2462MHz	

\*As a result of preliminary check for two antennas (ANT0 and ANT1), the formal test was performed as above-mentioned table.

#### **Preliminary check result (Worst antenna & Data rate):**

Conducted Emission & Radiated Emission	11b: ANT0, 11Mbps 11g: ANT0, 54Mbps
Antenna Terminal Conducted test	11b: ANT1, 2Mbps 11g: ANT1, 12Mbps

**UL Japan, Inc.**

**Head Office EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

## 4.2 Configuration and peripherals

**This page has been submitted for a separate exhibit.**

**This page has been submitted for a separate exhibit.**

## **SECTION 5: Conducted Emission**

### **Test Procedure and conditions**

EUT was placed on a urethane platform of nominal size, 1.0m by 1.5m, raised 80cm above the conducting ground plane. The rear of tabletop was located 40cm to the vertical conducting plane. The rear of EUT, including peripherals aligned and flushed with rear of tabletop. All other surfaces of tabletop were at least 80cm from any other grounded conducting surface. EUT was located 80cm from a Line Impedance Stabilization Network (LISN)/ Artificial mains Network (AMN) and excess AC cable was bundled in center.

#### For the tests on EUT with other peripherals (as a whole system)

I/O cable and AC cables that were connected to the peripherals were bundled in center. They were folded back and forth forming a bundle 30cm to 40cm long and were hanged at a 40cm height to the ground plane. All unused 50ohm connectors of the LISN(AMN) were resistivity terminated in 50ohm when not connected to the measuring equipment.

The AC Mains Terminal Continuous disturbance Voltage has been measured with the EUT in a Semi Anechoic Chamber or a Measurement Room.

The EUT was connected to a LISN (AMN).

An overview sweep with peak detection has been performed.

**Detector** : quasi-peak and average detector (IF BW 9 kHz)  
**Measurement range** : 0.15-30MHz  
**Test data** : APPENDIX 2  
**Test result** : Pass

---

**UL Japan, Inc.**

**Head Office EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

**SECTION 6: Spurious Emission**

**[Conducted]**

**Test Procedure**

The Out of Band Emission was measured with a spectrum analyzer connected to the antenna port.

**Test data : APPENDIX 2**

**Test result : Pass**

**[Radiated]**

**Test Procedure**

EUT was placed on a urethane platform of nominal size, 1.0m by 1.5m, raised 80cm above the conducting ground plane. The Radiated Electric Field Strength intensity has been measured in a Semi Anechoic Chamber with a ground plane and at a distance of 3m(Below 10GHz) and 1m(Upper 10GHz).

The height of the measuring varied between 1 and 4m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity.

The measurements were performed for both vertical and horizontal antenna polarization with the Test Receiver, or the Spectrum Analyzer (in linear mode).

The test was made with the detector (RBW/VBW) in the following table.

When using Spectrum analyzer, the test was made with adjusting span to zero by using peak hold.

In any 100kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator confirmed 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on a radiated measurement.

**20dBc was applied to the frequency over the limit of FCC 15.209 / Table 2 of RSS-210 2.7 (IC) and outside the restricted band of FCC15.205 / Table 1 of RSS-210 2.7 (IC).**

Frequency	Below 1GHz	Above 1GHz
Instrument used	Test Receiver / Spectrum Analyzer	Spectrum Analyzer
Detector	QP: BW 120kHz(T/R)	PK: RBW:1MHz/VBW: 1MHz
IF Bandwidth	20dBc : RBW: 100kHz VBW: 300kHz (S/A)	AV: RBW:1MHz/VBW:10Hz 20dBc : RBW:100kHz/VBW:300kHz

- The carrier level and noise levels were confirmed at each position of X and Y axes of EUT to see the position of maximum noise, and the test was made at the position that has the maximum noise.

**Test data : APPENDIX 2**

**Test result : Pass**

---

**UL Japan, Inc.**

**Head Office EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

## **SECTION 7: Bandwidth**

### **Test Procedure**

The bandwidth was measured with a spectrum analyzer connected to the antenna port.

**Test data** : APPENDIX 2  
**Test result** : Pass

## **SECTION 8: Maximum Peak Output Power**

### **Test Procedure**

The Maximum Peak Output Power was measured with a power meter (tested bandwidth: 50MHz) connected to the antenna port.

It was measured based on "Power Output Option 1" of "Guidance on Measurement of Digital Transmission Systems Operating under Section15.247".

**Test data** : APPENDIX 2  
**Test result** : Pass

## **SECTION 9: Peak Power Density**

[Conducted]

### **Test Procedure**

The Peak Power Density was measured with a spectrum analyzer connected to the antenna port.

It was measured based on "PSD Option 1" of "Guidance on Measurement of Digital Transmission Systems Operating under Section15.247".

**Test data** : APPENDIX 2  
**Test result** : Pass

---

**UL Japan, Inc.**

**Head Office EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124