



# RADIO TEST REPORT

**Test Report No. : 28KE0107-HO-01-A**

**Applicant** : **Sony Computer Entertainment Inc.**  
**Type of Equipment** : **PLAYSTATION®3**  
**Model No.** : **CECHL01**  
**FCC ID** : **AK8CBEH1500**  
**Test regulation** : **FCC Part 15 Subpart C 2008  
Section 15.207, Section 15.247**  
**Test Result** : **Complied**

1. This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
2. The results in this report apply only to the sample tested.
3. This sample tested is in compliance with the above regulation.
4. The test results in this report are traceable to the national or international standards.
5. This test report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

**Date of test:**

June 17 to July 3, 2008

**Tested by:**

*S. Matsuyama*

Satofumi Matsuyama  
EMC Services

*Y. Yoshida*

Yutaka Yoshida  
EMC Services

*T. Shimada*

Takumi Shimada  
EMC Services

*M. Imura*

Motoya Imura  
EMC Services

*Takayuki S.*

Takayuki Shimada  
EMC Services

*K. Adachi*

Kenichi Adachi  
EMC Services

*H. Sato*

Hisayoshi Sato  
EMC Services

**Approved by :**

*M. Fujimura*

Mitsuru Fujimura  
Assistant Manager of EMC Services



NVLAP LAB CODE: 200572-0

This laboratory is accredited by the NVLAP LAB CODE 200572-0, U.S.A. The tests reported herein have been performed in accordance with its terms of accreditation.  
\*As for the range of Accreditation in NVLAP, you may refer to the WEB address, <http://uljapan.co.jp/emc/nvlap.htm>

**UL Japan, Inc.**

**Head Office EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

MF060b (09.01.08)

<b>CONTENTS</b>	<b>PAGE</b>
<b>SECTION 1: Customer information.....</b>	<b>3</b>
<b>SECTION 2: Equipment under test (E.U.T.).....</b>	<b>3</b>
<b>SECTION 3: Test specification, procedures &amp; results.....</b>	<b>5</b>
<b>SECTION 4: Operation of E.U.T. during testing.....</b>	<b>9</b>
<b>SECTION 5: Conducted Emission.....</b>	<b>12</b>
<b>SECTION 6: Spurious Emission.....</b>	<b>13</b>
<b>SECTION 7: Bandwidth.....</b>	<b>14</b>
<b>SECTION 8: Maximum Peak Output Power.....</b>	<b>15</b>
<b>SECTION 9: Peak Power Density.....</b>	<b>15</b>
<b>APPENDIX 1: Photographs of test setup.....</b>	<b>16</b>
Conducted Emission.....	16
Spurious Emission (Radiated).....	17
Worst Case Position.....	18
<b>APPENDIX 2: Data of EMI test.....</b>	<b>21</b>
Conducted Emission.....	21
6dB Bandwidth.....	55
Maximum Peak Output Power.....	58
Radiated Spurious Emission (below 1GHz).....	62
Radiated Spurious Emission (above 1GHz).....	90
Conducted Spurious Emission.....	126
Conducted emission Band Edge compliance.....	133
Power Density.....	134
99%Occupied Bandwidth.....	137
<b>APPENDIX 3:Test instruments.....</b>	<b>139</b>

## **SECTION 1: Customer information**

Company Name	Sony Computer Entertainment Inc.
Brand Name	SONY
Address	2-6-21 Minamiaoyama, Minato-ku, Tokyo, 107-0062, Japan
Telephone Number	+81-3-6438-8023
Facsimile Number	+81-3-6438-8642
Contact Person	Akiko Tsukada

## **SECTION 2: Equipment under test (E.U.T.)**

### **2.1 Identification of E.U.T.**

Type of Equipment	PLAYSTATION®3
Model No	CECHL01
Serial No	1040132: Used for Antenna Terminal Conducted tests 1040134: Used for Conducted emission and Radiated spurious emission test (Power Supply: Delta) 1080015: Used for Conducted emission and Radiated spurious emission test (Power Supply: SONY)
Rating	AC 120V, 60Hz
Country of Manufacture	JAPAN/CHINA
Receipt Date of Sample	June 16, 2008
Condition of EUT	Engineering prototype (Not for Sale: This sample is equivalent to mass-produced items.)
Modification of EUT	No modification by the test lab.

---

**UL Japan, Inc.**

**Head Office EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

**2.2 Product Description**

Model: CECHL01, referred to as the EUT in this report, is a PLAYSTATION®3.

The EUT contains Bluetooth (Ver. 2.0+EDR) module and IEEE802.11b/g WLAN module. Those modules do not transmit simultaneously.

Clock Frequencies are CPU: 3.2GHz(CPU), 66MHz(ATA), 133MHz(ATA), 33MHz(PCI), and 750MHz(SATA1).

**Bluetooth (Ver. 2.0+EDR)**

Equipment Type	Transceiver
Frequency of Operation	2402-2480MHz
Type of Modulation	FHSS (GFSK, $\pi/4$ -DQPSK, 8DPSK)
Bandwidth & Channel spacing	1MHz & 1MHz
Power Supply (inner)	DC3.3V
Antenna Type	PWB Pattern Antenna
Antenna Gain	3.33 dBi (max)
Antenna Connector Type	N/A

For Bluetooth part, please see UL Japan, Inc. Test Report Number: 28KE0107-HO-01-B.

**IEEE802.11b/g WLAN**

Equipment Type	Transceiver	
Frequency of Operation	2412-2462MHz	
Type of Modulation	DSSS/OFDM	
Bandwidth & Channel spacing	20MHz & 5MHz	
Power Supply (inner)	DC 3.3V/DC1.3V	
Antenna Type	ANT 0: PWB Pattern Antenna	ANT 1: Reverse F Antenna
Antenna Gain	ANT 0: 2.01 dBi (max)	ANT 1: 1.48 dBi (max)
Antenna Connector Type	ANT 0: N/A	ANT 1: U.FL

**UL Japan, Inc.**

**Head Office EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

### **SECTION 3: Test specification, procedures & results**

#### **3.1 Test Specification**

Test Specification : FCC Part15 Subpart C: 2008, final revised on May 19, 2008

Title : FCC 47CFR Part15 Radio Frequency Device Subpart C Intentional Radiators  
Section 15.207 Conducted limits  
Section 15.247 Operation within the bands 902-928MHz,  
2400-2483.5MHz, and 5725-5850MHz

#### **FCC 15.31 (e)**

This EUT provides stable voltage(DC3.3V / DC1.3V) constantly to RF Module regardless of input voltage. Therefore, this EUT complies with the requirement.

#### **FCC Part 15.203 Antenna requirement**

It is impossible for end users to replace the antenna, because the antenna is mounted inside of the EUT. Therefore, the equipment complies with the antenna requirement of Section 15.203.

---

**UL Japan, Inc.**

**Head Office EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

3.2 Procedures and results

No.	Item	Test Procedure	Specification	Remarks	Deviation	Worst margin	Results
1	Conducted emission	FCC: ANSI C63.4:2003 7. AC powerline conducted emission measurements ----- IC: RSS-Gen 7.2.2	FCC: Section 15.207 ----- IC: RSS-Gen 7.2.2	Conducted	N/A	[QP] 16.4dB, 11.00675 MHz, N, ANT 0, 11b/g, Rx, Ch: Mid, Power Supply: Delta, 11.00905MHz, N, ANT 0, 11g, Tx, Ch: Mid, Power Supply: Delta [AV] 8.7dB, 0.55692MHz, N ANT 0, 11b/g, Rx, Ch: Mid, Power Supply: Delta	Complied
2	6dB Bandwidth	FCC: "Guidance on Measurement of Digital Transmission Systems Operating under Section15.247" ----- IC: RSS-Gen 4.6.2	FCC: Section 15.247(a)(2) ----- IC: RSS-210 A8.2(a)	Conducted	N/A	See data.	Complied
3	Maximum Peak Output Power	FCC: "Guidance on Measurement of Digital Transmission Systems Operating under Section15.247" ----- IC: RSS-Gen 4.8	FCC: Section 15.247(b)(3) ----- IC: RSS-210 A8.4(4)	Conducted	N/A		Complied
4	Restricted Band Edges	FCC: "Guidance on Measurement of Digital Transmission Systems Operating under Section15.247" ----- IC: -	FCC: Section 15.247 (d) ----- IC: RSS-210 A8.5	Conducted/ Radiated	N/A		Complied
5	Power Density	FCC: "Guidance on Measurement of Digital Transmission Systems Operating under Section15.247" ----- IC: -	FCC: Section 15.247 (e) ----- IC: RSS-210 A8.2(b)	Conducted	N/A		Complied
6	Spurious Emission	FCC: "Guidance on Measurement of Digital Transmission Systems Operating under Section15.247" ----- IC: RSS-Gen 4.9 RSS-Gen 4.10	FCC: Section15.247(d) ----- IC: RSS-210 A8.5 RSS-Gen 7.2.1 and 7.2.3	Conducted/ Radiated	N/A		[Tx] 4.2dB 215.998MHz, QP, Hori, 11b, Ch: Low, ANT 1, Power Supply: Delta [Rx] 6.4dB 215.997MHz, QP, Hori, 11b/g, Ch: Mid, ANT 0, Power Supply: SONY

Note: UL Japan, Inc.'s EMI Work Procedures No.QPM05 and QPM15.

\*These tests were performed without any deviations from test procedure except for additions or exclusions.

\* In case any questions arise about test procedure, ANSI C63.4: 2003 is also referred.

### 3.3 Addition to standards

No.	Item	Test Procedure	Specification	Remarks	Deviation	Worst margin	Results
1	99% Occupied Band Width	IC: RSS-Gen 4.6.1	IC: RSS-Gen 4.6.1	Conducted	N/A	N/A	N/A

### 3.4 Uncertainty

#### EMI

The following uncertainties have been calculated to provide a confidence level of 95% using a coverage factor k=2.

Test room	Conducted emission	Radiated emission (10m*)				Radiated emission (3m*)			Radiated emission (3m*)	
	150kHz-30MHz	9kHz-30MHz	30MHz-300MHz	300MHz-1GHz	9kHz-30MHz	30MHz-300MHz	300MHz-1GHz	1GHz-18GHz	18GHz-40GHz	
No.1 semi-anechoic chamber (±)	3.7dB	3.1dB	4.4dB	4.2dB	3.2dB	3.8dB	3.9dB	5.9dB	6.1dB	
No.2 semi-anechoic chamber (±)	3.7dB	-	-	-	3.2dB	4.4dB	4.0dB	5.9dB	6.1dB	
No.3 semi-anechoic chamber (±)	3.7dB	-	-	-	3.2dB	4.6dB	4.0dB	5.9dB	6.1dB	
No.4 semi-anechoic chamber (±)	3.7dB	-	-	-	3.2dB	3.9dB	3.9dB	5.9dB	6.1dB	

\*10m/3m = Measurement distance

#### Conducted emission test

The data listed in this test report has enough margin, more than the site margin.

#### Radiated emission test(3m)

The data listed in this test report has enough margin, more than the site margin.

#### Other test except Conducted Emission and Spurious Emission (Radiated)

The measurement uncertainty for this test is 3.0dB.

**UL Japan, Inc.**

**Head Office EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

### 3.5 Test Location

UL Japan, Inc. Head Office EMC Lab. \*NVLAP Lab. code: 200572-0  
4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN  
Telephone : +81 596 24 8116 Facsimile : +81 596 24 8124

	FCC Registration Number	IC Registration Number	Width x Depth x Height (m)	Size of reference ground plane (m) / horizontal conducting plane	Other rooms
No.1 semi-anechoic chamber	313583	2973C-1	19.2 x 11.2 x 7.7m	7.0 x 6.0m	No.1 Power source room
No.2 semi-anechoic chamber	655103	2973C-2	7.5 x 5.8 x 5.2m	4.0 x 4.0m	-
No.3 semi-anechoic chamber	148738	2973C-3	12.0 x 8.5 x 5.9m	6.8 x 5.75m	No.3 Preparation room
No.3 shielded room	-	-	4.0 x 6.0 x 2.7m	N/A	-
No.4 semi-anechoic chamber	134570	2973C-4	12.0 x 8.5 x 5.9m	6.8 x 5.75m	No.4 Preparation room
No.4 shielded room	-	-	4.0 x 6.0 x 2.7m	N/A	-
No.5 semi-anechoic chamber	-	-	6.0 x 6.0 x 3.9m	6.0 x 6.0m	-
No.6 shielded room	-	-	4.0 x 4.5 x 2.7m	4.75 x 5.4 m	-
No.6 measurement room	-	-	4.75 x 5.4 x 3.0m	4.75 x 4.15 m	-
No.7 shielded room	-	-	4.7 x 7.5 x 2.7m	4.7 x 7.5m	-
No.8 measurement room	-	-	3.1 x 5.0 x 2.7m	N/A	-
No.9 measurement room	-	-	8.0 x 4.5 x 2.8m	2.0 x 2.0m	-
No.10 measurement room	-	-	2.6 x 2.8 x 2.5m	2.4 x 2.4m	-
No.11 measurement room	-	-	3.1 x 3.4 x 3.0m	2.4 x 3.4m	-

\* Size of vertical conducting plane (for Conducted Emission test) : 2.0 x 2.0m for No.1, No.2, No.3, and No.4 semi-anechoic chambers and No.3 and No.4 shielded rooms.

### 3.6 Test set up, Test instruments and Data of EMI

Refer to APPENDIX 1 to 3.

**SECTION 4: Operation of E.U.T. during testing**

**4.1 Operating Mode(s)**

The mode used for test : [IEEE 802.11b / IEEE 802.11g : DSSS / OFDM]

Test	Mode	Tested frequency	Tested antenna
Conducted Emission Spurious Emission (Radiated)	IEEE802.11b Transmitting (Tx), 11Mbps *1)	2412MHz(L)	ANT 0
	IEEE802.11g Transmitting (Tx), 54Mbps *1)	2437MHz(M) 2462MHz(H)	ANT 1
	----- IEEE802.11b/g Receiving (Rx)	2437MHz(M)	ANT 0 ANT 1
6dB Bandwidth Power Density 99% Occupied Bandwidth	IEEE802.11b Transmitting (Tx), 2Mbps *1)	2412MHz(L)	ANT 0
	IEEE802.11g Transmitting (Tx), 36Mbps *1)	2437MHz(M) 2462MHz(H)	
Maximum Peak Output Power	IEEE802.11b Transmitting (Tx), 2Mbps *1)	2412MHz(L)	ANT 0
	IEEE802.11g Transmitting (Tx), 36Mbps *1)	2437MHz(M) 2462MHz(H)	ANT 1
Spurious Emission (Conducted)	IEEE802.11b Transmitting (Tx), 2Mbps *1)	2412MHz(L)	ANT 0
	IEEE802.11g Transmitting (Tx), 36Mbps *1)	2437MHz(M) 2462MHz(H)	
	----- IEEE802.11b/g Receiving (Rx)	2437MHz(M)	ANT 0
Restricted Band Edge (Radiated)	IEEE802.11b Transmitting (Tx), 11Mbps *1)	2412MHz(L)	ANT 0
	IEEE802.11g Transmitting (Tx), 54Mbps *1)	2462MHz(H)	ANT 1
Restricted Band Edge (Conducted)	IEEE802.11b Transmitting (Tx), 2Mbps *1) IEEE802.11g Transmitting (Tx), 36Mbps *1)	2412MHz(L) 2462MHz(H)	ANT 0

\*Transmitting duty was 100% on all tests.

\*As a result of preliminary check for two antennas (ANT 0 and ANT 1), the formal test was performed as above-mentioned table.

\*1) The transmitting data shall be scrambled with the following scramblers and it was transmitted continuously.

[11b]

2Mbps: IEEE Std 802.11(1999) Section 15.2.4

11Mbps: IEEE Std 802.11b(1999) Section 18.2.4

[11g]

36Mbps/54Mbps: IEEE Std 802.11a(1999) Section 17.3.5.4

**Preliminary check result (Worst antenna & Data rate):**

Conducted Emission & Radiated Emission

11b: ANT 0 / ANT 1, 11Mbps

11g: ANT 0 / ANT 1, 54Mbps

Antenna Terminal Conducted test

11b: ANT 0, 2Mbps

11g: ANT 0, 36Mbps

**UL Japan, Inc.**

**Head Office EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

## 4.2 Configuration and peripherals

**This page has been submitted for a separate exhibit.**

**This page has been submitted for a separate exhibit.**

## **SECTION 5: Conducted Emission**

### **Test Procedure and conditions**

EUT was placed on a wooden table of nominal size, 1.0m by 1.5m, raised 80cm above the conducting ground plane. The rear of tabletop was located 40cm to the vertical conducting plane. The rear of EUT, including peripherals aligned and flushed with rear of tabletop. All other surfaces of tabletop were at least 80cm from any other grounded conducting surface. EUT was located 80cm from a Line Impedance Stabilization Network (LISN)/ Artificial mains Network (AMN) and excess AC cable was bundled in center.

#### For the tests on EUT with other peripherals (as a whole system)

I/O cable and AC cables that were connected to the peripherals were bundled in center. They were folded back and forth forming a bundle 30cm to 40cm long and were hanged at a 40cm height to the ground plane. All unused 50ohm connectors of the LISN(AMN) were resistivity terminated in 50ohm when not connected to the measuring equipment.

The AC Mains Terminal Continuous disturbance Voltage has been measured with the EUT in a Semi Anechoic Chamber or a Measurement Room.

The EUT was connected to a LISN (AMN).

An overview sweep with peak detection has been performed.

**Detector** : quasi-peak and average detector (IF BW 9 kHz)  
**Measurement range** : 0.15-30MHz  
**Test data** : APPENDIX 2  
**Test result** : Pass

---

**UL Japan, Inc.**

**Head Office EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

**SECTION 6: Spurious Emission**

**[Conducted]**

**Test Procedure**

The Out of Band Emission was measured with a spectrum analyzer connected to the antenna port. It was measured based on "1. RF antenna conducted test" of "Guidance on Measurement of Digital Transmission Systems Operating under Section 15.247".

The following spectrum analyzer setting was used:

- RBW: 100kHz
- VBW: 300kHz
- Sweep: Auto
- Detector: Peak
- Trace: Max Hold

**Test data** : APPENDIX 2  
**Test result** : Pass

**[Radiated]**

**Test Procedure**

It was measured based on "2. Radiated emission test" of "Guidance on Measurement of Digital Transmission Systems Operating under Section 15.247".

EUT was placed on an urethane platform of nominal size, 1.0m by 1.5m, raised 80cm above the conducting ground plane. The Radiated Electric Field Strength intensity has been measured in a Semi Anechoic Chamber with a ground plane and at a distance of 3m (Below 10GHz) and 1m (Upper 10GHz).

The height of the measuring varied between 1 and 4m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity.

The measurements were performed for both vertical and horizontal antenna polarization with the Test Receiver, or the Spectrum Analyzer (in linear mode).

The test was made with the detector (RBW/VBW) in the following table.

When using Spectrum analyzer, the test was made with adjusting span to zero by using peak hold.

In any 100kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator confirmed 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on a radiated measurement.

**20dBc was applied to the frequency over the limit of FCC 15.209 / Table 2 of RSS-210 2.7 (IC) and outside the restricted band of FCC 15.205 / Table 1 of RSS-210 2.7 (IC).**

Frequency	Below 1GHz	Above 1GHz
Instrument used	Test Receiver	Spectrum Analyzer *1)
Detector	QP: BW 120kHz(T/R)	PK: RBW:1MHz/VBW: 1MHz
IF Bandwidth		AV: RBW:1MHz/VBW:10Hz 20dBc : RBW:100kHz/VBW:300kHz

\*1) The Spectrum Analyzer was used in 3dB resolution bandwidth.

- The carrier level and noise levels were confirmed at each position of X, Y axes of EUT to see the position of maximum noise, and the test was made at the position that has the maximum noise.

**Test data** : APPENDIX 2  
**Test result** : Pass

**UL Japan, Inc.**

**Head Office EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

## **SECTION 7: Bandwidth**

### **Test Procedure**

#### **6dB Bandwidth**

##### **Test Procedure**

The bandwidth was measured with a spectrum analyzer connected to the antenna port.

It was measured based on "Guidance on Measurement of Digital Transmission Systems Operating under Section 15.247".

The following spectrum analyzer setting was used:

- Span: 50MHz
- RBW: 100kHz
- VBW: 300kHz
- Sweep: Auto
- Detector: Peak
- Trace: Max Hold

**Test data** : APPENDIX 2  
**Test result** : Pass

#### **99% Occupied Bandwidth**

##### **Test Procedure**

The bandwidth was measured with a spectrum analyzer connected to the antenna port.

The following spectrum analyzer setting was used:

- Span: Enough width to display 20dB Bandwidth
- RBW: as close to 1% of the Span as is possible without being below 1%
- VBW: Three times of RBW
- Sweep: Auto
- Detector: Peak
- Trace: Max Hold

**Test data** : APPENDIX 2  
**Test result** : Pass

---

**UL Japan, Inc.**

**Head Office EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

## **SECTION 8: Maximum Peak Output Power**

### **Test Procedure**

The Maximum Peak Output Power was measured with a power meter (tested bandwidth: 50MHz) connected to the antenna port. It was measured based on "Power Output Option 1" of "Guidance on Measurement of Digital Transmission Systems Operating under Section15.247".

**Test data** : APPENDIX 2  
**Test result** : Pass

## **SECTION 9: Peak Power Density**

### **Test Procedure**

The Peak Power Density (=PSD) was measured with a spectrum analyzer connected to the antenna port. It was measured based on "PSD Option 1" of "Guidance on Measurement of Digital Transmission Systems Operating under Section15.247".

**Test data** : APPENDIX 2  
**Test result** : Pass

---

**UL Japan, Inc.**

**Head Office EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124