

## FCC PART 15C TEST REPORT FOR CERTIFICATION

On Behalf of

Sony Corporation

Brand Name	SONY
System Name	HOME AUDIO SYSTEM
System Model No.	CMT-SBT20
EUT Name	COMPACT DISC RECEIVER
EUT Model No.	HCD-SBT20

FCC ID: AK8CMTSBT20

Prepared for : Sony Corporation

1-7-1 Konan, Minato-ku, Tokyo 108-0075 Japan

Prepared By : Audix Technology (Shenzhen) Co., Ltd.  
No. 6, Ke Feng Rd., 52 Block,  
Shenzhen Science & Industrial Park,  
Nantou, Shenzhen, Guangdong, China

Tel: (0755) 26639496

Report Number : ACS-F15340

Date of Test : Dec.10~14, 2015

Date of Report : Jan.07, 2016

**TABLE OF CONTENTS**

<u>Description</u>	<u>Page</u>
<b>1. SUMMARY OF STANDARDS AND RESULTS.....</b>	<b>1-1</b>
1.1. Description of Standards and Results .....	1-1
<b>2. GENERAL INFORMATION .....</b>	<b>2-1</b>
2.1. Description of Device (EUT).....	2-1
2.2. Tested Supporting System Details .....	2-2
2.3. Block Diagram of connection between EUT and simulators.....	2-2
2.4. Test information.....	2-2
2.5. Test Facility .....	2-3
2.6. Measurement Uncertainty (95% confidence levels, k=2).....	2-3
<b>3. POWER LINE CONDUCTED EMISSION TEST .....</b>	<b>3-1</b>
3.1. Test Equipments.....	3-1
3.2. Block Diagram of Test Setup.....	3-1
3.3. Power Line Conducted Emission Test Limits.....	3-1
3.4. Configuration of EUT on Test.....	3-2
3.5. Operating Condition of EUT .....	3-2
3.6. Test Procedure .....	3-2
3.7. Power Line Conducted Emission Test Results .....	3-2
<b>4. RADIATED EMISSION MEASUREMENT.....</b>	<b>4-1</b>
4.1. Test Equipment .....	4-1
4.2. Block Diagram of Test Setup.....	4-2
4.3. Radiated Emission Limit Standard: .....	4-3
4.4. EUT Configuration on Test .....	4-3
4.5. Operating Condition of EUT .....	4-3
4.6. Test Procedure .....	4-3
4.7. Radiated Emission Test Results.....	4-4
<b>5. CONDUCTED SPURIOUS EMISSIONS.....</b>	<b>5-1</b>
5.1. Test Equipment .....	5-1
5.2. Limit.....	5-1
5.3. Test Procedure .....	5-1
5.4. Test result.....	5-1
<b>6. 6dB BANDWIDTH TEST .....</b>	<b>6-1</b>
6.1. Test Equipment .....	6-1
6.2. Limit.....	6-1
6.3. Test Procedure .....	6-1
6.4. Test Results.....	6-1
<b>7. MAXIMUM PEAK OUTPUT POWER TEST .....</b>	<b>7-1</b>
7.1. Test Equipment .....	7-1
7.2. Limit.....	7-1
7.3. Test Procedure .....	7-1
7.4. Test Results.....	7-1
<b>8. BAND EDGE COMPLIANCE TEST .....</b>	<b>8-1</b>
8.1. Test Equipment .....	8-1
8.2. Limit.....	8-1
8.3. Test Produce.....	8-1
8.4. Test Results .....	8-1
<b>9. POWER SPECTRAL DENSITY TEST .....</b>	<b>9-1</b>

9.1.	Test Equipment .....	9-1
9.2.	Limit.....	9-1
9.3.	Test Procedure .....	9-1
9.4.	Test Results.....	9-1
<b>10.</b>	<b>ANTENNA REQUIREMENT .....</b>	<b>10-1</b>
10.1.	Standard Applicable.....	10-1
10.2.	Antenna Connected Construction .....	10-1
<b>11.</b>	<b>DEVIATION TO TEST SPECIFICATIONS.....</b>	<b>11-1</b>
<b>12.</b>	<b>HOTOGRAPH OF TEST.....</b>	<b>12-1</b>
12.1.	Photos of Power Line Conducted Emission Test.....	12-1
12.2.	Photos of Radiated Emission Test .....	12-2
<b>13.</b>	<b>PHOTOGRAPHS OF EUT .....</b>	<b>13-1</b>

TEST REPORT CERTIFICATION

Applicant : Sony Corporation  
 Manufacture : Sony Corporation  
 EUT Description : COMPACT DISC RECEIVER  
 FCC ID : AK8CMTSBT20

Brand Name	SONY
System Name	HOME AUDIO SYSTEM
System Model No.	CMT-SBT20
EUT Name	COMPACT DISC RECEIVER
EUT Model No.	HCD-SBT20

(A) Serial No. : N/A  
 (B) Test Voltage : AC 120V/60Hz

Tested for comply with:

FCC CFR 47 Part 15 Subpart C: 2014  
 Test procedure used: ANSI C63.10: 2013;  
 KDB558074 D01 v03r03

The device described above is tested by AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. to confirm comply with all the FCC Part 15 Subpart C requirements. The test results are contained in this test report and AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. is assumed full responsibility for the accuracy and completeness of these tests. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements. This report contains data that are not covered by the NVLAP accreditation.

This Report is made under FCC Part 2.1075. No modifications were required during testing to bring this product into compliance.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of AUDIX TECHNOLOGY (SHENZHEN) CO., LTD.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

Date of Test : Dec.10~14, 2015 Report of date: Jan.07, 2016

Prepared by : Cindy Zhu Reviewed by : Sunny Lu  
 Cindy Zhu / Assistant Sunny Lu / Assistant Manager

Stamp only for EMC Dept. Report  
 Signature: David Jin

Approved & Authorized Signer : David Jin  
 David Jin / Manager

## 1. SUMMARY OF STANDARDS AND RESULTS

### 1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below.

EMISSION		
Description of Test Item	Standard	Results
Power Line Conducted Emission Test	FCC Part 15: 15.207 ANSI C63.10 :2013	PASS
Radiated Emission Test	FCC Part 15: 15.209 FCC Part 15: 15.247(d) ANSI C63.10 : 2013	PASS
Conducted Spurious Emissions	FCC Part 15: 15.247(a)(1) ANSI C63.10 : 2013	PASS
Carrier Frequency Separation Test	FCC Part 15: 15.247(a)(1) ANSI C63.10 : 2013	PASS
6dB Bandwidth Test	FCC Part 15: 15.215 ANSI C63.10 : 2013	PASS
Maximum Peak Output Power Test	FCC Part 15: 15.247(b)(1) ANSI C63.10 : 2013	PASS
Band Edge Compliance Test	FCC Part 15: 15.247(d) ANSI C63.10 : 2013	PASS
Power Spectral Density Test	FCC Part 15: 15.247(d) ANSI C63.10 : 2013	PASS

## 2. GENERAL INFORMATION

### 2.1. Description of Device (EUT)

Product Name & Model Number	Brand Name	SONY
	System Name	HOME AUDIO SYSTEM
	System Model No.	CMT-SBT20
	EUT Name	COMPACT DISC RECEIVER
	EUT Model No.	HCD-SBT20

Remark:


The device covered in this report was HOME AUDIO SYSTEM (CMT-SBT20), It consists of COMPACT DISC RECEIVER (HCD-SBT20) and SPEAKER SYSTEM (SS-SBT20).

FCC ID	: AK8CMTSBT20
Radio	: Bluetooth V3.0+EDR Bluetooth V4.0 NFC Rx
Operation Frequency	: 2402-2480MHz for Bluetooth 13.56MHz for NFC
Channel Number	: Bluetooth V3.0+EDR: 79 channels Bluetooth V4.0: 40 channels
Modulation Technology	: Bluetooth V3.0+EDR: GFSK, $\pi/4$ DQPSK, 8DPSK; Bluetooth V4.0: GFSK NFC: ASK
Antenna Assembly Gain	: Integrated PCB Antenna, 2.12dBi PK gain
Applicant	: Sony Corporation 1-7-1 Konan, Minato-ku, Tokyo 108-0075 Japan
Manufacturer	: Sony Corporation 1-7-1 Konan, Minato-ku, Tokyo 108-0075 Japan
Remote	: Manufacture: SONY; Model:RM-AMU212
FM Antenna Cable	: Unshielded, Detachable 120cm
Date of Test	: Dec.10~14, 2015
Date of Receipt	: Dec.08, 2015
Remark:	: This report only for Bluetooth V4.0+EDR.

2.2. Tested Supporting System Details

No.	Description	ACS No.	Manufacturer	Model	Serial Number
1.	Notebook	---	DELL	PP09S	---
		Power Cable: Unshielded, Detectable, 1.8m Power Adaptor:Manufacturer:DELL;Model:LA65NS1-00;			
2.	iPod	ACS-EMC-IP01	APPLE	A1199	YM706MLDVQ5
		Data Cable: Shielded, Detachable, 1.0m			
3.	USB Disk	---	---	Kingston 4G mini memory	---

2.3. Block Diagram of connection between EUT and simulators



**(EUT: COMPACT DISC RECEIVER)**

2.4. Test information

A Special Test Software was used to control EUT work in Continuous TX mode (GFSK modulation), and select test channel.

Tested mode, channel, and data rate information			
Mode	data rate (Mbps)	Channel	Frequency (MHz)
Tx Mode GFSK modulation	3	Low :CH 0	2402
	3	Middle: CH19	2440
	3	High: CH39	2480

2.5. Test Facility

Site Description

Name of Firm	:	Audix Technology (Shenzhen) Co., Ltd. No. 6, Ke Feng Rd., 52 Block, Shenzhen Science & Industrial Park, Nantou, Shenzhen, Guangdong, China
3m Anechoic Chamber	:	Certificated by FCC, USA Registration Number: 90454 Valid Date: Dec.30,2017
3m & 10m Anechoic Chamber	:	Certificated by FCC, USA Registration Number: 794232 Valid Date: Jul.12, 2016
EMC Lab.	:	Certificated by Industry Canada Registration Number: IC 5183A-1 Valid Date: May.14, 2017
	:	Certificated by DAkkS, Germany Registration No: D-PL-12151-01-00 Valid Date: Dec.15, 2016
	:	Accredited by NVLAP, USA NVLAP Code: 200372-0 Valid Date: Mar.31, 2016

2.6. Measurement Uncertainty (95% confidence levels, k=2)


Test Item	Uncertainty
Uncertainty for Conduction emission test in No. 1 Conduction	3.4 dB(150KHz to 30MHz)
Uncertainty for Radiation Emission test in 3m chamber	2.6 dB(30~200MHz, Polarization: H)
	2.6 dB(30~200MHz, Polarization: V)
	3.0 dB(200M~1GHz, Polarization: H)
	2.8 dB(200M~1GHz, Polarization: V)
Uncertainty for Radiation Emission test in 3m chamber (1GHz-18GHz)	6.3 dB (1~6GHz, Distance: 3m)
	5.7 dB (6~18GHz, Distance: 3m)
Uncertainty for Radiated Spurious Emission test in RF chamber	3.6 dB
Uncertainty for Conduction Spurious emission test	2.0 dB
Uncertainty for Output power test	0.8 dB
Uncertainty for Bandwidth test	83 kHz
Uncertainty for DC power test	0.1 %
Uncertainty for test site temperature and humidity	0.6
	3%

### 3. POWER LINE CONDUCTED EMISSION TEST

#### 3.1. Test Equipments

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	1# Shielding Room	AUDIX	N/A	N/A	Apr.17,15	1 Year
2.	Test Receiver	Rohde & Schwarz	ESCI	100842	Apr.28,15	1 Year
3.	L.I.S.N.#1	Rohde & Schwarz	ESH2-Z5	100429	Oct.18,15	1 Year
4.	L.I.S.N.#2	Kyoritsu	K NW-403D	8-1750-2	Apr.28,15	1 Year
5.	Terminator	Hubersuhner	50Ω	No.1	Apr.28,15	1 Year
6.	Terminator	Hubersuhner	50Ω	No.2	Apr.28,15	1 Year
7.	RF Cable	MIYAZAKI	3D-2W	No.1	Apr.28,15	1Year
8.	Coaxial Switch	Anritsu	MP59B	6200766906	Apr.28,15	1 Year
9.	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	101838	Oct.17,15	1 Year
10.	Test Software	AUDIX	E3	6.100913a	N/A	N/A

#### 3.2. Block Diagram of Test Setup



▣ :50Ω Terminator

#### 3.3. Power Line Conducted Emission Test Limits

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. \* Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

### 3.4. Configuration of EUT on Test

The following equipment are installed on Power Line Conducted Emission Test to meet the commission requirement and operating regulations in a manner which tends to maximize its emission characteristics in a normal application.

#### 3.4.1. COMPACT DISC RECEIVER (EUT)

Model Number : HCD-SBT20

Serial Number : N/A

3.4.2. Support Equipment: As Tested Supporting System Details, in Section 2.2.

### 3.5. Operating Condition of EUT

3.5.1. Setup the EUT and simulator as shown as Section 3.2.

3.5.2. Turn on the power of all equipments.

3.5.3. PC run test software to control EUT work in BT 4.0 Tx mode.

### 3.6. Test Procedure


The EUT was placed on a non-metallic table, 80cm above the ground plane. The EUT Power Via PC connected to the power mains through a line impedance stabilization network (L.I.S.N. 1#). This provides a 50 ohm coupling impedance for the EUT (Please refer the block diagram of the test setup and photographs). The AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10: 2013 on Conducted Emission Test.

The bandwidth of test receiver (R & S ESCI) is set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

### 3.7. Power Line Conducted Emission Test Results


**PASS.** (All emissions not reported below are too low against the prescribed limits.)



Site no :1# Conduction Data No :4  
 Dis./Lisn :2015 KNW-242C VA  
 Limit :FCC PART 15 C  
 Env./Ins. :22.1\*C/51% Engineer :Alvis-Wu  
 EUT :COMPACT DISC RECEIVER M/N:HCD-SBT20  
 Power Rating :AC 120V/60Hz  
 Test Mode :TX Mode

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.186	0.49	9.95	32.70	43.14	54.21	11.07	Average
2	0.186	0.49	9.95	44.80	55.24	64.21	8.97	QP
3	0.230	0.49	9.95	27.50	37.94	52.45	14.51	Average
4	0.230	0.49	9.95	39.20	49.64	62.45	12.81	QP
5	0.274	0.48	9.94	25.90	36.32	51.00	14.68	Average
6	0.274	0.48	9.94	35.90	46.32	61.00	14.68	QP
7	0.369	0.46	9.94	23.40	33.80	48.52	14.72	Average
8	0.369	0.46	9.94	30.40	40.80	58.52	17.72	QP
9	3.345	0.55	9.98	22.21	32.74	46.00	13.26	Average
10	3.345	0.55	9.98	29.51	40.04	56.00	15.96	QP
11	3.860	0.60	9.99	23.10	33.69	46.00	12.31	Average
12	3.860	0.60	9.99	29.30	39.89	56.00	16.11	QP

Remarks: 1.Emission Level=LISN Factor+Cable Loss(Include 10dB pulse limit)+Reading.  
 2.If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.



Site no :1# Conduction Data No :3  
 Dis./Lisn :2015 KNW-242C VB  
 Limit :FCC PART 15 C  
 Env./Ins. :22.1\*C/51% Engineer :Alvis-Wu  
 EUT :COMPACT DISC RECEIVER M/N:HCD-SBT20  
 Power Rating :AC 120V/60Hz  
 Test Mode :TX Mode

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.181	0.41	9.95	34.30	44.66	54.44	9.78	Average
2	0.181	0.41	9.95	46.10	56.46	64.44	7.98	QP
3	0.225	0.41	9.95	33.20	43.56	52.63	9.07	Average
4	0.225	0.41	9.95	40.80	51.16	62.63	11.47	QP
5	0.270	0.41	9.94	26.10	36.45	51.12	14.67	Average
6	0.270	0.41	9.94	35.60	45.95	61.12	15.17	QP
7	0.357	0.40	9.94	22.10	32.44	48.80	16.36	Average
8	0.357	0.40	9.94	29.70	40.04	58.80	18.76	QP
9	3.340	0.30	9.98	22.20	32.48	46.00	13.52	Average
10	3.340	0.30	9.98	30.10	40.38	56.00	15.62	QP
11	3.920	0.31	9.99	21.60	31.90	46.00	14.10	Average
12	3.920	0.31	9.99	27.40	37.70	56.00	18.30	QP

Remarks: 1.Emission Level=LISN Factor+Cable Loss(Include 10dB pulse limit)+Reading.  
 2.If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.

## 4. RADIATED EMISSION MEASUREMENT

### 4.1. Test Equipment


Frequency range: 30~1000MHz

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	3#Chamber	AUDIX	N/A	N/A	Mar.28,15	1 Year
2.	EMI Spectrum	Agilent	E4407B	MY41440292	Apr.28,15	1 Year
3.	Test Receiver	Rohde & Schwarz	ESVS10	834468/011	Apr.28,15	1 Year
4.	Amplifier	HP	8447D	2648A04738	Apr.28,15	1 Year
5.	Trilog-Broadband Antenna	SCHWARZBECK	VULB 9168	9168-493	May.06,15	1 Year
6.	RF Cable	MIYAZAKI	CFD400-N W(3.5M)	No.3	Apr.28,15	1 Year
7.	RF Cable	MIYAZAKI	CFD400-L W(22M)	No.7	Apr.28,15	1 Year
8.	Coaxial Switch	Anritsu	MP59B	6201397222	Apr.28,15	1 Year
9.	Test Software	AUDIX	E3	6.2009-5-21a(n)	N/A	N/A


Frequency range: above 1000MHz

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analyzer	Agilent	E4446A	US44300459	Apr.28,15	1 Year
2.	Horn Antenna	ETC	MCTD 1209	DRH15F03007	Feb.03,15	1 Year
3.	Amplifier	Agilent	8449B	3008A02495	Apr.28,15	1 Year
4.	RF Cable	Hubersuhner	SUCOFLEX106	77977/6	Apr.28,15	1 Year
5.	Horn Antenna	ETS	3116	00060088	Nov.18.15	1 Year
6.	Test Software	AUDIX	E3	6.2009-5-21a(n)	N/A	N/A

4.2. Block Diagram of Test Setup  
For frequency range 30MHz-1000MHz



For frequency range 1GHz-25GHz



4.3. Radiated Emission Limit Standard:

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000MHz	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	

Remarks : (1) Emission level dBμV = 20 log Emission level μV/m

(2) The smaller limit shall apply at the cross point between two frequency bands.

(3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

(4) The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

4.4. EUT Configuration on Test

The following equipment are installed on Radiated Emission Test to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

4.4.1. COMPACT DISC RECEIVER (EUT)

Model Number : HCD-SBT20  
Serial Number : N/A

4.5. Operating Condition of EUT

4.5.1. Setup the EUT and simulator as shown as Section 4.2.

4.5.2. Turn on the power of all equipments.

4.5.3. Let EUT work in BT 4.0 Tx mode.

4.6. Test Procedure

EUT and its simulators are placed on a turn table, which is 0.8 meter high above ground for frequency 30MHz~1000MHz, 1.5 meter high above ground for frequency above 1GHz and put the absorbing with 2.4m(L)\*2.4m(W)\*0.3m(H) on the ground . The turn table can rotate 360 degrees to determine the position of the maximum emission level. Power on the EUT and let it working in test mode, then test it.EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna for frequency 30MHz~1000MHz, and the Horn antenna is used as receiving antenna for frequency above 1GHz. Both horizontal and vertical polarization of the antenna is set on Test. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.10-2013 on radiated emission Test.

This test was performed with EUT in X, Y, Z position, and the worse case was found when EUT in X position as the test photo indicated.

The bandwidth of the EMI test receiver (R&S ESVS10) is set at 120kHz for frequency range from 30MHz to 1000 MHz.

The bandwidth of the Spectrum’s RBW is set at 1MHz and VBW is set at 3MHz for peak emissions measurement above 1GHz.

This device is pulse Modulated, a duty cycle factor was used to calculated average level based measured peak level.

The frequency range from 30MHz to 10th harmonic (25GHz) are checked. and no any emissions were found from 18GHz to 25 GHz, So the radiated emissions from 18GHz to 25GHz were not record.


#### 4.7. Radiated Emission Test Results



**PASS.**

All the emissions from 30MHz to 25GHz were comply with the 15.209 Limit.


Note: The duty cycle factor for calculate average level is 2.864 dB, and average limit is 20dB below peak limit, so if peak measured level comply with average limit, the average level was deemed to comply with average limit

$$\text{Duty cycle factor} = 20\log (1/\text{duty cycle}) = 2.864\text{dB}$$










Site no. : 3m Chamber Data no. : 3  
 Dis. / Ant. : 3m Ant. pol. : VERTICAL  
 Limit : FCC PART 15 C (3M)  
 Env. / Ins. : 24\*C/56% Engineer : Jolly\_Xu  
 EUT : COMPACT DISC RECEIVER M/N:HCD-SBT20  
 Power rating : AC 120V/60Hz  
 Test Mode : BT4.0 TX Mode


No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	70.740	0.00	0.93	32.79	33.72	40.00	6.28	QP
2	131.850	0.00	1.24	31.02	32.26	43.50	11.24	QP
3	136.700	0.00	1.27	31.77	33.04	43.50	10.46	QP
4	163.860	0.00	1.35	33.31	34.66	43.50	8.84	QP
5	175.500	0.00	1.40	30.49	31.89	43.50	11.61	QP
6	187.140	0.00	1.46	28.90	30.36	43.50	13.14	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.

Frequency:1GHz~18GHz



Site no. : 3m Chamber Data no. : 35  
Dis. / Ant. : 3m 2015 MCTD1209 3007 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23.6°C/52.1%  
Engineer : Thomax\_Chen  
EUT : COMPACT DISC RECEIVER M/N:HCD-SBT20  
Power rating : AC 120V/60Hz  
Test Mode : GFSK 2402MHz Tx Mode




Site no. : 3m Chamber Data no. : 36  
 Dis. / Ant. : 3m 2015 MCTD1209 3007 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23.6°C/52.1%  
 Engineer : Thomax\_Chen  
 EUT : COMPACT DISC RECEIVER M/N:HCD-SBT20  
 Power rating : AC 120V/60Hz  
 Test Mode : GFSK 2402MHz Tx Mode


No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.000	27.80	7.32	36.62	96.21	94.71	74.00	-20.71	Peak
2	4804.000	32.30	9.46	35.54	50.11	56.33	74.00	17.67	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.

Frequency ( MHz )	Peak level ( dBuV/m )	Duty cycle factor (dB)	AV level (dBuV/m)	Limit(dBuV/m)	Conclusion
4804.000	56.33	2.864	53.466	54	Pass



Site no. : 3m Chamber Data no. : 37  
Dis. / Ant. : 3m 2015 MCTD1209 3007 Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23.6°C/52.1%  
Engineer : Thomax\_Chen  
EUT : COMPACT DISC RECEIVER M/N:HCD-SBT20  
Power rating : AC 120V/60Hz  
Test Mode : GFSK 2402MHz Tx Mode




Site no. : 3m Chamber Data no. : 38  
 Dis. / Ant. : 3m 2015 MCTD1209 3007 Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23.6°C/52.1%  
 Engineer : Thomax\_Chen  
 EUT : COMPACT DISC RECEIVER M/N:HCD-SBT20  
 Power rating : AC 120V/60Hz  
 Test Mode : GFSK 2402MHz Tx Mode


No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.000	27.80	7.32	36.62	97.56	96.06	74.00	-22.06	Peak
2	4804.000	32.30	9.46	35.54	50.82	56.22	74.00	16.96	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.

Frequency (MHz)	Peak level (dBuV/m)	Duty cycle factor (dB)	AV level (dBuV/m)	Limit(dBuV/m)	Conclusion
4804.000	56.22	2.864	53.356	54	Pass



Site no. : 3m Chamber Data no. : 39  
Dis. / Ant. : 3m 2015 MCTD1209 3007 Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23.6°C/52.1%  
Engineer : Thomax\_Chen  
EUT : COMPACT DISC RECEIVER M/N:HCD-SBT20  
Power rating : AC 120V/60Hz  
Test Mode : GFSK 2440MHz Tx Mode




Site no. : 3m Chamber Data no. : 40  
 Dis. / Ant. : 3m 2015 MCTD1209 3007 Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23.6°C/52.1%  
 Engineer : Thomax\_Chen  
 EUT : COMPACT DISC RECEIVER M/N:HCD-SBT20  
 Power rating : AC 120V/60Hz  
 Test Mode : GFSK 2440MHz Tx Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2440.000	27.88	7.39	36.60	99.83	98.50	74.00	-24.50	Peak
2	4880.000	32.22	9.49	35.51	50.06	56.26	74.00	17.74	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.

Frequency ( MHz )	Peak level ( dBuV/m )	Duty cycle factor (dB)	AV level (dBuV/m)	Limit(dBuV/m)	Conclusion
4880.000	56.26	2.864	53.396	54	Pass



Site no. : 3m Chamber Data no. : 41  
Dis. / Ant. : 3m 2015 MCTD1209 3007 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23.6°C/52.1%  
Engineer : Thomax\_Chen  
EUT : COMPACT DISC RECEIVER M/N:HCD-SBT20  
Power rating : AC 120V/60Hz  
Test Mode : GFSK 2440MHz Tx Mode




Site no. : 3m Chamber Data no. : 42  
 Dis. / Ant. : 3m 2015 MCTD1209 3007 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23.6°C/52.1%  
 Engineer : Thomax\_Chen  
 EUT : COMPACT DISC RECEIVER M/N:HCD-SBT20  
 Power rating : AC 120V/60Hz  
 Test Mode : GFSK 2440MHz Tx Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2440.000	27.88	7.39	36.60	96.24	94.91	74.00	-20.91	Peak
2	4880.000	32.22	9.49	35.51	51.04	56.32	74.00	16.76	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.

Frequency (MHz)	Peak level (dBuV/m)	Duty cycle factor (dB)	AV level (dBuV/m)	Limit(dBuV/m)	Conclusion
4880.000	56.32	2.864	53.456	54	Pass



Site no. : 3m Chamber Data no. : 43  
Dis. / Ant. : 3m 2015 MCTD1209 3007 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23.6°C/52.1%  
Engineer : Thomax\_Chen  
EUT : COMPACT DISC RECEIVER M/N:HCD-SBT20  
Power rating : AC 120V/60Hz  
Test Mode : GFSK 2480MHz Tx Mode




Site no. : 3m Chamber Data no. : 44  
 Dis. / Ant. : 3m 2015 MCTD1209 3007 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23.6°C/52.1%  
 Engineer : Thomax\_Chen  
 EUT : COMPACT DISC RECEIVER M/N:HCD-SBT20  
 Power rating : AC 120V/60Hz  
 Test Mode : GFSK 2480MHz Tx Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.000	27.96	7.47	36.59	96.72	95.56	74.00	-21.56	Peak
2	4960.000	32.14	9.52	35.47	50.15	56.34	74.00	17.66	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.

Frequency ( MHz )	Peak level ( dBuV/m )	Duty cycle factor (dB)	AV level (dBuV/m)	Limit(dBuV/m)	Conclusion
4960.000	56.34	2.864	53.476	54	Pass



Site no. : 3m Chamber Data no. : 45  
Dis. / Ant. : 3m 2015 MCTD1209 3007 Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23.6°C/52.1%  
Engineer : Thomax\_Chen  
EUT : COMPACT DISC RECEIVER M/N:HCD-SBT20  
Power rating : AC 120V/60Hz  
Test Mode : GFSK 2480MHz Tx Mode



Site no. : 3m Chamber Data no. : 46  
 Dis. / Ant. : 3m 2015 MCTD1209 3007 Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23.6°C/52.1%  
 Engineer : Thomax\_Chen  
 EUT : COMPACT DISC RECEIVER M/N:HCD-SBT20  
 Power rating : AC 120V/60Hz  
 Test Mode : GFSK 2480MHz Tx Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.000	27.96	7.47	36.59	96.64	95.48	74.00	-21.48	Peak
2	4960.000	32.14	9.52	35.47	49.90	56.09	74.00	17.91	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.

Frequency ( MHz )	Peak level ( dBuV/m )	Duty cycle factor (dB)	AV level (dBuV/m)	Limit(dBuV/m)	Conclusion
4960.000	56.09	2.864	53.226	54	Pass

## 5. CONDUCTED SPURIOUS EMISSIONS

### 5.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum	Agilent	N9030A	MY51380221	Oct.18,15	1Year
2.	Attenuator (20dB)	Agilent	8491B	MY39262165	Apr.28,15	1 Year
3.	RF Cable	Marvelous Microwave Inc	SFL402105FLEX	NO.1	Oct.17,15	1 Year

### 5.2. Limit

In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

### 5.3. Test Procedure


The transmitter output was connected to a spectrum analyzer, The resolution bandwidth is set to 100 kHz, The video bandwidth is set to 300 kHz and measure all the emissions With peak detector.

### 5.4. Test result


**PASS** (The testing data was attached in the next pages.)

GFSK


2402MHz(30MHz-1GHz)




2402MHz(2.31GHz-2.405GHz)




2402MHz(1GHz-10GHz)




2440MHz(30MHz-1GHz)




2402MHz(10GHz-25GHz)




2440MHz(1GHz-10GHz)




2440MHz(10GHz-25GHz)



2480MHz(10GHz-25GHz)




2480MHz(30MHz-1GHz)



2480MHz(2.477GHz-2.51GHz)



2480MHz(1GHz-10GHz)



## 6. 6dB BANDWIDTH TEST

### 6.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum	Agilent	N9030A	MY51380221	Oct.18,15	1 Year
2.	Attenuator (20dB)	Agilent	8491B	MY39262165	Apr.28,15	1 Year
3.	RF Cable	Marvelous Microwave Inc	SFL402105FLEX	NO.1	Oct.17.15	1 Year

### 6.2. Limit

For direct sequence systems, the minimum 6dB bandwidth shall be at least 500kHz.

### 6.3. Test Procedure

The transmitter output was connected to a spectrum analyzer, The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100kHz RBW and 300KHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

### 6.4. Test Results


EUT: COMPACT DISC RECEIVER		
M/N: HCD-SBT20		
Test date: 2015-12-10	Pressure: 102.3±1.0 kpa	Humidity: 51.3±3.0%
Tested by: Dota_Yao	Test site: RF site	Temperature:24.5±0.6

Test Mode	Frequency (MHz)	6 dB bandwidth (kHz)	Limit (KHz)
GFSK	2402	701.0	>500
	2440	693.0	>500
	2480	694.8	>500


Conclusion : PASS

**GFSK**

**2402MHz**



**2480MHz**



**2440MHz**



## 7. MAXIMUM PEAK OUTPUT POWER TEST

### 7.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum	Agilent	N9030A	MY51380221	Oct.18,15	1 Year
2.	Power meter	Anritsu	ML2487A	6K00002472	Aug.21,15	1 Year
3.	Power sensor	Anritsu	MA2491A	0033005	Aug.21,15	1 Year
4.	Attenuator (20dB)	Agilent	8491B	MY39262165	Apr.28,15	1 Year
5.	RF Cable	Marvelous Microwave Inc	SFL402105FLEX	NO.1	Oct.17,15	1 Year

### 7.2. Limit

For systems using digital modulation in the 2400—2483.5MHz, The Peak out put Power shall not exceed 1W(30dBm).

### 7.3. Test Procedure

Connected the EUT's antenna port to Power Sensor, and use power meter to test peak output power.

### 7.4. Test Results

EUT: COMPACT DISC RECEIVER			
M/N: HCD-SBT20			
Test date: 2015-12-10		Pressure: 102.3±1.0 kpa	Humidity: 51.3±3.0%
Tested by: Dota_Yao		Test site: RF site	Temperature:24.5±0.6
Test Mode	Frequency (MHz)	Peak output Power ( dBm)	Limit (dBm)
GFSK	2402	3.964	30
	2440	5.716	30
	2480	6.595	30
Conclusion: PASS			

## 8. BAND EDGE COMPLIANCE TEST

### 8.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum	Agilent	E4446A	US44300459	Apr.28,15	1 Year
2.	Amp	HP	8449B	3008A02495	Apr.28,15	1 Year
3.	Horn Antenna	ETC	MCTD 1209	DRH15F03007	Feb.03,15	1 Year
4.	HF Cable	Hubersuhner	Sucoflex104	274094/4	Apr.28,15	1 Year

### 8.2. Limit

All the lower and upper band-edges emissions appearing within 2310MHz to 2390MHz and 2483.5MHz to 2500MHz restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

### 8.3. Test Produce

For upper band emissions that are up to two bandwidths(2MHz) away (2483.5MHz to 2485.5MHz ) from the band-edge use below produce:

1. Choose a spectrum analyzer span that encompasses both the peak of the fundamental emission and the band-edge emission under investigation. Set the analyzer RBW to 100KHz and with a video bandwidth 300KHz. Record the peak levels of the fundamental emission and the relevant band-edge emission, Observe the stored trace and measure the amplitude delta between the peak of the fundamental and the peak of the band-edge emission. This is not a field strength measurement, it is only a relative measurement to determine the amount by which the emission drops at the band edge relative to the highest fundamental emission level.
2. Subtract the delta measured in step (1) from the maximum field strengths measured in clause 4 .The resultant field strengths are then used to determine band-edge compliance as required by Section 15.205


For emissions above two bandwidths away from the band-edge use below produce:

1. The EUT is placed on a turntable, which is 0.8m above the ground plane and worked at highest radiated power.
2. The turntable was rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upperband-edges of the emission:
  - (a) PEAK: RBW=1MHz ;VBW=3MHz, PK detector, Sweep=AUTO
  - (b) This is pulse Modulation device a duty cycle factor was used to calculate average level based measured peak level.

### 8.4. Test Results

Pass (The testing data was attached in the next pages.)


Note: If the PK measured levels comply with average limit, then the average level were deemed to comply with average limit.



Site no. : 3m Chamber Data no. : 33  
 Dis. / Ant. : 3m 2015 MCTD1209 3007 Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23.6°C/52.1%  
 Engineer : Thomax\_Chen  
 EUT : COMPACT DISC RECEIVER M/N:HCD-SBT20  
 Power rating : AC 120V/60Hz  
 Test Mode : GFSK 2402MHz Tx Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.000	27.78	7.28	36.62	42.86	41.30	74.00	32.70	Peak
2	2400.000	27.80	7.32	36.62	57.47	55.97	74.00	18.03	Peak
3	2402.340	27.80	7.32	36.62	95.30	93.80	74.00	-19.80	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 34  
 Dis. / Ant. : 3m 2015 MCTD1209 3007 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23.6°C/52.1%  
 Engineer : Thomax\_Chen  
 EUT : COMPACT DISC RECEIVER M/N:HCD-SBT20  
 Power rating : AC 120V/60Hz  
 Test Mode : GFSK 2402MHz Tx Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.000	27.78	7.28	36.62	43.37	41.81	74.00	32.19	Peak
2	2400.000	27.80	7.32	36.62	56.52	55.02	74.00	18.98	Peak
3	2402.150	27.80	7.32	36.62	94.81	93.31	74.00	-19.31	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 47  
 Dis. / Ant. : 3m 2015 MCTD1209 3007 Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23.6°C/52.1%  
 Engineer : Thomax\_Chen  
 EUT : COMPACT DISC RECEIVER M/N:HCD-SBT20  
 Power rating : AC 120V/60Hz  
 Test Mode : GFSK 2480MHz Tx Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.739	27.96	7.47	36.59	99.71	98.55	74.00	-24.55	Peak
2	2483.500	27.97	7.51	36.59	49.35	48.24	74.00	25.76	Peak
3	2500.000	28.00	7.51	36.58	44.03	42.96	74.00	31.04	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 48  
 Dis. / Ant. : 3m 2015 MCTD1209 3007 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23.6°C/52.1%  
 Engineer : Thomax\_Chen  
 EUT : COMPACT DISC RECEIVER M/N:HCD-SBT20  
 Power rating : AC 120V/60Hz  
 Test Mode : GFSK 2480MHz Tx Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.706	27.96	7.47	36.59	98.77	97.61	74.00	-23.61	Peak
2	2483.500	27.97	7.51	36.59	47.91	46.80	74.00	27.20	Peak
3	2500.000	28.00	7.51	36.58	44.05	42.98	74.00	31.02	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.

## 9. POWER SPECTRAL DENSITY TEST

### 9.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
2.	Spectrum	Agilent	N9030A	MY51380221	Oct.18,15	1 Year
4.	Attenuator (20dB)	Agilent	8491B	MY39262165	Apr.28,15	1 Year
5	RF Cable	Marvelous Microwave Inc	SFL402105FLEX	NO.1	Oct.17,15	1 Year

### 9.2. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

### 9.3. Test Procedure

1. Connected the EUT's antenna port to spectrum analyzer device by 20dB attenuator.
2. Set the test frequency as center frequency, Set RBW=3KHz,VBW=10KHz,Span large enough capture the entire frequency, Read out maximum peak level frequency
3. Set the span to 1.5 times of the DTS Bandwidth Detector= Peak; Sweep time= Auto Couple; Trace Mode= Max hold.
4. Allow trace to fully stabilize use the peak marker function to determine the maximum amplitude level within the RBW.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude

### 9.4. Test Results

EUT: COMPACT DISC RECEIVER		
M/N: HCD-SBT20		
Test date: 2015-12-10	Pressure: 102.3±1.0 kpa	Humidity: 51.3±3.0%
Tested by: Dota_Yao	Test site: RF site	Temperature:24.5±0.6

Test Mode	Frequency (MHz)	Power density (dBm/3KHz)	Limit (dBm/3KHz)
GFSK	2402	-14.24	8
	2440	-10.798	8
	2480	-9.262	8
Conclusion : PASS			

**GFSK**

**2402MHz**



**2480MHz**



**2440MHz**



## **10. ANTENNA REQUIREMENT**

### **10.1. Standard Applicable**

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### **10.2. Antenna Connected Construction**

The antennas used for this product are PCB antenna that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is 2.12dBi.

## 11. DEVIATION TO TEST SPECIFICATIONS

[NONE]