



RADIO TEST REPORT


Test Report No. : 10682751H-A


Applicant : Sony Computer Entertainment Inc.
Type of Equipment : Wireless Controller
Model No. : CUH-ZCT1U
FCC ID : AK8CUHZCT1A
Test regulation : FCC Part 15 Subpart C: 2015
Test Result : Complied

1. This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
2. The results in this report apply only to the sample tested.
3. This sample tested is in compliance with the above regulation.
4. The test results in this report are traceable to the national or international standards.
5. This test report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.
6. This test report covers Radio technical requirements. It does not cover administrative issues such as Manual or non-Radio test related Requirements. (if applicable)

Date of test: February 23 to March 10, 2015

Representative test engineer: 
Takumi Shimada
Engineer
Consumer Technology Division

Approved by: 
Masanori Nishiyama
Manager
Consumer Technology Division



This laboratory is accredited by the NVLAP LAB CODE 200572-0, U.S.A. The tests reported herein have been performed in accordance with its terms of accreditation.
*As for the range of Accreditation in NVLAP, you may refer to the WEB address,
<http://www.ul.com/japan/jpn/pages/services/emc/about/mark1/index.jsp#nvlap>

UL Japan, Inc.
Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN
Telephone : +81 596 24 8999
Facsimile : +81 596 24 8124

CONTENTS	PAGE
SECTION 1: Customer information.....	4
SECTION 2: Equipment under test (E.U.T.).....	4
SECTION 3: Test specification, procedures & results.....	5
SECTION 4: Operation of E.U.T. during testing	8
SECTION 5: Conducted Emission.....	10
SECTION 6: Radiated Spurious Emission	11
SECTION 7: Antenna Terminal Conducted Tests.....	12
APPENDIX 1: Data of EMI test.....	13
Conducted Emission	13
20dB Bandwidth and Carrier Frequency Separation.....	17
Number of Hopping Frequency	20
Dwell time.....	22
Maximum Peak Output Power	25
Radiated Spurious Emission	27
Conducted Spurious Emission	34
Conducted Emission Band Edge compliance	46
99%Occupied Bandwidth	48
APPENDIX 2: Test instruments	50
APPENDIX 3: Photographs of test setup	51
Conducted Emission	51
Radiated Spurious Emission	52
Worst Case Position (Horizontal: Z-axis/ Vertical:Y-axis)	53
Test Configuration and peripherals.....	54

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

SECTION 1: Customer information

Company Name	Sony Computer Entertainment Inc.
Brand Name	SONY
Address	1-7-1 Konan, Minato-ku, Tokyo, 108-0075 Japan
Telephone Number	+81-3-6748-6333
Facsimile Number	+81-3-6748-6383
Contact Person	Kiyoto Sasaki

SECTION 2: Equipment under test (E.U.T.)

2.1 Identification of E.U.T.

Type of Equipment	Wireless Controller
Model No	CUH-ZCT1U
Serial No	See Clause 4.2
Country of Manufacture	China
Receipt Date of Sample	February 10, 2015
Condition of EUT	Production prototype (Not for Sale: This sample is equivalent to mass-produced items.)
Modification of EUT	No modification by the test lab

2.2 Product Description

Model No: CUH-ZCT1U is the Wireless Controller for game machine.

Product Specification

Maximum clock frequency in the system (except radio part)	96MHz
Clock frequency in the system (radio part)	26MHz
Operating Temperature	5-35 deg. C
Power Supply	DC 5V (USB Bus Power)
Battery Supply	DC 3.75V
Size	161.2 x 100.3 x 64.5 mm
Weight	210 g

Radio Specification: Bluetooth (Ver. 2.1+EDR)

Equipment Type	Transceiver
Frequency of Operation	2402-2480MHz
Type of Modulation	FHSS (GFSK, π /4DQPSK, 8DPSK)
Bandwidth & Channel spacing	79MHz & 1MHz
Method of frequency generation	Synthesizer
Power Supply (inner)	DC 3.2V
Antenna Type	IFA
Antenna Gain	4.00dBi max

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

SECTION 3: Test specification, procedures & results

3.1 Test Specification

Test Specification : FCC Part 15 Subpart C: 2015, final revised on January 21, 2015

Title : FCC 47CFR Part15 Radio Frequency Device Subpart C Intentional Radiators
Section 15.207 Conducted limits
Section 15.247 Operation within the bands 902-928MHz,
2400-2483.5MHz, and 5725-5850MHz

* The EUT complies with FCC Part 15 Subpart B: 2015, final revised on January 21, 2015.

3.2 Procedures and results

Item	Test Procedure	Specification	Worst Margin	Results	Remarks
Conducted Emission	FCC: ANSI C63.4:2009 7. AC powerline conducted emission measurements IC: RSS-Gen 8.8	FCC: Section 15.207 IC: RSS-Gen 8.8	QP 18.1dB, 0.15236MHz, N AV 18.1dB, 19.32340MHz, N	Complied	-
Carrier Frequency Separation	FCC: FCC Public Notice DA 00-705 IC: -	FCC: Section15.247(a)(1) IC: RSS-210 A8.1 (b)	See data.	Complied	Conducted
20dB Bandwidth	FCC: FCC Public Notice DA 00-705 IC: -	FCC: Section15.247(a)(1) IC: RSS-210 A8.1 (a)		Complied	Conducted
Number of Hopping Frequency	FCC: FCC Public Notice DA 00-705 IC: -	FCC: Section15.247(a)(1)(iii) IC: RSS-210 A8.1 (d)		Complied	Conducted
Dwell time	FCC: FCC Public Notice DA 00-705 IC: -	FCC: Section15.247(a)(1)(iii) IC: RSS-210 A8.1 (d)		Complied	Conducted
Maximum Peak Output Power	FCC: FCC Public Notice DA 00-705 IC: RSS-Gen 6.12	FCC: Section15.247(a)(b)(1) IC: RSS-210 A8.4 (2)		Complied	Conducted
Spurious Emission & Band Edge Compliance	FCC: FCC Public Notice DA 00-705 IC: RSS-Gen 6.13	FCC: Section15.247(d) IC: RSS-210 A8.5 RSS-Gen 8.9 RSS-Gen 8.10		7.2dB 71.850MHz, QP, Horizontal	Complied

Note: UL Japan, Inc.'s EMI Work Procedures No. 13-EM-W0420 and 13-EM-W0422.

* In case any questions arise about test procedure, ANSI C63.4: 2009 is also referred.

FCC 15.31 (e)

This EUT provides stable voltage (DC 3.2V) constantly to RF Part regardless of input voltage. Therefore, this EUT complies with the requirement.

FCC Part 15.203 Antenna requirement

It is impossible for end users to replace the antenna, because the antenna is mounted inside of the EUT. Therefore, the equipment complies with the antenna requirement of Section 15.203.

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

3.3 Addition to standard

Item	Test Procedure	Specification	Worst margin	Results	Remarks
99% Occupied Bandwidth	IC: RSS-Gen 6.6	IC: -	N/A	-	Conducted

Other than above, no addition, exclusion nor deviation has been made from the standard.

3.4 Uncertainty

EMI

The following uncertainties have been calculated to provide a confidence level of 95% using a coverage factor k=2.

Test room (semi-anechoic chamber)	Conducted emission (+dB)
	150kHz-30MHz
No.1	3.5dB
No.2	3.5dB
No.3	3.4dB
No.4	3.5dB

Test room (semi-anechoic chamber)	Radiated emission						
	(3m*)(+dB)				(1m*)(+dB)		(0.5m*)(+dB)
	9kHz -30MHz	30MHz -300MHz	300MHz -1GHz	1GHz -10GHz	10GHz -18GHz	18GHz -26.5GHz	26.5GHz -40GHz
No.1	4.3dB	5.5dB	6.3dB	5.5dB	5.8dB	5.8dB	4.3dB
No.2	4.2dB	5.4dB	6.3dB	5.4dB	5.7dB	5.9dB	5.6dB
No.3	4.4dB	5.4dB	6.4dB	5.2dB	5.5dB	5.8dB	5.5dB
No.4	4.7dB	5.6dB	6.4dB	5.3dB	5.7dB	5.9dB	5.5dB

*3m/1m/0.5m = Measurement distance

Power meter (+dB)	
Below 1GHz	Above 1GHz
0.7dB	1.5dB

Antenna terminal conducted emission and Power density (+dB)			Antenna terminal conducted emission (+dB)		Channel power (+dB)
Below 1GHz	1GHz-3GHz	3GHz-18GHz	18GHz-26.5GHz	26.5GHz-40GHz	
1.5dB	1.7dB	2.8dB	2.8dB	2.9dB	2.6dB

Conducted Emission test

The data listed in this test report has enough margin, more than the site margin.

Radiated emission test (3m)

The data listed in this test report has enough margin, more than the site margin.

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

3.5 Test Location

UL Japan, Inc. Ise EMC Lab. *NVLAP Lab. code: 200572-0
4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN
Telephone : +81 596 24 8999 Facsimile : +81 596 24 8124

	IC Registration Number	Width x Depth x Height (m)	Size of reference ground plane (m) / horizontal conducting plane	Other rooms
No.1 semi-anechoic chamber	2973C-1	19.2 x 11.2 x 7.7m	7.0 x 6.0m	No.1 Power source room
No.2 semi-anechoic chamber	2973C-2	7.5 x 5.8 x 5.2m	4.0 x 4.0m	-
No.3 semi-anechoic chamber	2973C-3	12.0 x 8.5 x 5.9m	6.8 x 5.75m	No.3 Preparation room
No.3 shielded room	-	4.0 x 6.0 x 2.7m	N/A	-
No.4 semi-anechoic chamber	2973C-4	12.0 x 8.5 x 5.9m	6.8 x 5.75m	No.4 Preparation room
No.4 shielded room	-	4.0 x 6.0 x 2.7m	N/A	-
No.5 semi-anechoic chamber	-	6.0 x 6.0 x 3.9m	6.0 x 6.0m	-
No.6 shielded room	-	4.0 x 4.5 x 2.7m	4.0 x 4.5 m	-
No.6 measurement room	-	4.75 x 5.4 x 3.0m	4.75 x 4.15 m	-
No.7 shielded room	-	4.7 x 7.5 x 2.7m	4.7 x 7.5m	-
No.8 measurement room	-	3.1 x 5.0 x 2.7m	N/A	-
No.9 measurement room	-	8.0 x 4.6 x 2.8m	2.4 x 2.4m	-
No.11 measurement room	-	6.2 x 4.7 x 3.0m	4.8 x 4.6m	-

* Size of vertical conducting plane (for Conducted Emission test) : 2.0 x 2.0m for No.1, No.2, No.3, and No.4 semi-anechoic chambers and No.3 and No.4 shielded rooms.

3.6 Data of EMI, Test instruments, and Test set up

Refer to APPENDIX.

UL Japan, Inc. Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN
Telephone : +81 596 24 8999
Facsimile : +81 596 24 8124

SECTION 4: Operation of E.U.T. during testing

4.1 Operating Mode(s)

Bluetooth (BT): Transmitting (Tx), Payload: PRBS9
Inquiry

Details of Operating Mode(s)

Test Item	Mode	Tested frequency
Conducted Emission, Spurious Emission (Conducted/Radiated)	Tx (Hopping off) DH5, 3DH5	2402MHz 2441MHz 2480MHz
Carrier Frequency Separation	Tx (Hopping on) DH5, 3DH5 Inquiry	2402MHz 2441MHz 2480MHz
20dB Bandwidth	Tx (Hopping off) DH5, 3DH5 Inquiry	2402MHz 2441MHz 2480MHz
Number of Hopping Frequency	Tx (Hopping on) DH5, 3DH5 Inquiry	-
Dwell time	Tx (Hopping on), -DH1, DH3, DH5 -3DH1, 3DH3, 3DH5 Inquiry	-
Maximum Peak Output Power	Tx (Hopping off) DH5, 2DH5, 3DH5 Inquiry	2402MHz 2441MHz 2480MHz
Band Edge Compliance (Conducted)	Tx DH5, 3DH5 -Hopping on -Hopping off	2402MHz 2480MHz
99% Occupied Bandwidth	Tx DH5, 3DH5 -Hopping on -Hopping off Inquiry	2402MHz 2441MHz 2480MHz
<p>*As a result of preliminary test, the formal test was performed with the above modes, which had the maximum payload length (except Dwell time test) *2DH mode (2Mb/s EDR: pi/4DQPSK) was excluded for other tests than power measurement by using 3DH mode (3 Mb/s EDR: 8DPSK) as a representative.</p> <p>*EUT has the power settings by the software as follows; Power settings: 4dBm Software: BtUART V2.1.6 *This setting of software is the worst case. Any conditions under the normal use do not exceed the condition of setting. In addition, end users cannot change the settings of the output power of the product.</p>		

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

4.2 Configuration and peripherals

This page has been submitted for a separate exhibit.

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

SECTION 5: Conducted Emission

Test Procedure and conditions

EUT was placed on a urethane platform of nominal size, 1.0m by 1.5m, raised 0.8m above the conducting ground plane. The rear of tabletop was located 40cm to the vertical conducting plane. The rear of EUT, including peripherals aligned and flushed with rear of tabletop. All other surfaces of tabletop were at least 80cm from any other grounded conducting surface. EUT was located 80cm from a Line Impedance Stabilization Network (LISN)/ Artificial mains Network (AMN) and excess AC cable was bundled in center.

For the tests on EUT with other peripherals (as a whole system)

I/O cables that were connected to the peripherals were bundled in center. They were folded back and forth forming a bundle 30cm to 40cm long and were hanged at a 40cm height to the ground plane. All unused 50ohm connectors of the LISN(AMN) were resistivity terminated in 50ohm when not connected to the measuring equipment.

The AC Mains Terminal Continuous disturbance Voltage has been measured with the EUT in a Semi Anechoic Chamber .

The EUT was connected to a LISN (AMN).

An overview sweep with peak detection has been performed.

The test results and limit are rounded off to one decimal place, so some differences might be observed.

Detector	: QP and CISPR AV
Measurement range	: 0.15-30MHz
Test data	: APPENDIX
Test result	: Pass

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

SECTION 6: Radiated Spurious Emission

Test Procedure

EUT was placed on a urethane platform of nominal size, 1.0m by 1.5m, raised 0.8m above the conducting ground plane. The Radiated Electric Field Strength has been measured in a Semi Anechoic Chamber with a ground plane.

The height of the measuring antenna varied between 1 and 4m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field strength.

The measurements were performed for both vertical and horizontal antenna polarization with the Test Receiver, or the Spectrum Analyzer.

The measurements were made with the following detector function of the test receiver and the Spectrum analyzer (in linear mode).

The test was made with the detector (RBW/VBW) in the following table.

When using Spectrum analyzer, the test was made with adjusting span to zero by using peak hold.

Test Antennas are used as below;

Frequency	30MHz to 300MHz	300MHz to 1GHz	Above 1GHz
Antenna Type	Biconical	Logperiodic	Horn

In any 100kHz bandwidth outside the restricted band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator confirmed 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on a radiated measurement.

20dBc was applied to the frequency over the limit of FCC 15.209 / Table 4 of RSS-Gen 8.9 (IC) and outside the restricted band of FCC15.205 / Table 6 of RSS-Gen 8.10 (IC).

Frequency	Below 1GHz	Above 1GHz		20dBc
Instrument used	Test Receiver	Spectrum Analyzer		Spectrum Analyzer
Detector	QP	PK	AV	PK
IF Bandwidth	BW 120kHz	RBW: 1MHz VBW: 3MHz	RBW: 1MHz VBW: 10Hz *1)	RBW: 100kHz VBW: 300kHz
Test Distance	3m	3m (below 10GHz), 1m*2) (above 10GHz)		3m (below 10GHz), 1m*2) (above 10GHz)

*1) Although 00-705 accepts VBW=10Hz for AV measurements, it was confirmed that superfluous smoothing was not performed.

*2) Distance Factor: $20 \times \log(3.0\text{m}/1.0\text{m}) = 9.5\text{dB}$

- The carrier level and noise levels were confirmed at each position of X, Y and Z axes of EUT to see the position of maximum noise, and the test was made at the position that has the maximum noise.

The test results and limit are rounded off to one decimal place, so some differences might be observed.

Measurement range : 30M-26.5GHz
Test data : APPENDIX
Test result : Pass

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

SECTION 7: Antenna Terminal Conducted Tests

Test Procedure

The tests were made with below setting connected to the antenna port.

Test	Span	RBW	VBW	Sweep time	Detector	Trace	Instrument used
20dB Bandwidth	3MHz	30kHz	100kHz	Auto	Peak	Max Hold	Spectrum Analyzer
99% Occupied Bandwidth	Enough width to display 20dB Bandwidth	1 to 5% of OBW	Three times of RBW	Auto	Peak	Max Hold *1)	Spectrum Analyzer
Maximum Peak Output Power	-	-	-	Auto	Peak Average *2)	-	Power Meter (Sensor: 50MHz BW)
Carrier Frequency Separation	5MHz or 3MHz	100kHz or 30kHz	300kHz or 100kHz	Auto	Peak	Max Hold	Spectrum Analyzer
Number of Hopping Frequency	30MHz	300kHz	1MHz	Auto	Peak	Max Hold	Spectrum Analyzer
Dwell Time	Zero Span	100kHz, 1MHz	300kHz, 3MHz	As necessary capture the entire dwell time per hopping channel	Peak	Clear Write	Spectrum Analyzer
Conducted Spurious Emission *3)	9kHz to 150kHz	200Hz	620Hz	Auto	Peak	Max Hold	Spectrum Analyzer
	150kHz to 30MHz	9.1kHz	27kHz				
	30MHz to 25GHz (Less or equal to 5GHz)	100kHz	300kHz				
Conducted Spurious Emission Band Edge compliance	10MHz	100kHz	300kHz	Auto	Peak	Max Hold	Spectrum Analyzer
*1) The measurement was performed with Max Hold since the duty cycle was not 100%. *2) Reference data *3) In the frequency range below 30MHz, RBW was narrowed to separate the noise contents. Then, wide-band noise near the limit was checked separately, however the noise was not detected as shown in the chart. (9kHz-150kHz:RBW=200Hz, 150kHz-30MHz:RBW=9.1kHz)							

The test results and limit are rounded off to two decimals place, so some differences might be observed.

Test data : APPENDIX
Test result : Pass

UL Japan, Inc.
Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN
Telephone : +81 596 24 8999
Facsimile : +81 596 24 8124

APPENDIX 1: Data of EMI test

Conducted Emission


DATA OF CONDUCTED EMISSION TEST

UL Japan, Inc. Ise EMC Lab. No.3 Semi Anechoic Chamber
Date : 2015/03/10

Report No. : 10682751H
Temp./Humi. : 21deg. C / 33% RH
Engineer : Kazuya Yoshioka

Mode / Remarks : BT Tx DH5 2402MHz

LIMIT : FCC15.207 QP
FCC15.207 AV




Frequency [MHz]	Reading Level		Corr. Factor	Results		Limit		Margin		Phase	Comment
	QP [dBuV]	AV [dBuV]		QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	QP [dB]	AV [dB]		
0.15236	34.6	18.9	13.2	47.8	32.1	65.9	55.9	18.1	23.8	N	
0.54150	17.1	11.7	13.3	30.4	25.0	56.0	46.0	25.6	21.0	N	
2.88343	16.6	11.6	13.4	30.0	25.0	56.0	46.0	26.0	21.0	N	
6.42201	14.7	9.8	13.8	28.5	23.6	60.0	50.0	31.5	26.4	N	
9.00694	12.4	7.8	13.9	26.3	21.7	60.0	50.0	33.7	28.3	N	
19.32340	22.5	17.5	14.4	36.9	31.9	60.0	50.0	23.1	18.1	N	
0.15328	32.8	13.0	13.2	46.0	26.2	65.8	55.8	19.8	29.6	L	
0.54803	15.2	9.7	13.3	28.5	23.0	56.0	46.0	27.5	23.0	L	
3.07948	19.0	14.1	13.6	32.6	27.7	56.0	46.0	23.4	18.3	L	
5.62838	13.5	8.7	13.7	27.2	22.4	60.0	50.0	32.8	27.6	L	
7.60111	12.2	7.4	13.8	26.0	21.2	60.0	50.0	34.0	28.8	L	
19.17302	22.4	17.1	14.4	36.8	31.5	60.0	50.0	23.2	18.5	L	

CHART: WITH FACTOR, Peak hold data. CALCULATION: RESULT=READING+C.F (LISN LOSS+ATT LOSS +CABLE LOSS)
Except for the above table : adequate margin data below the limits.

Conducted Emission

Test place	Ise EMC Lab. No.3 Semi Anechoic Chamber
Report No.	10682751H
Date	03/10/2015
Temperature/ Humidity	21deg. C / 33% RH
Engineer	Kazuya Yoshioka
Mode	Tx DH5



UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Conducted Emission


DATA OF CONDUCTED EMISSION TEST

UL Japan, Inc. Ise EMC Lab. No.3 Semi Anechoic Chamber
Date : 2015/03/10

Report No. : 10682751H
Temp./Humi. : 21deg. C / 33% RH
Engineer : Kazuya Yoshioka

Mode / Remarks : BT Tx 3DH5 2402MHz

LIMIT : FCC15.207 QP
FCC15.207 AV



Frequency [MHz]	Reading Level		Corr. Factor [dB]	Results		Limit		Margin		Phase	Comment
	QP [dBuV]	AV [dBuV]		QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	QP [dB]	AV [dB]		
0.15218	29.3	14.9	13.2	42.5	28.1	65.9	55.9	23.4	27.8	N	
0.57848	16.7	11.5	13.3	30.0	24.8	56.0	46.0	26.0	21.2	N	
2.65795	15.6	10.9	13.4	29.0	24.3	56.0	46.0	27.0	21.7	N	
6.14991	11.3	6.5	13.8	25.1	20.3	60.0	50.0	34.9	29.7	N	
8.25868	10.0	5.3	13.8	23.8	19.1	60.0	50.0	36.2	30.9	N	
18.97252	20.0	14.7	14.4	34.4	29.1	60.0	50.0	25.6	20.9	N	
0.15342	30.1	14.8	13.2	43.3	28.0	65.8	55.8	22.5	27.8	L	
0.56978	15.1	10.9	13.3	28.4	24.2	56.0	46.0	27.6	21.8	L	
2.70330	17.0	12.5	13.4	30.4	25.9	56.0	46.0	25.6	20.1	L	
5.22023	11.4	6.7	13.7	25.1	20.4	60.0	50.0	34.9	29.6	L	
7.30634	9.8	5.2	13.8	23.6	19.0	60.0	50.0	36.4	31.0	L	
18.72190	19.4	14.1	14.4	33.8	28.5	60.0	50.0	26.2	21.5	L	

CHART:WITH FACTOR,Peak hold data. CALCULATION:RESULT=READING+C.F(LISN LOSS+ATT LOSS +CABLE LOSS)
Except for the above table : adequate margin data below the limits.

UL Japan, Inc.
Ise EMC Lab.


4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Conducted Emission

Test place	Ise EMC Lab. No.3 Semi Anechoic Chamber
Report No.	10682751H
Date	03/10/2015
Temperature/ Humidity	21deg. C / 33% RH
Engineer	Kazuya Yoshioka
Mode	Tx 3DH5



UL Japan, Inc.
Ise EMC Lab.


4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN
 Telephone : +81 596 24 8999
 Facsimile : +81 596 24 8124

20dB Bandwidth and Carrier Frequency Separation

Test place	Ise EMC Lab. No.11 Measurement Room
Report No.	10682751H
Date	02/23/2015
Temperature/ Humidity	23 deg. C / 42% RH
Engineer	Kazuya Yoshioka
Mode	Tx (Hopping on) DH5/3DH5/Inquiry

Mode	Freq. [MHz]	20dB Bandwidth [MHz]	Carrier Frequency Separation [MHz]	Limit for Carrier Frequency separation [MHz]
DH5	2402.0	0.945	1.000	≥ 0.630
DH5	2441.0	0.938	1.000	≥ 0.625
DH5	2480.0	0.943	1.000	≥ 0.629
3DH5	2402.0	1.297	1.000	≥ 0.865
3DH5	2441.0	1.293	1.000	≥ 0.862
3DH5	2480.0	1.306	1.000	≥ 0.871
Inquiry	2441.0	0.821	2.000	≥ 0.547


Limit: Two-thirds of 20dB Bandwidth or 25kHz (whichever is greater).
No limit applies to 20dB Bandwidth.




UL Japan, Inc.
Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN
Telephone : +81 596 24 8999
Facsimile : +81 596 24 8124

20dB Bandwidth and Carrier Frequency Separation



20dB Bandwidth and Carrier Frequency Separation




Number of Hopping Frequency


Test place	Ise EMC Lab. No.11 Measurement Room
Report No.	10682751H
Date	02/23/2015
Temperature/ Humidity	23 deg. C / 42% RH
Engineer	Kazuya Yoshioka
Mode	Tx (Hopping on) DH5/3DH5/Inquiry

Mode	Number of channel [times]	Limit [times]
DH5	79	>= 15
3DH5	79	>= 15
Inquiry	32	>= 15

Test was not performed at AFH mode whose number of hopping channel is 20 channels because this Bluetooth radio is in compliance of Bluetooth Specification.



Number of Hopping Frequency



UL Japan, Inc.


Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Dwell time



UL Japan, Inc.


Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Dwell time



UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Maximum Peak Output Power

Test place : Ise EMC Lab. No.11 Measurement Room
Report No. : 10682751H
Date : 02/23/2015
Temperature/ Humidity : 23 deg. C / 42% RH
Engineer : Kazuya Yoshioka
Mode : Tx (Hopping off) DH5/2DH5/3DH5/Inquiry

Mode	Freq. [MHz]	Reading [dBm]	Cable Loss [dB]	Atten. [dB]	Result		Limit		Margin [dB]
					[dBm]	[mW]	[dBm]	[mW]	
DH5	2402.0	-8.31	0.80	10.08	2.57	1.81	20.97	125	18.40
DH5	2441.0	-8.47	0.80	10.08	2.41	1.74	20.97	125	18.56
DH5	2480.0	-8.63	0.80	10.08	2.25	1.68	20.97	125	18.72
2DH5	2402.0	-6.09	0.80	10.08	4.79	3.01	20.97	125	16.18
2DH5	2441.0	-6.05	0.80	10.08	4.83	3.04	20.97	125	16.14
2DH5	2480.0	-6.14	0.80	10.08	4.74	2.98	20.97	125	16.23
3DH5	2402.0	-5.60	0.80	10.08	5.28	3.37	20.97	125	15.69
3DH5	2441.0	-5.58	0.80	10.08	5.30	3.39	20.97	125	15.67
3DH5	2480.0	-5.62	0.80	10.08	5.26	3.36	20.97	125	15.71
Inquiry	2441.0	-8.26	0.80	10.08	2.62	1.83	20.97	125	18.35

Sample Calculation:

Result = Reading + Cable Loss (including the cable(s) customer supplied)+ Attenuator

Test was not performed at AFH mode, because the decrease of number of channel (min: 20ch) at AFH mode does not influence on the output power and bandwidth of the EUT.

As this device had AFH mode and frequency separation could not meet the requirement of over 20dB BW without 2/3 relaxation, 125mW power limit was applied to it.

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Average Output Power
(Reference data for SAR testing)

Test place Ise EMC Lab. No.11 Measurement Room
Report No. 10682751H
Date 02/23/2015
Temperature/ Humidity 23 deg. C / 42% RH
Engineer Kazuya Yoshioka
Mode Tx (Hopping off) DH5/2DH5/3DH5/Inquiry

Mode	Freq. [MHz]	Reading [dBm]	Cable Loss [dB]	Atten. [dB]	Result	
					[dBm]	[mW]
DH5	2402.0	-9.72	0.80	10.08	1.16	1.31
DH5	2441.0	-9.83	0.80	10.08	1.05	1.27
DH5	2480.0	-9.98	0.80	10.08	0.90	1.23
2DH5	2402.0	-9.58	0.80	10.08	1.30	1.35
2DH5	2441.0	-9.61	0.80	10.08	1.27	1.34
2DH5	2480.0	-9.79	0.80	10.08	1.09	1.29
3DH5	2402.0	-9.51	0.80	10.08	1.37	1.37
3DH5	2441.0	-9.58	0.80	10.08	1.30	1.35
3DH5	2480.0	-9.74	0.80	10.08	1.14	1.30
Inquiry	2441.0	-16.63	0.80	10.08	-5.75	0.27

Sample Calculation:

Result = Reading + Cable Loss (including the cable(s) customer supplied)+ Attenuator

Radiated Spurious Emission

Test place Ise EMC Lab. No.3 Semi Anechoic Chamber
Report No. 10682751H
Date 03/09/2015 03/10/2015
Temperature/ Humidity 24deg. C / 40% RH 23deg. C / 33% RH
Engineer Kazuya Yoshioka Takumi Shimada
(Below 1GHz) (10-26.5GHz)
(1-10GHz)
Mode Tx, DH5 2402MHz

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori	37.650	QP	28.6	15.1	7.1	32.3	18.5	40.0	21.5	
Hori	71.850	QP	49.8	6.2	7.7	32.1	31.6	40.0	8.4	
Hori	84.100	QP	42.6	7.5	7.8	32.1	25.8	40.0	14.2	
Hori	143.850	QP	35.1	14.6	8.5	32.2	26.0	43.5	17.5	
Hori	286.050	QP	38.0	19.1	9.9	32.0	35.0	46.0	11.0	
Hori	431.832	QP	37.0	17.8	10.7	32.1	33.4	46.0	12.6	
Hori	2390.000	PK	43.5	26.8	3.2	32.7	40.8	73.9	33.1	
Hori	2400.000	PK	53.1	26.8	3.2	32.7	50.4	-	-	- See 20dBc Data Sheet
Hori	2402.000	PK	98.6	26.8	3.2	32.7	95.9	-	-	- See 20dBc Data Sheet
Hori	2558.000	PK	45.1	27.0	3.3	32.7	42.7	73.9	31.2	
Hori	4804.000	PK	41.5	30.6	5.2	31.8	45.5	73.9	28.4	
Hori	7206.000	PK	44.2	35.9	6.6	32.7	54.0	73.9	19.9	
Hori	9608.000	PK	43.1	38.4	7.0	33.3	55.2	73.9	18.7	
Hori	2390.000	AV	29.8	26.8	3.2	32.7	27.1	53.9	26.8	
Hori	2558.000	AV	36.1	27.0	3.3	32.7	33.7	53.9	20.2	
Hori	4804.000	AV	28.0	30.6	5.2	31.8	32.0	53.9	21.9	
Hori	7206.000	AV	29.5	35.9	6.6	32.7	39.3	53.9	14.6	
Hori	9608.000	AV	29.8	38.4	7.0	33.3	41.9	53.9	12.0	
Vert	37.650	QP	33.2	15.1	7.1	32.3	23.1	40.0	16.9	
Vert	70.950	QP	38.6	6.2	7.7	32.1	20.4	40.0	19.6	
Vert	84.100	QP	39.8	7.5	7.8	32.1	23.0	40.0	17.0	
Vert	139.800	QP	37.7	14.4	8.5	32.2	28.4	43.5	15.1	
Vert	286.800	QP	28.2	19.1	9.9	32.0	25.2	46.0	20.8	
Vert	431.832	QP	41.9	17.8	10.7	32.1	38.3	46.0	7.7	
Vert	2390.000	PK	42.4	26.8	3.2	32.7	39.7	73.9	34.2	
Vert	2400.000	PK	49.7	26.8	3.2	32.7	47.0	-	-	- See 20dBc Data Sheet
Vert	2402.000	PK	97.7	26.8	3.2	32.7	95.0	-	-	- See 20dBc Data Sheet
Vert	2558.000	PK	45.7	27.0	3.3	32.7	43.3	73.9	30.6	
Vert	4804.000	PK	41.9	30.6	5.2	31.8	45.9	73.9	28.0	
Vert	7206.000	PK	43.3	35.9	6.6	32.7	53.1	73.9	20.8	
Vert	9608.000	PK	43.5	38.4	7.0	33.3	55.6	73.9	18.3	
Vert	2390.000	AV	29.3	26.8	3.2	32.7	26.6	53.9	27.3	
Vert	2558.000	AV	34.7	27.0	3.3	32.7	32.3	53.9	21.6	
Vert	4804.000	AV	29.2	30.6	5.2	31.8	33.2	53.9	20.7	
Vert	7206.000	AV	29.5	35.9	6.6	32.7	39.3	53.9	14.6	
Vert	9608.000	AV	29.8	38.4	7.0	33.3	41.9	53.9	12.0	

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter-Distance factor(above 10GHz)) - Gain(Amplifier)

*Other frequency noises omitted in this report were not seen or had enough margin (more than 20dB).

Distance factor: 10GHz-26.5GHz 20log(3.0m/1.0m)= 9.5dB

20dBc Data Sheet

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori	2402.000	PK	98.6	26.8	3.2	32.7	95.9	-	-	Carrier
Hori	2400.000	PK	53.1	26.8	3.2	32.7	50.4	75.9	25.5	
Vert	2402.000	PK	97.7	26.8	3.2	32.7	95.0	-	-	Carrier
Vert	2400.000	PK	49.7	26.8	3.2	32.7	47.0	75.0	28.0	

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter-Distance factor(above 10GHz)) - Gain(Amplifier)

UL Japan, Inc.
Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Radiated Spurious Emission

Test place Ise EMC Lab. No.3 Semi Anechoic Chamber
Report No. 10682751H
Date 03/09/2015 03/10/2015
Temperature/ Humidity 24deg. C / 40% RH 23deg. C / 33% RH
Engineer Kazuya Yoshioka Takumi Shimada
(Below 1GHz) (10-26.5GHz)
(1-10GHz)
Mode Tx, DH5 2441MHz

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori	37.650	QP	28.7	15.1	7.1	32.3	18.6	40.0	21.4	
Hori	71.850	QP	51.0	6.2	7.7	32.1	32.8	40.0	7.2	
Hori	84.100	QP	43.0	7.5	7.8	32.1	26.2	40.0	13.8	
Hori	139.800	QP	34.0	14.4	8.5	32.2	24.7	43.5	18.8	
Hori	287.400	QP	37.6	19.1	9.9	32.0	34.6	46.0	11.4	
Hori	431.832	QP	37.2	17.8	10.7	32.1	33.6	46.0	12.4	
Hori	2597.000	PK	47.4	27.0	3.4	32.6	45.2	73.9	28.7	
Hori	4882.000	PK	42.2	30.8	5.3	31.7	46.6	73.9	27.3	
Hori	7323.000	PK	45.0	35.9	6.5	32.7	54.7	73.9	19.2	
Hori	9764.000	PK	42.1	38.7	7.1	33.4	54.5	73.9	19.4	
Hori	2597.000	AV	34.6	27.0	3.4	32.6	32.4	53.9	21.5	
Hori	4882.000	AV	29.1	30.8	5.3	31.7	33.5	53.9	20.4	
Hori	7323.000	AV	31.9	35.9	6.5	32.7	41.6	53.9	12.3	
Hori	9764.000	AV	29.3	38.7	7.1	33.4	41.7	53.9	12.2	
Vert	37.650	QP	32.8	15.1	7.1	32.3	22.7	40.0	17.3	
Vert	71.850	QP	39.2	6.2	7.7	32.1	21.0	40.0	19.0	
Vert	84.100	QP	40.2	7.5	7.8	32.1	23.4	40.0	16.6	
Vert	139.800	QP	40.3	14.4	8.5	32.2	31.0	43.5	12.5	
Vert	287.400	QP	28.4	19.1	9.9	32.0	25.4	46.0	20.6	
Vert	431.832	QP	39.9	17.8	10.7	32.1	36.3	46.0	9.7	
Vert	2597.000	PK	44.6	27.0	3.4	32.6	42.4	73.9	31.5	
Vert	4882.000	PK	42.1	30.8	5.3	31.7	46.5	73.9	27.4	
Vert	7323.000	PK	43.1	35.9	6.5	32.7	52.8	73.9	21.1	
Vert	9764.000	PK	42.5	38.7	7.1	33.4	54.9	73.9	19.0	
Vert	2597.000	AV	33.0	27.0	3.4	32.6	30.8	53.9	23.1	
Vert	4882.000	AV	27.9	30.8	5.3	31.7	32.3	53.9	21.6	
Vert	7323.000	AV	28.8	35.9	6.5	32.7	38.5	53.9	15.4	
Vert	9764.000	AV	29.4	38.7	7.1	33.4	41.8	53.9	12.1	

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter-Distance factor(above 10GHz)) - Gain(Amplifier)

*Other frequency noises omitted in this report were not seen or had enough margin (more than 20dB).

Distance factor: 10GHz-26.5GHz 20log(3.0m/1.0m)= 9.5dB

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Radiated Spurious Emission

Test place Ise EMC Lab. No.3 Semi Anechoic Chamber
Report No. 10682751H
Date 03/09/2015 03/10/2015
Temperature/ Humidity 24deg. C / 40% RH 23deg. C / 33% RH
Engineer Kazuya Yoshioka Takumi Shimada
(Below 1GHz) (10-26.5GHz)
(1-10GHz)
Mode Tx, 3DH5 2480MHz

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori	37.650	QP	28.5	15.1	7.1	32.3	18.4	40.0	21.6	
Hori	70.900	QP	49.9	6.2	7.7	32.1	31.7	40.0	8.3	
Hori	84.100	QP	42.6	7.5	7.8	32.1	25.8	40.0	14.2	
Hori	139.800	QP	35.6	14.4	8.5	32.2	26.3	43.5	17.2	
Hori	286.050	QP	38.1	19.1	9.9	32.0	35.1	46.0	10.9	
Hori	431.832	QP	37.0	17.8	10.7	32.1	33.4	46.0	12.6	
Hori	2483.500	PK	42.9	26.9	3.2	32.7	40.3	73.9	33.6	
Hori	2636.000	PK	44.4	27.0	3.4	32.6	42.2	73.9	31.7	
Hori	4960.000	PK	41.1	30.9	5.2	31.7	45.5	73.9	28.4	
Hori	7440.000	PK	43.0	35.9	6.6	32.7	52.8	73.9	21.1	
Hori	9920.000	PK	42.3	38.9	7.1	33.5	54.8	73.9	19.1	
Hori	2483.500	AV	31.8	26.9	3.2	32.7	29.2	53.9	24.7	
Hori	2636.000	AV	31.3	27.0	3.4	32.6	29.1	53.9	24.8	
Hori	4960.000	AV	28.0	30.9	5.2	31.7	32.4	53.9	21.5	
Hori	7440.000	AV	29.4	35.9	6.6	32.7	39.2	53.9	14.7	
Hori	9920.000	AV	29.3	38.9	7.1	33.5	41.8	53.9	12.1	
Vert	37.650	QP	33.2	15.1	7.1	32.3	23.1	40.0	16.9	
Vert	70.900	QP	38.5	6.2	7.7	32.1	20.3	40.0	19.7	
Vert	84.100	QP	39.9	7.5	7.8	32.1	23.1	40.0	16.9	
Vert	143.850	QP	37.7	14.6	8.5	32.2	28.6	43.5	14.9	
Vert	286.840	QP	28.1	19.1	9.9	32.0	25.1	46.0	20.9	
Vert	431.832	QP	41.8	17.8	10.7	32.1	38.2	46.0	7.8	
Vert	2483.500	PK	42.6	26.9	3.2	32.7	40.0	73.9	33.9	
Vert	2636.000	PK	44.0	27.0	3.4	32.6	41.8	73.9	32.1	
Vert	4960.000	PK	41.4	30.9	5.2	31.7	45.8	73.9	28.1	
Vert	7440.000	PK	43.1	35.9	6.6	32.7	52.9	73.9	21.0	
Vert	9920.000	PK	42.3	38.9	7.1	33.5	54.8	73.9	19.1	
Vert	2483.500	AV	31.4	26.9	3.2	32.7	28.8	53.9	25.1	
Vert	2636.000	AV	31.2	27.0	3.4	32.6	29.0	53.9	24.9	
Vert	4960.000	AV	28.1	30.9	5.2	31.7	32.5	53.9	21.4	
Vert	7440.000	AV	29.4	35.9	6.6	32.7	39.2	53.9	14.7	
Vert	9920.000	AV	29.4	38.9	7.1	33.5	41.9	53.9	12.0	

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter-Distance factor(above 10GHz)) - Gain(Amplifier)

*Other frequency noises omitted in this report were not seen or had enough margin (more than 20dB).

Distance factor: 10GHz-26.5GHz 20log(3.0m/1.0m)= 9.5dB

UL Japan, Inc.

Ise EMC Lab.


4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Burst Rate Confirmation

Test place	Ise EMC Lab. No.11 Measurement Room
Report No.	10682751H
Date	02/23/2015
Temperature/ Humidity	23 deg. C / 42% RH
Engineer	Kazuya Yoshioka
Mode	Tx (Hopping off) DH5/3DH5




UL Japan, Inc.
Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN
 Telephone : +81 596 24 8999
 Facsimile : +81 596 24 8124

Conducted Spurious Emission

Test place	Ise EMC Lab. No.11 Measurement Room
Report No.	10682751H
Date	02/23/2015
Temperature/ Humidity	23 deg. C / 42% RH
Engineer	Kazuya Yoshioka
Mode	Tx (Hopping off) DH5

Tx DH5 2402MHz



UL Japan, Inc.
Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN


Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Conducted Spurious Emission

Test place	Ise EMC Lab. No.11 Measurement Room
Report No.	10682751H
Date	02/23/2015
Temperature/ Humidity	23 deg. C / 42% RH
Engineer	Kazuya Yoshioka
Mode	Tx (Hopping off) DH5


Tx DH5 2402MHz



Conducted Spurious Emission

Test place	Ise EMC Lab. No.11 Measurement Room
Report No.	10682751H
Date	02/23/2015
Temperature/ Humidity	23 deg. C / 42% RH
Engineer	Kazuya Yoshioka
Mode	Tx (Hopping off) DH5

Tx DH5 2441MHz



UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN


Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Conducted Spurious Emission

Test place	Ise EMC Lab. No.11 Measurement Room
Report No.	10682751H
Date	02/23/2015
Temperature/ Humidity	23 deg. C / 42% RH
Engineer	Kazuya Yoshioka
Mode	Tx (Hopping off) DH5

Tx DH5 2441MHz



UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN


Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Conducted Spurious Emission

Test place	Ise EMC Lab. No.11 Measurement Room
Report No.	10682751H
Date	02/23/2015
Temperature/ Humidity	23 deg. C / 42% RH
Engineer	Kazuya Yoshioka
Mode	Tx (Hopping off) DH5

Tx DH5 2480MHz



UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN


Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Conducted Spurious Emission

Test place	Ise EMC Lab. No.11 Measurement Room
Report No.	10682751H
Date	02/23/2015
Temperature/ Humidity	23 deg. C / 42% RH
Engineer	Kazuya Yoshioka
Mode	Tx (Hopping off) DH5


Tx DH5 2480MHz



Conducted Spurious Emission

Test place	Ise EMC Lab. No.11 Measurement Room
Report No.	10682751H
Date	02/23/2015
Temperature/ Humidity	23 deg. C / 42% RH
Engineer	Kazuya Yoshioka
Mode	Tx (Hopping off) 3DH5

Tx 3DH5 2402MHz



UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN


Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Conducted Spurious Emission

Test place	Ise EMC Lab. No.11 Measurement Room
Report No.	10682751H
Date	02/23/2015
Temperature/ Humidity	23 deg. C / 42% RH
Engineer	Kazuya Yoshioka
Mode	Tx (Hopping off) 3DH5


Tx 3DH5 2402MHz



Conducted Spurious Emission

Test place	Ise EMC Lab. No.11 Measurement Room
Report No.	10682751H
Date	02/23/2015
Temperature/ Humidity	23 deg. C / 42% RH
Engineer	Kazuya Yoshioka
Mode	Tx (Hopping off) 3DH5

Tx 3DH5 2441MHz



UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN


Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Conducted Spurious Emission

Test place	Ise EMC Lab. No.11 Measurement Room
Report No.	10682751H
Date	02/23/2015
Temperature/ Humidity	23 deg. C / 42% RH
Engineer	Kazuya Yoshioka
Mode	Tx (Hopping off) 3DH5

Tx 3DH5 2441MHz



UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN


Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Conducted Spurious Emission

Test place	Ise EMC Lab. No.11 Measurement Room
Report No.	10682751H
Date	02/23/2015
Temperature/ Humidity	23 deg. C / 42% RH
Engineer	Kazuya Yoshioka
Mode	Tx (Hopping off) 3DH5

Tx 3DH5 2480MHz



UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN


Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Conducted Spurious Emission

Test place	Ise EMC Lab. No.11 Measurement Room
Report No.	10682751H
Date	02/23/2015
Temperature/ Humidity	23 deg. C / 42% RH
Engineer	Kazuya Yoshioka
Mode	Tx (Hopping off) 3DH5


Tx 3DH5 2480MHz




Conducted Emission Band Edge compliance

Test place	Ise EMC Lab. No.11 Measurement Room
Report No.	10682751H
Date	02/23/2015
Temperature/ Humidity	23 deg. C / 42% RH
Engineer	Kazuya Yoshioka
Mode	Tx (Hopping on/off) DH5

Tx DH5, Hopping off



Tx DH5, Hopping on



UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN


Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124


Conducted Emission Band Edge compliance

Test place	Ise EMC Lab. No.11 Measurement Room
Report No.	10682751H
Date	02/23/2015
Temperature/ Humidity	23 deg. C / 42% RH
Engineer	Kazuya Yoshioka
Mode	Tx (Hopping on/off) 3DH5

Tx 3DH5, Hopping off



Tx 3DH5, Hopping on



UL Japan, Inc.

Ise EMC Lab.


4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124


99% Occupied Bandwidth

Test place	Ise EMC Lab. No.11 Measurement Room
Report No.	10682751H
Date	02/23/2015
Temperature/ Humidity	23 deg. C / 42% RH
Engineer	Kazuya Yoshioka
Mode	Tx (Hopping off) DH5/3DH5



99% Occupied Bandwidth

Test place	Ise EMC Lab. No.11 Measurement Room
Report No.	10682751H
Date	02/23/2015
Temperature/ Humidity	23 deg. C / 42% RH
Engineer	Kazuya Yoshioka
Mode	Tx (Hopping on) DH5/3DH5/Inquiry



APPENDIX 2: Test instruments

EMI test equipment

Control No.	Instrument	Manufacturer	Model No	Serial No	Test Item	Calibration Date * Interval(month)
MSA-13	Spectrum Analyzer	Agilent	E4440A	MY46185823	AT	2014/06/06 * 12
MAT-20	Attenuator(10dB)(above1 GHz)	HIROSE ELECTRIC CO.,LTD.	AT-110	-	AT	2015/01/08 * 12
MPM-09	Power Meter	Anritsu	ML2495A	6K00003348	AT	2014/10/06 * 12
MPSE-12	Power sensor	Anritsu	MA2411B	011598	AT	2014/10/06 * 12
MOS-19	Thermo-Hygrometer	Custom	CTH-201	0001	AT	2014/12/22 * 12
MOTS-MATM	Antenna Terminal Measurement Software	UL Japan	-	-	AT	-
MAEC-03	Semi Anechoic Chamber(NSA)	TDK	Semi Anechoic Chamber 3m	DA-10005	RE,CE	2015/02/19 * 12
MOS-13	Thermo-Hygrometer	Custom	CTH-180	1301	RE,CE	2015/01/13 * 12
MJM-16	Measure	KOMELON	KMC-36	-	RE,CE	-
COTS-MEMI	EMI measurement program	TSJ	TEPTO-DV	-	RE,CE	-
MSA-03	Spectrum Analyzer	Agilent	E4448A	MY44020357	RE,CE	2014/04/08 * 12
MTR-08	Test Receiver	Rohde & Schwarz	ESCI	100767	RE,CE	2014/08/19 * 12
MBA-03	Biconical Antenna	Schwarzbeck	BBA9106	1915	RE	2014/10/18 * 12
MLA-03	Logperiodic Antenna	Schwarzbeck	USLP9143	174	RE	2014/10/18 * 12
MCC-51	Coaxial cable	UL Japan	-	-	RE	2014/07/14 * 12
MAT-70	Attenuator(6dB)	Agilent	8491A-006	MY52460153	RE	2014/04/14 * 12
MPA-13	Pre Amplifier	SONOMA INSTRUMENT	310	260834	RE	2015/03/10 * 12
MHA-20	Horn Antenna 1-18GHz	Schwarzbeck	BBHA9120D	258	RE	2014/05/26 * 12
MCC-167	Microwave Cable	Junkosha	MWX221	1404S374(1m) / 1405S074(5m)	RE	2014/05/26 * 12
MPA-11	MicroWave System Amplifier	Agilent	83017A	MY39500779	RE	2014/03/24 * 12
MHF-25	High Pass Filter 3.5-18.0GHz	UL Japan	HPF SELECTOR	001	RE	2014/09/22 * 12
MHA-16	Horn Antenna 15-40GHz	Schwarzbeck	BBHA9170	BBHA9170306	RE	2014/05/26 * 12
MLS-24	LISN(AMN)	Schwarzbeck	NSLK8127	8127-730	CE	2014/07/10 * 12
MCC-112	Coaxial cable	Fujikura/Suhner/TSJ	5D-2W(10m)/SFM141(3m)/sucoform141-PE(1m)/421-010(1.5m)/RFM-E321(Switcher)	-/00640	CE	2014/07/14 * 12
MAT-66	Attenuator(13dB)	JFW Industries, Inc.	50FP-013H2 N	-	CE	2015/01/29 * 12

The expiration date of the calibration is the end of the expired month.

All equipment is calibrated with valid calibrations. Each measurement data is traceable to the national or international standards.

As for some calibrations performed after the tested dates, those test equipment have been controlled by means of an unbroken chains of calibrations.

Test Item: CE: Conducted Emission test

RE: Radiated Emission test

AT: Antenna Terminal Conducted test

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124