



# RADIO TEST REPORT


Test Report No. : 11249046H-A

**Applicant** : Sony Interactive Entertainment Inc.  
**Type of Equipment** : Wireless Adaptor  
**Model No.** : CUH-ZWA1U  
**FCC ID** : AK8CUHZWA1  
**Test regulation** : FCC Part 15 Subpart C: 2015  
**Test Result** : Complied

1. This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
2. The results in this report apply only to the sample tested.
3. This sample tested is in compliance with the above regulation.
4. The test results in this report are traceable to the national or international standards.
5. This test report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.
6. This test report covers Radio technical requirements. It does not cover administrative issues such as Manual or non-Radio test related Requirements. (if applicable)

**Date of test:** April 15 to 19, 2016

**Representative test engineer:**

  
Yuta Moriya  
Engineer

Consumer Technology Division

**Approved by:**

  
Takayuki Shimada  
Engineer

Consumer Technology Division



NVLAP LAB CODE: 200572-0

This laboratory is accredited by the NVLAP LAB CODE 200572-0, U.S.A. The tests reported herein have been performed in accordance with its terms of accreditation.  
\*As for the range of Accreditation in NVLAP, you may refer to the WEB address,  
[http://japan.ul.com/resources/emc\\_accredited/](http://japan.ul.com/resources/emc_accredited/)

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

13-EM-F0429



---

| <b>CONTENTS</b>   | <b>PAGE</b> |
|---|-------------|
| <b>SECTION 1: Customer information.....</b>                         | <b>4</b>    |
| <b>SECTION 2: Equipment under test (E.U.T.).....</b>                | <b>4</b>    |
| <b>SECTION 3: Test specification, procedures &amp; results.....</b> | <b>5</b>    |
| <b>SECTION 4: Operation of E.U.T. during testing.....</b>           | <b>8</b>    |
| <b>SECTION 5: Conducted Emission.....</b>                           | <b>10</b>   |
| <b>SECTION 6: Radiated Spurious Emission .....</b>                  | <b>11</b>   |
| <b>SECTION 7: Antenna Terminal Conducted Tests.....</b>             | <b>12</b>   |
| <b>APPENDIX 1: Test data .....</b>                                  | <b>13</b>   |
| Conducted Emission .....  | 13          |
| 20dB Bandwidth and Carrier Frequency Separation.....                | 17          |
| Number of Hopping Frequency .....                                   | 20          |
| Dwell time.....   | 22          |
| Maximum Peak Output Power .....                                     | 25          |
| Average Output Power .....  | 26          |
| Radiated Spurious Emission .....                                    | 28          |
| Conducted Spurious Emission .....                                   | 39          |
| Conducted Emission Band Edge compliance .....                       | 45          |
| 99%Occupied Bandwidth .....   | 47          |
| <b>APPENDIX 2: Test instruments .....</b>                           | <b>49</b>   |
| <b>APPENDIX 3: Photographs of test setup .....</b>                  | <b>50</b>   |
| Conducted Emission .....  | 50          |
| Radiated Spurious Emission .....                                    | 51          |
| Worst Case Position .....   | 52          |
| Test Configuration and peripherals.....                             | 53          |

## **SECTION 1: Customer information**

|                  |   |
|------------------|---|
| Company Name     | Sony Interactive Entertainment Inc.           |
| Brand Name       | SONY  |
| Address          | 1-7-1 Konan, Minato-ku, Tokyo, 108-0075 Japan |
| Telephone Number | +81-3-6748-6333                               |
| Facsimile Number | +81-3-6748-6383                               |
| Contact Person   | Kiyoto Sasaki                                 |

## **SECTION 2: Equipment under test (E.U.T.)**

### **2.1 Identification of E.U.T.**

|                        |  |
|------------------------|--|
| Type of Equipment      | Wireless Adaptor   |
| Model No               | CUH-ZWA1U  |
| Serial No              | Refer to Clause 4.2  |
| Country of Manufacture | China  |
| Receipt Date of Sample | April 15, 2016   |
| Condition of EUT       | Engineering prototype<br>(Not for Sale: This sample is equivalent to mass-produced items.) |
| Modification of EUT    | No modification by the test lab.   |

### **2.2 Product Description**

CUH-ZWA1U is the Wireless Adaptor.

#### **Product Specification**

|  |   |
|--|---|
| Clock frequency in the system (radio part) | 24 MHz, 26 MHz, 64 MHz, 96 MHz, 384 MHz |
| Operating Temperature                      | +5 to +35 deg. C                        |
| Power Supply                               | 5 ± 0.25 V                              |
| Size                                       | 18 mm x 9 mm x 75mm                     |

#### **Radio Specification**

##### **Bluetooth (BDR/EDR)**

|                                |                                   |
|--------------------------------|-----------------------------------|
| Equipment Type                 | Transceiver                       |
| Frequency of Operation         | 2402-2480MHz                      |
| Type of Modulation             | FHSS (GFSK, $\pi/4$ DQPSK, 8DPSK) |
| Bandwidth & Channel spacing    | 79MHz & 1MHz                      |
| Method of frequency generation | Synthesizer                       |
| Power Supply (inner)           | DC 1.2 V / DC 3.2 V               |
| Antenna Type                   | Monopole                          |
| Antenna Gain                   | 4.5 dBi (Max)                     |

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

## **SECTION 3: Test specification, procedures & results**

### **3.1 Test Specification**

Test Specification : FCC Part 15 Subpart C: 2015, final revised on November 23, 2015  
\*Some parts are effective on and after December 17, 2015 or December 23, 2015. The revision does not affect the test specification applied to the EUT.

Title : FCC 47CFR Part15 Radio Frequency Device Subpart C Intentional Radiators  
Section 15.207 Conducted limits  
Section 15.247 Operation within the bands 902-928MHz,  
2400-2483.5MHz, and 5725-5850MHz

\* The EUT complies with FCC Part 15 Subpart B: 2015, final revised on November 23, 2015

### **3.2 Procedures and results**

| Item                                     | Test Procedure   | Specification   | Worst Margin   | Results  | Remarks   |
|--|--|---|--|----------|---|
| Conducted Emission                       | FCC: ANSI C63.10-2013<br>6. Standard test methods<br>IC: RSS-Gen 8.8 | FCC: Section 15.207<br>IC: RSS-Gen 8.8                                  | QP<br>15.7 dB, 0.19420 MHz, N<br>AV<br>13.5 dB, 0.39200 MHz, L | Complied | -   |
| Carrier Frequency Separation             | FCC: FCC Public Notice<br>DA 00-705<br>IC: -                         | FCC: Section15.247(a)(1)<br>IC: RSS-247 5.1 (2)                         | See data.  | Complied | Conducted                                       |
| 20dB Bandwidth                           | FCC: FCC Public Notice<br>DA 00-705<br>IC: -                         | FCC: Section15.247(a)(1)<br>IC: RSS-247 5.1 (1)                         |  | Complied | Conducted                                       |
| Number of Hopping Frequency              | FCC: FCC Public Notice<br>DA 00-705<br>IC: -                         | FCC: Section15.247(a)(1)(iii)<br>IC: RSS-247 5.1 (4)                    |  | Complied | Conducted                                       |
| Dwell time                               | FCC: FCC Public Notice<br>DA 00-705<br>IC: -                         | FCC: Section15.247(a)(1)(iii)<br>IC: RSS-247 5.1 (4)                    |  | Complied | Conducted                                       |
| Maximum Peak Output Power                | FCC: FCC Public Notice<br>DA 00-705<br>IC: RSS-Gen 6.12              | FCC: Section15.247(a)(b)(1)<br>IC: RSS-247 5.4 (2)                      |  | Complied | Conducted                                       |
| Spurious Emission & Band Edge Compliance | FCC: FCC Public Notice<br>DA 00-705<br>IC: RSS-Gen 6.13              | FCC: Section15.247(d)<br>IC: RSS-247 5.5<br>RSS-Gen 8.9<br>RSS-Gen 8.10 | 15.5 dB<br>168.000 MHz, QP, Vert.                              | Complied | Conducted/<br>Radiated<br>(above 30 MHz)<br>*1) |

Note: UL Japan, Inc.'s EMI Work Procedures No. 13-EM-W0420 and 13-EM-W0422.  
\*1) Radiated test was selected over 30 MHz based on section 15.247(d).

\* In case any questions arise about test procedure, ANSI C63.10: 2013 is also referred.

#### **FCC Part 15.31 (e)**

This EUT provides stable voltage (DC 1.2 V / DC 3.2 V) constantly to RF Part regardless of input voltage. Therefore, this EUT complies with the requirement.

#### **FCC Part 15.203 Antenna requirement**

It is impossible for end users to replace the antenna, because the antenna is mounted inside of the EUT. Therefore, the equipment complies with the antenna requirement of Section 15.203.

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

### 3.3 Addition to standard

| Item                   | Test Procedure  | Specification | Worst margin | Results | Remarks   |
|------------------------|-----------------|---------------|--------------|---------|-----------|
| 99% Occupied Bandwidth | IC: RSS-Gen 6.6 | IC: -         | N/A          | -       | Conducted |

Other than above, no addition, exclusion nor deviation has been made from the standard.

### 3.4 Uncertainty

#### EMI

The following uncertainties have been calculated to provide a confidence level of 95 % using a coverage factor  $k = 2$ .  
Ise EMC Lab.

| Antenna terminal test Uncertainty (+/-) |             |                                      |               |                |                    |                   |               |
|---|-------------|--------------------------------------|---------------|----------------|--------------------|-------------------|---------------|
| Power meter                             |             | Conducted emission and Power density |               |                | Conducted emission |                   | Channel power |
| Below 1 GHz                             | Above 1 GHz | Below 1 GHz                          | 1 GHz - 3 GHz | 3 GHz - 18 GHz | 18 GHz - 26.5 GHz  | 26.5 GHz - 40 GHz |               |
| 0.9 dB                                  | 1.0 dB      | 1.4 dB                               | 1.7 dB        | 2.8 dB         | 2.8 dB             | 2.9 dB            | 2.6 dB        |

| Frequency range | Conducted emission using AMN(LISN) (+dB) |
|-----------------|--|
| 0.009 – 0.15MHz | 3.5 dB                                   |
| 0.15 – 30MHz    | 2.9 dB                                   |

| Test distance | Radiated emission (+dB)<br>9 kHz - 30 MHz |
|---------------|---|
| 3m            | 3.8 dB                                    |
| 10m           | 3.7 dB                                    |

| Polarity   | Radiated emission (Below 1GHz) |               |              |               |
|------------|--------------------------------|---------------|--------------|---------------|
|            | (3 m*)(±dB)                    |               | (10 m*)(±dB) |               |
|            | 30 – 200 MHz                   | 200 – 1000MHz | 30 – 200 MHz | 200 – 1000MHz |
| Horizontal | 4.8 dB                         | 5.2 dB        | 4.8 dB       | 5.0 dB        |
| Vertical   | 4.5 dB                         | 5.9 dB        | 4.8 dB       | 5.1 dB        |

| Radiated emission |           |               |               |              |
|-------------------|-----------|---------------|---------------|--------------|
| (3 m*)(±dB)       |           | (1 m*)(±dB)   | (0.5 m*)(±dB) | (10 m*)(±dB) |
| 1 – 6GHz          | 6 – 18GHz | 10 – 26.5 GHz | 26.5 – 40GHz  | 1 -18 GHz    |
| 5.1 dB            | 5.3 dB    | 5.1 dB        | 5.1 dB        | 5.3 dB       |

\*Measurement distance

#### Conducted Emission test

The data listed in this test report has enough margin, more than the site margin.

#### Radiated emission test

The data listed in this test report has enough margin, more than the site margin.

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

### 3.5 Test Location

UL Japan, Inc. Ise EMC Lab. \*NVLAP Lab. code: 200572-0  
 4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN  
 Telephone: +81 596 24 8999, Facsimile: +81 596 24 8124

| Test site                  | IC Registration Number | Width x Depth x Height (m) | Size of reference ground plane (m) / horizontal conducting plane | Other rooms            | Maximum measurement distance |
|----------------------------|------------------------|----------------------------|--|------------------------|------------------------------|
| No.1 semi-anechoic chamber | 2973C-1                | 19.2 x 11.2 x 7.7          | 7.0 x 6.0  | No.1 Power source room | 10 m                         |
| No.2 semi-anechoic chamber | 2973C-2                | 7.5 x 5.8 x 5.2            | 4.0 x 4.0  | -                      | 3 m                          |
| No.3 semi-anechoic chamber | 2973C-3                | 12.0 x 8.5 x 5.9           | 6.8 x 5.75   | No.3 Preparation room  | 3 m                          |
| No.3 shielded room         | -                      | 4.0 x 6.0 x 2.7            | N/A  | -                      | -                            |
| No.4 semi-anechoic chamber | 2973C-4                | 12.0 x 8.5 x 5.9           | 6.8 x 5.75   | No.4 Preparation room  | 3 m                          |
| No.4 shielded room         | -                      | 4.0 x 6.0 x 2.7            | N/A  | -                      | -                            |
| No.5 semi-anechoic chamber | -                      | 6.0 x 6.0 x 3.9            | 6.0 x 6.0  | -                      | -                            |
| No.6 shielded room         | -                      | 4.0 x 4.5 x 2.7            | 4.0 x 4.5  | -                      | -                            |
| No.6 measurement room      | -                      | 4.75 x 5.4 x 3.0           | 4.75 x 4.15  | -                      | -                            |
| No.7 shielded room         | -                      | 4.7 x 7.5 x 2.7            | 4.7 x 7.5  | -                      | -                            |
| No.8 measurement room      | -                      | 3.1 x 5.0 x 2.7            | N/A  | -                      | -                            |
| No.9 measurement room      | -                      | 8.8 x 4.6 x 2.8            | 2.4 x 2.4  | -                      | -                            |
| No.11 measurement room     | -                      | 6.2 x 4.7 x 3.0            | 4.8 x 4.6  | -                      | -                            |

### 3.6 Test data, Test instruments, and Test set up

Refer to APPENDIX.

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

## **SECTION 4: Operation of E.U.T. during testing**

### **4.1 Operating Mode(s)**

Bluetooth (BT): Transmitting (Tx), Payload: PRBS9

Details of Operating Mode(s)

| <b>Test Item</b>  | <b>Mode</b>   | <b>Tested frequency</b>          |
|---|---|----------------------------------|
| Conducted Emission,<br>Spurious Emission<br>(Conducted/Radiated)  | Tx (Hopping Off) DH5, 3DH5                              | 2402 MHz<br>2441 MHz<br>2480 MHz |
| Carrier Frequency Separation  | Tx (Hopping On) DH5, 3DH5                               | 2402 MHz<br>2441 MHz<br>2480 MHz |
| 20dB Bandwidth  | Tx (Hopping Off) DH5, 3DH5                              | 2402 MHz<br>2441 MHz<br>2480 MHz |
| Number of Hopping Frequency   | Tx (Hopping On) DH5, 3DH5                               | -                                |
| Dwell time  | Tx (Hopping On),<br>-DH1, DH3, DH5<br>-3DH1, 3DH3, 3DH5 | -                                |
| Maximum Peak Output Power   | Tx (Hopping Off) DH5, 2DH5, 3DH5                        | 2402 MHz<br>2441 MHz<br>2480 MHz |
| Band Edge Compliance<br>(Conducted)   | Tx DH5, 3DH5<br>-Hopping On<br>-Hopping Off             | 2402 MHz<br>2480 MHz             |
| 99% Occupied Bandwidth  | Tx DH5, 3DH5<br>-Hopping On<br>-Hopping Off             | 2402 MHz<br>2441 MHz<br>2480 MHz |
| <p>*As a result of preliminary test, the formal test was performed with the above modes, which had the maximum payload length (except Dwell time test)</p> <p>*2DH mode (2Mb/s EDR: pi/4DQPSK) was excluded for other tests than power measurement by using 3DH mode (3 Mb/s EDR: 8DPSK) as a representative.</p> <p>* It is considered that the non-tested packet type (e.g. inquiry) can be omitted as it is complied with above all test items based on Bluetooth Core specification.</p> <p>*The power value of the EUT was set for testing as follows (setting value might be different from product specification value);<br/> Power settings: 4 dBm<br/> Software: BtUART V2.1.6<br/> *This setting of software is the worst case.<br/> Any conditions under the normal use do not exceed the condition of setting.<br/> In addition, end users cannot change the settings of the output power of the product.</p> |   |                                  |

## 4.2 Configuration and peripherals

**This page has been submitted for a separate exhibit.**

## **SECTION 5: Conducted Emission**

### **Test Procedure and conditions**

EUT was placed on a urethane platform / a wooden table of nominal size, 1.0 m by 1.5 m, raised 0.8m above the conducting ground plane.

The rear of tabletop was located 40 cm to the vertical conducting plane. The rear of EUT, including peripherals aligned and flushed with rear of tabletop. All other surfaces of tabletop were at least 80 cm from any other grounded conducting surface. EUT was located 80 cm from a Line Impedance Stabilization Network (LISN) / Artificial mains Network (AMN) and excess AC cable was bundled in center.

#### For the tests on EUT with other peripherals (as a whole system)

I/O cables that were connected to the peripherals were bundled in center. They were folded back and forth forming a bundle 30 cm to 40 cm long and were hanged at a 40 cm height to the ground plane. All unused 50 ohm connectors of the LISN (AMN) were resistivity terminated in 50 ohm when not connected to the measuring equipment.

The AC Mains Terminal Continuous disturbance Voltage has been measured with the EUT in a Semi Anechoic Chamber.

The EUT was connected to a LISN (AMN).

An overview sweep with peak detection has been performed.

The test results and limit are rounded off to one decimal place, so some differences might be observed.

**Detector** : QP and CISPR AV  
**Measurement range** : 0.15 MHz - 30 MHz  
**Test data** : APPENDIX  
**Test result** : Pass

## **SECTION 6: Radiated Spurious Emission**

### **Test Procedure**

[For below 1GHz]

EUT was placed on a urethane platform of nominal size, 1.0 m by 1.5 m, raised 0.8 m above the conducting ground plane. The Radiated Electric Field Strength has been measured in a Semi Anechoic Chamber with a ground plane.

[For above 1GHz]

EUT was placed on a urethane platform of nominal size, 0.5 m by 0.5 m, raised 1.5 m above the conducting ground plane.

The Radiated Electric Field Strength has been measured in a Semi Anechoic Chamber with absorbent materials lined on a ground plane.

The height of the measuring antenna varied between 1 and 4 m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field strength.

The measurements were performed for both vertical and horizontal antenna polarization with the Test Receiver, or the Spectrum Analyzer.

The measurements were made with the following detector function of the test receiver and the Spectrum analyzer (in linear mode).

The test was made with the detector (RBW/VBW) in the following table.

When using Spectrum analyzer, the test was made with adjusting span to zero by using peak hold.

### **Test Antennas are used as below;**

|              |                   |                  |             |
|--------------|-------------------|------------------|-------------|
| Frequency    | 30 MHz to 200 MHz | 200 MHz to 1 GHz | Above 1 GHz |
| Antenna Type | Biconical         | Logperiodic      | Horn        |

In any 100 kHz bandwidth outside the restricted band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator confirmed 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on a radiated measurement.

### **20 dBc was applied to the frequency over the limit of FCC 15.209 / Table 4 of RSS-Gen 8.9 (IC) and outside the restricted band of FCC15.205 / Table 6 of RSS-Gen 8.10 (IC).**

|                 |               |  |                              |  |
|-----------------|---------------|--|------------------------------|--|
| Frequency       | Below 1 GHz   | Above 1 GHz  |                              | 20 dBc   |
| Instrument used | Test Receiver | Spectrum Analyzer  |                              | Spectrum Analyzer  |
| Detector        | QP            | PK   | AV                           | PK   |
| IF Bandwidth    | BW 120 kHz    | RBW: 1 MHz<br>VBW: 3 MHz                                 | RBW: 1 MHz<br>VBW: 10 Hz *1) | RBW: 100 kHz<br>VBW: 300 kHz                             |
| Test Distance   | 3 m           | 4.5 m*2) (1 GHz – 10 GHz),<br>1 m*3) (10 GHz – 26.5 GHz) |                              | 4.5 m*2) (1 GHz – 10 GHz),<br>1 m*3) (10 GHz – 26.5 GHz) |

\*1) Although DA 00-705 accepts VBW = 10 Hz for AV measurements, it was confirmed that superfluous smoothing was not performed.

\*2) Distance Factor:  $20 \times \log(4.5 \text{ m}/3.0 \text{ m}) = 3.52 \text{ dB}$

\*2) Distance Factor:  $20 \times \log(1.0 \text{ m}/3.0 \text{ m}) = -9.5 \text{ dB}$

- The carrier level and noise levels were confirmed at each position of X, Y and Z axes of EUT to see the position of maximum noise, and the test was made at the position that has the maximum noise.

The test results and limit are rounded off to one decimal place, so some differences might be observed.

**Measurement range** : 30 M - 26.5 GHz  
**Test data** : APPENDIX  
**Test result** : Pass

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

## **SECTION 7: Antenna Terminal Conducted Tests**

### **Test Procedure**

The tests were made with below setting connected to the antenna port.

| Test   | Span                                    | RBW             | VBW                | Sweep time   | Detector         | Trace       | Instrument used                |
|--|---|-----------------|--------------------|--|------------------|-------------|--------------------------------|
| 20dB Bandwidth                                   | 3 MHz                                   | 30 kHz          | 100 kHz            | Auto   | Peak             | Max Hold    | Spectrum Analyzer              |
| 99% Occupied Bandwidth *1)                       | Enough width to display emission skirts | 1 to 5 % of OBW | Three times of RBW | Auto   | Peak             | Max Hold    | Spectrum Analyzer              |
| Maximum Peak Output Power                        | -                                       | -               | -                  | Auto   | Peak Average *3) | -           | Power Meter (Sensor: 50MHz BW) |
| Carrier Frequency Separation                     | 3 MHz                                   | 30 kHz          | 100 kHz            | Auto   | Peak             | Max Hold    | Spectrum Analyzer              |
| Number of Hopping Frequency                      | 30 MHz                                  | 300 kHz         | 1 MHz              | Auto   | Peak             | Max Hold    | Spectrum Analyzer              |
| Dwell Time                                       | Zero Span                               | 100 kHz, 1 MHz  | 300 kHz, 3 MHz     | As necessary capture the entire dwell time per hopping channel | Peak             | Clear Write | Spectrum Analyzer              |
| Conducted Spurious Emission *2)                  | 9 kHz to 150 kHz                        | 200 Hz          | 620 Hz             | Auto   | Peak             | Max Hold    | Spectrum Analyzer              |
|  | 150 kHz to 30 MHz                       | 9.1 kHz         | 27 kHz             |  |                  |             |                                |
|  | 30 MHz to 25 GHz                        | 100 kHz         | 300 kHz            |  |                  |             |                                |
| Conducted Spurious Emission Band Edge compliance | 10 MHz                                  | 100 kHz         | 300 kHz            | Auto   | Peak             | Max Hold    | Spectrum Analyzer              |

\*1) Peak hold was applied as Worst-case measurement.

\*2) In the frequency range below 30MHz, RBW was narrowed to separate the noise contents. Then, wide-band noise near the limit was checked separately, however the noise was not detected as shown in the chart. (9 kHz -150 kHz: RBW = 200 Hz, 150 kHz - 30 MHz: RBW = 9.1 kHz)

\*3) Reference data

The test results and limit are rounded off to two decimals place, so some differences might be observed.

**Test data : APPENDIX**  
**Test result : Pass**

**APPENDIX 1: Test data**

**Conducted Emission**

**DATA OF CONDUCTED EMISSION TEST**


UL Japan, Inc. Ise EMC Lab. No.3 Semi Anechoic Chamber  
Date : 2016/04/18

Report No. : 11249046H

Temp./Humi. : 22deg. C / 45% RH  
Engineer : Shinichi Miyazono

Mode / Remarks : Tx DH5 2402MHz

LIMIT : FCC15.207 QP  
FCC15.207 AV




| Frequency<br>[MHz] | Reading Level |              | Corr.<br>Factor<br>[dB] | Results      |              | Limit        |              | Margin     |            | Phase | Comment |
|--------------------|---------------|--------------|-------------------------|--------------|--------------|--------------|--------------|------------|------------|-------|---------|
|                    | QP<br>[dBuV]  | AV<br>[dBuV] |                         | QP<br>[dBuV] | AV<br>[dBuV] | QP<br>[dBuV] | AV<br>[dBuV] | QP<br>[dB] | AV<br>[dB] |       |         |
| 0.15000            | 28.5          | 7.4          | 13.2                    | 41.7         | 20.6         | 66.0         | 56.0         | 24.3       | 35.4       | N     |         |
| 0.19950            | 34.6          | 25.1         | 13.2                    | 47.8         | 38.3         | 63.6         | 53.6         | 15.8       | 15.3       | N     |         |
| 0.26580            | 29.8          | 21.7         | 13.2                    | 43.0         | 34.9         | 61.2         | 51.2         | 18.2       | 16.3       | N     |         |
| 0.33160            | 24.3          | 17.6         | 13.3                    | 37.6         | 30.9         | 59.4         | 49.4         | 21.8       | 18.5       | N     |         |
| 4.66400            | 14.5          | 6.9          | 13.6                    | 28.1         | 20.5         | 56.0         | 46.0         | 27.9       | 25.5       | N     |         |
| 12.51700           | 21.1          | 14.0         | 14.2                    | 35.3         | 28.2         | 60.0         | 50.0         | 24.7       | 21.8       | N     |         |
| 0.15000            | 30.8          | 8.2          | 13.2                    | 44.0         | 21.4         | 66.0         | 56.0         | 22.0       | 34.6       | L     |         |
| 0.20150            | 34.1          | 17.8         | 13.2                    | 47.3         | 31.0         | 63.5         | 53.5         | 16.2       | 22.5       | L     |         |
| 0.26880            | 27.1          | 11.5         | 13.2                    | 40.3         | 24.7         | 61.2         | 51.2         | 20.9       | 26.5       | L     |         |
| 0.33640            | 24.3          | 13.8         | 13.3                    | 37.6         | 27.1         | 59.3         | 49.3         | 21.7       | 22.2       | L     |         |
| 4.76600            | 15.5          | 4.9          | 13.6                    | 29.1         | 18.5         | 56.0         | 46.0         | 26.9       | 27.5       | L     |         |
| 12.34100           | 24.1          | 15.9         | 14.2                    | 38.3         | 30.1         | 60.0         | 50.0         | 21.7       | 19.9       | L     |         |

CHART : WITH FACTOR, Peak hold data. CALCULATION : RESULT = READING + C.F (LISN + ATTEN + CABLE)  
Except for the above table : adequate margin data below the limits.

## Conducted Emission

|                        |   |
|------------------------|---|
| Test place             | Ise EMC Lab. No.3 Semi Anechoic Chamber |
| Report No.             | 11249046H                               |
| Date                   | April 18, 2016                          |
| Temperature / Humidity | 22 deg. C / 45 % RH                     |
| Engineer               | Shinichi Miyazono                       |
| Mode                   | Tx, Hopping Off, DH5                    |



**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

## Conducted Emission

### DATA OF CONDUCTED EMISSION TEST


UL Japan, Inc. Ise EMC Lab. No.3 Semi Anechoic Chamber  
 Date : 2016/04/18

Report No : 11249046H

Temp./Humi. : 22deg. C / 45% RH  
 Engineer : Shinichi Miyazono

Mode / Remarks : Tx 3DH5 2402MHz

LIMIT : FCC15.207 QP  
FCC15.207 AV




| Frequency<br>[MHz] | Reading Level |              | Corr.<br>Factor<br>[dB] | Results      |              | Limit        |              | Margin     |            | Phase | Comment |
|--------------------|---------------|--------------|-------------------------|--------------|--------------|--------------|--------------|------------|------------|-------|---------|
|                    | QP<br>[dBuV]  | AV<br>[dBuV] |                         | QP<br>[dBuV] | AV<br>[dBuV] | QP<br>[dBuV] | AV<br>[dBuV] | QP<br>[dB] | AV<br>[dB] |       |         |
| 0.15000            | 20.9          | 0.5          | 13.2                    | 34.1         | 13.7         | 66.0         | 56.0         | 31.9       | 42.3       | N     |         |
| 0.19420            | 35.0          | 26.2         | 13.2                    | 48.2         | 39.4         | 63.9         | 53.9         | 15.7       | 14.5       | N     |         |
| 0.25710            | 28.3          | 19.0         | 13.2                    | 41.5         | 32.2         | 61.5         | 51.5         | 20.0       | 19.3       | N     |         |
| 0.31925            | 23.1          | 15.2         | 13.3                    | 36.4         | 28.5         | 59.7         | 49.7         | 23.3       | 21.2       | N     |         |
| 4.61700            | 11.8          | 3.6          | 13.6                    | 25.4         | 17.2         | 56.0         | 46.0         | 30.6       | 28.8       | N     |         |
| 12.62000           | 20.1          | 13.1         | 14.2                    | 34.3         | 27.3         | 60.0         | 50.0         | 25.7       | 22.7       | N     |         |
| 0.15000            | 21.6          | 0.7          | 13.2                    | 34.8         | 13.9         | 66.0         | 56.0         | 31.2       | 42.1       | L     |         |
| 0.19690            | 33.2          | 25.1         | 13.2                    | 46.4         | 38.3         | 63.7         | 53.7         | 17.3       | 15.4       | L     |         |
| 0.26310            | 27.6          | 20.2         | 13.2                    | 40.8         | 33.4         | 61.3         | 51.3         | 20.5       | 17.9       | L     |         |
| 0.39200            | 23.5          | 21.2         | 13.3                    | 36.8         | 34.5         | 58.0         | 48.0         | 21.2       | 13.5       | L     |         |
| 4.89080            | 14.3          | 3.7          | 13.6                    | 27.9         | 17.3         | 56.0         | 46.0         | 28.1       | 28.7       | L     |         |
| 12.82200           | 21.5          | 14.9         | 14.2                    | 35.7         | 29.1         | 60.0         | 50.0         | 24.3       | 20.9       | L     |         |

CHART : WITH FACTOR, Peak hold data. CALCULATION : RESULT = READING + C.F (LISN + ATTN + CABLE)  
 Except for the above table : adequate margin data below the limits.

## Conducted Emission

|                        |   |
|------------------------|---|
| Test place             | Ise EMC Lab. No.3 Semi Anechoic Chamber |
| Report No.             | 11249046H                               |
| Date                   | April 18, 2016                          |
| Temperature / Humidity | 22 deg. C / 45 % RH                     |
| Engineer               | Shinichi Miyazono                       |
| Mode                   | Tx, Hopping Off, 3DH5                   |



**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

## 20dB Bandwidth and Carrier Frequency Separation


Test place Ise EMC Lab. No.3 Measurement Room  
Report No. 11249046H  
Date April 19, 2016  
Temperature / Humidity 22 deg. C / 35 % RH  
Engineer Shinichi Miyazono  
Mode Tx, Hopping On/Off

| Mode | Freq.<br>[MHz] | 20dB Bandwidth<br>[MHz] | Carrier Frequency<br>Separation<br>[MHz] | Limit for Carrier<br>Frequency separation<br>[MHz] |
|------|----------------|-------------------------|--|--|
| DH5  | 2402.0         | 0.945                   | 1.000                                    | $\geq 0.630$                                       |
| DH5  | 2441.0         | 0.947                   | 1.000                                    | $\geq 0.631$                                       |
| DH5  | 2480.0         | 0.946                   | 1.000                                    | $\geq 0.631$                                       |
| 3DH5 | 2402.0         | 1.297                   | 1.000                                    | $\geq 0.865$                                       |
| 3DH5 | 2441.0         | 1.299                   | 1.000                                    | $\geq 0.866$                                       |
| 3DH5 | 2480.0         | 1.297                   | 1.000                                    | $\geq 0.865$                                       |

Limit: Two-thirds of 20dB Bandwidth or 25kHz (whichever is greater).

No limit applies to 20dB Bandwidth.

**20dB Bandwidth and Carrier Frequency Separation**



**UL Japan, Inc.**


**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

**20dB Bandwidth and Carrier Frequency Separation**



**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124


### Number of Hopping Frequency

Test place Ise EMC Lab. No.4 Measurement Room  
Report No. 11249046H  
Date April 19, 2016  
Temperature / Humidity 22 deg. C / 35% RH  
Engineer Shinichi Miyazono  
Mode Tx, Hopping On

| Mode | Number of channel<br>[channels] | Limit<br>[channels] |
|------|---------------------------------|---------------------|
| DH5  | 79                              | $\geq 15$           |
| 3DH5 | 79                              | $\geq 15$           |

Test was not performed at AFH mode whose number of hopping channel is 20 channels because this Bluetooth radio is in compliance of Bluetooth Specification.

**Number of Hopping Frequency**



### Dwell time

|                        |                                    |
|------------------------|------------------------------------|
| Test place             | Ise EMC Lab. No.4 Measurement Room |
| Report No.             | 11249046H                          |
| Date                   | April 19, 2016                     |
| Temperature / Humidity | 22 deg. C / 35 % RH                |
| Engineer               | Shinichi Miyazono                  |
| Mode                   | Tx, Hopping On                     |

| Mode | Number of transmission<br>in a 31.6(79 Hopping x 0.4)<br>/ 12.8 (32 Hopping x 0.4) second period | Length of<br>transmission<br>[msec] | Result<br>[msec] | Limit<br>[msec] |
|------|--|-------------------------------------|------------------|-----------------|
| DH1  | 50.0 times / 5 sec. x 31.6 sec. = 316 times  | 0.404                               | 128              | 400             |
| DH3  | 25.4 times / 5 sec. x 31.6 sec. = 161 times  | 1.662                               | 268              | 400             |
| DH5  | 17.4 times / 5 sec. x 31.6 sec. = 110 times  | 2.925                               | 322              | 400             |
| 3DH1 | 51.4 times / 5 sec. x 31.6 sec. = 325 times  | 0.414                               | 135              | 400             |
| 3DH3 | 26.0 times / 5 sec. x 31.6 sec. = 165 times  | 1.668                               | 275              | 400             |
| 3DH5 | 20.2 times / 5 sec. x 31.6 sec. = 128 times  | 2.930                               | 375              | 400             |

Sample Calculation

Result = Number of transmission x Length of transmission

\*Average data of 5 tests.(except Inquiry)


| Mode | Sampling [times] |    |    |    |    | Average<br>[times] |
|------|------------------|----|----|----|----|--------------------|
|      | 1                | 2  | 3  | 4  | 5  |                    |
| DH1  | 50               | 49 | 52 | 50 | 49 | 50                 |
| DH3  | 25               | 28 | 27 | 23 | 24 | 25.4               |
| DH5  | 18               | 20 | 18 | 15 | 16 | 17.4               |
| 3DH1 | 51               | 52 | 51 | 51 | 52 | 51.4               |
| 3DH3 | 26               | 24 | 29 | 23 | 28 | 26                 |
| 3DH5 | 18               | 18 | 24 | 22 | 19 | 20.2               |

Sample Calculation

Average = Summation (Sampling 1 to 5) / 5

This device complies with the Bluetooth protocol for FHSS operation, employing a pseudo random channel selection and hopping rate to ensure that the occupancy time in  $N \times 0.4s$ , where  $N$  is the number of channels being used in the hopping sequence ( $20 \leq N \leq 79$ ), is always less than  $0.4s$  regardless of packet size. This is confirmed in the test report for  $N = 79$ .

**Dwell time**



**UL Japan, Inc.**


**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

**Dwell time**



**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

## Maximum Peak Output Power

Test place : Ise EMC Lab. No.4 Measurement Room  
Report No. : 11249046H  
Date : April 19, 2016  
Temperature / Humidity : 22 deg. C / 35% RH  
Engineer : Shinichi Miyazono  
Mode : Tx, Hopping Off

| Mode | Freq.<br>[MHz] | Reading<br>[dBm] | Cable<br>Loss<br>[dB] | Atten.<br>Loss<br>[dB] | Result |      | Limit |      | Margin<br>[dB] |
|------|----------------|------------------|-----------------------|------------------------|--------|------|-------|------|----------------|
|      |                |                  |                       |                        | [dBm]  | [mW] | [dBm] | [mW] |                |
| DH5  | 2402.0         | 0.37             | 0.80                  | 0.00                   | 1.17   | 1.31 | 20.96 | 125  | 19.79          |
| DH5  | 2441.0         | 0.20             | 0.80                  | 0.00                   | 1.00   | 1.26 | 20.96 | 125  | 19.96          |
| DH5  | 2480.0         | 0.13             | 0.80                  | 0.00                   | 0.93   | 1.24 | 20.96 | 125  | 20.03          |
| 2DH5 | 2402.0         | 2.83             | 0.80                  | 0.00                   | 3.63   | 2.31 | 20.96 | 125  | 17.33          |
| 2DH5 | 2441.0         | 2.68             | 0.80                  | 0.00                   | 3.48   | 2.23 | 20.96 | 125  | 17.48          |
| 2DH5 | 2480.0         | 2.62             | 0.80                  | 0.00                   | 3.42   | 2.20 | 20.96 | 125  | 17.54          |
| 3DH5 | 2402.0         | 3.26             | 0.80                  | 0.00                   | 4.06   | 2.55 | 20.96 | 125  | 16.90          |
| 3DH5 | 2441.0         | 3.10             | 0.80                  | 0.00                   | 3.90   | 2.45 | 20.96 | 125  | 17.06          |
| 3DH5 | 2480.0         | 3.08             | 0.80                  | 0.00                   | 3.88   | 2.44 | 20.96 | 125  | 17.08          |

Sample Calculation:

Result = Reading + Cable Loss (including the cable(s) customer supplied) + Attenuator Loss

\*The equipment and cables were not used for factor 0 dB of the data sheets.

Test was not performed at AFH mode, because the decrease of number of channel (min: 20ch) at AFH mode does not influence on the output power and bandwidth of the EUT.

As this device had AFH mode and frequency separation could not meet the requirement of over 20dB BW without 2/3 relaxation, 125mW power limit was applied to it.

**Average Output Power**  
**(Reference data for RF Exposure / SAR testing)**

Test place : Ise EMC Lab. No.4 Measurement Room  
Report No. : 11249046H  
Date : April 19, 2016  
Temperature / Humidity : 22 deg. C / 35% RH  
Engineer : Shinichi Miyazono  
Mode : Tx, Hopping Off

| Mode | Freq.<br>[MHz] | Reading<br>[dBm] | Cable<br>Loss<br>[dB] | Atten.<br>Loss<br>[dB] | Result<br>(Time average) |      |
|------|----------------|------------------|-----------------------|------------------------|--------------------------|------|
|      |                |                  |                       |                        | [dBm]                    | [mW] |
| DH5  | 2402.0         | -1.13            | 0.80                  | 0.00                   | -0.33                    | 0.93 |
| DH5  | 2441.0         | -1.34            | 0.80                  | 0.00                   | -0.54                    | 0.88 |
| DH5  | 2480.0         | -1.39            | 0.80                  | 0.00                   | -0.59                    | 0.87 |
| 2DH5 | 2402.0         | -0.86            | 0.80                  | 0.00                   | -0.06                    | 0.99 |
| 2DH5 | 2441.0         | -1.14            | 0.80                  | 0.00                   | -0.34                    | 0.92 |
| 2DH5 | 2480.0         | -1.16            | 0.80                  | 0.00                   | -0.36                    | 0.92 |
| 3DH5 | 2402.0         | -0.84            | 0.80                  | 0.00                   | -0.04                    | 0.99 |
| 3DH5 | 2441.0         | -1.09            | 0.80                  | 0.00                   | -0.29                    | 0.94 |
| 3DH5 | 2480.0         | -1.11            | 0.80                  | 0.00                   | -0.31                    | 0.93 |

Sample Calculation:


Result (Time average) = Reading + Cable Loss (including the cable(s) customer supplied) + Attenuator Loss

\*The equipment and cables were not used for factor 0 dB of the data sheets.


### Burst Rate Confirmation

|                        |                                    |
|------------------------|------------------------------------|
| Test place             | Ise EMC Lab. No.4 Measurement Room |
| Report No.             | 11249046H                          |
| Date                   | April 19, 2016                     |
| Temperature / Humidity | 22 deg. C / 35 % RH                |
| Engineer               | Shinichi Miyazono                  |
| Mode                   | Tx, Hopping Off                    |


#### DH5



#### 2DH5





#### 3DH5





**Radiated Spurious Emission**  
**(Reference Plot for band-edge)**

|                        |   |
|------------------------|---|
| Test place             | Ise EMC Lab. No.3 Semi Anechoic Chamber |
| Report No.             | 11249046H                               |
| Date                   | April 15, 2016                          |
| Temperature / Humidity | 21 deg. C / 40 % RH                     |
| Engineer               | Tomoki Matsui<br>(1-10GHz)              |
| Mode                   | Tx, Hopping Off, DH5 2402 MHz           |





\* Final result of restricted band edge was shown in tabular data.





**Radiated Spurious Emission**  
**(Reference Plot for band-edge)**

|                        |   |
|------------------------|---|
| Test place             | Ise EMC Lab. No.3 Semi Anechoic Chamber |
| Report No.             | 11249046H                               |
| Date                   | April 15, 2016                          |
| Temperature / Humidity | 21 deg. C / 40 % RH                     |
| Engineer               | Yuta Moriya<br>(1-10GHz)                |
| Mode                   | Tx, Hopping Off, DH5 2480 MHz           |



\* Final result of restricted band edge was shown in tabular data.

## Radiated Spurious Emission

Test place : Ise EMC Lab. No.3 Semi Anechoic Chamber  
Report No. : 11249046H  
Date : April 15, 2016                      April 18, 2016  
Temperature / Humidity : 21 deg. C / 40 % RH      20 deg. C / 55 % RH  
Engineer : Yuta Moriya                      Yuta Moriya  
                  (1-10GHz)                      (Above 10GHz and Below 1GHz)  
Mode : Tx, Hopping Off, 3DH5 2402 MHz

| Polarity | Frequency [MHz] | Detector | Reading [dBuV] | Ant.Fac. [dB/m] | Loss [dB] | Gain [dB] | Result [dBuV/m] | Limit [dBuV/m] | Margin [dB] | Remark      |
|----------|-----------------|----------|----------------|-----------------|-----------|-----------|-----------------|----------------|-------------|-------------|
| Hori     | 35.933          | QP       | 22.5           | 15.3            | 7.1       | 32.2      | 12.7            | 40.0           | 27.3        |             |
| Hori     | 120.100         | QP       | 30.6           | 12.4            | 8.3       | 32.2      | 19.1            | 43.5           | 24.4        |             |
| Hori     | 168.000         | QP       | 27.9           | 15.7            | 8.7       | 32.1      | 20.2            | 43.5           | 23.3        |             |
| Hori     | 216.000         | QP       | 30.2           | 11.8            | 9.2       | 32.0      | 19.2            | 43.5           | 24.3        |             |
| Hori     | 408.022         | QP       | 32.0           | 15.8            | 10.6      | 31.9      | 26.5            | 46.0           | 19.5        |             |
| Hori     | 799.772         | QP       | 22.7           | 20.8            | 12.9      | 31.5      | 24.9            | 46.0           | 21.1        |             |
| Hori     | 2390.000        | PK       | 42.4           | 26.9            | 6.8       | 32.7      | 43.4            | 73.9           | 30.5        |             |
| Hori     | 4804.000        | PK       | 38.9           | 31.8            | 9.0       | 31.8      | 47.9            | 73.9           | 26.0        | Floor Noise |
| Hori     | 7206.000        | PK       | 40.9           | 36.0            | 10.2      | 32.6      | 54.5            | 73.9           | 19.4        | Floor Noise |
| Hori     | 9608.000        | PK       | 41.0           | 38.2            | 11.0      | 33.2      | 57.0            | 73.9           | 16.9        | Floor Noise |
| Hori     | 2390.000        | AV       | 29.6           | 26.9            | 6.8       | 32.7      | 30.6            | 53.9           | 23.3        |             |
| Hori     | 4804.000        | AV       | 27.5           | 31.8            | 9.0       | 31.8      | 36.5            | 53.9           | 17.4        | Floor Noise |
| Hori     | 7206.000        | AV       | 28.3           | 36.0            | 10.2      | 32.6      | 41.9            | 53.9           | 12.0        | Floor Noise |
| Hori     | 9608.000        | AV       | 29.3           | 38.2            | 11.0      | 33.2      | 45.3            | 53.9           | 8.6         | Floor Noise |
| Vert     | 35.933          | QP       | 33.2           | 15.3            | 7.1       | 32.2      | 23.4            | 40.0           | 16.6        |             |
| Vert     | 120.100         | QP       | 37.2           | 12.4            | 8.3       | 32.2      | 25.7            | 43.5           | 17.8        |             |
| Vert     | 168.000         | QP       | 35.1           | 15.7            | 8.7       | 32.1      | 27.4            | 43.5           | 16.1        |             |
| Vert     | 216.000         | QP       | 36.1           | 11.8            | 9.2       | 32.0      | 25.1            | 43.5           | 18.4        |             |
| Vert     | 408.022         | QP       | 26.7           | 15.8            | 10.6      | 31.9      | 21.2            | 46.0           | 24.8        |             |
| Vert     | 799.772         | QP       | 26.7           | 20.8            | 12.9      | 31.5      | 28.9            | 46.0           | 17.1        |             |
| Vert     | 2390.000        | PK       | 42.0           | 26.9            | 6.8       | 32.7      | 43.0            | 73.9           | 30.9        |             |
| Vert     | 4804.000        | PK       | 39.3           | 31.8            | 9.0       | 31.8      | 48.3            | 73.9           | 25.6        | Floor Noise |
| Vert     | 7206.000        | PK       | 40.7           | 36.0            | 10.2      | 32.6      | 54.3            | 73.9           | 19.6        | Floor Noise |
| Vert     | 9608.000        | PK       | 41.0           | 38.2            | 11.0      | 33.2      | 57.0            | 73.9           | 16.9        | Floor Noise |
| Vert     | 2390.000        | AV       | 29.9           | 26.9            | 6.8       | 32.7      | 30.9            | 53.9           | 23.0        |             |
| Vert     | 4804.000        | AV       | 27.3           | 31.8            | 9.0       | 31.8      | 36.3            | 53.9           | 17.6        | Floor Noise |
| Vert     | 7206.000        | AV       | 28.4           | 36.0            | 10.2      | 32.6      | 42.0            | 53.9           | 11.9        | Floor Noise |
| Vert     | 9608.000        | AV       | 29.3           | 38.2            | 11.0      | 33.2      | 45.3            | 53.9           | 8.6         | Floor Noise |

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier)

\*Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).

Distance factor:      1 GHz - 10 GHz      20log (4.5 m / 3.0 m) = 3.52 dB  
                                  10 GHz - 26.5 GHz 20log (1.0 m / 3.0 m) = -9.5 dB

### 20dBc Data Sheet



| Polarity | Frequency [MHz] | Detector | Reading [dBuV] | Ant Factor [dB/m] | Loss [dB] | Gain [dB] | Result [dBuV/m] | Limit [dBuV/m] | Margin [dB] | Remark  |
|----------|-----------------|----------|----------------|-------------------|-----------|-----------|-----------------|----------------|-------------|---------|
| Hori     | 2402.000        | PK       | 93.7           | 26.9              | 6.8       | 32.7      | 94.7            | -              | -           | Carrier |
| Hori     | 2400.000        | PK       | 37.5           | 26.9              | 6.8       | 32.7      | 38.5            | 74.7           | 36.2        |         |
| Vert     | 2402.000        | PK       | 94.8           | 26.9              | 6.8       | 32.7      | 95.8            | -              | -           | Carrier |
| Vert     | 2400.000        | PK       | 37.9           | 26.9              | 6.8       | 32.7      | 38.9            | 75.8           | 36.9        |         |

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier)

**\*These results have sufficient margin without taking account Dwell time factor.**

**Radiated Spurious Emission**  
**(Reference Plot for band-edge)**

|                        |   |
|------------------------|---|
| Test place             | Ise EMC Lab. No.3 Semi Anechoic Chamber |
| Report No.             | 11249046H                               |
| Date                   | April 15, 2016                          |
| Temperature / Humidity | 21 deg. C / 40 % RH                     |
| Engineer               | Yuta Moriya<br>(1-10GHz)                |
| Mode                   | Tx, Hopping Off, 3DH5 2402 MHz          |





\* Final result of restricted band edge was shown in tabular data.





**Radiated Spurious Emission**  
**(Reference Plot for band-edge)**



Test place : Ise EMC Lab. No.3 Semi Anechoic Chamber  
Report No. : 11249046H  
Date : April 15, 2016  
Temperature / Humidity : 21 deg. C / 40 % RH  
Engineer : Yuta Moriya  
(1-10GHz)  
Mode : Tx, Hopping Off, 3DH5 2480 MHz



\* Final result of restricted band edge was shown in tabular data.

**Radiated Spurious Emission**  
**(Plot data, Worst case)**

|                        |   |                              |
|------------------------|---|------------------------------|
| Test place             | Ise EMC Lab. No.3 Semi Anechoic Chamber |                              |
| Report No.             | 11249046H                               |                              |
| Date                   | April 15, 2016                          | April 18, 2016               |
| Temperature / Humidity | 21 deg. C / 40 % RH                     | 20 deg. C / 55 % RH          |
| Engineer               | Yuta Moriya                             | Yuta Moriya                  |
|                        | (1-10GHz)                               | (Above 10GHz and Below 1GHz) |
| Mode                   | Tx, Hopping Off, 3DH5 2402 MHz          |                              |





\*These plots data contains sufficient number to show the trend of characteristic features for EUT.

## Conducted Spurious Emission

|                        |                                    |
|------------------------|------------------------------------|
| Test place             | Ise EMC Lab. No.4 Measurement Room |
| Report No.             | 11249046H                          |
| Date                   | April 19, 2016                     |
| Temperature / Humidity | 22 deg. C / 35% RH                 |
| Engineer               | Shinichi Miyazono                  |
| Mode                   | Tx, Hopping Off, DH5               |



### 2402 MHz



## Conducted Spurious Emission

|                        |                                    |
|------------------------|------------------------------------|
| Test place             | Ise EMC Lab. No.4 Measurement Room |
| Report No.             | 11249046H                          |
| Date                   | April 19, 2016                     |
| Temperature / Humidity | 22 deg. C / 35% RH                 |
| Engineer               | Shinichi Miyazono                  |
| Mode                   | Tx, Hopping Off, DH5               |



### 2441 MHz



## Conducted Spurious Emission

|                        |                                    |
|------------------------|------------------------------------|
| Test place             | Ise EMC Lab. No.4 Measurement Room |
| Report No.             | 11249046H                          |
| Date                   | April 19, 2016                     |
| Temperature / Humidity | 22 deg. C / 35% RH                 |
| Engineer               | Shinichi Miyazono                  |
| Mode                   | Tx, Hopping Off, DH5               |



### 2480 MHz



## Conducted Spurious Emission

|                        |                                    |
|------------------------|------------------------------------|
| Test place             | Ise EMC Lab. No.4 Measurement Room |
| Report No.             | 11249046H                          |
| Date                   | April 19, 2016                     |
| Temperature / Humidity | 22 deg. C / 35% RH                 |
| Engineer               | Shinichi Miyazono                  |
| Mode                   | Tx, Hopping Off, 3DH5              |



### 2402 MHz



## Conducted Spurious Emission

|                        |                                    |
|------------------------|------------------------------------|
| Test place             | Ise EMC Lab. No.4 Measurement Room |
| Report No.             | 11249046H                          |
| Date                   | April 19, 2016                     |
| Temperature / Humidity | 22 deg. C / 35% RH                 |
| Engineer               | Shinichi Miyazono                  |
| Mode                   | Tx, Hopping Off, 3DH5              |



### 2441 MHz



## Conducted Spurious Emission

|                        |                                    |
|------------------------|------------------------------------|
| Test place             | Ise EMC Lab. No.4 Measurement Room |
| Report No.             | 11249046H                          |
| Date                   | April 19, 2016                     |
| Temperature / Humidity | 22 deg. C / 35% RH                 |
| Engineer               | Shinichi Miyazono                  |
| Mode                   | Tx, Hopping Off, 3DH5              |


### 2480 MHz




## Conducted Emission Band Edge compliance

|                        |                                    |
|------------------------|------------------------------------|
| Test place             | Ise EMC Lab. No.4 Measurement Room |
| Report No.             | 11249046H                          |
| Date                   | April 19, 2016                     |
| Temperature / Humidity | 22 deg. C / 35% RH                 |
| Engineer               | Shinichi Miyazono                  |
| Mode                   | Tx DH5                             |

### Hopping On




### Hopping Off




## Conducted Emission Band Edge compliance

|                        |                                    |
|------------------------|------------------------------------|
| Test place             | Ise EMC Lab. No.4 Measurement Room |
| Report No.             | 11249046H                          |
| Date                   | April 19, 2016                     |
| Temperature / Humidity | 22 deg. C / 35% RH                 |
| Engineer               | Shinichi Miyazono                  |
| Mode                   | Tx 3DH5                            |

### Hopping On



### Hopping Off



**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN


Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124


## 99%Occupied Bandwidth

|                        |                                    |
|------------------------|------------------------------------|
| Test place             | Ise EMC Lab. No.4 Measurement Room |
| Report No.             | 11249046H                          |
| Date                   | April 19, 2016                     |
| Temperature / Humidity | 22 deg. C / 35% RH                 |
| Engineer               | Shinichi Miyazono                  |
| Mode                   | Tx Hopping Off                     |


### Hopping Off, DH5




### Hopping Off, 3DH5




### 2441 MHz




### 2441 MHz



### 2480 MHz



### 2480 MHz



**UL Japan, Inc.**

**Ise EMC Lab.**


4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

## 99% Occupied Bandwidth

|                        |                                    |
|------------------------|------------------------------------|
| Test place             | Ise EMC Lab. No.4 Measurement Room |
| Report No.             | 11249046H                          |
| Date                   | April 19, 2016                     |
| Temperature / Humidity | 22 deg. C / 35% RH                 |
| Engineer               | Shinichi Miyazono                  |
| Mode                   | Tx Hopping On                      |



## **APPENDIX 2: Test instruments**

### **Test equipment**

| Control No. | Instrument                       | Manufacturer         | Model No  | Serial No                   | Test Item | Calibration Date *<br>Interval(month) |
|-------------|----------------------------------|----------------------|---|-----------------------------|-----------|---------------------------------------|
| MAEC-03     | Semi Anechoic Chamber(NSA)       | TDK                  | Semi Anechoic Chamber 3m  | DA-10005                    | RE/CE     | 2015/10/01 * 12                       |
| MOS-13      | Thermo-Hygrometer                | Custom               | CTH-180   | 1301                        | RE/CE     | 2016/01/21 * 12                       |
| MJM-16      | Measure                          | KOMELON              | KMC-36  | -                           | RE/CE     | -                                     |
| COTS-MEMI   | EMI measurement program          | TSJ                  | TEPTO-DV  | -                           | RE/CE     | -                                     |
| MSA-10      | Spectrum Analyzer                | Agilent              | E4448A  | MY46180655                  | RE/CE/AT  | 2016/02/24 * 12                       |
| MHA-20      | Horn Antenna 1-18GHz             | Schwarzbeck          | BBHA9120D   | 258                         | RE        | 2015/05/18 * 12                       |
| MCC-167     | Microwave Cable                  | Junkosha             | MWX221  | 1404S374(1m) / 1405S074(5m) | RE        | 2015/05/21 * 12                       |
| MPA-11      | MicroWave System Amplifier       | Agilent              | 83017A  | MY39500779                  | RE        | 2016/03/24 * 12                       |
| MMM-08      | DIGITAL HiTESTER                 | Hioki                | 3805  | 051201197                   | RE/CE     | 2016/01/13 * 12                       |
| MHF-25      | High Pass Filter 3.5-18.0GHz     | UL Japan             | HPF SELECTOR  | 001                         | RE        | 2015/09/16 * 12                       |
| MHA-16      | Horn Antenna 15-40GHz            | Schwarzbeck          | BBHA9170  | BBHA9170306                 | RE        | 2015/05/19 * 12                       |
| MTR-08      | Test Receiver                    | Rohde & Schwarz      | ESCI  | 100767                      | RE/CE     | 2015/09/02 * 12                       |
| MBA-03      | Biconical Antenna                | Schwarzbeck          | BBA9106   | 1915                        | RE        | 2015/10/11 * 12                       |
| MLA-22      | Logperiodic Antenna(200-1000MHz) | Schwarzbeck          | VUSLP9111B  | 911B-191                    | RE        | 2016/01/30 * 12                       |
| MCC-51      | Coaxial cable                    | UL Japan             | -   | -                           | RE        | 2015/07/13 * 12                       |
| MAT-70      | Attenuator(6dB)                  | Agilent              | 8491A-006   | MY52460153                  | RE        | 2016/04/05 * 12                       |
| MPA-13      | Pre Amplifier                    | SONOMA INSTRUMENT    | 310   | 260834                      | RE        | 2016/03/24 * 12                       |
| MLS-23      | LISN(AMN)                        | Schwarzbeck          | NSLK8127  | 8127-729                    | CE(EUT)   | 2015/07/10 * 12                       |
| MTA-31      | Terminator                       | TME                  | CT-01   | -                           | CE        | 2016/01/12 * 12                       |
| MCC-112     | Coaxial cable                    | Fujikura/Suhner/TSJ  | 5D-2W(10m)/SFM141(3m)/suciform141-PE(1m)/421-010(1.5m)/RFM-E321(Switcher) | -/00640                     | CE        | 2015/07/02 * 12                       |
| MAT-66      | Attenuator(13dB)                 | JFW Industries, Inc. | 50FP-013H2 N  | -                           | CE        | 2016/01/14 * 12                       |
| MOS-29      | Thermo-Hygrometer                | Custom               | CTH-201   | 2901                        | AT        | 2016/01/21 * 12                       |
| MAT-92      | Attenuator                       | Weinschel Associates | WA56-10   | 56100308                    | AT        | 2015/06/01 * 12                       |
| MCC-138     | Microwave cable                  | HUBER+SUHNER         | SUCOFLEX 102  | 37953/2                     | AT        | 2015/10/08 * 12                       |
| MPM-13      | Power Meter                      | Anritsu              | ML2495A   | 0824014                     | AT        | 2015/11/11 * 12                       |
| MPSE-18     | Power sensor                     | Anritsu              | MA2411B   | 0738174                     | AT        | 2015/11/11 * 12                       |

**The expiration date of the calibration is the end of the expired month.**

**All equipment is calibrated with valid calibrations. Each measurement data is traceable to the national or international standards.**

**As for some calibrations performed after the tested dates, those test equipment have been controlled by means of an unbroken chains of calibrations.**

**Test Item:**  
**CE: Conducted Emission test**  
**RE: Radiated Emission test**  
**AT: Antenna Terminal Conducted test**

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124