

EMI TEST REPORT


Test Report No. : 23BE0019-HO-9

Applicant : Sony Corporation
Type of Equipment : Digital Still Camera
Model No. : DKC-C200X
Test standard : FCC Part 15 Subpart C Section 15.207, Section 15.247
FCC ID : AK8DKCC200X
Test Result : Complied

1. This test report shall not be reproduced in full or partial, without the written approval of A-Pex International Co., Ltd.
2. The results in this report apply only to the sample tested.
3. This equipment is in compliance with above regulation. We hereby certify that the data contain a true representation of the EMC profile.
4. The test results in this report are traceable to the national or international standards.
5. This test report does not constitute an endorsement by NIST/NVLAP or U.S. Government.

Date of test : January 8, 9, 10 and 14, 2003

Tested by : 
Hiroka Umeyama
EMC Head Office Division

Approved by : 
Hironobu Shimoji
Group Leader of EMC Head Office Division

A-Pex International Co., Ltd.
EMC Head Office Division.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN
Telephone: +81 596 24 8116 Facsimile: +81 596 24 8124

MF060b(23.04.02)

CONTENTS

	PAGE
SECTION 1: Client information	3
SECTION 2: Equipment under test (E.U.T.)	3
SECTION 3: Test specification, procedures and results	5
SECTION 4: Operation of E.U.T. during testing	7
SECTION 5: Conducted Emission, Section 15.207	9
SECTION 6: Carrier Frequency Separation, Section 15.247 (a)(1)	9
SECTION 7: 20dB Bandwidth, Section 15.247(a)(1)	10
SECTION 8: Number of Hopping Frequency, Section 15.247(a)(1)(iii)	10
SECTION 9: Dwell time, Section 15.247(a)(1)(iii)	10
SECTION 10: Maximum Peak Output Power, Section 15.247(b)(1)	10
SECTION 11: Band Edge Compliance, Section 15.247(c)	11
SECTION 12: Spurious Emission , Section 15.247(c)	11
APPENDIX 1: Photographs of test setup	12
APPENDIX 2: Test instruments	12
APPENDIX 3: Data of EMI test	12

SECTION 1: Client information

Company name : Sony Corporation
Brand name : SONY
Address : 6-7-35 Kitashinagawa, Shinagawa-ku, Tokyo 141-0001 JAPAN
Telephone Number : +81-46-230-5603
Facsimile Number : +81-46-230-6354
Contact Person : Kazuo Aihara

SECTION 2: Equipment under test (E.U.T.)

2.1 Identification of E.U.T.

Type of Equipment : Digital Still Camera
Model No. : DKC-C200X
Serial No. : 59810047, 59810048
Rating : DKC-C200X : AC Adaptor (DC+8.4V), Ni-MH Battery (DC + 4.8V)
Alkaline Battery (DC+6V)
Country of Manufacture : Japan
Receipt Date of Sample : January 6, 2003
Condition of EUT : Production prototype

2.2 Product Description

Model: DKC-C200X (referred to as the EUT in this report) is the Digital Still Camera.

The clock frequency used in EUT is 96.016044MHz (ASIC), 48.008022MHz(USB), 14.31818MHz(NTSC), 17.734450MHz (PAL).

A-Pex International Co., Ltd.

EMC Head Office Division.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8116 Facsimile: +81 596 24 8124

Equipment Type : Transceiver
Frequency characteristics : from 2400 MHz to 2483.5 MHz
Number of channels and spacing : 79 channels / 1MHz
Modulation : GFSK
Antenna Gain : Max: 3.56dBi, AVG: -3.40dBi
Antenna Type : External Ground, Ceramic chip, lambda/4, YCE-5226 (Yokowo)
Temperature Range : 5 degree C. to 35 degree C.
ITU code : F1D

***FCC Part 15.31(e) Verification of Input Power:**

The host device DKC-C200X provide the stable power-supply (DC 8.4/4.8/6V); and the Digital Still Camera complies power supply regulation.

***FCC Part 15.203 Antenna requirement**

The antenna built in the DKC-C200X is a chip antenna and is permanently mounted by soldering on a printed electronic circuit board in DKC-C200X. It is impossible for end users to replace it, because a special tool is necessary for removal of the antenna.

A-Pex International Co., Ltd.

EMC Head Office Division.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8116 Facsimile: +81 596 24 8124

SECTION 3: Test specification, procedures and results

3.1 Test Specification

Test Specification : FCC Part 15 Subpart C Section 15.207 and Section 15.247
Title : FCC 47CFR Part 15 Radio Frequency Device Subpart C Intentional Radiators
Section 15.207 Conducted emission limits; general requirements
Section 15.247 Operation within the bands 902-928MHz, 2400-2483.5MHz,
5725-5850MHz

3.2 Procedures and results

No.	Item	Test Procedure	Specification	Remarks	Deviation	Worst margin	Results
1	Conducted Emission	ANSI C63.4:2001	Section 15.207	N/A	N/A	19.7dB 0.2715MHz, L1	Complied
2	Carrier Frequency Separation	ANSI C63.4:2001	Section 15.247(a)(1)	Conducted	N/A	N/A	Complied
3	20dB Bandwidth	ANSI C63.4:2001	Section 15.247(a)(1)	Conducted	N/A	N/A	Complied
4	Number of Hopping Frequency	ANSI C63.4:2001	Section 15.247(a)(1)(iii)	Conducted	N/A	N/A	Complied
5	Dwell time	ANSI C63.4:2001	Section 15.247(a)(1)(iii)	Conducted	N/A	N/A	Complied
6	Maximum Peak Output Power	ANSI C63.4:2001	Section 15.247(b)(1)	Conducted	N/A	N/A	Complied
7	Band Edge Compliance	ANSI C63.4:2001	Section 15.247(c)	Conducted	N/A	N/A	Complied
8	Spurious Emission	ANSI C63.4:2001	Section 15.247(c)	Conducted / Radiated	N/A	5.9dB 288.05MHz Horizontal	Complied

These tests were also referred to FCC Public Notice DA 00-705 "Guidance on Measurement for Frequency Hopping Spread Spectrum Systems.

3.3 Additions to standards

No addition, deviation or exclusion has been made from standards.

3.4 Confirmation

A-Pex International Co., Ltd. hereby confirms that E.U.T. , in the configuration tested, complies with the specifications FCC Part 15 Subpart C Section 15.207 and Section 15.247.

3.5 Uncertainty

Conducted Emission

The measurement uncertainty (with a 95% confidence level) for this test was ± 1.3 dB.

The data listed in this test report has enough margin, more than the site margin.

Spurious Emission(Radiated)

The measurement uncertainty (with a 95% confidence level) for this test using Biconical antenna is ± 4.5 dB.

The measurement uncertainty (with a 95% confidence level) for this test using Logperiodic antenna is ± 5.2 dB.

The measurement uncertainty (with a 95% confidence level) for this test using Horn antenna is ± 6.6 dB.

The data listed in this test report may exceed the test limit because it does not have enough margin.

Other test except Conducted Emission and Spurious Emission(Radiated)

The measurement uncertainty (with a 95% confidence level) for this test was ± 3.0 dB.

The data listed in this test report has enough margin.

3.6 Test Location

A-Pex International Co., Ltd. EMC Head Office Division.

No.1 semi anechoic chamber, 19.2 x 11.2 x 7.7m.and No.2 semi anechoic chamber, 7.5 x 5.8 x 5.2m.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8116 Facsimile: +81 596 24 8124

This site has been fully described in a report submitted to FCC office, and listed on February 01, 2002 / June 05, 2002 (Registration number: 313583 / 846015).

*NVLAP Lab. code: 200572-0

3.7 Test setup, Data of EMI and Test instruments

Refer to Appendix 1 to 3.

A-Pex International Co., Ltd.

EMC Head Office Division.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8116 Facsimile: +81 596 24 8124

SECTION 4: Operation of E.U.T. during testing

4.1 Operating Modes

The EUT exercise program used during radiated testing was designed to exercise the various system components in a manner similar to typical use.

The operating mode/system was as follows:

Operation mode : Transmitting


1. Transmitting mode(2402 MHz)
2. Transmitting mode(2441 MHz)
3. Transmitting mode(2480MHz)
4. Transmitting mode(Hopping on)
5. Inquiry

Justification: The system was configured in typical fashion (as a customer would normally use it) for testing.

4.2 Configuration and peripherals

[Conducted emission and spurious Emission (Radiated)]

DKC-C200X



* Cabling was taken into consideration and test data was taken under worst case conditions.

A-Pex International Co., Ltd.


EMC Head Office Division.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8116 Facsimile: +81 596 24 8124

[Other tests except Conducted Emission and Spurious Emission (Radiated)]

DKC-C200X



Description of EUT and Support equipment

No.	Item	Model number	Serial number	Manufacturer	FCC ID	Remark
A	Digital Photo Camera	DKC-C200X	59810047, 59810048	SONY	AK8DKCC200X	EUT
B	PC	PCV-J21MBP	0003016	SONY	-	-
C	Keyboard	PCVA-KB1P/JA	0140216	SONY	-	-
D	Mouse	X06-8477	4449049	DELL	DoC	-
E	CRT	PCVD-A201	169-0034466	SONY	-	-
F	Loopback Jig	-	-	-	-	-
G	Video Monitor	TM-1010PM	12705390	JVC	-	-
H	Release Switch	1-418-118-11	-	SONY	-	-
I	AC Adaptor	PCS-AC08	21027133	SONY	-	-

List of cables used

No.	Name	Length (m)	Shield	Backshell Material	Remark
2	USB Cable	2.0	Y	Polyvinyl chloride	-
3	Video Cable	2.5	Y	Polyvinyl chloride	-
5	AC Cable	2.0	N	Polyvinyl chloride	-
6	DC Cable	1.5	N	Polyvinyl chloride	-
7	Release Switch Cable	1.0	N	Polyvinyl chloride	-
8	AC Cable	2.0	N	Polyvinyl chloride	-
9	Mouse Cable	1.7	N	Polyvinyl chloride	-
10	Keyboard Cable	1.8	Y	Polyvinyl chloride	
11	AC Cable	2.0	N	Polyvinyl chloride	
12	AC Cable	2.0	N	Polyvinyl chloride	
13	RGB Cable	1.4	Y	Polyvinyl chloride	
14	RS232C Cable	1.5	Y	Polyvinyl chloride	
15	Printer Cable	2.0	Y	Polyvinyl chloride	

A-Pex International Co., Ltd.

EMC Head Office Division.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8116 Facsimile: +81 596 24 8124

SECTION 5: Conducted Emission, Section 15.207

Test Procedure

EUT was placed on a platform of nominal size, 1m by 1.5m, raised 80cm above the conducting ground plane. The rear of tabletop was located 40cm to the vertical conducting plane. The rear of EUT, including peripherals aligned and flushed with rear of tabletop. All other surfaces of tabletop were at least 80cm from any other grounded conducting surface. I/O cables and AC cables that were connected to the peripherals were bundled in center. They were folded back and forth forming a bundle 30cm to 40cm long and were hanged at a 40cm height to the ground plane. Each EUT current-carrying power lead, except the ground (safety) lead, was individually connected through a LISN to the input power source. All unused 50ohm connectors of the LISN were resistively terminated in 50ohm when not connected to the measuring equipment.

The AC Mains Terminal Continuous disturbance Voltage has been measured with the EUT on a reference ground plane 4.0 x 4.0m in a No.2 semi Anechoic Chamber.

The EUT was connected to a Line Impedance Stabilization Network (LISN).

An overview sweep with peak detection has been performed.

The measurements have been performed with a CISPR quasi-peak detector (IF BW 9 kHz).

Measurement range: 0.15-30MHz

Test data : **APPENDIX 2**
Test result : **Pass**
Test instruments : **MTR-02, MSA-02, MCC-13, MLS-06, MLS-07, MTA-01, MPL-01**

SECTION 6: Carrier Frequency Separation , Section 15.247(a)(1)

Test Procedure

The carrier frequency separation was measured with a spectrum analyzer connected to the antenna port.

Test data : **APPENDIX 2**
Test result : **Pass**
Test instruments : **MTR-01, MCC-05**

A-Pex International Co., Ltd.

EMC Head Office Division.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8116 Facsimile: +81 596 24 8124

SECTION 7: 20dB Bandwidth , Section 15.247(a)(1)

Test Procedure

The 20dB bandwidth was measured with a spectrum analyzer connected to the antenna port.

Test data : APPENDIX 2
Test result : Pass
Test instruments : MTR-01, MCC-05

SECTION 8: Number of Hopping Frequency, Section 15.247(a)(1)(iii)

Test Procedure

The Number of Hopping Frequency was measured with a spectrum analyzer connected to the antenna port.

Test data : APPENDIX 2
Test result : Pass
Test instruments : MTR-01, MCC-05

SECTION 9: Dwell time, Section 15.247(a)(1)(iii)

Test Procedure

The Dwell time was measured with a spectrum analyzer connected to the antenna port.

Test data : APPENDIX 2
Test result : Pass
Test instruments : MTR-01, MCC-05

SECTION 10: Maximum Peak Output Power, Section 15.247(b)(1)

Test Procedure

The Maximum Peak Output Power was measured with a spectrum analyzer connected to the antenna port.

Test data : APPENDIX 2
Test result : Pass
Test instruments : MTR-01, MCC-05

SECTION 11: Band Edge Compliance, Section 15.247(c)

Test Procedure

The Band Edge Compliance was measured with a spectrum analyzer connected to the antenna port.

Test data : APPENDIX 2
Test result : Pass
Test instruments : MTR-01, MCC-05

SECTION 12: Spurious Emission , Section 15.247(c)

[Conducted]

Test Procedure

The Spurious Emission (Conducted) was measured with a spectrum analyzer connected to the antenna port.

Test data : APPENDIX 2
Test result : Pass
Test instruments : MTR-01, MCC-05

[Radiated]

Test Procedure

EUT was placed on a platform of nominal size, 1m by 1.5m, raised 80cm above the conducting ground plane.

Test was made with the antenna positioned in both the horizontal and vertical planes of polarization.

The Radiated Electric Field Strength intensity has been measured in No.2 semi anechoic chamber (7.5x5.8x5.2m) with a ground plane and at a distance of 3m.

The measuring antenna height was varied between 1 to 4m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity.

The measurements were performed for both vertical and horizontal antenna polarization.

Test data : APPENDIX 2
Test result : Pass
Test instruments : MTR-01, MCC-12, MCC-05, MCC-06, MHA-05, MPA-01
MBA-03, MLA-03, MPA-04, MAT-07, MCC-11
MBF-01, MHA-01, MSA-02, MTR-02

A-Pex International Co., Ltd.

EMC Head Office Division.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8116 Facsimile: +81 596 24 8124

APPENDIX 1: Photographs of test setup

- Page 13 : Conducted Emission (DKC-C200X)
Page 14 : Spurious Emission (Radiated) (DKC-C200X)
Page 15 : Other tests except Conducted emission and Spurious Emission (Radiated) (DKC-C200X)

APPENDIX 2: Test instruments

- Page 16 : Test instruments

APPENDIX 3: Data of EMI test

- Page 17-20 : Conducted Emission
Page 21-23 : Carrier Frequency Separation
Page 24-26 : 20dB Bandwidth
Page 27-30 : Number of Hopping Frequency
Page 31-35 : Dwell time
Page 36-38 : Maximum Peak Output Power
Page 39-41 : Band Edge Compliance
Page 42-53 : Spurious Emission

APPENDIX 1: Photographs of test setup

Conducted emission (DXC-C200X)



Spurious Emission (Radiated) (DKC-C200X)



Other tests except Conducted emission and Spurious Emission (Radiated) (DKC-C200X)

