



# RADIO TEST REPORT

Test Report No. : 29JE0027-HO-01-A

Applicant : Sony Computer Entertainment Inc.  
Type of Equipment : Development Tool  
Model No. : DTP-T1000A B  
FCC ID : AK8DTPT1000AB  
Test regulation : FCC Part 15 Subpart C 2009  
Section 15.207, Section 15.247  
(Permissive Change Class II Application)  
Test Result : Complied

1. This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
2. The results in this report apply only to the sample tested.
3. This sample tested is in compliance with the above regulation.
4. The test results in this report are traceable to the national or international standards.
5. This test report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

Date of test: May 13 to 21, 2009

Tested by:

*T. Shimada*

Takumi Shimada  
EMC Services

*Takayuki S.*

Takayuki Shimada  
EMC Services

Approved by :

*M. Fujimura*

Mitsuru Fujimura  
Assistant Manager of EMC Services



NVLAP LAB CODE: 200572-0

This laboratory is accredited by the NVLAP LAB CODE 200572-0, U.S.A. The tests reported herein have been performed in accordance with its terms of accreditation.  
\*As for the range of Accreditation in NVLAP, you may refer to the WEB address, <http://uljapan.co.jp/emc/nvlap.html>

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

MF060b (09.01.08)

<b>CONTENTS</b>	<b>PAGE</b>
<b>SECTION 1: Customer information.....</b>	<b>3</b>
<b>SECTION 2: Equipment under test (E.U.T.).....</b>	<b>3</b>
<b>SECTION 3: Test specification, procedures &amp; results.....</b>	<b>5</b>
<b>SECTION 4: Operation of E.U.T. during testing.....</b>	<b>9</b>
<b>SECTION 5: Conducted Emission.....</b>	<b>12</b>
<b>SECTION 6: Spurious Emission.....</b>	<b>13</b>
<b>SECTION 7: Bandwidth.....</b>	<b>14</b>
<b>SECTION 8: Maximum Peak Output Power.....</b>	<b>15</b>
<b>SECTION 9: Peak Power Density.....</b>	<b>15</b>
<b>APPENDIX 1: Photographs of test setup.....</b>	<b>16</b>
<b>Conducted Emission.....</b>	<b>16</b>
<b>Spurious Emission (Radiated).....</b>	<b>17</b>
<b>Antenna Worst Case Position (Horizontal: 90deg./ Vertical:180deg.).....</b>	<b>18</b>
<b>APPENDIX 2: Data of EMI test.....</b>	<b>21</b>
<b>Conducted Emission.....</b>	<b>21</b>
<b>6dB Bandwidth.....</b>	<b>25</b>
<b>Maximum Peak Output Power.....</b>	<b>27</b>
<b>Radiated Spurious Emission (below 1GHz).....</b>	<b>28</b>
<b>Radiated Spurious Emission (above 1GHz).....</b>	<b>32</b>
<b>Conducted Spurious Emission.....</b>	<b>36</b>
<b>Conducted emission Band Edge compliance.....</b>	<b>40</b>
<b>Power Density.....</b>	<b>41</b>
<b>99%Occupied Bandwidth.....</b>	<b>43</b>
<b>APPENDIX 3: Test instruments.....</b>	<b>44</b>

## **SECTION 1: Customer information**

Company Name	Sony Computer Entertainment Inc.
Brand Name	SONY
Address	2-6-21 Minami-Aoyama, Minato-ku, Tokyo, 107-0062, Japan
Telephone Number	+81-3-6438-8023
Facsimile Number	+81-3-6438-8642
Contact Person	Akiko Tsukada

## **SECTION 2: Equipment under test (E.U.T.)**

### **2.1 Identification of E.U.T.**

Type of Equipment	Development Tool
Model No	DTP-T1000A B
Serial No	SJ0035268: Used for Conducted emission and Spurious emission(Radiated). SJ0006900: Used for Antenna Terminal Conducted tests.
Country of Manufacture	Japan
Receipt Date of Sample	May 11, 2009
Condition of EUT	Production prototype (Not for Sale: This sample is equivalent to mass-produced items.)
Modification of EUT	No modification by the test lab.

---

**UL Japan, Inc.**

**Head Office EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

## 2.2 Product Description

Model No: DTP-T1000A B is the Development Tool.  
The clock frequency used in EUT: Max System Clock 480 MHz

### Product Specification

Clock frequency in the system	44MHz
Operating Temperature	10-35 deg. C
Power Supply	DC19.5V (AC Adaptor: AC100-240V, 50/60Hz)

### Radio Specification

Equipment Type	Transceiver
Frequency of Operation	2412-2462MHz
Type of Modulation	DSSS
Bandwidth & Channel spacing	20MHz & 5MHz
Method of frequency generation	Crystal
Power Supply (inner)	DC3.2V
Antenna Type	External antenna
Antenna Gain	5.0dBi max

### List of Model No.:

Product Name	Package Model Name	Product Model Name
Development Tool	DTP-T2000A	DTP-T1000A B

### Controller

SCE Model Name
DTP-H300

### AC Adaptor

SCE Model Name	Vendor Name, Model Name
DTP-H100	Nagano Japan Radio, SQ120W19P-02

<Contents of the change from original model>

Original test report number of this report is 29AE0044-HO-01-A.

The EUT is changed the specification from original model as below. The RF part is not changed.

- \* The change of the pattern of PCB except for RF part.
- \* The addition of the EMC countermeasure parts.
- \* The addition of the new controller.

**UL Japan, Inc.**

**Head Office EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

### **SECTION 3: Test specification, procedures & results**

#### **3.1 Test Specification**

Test Specification : FCC Part15 Subpart C: 2009, final revised on February 27, 2009

Title : FCC 47CFR Part15 Radio Frequency Devices Subpart C Intentional Radiators  
Section 15.207 Conducted limits  
Section 15.247 Operation within the bands 902-928MHz,  
2400-2483.5MHz, and 5725-5850MHz

The EUT complies with FCC Part 15 Subpart B. Refer to the test report 29JE0042-YW.

#### **FCC 15.31 (e)**

This EUT provides stable voltage(DC3.2V) constantly to RF Module regardless of input voltage. Therefore, this EUT complies with the requirement.

#### **FCC Part 15.203 Antenna requirement**

The antenna is not removable from the EUT. Therefore, the equipment complies with the antenna requirement of Section 15.203.

---

**UL Japan, Inc.**

**Head Office EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

### 3.2 Procedures and results

#### [DSSS and other forms of modulation]

No.	Item	Test Procedure	Specification	Remarks	Deviation	Worst margin	Results
1	Conducted emission	FCC: ANSI C63.4:2003 7. AC powerline conducted emission measurements ----- IC: RSS-Gen 7.2.2	FCC: Section 15.207 ----- IC: RSS-Gen 7.2.2	Conducted	N/A	[QP] 13.0dB 4.80552MHz, N [AV] 7.8dB 4.80552MHz, N	Complied
2	6dB Bandwidth	FCC: "Guidance on Measurement of Digital Transmission Systems Operating under Section15.247" ----- IC: RSS-Gen 4.6.2	FCC: Section 15.247(a)(2) ----- IC: RSS-210 A8.2(a)	Conducted	N/A	See data.	Complied
3	Maximum Peak Output Power	FCC: "Guidance on Measurement of Digital Transmission Systems Operating under Section15.247" ----- IC: RSS-Gen 4.8	FCC: Section 15.247(b)(3) ----- IC: RSS-210 A8.4(4)	Conducted	N/A		Complied
4	Restricted Band Edges	FCC: "Guidance on Measurement of Digital Transmission Systems Operating under Section15.247" ----- IC: -	FCC: Section 15.247 (d) ----- IC: RSS-210 A8.5	Conducted/ Radiated	N/A		Complied
5	Power Density	FCC: "Guidance on Measurement of Digital Transmission Systems Operating under Section15.247" ----- IC: -	FCC: Section 15.247 (e) ----- IC: RSS-210 A8.2(b)	Conducted	N/A		Complied
6	Spurious Emission	FCC: "Guidance on Measurement of Digital Transmission Systems Operating under Section15.247" ----- IC: RSS-Gen 4.9 RSS-Gen 4.10	FCC: Section15.247(d) ----- IC: RSS-210 A8.5 RSS-Gen 7.2.1 and 7.2.3	Conducted/ Radiated	N/A	[Tx] 2.9dB 249.985MHz QP, Horizontal [Rx] 3.2dB 249.985MHz QP, Horizontal	Complied

Note: UL Japan, Inc.'s EMI Work Procedures No.QPM05 and QPM15.

\* In case any questions arise about test procedure, ANSI C63.4: 2003 is also referred.

**UL Japan, Inc.**

**Head Office EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

### 3.3 Addition to standard

No.	Item	Test Procedure	Specification	Remarks	Deviation	Worst margin	Results
1	99% Occupied Band Width	RSS-Gen 4.6.1	RSS-Gen 4.6.1	Radiated	N/A	N/A	N/A

Other than above, no addition, exclusion nor deviation has been made from the standard.

### 3.4 Uncertainty

#### EMI

The following uncertainties have been calculated to provide a confidence level of 95% using a coverage factor k=2.

Test room	Conducted emission	Radiated emission (10m*)			Radiated emission (3m*)			Radiated emission (3m*)	
	150kHz-30MHz	9kHz-30MHz	30MHz-300MHz	300MHz-1GHz	9kHz-30MHz	30MHz-300MHz	300MHz-1GHz	1GHz-18GHz	18GHz-40GHz
No.1 semi-anechoic chamber (±)	3.7dB	3.1dB	4.4dB	4.2dB	3.2dB	3.8dB	3.9dB	5.9dB	6.1dB
No.2 semi-anechoic chamber (±)	3.7dB	-	-	-	3.2dB	4.4dB	4.0dB	5.9dB	6.1dB
No.3 semi-anechoic chamber (±)	3.7dB	-	-	-	3.2dB	4.6dB	4.0dB	5.9dB	6.1dB
No.4 semi-anechoic chamber (±)	3.7dB	-	-	-	3.2dB	3.9dB	3.9dB	5.9dB	6.1dB

\*10m/3m = Measurement distance

#### Conducted emission test

The data listed in this test report has enough margin, more than the site margin.

#### Radiated emission test(3m)

The data listed in this report meets the limits unless the uncertainty is taken into consideration.

#### Other test except Conducted Emission and Spurious Emission (Radiated)

The measurement uncertainty for this test is 3.0dB.

**UL Japan, Inc.**

**Head Office EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

### 3.5 Test Location

UL Japan, Inc. Head Office EMC Lab. \*NVLAP Lab. code: 200572-0  
4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN  
Telephone : +81 596 24 8116 Facsimile : +81 596 24 8124

	FCC Registration Number	IC Registration Number	Width x Depth x Height (m)	Size of reference ground plane (m) / horizontal conducting plane	Other rooms
No.1 semi-anechoic chamber	313583	2973C-1	19.2 x 11.2 x 7.7m	7.0 x 6.0m	No.1 Power source room
No.2 semi-anechoic chamber	655103	2973C-2	7.5 x 5.8 x 5.2m	4.0 x 4.0m	-
No.3 semi-anechoic chamber	148738	2973C-3	12.0 x 8.5 x 5.9m	6.8 x 5.75m	No.3 Preparation room
No.3 shielded room	-	-	4.0 x 6.0 x 2.7m	N/A	-
No.4 semi-anechoic chamber	134570	2973C-4	12.0 x 8.5 x 5.9m	6.8 x 5.75m	No.4 Preparation room
No.4 shielded room	-	-	4.0 x 6.0 x 2.7m	N/A	-
No.5 semi-anechoic chamber	-	-	6.0 x 6.0 x 3.9m	6.0 x 6.0m	-
No.6 shielded room	-	-	4.0 x 4.5 x 2.7m	4.75 x 5.4 m	-
No.6 measurement room	-	-	4.75 x 5.4 x 3.0m	4.75 x 4.15 m	-
No.7 shielded room	-	-	4.7 x 7.5 x 2.7m	4.7 x 7.5m	-
No.8 measurement room	-	-	3.1 x 5.0 x 2.7m	N/A	-
No.9 measurement room	-	-	8.0 x 4.5 x 2.8m	2.0 x 2.0m	-
No.10 measurement room	-	-	2.6 x 2.8 x 2.5m	2.4 x 2.4m	-
No.11 measurement room	-	-	3.1 x 3.4 x 3.0m	2.4 x 3.4m	-

\* Size of vertical conducting plane (for Conducted Emission test) : 2.0 x 2.0m for No.1, No.2, No.3, and No.4 semi-anechoic chambers and No.3 and No.4 shielded rooms.

### 3.6 Test set up, Data of EMI, and Test instruments

Refer to APPENDIX 1 to 3.

## **SECTION 4: Operation of E.U.T. during testing**

### **4.1 Operating Mode(s)**

The mode used for test : [IEEE 802.11b: DSSS]

<b>Test</b>	<b>Mode</b>	<b>Tested frequency</b>
Conducted Emission Spurious Emission	IEEE802.11b Transmitting (Tx) 2Mbps *1)	2412MHz(L) 2437MHz(M) 2462MHz(H)
	----- IEEE802.11b Receiving (Rx)	----- 2437MHz(M)
6dB Bandwidth Maximum Peak Output Power Power Density 99% Occupied Bandwidth	IEEE802.11b Transmitting (Tx), 2Mbps *1)	2412MHz(L) 2437MHz(M) 2462MHz(H)
Restricted Band Edge	IEEE802.11b Transmitting (Tx), 2Mbps *1)	2412MHz(L) 2462MHz(H)

\*Transmitting duty was 100% on all tests.

\*As a result of preliminary test, the formal test was performed with the above modes, which had the maximum rated power.

\*1) The transmitting data shall be scrambled with the following scramblers and it was transmitted continuously.

[11b]

2Mbps: IEEE Std 802.11(1999) Section 15.2.4

**UL Japan, Inc.**

**Head Office EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

## 4.2 Configuration and peripherals

**This page has been submitted for a separate exhibit.**

**This page has been submitted for a separate exhibit.**

## **SECTION 5: Conducted Emission**

### **Test Procedure and conditions**

EUT was placed on a urethane platform of nominal size, 1.0m by 1.5m, raised 0.8m above the conducting ground plane. The rear of tabletop was located 40cm to the vertical conducting plane. The rear of EUT, including peripherals aligned and flushed with rear of tabletop. All other surfaces of tabletop were at least 80cm from any other grounded conducting surface. EUT was located 80cm from a Line Impedance Stabilization Network (LISN)/ Artificial mains Network (AMN) and excess AC cable was bundled in center.

#### For the tests on EUT with other peripherals (as a whole system)

I/O cable and AC cables that were connected to the peripherals were bundled in center. They were folded back and forth forming a bundle 30cm to 40cm long and were hanged at a 40cm height to the ground plane. All unused 50ohm connectors of the LISN(AMN) were resistivity terminated in 50ohm when not connected to the measuring equipment.

The AC Mains Terminal Continuous disturbance Voltage has been measured with the EUT in a Semi Anechoic Chamber. The EUT was connected to a LISN (AMN). An overview sweep with peak detection has been performed.

**Detector** : quasi-peak and average detector (IF BW 9 kHz)  
**Measurement range** : 0.15-30MHz  
**Test data** : APPENDIX 2  
**Test result** : Pass

**SECTION 6: Spurious Emission**

**[Conducted]**

**Test Procedure**

The Out of Band Emission was measured with a spectrum analyzer connected to the antenna port. It was measured based on "1. RF antenna conducted test" of "Guidance on Measurement of Digital Transmission Systems Operating under Section 15.247".

The following spectrum analyzer setting was used:

- RBW: 100kHz
- VBW: 300kHz
- Sweep: Auto
- Detector: Peak
- Trace: Max Hold

**Test data : APPENDIX 2**

**Test result : Pass**

**[Radiated]**

**Test Procedure**

It was measured based on "2. Radiated emission test" of "Guidance on Measurement of Digital Transmission Systems Operating under Section 15.247".

EUT was placed on a urethane platform of nominal size, 1.0m by 1.5m, raised 0.8m above the conducting ground plane. The Radiated Electric Field Strength intensity has been measured in a Semi Anechoic Chamber with a ground plane and at a distance of 3m (Below 10GHz) and 1m (Upper 10GHz).

The height of the measuring varied between 1 and 4m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity.

The measurements were performed for both vertical and horizontal antenna polarization with the Test Receiver, or the Spectrum Analyzer.

The radiated emission measurements were made with the following detector function of the test receiver and the Spectrum analyzer.

The result also satisfied with the general limits specified in section FCC 15.209(a) / RSS-210 2.7 (IC).

Frequency	Below 1GHz	Above 1GHz
Instrument used	Test Receiver	Spectrum Analyzer
Detector	QP: BW 120kHz	PK: RBW:1MHz/VBW: 1MHz
IF Bandwidth		AV *1): RBW:1MHz/VBW: 10Hz

\*1) When using Spectrum analyzer, the test was made with adjusting span to zero by using peak hold.

- The carrier level and noise levels were confirmed at each position of 0 deg., 90 deg., and 180 deg., axes of Antenna to see the position of maximum noise, and the test was made at the position that has the maximum noise.

**Test data : APPENDIX 2**

**Test result : Pass**

---

**UL Japan, Inc.**

**Head Office EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

## **SECTION 7: Bandwidth**

### **6dB Bandwidth**

#### **Test Procedure**

The bandwidth was measured with a spectrum analyzer connected to the antenna port.  
It was measured based on "Guidance on Measurement of Digital Transmission Systems Operating under Section 15.247".  
The following spectrum analyzer setting was used:

- Span: 50MHz
- RBW: 100kHz
- VBW: 300kHz
- Sweep: Auto
- Detector: Peak
- Trace: Max Hold

**Test data** : APPENDIX 2  
**Test result** : Pass

### **99% Occupied Bandwidth**

#### **Test Procedure**

The bandwidth was measured with a spectrum analyzer connected to the antenna port.  
The following spectrum analyzer setting was used:

- Span: Enough width to display 20dB Bandwidth
- RBW: as close to 1% of the Span as is possible without being below 1%
- VBW: Three times of RBW
- Sweep: Auto
- Detector: Peak
- Trace: Max Hold

**Test data** : APPENDIX 2  
**Test result** : Pass

## **SECTION 8: Maximum Peak Output Power**

### **Test Procedure**

The Maximum Peak Output Power was measured with a power meter (tested bandwidth: 50MHz) connected to the antenna port.

It was measured based on "Power Output Option 1" of "Guidance on Measurement of Digital Transmission Systems Operating under Section15.247".

**Test data** : APPENDIX 2  
**Test result** : Pass

## **SECTION 9: Peak Power Density**

### **[Conducted]**

#### **Test Procedure**

The Peak Power Density was measured with a spectrum analyzer connected to the antenna port.

It was measured based on "PSD Option 1" of "Guidance on Measurement of Digital Transmission Systems Operating under Section15.247".

- Span: 9MHz
- RBW: 30kHz\*)
- VBW: 100kHz
- Sweep: 300sec
- Detector: Peak
- Trace: Max Hold

\*) The test was not performed at RBW: 3kHz that was stated in the Regulation.

However, the measurement value with RBW:3kHz is less than the value of RBW:30kHz and the test data met the limit with RBW:3kHz.

**Test data** : APPENDIX 2  
**Test result** : Pass

---

## **UL Japan, Inc.**

### **Head Office EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124