

FCC PART 15C TEST REPORT FOR CERTIFICATION

On Behalf of

Sony Corporation

Home Audio System

Brand Name	Model No.
SONY	GTK-XB5

FCC ID: AK8GTKXB5

Prepared for : Sony Corporation
1-7-1 Konan, Minato-ku, Tokyo 108-0075 Japan

Prepared By : Audix Technology (Shenzhen) Co., Ltd.
No. 6, Ke Feng Rd., 52 Block,
Shenzhen Science & Industrial Park,
Nantou, Shenzhen, Guangdong, China

Tel: (0755) 26639496

Report Number : ACS-F16114
Date of Test : Apr.29~May.23, 2016
Date of Report : Jun.03, 2016

TABLE OF CONTENTS

<u>Description</u>	<u>Page</u>
1. SUMMARY OF STANDARDS AND RESULTS.....	1-1
1.1. Description of Standards and Results	1-1
2. GENERAL INFORMATION	2-1
2.1. Description of Device (EUT).....	2-1
2.2. Tested Supporting System Details	2-2
2.3. Block Diagram of connection between EUT and simulators.....	2-2
2.4. Test information.....	2-2
2.5. Test Facility	2-3
2.6. Measurement Uncertainty (95% confidence levels, k=2).....	2-3
3. POWER LINE CONDUCTED EMISSION TEST.....	3-1
3.1. Test Equipments.....	3-1
3.2. Block Diagram of Test Setup.....	3-1
3.3. Power Line Conducted Emission Test Limits.....	3-2
3.4. Configuration of EUT on Test.....	3-2
3.5. Operating Condition of EUT	3-2
3.6. Test Procedure	3-2
3.7. Power Line Conducted Emission Test Results	3-2
4. RADIATED EMISSION MEASUREMENT.....	4-1
4.1. Test Equipments.....	4-1
4.2. Block Diagram of Test Setup.....	4-1
4.3. Radiated Emission Limit Standard:	4-3
4.4. EUT Configuration on Test	4-3
4.5. Operating Condition of EUT	4-3
4.6. Test Procedure	4-3
4.7. Radiated Emission Test Results.....	4-4
5. CONDUCTED SPURIOUS EMISSIONS.....	5-1
5.1. Test Equipments.....	5-1
5.2. Limit.....	5-1
5.3. Test Procedure	5-1
5.4. Test result.....	5-1
6. 20 DB BANDWIDTH TEST	6-1
6.1. Test Equipments.....	6-1
6.2. Limit.....	6-1
6.3. Test Results.....	6-1
7. CARRIER FREQUENCY SEPARATION TEST	7-1
7.1. Test Equipments.....	7-1
7.2. Limit.....	7-1
7.3. Test Results.....	7-1
8. NUMBER OF HOPPING FREQUENCY TEST	8-1
8.1. Test Equipments.....	8-1
8.2. Limit.....	8-1
8.3. Test Results.....	8-1
9. DWELL TIME	9-1
9.1. Test Equipments.....	9-1

9.2.	Limit.....	9-1
9.3.	Test Results.....	9-1
10.	MAXIMUM PEAK OUTPUT POWER TEST	10-1
10.1.	Test Equipments.....	10-1
10.2.	Limit.....	10-1
10.3.	Test Procedure	10-1
10.4.	Test Results.....	10-1
11.	BAND EDGE COMPLIANCE TEST	11-1
11.1.	Test Equipments.....	11-1
11.2.	Limit.....	11-1
11.3.	Test Produce.....	11-1
11.4.	Test Results	11-1
12.	ANTENNA REQUIREMENT	12-1
12.1.	Standard Applicable.....	12-1
12.2.	Antenna Connected Construction	12-1
13.	DEVIATION TO TEST SPECIFICATIONS.....	13-1
14.	PHOTOGRAPH OF TEST	14-1
14.1.	Photos of Power Line Conducted Emission Test.....	14-1
14.2.	Photos of Radiated Emission Test	14-3
15.	PHOTOGRAPHS OF EUT	15-1

TEST REPORT CERTIFICATION

Applicant : Sony Corporation
 Product : Home Audio System
 FCC ID : AK8GTKXB5

(A) Brand Name & Model No.	Brand Name SONY	Model No. GTK-XB5
(B) Serial No.	: N/A	
(C) Test Voltage	: AC 120V/60Hz	

Tested for comply with:
 FCC CRF 47 Part 15 Subpart C: 2014

Test procedure used:
 ANSI C63.10: 2013

The device described above is tested by AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. to confirm comply with all the FCC Part 15 Subpart C requirements. The test results are contained in this test report and AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. is assumed full responsibility for the accuracy and completeness of these tests. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC and IC requirements. This report contains data that are not covered by the NVLAP accreditation.

This Report is made under FCC Part 2.1075. No modifications were required during testing to bring this product into compliance.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of AUDIX TECHNOLOGY (SHENZHEN) CO., LTD.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

Date of Test : Apr.29~May.23, 2016 Report of date: Jun.03, 2016

Prepared by : Kayli He Reviewed by : Sunny Lu
 Kayli He / Assistant Sunny Lu / Assistant Manager

信華科技 (深圳) 有限公司
 Audix Technology (Shenzhen) Co., Ltd.
 EMC 部門報告專用章

Stamp only for EMC Dept. Report

Signature: David Jin
 David Jin / Manager

Approved & Authorized Signer :

1. SUMMARY OF STANDARDS AND RESULTS

1.1. Description of Standards and Results

The EUT has been tested according to the applicable standards as referenced below.

EMISSION		
Description of Test Item	Standard	Results
Power Line Conducted Emission Test	FCC Part 15: 15.207 ANSI C63.10 2013	PASS
Radiated Emission Test	FCC Part 15 15.209 FCC Part 15 15.247(d) ANSI C63.10 2013	PASS
Conducted Spurious Emissions	FCC Part 15: 15.247(a)(1) ANSI C63.10 2013	PASS
Carrier Frequency Separation Test	FCC Part 15: 15.247(a)(1) ANSI C63.10 2013	PASS
20dB Bandwidth Test	FCC Part 15: 15.215 ANSI C63.10 2013	PASS
Number Of Hopping Frequency Test	FCC Part 15: 15.247(a)(1)(iii) ANSI C63.10 2013	PASS
Dwell Time Test	FCC Part 15: 15.247(a)(1)(iii) ANSI C63.10 2013	PASS
Maximum Peak Output Power Test	FCC Part 15 15.247(b)(1)\ ANSI C63.10 2013	PASS
Band Edge Compliance Test	FCC Part 15 15.247(d) ANSI C63.10 2013	PASS

2. GENERAL INFORMATION

2.1. Description of Device (EUT)

Product : Home Audio System

Brand Name & Model No.	Brand Name	Model No.
	SONY	GTK-XB5

FCC ID : AK8GTKXB5

Radio : Bluetooth V3.0+EDR; NFC Rx

Operation Frequency : Bluetooth : 2402-2480MHz;
NFC: 13.56MHz

Channel Number : Bluetooth: 79 channels;
NFC: 1 channel

Modulation Technology : Bluetooth: GFSK, $\pi/4$ DQPSK, 8DPSK;
NFC: ASK

Antenna Assembly Gain : PCB Antenna, 2.4dBi PK gain

Applicant : Sony Corporation
1-7-1 Konan, Minato-ku, Tokyo 108-0075 Japan

Date of Test : Apr.29~May.23, 2016


Date of Receipt : Apr.29, 2016

Remark: : This report only for Bluetooth V3.0+EDR.

2.2. Tested Supporting System Details

No.	Description	ACS No.	Manufacturer	Model	Serial Number
1.	Notebook	N/A	SONY	SVF143A1QT	N/A
		Power Cord: Unshielded, Detachable, 1.8m Power Adaptor: Manufacturer: DELL, M/N: LA65NS1-00 Cable: Unshielded, Detachable, 4.0m(Bond one ferrite core)			
2.	Walkman	Walkman	---	Sony	NWZ-B172F

2.3. Block Diagram of connection between EUT and simulators



(EUT: Home Audio System)

2.4. Test information

A special software was used to control EUT work in Continuous TX mode(GFSK, $\pi/4$ DQPSK,8-DPSK Modulation), and select test channel.

Tested mode, channel, and data rate information			
Mode	data rate (Mbps)	Channel	Frequency (MHz)
Tx Mode GFSK modulation	1	Low :CH 0	2402
	1	Middle: CH39	2441
	1	High: CH78	2480
Tx Mode 8-DPSK modulation	3	Low :CH 0	2402
	3	Middle: CH39	2441
	3	High: CH78	2480

Note: $\pi/4$ DQPSK modulation is same type modulation with 8-DPSK, and according exploratory test, 8-DPSK will have worse emissions, so the final test were only performed with GFSK and 8-DPSK modulation.

2.5. Test Facility

Site Description

- Name of Firm : Audix Technology (Shenzhen) Co., Ltd.
 No. 6, Ke Feng Rd., 52 Block, Shenzhen
 Science & Industrial Park, Nantou, Shenzhen,
 Guangdong, China
- 3m Anechoic Chamber : Certificated by FCC, USA
 Registration Number: 90454
 Valid Date: Dec.30, 2017
- 3m & 10m Anechoic Chamber : Certificated by FCC, USA
 Registration Number: 794232
 Valid Date: Jul.12, 2016
- EMC Lab. : Certificated by Industry Canada
 Registration Number: IC 5183A-1
 Valid Date: May.14, 2017
- : Certificated by DAkkS, Germany
 Registration No: D-PL-12151-01-00
 Valid Date: Dec.15, 2016
- : Accredited by NVLAP, USA
 NVLAP Code: 200372-0
 Valid Date: Mar.31, 2017

2.6. Measurement Uncertainty (95% confidence levels, k=2)

Test Item	Uncertainty
Uncertainty for Conduction emission test in No. 1 Conduction	3.2dB(150KHz to 30MHz)
Uncertainty for Radiation Emission test in 3m chamber	2.8dB(30~200MHz, Polarization: H)
	2.8dB(30~200MHz, Polarization: V)
	2.8dB(200M~1GHz, Polarization: H)
	2.8dB(200M~1GHz, Polarization: V)
Uncertainty for Radiation Emission test in 3m chamber (1GHz-18GHz)	5.8dB(1~6GHz, Distance: 3m)
	5.8dB(6~18GHz, Distance: 3m)
Uncertainty for Radiated Spurious Emission test in RF chamber	3.6dB
Uncertainty for Conduction Spurious emission test	2.0dB
Uncertainty for Output power test	0.8dB
Uncertainty for Bandwidth test	83kHz
Uncertainty for DC power test	0.1%
Uncertainty for test site temperature and humidity	0.6°C
	3%

3. POWER LINE CONDUCTED EMISSION TEST


3.1. Test Equipments

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	1# Shielding Room	AUDIX	N/A	N/A	Apr.17,16	1 Year
2.	Test Receiver	Rohde & Schwarz	ESCI	100842	Apr.24,16	1 Year
3.	L.I.S.N.#1	Rohde & Schwarz	ESH2-Z5	100429	Oct.18,15	1 Year
4.	L.I.S.N.#2	Kyoritsu	K NW-403D	8-1750-2	Apr.24,16	1 Year
5.	Terminator	Hubersuhner	50Ω	No.1	May.05.16	1 Year
6.	Terminator	Hubersuhner	50Ω	No.2	May.05.16	1 Year
7.	RF Cable	MIYAZAKI	3D-2W	No.1	Apr.24,16	1Year
8.	Coaxial Switch	Anritsu	MP59B	6200766906	Apr.23,16	1 Year
9.	Test Software	AUDIX	e3	6.100913a	N/A	N/A


Note: N/A means Not applicable.

3.2. Block Diagram of Test Setup

EUT is horizontal:



EUT is vertical:



3.3. Power Line Conducted Emission Test Limits

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. * Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

3.4. Configuration of EUT on Test

The following equipment are installed on Power Line Conducted Emission Test to meet the commission requirement and operating regulations in a manner which tends to maximize its emission characteristics in a normal application.

3.4.1. Home Audio System (EUT)

Model No. : GTK-XB5

Serial No. : N/A

3.4.2. Support Equipment: As Tested Supporting System Details, in Section 2.2.

3.5. Operating Condition of EUT

3.5.1. Setup the EUT and simulator as shown as Section 3.2.

3.5.2. Turn on the power of all equipments.

3.5.3. PC runs test software to control EUT work in BT 3.0 Tx mode.

3.6. Test Procedure


The EUT was placed on a non-metallic table, 80cm above the ground plane for EUT is horizontal; The EUT was placed on the 10cm non-conductive plan for EUT is vertical. The EUT Power Via PC connected to the power mains through a line impedance stabilization network (L.I.S.N. 1#). This provides a 50 ohm coupling impedance for the EUT (Please refer the block diagram of the test setup and photographs). The AC lines are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10: 2013 on Conducted Emission Test.

The bandwidth of test receiver (R & S ESCI) is set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.


3.7. Power Line Conducted Emission Test Results

PASS. (All emissions not reported below are too low against the prescribed limits.)




No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.158	0.15	0.02	51.06	51.23	65.56	14.33	QP
2	0.170	0.15	0.02	50.20	50.37	64.94	14.57	QP
3	0.182	0.15	0.02	48.47	48.64	64.42	15.78	QP
4	0.381	0.16	0.03	39.21	39.40	58.25	18.85	QP
5	2.650	0.20	0.08	31.84	32.12	56.00	23.88	QP
6	29.527	0.95	0.25	39.16	40.36	60.00	19.64	QP

Remarks: 1.Emission Level=LISN Factor+Cable Loss+Reading.
 2.If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.




No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.154	0.33	0.02	52.35	52.70	65.78	13.08	QP
2	0.166	0.33	0.02	50.84	51.19	65.16	13.97	QP
3	0.253	0.39	0.02	42.42	42.83	61.64	18.81	QP
4	0.601	0.43	0.04	40.11	40.58	56.00	15.42	QP
5	2.358	0.48	0.08	33.35	33.91	56.00	22.09	QP
6	29.841	1.15	0.25	43.84	45.24	60.00	14.76	QP

Remarks: 1.Emission Level=LISN Factor+Cable Loss+Reading.
 2.If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.



No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.154	0.15	0.02	51.66	51.83	65.78	13.95	QP
2	0.202	0.15	0.02	47.64	47.81	63.54	15.73	QP
3	0.385	0.16	0.03	40.01	40.20	58.17	17.97	QP
4	0.611	0.17	0.04	40.16	40.37	56.00	15.63	QP
5	0.822	0.18	0.05	42.52	42.75	56.00	13.25	QP
6	1.585	0.18	0.07	38.78	39.03	56.00	16.97	QP

Remarks: 1.Emission Level=LISN Factor+Cable Loss+Reading.
 2.If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.



No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.170	0.33	0.02	49.40	49.75	64.94	15.19	QP
2	0.194	0.38	0.02	49.90	50.30	63.84	13.54	QP
3	0.381	0.40	0.03	38.19	38.62	58.25	19.63	QP
4	0.608	0.43	0.04	35.20	35.67	56.00	20.33	QP
5	1.636	0.47	0.07	32.40	32.94	56.00	23.06	QP
6	30.000	1.15	0.25	41.72	43.12	60.00	16.88	QP

Remarks: 1.Emission Level=LISN Factor+Cable Loss+Reading.
 2.If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.

4. RADIATED EMISSION MEASUREMENT

4.1. Test Equipments

Frequency range: 30~1000MHz

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	3#Chamber	AUDIX	N/A	N/A	Mar.28,16	1 Year
2.	EMI Spectrum	Agilent	E4407B	MY41440292	Apr.24,16	1 Year
3.	Test Receiver	Rohde & Schwarz	ESVS10	834468/011	Apr.24,16	1 Year
4.	Amplifier	HP	8447D	2648A04738	Apr.24,16	1 Year
5.	Bi-log Antenna	TESEQ	CBL6112D	35375	Jun.30,15	1 Year
6.	RF Cable	MIYAZAKI	CFD400-N W(3.5M)	No.3	Apr.24,16	1 Year
7.	RF Cable	MIYAZAKI	CFD400-L W(22M)	No.7	Apr.24,16	1 Year
8.	Coaxial Switch	Anritsu	MP59B	6201397222	Apr.23,16	1 Year
9.	Test Software	AUDIX	e3	6.2009-5-21a(n)	N/A	N/A

Note: N/A means Not applicable.

Frequency range: above 1000MHz


Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analyzer	Agilent	E4446A	US44300459	Apr.24,16	1 Year
2.	Horn Antenna	ETS	3115	9510-4877	Oct.15,15	1 Year
3.	Amplifier	Agilent	8449B	3008A02495	Apr.24,16	1 Year
4.	RF Cable	Hubersuhner	SUCOFLEX104	274094/4	Apr.24,16	1 Year
5.	Horn Antenna	ETS	3116	00060089	Oct.15,15	1 Year
6.	Test Software	AUDIX	e3	6.2009-5-21a(n)	N/A	N/A

Note: N/A means Not applicable.


4.2. Block Diagram of Test Setup

EUT is horizontal:


For frequency range 30MHz-1000MHz




For frequency range 1GHz-25GHz



EUT is vertical:
For frequency range 30MHz-1000MHz



For frequency range 1GHz-25GHz



4.3. Radiated Emission Limit Standard:

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000MHz	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	

Remarks : (1) Emission level dBμV = 20 log Emission level μV/m

- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.
- (4) The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490kHz and above 1000MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

4.4. EUT Configuration on Test

The following equipment are installed on Radiated Emission Test to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

4.4.1. Home Audio System (EUT)

Model No. : GTK-XB5
Serial No. : N/A

4.5. Operating Condition of EUT

- 4.5.1. Setup the EUT and simulator as shown as Section 4.2.
- 4.5.2. Turn on the power of all equipments.
- 4.5.3. Let EUT work in BT 3.0 Tx mode.

4.6. Test Procedure

EUT and its simulators are placed on a turn table, which is 0.8 meter high above ground for frequency 30MHz~1000MHz, 1.5 meter high above ground for frequency above 1GHz and put the absorbing with 2.4m(L)*2.4m(W)*0.3m(H) on the ground for EUT is horizontal; EUT placed on the 10cm non-conductive plan for EUT is vertical. The turn table can rotate 360 degrees to determine the position of the maximum emission level. Power on the EUT and let it working in test mode, then test it. EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna for frequency 30MHz~1000MHz, and the Horn antenna is used as receiving antenna for frequency above 1GHz. Both horizontal and vertical polarization of the antenna is set on Test. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.10-2013 on radiated emission Test.

This test was performed with EUT in X, Y, Z position, and the worse case was found when EUT in X position as the test photo indicated.

The bandwidth of the EMI test receiver (R&S ESVS10) is set at 120kHz for frequency range from 30MHz to 1000MHz.

The bandwidth of the Spectrum's RBW is set at 1MHz and VBW is set at 3MHz for peak emissions measurement above 1GHz

This device is pulse Modulated, a duty cycle factor was used to calculate average level based measured peak level.

The frequency ranges from 30MHz to 10th harmonic (25GHz) are checked. and no any emissions were found from 18GHz to 25GHz, So the radiated emissions from 18GHz to 25GHz were not record.



4.7.Radiated Emission Test Results

PASS.


All the emissions from 30MHz to 25GHz were complying with the 15.209 Limit.

Note: The duty cycle factor for calculate average level is -30.618dB, and average limit is 20dB below peak limit, so if peak measured level comply with average limit, the average level was deemed to comply with average limit.

Duty cycle factor = $20\log(\text{Dwell time}/100\text{ms}) = -30.618$




Frequency: 30MHz~1GHz




No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	41.640	13.28	0.71	14.66	28.65	40.00	11.35	QP
2	144.460	11.89	1.29	16.98	30.16	43.50	13.34	QP
3	209.450	10.79	1.54	20.88	33.21	43.50	10.29	QP
4	270.560	14.09	1.79	16.03	31.91	46.00	14.09	QP
5	435.460	17.43	2.31	12.86	32.60	46.00	13.40	QP
6	602.300	19.32	2.77	9.22	31.31	46.00	14.69	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.




No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	31.940	19.06	0.61	14.29	33.96	40.00	6.04	QP
2	144.460	11.89	1.29	18.36	31.54	43.50	11.96	QP
3	192.960	10.39	1.49	20.32	32.20	43.50	11.30	QP
4	206.540	10.73	1.54	23.06	35.33	43.50	8.17	QP
5	454.860	17.72	2.38	13.20	33.30	46.00	12.70	QP
6	604.240	19.33	2.77	10.99	33.09	46.00	12.91	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	144.460	11.89	1.29	17.04	30.22	43.50	13.28	QP
2	192.960	10.39	1.49	17.99	29.87	43.50	13.63	QP
3	206.540	10.73	1.54	18.64	30.91	43.50	12.59	QP
4	352.040	15.62	2.05	21.03	38.70	46.00	7.30	QP
5	369.500	16.09	2.12	21.64	39.85	46.00	6.15	QP
6	425.760	17.29	2.29	14.81	34.39	46.00	11.61	QP


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.




No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	30.000	20.30	0.51	11.36	32.17	40.00	7.83	QP
2	128.940	12.76	1.21	18.77	32.74	43.50	10.76	QP
3	144.460	11.89	1.29	19.97	33.15	43.50	10.35	QP
4	206.540	10.73	1.54	22.26	34.53	43.50	8.97	QP
5	369.500	16.09	2.12	16.22	34.43	46.00	11.57	QP
6	427.700	17.32	2.29	13.84	33.45	46.00	12.55	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.


Frequency: 1GHz~18GHz



Site no. : 3m Chamber Data no. : 3
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : GFSK 2402MHz Tx Mode
 M/N : V Place




Site no. : 3m Chamber Data no. : 1
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : GFSK 2402MHz Tx Mode
 M/N : V Place



Site no. : 3m Chamber Data no. : 4
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : GFSK 2402MHz Tx Mode
 M/N : V Place

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.000	28.28	7.32	36.62	89.86	88.84	74.00	-14.84	Peak
2	4804.000	33.11	9.46	35.54	44.84	51.87	74.00	22.13	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 2
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : GFSK 2402MHz Tx Mode
 M/N : V Place

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.000	28.28	7.32	36.62	90.85	89.83	74.00	-15.83	Peak
2	4804.000	33.11	9.46	35.54	44.10	51.13	74.00	22.87	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 9
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : GFSK 2441MHz Tx Mode
 M/N : V Place




Site no. : 3m Chamber Data no. : 7
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : GFSK 2441MHz Tx Mode
 M/N : V Place



Site no. : 3m Chamber Data no. : 10
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : GFSK 2441MHz Tx Mode
 M/N : V Place

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2441.000	28.33	7.39	36.60	89.05	88.17	74.00	-14.17	Peak
2	4882.000	33.26	9.49	35.51	43.27	50.51	74.00	23.49	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 8
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : GFSK 2441MHz Tx Mode
 M/N : V Place

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2441.000	28.33	7.39	36.60	89.87	88.99	74.00	-14.99	Peak
2	4882.000	33.26	9.49	35.51	44.03	51.27	74.00	22.73	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 11
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : GFSK 2480MHz Tx Mode
 M/N : V Place




Site no. : 3m Chamber Data no. : 13
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : GFSK 2480MHz Tx Mode
 M/N : V Place



Site no. : 3m Chamber Data no. : 12
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : GFSK 2480MHz Tx Mode
 M/N : V Place

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.000	28.38	7.47	36.59	88.03	87.29	74.00	-13.29	Peak
2	4960.000	33.42	9.52	35.47	43.11	50.58	74.00	23.42	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 14
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : GFSK 2480MHz Tx Mode
 M/N : V Place

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.000	28.38	7.47	36.59	91.10	90.36	74.00	-16.36	Peak
2	4960.000	33.42	9.52	35.47	43.54	51.01	74.00	22.99	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 21
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : 8-DPSK 2480MHz Tx Mode
 M/N : V Place




Site no. : 3m Chamber Data no. : 19
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : 8-DPSK 2480MHz Tx Mode
 M/N : V Place



Site no. : 3m Chamber Data no. : 22
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : 8-DPSK 2480MHz Tx Mode
 M/N : V Place

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.000	28.38	7.47	36.59	89.80	89.06	74.00	-15.06	Peak
2	4960.000	33.42	9.52	35.47	43.12	50.59	74.00	23.41	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 20
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : 8-DPSK 2480MHz Tx Mode
 M/N : V Place

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.000	28.38	7.47	36.59	90.84	90.10	74.00	-16.10	Peak
2	4960.000	33.42	9.52	35.47	44.02	51.49	74.00	22.51	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 23
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : 8-DPSK 2441MHz Tx Mode
 M/N : V Place




Site no. : 3m Chamber Data no. : 25
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : 8-DPSK 2441MHz Tx Mode
 M/N : V Place



Site no. : 3m Chamber Data no. : 24
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : 8-DPSK 2441MHz Tx Mode
 M/N : V Place

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2441.000	28.33	7.39	36.60	89.80	88.92	74.00	-14.92	Peak
2	4882.000	33.26	9.49	35.51	43.27	50.51	74.00	23.49	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 26
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : 8-DPSK 2441MHz Tx Mode
 M/N : V Place

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2441.000	28.33	7.39	36.60	89.98	89.10	74.00	-15.10	Peak
2	4882.000	33.26	9.49	35.51	44.04	51.28	74.00	22.72	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 29
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : 8-DPSK 2402MHz Tx Mode
 M/N : V Place




Site no. : 3m Chamber Data no. : 27
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : 8-DPSK 2402MHz Tx Mode
 M/N : V Place



Site no. : 3m Chamber Data no. : 30
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : 8-DPSK 2402MHz Tx Mode
 M/N : V Place

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.000	28.28	7.32	36.62	88.16	87.14	74.00	-13.14	Peak
2	4804.000	33.11	9.46	35.54	43.25	50.28	74.00	23.72	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 28
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : 8-DPSK 2402MHz Tx Mode
 M/N : V Place

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.000	28.28	7.32	36.62	88.85	87.83	74.00	-13.83	Peak
2	4804.000	33.11	9.46	35.54	43.13	50.16	74.00	23.84	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 33
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : GFSK 2402MHz Tx Mode
 M/N : H Place




Site no. : 3m Chamber Data no. : 35
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : GFSK 2402MHz Tx Mode
 M/N : H Place



Site no. : 3m Chamber Data no. : 34
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : GFSK 2402MHz Tx Mode
 M/N : H Place

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.000	28.28	7.32	36.62	91.38	90.36	74.00	-16.36	Peak
2	4804.000	33.11	9.46	35.54	44.82	51.85	74.00	22.15	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 36
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : GFSK 2402MHz Tx Mode
 M/N : H Place

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.000	28.28	7.32	36.62	93.76	92.74	74.00	-18.74	Peak
2	4804.000	33.11	9.46	35.54	44.94	51.97	74.00	22.03	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 39
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : GFSK 2441MHz Tx Mode
 M/N : H Place




Site no. : 3m Chamber Data no. : 41
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : GFSK 2441MHz Tx Mode
 M/N : H Place



Site no. : 3m Chamber Data no. : 40
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : GFSK 2441MHz Tx Mode
 M/N : H Place

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2441.000	28.33	7.39	36.60	88.85	87.97	74.00	-13.97	Peak
2	4882.000	33.26	9.49	35.51	44.16	51.40	74.00	22.60	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 42
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : GFSK 2441MHz Tx Mode
 M/N : H Place

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2441.000	28.33	7.39	36.60	91.82	90.94	74.00	-16.94	Peak
2	4882.000	33.26	9.49	35.51	43.84	51.08	74.00	22.92	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 45
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : GFSK 2480MHz Tx Mode
 M/N : H Place




Site no. : 3m Chamber Data no. : 43
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : GFSK 2480MHz Tx Mode
 M/N : H Place



Site no. : 3m Chamber Data no. : 46
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : GFSK 2480MHz Tx Mode
 M/N : H Place

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.000	28.38	7.47	36.59	90.12	89.38	74.00	-15.38	Peak
2	4960.000	33.42	9.52	35.47	44.14	51.61	74.00	22.39	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 44
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : GFSK 2480MHz Tx Mode
 M/N : H Place

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.000	28.38	7.47	36.59	94.61	93.87	74.00	-19.87	Peak
2	4960.000	33.42	9.52	35.47	44.23	51.70	74.00	22.30	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 49
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : 8-DPSK 2402MHz Tx Mode
 M/N : H Place




Site no. : 3m Chamber Data no. : 51
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : 8-DPSK 2402MHz Tx Mode
 M/N : H Place



Site no. : 3m Chamber Data no. : 50
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : 8-DPSK 2402MHz Tx Mode
 M/N : H Place

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.000	28.28	7.32	36.62	87.73	86.71	74.00	-12.71	Peak
2	4804.000	33.11	9.46	35.54	44.16	51.19	74.00	22.81	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 52
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : 8-DPSK 2402MHz Tx Mode
 M/N : H Place

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.000	28.28	7.32	36.62	89.39	88.37	74.00	-14.37	Peak
2	4804.000	33.11	9.46	35.54	44.06	51.09	74.00	22.91	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 55
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : 8-DPSK 2441MHz Tx Mode
 M/N : H Place




Site no. : 3m Chamber Data no. : 57
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : 8-DPSK 2441MHz Tx Mode
 M/N : H Place



Site no. : 3m Chamber Data no. : 56
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : 8-DPSK 2441MHz Tx Mode
 M/N : H Place

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2441.000	28.33	7.39	36.60	86.02	85.14	74.00	-11.14	Peak
2	4882.000	33.26	9.49	35.51	44.08	51.32	74.00	22.68	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 58
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : 8-DPSK 2441MHz Tx Mode
 M/N : H Place

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2441.000	28.33	7.39	36.60	88.23	87.35	74.00	-13.35	Peak
2	4882.000	33.26	9.49	35.51	44.52	51.76	74.00	22.24	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 61
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : 8-DPSK 2480MHz Tx Mode
 M/N : H Place




Site no. : 3m Chamber Data no. : 59
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : 8-DPSK 2480MHz Tx Mode
 M/N : H Place



Site no. : 3m Chamber Data no. : 62
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : 8-DPSK 2480MHz Tx Mode
 M/N : H Place

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Loss factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.000	28.38	7.47	36.59	84.99	84.25	74.00	-10.25	Peak
2	4960.000	33.42	9.52	35.47	43.44	50.91	74.00	23.09	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 60
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : 8-DPSK 2480MHz Tx Mode
 M/N : H Place

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Loss factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.000	28.38	7.47	36.59	88.22	87.48	74.00	-13.48	Peak
2	4960.000	33.42	9.52	35.47	43.46	50.93	74.00	23.07	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.

5. CONDUCTED SPURIOUS EMISSIONS

5.1. Test Equipments

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum	Agilent	N9030A	MY51380221	Oct.17,15	1 Year
2.	Attenuator (20dB)	Agilent	8491B	MY39262165	Apr.23,16	1 Year
3.	RF Cable	Marvelous Microwave Inc	SFL402105FLEX	NO.1	Oct.17,15	1 Year

5.2. Limit

In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

5.3. Test Procedure

The transmitter output was connected to a spectrum analyzer, The resolution bandwidth is set to 100 kHz, The video bandwidth is set to 300 kHz and measure all the emissions with peak detector.


5.4. Test result

PASS (The testing data was attached in the next pages.)

Hopping off

GFSK


2402MHz(30MHz – 1GHz)



2402MHz(10GHz – 25GHz)




2402MHz(1GHz – 10GHz)




2441(30MHz – 1GHz)



2402MHz(2.3GHz – 2.4GHz)




2441(1GHz – 10GHz)




2441(10GHz – 25GHz)



2480MHz(2.4GHz – 2.5GHz)




2480MHz(30MHz – 1GHz)



2480MHz(10GHz – 25GHz)




2480MHz(1GHz – 10GHz)




8-DPSK


2402MHz(30MHz – 1GHz)




2402MHz(1GHz – 10GHz)




2441MHz (30MHz – 1GHz)



2402MHz(2.3GHz – 2.4GHz)



2441MHz(1GHz – 10GHz)



2402MHz(10GHz – 25GHz)




2441MHz(10GHz – 25GHz)




2480MHz(30MHz – 1GHz)



2480MHz(2.4GHz – 2.5GHz)



2480MHz(1GHz – 10GHz)




2480MHz(10GHz – 25GHz)




Hopping on


GFSK(2.3GHz – 2.4GHz)



8-DPSK(2.3GHz – 2.4GHz)



(2.4GHz – 2.5GHz)



(2.4GHz – 2.5GHz)



6. 20 DB BANDWIDTH TEST

6.1. Test Equipments

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum	Agilent	N9030A	MY51380221	Oct.18,15	1Year
2.	RF Cable	Marvelous Microwave Inc	SFL402105FLEX	NO.1	Oct.17.15	1 Year

6.2. Limit

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

6.3. Test Results

EUT: Home Audio System			
M/N: GTK-XB5			
Test date: 2016-04-29		Pressure: 101.8±1.0kpa	Humidity: 50.9±3.0%
Tested by: THOMAX		Test site: RF site	Temperature:22.5±0.6 °C
Test Mode	Frequency (MHz)	20dB bandwidth (KHz)	Limit (KHz)
GFSK	2402	680.7	N/A
	2441	677.4	N/A
	2480	689.8	N/A
8-DPSK	2402	1164.0	N/A
	2441	1163.0	N/A
	2480	1164.0	N/A
Conclusion : PASS			


GFSK

2402MHz



8-DPSK

2402MHz



2441MHz



2441MHz



2480MHz



2480MHz



7. CARRIER FREQUENCY SEPARATION TEST

7.1. Test Equipments

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum	Agilent	N9030A	MY51380221	Oct.18,15	1 Year
2.	RF Cable	Marvelous Microwave Inc	SFL402105FLEX	NO.1	Oct.17.15	1 Year


7.2. Limit

Frequency hopping systems shall have hopping channel carrier frequency separated by a minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5MHz band may have hopping channel carrier frequencies that are separated by 25kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125mW.

7.3. Test Results.

EUT: Home Audio System		
M/N: GTK-XB5		
Test date: 2016-04-29	Pressure: 101.8±1.0kpa	Humidity: 50.9±3.0%
Tested by: THOMAX	Test site: RF site	Temperature: 22.5±0.6 °C

Test Mode	Channel separation	Limit(KHz)	Conclusion
GFSK	1.0MHz	610.172	PASS
8-DPSK	1.0MHz	806.403	PASS



8. NUMBER OF HOPPING FREQUENCY TEST

8.1. Test Equipments

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum	Agilent	N9030A	MY51380221	Oct.18,15	1 Year
2.	RF Cable	Marvelous Microwave Inc	SFL402105FLEX	NO.1	Oct.17.15	1 Year


8.2. Limit

Frequency hopping systems in the 2400-2483.5MHz band shall use at least 15 channels

8.3. Test Results

EUT: Home Audio System		
M/N: GTK-XB5		
Test date: 2016-04-29	Pressure: 101.8±1.0kpa	Humidity: 50.9±3.0%
Tested by: THOMAX	Test site: RF site	Temperature:22.5±0.6 °C

Test Mode	Number of channel	Limit	Conclusion
8-DPSK	79	>=15	PASS
GFSK	79	>=15	PASS



9. DWELL TIME

9.1. Test Equipments

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum	Agilent	N9030A	MY51380221	Oct.18,15	1 Year
2.	RF Cable	Marvelous Microwave Inc	SFL402105FLEX	NO.1	Oct.17.15	1 Year

9.2. Limit

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

9.3. Test Results



EUT: Home Audio System		
M/N: GTK-XB5		
Test date: 2016-04-29	Pressure: 101.8±1.0kpa	Humidity: 50.9±3.0%
Tested by: THOMAX	Test site: RF site	Temperature: 22.5±0.6 °C

Mode		dwell time	Limit	Conclusion
GFSK	DH1	47 hops/5s*0.4*79channels* 0.427 ms =126.836ms	≅ 400ms	PASS
	DH3	21 hops/5s*0.4*79channels* 1.695 ms =224.960ms	≅ 400ms	PASS
	DH5	15 hops/5s*0.4*79channels* 2.950 ms =279.660ms	≅ 400ms	PASS
8-DPSK	3-DH1	50 hops/5s*0.4*79channels* 0.442 ms =139.672ms	≅ 400ms	PASS
	3-DH3	24 hops/5s*0.4*79channels* 1.683 ms =255.277ms	≅ 400ms	PASS
	3-DH5	14 hops/5s*0.4*79channels* 2.950 ms =261.016ms	≅ 400ms	PASS



Note: All the lower levels were signaled from receiver and should not be considered in here.

GFSK



DH 1



DH 3





DH 5





8-DPSK



3DH 1



3DH 3



3DH 5



10. MAXIMUM PEAK OUTPUT POWER TEST

10.1. Test Equipments

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum	Agilent	N9030A	MY51380221	Oct.18,15	1 Year
2.	Power meter	Anritsu	ML2487A	6K00002472	Aug.21,15	1 Year
3.	Power sensor	Anritsu	MA2491A	0033005	Aug.21,15	1 Year
4.	Attenuator (20dB)	Agilent	8491B	MY39262165	Apr.23,16	1 Year
5.	RF Cable	Marvelous Microwave Inc	SFL402105FLEX	NO.1	Oct.17,15	1 Year

10.2. Limit

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850MHz band: 1 watt.

10.3. Test Procedure

Connected the EUT's antenna port to Power Sensor, and use power meter to test peak output power directly.

10.4. Test Results

EUT: Home Audio System			
M/N: GTK-XB5			
Test date: 2016-04-29		Pressure: 101.8±1.0kpa	Humidity: 50.9±3.0%
Tested by: THOMAX		Test site: RF site	Temperature: 22.5±0.6 °C
Test Mode	Frequency (MHz)	Peak output Power (dBm)	Limit (dBm)
GFSK	2402	-2.188	30
	2441	-1.529	30
	2480	-1.538	30
8-DPSK	2402	-1.802	30
	2441	-1.197	30
	2480	-1.423	30
Conclusion: PASS			

11. BAND EDGE COMPLIANCE TEST

11.1. Test Equipments

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum	Agilent	E4446A	US44300459	Apr.24,16	1 Year
2.	Amp	HP	8449B	3008A02495	Apr.24,16	1 Year
3.	Horn Antenna	ETS	3115	9510-4877	Oct.15,15	1 Year
4.	RF Cable	Hubersuhner	Sucoflex104	274094/4	Apr.24,16	1 Year

11.2. Limit

All the lower and upper band-edges emissions appearing within 2310MHz to 2390MHz and 2483.5MHz to 2500MHz restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

11.3. Test Produce

For upper band emissions that are up to two bandwidths(2MHz) away (2483.5MHz to 2485.5MHz) from the band-edge use below produce:

1. Choose a spectrum analyzer span that encompasses both the peak of the fundamental emission and the band-edge emission under investigation. Set the analyzer RBW to 100KHz and with a video bandwidth 300KHz. Record the peak levels of the fundamental emission and the relevant band-edge emission, Observe the stored trace and measure the amplitude delta between the peak of the fundamental and the peak of the band-edge emission. This is not a field strength measurement, it is only a relative measurement to determine the amount by which the emission drops at the band edge relative to the highest fundamental emission level.
2. Subtract the delta measured in step (1) from the maximum field strengths measured in clause 4 .The resultant field strengths are then used to determine band-edge compliance as required by Section 15.205


For emissions above two bandwidths away from the band-edge use below produce:

1. The EUT is placed on a insulating material (up to 12mm thick) worked at highest radiated power.
2. The turntable was rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upperband-edges of the emission:
 - (a) PEAK: RBW=1MHz ;VBW=3MHz, PK detector, Sweep=AUTO
 - (b) This is pulse Modulation device a duty cycle factor was used to calculate average level based measured peak level.

11.4. Test Results

Pass (The testing data was attached in the next pages.)


Note: If the PK measured levels comply with average limit, then the average level were deemed to comply with average limit.



Site no. : 3m Chamber Data no. : 5
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-L1
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : GFSK 2402MHz Tx Mode
 M/N : V Place

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2340.210	28.21	7.20	36.64	46.54	45.31	74.00	28.69	Peak
2	2390.000	28.27	7.28	36.62	44.52	43.45	74.00	30.55	Peak
3	2400.000	28.28	7.32	36.62	48.17	47.15	74.00	26.85	Peak
4	2401.960	28.28	7.32	36.62	89.62	88.60	74.00	-14.60	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 6
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-L1
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : GFSK 2402MHz Tx Mode
 M/N : V Place

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2387.140	28.26	7.28	36.63	46.95	45.86	74.00	28.14	Peak
2	2390.000	28.27	7.28	36.62	44.81	43.74	74.00	30.26	Peak
3	2400.000	28.28	7.32	36.62	49.34	48.32	74.00	25.68	Peak
4	2401.960	28.28	7.32	36.62	88.42	87.40	74.00	-13.40	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 16
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-L1
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : GFSK 2480MHz Tx Mode
 M/N : V Place

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.871	28.38	7.47	36.59	87.83	87.09	74.00	-13.09	Peak
2	2483.500	28.38	7.51	36.59	44.31	43.61	74.00	30.39	Peak
3	2486.504	28.38	7.51	36.59	46.73	46.03	74.00	27.97	Peak
4	2500.000	28.40	7.51	36.58	43.99	43.32	74.00	30.68	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 15
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-L1
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : GFSK 2480MHz Tx Mode
 M/N : V Place

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.805	28.38	7.47	36.59	90.96	90.22	74.00	-16.22	Peak
2	2483.500	28.38	7.51	36.59	45.44	44.74	74.00	29.26	Peak
3	2489.704	28.40	7.51	36.58	46.81	46.14	74.00	27.86	Peak
4	2500.000	28.40	7.51	36.58	44.58	43.91	74.00	30.09	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 17
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : 8-DPSK 2480MHz Tx Mode
 M/N : V Place

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.805	28.38	7.47	36.59	89.60	88.86	74.00	-14.86	Peak
2	2483.500	28.38	7.51	36.59	44.69	43.99	74.00	30.01	Peak
3	2489.639	28.39	7.51	36.58	46.70	46.02	74.00	27.98	Peak
4	2500.000	28.40	7.51	36.58	44.39	43.72	74.00	30.28	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 18
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : 8-DPSK 2480MHz Tx Mode
 M/N : V Place

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.805	28.38	7.47	36.59	89.67	88.93	74.00	-14.93	Peak
2	2483.500	28.38	7.51	36.59	44.82	44.12	74.00	29.88	Peak
3	2491.256	28.39	7.51	36.58	46.23	45.55	74.00	28.45	Peak
4	2500.000	28.40	7.51	36.58	45.28	44.61	74.00	29.39	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 31
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : 8-DPSK 2402MHz Tx Mode
 M/N : V Place

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2382.675	28.26	7.28	36.63	45.84	44.75	74.00	29.25	Peak
2	2390.000	28.27	7.28	36.62	45.15	44.08	74.00	29.92	Peak
3	2400.000	28.28	7.32	36.62	52.83	51.81	74.00	22.19	Peak
4	2401.960	28.28	7.32	36.62	87.63	86.61	74.00	-12.61	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 32
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : 8-DPSK 2402MHz Tx Mode
 M/N : V Place

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2313.135	28.18	7.12	36.65	46.86	45.51	74.00	28.49	Peak
2	2390.000	28.27	7.28	36.62	44.94	43.87	74.00	30.13	Peak
3	2400.000	28.28	7.32	36.62	53.40	52.38	74.00	21.62	Peak
4	2401.865	28.28	7.32	36.62	88.97	87.95	74.00	-13.95	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 38
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-L1
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : GFSK 2402MHz Tx Mode
 M/N : H Place

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2310.000	28.17	7.12	36.67	44.92	43.54	74.00	30.46	Peak
2	2363.485	28.24	7.24	36.63	46.87	45.72	74.00	28.28	Peak
3	2390.000	28.27	7.28	36.62	45.00	43.93	74.00	30.07	Peak
4	2400.000	28.28	7.32	36.62	46.48	45.46	74.00	28.54	Peak
5	2401.865	28.28	7.32	36.62	87.01	85.99	74.00	-11.99	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 37
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-L1
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : GFSK 2402MHz Tx Mode
 M/N : H Place

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2310.000	28.17	7.12	36.67	45.42	44.04	74.00	29.96	Peak
2	2315.510	28.18	7.12	36.65	47.79	46.44	74.00	27.56	Peak
3	2390.000	28.27	7.28	36.62	45.51	44.44	74.00	29.56	Peak
4	2400.000	28.28	7.32	36.62	53.36	52.34	74.00	21.66	Peak
5	2401.865	28.28	7.32	36.62	94.54	93.52	74.00	-19.52	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 47
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-L1
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : GFSK 2480MHz Tx Mode
 M/N : H Place

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.990	28.38	7.47	36.59	91.47	90.73	74.00	-16.73	Peak
2	2483.500	28.38	7.51	36.59	46.05	45.35	74.00	28.65	Peak
3	2497.194	28.40	7.51	36.58	46.34	45.67	74.00	28.33	Peak
4	2500.000	28.40	7.51	36.58	44.39	43.72	74.00	30.28	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 48
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-L1
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : GFSK 2480MHz Tx Mode
 M/N : H Place

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.990	28.38	7.47	36.59	91.58	90.84	74.00	-16.84	Peak
2	2483.500	28.38	7.51	36.59	44.83	44.13	74.00	29.87	Peak
3	2496.274	28.40	7.51	36.58	46.24	45.57	74.00	28.43	Peak
4	2500.000	28.40	7.51	36.58	43.63	42.96	74.00	31.04	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 54
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-L1
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : 8-DPSK 2402MHz Tx Mode
 M/N : H Place

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2310.000	28.17	7.12	36.67	45.27	43.89	74.00	30.11	Peak
2	2381.250	28.26	7.28	36.63	46.24	45.15	74.00	28.85	Peak
3	2390.000	28.27	7.28	36.62	44.69	43.62	74.00	30.38	Peak
4	2400.000	28.28	7.32	36.62	53.10	52.08	74.00	21.92	Peak
5	2401.865	28.28	7.32	36.62	86.45	85.43	74.00	-11.43	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 53
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-L1
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : 8-DPSK 2402MHz Tx Mode
 M/N : H Place

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2310.000	28.17	7.12	36.67	44.18	42.80	74.00	31.20	Peak
2	2329.190	28.20	7.15	36.65	46.68	45.39	74.00	28.61	Peak
3	2390.000	28.27	7.28	36.62	44.45	43.38	74.00	30.62	Peak
4	2400.000	28.28	7.32	36.62	53.56	52.54	74.00	21.46	Peak
5	2401.865	28.28	7.32	36.62	89.40	88.38	74.00	-14.38	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 63
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-L1
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : 8-DPSK 2480MHz Tx Mode
 M/N : H Place

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.829	28.38	7.47	36.59	85.25	84.51	74.00	-10.51	Peak
2	2483.500	28.38	7.51	36.59	45.08	44.38	74.00	29.62	Peak
3	2494.894	28.39	7.51	36.58	46.24	45.56	74.00	28.44	Peak
4	2500.000	28.40	7.51	36.58	44.94	44.27	74.00	29.73	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 64
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-L1
 EUT : Home Audio System M/N:GTK-XB5
 Power rating : AC 120V/60Hz
 Test Mode : 8-DPSK 2480MHz Tx Mode
 M/N : H Place

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.875	28.38	7.47	36.59	87.17	86.43	74.00	-12.43	Peak
2	2483.500	28.38	7.51	36.59	44.44	43.74	74.00	30.26	Peak
3	2485.809	28.38	7.51	36.59	46.79	46.09	74.00	27.91	Peak
4	2500.000	28.40	7.51	36.58	44.80	44.13	74.00	29.87	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.

12. ANTENNA REQUIREMENT

12.1. Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

12.2. Antenna Connected Construction

The antennas used for this product are PCB antenna that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is 2.4dBi

13.DEVIATION TO TEST SPECIFICATIONS

[NONE]