



# RADIO TEST REPORT

**Test Report No.: 32KE0130-SH-01-A**

**Applicant** : Sony Corporation  
**Type of Equipment** : Bluetooth Audio System  
**Model No.** : MEX-BT4100P  
**FCC ID** : AK8MEXBT4100  
**Test regulation** : FCC Part15 Subpart C: 2012  
**Test result** : Complied

1. This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
2. The results in this report apply only to the sample tested.
3. This sample tested is in compliance with the limits of the above regulation.
4. The test results in this test report are traceable to the national or international standards.
5. This test report must not be used by the customer to claim product certification, approval, or endorsement by any agency of the Federal Government.
6. The opinions and the interpretations to the result of the description in this report are outside scopes where UL Japan has been accredited.

**Date of test:** June 19 to 27, 2012

**Tested by:**

*K. Adachi*

Kenichi Adachi  
Engineer of WiSE Japan,  
UL Verification Service

**Approved by :**

*T. Imamura*

Toyokazu Imamura  
Leader of WiSE Japan,  
UL Verification Service

- The testing in which "Non-accreditation" is displayed is outside the accreditation scopes in UL Japan.  
 There is no testing item of "Non-accreditation".



**UL Japan, Inc.**  
**Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

13-EM-F0429



**Contents**

	<b><u>Page</u></b>
<b>SECTION 1: Customer information .....</b>	<b>4</b>
<b>SECTION 2: Equipment under test (E.U.T.) .....</b>	<b>4</b>
<b>SECTION 3: Test specification, procedures &amp; results .....</b>	<b>5</b>
<b>SECTION 4: Operation of E.U.T. during testing .....</b>	<b>8</b>
<b>SECTION 5: Carrier frequency separation .....</b>	<b>11</b>
<b>SECTION 6: 20dB bandwidth &amp; Occupied bandwidth (99%) .....</b>	<b>11</b>
<b>SECTION 7: Number of hopping frequency .....</b>	<b>11</b>
<b>SECTION 8: Dwell time .....</b>	<b>11</b>
<b>SECTION 9: Maximum peak output power .....</b>	<b>11</b>
<b>SECTION 10: Spurious emissions (Radiated) .....</b>	<b>12</b>
<b>SECTION 11: Spurious emissions (Antenna port conducted) .....</b>	<b>13</b>
<b>Contents of APPENDIXES .....</b>	<b>14</b>
<b>APPENDIX 1: Data of radio tests .....</b>	<b>15</b>
<b>APPENDIX 2: Test instruments .....</b>	<b>49</b>
<b>APPENDIX 3: Photographs of test setup .....</b>	<b>50</b>

---

**UL Japan, Inc.**

**Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

**SECTION 1: Customer information**

Company Name : Sony Corporation  
Address : Shinagawa INTERCITY C Tower 2-15-3, Konan Minato-ku, Tokyo, Japan  
Telephone Number : +81-3-5769-5640  
Facsimile Number : +81-3-5769-5901  
Contact Person : Maeda Toshihiro

**SECTION 2: Equipment under test (E.U.T.)****2.1 Identification of E.U.T.**

Type of Equipment : Bluetooth Audio System  
Model Number : MEX-BT4100P  
Serial Number : Refer to clause 4.2  
Rating : DC12V  
Country of Mass-production : Thailand  
Condition of EUT : Engineering prototype  
(Not for Sale: This sample is equivalent to mass-produced items.)  
Receipt Date of Sample : June 19, 2012  
Modification of EUT : No modification by the test lab.

**2.2 Product description**

Model: MEX-BT4100P (referred to as the EUT in this report) is a Bluetooth Audio System.

Clock frequency(ies) in the system : 36.48MHz, 24.000 MHz, 16.934MHz, 12MHz, 7.920MHz, 32.768kHz

Bluetooth specification:

Equipment type : Transceiver  
Frequency of operation : 2402-2480MHz  
Bandwidth & channel spacing : 79MHz & 1MHz  
Type of modulation : FHSS  
Antenna type : Inverted F  
Antenna connector type : U-FL  
Antenna gain with cable loss : -4.9dBi  
ITU code : F1D, G1D  
Operation temperature range : -20 to +60 deg.C.

FCC 15.31 (e)

The equipment provides the Bluetooth transmitter with stable power supply (DC 3.3 V), therefore, the equipment complies with power supply regulation.

FCC 15.203

The equipment and its antenna comply with this requirement since this antenna is built in the equipment and it cannot be replaced by end users.

---

**UL Japan, Inc.****Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

**SECTION 3: Test specification, procedures & results****3.1 Test specification**

Test specification : FCC Part 15 Subpart C: 2012, final revised on May 17, 2012 and effective June 18, 2012  
 Title : FCC 47CFR Part15 Radio Frequency Device Subpart C Intentional Radiators  
 Section 15.207 Conducted limits  
 Section 15.209 Radiated emission limits, general requirements  
 Section 15.247 Operation within the bands 902-928MHz, 2400-2483.5MHz,  
 and 5725-5850MHz

The EUT complies with FCC Part 15 Subpart B. Refer to the test report: 32KE0130-SH-01-C.

**3.2 Procedures & Results**

Item	Test Procedure	Specification	Remarks	Deviation	Worst Margin	Results
Conducted emission	ANSI C63.4:2009 7. AC powerline conducted emission measurements	FCC 15.207	-	N/A *1)	N/A	N/A
Carrier frequency separation	FCC Public Notice DA 00-705 & ANSI C63.4:2009 13. Measurement of intentional radiators	FCC 15.247 (a)(1)	Conducted	N/A	*See data.	Complied
20dB bandwidth	FCC Public Notice DA 00-705 & ANSI C63.4:2009 13. Measurement of intentional radiators	FCC 15.247 (a)(1)	Conducted	N/A		-
Number of hopping frequency	FCC Public Notice DA 00-705 & ANSI C63.4:2009 13. Measurement of intentional radiators	FCC 15.247 (a)(1)(iii)	Conducted	N/A		Complied
Dwell time	FCC Public Notice DA 00-705 & ANSI C63.4:2009 13. Measurement of intentional radiators	FCC 15.247 (a)(1)(iii)	Conducted	N/A		Complied
Maximum peak output power	FCC Public Notice DA 00-705 & ANSI C63.4:2009 13. Measurement of intentional radiators	FCC 15.247 (b)(1)	Conducted	N/A		Complied
Band edge compliance & Spurious emission	FCC Public Notice DA 00-705 & ANSI C63.4:2009 13. Measurement of intentional radiators	FCC 15.247 (d) 15.209	Conducted/ Radiated	N/A		6.0dB Freq.: 30.286MHz Polarization: Vertical Detection: Quasi-Peak Mode: Tx 2441MHz, DH5

Note: UL Japan's Work Procedures No. 13-EM-W0420 and 13-EM-W0422  
 \*1) The test is not applicable since the EUT does not have AC Mains.

**UL Japan, Inc.****Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

### 3.3 Addition to standard

Item	Test Procedure	Specification	Remarks	Worst Margin	Results
Occupied Bandwidth (99%)	ANSI C63.4:2009 13. Measurement of intentional radiators, RSS-Gen 4.6.1	-	Conducted	-	-
Note: UL Japan's Work Procedures No. 13-EM-W0420 and 13-EM-W0422					

\* Other than above, no addition, exclusion nor deviation has been made from the standard.

### 3.4 Uncertainty

The following uncertainties have been calculated to provide a confidence level of 95% using a coverage factor k=2.

Item	Frequency range	No.1 SAC* <sup>1</sup> (±)	No.2 SAC (±)	No.3 SAC (±)
<b>Radiated emission (Measurement distance: 3m)</b>	9kHz-30MHz	3.7 dB	3.7 dB	3.6 dB
	30MHz-300MHz	4.9 dB	5.1 dB	5.0 dB
	300MHz-1GHz	5.0 dB	5.2 dB	5.0 dB
	1GHz-15GHz	4.8 dB	4.8 dB	4.9 dB
<b>Radiated emission (Measurement distance: 1m)</b>	15GHz-18GHz	5.6 dB	5.6 dB	5.6 dB
	18GHz-40GHz	4.8 dB	4.3 dB	4.4 dB

\*1: SAC=Semi-Anechoic Chamber

The data listed in this test report has enough margin, more than site margin.

#### Antenna port conducted test

Power measurement uncertainty above 1GHz for this test was: (±) 1.5dB

Spurious emission (Conducted) measurement (below 1GHz) uncertainty for this test was: (±) 1.7dB

Spurious emission (Conducted) measurement (1G-3GHz) uncertainty for this test was: (±) 2.3dB

Spurious emission (Conducted) measurement (3G-18GHz) uncertainty for this test was: (±) 3.0dB

Spurious emission (Conducted) measurement (18G-26.5GHz) uncertainty for this test was: (±) 2.9dB

Bandwidth measurement uncertainty for this test was: (±) 5.4%

## UL Japan, Inc.

### Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

### 3.5 Test location

UL Japan, Inc. Shonan EMC Lab.

1-22-3, Megumigaoka, Hiratsuka-shi, Kanagawa-ken 259-1220 JAPAN

Telephone number : +81 463 50 6400

Facsimile number : +81 463 50 6401

JAB Accreditation No. : RTL02610

	FCC Registration No.	IC Registration No.	Width x Depth x Height (m)	Size of reference ground plane (m) / horizontal conducting plane	Maximum measurement distance
<input type="checkbox"/> No.1 Semi-anechoic chamber	697847	2973D-1	20.6 x 11.3 x 7.65	20.6 x 11.3	10m
<input type="checkbox"/> No.2 Semi-anechoic chamber	697847	2973D-2	20.6 x 11.3 x 7.65	20.6 x 11.3	10m
<input checked="" type="checkbox"/> No.3 Semi-anechoic chamber	697847	2973D-3	12.7 x 7.7 x 5.35	12.7 x 7.7	5m
<input type="checkbox"/> No.4 Full-anechoic chamber	-	-	8.1 x 5.1 x 3.55	8.1 x 5.1	-
<input type="checkbox"/> No.1 shielded room	-	-	6.8 x 4.1 x 2.7	6.8 x 4.1	-
<input type="checkbox"/> No.2 shielded room	-	-	6.8 x 4.1 x 2.7	6.8 x 4.1	-
<input type="checkbox"/> No.3 shielded room	-	-	6.3 x 4.7 x 2.7	6.3 x 4.7	-
<input type="checkbox"/> No.4 shielded room	-	-	4.4 x 4.7 x 2.7	4.4 x 4.7	-
<input checked="" type="checkbox"/> No.5 shielded room	-	-	7.8 x 6.4 x 2.7	7.8 x 6.4	-
<input type="checkbox"/> No.6 shielded room	-	-	7.8 x 6.4 x 2.7	7.8 x 6.4	-

### 3.6 Test setup, Data of test & Test instruments

Refer to APPENDIX 1 to 3.

**UL Japan, Inc.**

**Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

## **SECTION 4: Operation of E.U.T. during testing**

### **4.1 Operating mode**

The EUT exercise program used during testing was designed to exercise the various system components in a manner similar to typical use.

<b>Test item</b>	<b>Operating mode</b>	<b>Tested frequency</b>
Carrier frequency separation	Transmitting Hopping ON (DH5/3-DH5)/Inquiry, Payload: PRBS9	-
20dB bandwidth	Transmitting Hopping OFF (DH5/3-DH5)/Inquiry, Payload: PRBS9	2402MHz, 2441MHz, 2480MHz
Number of hopping frequency	Transmitting Hopping ON (DH5/3-DH5)/Inquiry, Payload: PRBS9	-
Dwell time	Transmitting (Hopping ON) -DH1, -DH3, -DH5 -3-DH1, -3-DH3, -3-DH5 -Inquiry	-
Maximum peak output power	Transmitting Hopping OFF (DH5/2-DH5/3-DH5) /Inquiry, Payload: PRBS9 -DH5 -2-DH5 -3-DH5	2402MHz, 2441MHz, 2480MHz
Band edge compliance & Spurious emission (Conducted)	Transmitting (DH5/3-DH5), Payload: PRBS9 -Hopping ON/Inquiry -Hopping OFF	Band edge compliance: 2402MHz, 2480MHz
(Radiated)	Transmitting (DH5/3-DH5), Payload: PRBS9	Spurious emission: 2402MHz, 2441MHz, 2480MHz
99% occupied bandwidth	Transmitting (DH5/3-DH5), Payload: PRBS9 -Hopping ON -Hopping OFF	2402MHz, 2441MHz, 2480MHz

\*As a result of preliminary test, the formal test was performed with the above modes, which had the maximum payload (except Dwell time test)

\*Remarks: Test was not performed at AFH mode, because the decrease of number of channel (min: 20ch) at AFH mode does not affect the output power and bandwidth of the EUT.

As this device had AFH mode and frequency separation could not meet the requirement of over 20dB BW without 2/3 relaxation, 125mW power limit was applied to it.

EUT has the power settings by the software as follows;

Power settings: BDR: Ext.=255, Int.=44

EDR: Ext.=255, Int.=48

Software: BtCli.exe Version 1.24 (for Inquiry mode), BlueTest.exe Version 1.24 (for other mode)

**UL Japan, Inc.**


**Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

## 4.2 Configuration and peripherals



\* Cabling and setup were taken into consideration and test data was taken under worse case conditions.

\*1) DC power supply (Model No.: PAN35-10A) was used for DC 12V input.

### Description of EUT and support equipment

No.	Item	Model number	Serial number	Manufacturer	Remarks
A	Bluetooth Audio System	MEX-BT4100P	*2)	Sony	EUT
B	Remote Commander	RM-X231	-	Sony	-
C	USB Memory	SDK-USM4GL(B)	10615MEDB	Sony	-
D	Microphone	XA-MC10	-	Sony	-
E	Wired Remote Controller	RM-X4S	-	Sony	-
F	Speaker 1	XS-F1611	-	Sony	-
G	Speaker 2	XS-F1611	-	Sony	-
H	Speaker 3	1-544-814-31	-	AIWA	-
I	Speaker 4	1-544-814-31	-	AIWA	-
J	Stereo Power Amplifier	XM-423SL	0020316	Sony	-
K	SIRIUS XM Connector Vehicle Tuner	SXV100	1113	SIRIUS	-
L	Antenna	XVANT1	1046	SIRIUS	-

\*2) 33: for Antenna terminal conducted tests, 32: for Radiated emission tests

**UL Japan, Inc.**

**Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

**List of cables used**

No.	Name	Length (m)	Shield		Remark
			Cable	Connector	
1	USB	2.0	Shielded	Shielded	-
2	AUX	3.0	Shielded	Shielded	-
3	FM antenna	1.1	Shielded	Shielded	-
4	External Microphone	0.25+4.0	Shielded	Shielded	-
5	REMOTE IN	1.9	Shielded	Shielded	-
6	Speaker (1)	0.25+2.0	Unshielded	Unshielded	-
7	Speaker (2)	0.25+2.0	Unshielded	Unshielded	-
8	Speaker (3)	0.25+2.0	Unshielded	Unshielded	-
9	Speaker (4)	0.25+2.0	Unshielded	Unshielded	-
10	DC Power	1.5	Unshielded	Unshielded	-
11	RCA (Front Audio Out)	5.0	Shielded	Shielded	-
12	RCA (Rear Audio Out)	5.0	Shielded	Shielded	-
13	RCA (Sub Audi Out)	1.5	Shielded	Shielded	-
14	Illumination	3.0	Unshielded	Unshielded	-
15	AMP Remote	3.0	Unshielded	Unshielded	-
16	DC Power	0.7+0.7	Unshielded	Unshielded	-
17	Sirius Tuner	0.8	Shielded	Shielded	-
18	Sirius Antenna	6.8	Shielded	Shielded	-

\* All cables used for the measurement are exclusive use or marketed.

**UL Japan, Inc.****Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

### **SECTION 5: Carrier frequency separation**

#### **Test procedure**

The carrier frequency separation was measured with a spectrum analyzer connected to the antenna port.

Summary of the test results: Pass

Refer to APPENDIX 1

### **SECTION 6: 20dB bandwidth & Occupied bandwidth (99%)**

#### **Test procedure**

The bandwidth was measured with a spectrum analyzer connected to the antenna port.

The channel separation in Hopping mode and Inquiry mode was separated by 25kHz and 2/3 of the 20dB bandwidth.

Summary of the test results: Pass

Refer to APPENDIX 1

### **SECTION 7: Number of hopping frequency**

#### **Test procedure**

The number of hopping frequency was measured with a spectrum analyzer connected to the antenna port.

Summary of the test results: Pass

Refer to APPENDIX 1

### **SECTION 8: Dwell time**

#### **Test procedure**

The dwell time was measured with a spectrum analyzer connected to the antenna port.

Summary of the test results: Pass

Refer to APPENDIX 1

### **SECTION 9: Maximum peak output power**

#### **Test procedure**

The maximum peak output power was measured with a power meter connected to the antenna port.

Summary of the test results: Pass

Refer to APPENDIX 1

---

**UL Japan, Inc.**

**Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

---

## **SECTION 10: Spurious emissions (Radiated)**

### **10.1 Operating environment**

Test place : See test data (APPENDIX 1)  
 Temperature : See test data (APPENDIX 2)  
 Humidity : See test data (APPENDIX 2)

### **10.2 Test configuration**

EUT was placed on a platform of nominal size, 1m by 1.5m (for 30-1000MHz) or 1m by 2.0m (for 1-25GHz), raised 0.8m above the conducting ground plane. The table is made of Styrofoam and covered with polyvinyl chloride. That has very low permittivity. The rear of EUT was aligned and flushed with rear of tabletop. I/O cables that were connected to the peripherals were bundled in center. They were folded back and for the forming a bundle 0.3 to 0.4m long and were hanged at a 0.4m height to the ground plane. Photographs of the set up are shown in Appendix 1.

### **10.3 Test conditions**

Frequency range : 30MHz to 25GHz  
 EUT position : Table top

### **10.4 Test procedure**

The Radiated Electric Field Strength intensity has been measured on a semi-anechoic chamber with a ground plane and at a distance of 3m (below 15GHz) / 1m (above 15GHz) (Refer to Figure 1). Measurements were performed with quasi-peak, peak and average detector. The measuring antenna height was varied between 1 and 4m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity. The measurements were performed for both vertical and horizontal antenna polarization.

The radiated emission measurements were made with the following detection of the test receiver.

Frequency	30-1000MHz	1-25GHz		20dBc
Detection type	Quasi-Peak	Peak	Average *1)	Peak
IF Bandwidth	120kHz	RBW: 1MHz VBW: 3MHz	RBW: 1MHz VBW: 10Hz	RBW: 100kHz VBW: 300kHz

\*1) When using Spectrum analyzer, the test was made with adjusting span to zero by using peak hold.

Although 00-705 accepts VBW=10Hz for AV measurements, confirmed that superfluous smoothing was not performed.

The carrier level and noise levels were confirmed at angle of 0 to 45 deg. based on the product specification to see the position of maximum noise, and the test was made at the position (45 deg.) that has the maximum noise.

---

## **UL Japan, Inc.**


### **Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

**Figure 1. Antenna angle**



**10.5 Band edge**

Band edge level at 2390MHz and 2483.5MHz is below the limits of FCC 15.209 and band edge level at 2400MHz is below the 20dBc. Refer to the data.

**10.6 Results**

Summary of the test results : Pass \*No harmonics other than listed on the data were detected.

Refer to APPENDIX 1

**SECTION 11: Spurious emissions (Antenna port conducted)**

**Test procedure**

The spurious emissions were measured with a spectrum analyzer connected to the antenna port. In any 100kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator confirmed 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on a radiated measurement. In the frequency range below 30MHz, RBW was narrowed to separate the noise contents. Then, wide-band noise near the limit was checked separately, however the noise was not detected as shown in the chart.  
(9kHz-150kHz:RBW=200Hz, 150kHz-30MHz:RBW=10kHz)

Summary of the test results: Pass  
Refer to APPENDIX 1

## **Contents of APPENDIXES**

### **APPENDIX 1: Data of Radio tests**

20dB bandwidth and Carrier frequency separation  
Number of hopping frequency  
Dwell time  
Maximum peak output power  
Radiated emission  
Spurious emission (Antenna port conducted)  
Occupied bandwidth

### **APPENDIX 2: Test instruments**

Test instruments

### **APPENDIX 3: Photographs of test setup**

Radiated emission

---

**UL Japan, Inc.**

**Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401


**APPENDIX 1: Data of radio tests**

**20dB Bandwidth and Carrier Frequency Separation**

Test place                   UL Japan, Inc. Shonan EMC Lab.           No.5 Shielded Room  
 Date                         June 19, 2012  
 Temperature / Humidity   26 deg.C     , 62 %RH  
 Engineer                  Kenichi Adachi  
 Mode                        Tx, Bluetooth, BDR, PRBS9

Mode	Freq. [MHz]	20dB Bandwidth [MHz]	Carrier Frequency Separation [MHz]	Limit for Carrier Frequency Separation [MHz]
DH5	2402.0	0.929	1.000	>= 0.620
DH5	2441.0	0.937	1.000	>= 0.625
DH5	2480.0	0.961	1.000	>= 0.641
Inquiry	2441.0	0.812	2.000	>= 0.541

Limit: Two-thirds of 20dB Bandwidth or 25kHz (whichever is greater).  
 No limit applies to 20dB Bandwidth.




**UL Japan, Inc.**

**Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN  
 Telephone : +81 463 50 6400  
 Facsimile : +81 463 50 6401

## 20dB Bandwidth and Carrier Frequency Separation

### Tx, Bluetooth, BDR, PRBS9



**UL Japan, Inc.**

**Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

## 20dB Bandwidth and Carrier Frequency Separation

Test place                    UL Japan, Inc. Shonan EMC Lab.                    No.5 Shielded Room  
 Date                             June 19, 2012  
 Temperature / Humidity    26 deg.C     , 62 %RH  
 Engineer                       Kenichi Adachi  
 Mode                             Tx, Bluetooth, EDR, PRBS9

Mode	Freq. [MHz]	20dB Bandwidth [MHz]	Carrier Frequency Separation [MHz]	Limit for Carrier Frequency Separation [MHz]
3-DH5	2402.0	1.301	1.000	>= 0.867
3-DH5	2441.0	1.268	1.000	>= 0.845
3-DH5	2480.0	1.259	1.000	>= 0.839

Limit: Two-thirds of 20dB Bandwidth or 25kHz (whichever is greater).  
 No limit applies to 20dB Bandwidth.


**UL Japan, Inc.**

**Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN  
 Telephone     : +81 463 50 6400  
 Facsimile     : +81 463 50 6401

## 20dB Bandwidth and Carrier Frequency Separation

### Tx, Bluetooth, EDR, PRBS9



**UL Japan, Inc.**

**Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN

Telephone : +81 463 50 6400


Facsimile : +81 463 50 6401

### Number of Hopping Frequency

Test place	UL Japan, Inc. Shonan EMC Lab.	No.5 Shielded Room
Date	June 19, 2012	
Temperature / Humidity	26 deg.C , 62 %RH	
Engineer	Kenichi Adachi	
Mode	Tx, Bluetooth, BDR, PRBS9	

Mode	Number of Channel [times]	Limit [times]
DH5	79	>= 15

Test was not performed at AFH mode whose number of hopping channel is 20 channels because this Bluetooth radio is in compliance of Bluetooth Specification.



**UL Japan, Inc.**

**Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN


Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

### Number of Hopping Frequency

Test place	UL Japan, Inc. Shonan EMC Lab.	No.5 Shielded Room
Date	June 19, 2012	
Temperature / Humidity	26 deg.C , 62 %RH	
Engineer	Kenichi Adachi	
Mode	Tx, Bluetooth, Inquiry	

Mode	Number of Channel [times]	Limit [times]
Inquiry	32	>= 15




**UL Japan, Inc.**  
**Shonan EMC Lab.**  
 1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN  
 Telephone : +81 463 50 6400  
 Facsimile : +81 463 50 6401

### Number of Hopping Frequency

Test place	UL Japan, Inc. Shonan EMC Lab.	No.5 Shielded Room
Date	June 19, 2012	
Temperature / Humidity	26 deg.C , 62 %RH	
Engineer	Kenichi Adachi	
Mode	Tx, Bluetooth, EDR, PRBS9	

Mode	Number of Channel [times]	Limit [times]
3-DH5	79	>= 15

Test was not performed at AFH mode whose number of hopping channel is 20 channels because this Bluetooth radio is in compliance of Bluetooth Specification.



**UL Japan, Inc.**

**Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

## Dwell Time


Test place           UL Japan, Inc. Shonan EMC Lab.           No.5 Shielded Room  
 Date                 June 19, 2012  
 Temperature / Humidity 26 deg.C   , 62 %RH  
 Engineer            Kenichi Adachi  
 Mode                Tx, Bluetooth, BDR, PRBS9

Mode	Number of transmission in a 31.6 (79 Hopping x 0.4) / 12.8 (32 Hopping x 0.4) second period	Length of transmission time [msec]	Result [msec]	Limit [msec]
DH1	50.0 / 5.0 sec. x 31.6 sec. = 316 times	0.404	128	400
DH3	26.0 / 5.0 sec. x 31.6 sec. = 165 times	1.660	274	400
DH5	17.0 / 5.0 sec. x 31.6 sec. = 108 times	2.908	314	400
Inquiry	100.0 / 1.0 sec. x 12.8 sec. = 1280 times	0.105	134	400

Sample Calculation

Result = Number of transmission x Length of transmission time

This device complies with the Bluetooth protocol for FHSS operation, employing a pseudo random channel selection and hopping rate to ensure that the occupancy time in  $N \times 0.4s$ , where  $N$  is the number of channels being used in the hopping sequence ( $20 \leq N \leq 79$ ), is always less than 0.4s regardless of packet size (DH1, DH3 or DH5). This is confirmed in the test report for  $N=79$ .



**UL Japan, Inc.**

**Shonan EMC Lab.**


1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN

Telephone       : +81 463 50 6400

Facsimile       : +81 463 50 6401

## Dwell time

### Tx, Bluetooth, BDR, PRBS9



**UL Japan, Inc.**

**Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

## Dwell Time

Test place           UL Japan, Inc. Shonan EMC Lab.           No.5 Shielded Room  
 Date                 June 19, 2012  
 Temperature / Humidity 26 deg.C   , 62 %RH  
 Engineer            Kenichi Adachi  
 Mode                Tx, Bluetooth, EDR, PRBS9

Mode	Number of transmission in a 31.6 (79 Hopping x 0.4) second period	Length of transmission time [msec]	Result [msec]	Limit [msec]
3-DH1	50.0 / 5.0 sec. x 31.6 sec. = 316 times	0.416	132	400
3-DH3	26.0 / 5.0 sec. x 31.6 sec. = 165 times	1.667	275	400
3-DH5	17.0 / 5.0 sec. x 31.6 sec. = 108 times	2.915	315	400

Sample Calculation

Result = Number of transmission x Length of transmission time

This device complies with the Bluetooth protocol for FHSS operation, employing a pseudo random channel selection and hopping rate to ensure that the occupancy time in  $N \times 0.4s$ , where  $N$  is the number of channels being used in the hopping sequence ( $20 \leq N \leq 79$ ), is always less than 0.4s regardless of packet size (3DH1, 3DH3 or 3DH5). This is confirmed in the test report for  $N=79$ .

**UL Japan, Inc.**

**Shonan EMC Lab.**


1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

## Dwell time

### Tx, Bluetooth, EDR, PRBS9



**UL Japan, Inc.**

**Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

## Peak Output Power (Conducted)

Test place                   UL Japan, Inc. Shonan EMC Lab.       No.5 Shielded Room  
 Date                         June 19, 2012  
 Temperature / Humidity   26 deg.C   , 62 %RH  
 Engineer                  Kenichi Adachi  
 Mode                        Tx, Bluetooth

(\* P/M: Power Meter with power sensor)

	Freq. [MHz]	P/M (Peak) Reading [dBm]	Cable Loss [dB]	Atten. Loss [dB]	Result		Limit		Margin [dB]
					[dBm]	[mW]	[dBm]	[mW]	
DH5	2402.0	-9.74	1.03	9.68	0.97	1.25	20.97	125	20.00
DH5	2441.0	-9.54	1.04	9.68	1.18	1.31	20.97	125	19.79
DH5	2480.0	-9.18	1.05	9.68	1.55	1.43	20.97	125	19.42
2-DH5	2402.0	-9.21	1.03	9.68	1.50	1.41	20.97	125	19.47
2-DH5	2441.0	-8.95	1.04	9.68	1.77	1.50	20.97	125	19.20
2-DH5	2480.0	-8.95	1.05	9.68	1.78	1.51	20.97	125	19.19
3-DH5	2402.0	-9.18	1.03	9.68	1.53	1.42	20.97	125	19.44
3-DH5	2441.0	-8.84	1.04	9.68	1.88	1.54	20.97	125	19.09
3-DH5	2480.0	-8.97	1.05	9.68	1.76	1.50	20.97	125	19.21

Sample Calculation:

Result = Reading + Cable Loss (including the cable(s) customer supplied) + Atten. Loss

**UL Japan, Inc.**  
**Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN  
 Telephone    : +81 463 50 6400  
 Facsimile    : +81 463 50 6401














### Spurious emission (Conducted)

Tx, Bluetooth, BDR, PRBS9

Tx, 2402MHz (1/2)



**UL Japan, Inc.**

**Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN


Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

### Spurious emission (Conducted)

Tx, Bluetooth, BDR, PRBS9

Tx, 2402MHz (2/2)



**UL Japan, Inc.**

**Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

### Spurious emission (Conducted)

Tx, Bluetooth, BDR, PRBS9

Tx, 2441MHz (1/2)



**UL Japan, Inc.**

**Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN


Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

### Spurious emission (Conducted)

Tx, Bluetooth, BDR, PRBS9

Tx, 2441MHz (2/2)



**UL Japan, Inc.**

**Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

### Spurious emission (Conducted)

Tx, Bluetooth, BDR, PRBS9

Tx, 2480MHz (1/2)



**UL Japan, Inc.**

**Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN


Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

**Spurious emission (Conducted)**

Tx, Bluetooth, BDR, PRBS9

Tx, 2480MHz (2/2)



**UL Japan, Inc.**  
**Shonan EMC Lab.**  
 1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN  
 Telephone : +81 463 50 6400  
 Facsimile : +81 463 50 6401

**Spurious emission (Conducted)**

**Tx, Bluetooth, EDR, PRBS9**

**Tx, 2402MHz (1/2)**




**UL Japan, Inc.**  
**Shonan EMC Lab.**  
 1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN  
 Telephone : +81 463 50 6400  
 Facsimile : +81 463 50 6401

### Spurious emission (Conducted)

Tx, Bluetooth, EDR, PRBS9

Tx, 2402MHz (2/2)



UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

### Spurious emission (Conducted)

Tx, Bluetooth, EDR, PRBS9

Tx, 2441MHz (1/2)



**UL Japan, Inc.**

**Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN


Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

### Spurious emission (Conducted)

Tx, Bluetooth, EDR, PRBS9

Tx, 2441MHz (2/2)



**UL Japan, Inc.**

**Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

### Spurious emission (Conducted)

Tx, Bluetooth, EDR, PRBS9

Tx, 2480MHz (1/2)



**UL Japan, Inc.**

**Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN


Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

### Spurious emission (Conducted)

Tx, Bluetooth, EDR, PRBS9

Tx, 2480MHz (2/2)



**UL Japan, Inc.**

**Shonan EMC Lab.**



1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

## Spurious emission (Conducted)

### Band Edge compliance



**UL Japan, Inc.**

**Shonan EMC Lab.**



1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

## Spurious emission (Conducted)

### Band Edge compliance



**UL Japan, Inc.**

**Shonan EMC Lab.**


1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401



### 99% Occupied Bandwidth



**UL Japan, Inc.**

**Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

## APPENDIX 2

### Test Instruments

#### EMI test equipment

Control No.	Instrument	Manufacturer	Model No	Serial No	Test Item	Calibration Date * Interval(month)
SPSS-03	Power sensor	Anritsu	MA2411B	0917063	AT	2012/04/19 * 12
SPM-06	Power Meter	Anritsu	ML2495A	0850009	AT	2012/04/19 * 12
KSA-08	Spectrum Analyzer	Agilent	E4446A	MY46180525	AT	2012/02/16 * 12
SCC-G12	Coaxial Cable	Suhner	SUCOFLEX 102	30790/2	AT	2012/03/12 * 12
SAT10-09	Attenuator	Weinschel Corp.	54A-10	W5692	AT	2011/11/09 * 12
SBM-09	Barometer	Sunoh	SBR121	001074	AT	2012/02/23 * 36
SOS-09	Humidity Indicator	A&D	AD-5681	4061484	AT	2012/03/26 * 12
SAF-05	Pre Amplifier	TOYO Corporation	TPA0118-36	1440490	RE	2012/03/12 * 12
SCC-G02	Coaxial Cable	Suhner	SUCOFLEX 104A	46498/4A	RE	2012/04/10 * 12
SCC-G22	Coaxial Cable	Suhner	SUCOFLEX 104	296199/4	RE	2012/05/22 * 12
SHA-02	Horn Antenna	Schwarzbeck	BBHA9120D	9120D-726	RE	2011/08/28 * 12
SOS-03	Humidity Indicator	A&D	AD-5681	4063325	RE	2012/02/06 * 12
SSA-02	Spectrum Analyzer	Agilent	E4448A	MY48250106	RE	2012/03/16 * 12
SJM-02	Measure	KOMELON	KMC-36	-	RE	-
COTS-SEMI-1	EMI Software	TSJ	TEPTO-DV(RE,CE, RFLMF)	-	RE	-
SAt10-06	Attenuator	Agilent	8493C-010	74865	RE	2011/12/27 * 12
SFL-02	Highpass Filter	MICRO-TRONICS	HPM50111	051	RE	2011/12/27 * 12
SAF-03	Pre Amplifier	SONOMA	310N	290213	RE	2012/02/10 * 12
SAT6-03	Attenuator	JFW	50HF-006N	-	RE	2012/02/10 * 12
SBA-03	Biconical Antenna	Schwarzbeck	BBA9106	91032666	RE	2011/10/23 * 12
SCC-C1/C2/C3/C4/C5/C10/SRSE-03	Coaxial Cable&RF Selector	Fujikura/Fujikura/Suhner/Suhner/Suhner/Suhner/TOYO	8D2W/12DSFA/141PE/141PE/141PE/141PE/NS4906	-/0901-271(RF Selector)	RE	2012/04/10 * 12
SLA-03	Logperiodic Antenna	Schwarzbeck	UHALP9108A	UHALP 9108-A 0901	RE	2011/10/23 * 12
SOS-05	Humidity Indicator	A&D	AD-5681	4062518	RE	2012/02/06 * 12
STR-06	Test Receiver	Rohde & Schwarz	ESCI	101259	RE	2012/02/07 * 12
SJM-10	Measure	PROMART	SEN1935	-	RE	-
SAEC-03(NSA)	Semi-Anechoic Chamber	TDK	SAEC-03(NSA)	3	RE	2011/09/23 * 12
SAF-06	Pre Amplifier	TOYO Corporation	TPA0118-36	1440491	RE	2011/07/19 * 12
SCC-G03	Coaxial Cable	Suhner	SUCOFLEX 104A	46499/4A	RE	2012/04/10 * 12
SCC-G23	Coaxial Cable	Suhner	SUCOFLEX 104	297342/4	RE	2012/05/22 * 12
SHA-03	Horn Antenna	Schwarzbeck	BBHA9120D	9120D-739	RE	2011/08/28 * 12
KSA-08	Spectrum Analyzer	Agilent	E4446A	MY46180525	RE	2012/02/16 * 12
SHA-04	Horn Antenna	ETS LINDGREN	3160-09	LM3640	RE	2012/03/30 * 12
SAF-08	Pre Amplifier	TOYO Corporation	HAP18-26W	00000019	RE	2012/03/12 * 12
SCC-G17	Coaxial Cable	Suhner	SUCOFLEX 104A	46291/4A	RE	2012/03/12 * 12
SFL-02	Highpass Filter	MICRO-TRONICS	HPM50111	051	RE	2011/12/27 * 12

The expiration date of the calibration is the end of the expired month .  
As for some calibrations performed after the tested dates , those test equipment have been controlled by means of an unbroken chains of calibrations .

All equipment is calibrated with valid calibrations . Each measurement data is traceable to the national or international standards .

Test Item :

RE: Radiated emission ,

AT: Antenna terminal conducted test