



Test report No. : 10329797S-A
Page : 1 of 46
Issued date : May 30, 2014
Revised date : June 17, 2014
FCC ID : AK8NWZWS610

RADIO TEST REPORT

Test Report No.: 10329797S-A

Applicant : Sony Corporation
Type of Equipment : Digital Music Player
Model No. : NWZ-WS613
FCC ID : AK8NWZWS610
Test regulation : FCC Part15 Subpart C: 2014
Test result : Complied

1. This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
2. The results in this report apply only to the sample tested.
3. This sample tested is in compliance with the limits of the above regulation.
4. The test results in this test report are traceable to the national or international standards.
5. This test report must not be used by the customer to claim product certification, approval, or endorsement by any agency of the Federal Government.
6. The opinions and the interpretations to the result of the description in this report are outside scopes where UL Japan has been accredited.

Date of test: May 12 to 18, 2014

Tested by: *H. Shirasawa*
Hikaru Shirasawa
Engineer
Consumer Technology Division

Approved by : *T. Imamura*
Toyokazu Imamura
Leader
Consumer Technology Division



- The testing in which "Non-accreditation" is displayed is outside the accreditation scopes in UL Japan.
 There is no testing item of "Non-accreditation".

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone: +81 463 50 6400

Facsimile: +81 463 50 6401

13-EM-F0429

Contents

| | Page |
|---|-------------|
| SECTION 1: Customer information | 4 |
| SECTION 2: Equipment under test (E.U.T.) | 4 |
| SECTION 3: Test specification, procedures & results | 5 |
| SECTION 4: Operation of E.U.T. during testing..... | 8 |
| SECTION 5: Carrier frequency separation..... | 10 |
| SECTION 6: 20dB bandwidth & Occupied bandwidth (99%) | 10 |
| SECTION 7: Number of hopping frequency | 10 |
| SECTION 8: Dwell time | 10 |
| SECTION 9: Maximum peak output power..... | 10 |
| SECTION 10: Spurious emissions (Antenna port conducted)..... | 10 |
| SECTION 11: Radiated emission..... | 11 |
| Contents of APPENDIXES | 13 |
| APPENDIX 1: Data of radio tests | 14 |
| APPENDIX 2: Test instruments..... | 44 |
| APPENDIX 3: Photographs of test setup..... | 45 |

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone: +81 463 50 6400

Facsimile: +81 463 50 6401

SECTION 1: Customer information

Company Name : Sony Corporation
Brand Name : SONY
Address : 2-10-1 Osaki, Shinagawa-ku, Tokyo, 141-8610, Japan
Telephone Number : +81 50 3750 7634
Contact Person : Shinichi Maru

SECTION 2: Equipment under test (E.U.T.)

2.1 Identification of E.U.T.

Type of Equipment : Digital Music Player
Model Number : NWZ-WS613
Serial Number : Refer to Clause 4.2
Rating : DC3.7V
Country of Mass-production : Malaysia
Condition of EUT : Engineering prototype
(Not for Sale: This sample is equivalent to mass-produced items.)
Receipt Date of Sample : May 9, 2014
Modification of EUT : No modification by the test lab.

2.2 Product description

Model: NWZ-WS613 (referred to as the EUT in this report) is a Digital Music Player.

Variant model: NWZ-WS615

Difference is the memory capacity: NWZ-WS613 (4GB), NWZ-WS615 (16GB)

Clock frequency(ies) in the system : 24MHz (CPU), 26MHz (BT), 240MHz (USB),
~151.58MHz (mSDRAM), 16MHz (eMMC_Data),
~454MHz (CPU core)

Bluetooth specification:

Equipment type : Transceiver
Frequency of operation : 2402-2480MHz
Bandwidth / Channel spacing : 1MHz / 2MHz & 1MHz
Type of modulation : FHSS (GFSK, $\pi/4$ -DQPSK, 8DPSK), DSSS (GFSK)
Antenna type : Pattern
Antenna connector type : None
Antenna gain : -1dBi
ITU code : F1D, G1D
Operation temperature range : +5 to +35 deg.C

* For Bluetooth Low Energy part, refer to the test report: 10329797S-B.

FCC 15.31 (e)

The EUT is a battery-operated device and test was performed with the full-charged battery. Therefore, the EUT complies with the requirement.

FCC 15.203

It is impossible for end users to replace the antenna, because the antenna is mounted inside of the EUT. Therefore the EUT complies with the requirement.

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone: +81 463 50 6400

Facsimile: +81 463 50 6401

SECTION 3: Test specification, procedures & results

3.1 Test specification

Test specification : FCC Part 15 Subpart C: 2014, final revised on March 6, 2014 and effective April 7, 2014
Title : FCC 47CFR Part15 Radio Frequency Device Subpart C Intentional Radiators
Section 15.207 Conducted limits
Section 15.209 Radiated emission limits, general requirements
Section 15.247 Operation within the bands 902-928MHz, 2400-2483.5MHz,
and 5725-5850MHz

* The EUT has been tested for compliance with FCC Part 15 Subpart B by the customer.

3.2 Procedures & Results

| Item | Test Procedure | Specification | Remarks | Deviation | Worst Margin | Results | |
|---|--|-----------------------------|------------------------|------------|--------------|--|----------|
| Conducted emission | ANSI C63.4:2009 7. AC powerline conducted emission measurements | FCC 15.207 | - | N/A *1) | N/A | N/A | |
| Carrier frequency separation | FCC Public Notice DA 00-705 & ANSI C63.4:2009 13. Measurement of intentional radiators | FCC 15.247 (a)(1) | Conducted | N/A | *See data. | Complied | |
| 20dB bandwidth | FCC Public Notice DA 00-705 & ANSI C63.4:2009 13. Measurement of intentional radiators | FCC 15.247 (a)(1) | Conducted | N/A | | - | |
| Number of hopping frequency | FCC Public Notice DA 00-705 & ANSI C63.4:2009 13. Measurement of intentional radiators | FCC 15.247 (a)(1)(iii) | Conducted | N/A | | Complied | |
| Dwell time | FCC Public Notice DA 00-705 & ANSI C63.4:2009 13. Measurement of intentional radiators | FCC 15.247 (a)(1)(iii) | Conducted | N/A | | Complied | |
| Maximum peak output power | FCC Public Notice DA 00-705 & ANSI C63.4:2009 13. Measurement of intentional radiators | FCC 15.247 (b)(1) | Conducted | N/A | | Complied | |
| Band edge compliance & Spurious emission | FCC Public Notice DA 00-705 & ANSI C63.4:2009 13. Measurement of intentional radiators | FCC 15.247 (d) 15.209 | Conducted/ Radiated | N/A | | 16.2dB Freq.: 225.026MHz Polarization: Horizontal Detection: Quasi-Peak Mode: Tx 2402MHz, 3DH5 | Complied |
| Note: UL Japan's Work Procedures No. 13-EM-W0420 and 13-EM-W0422 *1) The EUT operates with a battery. AC Line can be connected to the EUT via PC; however, the EUT stops transmission during recharging. Therefore, the test is not applicable to the EUT. | | | | | | | |

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone: +81 463 50 6400

Facsimile: +81 463 50 6401

3.3 Addition to standard

| Item | Test Procedure | Specification | Remarks | Worst Margin | Results |
|--------------------------|--|---------------|-----------|--------------|---------|
| Occupied Bandwidth (99%) | ANSI C63.4:2009 13. Measurement of intentional radiators, RSS-Gen 4.6.1 | - | Conducted | - | - |

Note: UL Japan's Work Procedures No. 13-EM-W0420 and 13-EM-W0422

* Other than above, no addition, exclusion nor deviation has been made from the standard.

3.4 Uncertainty

The following uncertainties have been calculated to provide a confidence level of 95% using a coverage factor k=2.

| Item | Frequency range | No.1 SAC ^{*1} /SR ^{*2} (±) | No.2 SAC/SR (±) | No.3 SAC/SR (±) |
|---|-----------------|---|--------------------|--------------------|
| Radiated emission (Measurement distance: 3m) | 9kHz-30MHz | 3.7 dB | 3.7 dB | 3.6 dB |
| | 30MHz-300MHz | 4.8 dB | 5.0 dB | 4.8 dB |
| | 300MHz-1GHz | 5.0 dB | 5.0 dB | 4.8 dB |
| | 1GHz-15GHz | 4.9 dB | 4.9 dB | 4.9 dB |
| Radiated emission (Measurement distance: 1m) | 15GHz-18GHz | 5.7 dB | 5.6 dB | 5.6 dB |
| | 18GHz-40GHz | 5.2 dB | 4.3 dB | 4.3 dB |

*1: SAC=Semi-Anechoic Chamber

*2: SR= Shielded Room is applied besides radiated emission

The data listed in this test report has enough margin, more than the site margin.

Antenna port conducted test

Power measurement uncertainty above 1GHz for this test was: (±) 1.5dB

Spurious emission (Conducted) measurement (below 1GHz) uncertainty for this test was: (±) 1.6dB

Spurious emission (Conducted) measurement (1G-3GHz) uncertainty for this test was: (±) 1.4dB

Spurious emission (Conducted) measurement (3G-18GHz) uncertainty for this test was: (±) 2.8dB

Spurious emission (Conducted) measurement (18G-26.5GHz) uncertainty for this test was: (±) 2.5dB

Bandwidth measurement uncertainty for this test was: (±) 5.4%

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone: +81 463 50 6400

Facsimile: +81 463 50 6401

3.5 Test location

UL Japan, Inc. Shonan EMC Lab.

1-22-3, Megumigaoka, Hiratsuka-shi, Kanagawa-ken 259-1220 JAPAN

Telephone number : +81 463 50 6400

Facsimile number : +81 463 50 6401

JAB Accreditation No. : RTL02610

| | IC Registration No. | Width x Depth x Height (m) | Size of reference ground plane (m) / horizontal conducting plane | Maximum measurement distance |
|--|---------------------|----------------------------|--|------------------------------|
| <input type="checkbox"/> No.1 semi-anechoic chamber | 2973D-1 | 20.6 x 11.3 x 7.65 | 20.6 x 11.3 | 10m |
| <input type="checkbox"/> No.2 semi-anechoic chamber | 2973D-2 | 20.6 x 11.3 x 7.65 | 20.6 x 11.3 | 10m |
| <input checked="" type="checkbox"/> No.3 semi-anechoic chamber | 2973D-3 | 12.7 x 7.7 x 5.35 | 12.7 x 7.7 | 5m |
| <input type="checkbox"/> No.4 semi-anechoic chamber | - | 8.1 x 5.1 x 3.55 | 8.1 x 5.1 | - |
| <input type="checkbox"/> No.1 shielded room | - | 6.8 x 4.1 x 2.7 | 6.8 x 4.1 | - |
| <input type="checkbox"/> No.2 shielded room | - | 6.8 x 4.1 x 2.7 | 6.8 x 4.1 | - |
| <input type="checkbox"/> No.3 shielded room | - | 6.3 x 4.7 x 2.7 | 6.3 x 4.7 | - |
| <input type="checkbox"/> No.4 shielded room | - | 4.4 x 4.7 x 2.7 | 4.4 x 4.7 | - |
| <input type="checkbox"/> No.5 shielded room | - | 7.8 x 6.4 x 2.7 | 7.8 x 6.4 | - |
| <input type="checkbox"/> No.6 shielded room | - | 7.8 x 6.4 x 2.7 | 7.8 x 6.4 | - |
| <input checked="" type="checkbox"/> No.1 measurement room | - | 2.55 x 4.1 x 2.5 | - | - |

3.6 Test setup, Data of test & Test instruments

Refer to APPENDIX 1 to 3.

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone: +81 463 50 6400

Facsimile: +81 463 50 6401

SECTION 4: Operation of E.U.T. during testing

4.1 Operating mode

| Test item | Operating mode | Tested frequency |
|--|---|--|
| Carrier frequency separation | Transmitting Hopping ON (DH5 / 3-DH5) / Inquiry, Payload: PRBS9 | - |
| 20dB bandwidth | Transmitting Hopping OFF (DH5 / 3-DH5) / Inquiry, Payload: PRBS9 | 2402MHz, 2441MHz, 2480MHz |
| Number of hopping frequency | Transmitting Hopping ON (DH5 / 3-DH5) / Inquiry, Payload: PRBS9 | - |
| Dwell time | Transmitting (Hopping ON), Payload: PRBS9 - DH1, - DH3, - DH5 - 3-DH1, - 3-DH3, - 3-DH5 -Inquiry | - |
| Maximum peak output power | Transmitting Hopping OFF, Payload: PRBS9 - DH5, - 2-DH5, - 3-DH5 | 2402MHz, 2441MHz, 2480MHz |
| Band edge compliance & Spurious emission (Conducted) | Transmitting (DH5 / 3-DH5), Payload: PRBS9 -Hopping ON -Hopping OFF | Band edge compliance: 2402MHz, 2480MHz |
| (Radiated) | Transmitting (DH5 / 3-DH5), Payload: PRBS9 -Hopping OFF | Spurious emission: 2402MHz, 2441MHz, 2480MHz |
| 99% occupied bandwidth | Transmitting (DH5 / 3-DH5), Payload: PRBS9 / Inquiry -Hopping ON -Hopping OFF | 2402MHz, 2441MHz, 2480MHz |

*As a result of preliminary test, the formal test was performed with the above modes, which had the maximum payload (except Dwell time test).

*Remarks: Test was not performed at AFH mode, because the decrease of number of channel (min: 20ch) at AFH mode does not affect the output power and bandwidth of the EUT.

The carrier separation may be less than 20 dB bandwidth, therefore 125mW power limit was applied to it.

Software : BtCli.exe ver.2.5.0.93 for Inquiry mode
BlueTest3.exe ver.2.5.0.93 for other mode
Power Settings : Fixed BDR= Ext PA:23, Int PA:38
EDR= Ext PA:72, Int PA:46

We removed 2-DH mode (2 Mb/s EDR: pi/4DQPSK) except power measurement by using 3-DH mode (3 Mb/s EDR: 8DPSK) as a representative.

Justification: The system was configured in typical fashion (as customer would normally use it) for testing.

UL Japan, Inc.


Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone: +81 463 50 6400

Facsimile: +81 463 50 6401

4.2 Configuration and peripherals



* Test data was taken under worse case conditions.

Description of EUT and support equipment

| No. | Item | Model number | Serial number | Manufacturer | Remarks |
|-----|----------------------|--------------|---------------|--------------|---------|
| A | Digital Music Player | NWZ-WS613 | *1) | SONY | EUT |

*1) Antenna port conducted tests: 3000060, Radiated emission tests: 3000043

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone: +81 463 50 6400

Facsimile: +81 463 50 6401

SECTION 5: Carrier frequency separation

Test procedure

The carrier frequency separation was measured with a spectrum analyzer connected to the antenna port.

Summary of the test results: Pass
Refer to APPENDIX 1.

SECTION 6: 20dB bandwidth & Occupied bandwidth (99%)

Test procedure

The bandwidth was measured with a spectrum analyzer connected to the antenna port.

Summary of the test results: Pass
Refer to APPENDIX 1.

SECTION 7: Number of hopping frequency

Test procedure

The Number of Hopping Frequency was measured with a spectrum analyzer connected to the antenna port.

Summary of the test results: Pass
Refer to APPENDIX 1.

SECTION 8: Dwell time

Test procedure

The Dwell time was measured with a spectrum analyzer connected to the antenna port.

Summary of the test results: Pass
Refer to APPENDIX 1.

SECTION 9: Maximum peak output power

Test procedure

The Maximum Peak Output Power was measured with a power meter connected to the antenna port.

Summary of the test results: Pass
Refer to APPENDIX 1.

SECTION 10: Spurious emissions (Antenna port conducted)

Test procedure

The Out of Band Emissions was measured with a spectrum analyzer connected to the antenna port.
The radio frequency power that is produced by the intentional radiator confirmed 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on a radiated measurement. In the frequency range below 30MHz, RBW was narrowed to separate the noise contents. Then, wide-band noise near the limit was checked separately, however the noise was not detected as shown in the chart. (9kHz-150kHz:RBW=200Hz, 150kHz-30MHz:RBW=10kHz)

Summary of the test results: Pass
Refer to APPENDIX 1.

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone: +81 463 50 6400

Facsimile: +81 463 50 6401

SECTION 11: Radiated emission

11.1 Operating environment

Test room : See test data (APPENDIX 1)
Temperature : See test data (APPENDIX 1)
Humidity : See test data (APPENDIX 1)

11.2 Test configuration

EUT was placed on a polystyrene platform of nominal size, 0.5m by 0.5m, raised 0.8m above the conducting ground plane. Photographs of the set up are shown in APPENDIX 3.

11.3 Test conditions

Frequency range : 30MHz - 25GHz
EUT position : Table top

11.4 Test procedure

The Radiated Electric Field Strength intensity has been measured on a semi-anechoic chamber with a ground plane and at a distance of 3m (below 15GHz) / 1m (above 15GHz) (Refer to Figure 1). Measurements were performed with quasi-peak, peak and average detector. The measuring antenna height was varied between 1 and 4m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity. The measurements were performed for both vertical and horizontal antenna polarization.

The radiated emission measurements were made with the following detection.

| Frequency | 30 - 1000MHz | 1 - 25GHz | | 20dBc |
|----------------|--------------|----------------------|----------------------|-----------------------------|
| Detection Type | : Quasi-Peak | Peak | Average *1) | Peak |
| IF Bandwidth | : 120kHz | RBW:1MHz VBW:3MHz | RBW:1MHz VBW:10Hz | RBW: 100kHz, VBW: 300kHz |

*1) When using Spectrum analyzer, the test was made with adjusting span to zero by using peak hold. Although 00-705 accepts VBW=10Hz for AV measurements, confirmed that superfluous smoothing was not performed.

The carrier levels and noise levels were confirmed at each position of X, Y and Z axes to see the position of maximum noise, and the test was made at the position that has the maximum noise.

| Antenna polarization | Carrier | Spurious (Below 1GHz) | Spurious (1-15GHz) | Spurious (15-18GHz) | Spurious (18-25GHz) |
|----------------------|---------|-----------------------|--------------------|---------------------|---------------------|
| Horizontal | X | X | X | X | Y |
| Vertical | Y | X | Y | Y | Z |

UL Japan, Inc.


Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone: +81 463 50 6400

Facsimile: +81 463 50 6401

Figure 1. Antenna angle



11.5 Band edge

Band edge level is below the limits of FCC 15.209. Refer to the data.

11.6 Results

Summary of the test results: Pass
*No noise was detected above the 9th order harmonics.

Refer to APPENDIX 1.

Contents of APPENDIXES

APPENDIX 1: Data of Radio tests

20dB bandwidth and Carrier frequency separation
Number of hopping frequency
Dwell time
Maximum peak output power
Radiated emission
Spurious emission (Antenna port conducted)
Occupied bandwidth

APPENDIX 2: Test instruments

Test instruments

APPENDIX 3: Photographs of test setup

Radiated emission
Pre-check of the worst position

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone: +81 463 50 6400

Facsimile: +81 463 50 6401

APPENDIX 1: Data of Radio tests


20dB Bandwidth and Carrier Frequency Separation

| | | |
|------------------------|--------------------------------|-----------------------|
| Test place | UL Japan, Inc. Shonan EMC Lab. | No.1 Measurement Room |
| Date | May 12, 2014 | |
| Temperature / Humidity | 24 deg.C , 43 %RH | |
| Engineer | Hikaru Shirasawa | |
| Mode | Tx, Bluetooth, BDR, PRBS9 | |

| Mode | Freq. [MHz] | 20dB Bandwidth [MHz] | Carrier Frequency Separation [MHz] | Limit for Carrier Frequency Separation [MHz] |
|---------|----------------|----------------------------|---|--|
| DH5 | 2402.0 | 0.958 | 1.005 | >= 0.638 |
| DH5 | 2441.0 | 0.934 | 1.005 | >= 0.623 |
| DH5 | 2480.0 | 0.971 | 1.003 | >= 0.647 |
| Inquiry | 2441.0 | 0.828 | 2.004 | >= 0.552 |

Limit: Two-thirds of 20dB Bandwidth or 25kHz (whichever is greater).

No limit applies to 20dB Bandwidth.



UL Japan, Inc.

Shonan EMC Lab.


1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

20dB Bandwidth and Carrier Frequency Separation

Tx, Bluetooth, BDR, PRBS9



UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

20dB Bandwidth and Carrier Frequency Separation

Test place UL Japan, Inc. Shonan EMC Lab. No.1 Measurement Room
 Date May 12, 2014
 Temperature / Humidity 24 deg.C , 43 %RH
 Engineer Hikaru Shirasawa
 Mode Tx, Bluetooth, EDR, PRBS9

| Mode | Freq. [MHz] | 20dB Bandwidth [MHz] | Carrier Frequency Separation [MHz] | Limit for Carrier Frequency Separation [MHz] |
|-------|----------------|----------------------------|---|--|
| 3-DH5 | 2402.0 | 1.274 | 1.005 | >= 0.849 |
| 3-DH5 | 2441.0 | 1.258 | 1.005 | >= 0.839 |
| 3-DH5 | 2480.0 | 1.261 | 1.005 | >= 0.841 |

Limit: Two-thirds of 20dB Bandwidth or 25kHz (whichever is greater).
 No limit applies to 20dB Bandwidth.

Tx2_Inquiry200BW

Tx2_InquirySeparation

UL Japan, Inc.

Shonan EMC Lab.


1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

20dB Bandwidth and Carrier Frequency Separation

Tx, Bluetooth, EDR, PRBS9



UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN

Telephone : +81 463 50 6400


Facsimile : +81 463 50 6401

Number of Hopping Frequency

| | | |
|------------------------|--------------------------------|-----------------------|
| Test place | UL Japan, Inc. Shonan EMC Lab. | No.1 Measurement Room |
| Date | May 12, 2014 | |
| Temperature / Humidity | 24 deg.C , 43 %RH | |
| Engineer | Hikaru Shirasawa | |
| Mode | Tx, Bluetooth, BDR, PRBS9 | |

| Mode | Number of Channel [times] | Limit [times] |
|------|---------------------------|---------------|
| DH5 | 79 | >= 15 |

* Test was not performed at AFH mode whose number of hopping channel is 20 channels because this Bluetooth radio is in compliance of Bluetooth Specification.




Number of Hopping Frequency

| | | |
|------------------------|--------------------------------|-----------------------|
| Test place | UL Japan, Inc. Shonan EMC Lab. | No.1 Measurement Room |
| Date | May 12, 2014 | |
| Temperature / Humidity | 24 deg.C , 43 %RH | |
| Engineer | Hikaru Shirasawa | |
| Mode | Tx, Bluetooth, EDR, PRBS9 | |

| Mode | Number of Channel [times] | Limit [times] |
|-------|---------------------------|---------------|
| 3-DH5 | 79 | >= 15 |


* Test was not performed at AFH mode whose number of hopping channel is 20 channels because this Bluetooth radio is in compliance of Bluetooth Specification.



Number of Hopping Frequency

| | | |
|------------------------|--------------------------------|-----------------------|
| Test place | UL Japan, Inc. Shonan EMC Lab. | No.1 Measurement Room |
| Date | May 12, 2014 | |
| Temperature / Humidity | 24 deg.C , 43 %RH | |
| Engineer | Hikaru Shirasawa | |
| Mode | Tx, Bluetooth, Inquiry | |

| Mode | Number of Channel [times] | Limit [times] |
|---------|---------------------------|---------------|
| Inquiry | 32 | >= 15 |



Dwell Time


| | | |
|------------------------|--------------------------------|-----------------------|
| Test place | UL Japan, Inc. Shonan EMC Lab. | No.1 Measurement Room |
| Date | May 12, 2014 | |
| Temperature / Humidity | 24 deg.C , 43 %RH | |
| Engineer | Hikaru Shirasawa | |
| Mode | Tx, Bluetooth, BDR, PRBS9 | |

| Mode | Number of transmission in a 31.6 (79 Hopping x 0.4) / 12.8 (32 Hopping x 0.4) second period | Length of transmission time [msec] | Result [msec] | Limit [msec] |
|---------|---|--|------------------|-----------------|
| DH1 | 50.0 / 5.0 sec. x 31.6 sec. = 316 times | 0.419 | 132 | 400 |
| DH3 | 26.0 / 5.0 sec. x 31.6 sec. = 165 times | 1.676 | 277 | 400 |
| DH5 | 17.0 / 5.0 sec. x 31.6 sec. = 108 times | 2.922 | 316 | 400 |
| Inquiry | 100.0 / 1.0 sec. x 12.8 sec. = 1280 times | 0.119 | 152 | 400 |

Sample Calculation

Result = Number of transmission x Length of transmission time

* This device complies with the Bluetooth protocol for FHSS operation, employing a pseudo random channel selection and hopping rate to ensure that the occupancy time in $N \times 0.4s$, where N is the number of channels being used in the hopping sequence ($20 \leq N \leq 79$), is always less than 0.4s regardless of packet size (DH1, DH3 or DH5). This is confirmed in the test report for $N=79$.



UL Japan, Inc.

Shonan EMC Lab.


1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

Dwell time

Tx, Bluetooth, BDR, PRBS9



UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

Dwell Time

Test place UL Japan, Inc. Shonan EMC Lab. No.1 Measurement Room
 Date May 12, 2014
 Temperature / Humidity 24 deg.C , 43 %RH
 Engineer Hikaru Shirasawa
 Mode Tx, Bluetooth, EDR, PRBS9

| Mode | Number of transmission in a 31.6 (79 Hopping x 0.4) second | Length of transmission time [msec] | Result [msec] | Limit [msec] |
|-------|---|--|------------------|-----------------|
| 3-DH1 | 50.0 / 5.0 sec. x 31.6 sec. = 316 times | 0.438 | 138 | 400 |
| 3-DH3 | 26.0 / 5.0 sec. x 31.6 sec. = 165 times | 1.693 | 279 | 400 |
| 3-DH5 | 17.0 / 5.0 sec. x 31.6 sec. = 108 times | 2.940 | 318 | 400 |

Sample Calculation

Result = Number of transmission x Length of transmission time

* This device complies with the Bluetooth protocol for FHSS operation, employing a pseudo random channel selection and hopping rate to ensure that the occupancy time in $N \times 0.4s$, where N is the number of channels being used in the hopping sequence ($20 \leq N \leq 79$), is always less than 0.4s regardless of packet size (3-DH1, 3-DH3 or 3-DH5). This is confirmed in the test report for $N=79$.

Tx2_DwellInquiry1

Tx2_DwellInquiry2

UL Japan, Inc.

Shonan EMC Lab.


1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

Dwell time

Tx, Bluetooth, EDR, PRBS9



UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

Maximum Peak Conducted Output Power (Conducted)

Test place UL Japan, Inc. Shonan EMC Lab. No.1 Measurement Room
 Date May 12, 2014
 Temperature / Humidity 24 deg.C , 43 %RH
 Engineer Hikaru Shirasawa
 Mode Tx, Bluetooth

(* P/M: Power Meter with power sensor)

| | Freq. [MHz] | P/M (Peak) Reading [dBm] | Cable Loss [dB] | Atten. Loss [dB] | Result | | Limit | | Margin [dB] |
|-------|----------------|--------------------------------|-----------------------|------------------------|--------|------|-------|------|----------------|
| | | | | | [dBm] | [mW] | [dBm] | [mW] | |
| DH5 | 2402.0 | -9.79 | 1.05 | 9.90 | 1.16 | 1.31 | 20.97 | 125 | 19.81 |
| DH5 | 2441.0 | -8.30 | 1.06 | 9.89 | 2.65 | 1.84 | 20.97 | 125 | 18.32 |
| DH5 | 2480.0 | -8.66 | 1.07 | 9.89 | 2.30 | 1.70 | 20.97 | 125 | 18.67 |
| 2-DH5 | 2402.0 | -7.44 | 1.05 | 9.90 | 3.51 | 2.24 | 20.97 | 125 | 17.46 |
| 2-DH5 | 2441.0 | -6.08 | 1.06 | 9.89 | 4.87 | 3.07 | 20.97 | 125 | 16.10 |
| 2-DH5 | 2480.0 | -6.38 | 1.07 | 9.89 | 4.58 | 2.87 | 20.97 | 125 | 16.39 |
| 3-DH5 | 2402.0 | -7.12 | 1.05 | 9.90 | 3.83 | 2.42 | 20.97 | 125 | 17.14 |
| 3-DH5 | 2441.0 | -5.85 | 1.06 | 9.89 | 5.10 | 3.24 | 20.97 | 125 | 15.87 |
| 3-DH5 | 2480.0 | -5.91 | 1.07 | 9.89 | 5.05 | 3.20 | 20.97 | 125 | 15.92 |

Sample Calculation:

Result = Reading + Cable Loss (including the cable(s) customer supplied) + Atten. Loss

UL Japan, Inc.
Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN


Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

Dwell time factor Calculation chart

Dwell time factor Calculation

Tx, Bluetooth, BDR, PRBS9

| Worst 100ms Dwell time factor = $20\log((2.922 \times 2)/100) = -24.67\text{dB}$ | 1cycle On time : 2.922ms | | | | | | | | | | | | | | | |
|--|--|--------|----------|------------|--------|-----------|----|-----|------|----------|------------|----|-----|------|----------|---------|
| <p>ON time of some channel during 100ms: Twice This is the worst case in hopping sequence of Bluetooth.</p> |  <table border="1" style="width: 100%; border-collapse: collapse; margin-top: 10px;"> <thead> <tr> <th>Marker</th> <th>Trace</th> <th>Type</th> <th>X Axis</th> <th>Amplitude</th> </tr> </thead> <tbody> <tr> <td>1R</td> <td>(3)</td> <td>Time</td> <td>1.089 ms</td> <td>-79.11 dBm</td> </tr> <tr> <td>1a</td> <td>(3)</td> <td>Time</td> <td>2.922 ms</td> <td>1.57 dB</td> </tr> </tbody> </table> | Marker | Trace | Type | X Axis | Amplitude | 1R | (3) | Time | 1.089 ms | -79.11 dBm | 1a | (3) | Time | 2.922 ms | 1.57 dB |
| Marker | Trace | Type | X Axis | Amplitude | | | | | | | | | | | | |
| 1R | (3) | Time | 1.089 ms | -79.11 dBm | | | | | | | | | | | | |
| 1a | (3) | Time | 2.922 ms | 1.57 dB | | | | | | | | | | | | |

VBW (Average) setting

*Although 00-705 accepts VBW=10Hz for AV measurements, confirmed that superfluous smoothing was not performed.

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN


Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

Dwell time factor Calculation chart

Dwell time factor Calculation

Tx, Bluetooth, EDR, PRBS9

| Worst 100ms Dwell time factor = $20\log((2.94 \times 2)/100) = -24.61\text{dB}$ | 1cycle On time : 2.94ms | | | | | | | | | | | | | | | |
|--|--|--------|----------|------------|--------|-----------|----|-----|------|----------|------------|----|-----|------|---------|----------|
| <p>ON time of some channel during 100ms: Twice This is the worst case in hopping sequence of Bluetooth.</p> |  <table border="1" style="width: 100%; border-collapse: collapse; margin-top: 10px;"> <thead> <tr> <th>Marker</th> <th>Trace</th> <th>Type</th> <th>X Axis</th> <th>Amplitude</th> </tr> </thead> <tbody> <tr> <td>1R</td> <td>(3)</td> <td>Time</td> <td>1.024 ms</td> <td>-81.48 dBm</td> </tr> <tr> <td>1a</td> <td>(3)</td> <td>Time</td> <td>2.94 ms</td> <td>-1.28 dB</td> </tr> </tbody> </table> | Marker | Trace | Type | X Axis | Amplitude | 1R | (3) | Time | 1.024 ms | -81.48 dBm | 1a | (3) | Time | 2.94 ms | -1.28 dB |
| Marker | Trace | Type | X Axis | Amplitude | | | | | | | | | | | | |
| 1R | (3) | Time | 1.024 ms | -81.48 dBm | | | | | | | | | | | | |
| 1a | (3) | Time | 2.94 ms | -1.28 dB | | | | | | | | | | | | |

VBW (Average) setting

*Although 00-705 accepts VBW=10Hz for AV measurements, confirmed that superfluous smoothing was not performed.

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

Radiated Emission

Test place No.3 Semi Anechoic Chamber
 Date May 16, 2014 May 17, 2014 May 18, 2014
 Temperature / Humidity 26 deg.C, 36 %RH 21 deg.C, 41 %RH 22 deg.C, 34 %RH
 Engineer Kenichi Adachi Wataru Kojima Wataru Kojima
 Mode Tx, 2402 MHz
 Tx, Bluetooth, BDR, PRBS9

(* PK: Peak, AV: Average, QP: Quasi-Peak)

| Polarity | Frequency [MHz] | Detector | Reading [dBuV] | Ant.Fac. [dB/m] | Loss [dB] | Gain [dB] | Result [dBuV/m] | Limit [dBuV/m] | Margin [dB] | Height [cm] | Angle [deg] | Remark |
|----------|-----------------|----------|----------------|-----------------|-----------|-----------|-----------------|----------------|-------------|-------------|-------------|--------|
| Hori. | 224.310 | QP | 36.5 | 16.7 | 8.0 | 32.0 | 29.2 | 46.0 | 16.8 | 148 | 209 | |
| Hori. | 240.060 | QP | 32.1 | 16.9 | 8.1 | 32.0 | 25.1 | 46.0 | 20.9 | 109 | 40 | |
| Hori. | 706.767 | QP | 22.1 | 19.7 | 10.0 | 31.9 | 19.9 | 46.0 | 26.1 | 134 | 2 | |
| Hori. | 2390.000 | PK | 43.1 | 26.8 | 14.6 | 38.2 | 46.3 | 73.9 | 27.6 | 100 | 41 | |
| Hori. | 2400.000 | PK | 44.3 | 26.8 | 14.6 | 38.2 | 47.5 | 73.9 | 26.4 | 100 | 41 | |
| Hori. | 4804.000 | PK | 55.1 | 30.9 | 7.5 | 37.1 | 56.4 | 73.9 | 17.5 | 100 | 43 | |
| Hori. | 7206.000 | PK | 45.1 | 37.1 | 8.6 | 39.4 | 51.4 | 73.9 | 22.5 | 100 | 0 | |
| Hori. | 9608.000 | PK | 43.1 | 38.6 | 9.6 | 37.6 | 53.7 | 73.9 | 20.2 | 100 | 0 | |
| Hori. | 19216.000 | PK | 51.2 | 40.8 | 1.9 | 48.4 | 45.5 | 73.9 | 28.4 | 131 | 172 | |
| Hori. | 2390.000 | AV | 31.2 | 26.8 | 14.6 | 38.2 | 34.4 | 53.9 | 19.5 | 100 | 41 | |
| Hori. | 2400.000 | AV | 32.7 | 26.8 | 14.6 | 38.2 | 35.9 | 53.9 | 18.0 | 100 | 41 | |
| Vert. | 91.813 | QP | 25.2 | 8.5 | 7.4 | 32.1 | 9.0 | 43.5 | 34.5 | 100 | 282 | |
| Vert. | 133.684 | QP | 25.9 | 13.9 | 7.3 | 32.1 | 15.0 | 43.5 | 28.5 | 100 | 164 | |
| Vert. | 294.342 | QP | 22.3 | 18.7 | 8.4 | 32.0 | 17.4 | 46.0 | 28.6 | 100 | 210 | |
| Vert. | 2390.000 | PK | 43.2 | 26.8 | 14.6 | 38.2 | 46.4 | 73.9 | 27.5 | 100 | 71 | |
| Vert. | 2400.000 | PK | 44.4 | 26.8 | 14.6 | 38.2 | 47.6 | 73.9 | 26.3 | 100 | 71 | |
| Vert. | 4804.000 | PK | 54.3 | 30.9 | 7.5 | 37.1 | 55.6 | 73.9 | 18.3 | 100 | 267 | |
| Vert. | 7206.000 | PK | 45.2 | 37.1 | 8.6 | 39.4 | 51.5 | 73.9 | 22.4 | 100 | 0 | |
| Vert. | 9608.000 | PK | 43.0 | 38.6 | 9.6 | 37.6 | 53.6 | 73.9 | 20.3 | 100 | 0 | |
| Vert. | 19216.000 | PK | 54.0 | 40.8 | 1.9 | 48.4 | 48.3 | 73.9 | 25.6 | 119 | 74 | |
| Vert. | 2390.000 | AV | 31.3 | 26.8 | 14.6 | 38.2 | 34.5 | 53.9 | 19.4 | 100 | 71 | |
| Vert. | 2400.000 | AV | 32.9 | 26.8 | 14.6 | 38.2 | 36.1 | 53.9 | 17.8 | 100 | 71 | |

Result = Reading + Ant.Fac. + Loss (Cable+(Attenuator or Filter)(below 18GHz)-Distance factor(above 15GHz)) - Gain(Amplifier)

Distance factor : 15GHz -40GHz : 20log(3.0m/1.0m)= 9.5dB

Dwell time factor relaxation

| Polarity | Frequency [MHz] | Detector | Reading [dBuV] | Ant.Fac. [dB/m] | Loss [dB] | Gain [dB] | Dwell Factor [dB] | Result [dBuV/m] | Limit [dBuV/m] | Margin [dB] | Remark |
|----------|-----------------|----------|----------------|-----------------|-----------|-----------|-------------------|-----------------|----------------|-------------|--------|
| Hori. | 4804.000 | AV | 49.7 | 30.9 | 7.5 | 37.1 | -24.6 | 26.4 | 53.9 | 27.5 | |
| Hori. | 7206.000 | AV | 33.2 | 37.1 | 8.6 | 39.4 | -24.6 | 14.9 | 53.9 | 39.0 | |
| Hori. | 9608.000 | AV | 31.3 | 38.6 | 9.6 | 37.6 | -24.6 | 17.3 | 53.9 | 36.6 | |
| Hori. | 19216.000 | AV | 45.9 | 40.8 | 1.9 | 48.4 | -24.6 | 15.6 | 53.9 | 38.3 | |
| Vert. | 4804.000 | AV | 48.1 | 30.9 | 7.5 | 37.1 | -24.6 | 24.8 | 53.9 | 29.1 | |
| Vert. | 7206.000 | AV | 33.3 | 37.1 | 8.6 | 39.4 | -24.6 | 15.0 | 53.9 | 38.9 | |
| Vert. | 9608.000 | AV | 31.2 | 38.6 | 9.6 | 37.6 | -24.6 | 17.2 | 53.9 | 36.7 | |
| Vert. | 19216.000 | AV | 49.0 | 40.8 | 1.9 | 48.4 | -24.6 | 18.7 | 53.9 | 35.2 | |

Result = Reading + Ant.Fac. + Loss (Cable+(Attenuator or Filter)(below 18GHz)-Distance factor(above 15GHz)) - Gain(Amplifier) + Dwell(time)factor

Distance factor : 15GHz -40GHz : 20log(3.0m/1.0m)= 9.5dB

UL Japan, Inc.**Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

Radiated Emission

Test place No.3 Semi Anechoic Chamber
 Date May 16, 2014 May 17, 2014 May 18, 2014
 Temperature / Humidity 26 deg.C, 36 %RH 21 deg.C, 41 %RH 22 deg.C, 34 %RH
 Engineer Kenichi Adachi Wataru Kojima Wataru Kojima
 Mode Tx, 2441 MHz
 Tx, Bluetooth, BDR, PRBS9

(* PK: Peak, AV: Average, QP: Quasi-Peak)

| Polarity | Frequency [MHz] | Detector | Reading [dBuV] | Ant.Fac. [dB/m] | Loss [dB] | Gain [dB] | Result [dBuV/m] | Limit [dBuV/m] | Margin [dB] | Height [cm] | Angle [deg] | Remark |
|----------|-----------------|----------|----------------|-----------------|-----------|-----------|-----------------|----------------|-------------|-------------|-------------|--------|
| Hori. | 225.069 | QP | 36.3 | 16.7 | 8.0 | 32.0 | 29.0 | 46.0 | 17.0 | 161 | 358 | |
| Hori. | 240.009 | QP | 33.0 | 16.9 | 8.1 | 32.0 | 26.0 | 46.0 | 20.0 | 150 | 114 | |
| Hori. | 808.602 | QP | 27.0 | 20.7 | 10.4 | 31.6 | 26.5 | 46.0 | 19.5 | 148 | 245 | |
| Hori. | 4882.000 | PK | 54.5 | 31.4 | 7.5 | 37.0 | 56.4 | 73.9 | 17.5 | 100 | 45 | |
| Hori. | 7323.000 | PK | 45.3 | 37.2 | 8.6 | 39.4 | 51.7 | 73.9 | 22.2 | 100 | 0 | |
| Hori. | 9764.000 | PK | 43.3 | 38.8 | 9.6 | 37.5 | 54.2 | 73.9 | 19.7 | 100 | 0 | |
| Hori. | 19528.000 | PK | 51.7 | 40.8 | 2.0 | 48.1 | 46.4 | 73.9 | 27.5 | 114 | 29 | |
| Vert. | 91.757 | QP | 24.8 | 8.4 | 7.4 | 32.1 | 8.5 | 43.5 | 35.0 | 100 | 39 | |
| Vert. | 146.383 | QP | 26.1 | 14.5 | 7.6 | 32.1 | 16.1 | 43.5 | 27.4 | 100 | 3 | |
| Vert. | 265.506 | QP | 26.4 | 17.6 | 8.2 | 32.0 | 20.2 | 46.0 | 25.8 | 100 | 109 | |
| Vert. | 4882.000 | PK | 53.6 | 31.4 | 7.5 | 37.0 | 55.5 | 73.9 | 18.4 | 100 | 263 | |
| Vert. | 7323.000 | PK | 45.4 | 37.2 | 8.6 | 39.4 | 51.8 | 73.9 | 22.1 | 100 | 0 | |
| Vert. | 9764.000 | PK | 43.2 | 38.8 | 9.6 | 37.5 | 54.1 | 73.9 | 19.8 | 100 | 0 | |
| Vert. | 19528.000 | PK | 50.8 | 40.8 | 2.0 | 48.1 | 45.5 | 73.9 | 28.4 | 118 | 78 | |

Result = Reading + Ant.Fac. + Loss (Cable+(Attenuator or Filter)(below 18GHz)-Distance factor(above 15GHz)) - Gain(Amplifier)

Distance factor : 15GHz -40GHz : 20log(3.0m/1.0m)= 9.5dB

Dwell time factor relaxation

| Polarity | Frequency [MHz] | Detector | Reading [dBuV] | Ant.Fac. [dB/m] | Loss [dB] | Gain [dB] | Dwell Factor [dB] | Result [dBuV/m] | Limit [dBuV/m] | Margin [dB] | Remark |
|----------|-----------------|----------|----------------|-----------------|-----------|-----------|-------------------|-----------------|----------------|-------------|--------|
| Hori. | 4882.000 | AV | 49.5 | 31.4 | 7.5 | 37.0 | -24.6 | 26.8 | 53.9 | 27.1 | |
| Hori. | 7323.000 | AV | 33.3 | 37.2 | 8.6 | 39.4 | -24.6 | 15.1 | 53.9 | 38.8 | |
| Hori. | 9764.000 | AV | 31.4 | 38.8 | 9.6 | 37.5 | -24.6 | 17.7 | 53.9 | 36.2 | |
| Hori. | 19528.000 | AV | 47.0 | 40.8 | 2.0 | 48.1 | -24.6 | 17.1 | 53.9 | 36.8 | |
| Vert. | 4882.000 | AV | 47.9 | 31.4 | 7.5 | 37.0 | -24.6 | 25.2 | 53.9 | 28.7 | |
| Vert. | 7323.000 | AV | 33.4 | 37.2 | 8.6 | 39.4 | -24.6 | 15.2 | 53.9 | 38.7 | |
| Vert. | 9764.000 | AV | 31.3 | 38.8 | 9.6 | 37.5 | -24.6 | 17.6 | 53.9 | 36.3 | |
| Vert. | 19528.000 | AV | 45.6 | 40.8 | 2.0 | 48.1 | -24.6 | 15.7 | 53.9 | 38.2 | |

Result = Reading + Ant.Fac. + Loss (Cable+(Attenuator or Filter)(below 18GHz)-Distance factor(above 15GHz)) - Gain(Amplifier) + Dwell(time)factor

Distance factor : 15GHz -40GHz : 20log(3.0m/1.0m)= 9.5dB

UL Japan, Inc.**Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

Radiated Emission

Test place No.3 Semi Anechoic Chamber
 Date May 16, 2014 May 17, 2014 May 18, 2014
 Temperature / Humidity 26 deg.C, 36 %RH 21 deg.C, 41 %RH 22 deg.C, 34 %RH
 Engineer Kenichi Adachi Wataru Kojima Wataru Kojima
 Mode Tx, 2480 MHz
 Tx, Bluetooth, BDR, PRBS9

(* PK: Peak, AV: Average, QP: Quasi-Peak)

| Polarity | Frequency [MHz] | Detector | Reading [dBuV] | Ant.Fac. [dB/m] | Loss [dB] | Gain [dB] | Result [dBuV/m] | Limit [dBuV/m] | Margin [dB] | Height [cm] | Angle [deg] | Remark |
|----------|-----------------|----------|----------------|-----------------|-----------|-----------|-----------------|----------------|-------------|-------------|-------------|--------|
| Hori. | 225.022 | QP | 36.5 | 16.7 | 8.0 | 32.0 | 29.2 | 46.0 | 16.8 | 150 | 347 | |
| Hori. | 240.052 | QP | 31.8 | 16.9 | 8.1 | 32.0 | 24.8 | 46.0 | 21.2 | 122 | 321 | |
| Hori. | 906.363 | QP | 23.1 | 21.7 | 10.7 | 31.0 | 24.5 | 46.0 | 21.5 | 150 | 167 | |
| Hori. | 2483.500 | PK | 42.7 | 26.9 | 14.7 | 38.1 | 46.2 | 73.9 | 27.7 | 100 | 37 | |
| Hori. | 4960.000 | PK | 53.5 | 31.8 | 7.5 | 37.0 | 55.8 | 73.9 | 18.1 | 100 | 42 | |
| Hori. | 9920.000 | PK | 42.7 | 38.9 | 9.6 | 37.5 | 53.7 | 73.9 | 20.2 | 100 | 0 | |
| Hori. | 19840.000 | PK | 49.9 | 40.7 | 2.1 | 47.9 | 44.8 | 73.9 | 29.1 | 100 | 234 | |
| Hori. | 2483.500 | AV | 31.6 | 26.9 | 14.7 | 38.1 | 35.1 | 53.9 | 18.8 | 100 | 37 | |
| Vert. | 62.339 | QP | 24.9 | 7.7 | 6.5 | 32.2 | 6.9 | 40.0 | 33.1 | 100 | 354 | |
| Vert. | 277.828 | QP | 24.5 | 18.1 | 8.3 | 32.0 | 18.9 | 46.0 | 27.1 | 100 | 332 | |
| Vert. | 727.858 | QP | 23.1 | 19.9 | 10.0 | 31.8 | 21.2 | 46.0 | 24.8 | 100 | 2 | |
| Vert. | 2483.500 | PK | 42.9 | 26.9 | 14.7 | 38.1 | 46.4 | 73.9 | 27.5 | 100 | 74 | |
| Vert. | 4960.000 | PK | 52.8 | 31.8 | 7.5 | 37.0 | 55.1 | 73.9 | 18.8 | 100 | 265 | |
| Vert. | 7440.000 | PK | 44.8 | 37.4 | 8.8 | 39.4 | 51.6 | 73.9 | 22.3 | 100 | 0 | |
| Vert. | 9920.000 | PK | 42.6 | 38.9 | 9.6 | 37.5 | 53.6 | 73.9 | 20.3 | 100 | 0 | |
| Vert. | 19840.000 | PK | 49.2 | 40.7 | 2.1 | 47.9 | 44.1 | 73.9 | 29.8 | 110 | 159 | |
| Vert. | 2483.500 | AV | 31.8 | 26.9 | 14.7 | 38.1 | 35.3 | 53.9 | 18.6 | 100 | 74 | |

Result = Reading + Ant.Fac. + Loss (Cable+(Attenuator or Filter)(below 18GHz)-Distance factor(above 15GHz)) - Gain(Amplifier)

Distance factor : 15GHz -40GHz : 20log(3.0m/1.0m)= 9.5dB

Dwell time factor relaxation

| Polarity | Frequency [MHz] | Detector | Reading [dBuV] | Ant.Fac. [dB/m] | Loss [dB] | Gain [dB] | Dwell Factor [dB] | Result [dBuV/m] | Limit [dBuV/m] | Margin [dB] | Remark |
|----------|-----------------|----------|----------------|-----------------|-----------|-----------|-------------------|-----------------|----------------|-------------|--------|
| Hori. | 4960.000 | AV | 48.6 | 31.8 | 7.5 | 37.0 | -24.6 | 26.3 | 53.9 | 27.6 | |
| Hori. | 7440.000 | AV | 32.8 | 37.4 | 8.8 | 39.4 | -24.6 | 15.0 | 53.9 | 38.9 | |
| Hori. | 9920.000 | AV | 30.7 | 38.9 | 9.6 | 37.5 | -24.6 | 17.1 | 53.9 | 36.8 | |
| Hori. | 19840.000 | AV | 43.6 | 40.7 | 2.1 | 47.9 | -24.6 | 13.9 | 53.9 | 40.0 | |
| Vert. | 4960.000 | AV | 47.0 | 31.8 | 7.5 | 37.0 | -24.6 | 24.7 | 53.9 | 29.2 | |
| Vert. | 7440.000 | AV | 32.9 | 37.4 | 8.8 | 39.4 | -24.6 | 15.1 | 53.9 | 38.8 | |
| Vert. | 9920.000 | AV | 30.6 | 38.9 | 9.6 | 37.5 | -24.6 | 17.0 | 53.9 | 36.9 | |
| Vert. | 19840.000 | AV | 43.5 | 40.7 | 2.1 | 47.9 | -24.6 | 13.8 | 53.9 | 40.1 | |

Result = Reading + Ant.Fac. + Loss (Cable+(Attenuator or Filter)(below 18GHz)-Distance factor(above 15GHz)) - Gain(Amplifier) + Dwell(time)factor

Distance factor : 15GHz -40GHz : 20log(3.0m/1.0m)= 9.5dB

UL Japan, Inc.**Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

Radiated Emission

Test place No.3 Semi Anechoic Chamber
 Date May 16, 2014 May 17, 2014 May 18, 2014
 Temperature / Humidity 26 deg.C, 36 %RH 21 deg.C, 41 %RH 22 deg.C, 34 %RH
 Engineer Kenichi Adachi Wataru Kojima Wataru Kojima
 Mode Tx, 2402 MHz
 Tx, Bluetooth, EDR, PRBS9

(* PK: Peak, AV: Average, QP: Quasi-Peak)

| Polarity | Frequency [MHz] | Detector | Reading [dBuV] | Ant.Fac. [dB/m] | Loss [dB] | Gain [dB] | Result [dBuV/m] | Limit [dBuV/m] | Margin [dB] | Height [cm] | Angle [deg] | Remark |
|----------|-----------------|----------|----------------|-----------------|-----------|-----------|-----------------|----------------|-------------|-------------|-------------|--------|
| Hori. | 225.026 | QP | 37.1 | 16.7 | 8.0 | 32.0 | 29.8 | 46.0 | 16.2 | 152 | 0 | |
| Hori. | 240.029 | QP | 31.9 | 16.9 | 8.1 | 32.0 | 24.9 | 46.0 | 21.1 | 181 | 353 | |
| Hori. | 927.428 | QP | 22.3 | 21.8 | 10.7 | 30.8 | 24.0 | 46.0 | 22.0 | 100 | 300 | |
| Hori. | 2390.000 | PK | 42.3 | 26.8 | 14.6 | 38.2 | 45.5 | 73.9 | 28.4 | 100 | 44 | |
| Hori. | 2400.000 | PK | 43.8 | 26.8 | 14.6 | 38.2 | 47.0 | 73.9 | 26.9 | 100 | 44 | |
| Hori. | 4804.000 | PK | 50.2 | 30.9 | 7.5 | 37.1 | 51.5 | 73.9 | 22.4 | 100 | 48 | |
| Hori. | 7206.000 | PK | 45.2 | 37.1 | 8.6 | 39.4 | 51.5 | 73.9 | 22.4 | 100 | 0 | |
| Hori. | 9608.000 | PK | 43.0 | 38.6 | 9.6 | 37.6 | 53.6 | 73.9 | 20.3 | 100 | 0 | |
| Hori. | 19216.000 | PK | 51.1 | 40.8 | 1.9 | 48.4 | 45.4 | 73.9 | 28.5 | 130 | 178 | |
| Hori. | 2390.000 | AV | 31.2 | 26.8 | 14.6 | 38.2 | 34.4 | 53.9 | 19.5 | 100 | 44 | |
| Hori. | 2400.000 | AV | 33.0 | 26.8 | 14.6 | 38.2 | 36.2 | 53.9 | 17.7 | 100 | 44 | |
| Vert. | 91.782 | QP | 26.2 | 8.5 | 7.4 | 32.1 | 10.0 | 43.5 | 33.5 | 100 | 316 | |
| Vert. | 116.795 | QP | 24.9 | 12.6 | 7.1 | 32.1 | 12.5 | 43.5 | 31.0 | 100 | 357 | |
| Vert. | 296.671 | QP | 22.8 | 18.8 | 8.4 | 32.0 | 18.0 | 46.0 | 28.0 | 100 | 2 | |
| Vert. | 2390.000 | PK | 42.4 | 26.8 | 14.6 | 38.2 | 45.6 | 73.9 | 28.3 | 100 | 72 | |
| Vert. | 2400.000 | PK | 44.0 | 26.8 | 14.6 | 38.2 | 47.2 | 73.9 | 26.7 | 100 | 72 | |
| Vert. | 4804.000 | PK | 51.3 | 30.9 | 7.5 | 37.1 | 52.6 | 73.9 | 21.3 | 100 | 266 | |
| Vert. | 7206.000 | PK | 45.3 | 37.1 | 8.6 | 39.4 | 51.6 | 73.9 | 22.3 | 100 | 0 | |
| Vert. | 9608.000 | PK | 43.1 | 38.6 | 9.6 | 37.6 | 53.7 | 73.9 | 20.2 | 100 | 0 | |
| Vert. | 19216.000 | PK | 52.7 | 40.8 | 1.9 | 48.4 | 47.0 | 73.9 | 26.9 | 121 | 71 | |
| Vert. | 2390.000 | AV | 31.3 | 26.8 | 14.6 | 38.2 | 34.5 | 53.9 | 19.4 | 100 | 72 | |
| Vert. | 2400.000 | AV | 33.6 | 26.8 | 14.6 | 38.2 | 36.8 | 53.9 | 17.1 | 100 | 72 | |

Result = Reading + Ant.Fac. + Loss (Cable+(Attenuator or Filter)(below 18GHz)-Distance factor(above 15GHz)) - Gain(Amplifier)

Distance factor : 15GHz -40GHz : 20log(3.0m/1.0m)= 9.5dB

Dwell time factor relaxation

| Polarity | Frequency [MHz] | Detector | Reading [dBuV] | Ant.Fac. [dB/m] | Loss [dB] | Gain [dB] | Dwell Factor [dB] | Result [dBuV/m] | Limit [dBuV/m] | Margin [dB] | Remark |
|----------|-----------------|----------|----------------|-----------------|-----------|-----------|-------------------|-----------------|----------------|-------------|--------|
| Hori. | 4804.000 | AV | 43.8 | 30.9 | 7.5 | 37.1 | -24.6 | 20.5 | 53.9 | 33.4 | |
| Hori. | 7206.000 | AV | 33.4 | 37.1 | 8.6 | 39.4 | -24.6 | 15.1 | 53.9 | 38.8 | |
| Hori. | 9608.000 | AV | 31.2 | 38.6 | 9.6 | 37.6 | -24.6 | 17.2 | 53.9 | 36.7 | |
| Hori. | 19216.000 | AV | 46.1 | 40.8 | 1.9 | 48.4 | -24.6 | 15.8 | 53.9 | 38.1 | |
| Vert. | 4804.000 | AV | 44.8 | 30.9 | 7.5 | 37.1 | -24.6 | 21.5 | 53.9 | 32.4 | |
| Vert. | 7206.000 | AV | 33.4 | 37.1 | 8.6 | 39.4 | -24.6 | 15.1 | 53.9 | 38.8 | |
| Vert. | 9608.000 | AV | 31.3 | 38.6 | 9.6 | 37.6 | -24.6 | 17.3 | 53.9 | 36.6 | |
| Vert. | 19216.000 | AV | 48.7 | 40.8 | 1.9 | 48.4 | -24.6 | 18.4 | 53.9 | 35.5 | |

Result = Reading + Ant.Fac. + Loss (Cable+(Attenuator or Filter)(below 18GHz)-Distance factor(above 15GHz)) - Gain(Amplifier) + Dwell(time)factor

Distance factor : 15GHz -40GHz : 20log(3.0m/1.0m)= 9.5dB

UL Japan, Inc.**Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

Radiated Emission

Test place No.3 Semi Anechoic Chamber
 Date May 16, 2014 May 17, 2014 May 18, 2014
 Temperature / Humidity 26 deg.C, 36 %RH 21 deg.C, 41 %RH 22 deg.C, 34 %RH
 Engineer Kenichi Adachi Wataru Kojima Wataru Kojima
 Mode Tx, 2441 MHz
 Tx, Bluetooth, EDR, PRBS9

(* PK: Peak, AV: Average, QP: Quasi-Peak)

| Polarity | Frequency [MHz] | Detector | Reading [dBuV] | Ant.Fac. [dB/m] | Loss [dB] | Gain [dB] | Result [dBuV/m] | Limit [dBuV/m] | Margin [dB] | Height [cm] | Angle [deg] | Remark |
|----------|-----------------|----------|----------------|-----------------|-----------|-----------|-----------------|----------------|-------------|-------------|-------------|--------|
| Hori. | 225.074 | QP | 36.9 | 16.7 | 8.0 | 32.0 | 29.6 | 46.0 | 16.4 | 155 | 211 | |
| Hori. | 240.035 | QP | 33.1 | 16.9 | 8.1 | 32.0 | 26.1 | 46.0 | 19.9 | 150 | 251 | |
| Hori. | 952.957 | QP | 21.9 | 22.1 | 10.8 | 30.6 | 24.2 | 46.0 | 21.8 | 150 | 3 | |
| Hori. | 4882.000 | PK | 50.7 | 31.4 | 7.5 | 37.0 | 52.6 | 73.9 | 21.3 | 100 | 47 | |
| Hori. | 7323.000 | PK | 45.3 | 37.2 | 8.6 | 39.4 | 51.7 | 73.9 | 22.2 | 100 | 0 | |
| Hori. | 9764.000 | PK | 43.2 | 38.8 | 9.6 | 37.5 | 54.1 | 73.9 | 19.8 | 100 | 0 | |
| Hori. | 19528.000 | PK | 51.7 | 40.8 | 2.0 | 48.1 | 46.4 | 73.9 | 27.5 | 100 | 239 | |
| Vert. | 103.097 | QP | 24.2 | 10.5 | 7.2 | 32.1 | 9.8 | 43.5 | 33.7 | 100 | 280 | |
| Vert. | 132.087 | QP | 25.1 | 13.8 | 7.3 | 32.1 | 14.1 | 43.5 | 29.4 | 100 | 72 | |
| Vert. | 270.360 | QP | 23.1 | 17.8 | 8.2 | 32.0 | 17.1 | 46.0 | 28.9 | 100 | 70 | |
| Vert. | 4882.000 | PK | 51.6 | 31.4 | 7.5 | 37.0 | 53.5 | 73.9 | 20.4 | 100 | 266 | |
| Vert. | 7323.000 | PK | 45.2 | 37.2 | 8.6 | 39.4 | 51.6 | 73.9 | 22.3 | 100 | 0 | |
| Vert. | 9764.000 | PK | 43.3 | 38.8 | 9.6 | 37.5 | 54.2 | 73.9 | 19.7 | 100 | 0 | |
| Vert. | 19528.000 | PK | 50.3 | 40.8 | 2.0 | 48.1 | 45.0 | 73.9 | 28.9 | 118 | 85 | |

Result = Reading + Ant.Fac. + Loss (Cable+(Attenuator or Filter)(below 18GHz)-Distance factor(above 15GHz)) - Gain(Amplifier)

Distance factor : 15GHz -40GHz : 20log(3.0m/1.0m)= 9.5dB

Dwell time factor relaxation

| Polarity | Frequency [MHz] | Detector | Reading [dBuV] | Ant.Fac. [dB/m] | Loss [dB] | Gain [dB] | Dwell Factor [dB] | Result [dBuV/m] | Limit [dBuV/m] | Margin [dB] | Remark |
|----------|-----------------|----------|----------------|-----------------|-----------|-----------|-------------------|-----------------|----------------|-------------|--------|
| Hori. | 4882.000 | AV | 44.9 | 31.4 | 7.5 | 37.0 | -24.6 | 22.2 | 53.9 | 31.7 | |
| Hori. | 7323.000 | AV | 33.4 | 37.2 | 8.6 | 39.4 | -24.6 | 15.2 | 53.9 | 38.7 | |
| Hori. | 9764.000 | AV | 31.3 | 38.8 | 9.6 | 37.5 | -24.6 | 17.6 | 53.9 | 36.3 | |
| Hori. | 19528.000 | AV | 46.9 | 40.8 | 2.0 | 48.1 | -24.6 | 17.0 | 53.9 | 36.9 | |
| Vert. | 4882.000 | AV | 45.8 | 31.4 | 7.5 | 37.0 | -24.6 | 23.1 | 53.9 | 30.8 | |
| Vert. | 7323.000 | AV | 33.3 | 37.2 | 8.6 | 39.4 | -24.6 | 15.1 | 53.9 | 38.8 | |
| Vert. | 9764.000 | AV | 31.4 | 38.8 | 9.6 | 37.5 | -24.6 | 17.7 | 53.9 | 36.2 | |
| Vert. | 19528.000 | AV | 45.7 | 40.8 | 2.0 | 48.1 | -24.6 | 15.8 | 53.9 | 38.1 | |

Result = Reading + Ant.Fac. + Loss (Cable+(Attenuator or Filter)(below 18GHz)-Distance factor(above 15GHz)) - Gain(Amplifier) + Dwell(time)factor

Distance factor : 15GHz -40GHz : 20log(3.0m/1.0m)= 9.5dB

UL Japan, Inc.**Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

Radiated Emission

Test place No.3 Semi Anechoic Chamber
 Date May 16, 2014 May 17, 2014 May 18, 2014
 Temperature / Humidity 26 deg.C, 36 %RH 21 deg.C, 41 %RH 22 deg.C, 34 %RH
 Engineer Kenichi Adachi Wataru Kojima Wataru Kojima
 Mode Tx, 2480 MHz
 Tx, Bluetooth, EDR, PRBS9

(* PK: Peak, AV: Average, QP: Quasi-Peak)

| Polarity | Frequency [MHz] | Detector | Reading [dBuV] | Ant.Fac. [dB/m] | Loss [dB] | Gain [dB] | Result [dBuV/m] | Limit [dBuV/m] | Margin [dB] | Height [cm] | Angle [deg] | Remark |
|----------|-----------------|----------|----------------|-----------------|-----------|-----------|-----------------|----------------|-------------|-------------|-------------|--------|
| Hori. | 225.011 | QP | 36.2 | 16.7 | 8.0 | 32.0 | 28.9 | 46.0 | 17.1 | 150 | 356 | |
| Hori. | 239.991 | QP | 33.0 | 16.9 | 8.1 | 32.0 | 26.0 | 46.0 | 20.0 | 150 | 358 | |
| Hori. | 956.389 | QP | 23.1 | 22.1 | 10.8 | 30.6 | 25.4 | 46.0 | 20.6 | 150 | 307 | |
| Hori. | 2483.500 | PK | 42.8 | 26.9 | 14.7 | 38.1 | 46.3 | 73.9 | 27.6 | 100 | 35 | |
| Hori. | 4960.000 | PK | 50.4 | 31.8 | 7.5 | 37.0 | 52.7 | 73.9 | 21.2 | 100 | 45 | |
| Hori. | 7440.000 | PK | 44.8 | 37.4 | 8.8 | 39.4 | 51.6 | 73.9 | 22.3 | 100 | 0 | |
| Hori. | 9920.000 | PK | 42.6 | 38.9 | 9.6 | 37.5 | 53.6 | 73.9 | 20.3 | 100 | 0 | |
| Hori. | 19840.000 | PK | 50.1 | 40.7 | 2.1 | 47.9 | 45.0 | 73.9 | 28.9 | 100 | 234 | |
| Hori. | 2483.500 | AV | 31.6 | 26.9 | 14.7 | 38.1 | 35.1 | 53.9 | 18.8 | 100 | 35 | |
| Vert. | 61.252 | QP | 25.6 | 7.9 | 6.5 | 32.2 | 7.8 | 40.0 | 32.2 | 100 | 332 | |
| Vert. | 198.359 | QP | 22.0 | 16.4 | 7.8 | 32.1 | 14.1 | 43.5 | 29.4 | 100 | 44 | |
| Vert. | 298.797 | QP | 24.2 | 18.9 | 8.4 | 32.0 | 19.5 | 46.0 | 26.5 | 100 | 211 | |
| Vert. | 2483.500 | PK | 42.9 | 26.9 | 14.7 | 38.1 | 46.4 | 73.9 | 27.5 | 100 | 69 | |
| Vert. | 4960.000 | PK | 51.1 | 31.8 | 7.5 | 37.0 | 53.4 | 73.9 | 20.5 | 100 | 263 | |
| Vert. | 7440.000 | PK | 44.7 | 37.4 | 8.8 | 39.4 | 51.5 | 73.9 | 22.4 | 100 | 0 | |
| Vert. | 9920.000 | PK | 42.7 | 38.9 | 9.6 | 37.5 | 53.7 | 73.9 | 20.2 | 100 | 0 | |
| Vert. | 19840.000 | PK | 50.4 | 40.7 | 2.1 | 47.9 | 45.3 | 73.9 | 28.6 | 116 | 333 | |
| Vert. | 2483.500 | AV | 31.7 | 26.9 | 14.7 | 38.1 | 35.2 | 53.9 | 18.7 | 100 | 69 | |

Result = Reading + Ant.Fac. + Loss (Cable+(Attenuator or Filter)(below 18GHz)-Distance factor(above 15GHz)) - Gain(Amplifier)

Distance factor : 15GHz -40GHz : 20log(3.0m/1.0m)= 9.5dB

Dwell time factor relaxation

| Polarity | Frequency [MHz] | Detector | Reading [dBuV] | Ant.Fac. [dB/m] | Loss [dB] | Gain [dB] | Dwell Factor [dB] | Result [dBuV/m] | Limit [dBuV/m] | Margin [dB] | Remark |
|----------|-----------------|----------|----------------|-----------------|-----------|-----------|-------------------|-----------------|----------------|-------------|--------|
| Hori. | 4960.000 | AV | 43.9 | 31.8 | 7.5 | 37.0 | -24.6 | 21.6 | 53.9 | 32.3 | |
| Hori. | 7440.000 | AV | 32.8 | 37.4 | 8.8 | 39.4 | -24.6 | 15.0 | 53.9 | 38.9 | |
| Hori. | 9920.000 | AV | 30.6 | 38.9 | 9.6 | 37.5 | -24.6 | 17.0 | 53.9 | 36.9 | |
| Hori. | 19840.000 | AV | 44.3 | 40.7 | 2.1 | 47.9 | -24.6 | 14.6 | 53.9 | 39.3 | |
| Vert. | 4960.000 | AV | 44.5 | 31.8 | 7.5 | 37.0 | -24.6 | 22.2 | 53.9 | 31.7 | |
| Vert. | 7440.000 | AV | 32.8 | 37.4 | 8.8 | 39.4 | -24.6 | 15.0 | 53.9 | 38.9 | |
| Vert. | 9920.000 | AV | 30.7 | 38.9 | 9.6 | 37.5 | -24.6 | 17.1 | 53.9 | 36.8 | |
| Vert. | 19840.000 | AV | 44.8 | 40.7 | 2.1 | 47.9 | -24.6 | 15.1 | 53.9 | 38.8 | |

Result = Reading + Ant.Fac. + Loss (Cable+(Attenuator or Filter)(below 18GHz)-Distance factor(above 15GHz)) - Gain(Amplifier) + Dwell(time)factor

Distance factor : 15GHz -40GHz : 20log(3.0m/1.0m)= 9.5dB

UL Japan, Inc.**Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN


Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

Spurious emission (Conducted)

Tx, Bluetooth, BDR, PRBS9

Tx, 2402MHz (below 30MHz)



UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN


Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

Spurious emission (Conducted)

Tx, Bluetooth, BDR, PRBS9

Tx, 2441MHz (below 30MHz)



UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN


Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

Spurious emission (Conducted)

Tx, Bluetooth, BDR, PRBS9

Tx, 2480MHz (below 30MHz)



UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN


Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

Spurious emission (Conducted)

Tx, Bluetooth, EDR, PRBS9

Tx, 2402MHz (below 30MHz)



UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN


Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

Spurious emission (Conducted)

Tx, Bluetooth, EDR, PRBS9

Tx, 2441MHz (below 30MHz)



UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN


Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

Spurious emission (Conducted)

Tx, Bluetooth, EDR, PRBS9

Tx, 2480MHz (below 30MHz)



UL Japan, Inc.

Shonan EMC Lab.



1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

Spurious emission (Conducted)

Band Edge compliance



UL Japan, Inc.

Shonan EMC Lab.



1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN

Telephone : +81 463 50 6400


Facsimile : +81 463 50 6401

Spurious emission (Conducted)

Band Edge compliance



99% Occupied Bandwidth



99% Occupied Bandwidth

| Tx, Bluetooth, EDR, PRBS9 | |
|--|---|
| Tx, 2402MHz | Tx, 2441MHz |
| <p>Tx1_99OBW</p> <p>Agilent R L</p> <p>Ref 107 dBμV *Atten 10 dB</p> <p>Center 2.402 000 0 GHz *Res BW 30 kHz *VBW 100 kHz Sweep 10.08 ms (1201 pts) Span 3 MHz</p> <p>Occupied Bandwidth 1.1560 MHz</p> <p>Occ BW % Pwr 99.00 % x dB -20.00 dB</p> <p>Transmit Freq Error 11.751 kHz x dB Bandwidth 1.270 MHz*</p> | <p>Tx2_99OBW</p> <p>Agilent R L</p> <p>Ref 107 dBμV *Atten 10 dB</p> <p>Center 2.441 000 0 GHz *Res BW 30 kHz *VBW 100 kHz Sweep 10.08 ms (1201 pts) Span 3 MHz</p> <p>Occupied Bandwidth 1.1538 MHz</p> <p>Occ BW % Pwr 99.00 % x dB -20.00 dB</p> <p>Transmit Freq Error -545.368 Hz x dB Bandwidth 1.252 MHz*</p> |
| <p>Tx3_99OBW</p> <p>Agilent R L</p> <p>Ref 107 dBμV *Atten 10 dB</p> <p>Center 2.480 000 0 GHz *Res BW 30 kHz *VBW 100 kHz Sweep 10.08 ms (1201 pts) Span 3 MHz</p> <p>Occupied Bandwidth 1.1537 MHz</p> <p>Occ BW % Pwr 99.00 % x dB -20.00 dB</p> <p>Transmit Freq Error -268.091 Hz x dB Bandwidth 1.253 MHz*</p> | <p>Tx2_Hopping99OBW</p> <p>Agilent R L</p> <p>Ref 107 dBμV *Atten 10 dB</p> <p>Center 2.441 00 GHz *Res BW 1 MHz *VBW 3 MHz Sweep 1.04 ms (1201 pts) Span 100 MHz</p> <p>Occupied Bandwidth 78.6304 MHz</p> <p>Occ BW % Pwr 99.00 % x dB -20.00 dB</p> <p>Transmit Freq Error 27.933 kHz x dB Bandwidth 80.966 MHz*</p> |
| <p>Tx2_inquiry99OBW</p> | <p>Tx2_inqHopping99OBW</p> |

APPENDIX 2 Test Instruments

EMI test equipment

| Control No. | Instrument | Manufacturer | Model No | Serial No | Test Item | Calibration Date * Interval(month) |
|--------------------------------|---------------------------|---|--|-------------------------|-----------|------------------------------------|
| KSA-08 | Spectrum Analyzer | Agilent | E4446A | MY46180525 | AT | 2014/03/04 * 12 |
| SPM-07 | Power Meter | Agilent | 8990B | MY5100272 | AT | 2014/04/04 * 12 |
| SPSS-04 | Power sensor | Agilent | N1923A | MY5326009 | AT | 2014/04/04 * 12 |
| SCC-G12 | Coaxial Cable | Suhner | SUCOFLEX 102 | 30790/2 | AT | 2014/03/13 * 12 |
| SAT10-11 | Attenuator | Weinschel Corp. | 54A-10 | 37588 | AT | 2014/04/22 * 12 |
| SOS-13 | Humidity Indicator | Custom | CTH-202 | Q.C.17 | AT | 2014/04/22 * 12 |
| SAEC-03(NSA) | Semi-Anechoic Chamber | TDK | SAEC-03(NSA) | 3 | RE | 2013/07/09 * 12 |
| SHA-03 | Horn Antenna | Schwarzbeck | BBHA9120D | 9120D-739 | RE | 2013/08/19 * 12 |
| SCC-G01 | Coaxial Cable | Suhner | SUCOFLEX 104A | 46497/4A | RE | 2014/04/22 * 12 |
| SAT10-06 | Attenuator | Agilent | 8493C-010 | 74865 | RE | 2013/11/22 * 12 |
| SFL-02 | Highpass Filter | MICRO-TRONICS | HPM50111 | 051 | RE | 2013/11/22 * 12 |
| SAF-05 | Pre Amplifier | TOYO Corporation | TPA0118-36 | 1440490 | RE | 2013/11/22 * 12 |
| SCC-G21 | Coaxial Cable | Suhner | SUCOFLEX 104 | 296169/4 | RE | 2014/05/15 * 12 |
| SSA-02 | Spectrum Analyzer | Agilent | E4448A | MY48250106 | RE | 2014/03/17 * 12 |
| SOS-05 | Humidity Indicator | A&D | AD-5681 | 4062518 | RE | 2014/02/21 * 12 |
| SJM-15 | Measure | ASKUL | - | - | RE | - |
| SHA-04 | Horn Antenna | ETS LINDGREN | 3160-09 | LM3640 | RE | 2014/03/15 * 12 |
| SCC-G15 | Coaxial Cable | Suhner | SUCOFLEX 102 | 32703/2 | RE | 2014/03/13 * 12 |
| SAF-08 | Pre Amplifier | TOYO Corporation | HAP18-26W | 00000019 | RE | 2014/03/14 * 12 |
| COTS-SEMI-1 | EMI Software | TSJ | TEPTO-DV(RE,CE, RFLMF) | - | RE | - |
| SAF-03 | Pre Amplifier | SONOMA | 310N | 290213 | RE | 2014/02/14 * 12 |
| SAT6-06 | Attenuator | JFW | 50HF-006N | - | RE | 2014/02/17 * 12 |
| SBA-03 | Biconical Antenna | Schwarzbeck | BBA9106 | 91032666 | RE | 2013/10/26 * 12 |
| SCC-C1/C2/C3/C4/C5/C10/SRSE-03 | Coaxial Cable&RF Selector | Fujikura/Fujikura/Suhner/Suhner/Suhner/TOYO | 8D2W/12DSFA/141PE/141PE/141PE/141PE/NS4906 | -/0901-271(RF Selector) | RE | 2014/04/25 * 12 |
| SLA-03 | Logperiodic Antenna | Schwarzbeck | UHALP9108A | UHALP 9108-A 0901 | RE | 2013/10/26 * 12 |
| STR-06 | Test Receiver | Rohde & Schwarz | ESCI | 101259 | RE | 2014/03/04 * 12 |
| | | | | | | |
| | | | | | | |

The expiration date of the calibration is the end of the expired month .

As for some calibrations performed after the tested dates , those test equipment have been controlled by means of an unbroken chains of calibrations .

All equipment is calibrated with valid calibrations . Each measurement data is traceable to the national or international standards .

Test Item :

RE: Radiated emission,

AT: Antenna terminal conducted tests