


SAR EVALUATION REPORT

Report No. : 23LE0006-HO-3

Applicant : Sony Corporation
Type of Equipment : Notebook Personal Computer
Model No. : PCG-492L
FCC ID : AK8PCG492L
Test standard : FCC47CFR 2.1093
FCC OET Bulletin 65, Supplement C
Test Result : Complied
Max SAR Measured : 0.101W/kg
(Body, OFDM (QPSK), 2412MHz)

1. This test report shall not be reproduced except full or partial, without the written approval of UL Apex Co., Ltd.
2. The results in this report apply only to the sample tested.
3. This equipment is in compliance with above regulation. We hereby certify that the data contain a true representation of the SAR profile.
4. The test results in this test report are traceable to the national or international standards.

Date of test: July 09 and 10, 2003

Tested by: 
Miyo Ikuta
EMC Head Office Division

Approved by: 
Tetsuo Maeno
Site Manager of EMC Head Office Division

CONTENTS

	PAGE
SECTION 1 : Client information	3
SECTION 2 : Equipment under test (E.U.T.)	3
SECTION 3 : Requirements for compliance testing defined by the FCC	4
SECTION 4 : Dosimetric assessment setup	4
SECTION 5 : Test system specifications	7
SECTION 6 : Test setup of EUT	8
SECTION 7 : Measurement uncertainty	11
SECTION 8 : Simulated tissue liquid parameter	12
SECTION 9 : System validation data	14
SECTION 10 : Evaluation procedure	15
SECTION 11 : Exposure limit	16
SECTION 12 : SAR Measurement results	17
SECTION 13 : Equipment & calibration information	21
SECTION 14 : References	22
SECTION 15 : APPENDIX	22
APPENDIX 1 : Photographs of test setup	
APPENDIX 2 : SAR Measurement data	
APPENDIX 3 : Validation Measurement data	
APPENDIX 4 : System Validation Dipole (D2450V2,S/N: 713)	
APPENDIX 5 : Dosimetric E-Field Probe Calibration(ET3DV6,S/N: 1684)	

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8116


Facsimile: +81 596 24 8124

SECTION 1 : Client information

Company Name : Sony Corporation
Brand Name : SONY
Address : 6-7-35 Kita-Sinagawa Sinagawa -ku Tokyo, Japan
Telephone Number : +81-3-5795-8033
Facsimile Number : +81-3-5795-8346
Contact Person : Kaoru Ichimura

SECTION 2 : Equipment under test (E.U.T.)**2.1 Identification of E.U.T.**

APPLICANT : Sony Corporation
Type of Equipment : Notebook Personal Computer
Model No. : PCG-492L
Serial No. : DVT26
Rating : DC 3.1V ~ 3.46 V
Country of Manufacture : JAPAN
Receipt Date of Sample : July 08,2003
Condition of EUT : Engineering prototype
Tx Frequency : 2412MHz~2462MHz
Modulation : OFDM, DSSS[DQPSK,DBPSK and CCK] Main Antenna (Right Antenna)
Max.Output Power Tested : 22.1dBm Peak Conducted
Antenna Type : $\lambda/4$ -Monopole Antenna
Position of Antenna : See Photograph of right
Battery option : Only one model with EUT
Category Identified : Portable device



UL Apex Co., Ltd.***Head Office EMC Lab.****4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN**Telephone: +81 596 24 8116**Facsimile: +81 596 24 8124*

SECTION 3 : Requirements for compliance testing defined by the FCC

The US Federal Communications Commission has released the report and order "Guidelines for Evaluating the Environmental Effects of RF Radiation", ET Docket No. 93-62 in August 1996. The order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 1.6 mW/g for an uncontrolled environment and 8.0 mW/g for an occupational/controlled environment as recommended by the ANSI/IEEE standard C95.1-1992. According to the Supplement C of OET Bulletin 65 "Evaluating Compliance with FCC Guide-lines for Human Exposure to Radio frequency Electromagnetic Fields", released on Jun 29, 2001 by the FCC, the device should be evaluated at maximum output power (radiated from the antenna) under "worst-case" conditions for normal or intended use, incorporating normal antenna operating positions, device peak performance frequencies and positions for maximum RF energy coupling.

- 1 Specific Absorption Rate (SAR) is a measure of the rate of energy absorption due to exposure to an RF transmitting source (wireless portable device).
- 2 IEEE/ANSI Std. C95.1-1992 limits are used to determine compliance with FCC ET Docket 93-62.

SECTION 4 : Dosimetry assessment setup

These measurements were performed with the automated near-field scanning system DASY3 from Schmid & Partner Engineering AG (SPEAG). The system is based on a high precision robot (working range greater than 0.9 m), which positions the probes with a positional repeatability of better than +/- 0.02 mm. Special E- and H-field probes have been developed for measurements close to material discontinuity, the sensors of which are directly loaded with a Schottky diode and connected via highly resistive lines to the data acquisition unit. The SAR measurements were conducted with the dosimetry probe ET3DV6, SN: 1684 (manufactured by SPEAG), designed in the classical triangular configuration and optimized for dosimetric evaluation. The probe has been calibrated according to the procedure described in [2] with accuracy of better than +/-10%. The spherical isotropy was evaluated with the procedure described in [3] and found to be better than +/-0.25 dB. The phantom used was the SAM Twin Phantom as described in FCC supplement C, IEE P1528 and CENELEC EN50361.

UL Apex Co., Ltd.


Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8116

Facsimile: +81 596 24 8124

4.1 Configuration and peripherals



The DASY3 system for performing compliance tests consist of the following items:

1. A standard high precision 6-axis robot (Stäubli RX family) with controller and software.
2. An arm extension for accommodating the data acquisition electronics (DAE).
3. A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
4. A data acquisition electronic (DAE), which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
5. A unit to operate the optical surface detector, which is connected to the EOC.
6. The Electro-optical coupler (EOC) performs the conversion from the optical into a digital electric signal of the DAE. The EOC is connected to the PC plug-in card.
7. The functions of the PC plug-in card based on a DSP is to perform the time critical task such as signal filtering, surveillance of the robot operation fast movement interrupts.
8. A computer operating Windows 98
9. DASY3 software
10. Remote control with teaches pendant and additional circuitry for robot safety such as warning lamps, etc.
11. The SAM phantom enabling testing left-hand and right-hand usage.
12. The device holder for handheld EUT.
13. Tissue simulating liquid mixed according to the given recipes (see Application Note).
14. System validation dipoles to validate the proper functioning of the system.

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8116

Facsimile: +81 596 24 8124

4.2 System components

4.2.1 ET3DV6 Probe Specification

Construction:

Symmetrical design with triangular core
Built-in optical fiber for surface detection System
Built-in shielding against static charges
PEEK enclosure material (resistant to organic solvents, e.g., glycol ether)

Calibration:

Basic Broad Band calibration in air from 10 MHz to 2.5 GHz
In brain and muscle simulating tissue at
Frequencies of 450 MHz, 900 MHz, 1.8 GHz and 2.45GHz (accuracy +/- 8%)

Frequency:

10 MHz to 3GHz; Linearity: +/-0.2 dB
(30 MHz to 3 GHz)

Directivity:

+/-0.2 dB in brain tissue (rotation around probe axis)
+/-0.4 dB in brain tissue (rotation normal probe axis)

Dynamic Range:

5 mW/g to > 100 mW/g; Linearity: +/-0.2 dB

Optical Surface Detection:

+/-0.2 mm repeatability in air and clear liquids over diffuse reflecting surfaces.

Dimensions:

Overall length: 330 mm (Tip: 16 mm)
Tip length: 16 mm
Body diameter: 12 mm (Body: 12 mm)
Tip diameter: 6.8 mm
Distance from probe tip to dipole centers: 2.7 mm

Application:

General dosimetric up to 3 GHz
Compliance tests of mobile phones
Fast automatic scanning in arbitrary phantoms



Inside view of
ET3DV6 E-field
Probe

4.2.2 SAM Phantom

Construction:

The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528-200X, CENELEC 50361 and IEC 62209. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points with the robot.


Shell Thickness:

2 +/-0.2 mm

Filling Volume:

Approx. 25 liters

Dimensions:(H x L x W): 810 x 1000 x 500 mm



SAM Phantom

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8116

Facsimile: +81 596 24 8124

4.2.3 Device Holder for Transmitters

In combination with the SAM Twin Phantom V4.0, the Mounting Device enables the rotation of the mounted transmitter in spherical coordinates whereby the rotation points is the ear opening. The devices can be easily, accurately, and repeatedly positioned according to the FCC and CENELEC specifications. The device holder can be locked at different phantom locations (left head, right head, flat phantom).

* Note: A simulating human hand is not used due to the complex anatomical and geometrical structure of the hand that may produced infinite number of configurations.

To produce the worst-case condition (the hand absorbs antenna output power), the hand is omitted during the tests.

Device holder couldn't be used at this SAR measurement.



Device Holder

SECTION 5 : Test system specifications

Positioner

Robot:	Stäubli Unimation Corp. Robot Model: RX60L
Repeatability:	0.02 mm
No. of axis:	6

Data Acquisition Electronic (DAE) System

Cell Controller

Processor:	Pentium III
Clock Speed:	450 MHz
Operating System:	Windows 98
Data Card:	DASY3 PC-Board

Data Converter

Features:	Signal Amplifier, multiplexer, A/D converter, and control logic
Software:	DASY3 software
Connecting Lines:	Optical downlink for data and status info. Optical uplink for commands and clock

PC Interface Card

Function:	24 bit (64 MHz) DSP for real time processing Link to DAE3 16-bit A/D converter for surface detection system serial link to robot direct emergency stop output for robot
------------------	---

E-Field Probe

Model:	ET3DV6
Serial No.:	1684
Construction:	Triangular core fiber optic detection system
Frequency:	10 MHz to 6 GHz
Linearity:	+/-0.2 dB (30 MHz to 3 GHz)

Phantom

Type:	SAM Twin Phantom V4.0
Shell Material:	Fiberglass
Thickness:	2.0 +/-0.2 mm
Volume:	Approx. 20 liters

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8116


Facsimile: +81 596 24 8124

SECTION 6 : Test setup of EUT

6.1 Photographs of test setup

When users operate or carry this EUT, it could be considered to touch or get close to their bodies. In order to assume this situation, we performed the test at the following positions. Please refer to "APPENDIX 1" for more details.

- | | |
|-------------------------|--|
| 1.Right Bottom | : We performed the test with right of bottom of PC touching to the center of flat phantom. |
| 2.Left Bottom | : We performed the test with left of bottom of PC touching to the center of flat phantom. |
| 4.Right Back of display | : We performed the test with right back of display distanced 15mm from the center of flat phantom. |
| 5.Left Back of display | : We performed the test with left back of display distanced 15mm from the center of flat phantom. |
| 6.Right Top of display | : We performed the test with right top of display distanced 15mm from the center of flat phantom. |
| 7.Left Top of display | : We performed the test with left top of display distanced 15mm from the center of flat phantom. |





UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8116

Facsimile: +81 596 24 8124



6.2 EUT Tune-up procedure

In order to measure SAR value, we used continuous transmission mode. The test set up mode was prepared by manufacturer.

Value of Crest Factor = 1 was used for SAR testing according modulation (DSSS and OFDM) of the EUT.

The test configuration tested at the low, middle and high frequency channels (2412MHz,2437MHz and 2462MHz) of wireless LAN.

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8116

Facsimile: +81 596 24 8124

SECTION 7 : Measurement uncertainty

The uncertainty budget has been determined for the DASY3 measurement system according to the NIS81 [13] and the NIST1297 [6] documents and is given in the following Table.

Error Description	Uncertainty value \pm %	Probability distribution	divisor	(ci)1 lg	Standard Uncertainty (1g)	vi or v _{eff}
Measurement System						
Probe calibration	± 4.8	Normal	1	1	± 4.8	∞
Axial isotropy of the probe	± 4.7	Rectangular	$\sqrt{3}$	$(1-c_p)^{1/2}$	± 1.9	∞
Spherical isotropy of the probe	± 9.6	Rectangular	$\sqrt{3}$	$(c_p)^{1/2}$	± 3.9	∞
Boundary effects	± 5.5	Rectangular	$\sqrt{3}$	1	± 3.2	∞
Probe linearity	± 4.7	Rectangular	$\sqrt{3}$	1	± 2.7	∞
Detection limit	± 1.0	Rectangular	$\sqrt{3}$	1	± 0.6	∞
Readout electronics	± 1.0	Normal	1	1	± 1.0	∞
Response time	± 0.8	Rectangular	$\sqrt{3}$	1	± 0.5	∞
Integration time	± 1.4	Rectangular	$\sqrt{3}$	1	± 0.8	∞
RF ambient conditions	± 3.0	Rectangular	$\sqrt{3}$	1	± 1.7	∞
Mech. constraints of robot	± 0.4	Rectangular	$\sqrt{3}$	1	± 0.2	∞
Probe positioning	± 2.9	Rectangular	$\sqrt{3}$	1	± 1.7	∞
Extrap. and integration	± 3.9	Rectangular	$\sqrt{3}$	1	± 2.3	∞
Test Sample Related						
Device positioning	± 6.0	Rectangular	$\sqrt{3}$	1	± 6.7	35
Device holder uncertainty	± 5.0	Rectangular	$\sqrt{3}$	1	± 5.9	6
Power drift	± 5.0	Rectangular	$\sqrt{3}$	1	± 2.9	∞
Phantom and Setup						
Phantom uncertainty	± 4.0	Rectangular	$\sqrt{3}$	1	± 2.3	∞
Liquid conductivity (target)	± 5.0	Rectangular	$\sqrt{3}$	0.64	± 1.8	∞
Liquid conductivity (meas.)	± 10.0	Rectangular	$\sqrt{3}$	0.64	± 3.7	∞
Liquid permittivity (target)	± 5.0	Rectangular	$\sqrt{3}$	0.6	± 1.7	∞
Liquid permittivity (meas.)	± 5.0	Rectangular	$\sqrt{3}$	0.6	± 1.7	∞
Combined Standard Uncertainty					± 13.7	
Expanded Uncertainty (k=2)					± 27.5	

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8116

Facsimile: +81 596 24 8124

SECTION 8 : Simulated tissue liquid parameter

8.1 Simulated Tissue Liquid Parameter confirmation

The dielectric parameters were checked prior to assessment using the HP85070A dielectric probe kit. The dielectric parameters measured are reported in each correspondent section.

8.1.1 Head 2450MHz

Type of liquid : **Head 2450 MHz**
Ambient temperature (deg.c.) : **24.5(July 09) / 23.8(July 10)**
Relative Humidity (%) : **59(July 09) / 58(July 10)**
Liquid depth (cm) : **15.3**

Measured By : Miyo Ikuta

DIELECTRIC PARAMETERS MEASUREMENT RESULTS							
Date	Liquid Temp [deg.c]		Parameters	Target Value	Measured	Deviation [%]	Limit [%]
	Before	After					
July 09	24.5	24.5	Relative Permittivity ϵ_r	39.2	35.6	-9.2	+/-10
			Conductivity σ [mho/m]	1.80	1.81	+0.6	+/-5
July 10	23.8	23.8	Relative Permittivity ϵ_r	39.2	35.9	-8.4	+/-10
			Conductivity σ [mho/m]	1.80	1.81	+0.6	+/-5

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8116

Facsimile: +81 596 24 8124

8.1.2 Muscle 2450MHz

Type of liquid : **Muscle 2450 MHz**
 Ambient temperature (deg.c.) : **24.0(July 09) / 24.0(July 10)**
 Relative Humidity (%) : **59(July 09) / 58(July 10)**
 Liquid depth (cm) : **15.1**

Measured By : Miyo Ikuta

DIELECTRIC PARAMETERS MEASUREMENT RESULTS							
Date	Liquid Temp [deg.c]		Parameters	Target Value	Measured	Deviation [%]	Limit [%]
	Before	After					
July 09	23.8	23.8	Relative Permittivity ϵ_r	52.7	48.1	-8.7	+/-10
			Conductivity σ [mho/m]	1.95	1.98	+1.5	+/-5
July 10	23.8	23.8	Relative Permittivity ϵ_r	52.7	48.3	-8.3	+/-10
			Conductivity σ [mho/m]	1.95	2.00	+2.6	+/-5

8.2 Simulated Tissues

Ingredient	MiXTURE(%)	
	Head 2450MHz	Muscle 2450MHz
Water	45.0	69.83
DGMBE	55.0	30.17

Note:DGMBE(Diethylenglycol-monobuthyl ether)

UL Apex Co., Ltd.**Head Office EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8116

Facsimile: +81 596 24 8124

SECTION 9 : System validation data



Prior to the assessment, the system validation kit was used to test whether the system was operating within its specifications of +/-10%. The validation results are tabulated below. And SAR plot is attached in the APPENDIX 3. IEEE P1528 Recommended Reference Value

Type of liquid : **HEAD 2450MHZ**
 Frequency : **2450MHz**
 Dipole : **D2450V2 SN:713**
 Liquid depth (cm) : **15.3**
 Ambient temperature (deg.c.) : **24.5(July 09) / 23.8(July 10)**
 Relative Humidity (%) : **59(July 09) / 58(July 10)**
 Power : **250mW**

Measured By : Miyo Ikuta

SYSTEM PERFORMANCE CHECK										
Date	Liquid (HEAD 2450MHz)						System dipole validation target & measured			
	temperature [deg.c.]		Relative Permittivity ϵ_r		Conductivity σ [mho/m]		SAR 1g [W/kg]		Deviation [%]	Limit [%]
	Before	After	Target	Measured	Target	Measured	Target	Measured		
July 09	24.5	24.5	39.2	35.6	1.80	1.81	13.1	14.1	+7.6	+/-10
July 10	23.0	23.0	39.2	35.9	1.80	1.81	13.1	14.3	+9.2	+/-10

Note: Please refer to Attachment for the result representation in plot format



2450MHz System performance check setup

Test system for the system performance check setup diagram

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8116

Facsimile: +81 596 24 8124

SECTION 10 : Evaluation procedure

The evaluation was performed with the following procedure:

Step 1: Measurement of the SAR value at a fixed location above the ear point or central position of flat phantom was used as a reference value for assessing the power drop.

Step 2: The SAR distribution at the exposed side of head or body position was measured at a distance of each device from the inner surface of the shell. The area covered the entire dimension of the head or EUT and the horizontal grid spacing was 20 mm x 20 mm. Based on these data, the area of the maximum absorption was determined by spline interpolation.

Step 3: Around this point, a volume of 32 mm x 32 mm x 30 mm was assessed by measuring 5 x 5 x 7 points. On the basis of this data set, the spatial peak SAR value was evaluated under the following procedure:

1. The data at the surface were extrapolated, since the center of the dipoles is 2.7 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.2 mm. The extrapolation was based on a least square algorithm [4]. A polynomial of the fourth order was calculated through the points in z-axes. This polynomial was then used to evaluate the points between the surface and the probe tip.
2. The maximum interpolated value was searched with a straightforward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1 g or 10 g) were computed by the 3D-Spline interpolation algorithm. The 3D-Spline is composed of three one-dimensional splines with the "Not a knot"-condition (in x, y and z-directions) [4], [5]. The volume was integrated with the trapezoidal-algorithm. One thousand points (10 x 10 x 10) were interpolated to calculate the average.
3. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.

Step 4: Re-measurement of the SAR value at the same location as in Step 1. If the value changed by more than 5%, the evaluation was repeated.

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8116

Facsimile: +81 596 24 8124

SECTION 11 : Exposure limit**(A) Limits for Occupational/Controlled Exposure (W/kg)**

Spatial Average (averaged over the whole body)	Spatial Peak (averaged over any 1g of tissue)	Spatial Peak (hands/wrists/feet/ankles averaged over 10g)
0.4	8.0	20.0

(B) Limits for General population/Uncontrolled Exposure (W/kg)

Spatial Average (averaged over the whole body)	Spatial Peak (averaged over any 1g of tissue)	Spatial Peak (hands/wrists/feet/ankles averaged over 10g)
0.08	1.6	4.0

Occupational/Controlled Environments: are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

General Population/Uncontrolled Environments: are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

NOTE:GENERAL POPULATION/UNCONTROLLED EXPOSURE SPATIAL PEAK(averaged over any 1g of tissue) LIMIT 1.6 W/kg
--

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8116

Facsimile: +81 596 24 8124

SECTION 12 : SAR Measurement results**12.1 Measurement results of main antenna (Right antenna)****12.1.1 Conducted power measurement results**

Date : July 09,2003

Measured By : Miyo Ikuta

CONDUCTED POWER MEASUREMENT RESULTS (MAIN ANTENNA)													
Modulation	Frequency [MHz]	Before					After					Deviation [%]	Limit [%]
		Reading [dBm]	Cable loss [dB]	Att. [dB]	Result [dBm]	Convert [mW]	Reading [dBm]	Cable loss [dB]	Att. [dB]	Result [dBm]	Convert [mW]		
DSSS (CCK)	2412.0	5.2	0.8	10.0	16.0	39.8	5.1	0.8	10.0	15.9	38.9	-2.3	+/-5
	2437.0	4.7	0.9	10.0	15.6	36.3	4.6	0.9	10.0	15.5	35.5	-2.3	+/-5
	2462.0	4.3	1.0	10.0	15.3	33.9	4.3	1.0	10.0	15.3	33.9	0.0	+/-5
OFDM (64QAM)	2412.0	7.7	0.8	10.0	18.5	70.8	7.8	0.8	10.0	18.6	72.4	2.3	+/-5
	2437.0	8.7	0.9	10.0	19.6	91.2	8.6	0.9	10.0	19.5	89.1	-2.3	+/-5
	2462.0	9.2	1.0	10.0	20.2	104.7	9.2	1.0	10.0	20.2	104.7	0.0	+/-5
OFDM (QPSK)	2412.0	10.0	0.8	10.0	20.8	120.2	10.0	0.8	10.0	20.8	120.2	0.0	+/-5
	2437.0	11.2	0.9	10.0	22.1	162.2	11.1	0.9	10.0	22.0	158.5	-2.3	+/-5
	2462.0	10.7	1.0	10.0	21.7	147.9	10.7	1.0	10.0	21.7	147.9	0.0	+/-5

12.1.2 Body 2450MHz SAR of main antenna

Liquid Depth (cm) : **15.1** Model : **PCG-492L**
Parameters : $\epsilon_r = 48.1, \sigma = 1.98$ Serial No. : **DVT26**
Ambient Temperature[deg.c.] : **24.5** Modulation : **DSSS,OFDM**
Relative Humidity (%) : **59** Crest factor : **1**

Date : July 09,2003

Measured By : Miyo Ikuta

BODY SAR MEASUREMENT RESULTS ABOUT MAIN ANTENNA									
Frequency		Modulation	Phantom Section	EUT Set-up Conditions			Liquid Temp.[deg.c]		SAR(1g) [w/kg]
Channel	MHz			Antenna	Position	Separation [mm]	Before	After	
Mid	2437	DSSS(CCK)	Flat	Fixed	Right Bottom	0	22.6	22.6	0.0231
Mid	2437	DSSS(CCK)	Flat	Fixed	Left Bottom	0	22.6	22.6	0.0043
Mid	2437	DSSS(CCK)	Flat	Fixed	Right Back of display	15	22.9	22.9	0.0423
Mid	2437	DSSS(CCK)	Flat	Fixed	Right Top of display	15	22.9	22.9	0.0453
Low	2412	DSSS(CCK)	Flat	Fixed	Right Top of display	15	22.9	22.8	0.0489
High	2462	DSSS(CCK)	Flat	Fixed	Right Top of display	15	22.8	22.8	0.0532
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure / General Population							Body SAR: 1.6 W/kg (averaged over 1 gram)		

UL Apex Co., Ltd.**Head Office EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8116

Facsimile: +81 596 24 8124

Date : July 09,2003

Measured By : Miyo Ikuta

BODY SAR MEASUREMENT RESULTS ABOUT MAIN ANTENNA									
Frequency		Modulation	Phantom Section	EUT Set-up Conditions			Liquid Temp.[deg.c]		SAR(1g) [w/kg]
Channel	MHz			Antenna	Position	Separation[mm]	Before	After	
Mid	2437	OFDM (64QAM)	Flat	Fixed	Right Bottom	0	22.8	22.8	0.0138
Mid	2437	OFDM (64QAM)	Flat	Fixed	Left Bottom	0	22.8	22.8	0.0012
Mid	2437	OFDM (64QAM)	Flat	Fixed	Right Back of display	15	22.6	22.6	0.0308
Mid	2437	OFDM (64QAM)	Flat	Fixed	Right Top of display	15	22.6	22.6	0.0450
Low	2412	OFDM (64QAM)	Flat	Fixed	Right Top of display	15	22.6	22.6	0.0422
High	2462	OFDM (64QAM)	Flat	Fixed	Right Top of display	15	22.6	22.6	0.0364
Mid	2437	OFDM (QPSK)	Flat	Fixed	Right Bottom	0	22.8	22.9	0.0420
Mid	2437	OFDM (QPSK)	Flat	Fixed	Left Bottom	0	22.9	23.0	0.0002
Mid	2437	OFDM (QPSK)	Flat	Fixed	Right Back of display	15	23.0	23.0	0.0465
Mid	2437	OFDM (QPSK)	Flat	Fixed	Right Top of display	15	23.0	23.0	0.0995
Low	2412	OFDM (QPSK)	Flat	Fixed	Right Top of display	15	23.0	23.1	0.101
High	2462	OFDM (QPSK)	Flat	Fixed	Right Top of display	15	23.1	23.1	0.0904
ANSI / IEEE C95.1 1992 - SAFETY LIMIT							Body SAR: 1.6 W/kg		
Spatial Peak Uncontrolled Exposure / General Population							(averaged over 1 gram)		

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8116

Facsimile: +81 596 24 8124

12.2 Measurement results of sub antenna (Left antenna)**12.2.1 Conducted power measurement results**

Date : July 10,2003

Measured By : Miyo Ikuta

CONDUCTED POWER MEASUREMENT RESULTS (SUB ANTENNA)													
Modulation	Frequency [MHz]	Before					After					Deviation [%]	Limit [%]
		Reading [dBm]	Cable loss [dB]	Att. [dB]	Result [dBm]	Convert [mW]	Reading [dBm]	Cable loss [dB]	Att. [dB]	Result [dBm]	Convert [mW]		
DSSS (CCK)	2412.0	5.1	0.8	10.0	15.9	38.9	5.0	0.8	10.0	15.8	38.0	-2.3	+/-5
	2437.0	4.9	0.9	10.0	15.8	38.0	4.9	0.9	10.0	15.8	38.0	0.0	+/-5
	2462.0	4.6	1.0	10.0	15.6	36.3	4.6	1.0	10.0	15.6	36.3	0.0	+/-5
OFDM (64QAM)	2412.0	8.2	0.8	10.0	19.0	79.4	8.1	0.8	10.0	18.9	77.6	-2.3	+/-5
	2437.0	8.2	0.9	10.0	19.1	81.3	8.2	0.9	10.0	19.1	81.3	0.0	+/-5
	2462.0	7.8	1.0	10.0	18.8	75.9	7.8	1.0	10.0	18.8	75.9	0.0	+/-5
OFDM (QPSK)	2412.0	10.5	0.8	10.0	21.3	134.9	10.4	0.8	10.0	21.2	131.8	-2.3	+/-5
	2437.0	10.5	0.9	10.0	21.4	138.0	10.5	0.9	10.0	21.4	138.0	0.0	+/-5
	2462.0	10.5	1.0	10.0	21.5	141.3	10.5	1.0	10.0	21.5	141.3	0.0	+/-5

12.2 Body 2450MHz SAR of sub antenna

Liquid Depth (cm) : **15.1** Model : **PCG-492L**
Parameters : $\epsilon_r = 48.3, \sigma = 2.00$ Serial No. : **DVT26**
Ambient Temperature[deg.c.] : **23.8** Modulation : **DSSS,OFDM**
Relative Humidity (%) : **58** Crest factor : **1**

Date : July 10,2003

Measured By : Miyo Ikuta

BODY SAR MEASUREMENT RESULTS ABOUT SUB ANTENNA									
Frequency		Modulation	Phantom Section	EUT Set-up Conditions			Liquid Temp.[deg.c]		SAR(1g) [w/kg]
Channel	MHz			Antenna	Position	Separation [mm]	Before	After	
Mid	2437	DSSS(CCK)	Flat	Fixed	Right Bottom	0	23.0	23.0	0.0014
Mid	2437	DSSS(CCK)	Flat	Fixed	Left Bottom	0	23.0	22.9	0.0002
Mid	2437	DSSS(CCK)	Flat	Fixed	Left Back of display	15	23.1	23.1	0.0368
Mid	2437	DSSS(CCK)	Flat	Fixed	Left Top of display	15	23.1	23.1	0.0456
Low	2412	DSSS(CCK)	Flat	Fixed	Left Top of display	15	23.1	23.1	0.0486
High	2462	DSSS(CCK)	Flat	Fixed	Left Top of display	15	23.1	23.1	0.0456
ANSI / IEEE C95.1 1992 - SAFETY LIMIT							Body SAR: 1.6 W/kg		
Spatial Peak Uncontrolled Exposure / General Population							(averaged over 1 gram)		

UL Apex Co., Ltd.**Head Office EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8116

Facsimile: +81 596 24 8124

Date : July 10,2003

Measured By : Miyo Ikuta

BODY SAR MEASUREMENT RESULTS ABOUT SUB ANTENNA									
Frequency		Modulation	Phantom Section	EUT Set-up Conditions			Liquid Temp.[deg.c]		SAR(1g) [w/kg]
Channel	MHz			Antenna	Position	Separation[mm]	Before	After	
Mid	2437	OFDM (64QAM)	Flat	Fixed	Right Bottom	0	22.8	22.7	0.0002
Mid	2437	OFDM (64QAM)	Flat	Fixed	Left Bottom	0	22.9	22.8	0.0006
Mid	2437	OFDM (64QAM)	Flat	Fixed	Left Back of display	15	23.0	23.0	0.0162
Mid	2437	OFDM (64QAM)	Flat	Fixed	Left Top of display	15	23.0	23.0	0.0265
Low	2412	OFDM (64QAM)	Flat	Fixed	Left Top of display	15	23.0	23.0	0.0264
High	2462	OFDM (64QAM)	Flat	Fixed	Left Top of display	15	23.0	23.0	0.0279
Mid	2437	OFDM (QPSK)	Flat	Fixed	Right Bottom	0	22.9	23.0	0.0013
Mid	2437	OFDM (QPSK)	Flat	Fixed	Left Bottom	0	22.9	22.9	0.0086
Mid	2437	OFDM (QPSK)	Flat	Fixed	Left Back of display	15	22.8	22.7	0.0469
Mid	2437	OFDM (QPSK)	Flat	Fixed	Left Top of display	15	22.7	22.6	0.0815
Low	2412	OFDM (QPSK)	Flat	Fixed	Left Top of display	15	22.6	22.6	0.0838
High	2462	OFDM (QPSK)	Flat	Fixed	Left Top of display	15	22.6	22.6	0.0892
ANSI / IEEE C95.1 1992 - SAFETY LIMIT							Body SAR: 1.6 W/kg		
Spatial Peak Uncontrolled Exposure / General Population							(averaged over 1 gram)		

UL Apex Co., Ltd.**Head Office EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8116

Facsimile: +81 596 24 8124

SECTION 13 : Equipment & calibration information

Name of Equipment	Manufacture	Model number	Serial number	Calibration	
				Last Cal	due date
Power Meter	Agilent	E4417A	GB41290639	2002/11/08	2003/11/07
Power Sensor	Agilent	E9300B	US40010300	2002/11/14	2003/11/13
Power Sensor	Agilent	E9327A	US40440544	2003/02/21	2004/02/20
S-Parameter Network Analyzer	Agilent	8753ES	US39174808	2000/10/05	2003/10/04
Signal Generator	Rohde&Schwarz	SML03	100332	2003/06/24	2004/06/23
RF Amplifier	OPHIR	5056F	1005	2003/02/06	2004/02/05
Dosimetric E-Field Probe	Schmid&Partner Engineering AG	ET3DV6	1684	2002/11/20	2003/11/19
Data Acquisition Electronics	Schmid&Partner Engineering AG	DAE3 V1	509	2003/04/10	2004/04/09
Robot,SAM Phantom	Schmid&Partner Engineering AG	DASY3	I021834	N/A	N/A
Attenuator	Agilent.	US40010300	08498-60012	2002/12/24	2003/12/23
Attenuator	HIROSE ELECTRIC Co.,LTD	AT-110	-	2003/02/04	2004/02/03
2450MHz System Validation Dipole	Schmid&Partner Engineering AG	D2450V2	713	2002/11/15	2004/11/14
Dual Directional Coupler	N/A	Narda	03702	N/A	N/A
Head 2450MHz	N/A	N/A	N/A	N/A	N/A
Body 2450MHz	N/A	N/A	N/A	N/A	N/A

UL Apex Co., Ltd.***Head Office EMC Lab.****4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN**Telephone: +81 596 24 8116**Facsimile: +81 596 24 8124*

SECTION 14 : References

- [1]ANSI, ANSI/IEEE C95.1-1992: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz, The Institute of Electrical and Electronics Engineers, Inc., New York, NY 10017, 1992.
- [2] Katja Pokovic, Thomas Schmid, and Niels Kuster, "Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies", in ICECOM '97, Dubrovnik, October 15-17, 1997, pp. 120-124.
- [3] Katja Pokovic, Thomas Schmid, and Niels Kuster, "E_ field probe with improved isotropy in brain simulating liquids", in Proceedings of the ELMAR, Zadar, Croatia, 23-25 June, 1996, pp.172-175.
- [4] W. Gander, Computermathematik, Birkhaeuser, Basel, 1992.
- [5] W. H. Press, S. A. Teukolsky, W. T. Vetterling, and B. P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second Edition, Cambridge University Press, 1992.
- [6] Barry N. Taylor and Christ E. Kuyatt, "Guidelines for evaluating and expressing the uncertainty of NIST measurement results", Tech. Rep., National Institute of Standards and Technology, 1994.

SECTION 15 : APPENDIX

APPENDIX 1	: Photographs of test setup	24-30
APPENDIX 2	: SAR Measurement data	31-68
APPENDIX 3	: Validation Measurement data	69-71
APPENDIX 4	: System Validation Dipole (D2450V2,S/N: 713)	72-81
APPENDIX 5	: Dosimetric E-Field Probe Calibration(ET3DV6,S/N: 1684)	82-95

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8116

Facsimile: +81 596 24 8124

APPENDIX 1 : Photographs of test setup

UL Apex Co., Ltd.


Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN



Telephone: +81 596 24 8116

Facsimile: +81 596 24 8124


Right Bottom (Measurement of main antenna)




Right Bottom (Measurement of sub antenna)





Left Bottom




Right Back of display




Right Top of display



Left Back of display



Left Top of display



UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8116

Facsimile: +81 596 24 8124