



September 16, 2014

UL Japan, Inc.  
4383-326 Asama-cho, Ise-shi, Mie 516-0021 Japan

FCC ID: AK8SSETN1

To whom it may concern,

We, UL Japan, Inc, hereby declare that Smart Tennis Sensor, model: SSE-TN1W (FCC ID: AK8SSETN1) of Sony Corporation is exempt from RF exposure SAR evaluation as its output power meets the exclusion limits stated in KDB 447498D01(V05).

KDB 447498D01(V05) has the following exclusion for portable devices:

The 1g and 10g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})]$

$\cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

$\cdot f(\text{GHz})$  is the RF channel transmit frequency in GHz

$\cdot$  Power and distance are rounded to the nearest mW and mm before calculation

$\cdot$  The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

This device has  $f = 2.48$  GHz and distance = 5 mm (minimum separation distance: 5mm was used in the calculation) and the maximum tune-up tolerance limit was 2 mW (declared value).

So for this device:

$2 \text{ mW}[\text{maximum tune-up tolerance limit}]/5 \text{ mm}[\text{minimum separation distance}] \cdot \sqrt{2.48} = 0.6$

\*This is less than 3.0, so no SAR is required.

Thank you for your attention to this matter.

---

Takayuki Shimada  
Engineer of Ise EMC Lab.  
Consumer Technology Division  
UL Japan, Inc.