



RF Exposure / MPE Calculation

No. : 28GE0170-HO-01-H

Applicant : Sony Corporation
Type of Equipment : UHF Synthesized Wireless Microphone
Model No. : UTX-H2(30)
FCC ID : AK8UTXH2

Sony Corporation declares that Model : UTX-H2(30)
complies with FCC radiation exposure requirement specified in the FCC Rules 2.1093(for portable)/2.1091 (for mobile).

The "UTX-H2(30)" has 36.9 mW of effective radiated power and 60.39 mW of EIRP.
This kind of equipment is below 60/frequency[GHz] mW(TCB Exclusion List)
so that SAR testing is excluded. The Following calculation is the reference data for 20cm distance.

RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided with the "UTX-H2(30)" as calculated from FCC OET Bulletin 65 Appendix A, Table (B) Limits for General Population / Uncontrolled Exposure. This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 0.39mW/cm² uncontrolled exposure limit. The Friis formula used was:

$$S = (P * G) / (4 * \pi * r^2)$$

Where

P = 36.90 mW (Effective radiated power)
G = 1.64 Numerical Antenna gain; equal 2.14 dBi
r = 20.0 cm

For: UTX-H2(30)

$$S = 0.01202 \text{ mW/cm}^2$$

Approved by :

Mitsuru Fujimura
Assistant Manager of EMC Services

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124